
AWS Identity & Access

Cloud Computing
Brenden west

Contents

Learning Outcomes

- AWS Shared Responsibility model
- AWS Identity & Access Management
- AWS account security

Reading

- AWS Cloud Foundations - module 4
- AWS Cloud Developing - modules 3, 4

Terminology

- **IAM** - Identity & Access Management
- **Authentication** - mechanism to verify the identity of a user
- **MFA** - multi-factor authentication uses two or more mechanisms to authenticate a user
- **Authorization** - mechanism to verify a user has permission to access a service or resource
-

AWS Shared Responsibility Model

- AWS & the customer share responsibility for security & compliance
- AWS responsible for security **of** the cloud (physical infrastructure)
- Customer responsible for security **in** the cloud
- Customers responsible for what is implemented using AWS products & services. E.g:
 - Managing their data
 - Configuring appropriate security using IAM & other security services
 - Guest operating systems on virtual machines
 - Firewalls & network configurations

AWS Shared Responsibility, cont.

CUSTOMER
RESPONSIBILITY
FOR SECURITY IN
THE CLOUD

Customer data		
Platform, applications, identity and access management		
Operating system, network, and firewall configuration		
Client-side data encryption and data integrity, authentication	Server-side encryption (file system and data)	Networking traffic protection (encryption, integrity, identity)

AWS
RESPONSIBILITY
FOR SECURITY OF
THE CLOUD

Software			
Compute	Storage	Databases	Networking
Hardware and AWS Global Infrastructure			
Regions	Availability Zones	Edge locations	

AWS Identity & Access Management (IAM)

Allows AWS customer to grant unique security credentials to users, roles, and groups.

- Securely controls who can access customer's AWS resources, what resources they can use, and in what ways
- Integrates with other AWS services
- Supports granular permissions
- Supports federated identity management (via corporate identity providers)
- Supports multi-factor authentication (MFA)

IAM Overview

- **IAM user** - a person or application with permanent credentials to access the services & resources in an AWS account
- **IAM group** - a collection of IAM users with same permissions. Group members inherit permissions attached to the group.
- **IAM role** - an AWS identity with attached permission policies. Does not have long-term credentials
- **IAM policy** - a document that lists explicit permissions. Can be attached to an IAM user, IAM group, or IAM role

Best practice - attach IAM policies to IAM groups and then assign IAM users to these groups.

Authenticating with IAM

- Any interaction with AWS services, whether through management console, AWS CLI, or AWS SDK, requires authentication by providing credentials
- Management console authentication depends on **user name** and **password**
- CLI, SDKs, and APIs depend on **AWS access keys** (access key and secret key)
- Users or services that assume an IAM role are provided with temporary security credentials to use in accessing AWS resources

AWS Credentials File

The AWS CLI client depends on credentials stored in a local text file to interact with AWS accounts.

- File location is **~/.aws/credentials** (Unix, Linux, MacOS) or **c:\Users\<USERNAME>\.aws\credentials** (Windows)
- credentials file can be used by multiple projects
- credentials file can contain keys (**profiles**) for multiple AWS accounts or environments
- Credentials should not be stored in code or publicly accessible locations


Authorizing with IAM

- By default, an authenticated user, group, or role has no access permissions
- Permissions to access AWS resources are controlled through IAM policies
- IAM policy is a JSON document that defines effect, action, resources, and optional conditions under which an entity can invoke API operations in an AWS account
- Any actions or resources not explicitly allowed are denied
- Actions may include wildcards (asterisks) to cover a set of related actions

Principle of Least Privilege

- Grant only permissions needed to perform a task
- Start with minimum set of permissions and grant additional permissions as needed
- Use account root user to create one or more IAM users
- Use IAM users for ongoing account access and management tasks

Evaluation logic for IAM policies



IAM Policy Types

Identity-based policy

- Attached to an IAM user, group, or role
- Specifies what an identity can do

Resource-based policy

- Attached to a resource
- Specifies what a user or group is permitted to do with the resource

IAM Policies

Managed policy

- Standalone, identity-based for attaching to multiple users, groups, and roles
- Provide reusability, central charge management, versioning, rollback, and ability to delegate permissions management

Inline policy

- Embedded in an entity
- If used for multiple entities, each has its own copy