

CO3 ASSESSMENT TOOL 3 – MOCK INTERVIEW



SIMATS Online Programming Lab
C PROGRAMMING

RESHINI PRIYA B
10120015108

CO3 - AT3 - Mock Interview

← Back

QUESTIONS

Q1

MOCK INTERVIEW

100 marks

1/1 answered

Q1 MOCK INTERVIEW

100 marks

- 1.What is the difference between an array and a variable?
2. What is meant by the base address of an array?
- 3.What happens if an array size is not specified during initialization?
4. How are 2D arrays stored in memory?
5. Give one real-life application of multidimensional arrays.
- 6.Why do arrays start from index 0 instead of 1?
- 7.Which engineering fields commonly use multidimensional arrays?
- 8.Can a multidimensional array have more than three dimensions?
- 9.Why are images stored as multidimensional arrays?
10. What is row-major order?
11. Does C use row-major or column-major order?
12. Why can't arrays return multiple values?
13. What happens when array bounds are exceeded?
14. Why are strings stored as character arrays?
15. Explain the difference between char str[] and char *str.
16. Can two-dimensional arrays be passed to functions?
17. When would a linked list outperform an array?
18. Differentiate gets(), fgets(), scanf(), and getchar().

Your Answer

6. Why arrays start from index 0: Arrays start from index 0 because the index represents the offset from the base address. The first element has zero offset from the base address, hence index 0.

7. Engineering fields using multidimensional arrays: Fields like computer science (image processing, graphics), civil engineering (structural analysis), electrical engineering (circuit matrices), and mechanical engineering (finite element analysis)

Save Answer

© 2026 SIMATS Online Lab. All rights reserved.

