```
boost::statechart::
simple_state< Default2
< Context >, Context,
  mpl::list<>, has_no_history >
```

- pContext_

```
+ outermost_context()
+ outermost_context()
+ context()
+ context()
+ state_cast()
+ state_downcast()
+ state_begin()
+ state_end()
+ post_event()
+ post_event()
+ discard_event()
+ forward_event()
+ defer_event()
+ transit()
+ transit()
+ terminate()
+ clear_shallow_history()
+ clear_deep_history()
+ triggering_event()
+ BOOST_STATIC_ASSERT()
+ BOOST_STATIC_ASSERT()
+ operator new()
+ operator delete()
+ outermost_context_base()
+ outermost_context_base()
+ outer_state_ptr()
+ react_impl()
+ exit_impl()
+ exit_impl()
+ set_outermost_unstable
_state()
+ context_ptr()
+ set_context()
+ store_deep_history_impl()
+ initial_deep_construct()
+ deep_construct()
+ shallow_construct()
+ deep_construct_inner()
# simple_state()
# ~simple_state()
- transit_impl()
- local_react()
- check_store_shallow
_history()
- check_store_deep_history()
```

```
boost::statechart::
state< Default2< Context
        >, Context >
```

```
+ initial_deep_construct()
+ deep_construct()
+ shallow_construct()
# state()
# ~state()
```

```
InnermostDefault< Default2
< Context >, Context::template
        orthogonal< 2 > >
```

```
+ InnermostDefault()
+ ~InnermostDefault()
+ exit()
```

```
Default2< Context >
```

```
+ Default2()
```