

I found a bad guy using who -u

Use tty to see who you are:

tty

Check which processes they started:

ps -ft <terminal> # example: pts/1

ps -fu <user>

Kill their shell and the processes (shell, process, process)

sudo pkill -KILL -t pts/1

sudo kill -9 <pid>

I want to change a password

sudo passwd <user>

You'll be asked for the new password twice unless you're changing your own

If they don't have UID 0: to make it safe, kill them with

sudo loginctl terminate-user <user>

If they have UID 0 you'll have to look into processes with ps -ft <usr>

I want to make sure no one is overprivileged:

grep -vE 'nologin|false' /etc/passwd

I want to know how this process happened:

ps -o pid,ppid,user,cmd -p <pid>

I want to fix an SSH bad thing:

The config is in: /etc/ssh/sshd_config, and systemctl restart ssh Restarts to activate saved changes (keys don't need saving)

echo \$\$ gives pid of my shell

This can help investigate an ssh process: `ps --ppid <pid> -o pid,user,cmd`

This tells you which ssh connections were accepted: `sudo grep -i accepted /var/log/auth.log`

Here's how to find all the files with the keys:

```
sudo find / -name "authorized_keys*" 2>/dev/null
```

I want to delete a user:

```
sudo userdel -r herobrine
```

```
sudo pkill -KILL -u herobrine 2>/dev/null
```