

remember to update passwords

rdp into 192.168.2xx.11

sign in as steve iyearn4theMines!

example: 192.168.2xx.11

copy and paste the files in lapis

optional, become admin in a terminal:

```
Start-Process powershell -Verb RunAs -ArgumentList "-NoExit", "-Command", "Set-Location '$PWD'"
```

for updating scoring passwords depending on accepted format:

\*

```
steve,kobaryoS?,alex,kobaryoA?,enderman,kobaryoE?,creeper,kobaryoG?,villager,kobaryoN?,zombie,kobaryoR?,enderdragon,kobaryoE?,irongolem,kobaryoI?,chickenjockey,kobaryoF?,ghast,kobaryoG?
```

\*

```
steve,kobaryoS? alex,kobaryoA? enderman,kobaryoE? creeper,kobaryoG? villager,kobaryoN? zombie,kobaryoR? enderdragon,kobaryoE? irongolem,kobaryoI? chickenjockey,kobaryoF? ghast,kobaryoG?
```

```
Set-ExecutionPolicy -Scope Process Bypass -Force  
run step 0
```

this needs to be run in powershell:

```
net user steve "kobaryoS?"; net user alex "kobaryoA?"; net user enderman "kobaryoE?"; net user creeper "kobaryoG?"; net user villager "kobaryoN?"; net user zombie "kobaryoR?"; net user enderdragon "kobaryoE?"; net user irongolem "kobaryoI?"; net user chickenjockey "kobaryoF?"; net user ghast "kobaryoG?"
```

```
net user Administrator *
```

```
# DUMB APPARENTLY: Disable-LocalUser -Name Guest
```

IRON from wsl do linux:

```
scp -r ccdc steve@192.168.2xx.10:~/ccdc
```

```
ssh steve@192.168.2xx.10
```

```
iyearn4theMines!
```

```
chmod +x ccdc/*
```

```
./step0_check.sh
```

```
printf '%s\n' 'root:kobaryoR?' 'steve:kobaryoS?' 'alex:kobaryoA?' 'enderman:kobaryoE?'  
'creeper:kobaryoG?' 'villager:kobaryoN?' 'zombie:kobaryoR?' 'enderdragon:kobaryoE?'  
'irongolem:kobaryoI?' 'chickenjockey:kobaryoF?' 'ghast:kobaryoG?' | sudo chpasswd
```

```
sudo passwd -l root
```

```
./iron_type1.sh
```

```
sudo iptables -I INPUT -p tcp --dport 6200 -j DROP
```

```
sudo netfilter-persistent save
```

BEDROCK in a new wsl:

```
scp -r ccdc vyos@192.168.2xx.2:~/ccdc
```

```
ssh vyos@192.168.2xx.2
```

```
chmod +x ccdc/*
```

(no step 0 bedrock)

```
# recon BEFORE changing anything
```

```
show configuration commands | match login
```

```
show configuration commands | match "service ssh"
```

```
show configuration commands | match firewall
```

```
show configuration commands | match nat
```

```
# --- config mode (#) ---
```

```
configure
```

```
# set the vyos password (the ONLY correct way — no chpasswd, no passwd -l)
```

```
set system login user vyos authentication plaintext-password 'yourStrongPw'
```

```
# delete any login user that isn't 'vyos' (repeat per bad user)
```

```
# delete system login user BADUSER
```

```
# your port drop
```

```
set firewall ipv4 forward filter rule 5 action drop
```

```
set firewall ipv4 forward filter rule 5 protocol tcp
```

```
set firewall ipv4 forward filter rule 5 destination port 6200
```

```
commit
```

```
save
```

```
exit
```

```
# --- back in operational mode ($): confirm ---
```

```
show system login users
```

REDSTONE in a new wsl:

```
scp -r ccdc steve@192.168.2xx.12:~/ccdc
```

```
REDSTONE ssh steve@192.168.2xx.12
```

```
chmod +x ccdc/*
```

```
./step0_check.sh
```

```
printf '%s\n' 'root:kobaryoR?' 'steve:kobaryoS?' 'alex:kobaryoA?' 'enderman:kobaryoE?'  
'creeper:kobaryoG?' 'villager:kobaryoN?' 'zombie:kobaryoR?' 'enderdragon:kobaryoE?'  
'irongolem:kobaryoI?' 'chickenjockey:kobaryoF?' 'ghast:kobaryoG?' | sudo chpasswd
```

```
sudo passwd -l root
```

```
./redstone_type1.sh
```

BACK TO WINDOWS

now check for unrecognized users on windows:

normal people dont exist??

domain people

```
Get-ADUser -Filter * | Select SamAccountName,Enabled
```

recommended delete:

```
Disable-ADAccount -Identity BADUSER
```

scary delete:

```
Remove-ADUser -Identity BADUSER
```

let's find bad admins

```
Get-ADGroupMember "Domain Admins"
```

```
Get-ADGroupMember "Enterprise Admins"
```

un-admin someone:

```
Remove-ADGroupMember -Identity "Domain Admins" -Members BADUSER
```

now check for unrecognized users on iron and redstone (better one below you can always use unless it is broken)

```
grep -vE 'nologin|false' /etc/passwd
```

better:

```
awk -F: '($7 !~ /(nologin|false|sync|halt|shutdown)$/) || ($3==0) {print $1" uid=\"$3" shell=\"$7" home=\"$6}' /etc/passwd
```

now check for unrecognized users on bedrock:

configure

```
delete system login user BADUSER    # for any user that isn't 'vyos'
```

```
commit
```

```
save
```

```
exit
```

```
show system login # confirm only vyos exists
```

Go through ssh keys now:

```
sudo find / -name "authorized_keys*" 2>/dev/null
```

just rm them all lwk

change splunk password: <http://192.168.2xx.12:8000> (admin, iyearn4theMines!)

DO NOT DO THIS ON SECOND THOUGHT:

`./linuxkillbashrc.sh` on all linux

backup http service

```
sudo ss -tlnp | grep ':80 '
```

```
netstat -ano | findstr :80
```

paste into AI and ask: how can i backup my http service based on this output? i want to do it in `/root/ccdc/backup`

do type2 ones

```
./iron_type2.sh
```

```
./redstone_type2.sh
```

```
lapis_type2.ps1
```

```
./cronfinder.sh
```

monitor everything once more (need to learn still)

kill bad cron jobs and `.bashrc`

at this point you can chase things

fix cves