

Structural and foundation concept report

Load path, structural grid and synthetic foundation basis

PROJECT	Uitbreiding moskee Haci Bayram
LOCATION	Bikkersweg 88, Bunschoten
ISSUE	2026-07-27
STATUS	CONCEPT - NOT FOR SUBMISSION OR EXECUTION

This report contains actual generated concept deliverables. It is not a professional certification and is not approved for permit submission or construction.

1. Structural scheme

A regular three-by-three column grid is used as a conceptual load path. Beams transfer floor and roof loads to columns and the foundation system. Final materials and member sizes are not selected in this concept issue.

2. Foundation concept

The simulated foundation uses a continuous 1.50 m wide and 0.40 m high strip with a 0.50 x 0.60 m beam. Groundwater is assumed at P=-0.50 m.

Field 1	Field 2	Field 3
Layer 1	0.0 to -0.8 m	synthetic sand fill
Layer 2	-0.8 to -2.5 m	synthetic soft clay
Layer 3	-2.5 to -8.0 m	synthetic medium-dense sand

3. Risks

Settlement and differential movement at the new-to-existing connection require explicit assessment. Soil profile, bearing resistance, stiffness, reinforcement and detailing are not professional conclusions.

4. Required evidence

Current structural survey and connection assessment (REQ-103).

Ground investigation and signed foundation advice (REQ-104).