COMPUTER BASICS

Module 1.1
COP4600 – Operating Systems
Richard Newman

WHAT IS A COMPUTER?

- Stored program concept
- Components
  - CPU(s) a.k.a. cores
  - RAM
  - I/O Devices – keyboard, display, mouse, joystick, game controller, printer, NIC, ...
  - Persistent Storage – disk, floppy, CD/DVD, flash drive, drum, tape ...
  - Bus
  - Power Supply
- Fetch-decode-execute cycle

WHAT IS A COMPUTER?



1. Scanner
2. CPU
3. DIMM
4. Expansion cards
5. Power supply
6. Optical disk drive
7. HDD
8. Motherboard
9. Speakers
10. Display
11&12. GUI
13. Keyboard
14. Mouse
15. UPS
16. Printer

GENERIC PERSONAL COMPUTER



Figure 1-6. Some of the components of a simple personal computer.

MOTHERBOARD



INSIDE THE CPU

- Central Processing Unit (CPU)
- Registers – very small, very fast storage
  - Special purpose – MAR, MBR, PC, IR, SR
  - General purpose – two or more for data
- Arithmetic Logic Unit (ALU)
- Decoder – interprets instruction opcode

- Bus(es) – move data around
  - Data – read from RAM or written to RAM
  - Address – where in RAM to access
  - Control
    - Enable (for read)
    - Set (for write)

INSIDE THE CPU



INSIDE THE CPU



Intel 80486 die

HOW DOES A COMPUTER WORK?

- Fetch-decode-execute cycle
- Fetch
  - Load MAR from PC
  - Read instruction from RAM into MBR
  - Move instruction from MBR to IR
  - Increment PC
- Decode
  - Interpret operation code (opcode) in IR
- Execute
  - Carry out instruction – get additional parts of multi-word instruction, move data to data registers, cause ALU to perform operation on data registers, test status register, change the PC, etc.

INSTRUCTIONS AND PROTECTION STATE

- Opcode and operands
  - Opcode determines what the instruction does
  - Operands determine what it does it to
- Extended instructions
  - Operands may be too large to fit into a single memory word
  - Instruction may require additional fetches
- Protected instructions
  - Some instructions are not available to user programs
  - Processor protection state must be compatible
- Protection state
  - Special register that hold current permission info
  - Changed when particular instructions are executed

FETCH-DECODE-EXECUTE CYCLE



SIMPLE PIPELINING



Get instruction address from PC
Load MBR

Move instruction to IR
While I-1 is decoded
Load MBR with I-2

Execute I-1 in ALU or buses
Move I-2 to IR and decode
Load MBR with I-3

Etc.
Etc.
Etc.

PARALLELISM IN PROCESSORS



Figure 1-7. (a) A three-stage pipeline.
(b) A superscalar CPU.

MEMORY



Figure 1-8. (a) A quad-core chip with a shared L2 cache.
(b) A quad-core chip with separate L2 caches.

MEMORY HIERARCHY



Figure 1-9. A typical memory hierarchy. The numbers are very rough approximations.

CACHING

Caching system issues:

- When to put a new item into the cache.
- How big a cache line should be.
- Which cache line to put the new item in.
- Which item to remove from the cache when a slot is needed.
- Where to put a newly evicted item in the larger memory.

BUSES



Figure 1-12. The structure of a large x86 system

HOW DOES A BUS WORK?

- Three types of bus lines
  - Data
  - Address
  - Control
- Bus Controller/Arbiter
  - Decides which competing device gets the bus
- Address/Data lines
  - Specify data and memory address to access
  - May reuse the same lines (different times)
- Control lines
  - Power, ground, clock
  - Read/Write (enable/set)
  - Interrupt line(s)

HOW MANY BUSES ARE THERE?

- Early computers had just two
  - One on CPU for routing between registers, ALU, CU, etc.
  - One “system bus” for access to memory, I/O devices
- Later, many evolved
  - Buses run synchronously at bus clock speed
  - CPU and memory speeds increased faster than I/O device speeds – needed separate bus to keep CPU fed
  - I/O devices may also run at different speeds
  - So multiple I/O buses have arisen to deal with this
- Multiple buses meant I/O controller /hub was needed
  - Southbridge/Northbridge

I/O DEVICES





Figure 1-11. (a) The steps in starting an I/O device and getting an interrupt.

(b) Interrupt processing involves taking the interrupt, running the interrupt handler, and returning to the user program.

DISKS



Figure 1-10. Structure of a disk drive.

METRIC UNITS

Exp.	Explicit	Prefix	Exp.	Explicit	Prefix
10^{-3}	0.001	milli	10^{3}	1,000	Kilo
10^{-6}	0.000001	micro	10^{6}	1,000,000	Mega
10^{-9}	0.000000001	nano	10^{9}	1,000,000,000	Giga
10^{-12}	0.000000000001	pico	10^{12}	1,000,000,000,000	Tera
10^{-15}	0.000000000000001	femto	10^{15}	1,000,000,000,000,000	Peta
10^{-18}	0.000000000000000001	atto	10^{18}	1,000,000,000,000,000,000	Exa
10^{-21}	0.000000000000000000001	zepto	10^{21}	1,000,000,000,000,000,000,000	Zetta
10^{-24}	0.000000000000000000000001	yocto	10^{24}	1,000,000,000,000,000,000,000,000	Yotta

Figure 1-31. The principal metric prefixes.

Decimal is used for clock rates (GHz) and network data rate (Gbps)

MEMORY SIZE UNITS

Prefix	Abbrev.	Exponent	Explicit
kilo	**K**	2^{10}	**1024**
mega	**M**	2^{20}	**1,048,576**
giga	**G**	2^{30}	**1,073,741,824**
tera	**T**	2^{40}	**1,099,511,627,776**
peta	**P**	2^{50}	**1,125,899,906,842,624**
exa	**X**	2^{60}	**1,152,921,504,606,846,976**
zetta	**Z**	2^{70}	**1,180,591,620,717,411,303,424**
yotta	**Y**	2^{80}	**1,208,925,819,614,629,174,706,176**

Memory sizes usually expressed in powers of 2 (GB), since addressing is in binary.

Powers of two may also be used for bus speeds (GBps).

HOW DOES A COMPUTER START?

- First instruction: initialize PC to 0 (usually)
  - Done by hardware
- Execute BIOS program stored in static RAM (is not erased when power off like DRAM)
- Power-on Self Test (POST) – make sure all components are OK
- Search for bootable device (DVD, HDD, etc.)
- Load boot block into RAM
- Start execution of program in boot block
- Bootstrap program loads operating system, starts OS execution

BOOTSTRAPPING



Figure 2-36. Disk structures used for bootstrapping.

(a) Unpartitioned disk. The first sector is the bootblock.

(b) Partitioned disk. The first sector is the master boot record, also called masterboot.

SUMMARY

- Stored Program Concept
  - Program determines functionality of machine
- Computer Organization
  - Components and how they work together
- CPU
  - Parts of the CPU
  - Fetch-Decode-Execute Cycle
  - Protected instructions
- Memory Hierarchy & Caching
  - I/O Devices & Interrupt Handling
- How a computer starts up – Bootstrapping

IMAGE SOURCES

- Exploded computer view: Self-published work by User:HereToHelp
- Motherboard: Moxfyre at en.wikipedia, CC BY-SA 3.0,
- 80486 die photo: Uberpenguin at the English language Wikipedia

LINKS

https://www.youtube.com/watch?v=XM4lGflQFvA

https://www.youtube.com/watch?v=xfJbpCJSpd8

https://quizlet.com/6585038/computer-hardware-and-ports-pictures-flash-cards/

https://www.youtube.com/watch?v=QGD4Gr4s6S8

https://commons.wikimedia.org/w/index.php?curid=6544498