



# **Working with APIs**

## **Cloud Insights**

NetApp  
September 27, 2022

# Table of Contents

- Cloud Insights API ..... 1
  - Requirements for API Access ..... 1
  - API Documentation (Swagger) ..... 1
  - API Access Tokens ..... 2
  - API Categories ..... 3
  - Inventory Traversal ..... 3
  - Expands ..... 4
  - Performance Data ..... 6
  - Object Performance Metrics ..... 8
  - Performance History Data ..... 8
  - Objects with Capacity Attributes ..... 9
  - Using Search to Look Up Objects ..... 10

# Cloud Insights API

The Cloud Insights API enables NetApp customers and independent software vendors (ISVs) to integrate Cloud Insights with other applications, such as CMDB's or other ticketing systems.

Note that Cloud Insights APIs are available based on your current Edition:

API Category	Basic	Standard	Premium
Acquisition Unit	✓	✓	✓
Data Collection	✓	✓	✓
User Management	✓	✓	✓
Alerts		✓	✓
Assets		✓	✓
Data Ingestion		✓	✓
Log Ingestion		✓	✓

Additionally, your Cloud Insights [feature set role](#) will determine which APIs you can access. User and Guest roles have fewer privileges than Administrator role. For example, if you have Administrator role in Observability, but User role in Reporting, you can manage all API types except Data Warehouse.

## Requirements for API Access

- An API Access Token model is used to grant access.
- API Token management is performed by Cloud Insights users with the Administrator role.

## API Documentation (Swagger)

The latest API information is found by logging in to Cloud Insights and navigating to **Admin > API Access**. Click the **API Documentation** link.



The API Documentation is Swagger-based, which provides a brief description and usage information for the API, and allows you to try it out in your environment.

POST

/assets/annotations Create annotation definition



## Parameters

Try it out

No parameters

Request body

application/json ▼

Request body should include required name, type, optional description and enumValues (if enum type). Enums should contain name and label. Example:

```
{
  "name": "StorageLocation",
  "type": "FIXED_ENUM",
  "description": "Storage Location",
  "enumValues": [
    {
      "name": "PT_LISBON",
      "label": "Lisbon (Portugal)"
    },
    {
      "name": "US_WALTHAM",
      "label": "Waltham (USA)"
    }
  ]
}
```

Example Value | Schema

{}

## API Access Tokens

Before using the Cloud Insights API, you must create one or more **API Access Tokens**. Access tokens are used for specified API categories, and can grant read and/or write permissions. You can also set the expiration for each access token. All APIs under the specified categories are valid for the access token. Each token is void of a username or password.

To create an Access Token:

- Click **Admin > API Access**
- Click **+API Access Token**
  - Enter Token Name
  - Select API Categories
  - Specify the permissions granted for this API access
  - Specify Token Expiration



Your token will only be available for copying to the clipboard and saving during the creation process. Tokens can not be retrieved after they are created, so it is highly recommended to copy the token and save it in a secure location. You will be prompted to click the **Copy API Access Token** button before you can close the token creation screen.

You can disable, enable, and revoke tokens. Tokens that are disabled can be enabled.

Tokens grant general purpose access to APIs from a customer perspective; managing access to APIs in the scope of their own tenant. Customer administrators may grant and revoke these keys without direct involvement from Cloud Insights back end personnel.

The application receives an Access Token after a user successfully authenticates and authorizes access, then passes the Access Token as a credential when it calls the target API. The passed token informs the API that the bearer of the token has been authorized to access the API and perform specific actions specified by the scope that was granted during authorization.

The HTTP header where the Access Token is passed is **X-CloudInsights-ApiKey:**.

For example, use the following to retrieve storages assets:

```
curl https://<tenant_host_name>/rest/v1/assets/storages -H 'X-CloudInsights-ApiKey: <API_Access_Token>'
```

Where *<API\_Access\_Token>* is the token you saved during API access key creation.

## API Categories

The Cloud Insights API is category-based, and currently contains the following categories:

- **ASSETS** category contains asset, query, and search APIs.
  - **Assets:** Enumerate top-level objects and retrieve a specific object or an object hierarchy.
  - **Query:** Retrieve and manage Cloud Insights queries.
  - **Import:** Import annotations or applications and assign them to objects
  - **Search:** Locate a specific object without knowing the object's unique ID or full name.
- **DATA COLLECTION** category is used to retrieve and manage data collectors.
- **DATA INGESTION** category is used to retrieve and manage ingestion data and custom metrics, such as from Telegraf agents

Additional categories and/or APIs may become available over time. You can find the latest API information in the [API Swagger documentation](#).

Note that the API categories to which a user has access depend also on the [User Role](#) they have in each Cloud Insights feature set (Observability, Security, Reporting).

## Inventory Traversal

This section describes how to traverse a hierarchy of Cloud Insights objects.

### Top Level Objects

Individual objects are identified in requests by unique URL (called “self” in JSON) and require knowledge of object type and internal id. For some of the top level objects (Hosts, Storages, and so on), REST API provides access to the complete collection.

The general format of an API URL is:

```
https://<tenant>/rest/v1/<category>/<object>
```

For example, to retrieve all storages from a tenant named *mysite.c01.cloudinsights.netapp.com*, the request URL is:

```
https://mysite.c01.cloudinsights.netapp.com/rest/v1/assets/storages
```

## Children and Related Objects

Top level objects, such as Storage, can be used to traverse to other children and related objects. For example, to retrieve all disks for a specific storage, concatenate the storage “self” URL with “/disks”, for example:

```
https://<tenant>/rest/v1/assets/storages/4537/disks
```

## Expands

Many API commands support the **expand** parameter, which provides additional details about the object or URLs for related objects.

The one common expand parameter is *expands*. The response contains a list of all available specific expands for the object.

For example, when you request the following:

```
https://<tenant>/rest/v1/assets/storages/2782?expand=_expands
```

The API returns all available expands for the object as follows:

```

{
  "id": "1247936",
  "self": "/rest/v1/assets/storages/1247936",
  "name": "amsprdclu01",
  "simpleName": "amsprdclu01",
  "naturalKey": "5DF483F0-1729-11DC-9A79-123478563412",
  "ip": "10.64.0.132",
  "serialNumber": "1-80-000011",
  "model": "FAS3270,FAS6290",
  "vendor": "NetApp",
  "microcodeVersion": "8.1.3 clustered Data ONTAP",
  "capacity": {
    "description": "Storage Capacity",
    "unitType": "MB",
    "total": {
      "value": 8.23185105E8
    },
    "storagePools": {
      "value": 5.43220974E8
    }
  },
  "isActive": true,
  "createTime": "2013-05-07T16:52:21-0700",
  "family": "FAS3200,FAS6200",
  "managementUrl": null,
  "virtualizedType": "STANDARD",
  "protocols": [
    "NAS",
    "NFS",
    "CIFS",
    "FC",
    "ISCSI"
  ],
  "_expands": {
    "performance": {
      "url": "/rest/v1/assets/storages/1247936/performance",
      "name": "Performance Data"
    },
    "storageNodes": {
      "url": "/rest/v1/assets/storages/1247936/storageNodes",
      "name": "Storage Storage Nodes"
    },
    "storagePools": {
      "url": "/rest/v1/assets/storages/1247936/storagePools",
      "name": "Storage Storage Pools"
    },
    "storageResources": {
      "url": "/rest/v1/assets/storages/1247936/storageResources",
      "name": "Storage Storage Resources"
    },
    "internalVolumes": {
      "url": "/rest/v1/assets/storages/1247936/internalVolumes",
      "name": "Storage Internal Volumes"
    },
    "volumes": {
      "url": "/rest/v1/assets/storages/1247936/volumes",
      "name": "Storage Volumes"
    },
    "disks": {
      "url": "/rest/v1/assets/storages/1247936/disks",
      "name": "Disks"
    },
    "datasources": {
      "url": "/rest/v1/assets/storages/1247936/datasources",
      "name": "Storage Datasources"
    },
    "ports": {
      "url": "/rest/v1/assets/storages/1247936/ports",
      "name": "Storage Ports"
    },
    "annotations": {
      "url": "/rest/v1/assets/storages/1247936/annotations",
      "name": "Storage Annotations"
    },
    "qtrees": {
      "url": "/rest/v1/assets/storages/1247936/qtrees",
      "name": "Qtrees"
    }
  },
  ".....":

```

Each expand contains data, a URL, or both. The expand parameter supports multiple and nested attributes, for example:

```
https://<tenant>/rest/v1/assets/storages/2782?expand=performance,storageRe  
sources.storage
```

Expand allows you to bring in a lot of related data in one response. NetApp advises that you do not request too much information at one time; this can cause performance degradation.

To discourage this, requests for top-level collections cannot be expanded. For example, you cannot request expand data for all storage objects at once. Clients are required to retrieve the list of objects and then choose specific objects to expand.

## Performance Data

Performance data is gathered across many devices as separate samples. Every hour (the default), Cloud Insights aggregates and summarizes performance samples.

The API allows access to both the samples and the summarized data. For an object with performance data, a performance summary is available as *expand=performance*. Performance history time series are available through nested *expand=performance.history*.

Examples of Performance Data objects include:

- StoragePerformance
- StoragePoolPerformance
- PortPerformance
- DiskPerformance

A Performance Metric has a description and category and contains a collection of performance summaries. For example, Latency, Traffic, and Rate.

A Performance Summary has a description, unit, sample start time, sample end time, and a collection of summarized values (current, min, max, avg, etc.) calculated from a single performance counter over a time range (1 hour, 24 hours, 3 days, and so on).



<https://tenant.cloudinsights.netapp.com/rest/v1/assets/storages/1/performance?expand=history>

## Details

### Response body

```
{
  "self": "/rest/v1/assets/storages/1/performance",
  "cacheHitRatio": {
    "read": {
      "description": "Cache Hit Ratio - Read",
      "unitType": "%",
      "start": null,
      "end": null,
      "current": null,
      "min": null,
      "max": null,
      "avg": null,
      "sum": null,
      "isDownsampled": false
    },
    "write": {
      "description": "Cache Hit Ratio - Write",
      "unitType": "%",
      "start": null,
      "end": null,
      "current": null,
      "min": null,
      "max": null,
      "avg": null,
      "sum": null,
      "isDownsampled": false
    }
  }
}
```

Self

Performance Metric

### Response body

```
}
},
"history": [
  [
    1578418848140,
    {
      "latency.total": 1.30578,
      "latency.read": 3.64681,
      "ioDensity.read": 9.62065,
      "iops.write": 686.35502,
      "ioDensity.total": 31.36259,
      "capacity.raw": 80024.92772,
      "throughput.read": 7.32371,
      "iops.total": 1488.7974,
      "latency.write": 0.39495,
      "ioDensity.write": 14.45856,
      "iops.read": 456.69703,
      "capacity.storagePools": 56058.1041,
      "throughput.write": 14.59581,
      "throughput.total": 21.91953
    }
  ],
  [
    1578419748198,
    {

```

History

Timestamp

Counter Values

The resulting Performance Data dictionary has the following keys:

- "self" is the object's unique URL

- “history” is the list of pairs of timestamp and map of counters values
- Every other dictionary key (“diskThroughput” and so on) is the name of a performance metric.

Each performance data object type has a unique set of performance metrics. For example, the Virtual Machine performance object supports “diskThroughput” as a performance metric. Each supported performance metric is of a certain “performanceCategory” presented in the metric dictionary. Cloud Insights supports several performance metric categories listed later in this document. Each performance metric dictionary will also have the “description” field that is a human-readable description of this performance metric and a set of performance summary counter entries.

The Performance Summary counter is the summarization of performance counters. It presents typical aggregated values like min, max, and avg for a counter and also the latest observed value, time range for summarized data, unit type for counter and thresholds for data. Only thresholds are optional; the rest of attributes are mandatory.

Performance summaries are available for these types of counters:

- Read – Summary for read operations
- Write – Summary for write operations
- Total – Summary for all operations. It may be higher than the simple sum of read and write; it may include other operations.
- Total Max – Summary for all operations. This is the maximum total value in the specified time range.

## Object Performance Metrics

The API can return detailed metrics for objects in your environment, for example:

- Storage Performance Metrics such as IOPS (Number of input/output requests per second), Latency, or Throughput.
- Switch Performance Metrics, such as Traffic Utilization, BB Credit Zero data, or Port Errors.

See the [API Swagger documentation](#) for information on metrics for each object type.

## Performance History Data

History data is presented in performance data as a list of timestamp and counter maps pairs.

History counters are named based on the performance metric object name. For example, the virtual machine performance object supports “diskThroughput” so the history map will contain keys named “diskThroughput.read”, “diskThroughput.write” and “diskThroughput.total”.



Timestamp is in UNIX time format.

The following is an example of a performance data JSON for a disk:

```

"performance": {
  "self": "/rest/v1/assets/disks/4013931/performance",
  "iops": {
    "performanceCategory": "IOPS",
    "description": "Disk IOPS",
    "read": {
      "description": "Disk Read Iops",
      "unitType": "IO/s",
      "start": 1399305599999,
      "end": 1402604368055,
      "current": 1,
      "min": 0,
      "max": 6,
      "avg": 0.5532
    },
    [...]
  },
  "total": {
    "description": "Disk Total Throughput",
    "unitType": "MB/s",
    "start": 1399305599999,
    "end": 1402604368055,
    "current": 0,
    "min": 0,
    "max": 2,
    "avg": 0.1702
  }
},
"history":
[
  [
    1399300412690,
    {
      "utilization.total": 12,
      "iops.total": 26,
      "iops.write": 22,
      "iops.read": 4,
      "throughput.read": 0,
      "utilization.read": 2.12,
      "throughput.total": 5,
      "utilization.write": 10.24,
      "throughput.write": 5
    }
  ]
]

```

## Objects with Capacity Attributes

Objects with capacity attributes use basic data types and the `CapacityItem` for representation.

### CapacityItem

`CapacityItem` is a single logical unit of capacity. It has “value” and “highThreshold” in units defined by its parent object. It also supports an optional breakdown map that explains how the capacity value is constructed. For example, the total capacity of a 100 TB storagePool would be a `CapacityItem` with a value of 100. The breakdown may show 60 TB allocated for “data” and 40 TB for “snapshots”.

#### Note

“highThreshold” represents system defined thresholds for the corresponding metrics, which a client can use to generate alerts or visual cues on values that are out of acceptable configured ranges.

The following shows the capacity for StoragePools with multiple capacity counters:

## StoragePoolCapacity

```
Model properties:
{
  description: string
  unitType: 'MB' or 'GB' or 'TB' or 'KiB' or 'MiB' or 'TiB'
  total: CapacityItem
  used: CapacityItem
  provisioned: CapacityItem
  reservedCapacity: CapacityItem
  softLimit: Double
  rawToUsableRatio: Double
  isDedupeEnabled: boolean
  dedupeSavings: NumericValueWithUnit
  isCompressionEnabled: boolean
  compressionSavings: NumericValueWithUnit
  isThinProvisioningSupported: boolean
}
```

close

## Using Search to Look Up Objects

The search API is a simple entry point to the system. The only input parameter to the API is a free-form string and the resulting JSON contains a categorized list of results. Categories are different asset types from the Inventory, such as storages, hosts, dataStores, and so on. Each category would contain a list of objects of the category type that match the search criteria.

Cloud Insights is an extensible (wide open) solution that allows integrations with third party orchestration, business management, change control and ticketing systems as well as custom CMDB integrations.

Cloud Insight's RESTful API is a primary point of integration that allows simple and effective movement of data as well as allows users to gain seamless access to their data.

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.