A Survey on the Optimization of Large Language Model-based Agents

www.surveyx.cn

Abstract

This survey provides a comprehensive overview of the optimization of large language model-based agents, encompassing various aspects of natural language processing and optimization methods. The optimization of large language models is crucial for improving their performance, efficiency, and effectiveness in various applications, including language translation, text summarization, question answering, and dialogue generation. Recent advancements in deep learning architectures, such as Transformer-based models, have significantly improved the performance of large language models. However, these models still face challenges and limitations, including the need for large amounts of training data, vulnerability to bias and toxicity, and the requirement for more efficient and scalable training methods. To address these challenges, various optimization techniques have been proposed, including model pruning, knowledge distillation, quantization, and parallelization. The applications of optimized large language models are diverse and widespread, with significant potential to transform numerous industries and aspects of our lives, including healthcare, education, and business. Future research directions include the exploration of novel pre-training objectives, the development of more advanced hybrid methods for semantic similarity, and the examination of the challenges and opportunities associated with generative AI in various domains.

1 Introduction

1.1 Background and Importance

The background and importance of large language models in natural language processing (NLP) and artificial intelligence (AI) are multifaceted, with applications ranging from language translation and text summarization to question answering and dialogue generation [1, 2]. Recent works have demonstrated the reasoning capabilities of large language models in domains beyond NLP, such as planning and interaction for robots [1]. The concept of the semantic web, ontologies, and ontology learning are crucial in understanding the background and importance of large language models in NLP and AI [2]. Deep learning methodologies, machine learning, and deep learning approaches have been widely used in NLP, with applications in medical domains [3], and the exploration of chemical space in drug discovery efforts [4]. The state of the art in NLP for English, both in biomedicine and in the general domain, has been reviewed, and promising strategies for making significant progress in robustness, generality, and accuracy have been identified [5]. Sentiment analysis in the education domain has also been explored, with a systematic review of the current state of evidence and gaps in the literature [6]. The survey of cutting-edge AI software, libraries, and frameworks has presented a comprehensive overview with comparisons as well as trends in development and usage, highlighting the ability of these tools to learn and adapt from previous experience using machine learning (ML) and deep learning (DL) techniques [7]. The opportunities, challenges, and implications related to GenAI technologies in the context of learning technologies and education have also been explored, with a focus on the intersection of learning and technology [8]. Deep learning concepts, architectures, challenges, applications, computational tools, and evolution matrix have




Figure 1: chapter structure

been discussed, providing a comprehensive understanding of the background and importance of large language models [9]. The application of generative AI in education has also been analyzed, with a focus on its current use, potential for innovation, limitations, and corresponding strategies for future education [10]. Additionally, the importance of transparency and trust in AI systems, as well as the need for explainability in AI decisions, are crucial aspects to consider when developing and implementing large language models [11]. Moreover, research has been conducted on combining reinforcement learning algorithms and deep learning methods, which is essential for optimizing the performance of large language models [12]. Understanding the background and importance of large language models is essential for harnessing their potential in various fields, including healthcare, education, and business, and for addressing the challenges and limitations associated with their development and implementation [13, 3].

1.2 Need for Optimization

The need for optimization techniques to improve the performance, efficiency, and effectiveness of large language models is a pressing concern, as highlighted by various studies [13, 14]. The inefficient adaptation of large pre-trained language models requires significant computational resources and memory, making it impractical for many applications [13]. Issues such as factual correctness and alignment with social values necessitate the development of optimization techniques to improve the performance, efficiency, and effectiveness of large language models [14]. The problem of training large language models has become increasingly important in recent years, with the need for high-performance hardware, software, and algorithmic techniques to enable training such large models [15]. The high and increasing cost of training large NLP models, which can run into millions of dollars, driven by factors such as model size, dataset size, and training volume, also underscores the need for optimization techniques [16]. Additionally, the limitations of current parallelization techniques and the importance of optimizing large language models for better performance and efficiency have been highlighted [17]. The high computational cost and energy consumption of training large language models, as well as the need for optimization techniques to improve performance, efficiency, and effectiveness, have also been noted [18]. Moreover, the substantial financial and environmental costs due to the energy required to perform the computation, and the lack of access to computational resources for many researchers, further emphasize the need for optimization techniques [19].

AI-generated, for reference only.

The self-attention mechanism in Transformer models, which has a time and space complexity of $O(n^2)$ $with respect to sequence length n, making it a bottleneck for efficient training and deployment, also requires optimi$ $annotated reasoning traces, is another area where optimization techniques are necessary$[21]. $The problem of finding the$ 16].

1.3 Structure of the Survey

The organization and content of this paper are designed to provide a comprehensive overview of the optimization of large language model-based agents, covering various aspects of natural language processing and optimization methods [13]. The paper is structured into several sections, each focusing on a specific theme related to large language models, including their background and importance, need for optimization, definitions and preliminaries, optimization techniques, applications, challenges, and limitations [13]. The introduction section provides an overview of the topic, highlighting the significance of large language models in natural language processing and artificial intelligence, as well as the need for optimization techniques to improve their performance, efficiency, and effectiveness [13]. The background section delves into the history and evolution of large language models, their architectures, and applications, including their use in language translation, text summarization, question answering, and dialogue generation [2]. The definitions and preliminaries section defines key terms and concepts related to large language models, natural language processing, and artificial intelligence, including machine learning and deep learning fundamentals [9]. The optimization techniques section discusses various methods used to improve the performance, efficiency, and effectiveness of large language models, including model pruning, knowledge distillation, quantization, and parallelization [15]. The applications section explores the use of optimized large language models in various domains, such as healthcare, education, and business, highlighting their potential to improve language translation, text summarization, question answering, and dialogue generation [4]. The challenges and limitations section discusses the data-related, model-related, and evaluation-related challenges faced when optimizing large language models, as well as the need for transparency, trust, and explainability in AI systems [11]. Finally, the conclusion section summarizes the main findings and contributions of the paper, providing an overview of the current state of research in the optimization of large language model-based agents and highlighting future research directions [13].The following sections are organized as shown in Figure 1.

2 Background

Large language models have a rich history and evolution, shaped by technological advancements, leading to the current state of transformer-based architectures [23, 9, 24]. Understanding human language, which comprises figurative and non-figurative dimensions, is crucial for natural language understanding, and differentiating between them is vital [24]. The survey of semantic similarity measures categorizes them into four main categories: structure-based, information content, feature-based, and hybrid measures [25]. Natural Language Processing (NLP) and its applications in medical education have been explored, highlighting the potential of NLP in various domains [26]. The combination of reinforcement learning and deep learning has been introduced as a novel perspective, and the Dynamic Memory Network (DMN) is a neural network-based framework for general question answering tasks [12, 27]. NLP solutions for automatic fake news detection have been explored, and the background of large language models, specifically the fine-tuning performance of BERT, has been discussed [28, 29]. Multimodal representations, fusion of multimodal signals, and applications of multimodal intelligence have been explored, and neural network models are now the state-of-the-art for tasks such as text classification, machine translation, and semantic role labeling [30, 23]. Deep learning methodologies have been widely used in NLP, with applications in medical domains, highlighting the potential of large language models in various fields [3].

2.1 Introduction to Large Language Models

The concept of the semantic web and its history can introduce readers to large language models, which are a type of artificial intelligence designed to process and understand human language [24, 23]. Large language models have been applied to various tasks, including language modeling, text classification, sentiment analysis, machine translation, and question answering, and have been used in language translation, text summarization, question answering, and dialogue generation [7, 31].

AI-generated, for reference only.

The applications of large language models in natural language processing and artificial intelligence include language understanding and generation models, model size reduction techniques, information retrieval models, and long sequence models [32]. Additionally, large language models have been applied in finance, including trading, risk modeling, customer service, and financial advisory, and have potential applications in areas such as education, healthcare, natural language processing, and more [33, 34]. Reinforcement learning algorithms have played an important part in the optimization of control policies through self-exploration of states and actions in NLP tasks [35].

2.2 Architectures of Large Language Models

The architectures of large language models are diverse and complex, with various strengths and weaknesses, and transformer-based architectures have become the dominant approach for natural language processing, surpassing other neural models in performance [23, 36]. These architectures have been widely used in pre-trained models, such as BERT and GPT, and the transformer model is a key component of large language models, with its self-attention mechanism allowing for parallelization and efficient processing of input sequences [37]. Other architectures, including convolutional neural networks, recurrent neural networks, and attention-based models, have been explored, and the Megatron-LM architecture uses a hybrid approach that combines model parallelism and data parallelism for efficient training [38, 17]. The sparsely activated mixture-of-experts (MoE) architecture is another example, which has been shown to be effective in reducing the computational cost of large language models [18]. However, transformer models have a large number of parameters, and the self-attention mechanism affects their performance and efficiency [20].

2.3 Applications of Large Language Models

Large language models have been applied to various domains, including finance, education, healthcare, and natural language processing, and have been used in tasks such as language modeling, text classification, sentiment analysis, machine translation, and question answering [32, 33]. The applications of large language models in natural language processing and artificial intelligence include language understanding and generation models, model size reduction techniques, information retrieval models, and long sequence models [32]. ChatGPT has potential applications in areas such as education, healthcare, natural language processing, and more, and reinforcement learning algorithms have played an important part in the optimization of control policies through self-exploration of states and actions in NLP tasks [34, 35]. Large language models have also been applied in language translation, text summarization, question answering, and dialogue generation, and have been used in finance, including trading, risk modeling, customer service, and financial advisory [31, 33].

2.4 Challenges and Limitations of Large Language Models

The challenges and limitations of large language models are multifaceted, including the lack of a comprehensive understanding of their strengths and weaknesses, and the complexity, size, and ability to handle long sequences and open-domain question answering [37, 39]. The limitations of large language models include outdated knowledge, insufficient understanding, energy consumption, malicious usage, bias, and discrimination [40]. Current chatbot technologies face limitations, including the inability to simulate human-like conversation, lack of domain-specific data, and limited evaluation frameworks [41]. The key obstacle to overcome is the large number of parameters in pre-trained language models, which makes fine-tuning and storing all the parameters prohibitively costly [13]. Large language models are also vulnerable to security and privacy attacks, including prompt injection, jailbreaking, backdoor, data poisoning, and privacy attacks [42]. Data-related challenges, such as unmeasured confounding in the training data, can lead to language models learning incorrect relationships between texts and reader responses [14]. The lack of explainability in NLP models makes it difficult to provide clear and understandable explanations for model predictions [43]. The large number of compute operations required can result in unrealistically long training times if special attention is not paid to concurrently optimizing the algorithms, software, and hardware stack [15]. The model still relies on superficial heuristics and has strong inherent biases, which can affect its performance on certain tasks [15].

AI-generated, for reference only.

3 Definitions and Preliminaries

To comprehensively understand the concepts and techniques underpinning the development and application of large language models, it is essential to delve into the foundational aspects of natural language processing, machine learning, and optimization algorithms, exploring key concepts, methodologies, and challenges associated with these fields [44, 45, 39]. Natural language processing (NLP) is a fundamental aspect of artificial intelligence that deals with the interaction between computers and humans in natural language, enabling computers to process, understand, and generate human language [46, 31]. Key concepts in NLP, including masked language modeling, next sentence prediction, and prefix tuning, are used in the pretraining, transfer learning, and in-context learning stages of large language models [47, 23].

The complexity of natural language and the difficulties in achieving high performance in various tasks, such as language modeling, text classification, and machine translation, are significant challenges in NLP [44, 48]. Sentiment analysis and opinion mining are essential applications of NLP, allowing for the analysis of text to determine the sentiment or opinion expressed [46]. The knowledge present in the weights of existing pretrained language models is also a crucial concept in NLP, enabling the development of more accurate and efficient models [31]. Explainability in NLP is another important concept, with various approaches being developed to provide transparent and interpretable models [49].

The hierarchical structure of these concepts can be visualized in Figure 2, which illustrates the relationships between natural language processing, machine learning, and optimization algorithms. This figure provides a comprehensive overview of the top-level categories, including natural language processing, machine learning and deep learning, and optimization algorithms and techniques, as well as their respective subcategories. For instance, the natural language processing category is further divided into subcategories such as key concepts, applications, and challenges, while the machine learning and deep learning category includes fundamentals, applications, and techniques. The optimization algorithms and techniques category comprises subcategories like optimization methods, parallelism techniques, and efficient optimization. This hierarchical structure highlights the interconnectedness of these fields and can serve as a guide for further research and development.

Text generation, language translation, and text summarization are fundamental concepts in NLP, allowing for the generation of human-like text, translation of text from one language to another, and summarization of long documents [50]. The complexity and variability of biological language, including specialized terminology, ambiguity, and diversity, are significant challenges in NLP, requiring innovative algorithms to translate this information into a machine-readable form [48]. Self-supervised masked language modeling and sentence-order prediction are used to learn the representation of clinical text in large clinical language models, such as GatorTron [51].

The survey of NLP methods and research organizes the current methods or research into several fields or stages, including data classification, image analysis, emotion analysis, quantitative data analysis, and pattern recognition [52]. Bias in NLP systems is a significant concern, with the importance of understanding the characteristics of datasets used to train and test NLP systems, and the need for transparency and fairness in NLP systems [53]. Various NLP tasks, such as Part-Of-Speech tagging, chunking, Named Entity Recognition, and Semantic Role Labeling, are essential concepts in NLP [54].

3.1 Key Concepts in Natural Language Processing

Natural language processing encompasses a wide range of concepts, including language understanding and generation models, which are crucial for developing large language models [39, 31]. The principles of brain function and organization, and how they inspire deep learning algorithms and architectures, are also crucial concepts in NLP [55]. Natural language processing, peer-feedback process, and textual data analysis are also important concepts in NLP, particularly in the context of educational settings [56].

Moreover, the definition of semantic similarity, knowledge-based methods, corpus-based methods, and deep neural network-based methods are fundamental concepts in NLP [57]. The survey discusses various datasets used for text analytics tasks, including the Amazon dataset, Arabic news datasets, and the Stanford Sentiment Treebank dataset [58]. Key concepts in NLP, such as attention mechanisms

AI-generated, for reference only.




Figure 2: This figure illustrates the hierarchical structure of natural language processing, machine learning, and optimization algorithms. The top-level categories include natural language processing, machine learning and deep learning, and optimization algorithms and techniques. Each category is further divided into subcategories, such as key concepts, applications, and challenges in natural language processing, and fundamentals, applications, and techniques in machine learning and deep learning. The optimization algorithms and techniques category includes subcategories such as optimization methods, parallelism techniques, and efficient optimization. This figure provides a comprehensive overview of the relationships between these concepts and can be used to guide further research and development in these fields.

and their importance in NLP, are also crucial for understanding the complexities of natural language [47].

The survey provides an overview of the core deep generative models (DGMs) that have shaped the evolution of GAI [59]. Fundamental concepts in natural language processing related to VL-PTMs, including visual question answering, image-text retrieval, and visual commonsense reasoning, are also essential for understanding the complexities of natural language [60]. Language should emerge from necessity, and agents should learn to communicate in order to accomplish goals in a physical environment [61].

The importance of integrating human knowledge and experience into machine learning models, human-in-the-loop techniques for natural language processing, are also crucial concepts in NLP [62]. Furthermore, statistical learning and language acquisition are fundamental concepts in NLP, as they enable machines to learn from data and acquire language skills [63]. The Dynamic Memory Network (DMN) is a neural network-based framework for general question answering tasks, sequence tagging, classification problems, sequence-to-sequence tasks, and question answering tasks that require transitive reasoning [27].

3.2 Machine Learning and Deep Learning Fundamentals

The fundamentals of machine learning and deep learning are crucial for understanding the capabilities and limitations of large language models [38]. Machine learning involves training algorithms on data to enable them to make predictions or take actions, while deep learning is a subset of machine learning that uses neural networks with multiple layers to analyze data [64]. Feed-forward neural networks, convolutional neural networks, and recurrent neural networks are essential components of deep learning, each with its strengths and weaknesses [38].

AI-generated, for reference only.

For example, feed-forward neural networks are suitable for tasks such as text classification, while convolutional neural networks are more suitable for image classification tasks [9]. Recurrent neural networks, including long short-term memory (LSTM) and gated recurrent units (GRU), are particularly useful for sequential data such as text or speech [9]. The survey of machine learning and deep learning algorithms for part-of-speech (POS) tagging highlights the importance of selecting the most suitable algorithm for a specific task [64].

The comparison of different algorithms, including LSTM, RNN, BiLSTM, CRF, and HMM, demonstrates the advantages and disadvantages of each approach [64]. For instance, LSTM and BiLSTM are suitable for sequential data, while CRF is more suitable for tasks that require modeling dependencies between variables [64]. The combination of reinforcement learning and deep learning is a promising approach for improving the performance of large language models [12].

3.3 Optimization Algorithms and Techniques

Optimization algorithms and techniques are crucial for improving the performance, efficiency, and effectiveness of large language models. Various optimization methods have been proposed to address the challenges and limitations of large language models, including causal preference optimization (CPO) and doubly robust CPO (DR-CPO) [14]. CPO is a framework for optimizing language models based on human preferences, which can be used to improve the performance of language models in various tasks, such as language translation and text summarization.

DR-CPO is an extension of CPO that uses a doubly robust estimator to reduce the variance of the preference estimates, which can lead to more stable and efficient optimization [14]. In addition to CPO and DR-CPO, other optimization algorithms and techniques have been proposed for large language models, such as 3D parallelism [15]. 3D parallelism combines data, tensor, and pipeline parallelism to address both compute and memory efficiency simultaneously.

Data parallelism is used to scale to an arbitrarily large number of GPUs, while tensor parallelism is used to partition the individual layers of the model across workers [15]. Pipeline parallelism is used to divide the layers of the model into stages that can be processed in parallel, which can lead to significant improvements in compute efficiency [15]. The development of more efficient optimization methods is an active area of research, with various techniques being proposed to improve the performance of large language models [65].

These techniques include the use of machine learning and deep learning techniques, such as reinforcement learning (RL) [21], which can be used to incentivize model reasoning behaviors and allow the model to autonomously develop advanced problem-solving strategies. Various optimization algorithms have been proposed for large language models, including the Limited Memory Variable Metric Algorithm [66], which is a quasi-Newton method that uses a Hessian matrix approximation to update the parameter vector.

Other optimization algorithms, such as stochastic gradient descent (SGD) and Adam [22], have also been widely used for large language models. The use of word embedding models, such as Word2Vec and GloVe, is another optimization technique that can be used to improve the performance of large language models [58]. These models can be used to represent words as vectors in a high-dimensional space, which can capture the semantic relationships between words and improve the performance of language models.

4 Optimization Techniques for Large Language Models

As shown in Table 1, which provides a comprehensive overview of the various optimization techniques for large language models, highlighting their key features and methods, and serving as a reference point for researchers and practitioners in the field of natural language processing, optimization techniques are vital for enhancing the performance, efficiency, and effectiveness of large language models in various natural language processing tasks and applications [10, 74, 25]. The primary challenges that researchers face in this area include opacity and inexplicability, data privacy and security, personalization and fairness, and effectiveness and reliability [10]. To address these challenges, various optimization techniques have been proposed, including domain-specific pretraining from scratch, which can capture the nuances of the biomedical domain and lead to better performance on downstream tasks [74]. Additionally, the use of semantic similarity measures, such

AI-generated, for reference only.

Category	Feature	Method
Model Pruning and Knowledge Distillation	Causal Methods	CPO[14]
	Efficiency Strategies	MT-NLG[15], PHVM[67]
	Efficiency Optimization	LF[20]
Quantization and Parallelization	Parallelization Techniques	MLM[17], UT-SCS[68], Veagle[69], BMWEI[70], TF[23]
	Hardware Adaptation	HAT[71]
Other Optimization Techniques	Adversarial Methods	TLM[72]
	Hybrid Optimization	MIXER[50], ERGBCS[73], PM[22]
	Reinforcement-Based	DSR1-Z[21]
	Efficient Computing	LMVM[66]

Table 1: Summary of optimization techniques for large language models, including model pruning and knowledge distillation, quantization and parallelization, and other techniques such as adversarial methods, hybrid optimization, and reinforcement-based approaches. These techniques aim to improve the performance, efficiency, and effectiveness of large language models in various natural language processing tasks and applications. The table provides an overview of the different methods and their corresponding features.

as hybrid-based measures, can offer high accuracy in various NLP tasks [25]. The potential of NLP to improve medical education by providing a way to analyze and understand large amounts of textual data is also a significant application of optimization techniques [26]. However, there is a need for a benchmark that specifically evaluates the ability of LLMs to provide accurate medical information, as existing benchmarks may not adequately assess this aspect [75]. The potential of ChatGPT to reduce the time required for various tasks, improve the accuracy and efficiency of research, and enhance patient care is another significant application of optimization techniques [76]. Furthermore, various techniques for explainable AI, including model-agnostic methods, gradient-based methods, and propagation-based approaches, can be used to improve the transparency and interpretability of large language models [11]. The comparison of different deep reinforcement learning methods, including Deep Q-Networks (DQN) and Deep Fitted Q-iteration (DFQ), can also provide insights into the strengths and weaknesses of various optimization techniques [12]. Table 1 provides a comprehensive overview of the various optimization techniques for large language models, highlighting their key features and methods, and serving as a reference point for researchers and practitioners in the field of natural language processing.

4.1 Introduction to Optimization Techniques

Optimization techniques for large language models are crucial for improving their performance, efficiency, and effectiveness in various natural language processing tasks and applications [10, 74, 25]. The use of importance weighting to optimize language models for human preferences, as proposed in [14], can also be related to model pruning and knowledge distillation techniques. Furthermore, the application of 3D parallelism, as discussed in [15], can facilitate more efficient training of large language models, making it possible to train models with hundreds of billions of parameters. Model pruning and knowledge distillation techniques can be used to improve the efficiency of Transformer models, as highlighted in [77]. Additionally, domain-specific adaptation and fine-tuning methods for pre-trained language models, as explored in [78], can be used in conjunction with model pruning and knowledge distillation to further optimize model performance. The application of model pruning and knowledge distillation techniques to large language models for text generation has also been discussed in [67]. Neural network-based embeddings, such as Word2Vec and BERT, can be used to improve performance on downstream NLP tasks, as mentioned in [79]. However, the primary challenge in addressing LLM hallucinations is the difficulty in distinguishing between factual and hallucinated content, particularly in cases where the model generates plausible but incorrect information, as noted in [80]. The limitations of transformer-based models, including their requirement for large amounts of training data, computational resources, and potential lack of interpretability, are also significant concerns [81].

4.2 Model Pruning and Knowledge Distillation

Model pruning and knowledge distillation are essential techniques for optimizing large language models, enabling the reduction of computational costs and improvement of model efficiency [82, 83, 14]. Model pruning involves removing redundant or unnecessary weights and connections in the neural network, resulting in a more compact and efficient model [83]. Knowledge distillation,

AI-generated, for reference only.

on the other hand, is a technique used to transfer knowledge from a large, pre-trained model (the teacher) to a smaller, target model (the student) [13]. This process allows the student model to learn from the teacher model's outputs, enabling it to achieve similar performance while requiring fewer computational resources. The use of importance weighting to optimize language models for human preferences, as proposed in [14], can also be related to model pruning and knowledge distillation techniques. Furthermore, the application of 3D parallelism, as discussed in [15], can facilitate more efficient training of large language models, making it possible to train models with hundreds of billions of parameters. Model pruning and knowledge distillation techniques can be used to improve the efficiency of Transformer models, as highlighted in [77]. Additionally, domain-specific adaptation and fine-tuning methods for pre-trained language models, as explored in [78], can be used in conjunction with model pruning and knowledge distillation to further optimize model performance. The application of model pruning and knowledge distillation techniques to large language models for text generation has also been discussed in [67]. Neural network-based embeddings, such as Word2Vec and BERT, can be used to improve performance on downstream NLP tasks, as mentioned in [79]. Model pruning, knowledge distillation, Hardware-Aware Transformer (HAT) framework, and weight-shared SuperTransformer can be used to optimize large language models, as proposed in [71]. The adaptive circulation mechanism can be used to allocate more computing resources to sentences with complex semantic information, as mentioned in [68]. Veagle uses a visual encoder to extract meaningful representations from images and a language model to process textual information, with a multi-layer perceptron and Q-Former enabling better alignment between the two modalities [69]. The importance of the "Retriever-Reader" architecture in OpenQA systems, including the Retriever and Reader components [84]. The method involves extracting bilingual MWEs, integrating them into the SMT system through model retraining, feature addition, or phrase table construction, and evaluating the system's performance using metrics such as BLEU score [70]. Overall, model pruning and knowledge distillation are crucial techniques for optimizing large language models, enabling the development of more efficient and effective models for various NLP tasks.

4.3 Quantization and Parallelization

Quantization and parallelization techniques are essential for optimizing the performance of large language models, enabling them to be trained and deployed more efficiently [17, 20]. The Megatron-LM architecture, for example, uses a combination of model parallelism and data parallelism to achieve high performance and efficiency [17]. In this approach, the model is divided into smaller parts, each of which is distributed across multiple GPUs. Data parallelism is then used to process multiple input sequences in parallel, allowing for significant improvements in training speed and efficiency. The use of quantization techniques, such as integer quantization, can also help to reduce the memory requirements and computational costs of large language models, making them more suitable for deployment on edge devices or in resource-constrained environments. Furthermore, the application of parallelization techniques, such as pipeline parallelism and tensor parallelism, can help to improve the scalability and efficiency of large language models, allowing them to be trained on larger datasets and deployed in more complex applications. The library's innovative approach lies in its domain-specific design, allowing for automatic support for model analysis, usage, deployment, benchmarking, and easy replicability, as discussed in [23]. Model pruning, knowledge distillation, Hardware-Aware Transformer (HAT) framework, and weight-shared SuperTransformer can be used to optimize large language models, as proposed in [71]. The adaptive circulation mechanism can be used to allocate more computing resources to sentences with complex semantic information, as mentioned in [68]. Veagle uses a visual encoder to extract meaningful representations from images and a language model to process textual information, with a multi-layer perceptron and Q-Former enabling better alignment between the two modalities [69]. The importance of the "Retriever-Reader" architecture in OpenQA systems, including the Retriever and Reader components [84]. The method involves extracting bilingual MWEs, integrating them into the SMT system through model retraining, feature addition, or phrase table construction, and evaluating the system's performance using metrics such as BLEU score [70]. Overall, quantization and parallelization techniques are critical for optimizing the performance of large language models and enabling them to be used in a wide range of applications, from natural language processing and language translation to question answering and text summarization.

AI-generated, for reference only.

4.4 Other Optimization Techniques

Other optimization techniques used in large language models include the application of ensemble learning, distributed or streaming implementations, and the exploration of new feature engineering techniques for review spam detection [85, 86]. The use of data programming, weak supervision, and transfer learning can also provide scalable and accurate solutions for data collection [86]. Additionally, careful design of pretraining methods and adaptation techniques is crucial to achieve good performance [87]. Developing effective defenses against trojaning attacks and investigating the vulnerabilities of LMs to instance-level backdoor attacks are also important optimization techniques [72]. Mixed loss functions that combine cross-entropy and reinforcement learning, such as MIXER, can also be used to optimize large language models [50]. Other optimization techniques include adversarial training, defensive distillation, feature squeezing, gradient hiding, blocking transferability, data compression, and data randomization [88]. The multi-seq2seq model, which integrates retrieved replies into the generation process, and a re-ranker to re-evaluate the retrieved and generated replies and select the best one, is another optimization technique for large language models [73]. DeepSeek-R1-Zero uses reinforcement learning to train large language models to develop reasoning abilities, with a focus on mathematical, coding, and logical reasoning domains [21]. The innovation of the proposed method is that it uses the cost function itself in addition to the first derivative of the cost function to solve the optimization problem, allowing the method to escape local minima and converge to the global minimum [22]. Limited Memory Variable Metric Algorithm is also an optimization technique that can be used to improve the convergence rate, accuracy, and computational efficiency of model parameter estimation [66]. Furthermore, there is a need for further investigation into the properties of evaluation measures and the development of new statistical significance tests that can handle dependent observations [89]. Overall, these optimization techniques can help improve the performance, efficiency, and effectiveness of large language models, and can be used in a variety of NLP tasks, including language translation, text summarization, and question answering.

Feature	Model Pruning and Knowledge Distillation	Quantization and Parallelization	Other Optimization Techniques
Optimization Scope	Model Weights	Model Parameters	Training Data
Optimization Method	Weight Pruning	Quantization	Ensemble Learning
Model Compatibility	Transformer	Large Models	Various Models

Table 2: Comparison of Optimization Techniques for Large Language Models. This table summarizes the key features and methods of various optimization techniques, including model pruning and knowledge distillation, quantization and parallelization, and other techniques. The optimization scope, method, and model compatibility are highlighted for each technique.

5 Applications of Optimized Large Language Models

The applications of optimized large language models are vast and varied, with significant potential to transform numerous industries and aspects of our lives, as highlighted in [37, 74]. Optimized large language models have been used in various domains, including language translation, text summarization, question answering, dialogue generation, healthcare, education, business, and finance, to improve the accuracy and effectiveness of tasks such as machine translation, text analysis, and decision-making [90, 70, 91].

5.1 Language Translation and Text Summarization

Optimized large language models have been used in language translation to improve the accuracy and effectiveness of machine translation systems, and in text summarization to automatically generate summaries of long documents, highlighting the key points and main ideas [70, 24]. The integration of bilingual multiword expressions into statistical machine translation systems has been shown to improve translation quality, particularly in Chinese-to-English translation tasks [70]. Additionally, the use of semantic similarity measures, such as hybrid-based measures, can offer high accuracy in various NLP tasks, including language translation and text summarization [25].

AI-generated, for reference only.

5.2 Question Answering and Dialogue Generation

Optimized large language models have been used in question answering to improve the accuracy and effectiveness of question answering systems, and in dialogue generation to generate coherent and contextually appropriate responses [91, 37]. The potential of ChatGPT to generate coherent and contextually appropriate responses in question answering and dialogue generation has been explored, and it has been shown to have significant potential in these areas [91]. Furthermore, the use of multi-task learning and transfer learning can improve the performance of optimized large language models in question answering and dialogue generation [92].

5.3 Applications in Healthcare and Education

Optimized large language models have been used in healthcare to improve patient engagement, provide personalized support, and manage chronic diseases, and in education to enhance student learning experience, provide personalized learning management systems, and improve teacher training [93, 78]. The applications of NLP in healthcare and education are significant, with the potential to improve clinical decision support, medical research, and language assessment [94]. Additionally, optimized large language models can be used in healthcare and education to provide accurate information on specific medical and educational topics and in certain situations, and to streamline bureaucratic tasks and facilitate increased direct patient-physician interaction [95].

5.4 Applications in Business and Finance

Optimized large language models have been used in business and finance to improve the accuracy and effectiveness of financial forecasting, portfolio management, and investment decisions [37, 96]. The application of optimized large language models in business and finance has the potential to transform financial AI, enabling companies to make more informed decisions, reduce risks, and improve customer experience [96]. Furthermore, optimized large language models can be used in business and finance to enhance customer experience, provide personalized support, and improve business outcomes [93]. However, companies must carefully consider the potential impacts of LLMs on their business practices and adapt their strategies to accommodate these tools [97].

The applications of optimized large language models in business and finance, such as financial text analysis, sentiment analysis, and risk assessment, using models like BERT, FinBERT, and XLNet, have been explored, and it has been shown that they can achieve good performance in these tasks [74]. Overall, the applications of optimized large language models in business and finance are diverse and widespread, with the potential to improve business outcomes, enhance financial decision-making, and streamline administrative processes in finance, as well as improve customer experience, provide personalized support, and improve business outcomes [98].

6 Challenges and Limitations

The optimization of large language models poses numerous challenges, broadly categorized into data-related, model-related, and evaluation and validation challenges, as highlighted in [99, 14, 43]. Data-related challenges include the need for large amounts of labeled data, risk of overfitting, and interpreting and explaining results, which are significant concerns, as noted in [99, 100, 32]. Model-related challenges comprise limitations in handling multimodal input, vulnerability to bias and toxicity, and the need for efficient and scalable training methods, as discussed in [37, 44, 45]. Evaluation and validation challenges involve the need for effective defense mechanisms against adversarial attacks, reproducibility and reliability of results, and robust evaluation metrics and methodologies, as emphasized in [42, 89].

6.1 Data-Related Challenges

Data-related challenges in optimizing large language models are significant, including the potential to perpetuate biases and generate misinformation, as noted in [99, 14]. The need for large amounts of labeled data, which can be time-consuming and expensive to obtain, is a primary challenge, as highlighted in [99]. Additionally, there is a risk of overfitting, and interpreting and explaining the results are significant concerns, as discussed in [99]. Other data-related challenges include

AI-generated, for reference only.

the presence of unmeasured confounding in the training data, leading to language models learning incorrect relationships between texts and reader responses, as noted in [14], and the requirement for large amounts of training data and vulnerability to out-of-vocabulary words in NMT, as discussed in [100]. The need for clearer terminology, standardized evaluation processes, and addressing the issue of fidelity in XAI is also a significant challenge, as emphasized in [43]. Furthermore, data-related challenges include biases in training data, the risk of propagating medical misinformation, and the need for large-scale datasets for conversational agents, as noted in [32, 33].

6.2 Model-Related Challenges

Model-related challenges of large language models are significant, including limitations in handling multimodal input, as discussed in [37], and vulnerability to bias and toxicity, as noted in [44]. The need for more efficient and scalable training methods, as well as the importance of incorporating linguistic knowledge and constraints, are also significant challenges, as emphasized in [45]. Model-related challenges include complexity, size, and the ability to handle long sequences and open-domain question answering, as noted in [39]. The production of disinformation, manifestation of biases, and regulatory and governance issues are also significant model-related challenges, as discussed in [96]. Furthermore, model-related challenges comprise the lack of robust evaluation schemes, the need for more research on reinforcement learning approaches for NLP tasks, and the difficulty of modeling complex linguistic structures and relationships, as noted in [101, 102]. The survey identifies gaps in current research, including the need for a deeper understanding of the theoretical principles behind delta-tuning and more systematic and comprehensive evaluations of delta-tuning methods, as emphasized in [13].

6.3 Evaluation and Validation Challenges

Benchmark	Size	Domain	Task Format	Metric
ChatGPT-Zero-Shot[103]	20	Natural Language Processing	Text-based Tasks	Accuracy, F1-score, ROUGE-1/2/L
LLM[104]	70,000	Natural Language Processing	Document-level Machine Translation	d-BLEU, COMET, CTT, AZPT
MIMIC-CDM[105]	2,400	Clinical Decision Making	Diagnostic Decision-making	Diagnostic accuracy
GLUE[29]	2,100	Natural Language Processing	Binary Classification	F1-score, Accuracy, Matthews Correlation Coefficient
Codex[106]	3500	Computer Science	Programming Exercises	Accuracy
LLM-Cancer[75]	104	Oncology	Question Answering	NCCN Concordance

Table 3: This table presents a selection of benchmarks used in the evaluation of large language models, covering various domains such as natural language processing, clinical decision making, and computer science. The benchmarks are characterized by their size, task format, and evaluation metrics. These benchmarks play a crucial role in assessing the performance and reliability of optimized large language models.

The evaluation and validation of optimized large language models pose significant challenges, including the need for effective defense mechanisms against adversarial attacks and the importance of reproducibility and reliability of results, as noted in [42]. The development of robust evaluation metrics and methodologies is crucial to ensure the reliability and validity of optimized large language models, as emphasized in [89]. Furthermore, the lack of standardized benchmarks and evaluation protocols makes it difficult to compare the performance of different models and identify areas for improvement, as discussed in [42]. To better understand the landscape of evaluation and validation in this context, Table 3 provides a detailed overview of representative benchmarks utilized in the evaluation and validation of optimized large language models, highlighting their diverse applications and assessment criteria. The need for proper statistical significance testing and considering the properties of evaluation measures and their distribution are also significant challenges in evaluating and validating optimized large language models, as noted in [89]. The use of techniques such as cross-validation and bootstrapping can help improve the reliability and validity of evaluation results, but these methods also have limitations and challenges, as discussed in [89]. Addressing these challenges is essential to ensure the reliability, validity, and effectiveness of optimized large language models in various applications, as highlighted in [42, 89].

AI-generated, for reference only.

7 Conclusion

7.1 Current State of Research and Future Directions

The optimization of large language models has undergone significant advancements in recent years, driven by the development of more efficient architectures and the integration of symbolic and connectionist AI, as seen in works such as [16, 36, 38]. Pre-trained models have achieved state-of-the-art results in various natural language processing and computer vision tasks, with the potential to revolutionize the field of artificial intelligence, as highlighted by [36, 38]. The current state of research in the application of neural networks to natural language processing, including the strengths and weaknesses of different architectures, necessitates further research and development, as noted by [38, 107].

Future research directions include adapting the proposed framework to new generations of language models, incorporating cognitive and knowledge-based components, and exploring the implications of the metaverse and Web 3.0 on Supply Chain and Operations Management, as suggested by [108, 107]. The survey provides a comprehensive review of the existing literature on ICL, including advanced techniques, analytical studies, relevant applications, and critical challenges and potential directions for future research, as discussed in [107, 109]. The potential of NLP to revolutionize medical education by providing a way to analyze and understand large amounts of textual data, and avenues for future research and development, are significant areas of research, as highlighted by [26, 75].

The current state of research on the applications and limitations of ChatGPT in the medical field, and the potential for future research directions, are significant areas of research, as noted by [76, 74]. The survey suggests potential directions for future research, including the development of mechanisms to make end-to-end learning practical in real-world applications and the exploration of transfer learning in deep reinforcement learning models, as discussed in [12, 110]. The current state of research in explainable AI, the importance of explainability in building trust in AI systems, and the need for further research in this area, are significant areas of research, as highlighted by [11, 111].

The current state of research in deep learning, natural language processing, and medical applications, is a significant area of research, as noted by [3, 4]. The survey suggests potential directions for future research, including the development of methods that scale, the integration of linguistic and domain knowledge with statistical processing, and the application of NLP in emerging areas such as social media text processing, as discussed in [5, 112]. The proposed method is a new optimization method that uses the first derivative of the cost function and the cost function itself to solve the optimization problem, as presented in [22, 6].

Current state of research in sentiment analysis in the education domain, including the need for more research on emotion detection, word embedding, and standardized datasets, is a significant area of research, as highlighted by [6, 113]. The survey suggests potential directions for future research, including the development of more hybrid measures, the application of semantic similarity measures in new domains such as multimodal processing, and the use of machine learning and deep learning techniques to improve the accuracy and efficiency of semantic similarity measures, as discussed in [25, 71].

Future work includes improving the accuracy of environment feedback, developing more robust control policies, and exploring the application of Inner Monologue to more complex tasks and environments, as suggested by [1, 2]. The current state of research in ontology learning and the need for more efficient preprocessing techniques, linguistic techniques, and human evaluation, is a significant area of research, as noted by [2, 114]. The current state of research in GenAI, including recent advancements and future directions, with a focus on the development of more advanced and efficient models, is a significant area of research, as highlighted by [8, 115].

The future of Vision-Language Models, including further exploration and innovation, with Veagle serving as a promising catalyst for advancements, is a significant area of research, as discussed in [69, 84]. The current state of research in OpenQA, including significant progress made in OpenQA research, the importance of the "Retriever-Reader" architecture, and the need for further exploration and advancement in areas such as generative readers and retriever-free methods, is a significant area of research, as noted by [84, 112]. The survey suggests potential directions for future research, including the development of more advanced deep learning architectures, and the application of text classification to emerging domains such as healthcare and finance, as discussed in [90, 9].

AI-generated, for reference only.

The current state of research in metaphor identification, including the need for further studies to extend the algorithms' performance beyond the specific sample, is a significant area of research, as highlighted by [24, 10]. The survey concludes that generative AI has the potential to provide personalized learning experiences, improve learning efficiency and effectiveness, and enhance students' interest and participation in learning, as discussed in [10, 25]. The potential directions for future research, including the development of more hybrid measures, the application of semantic similarity measures in new domains such as multimodal processing, and the use of machine learning and deep learning techniques to improve the accuracy and efficiency of semantic similarity measures, are significant areas of research, as noted by [25].

7.2 Future Research Directions

The future research directions for large language models are diverse and exciting, with several areas of focus that have the potential to significantly improve the performance, efficiency, and effectiveness of these models, as discussed in [116, 57]. One potential direction for future research is the exploration of novel pre-training objectives, such as those that incorporate reinforcement learning or multimodal learning, to improve the robustness and generalizability of large language models, as suggested by [116, 30].

Another potential direction for future research is the examination of the challenges and opportunities associated with generative AI in various domains, including education, healthcare, and finance, and the creation of new platforms and services centered around generative AI ecosystems, as noted by [59, 115]. The development of more robust and generalizable models, such as those that incorporate transfer learning or meta-learning, could lead to significant improvements in the performance of large language models, as discussed in [116, 30].

Future research directions in fake news detection include investigating the combination of handcrafted features with neural network models, developing content-based approaches, and extending the way of verification with contents, as suggested by [28, 21]. The development of more advanced multimodal fusion methods, such as those that incorporate attention mechanisms or graph-based models, could lead to significant improvements in multimodal intelligence, as noted by [30, 76].

The use of reinforcement learning to develop reasoning abilities in large language models is another potential direction for future research, with applications in natural language processing, computer vision, and other domains, as discussed in [21, 115]. The development of more advanced generative models, such as those that incorporate adversarial training or variational autoencoders, could lead to significant improvements in the performance of large language models, as suggested by [115, 116].

Future studies should aim to address the limitations of AI-mediated language instruction by conducting long-term follow-up studies, expanding the sample size, and exploring the applications of AI in different language contexts, as noted by [117, 116]. The development of more robust and generalizable models, such as those that incorporate transfer learning or meta-learning, could lead to significant improvements in the performance of large language models, as discussed in [116, 30].

The potential directions for future research in NLP, including the development of new statistical significance tests and the investigation of the impact of dependent observations on the results of NLP experiments, are crucial for advancing the field, as highlighted by [89, 76]. The development of methods to improve the accuracy and transparency of ChatGPT, the exploration of new applications in the medical field, and the establishment of clear guidelines and protocols for the use of ChatGPT in research and writing, are essential for ensuring the safe and effective use of large language models, as noted by [76, 112].

The future research directions for large language models are diverse and exciting, with several areas of focus that have the potential to significantly improve the performance, efficiency, and effectiveness of these models, as discussed in [116, 30]. As the field continues to evolve, it is likely that we will see significant advancements in the development and application of large language models, with the potential to transform various industries and domains, as highlighted by [8, 69].

AI-generated, for reference only.

References

[1] Wenlong Huang, Andy Zeng, Brian Ichter, Fei Xia, Harris Chan, Igor Mordatch, Jacky Liang, Jonathan Tompson, Karol Hausman, Linda Luu, Noah Brown, Pete Florence, Pierre Sermanet, Sergey Levine, Ted Xiao, Tomas Jackson, and Yevgen Chebotar. Inner monologue: Embodied reasoning through planning with language models. *arXiv preprint arXiv:2207.05608*, 2022.

[2] Muhammad Nabeel Asim, Hafiza Mahnoor Abbasi, Muhammad Usman Ghani Khan, Muhammad Wasim, and Waqar Mahmood. A survey of ontology learning techniques and applications. *Database*, 2018.

[3] Mohammad Mustafa Taye. Understanding of machine learning with deep learning: Architectures, workflow, applications and future directions. *Computers*, 2023.

[4] Elif Özkırımlı, Teodoro Laino, Arzucan Özgür, Hakime Öztürk, and Philippe Schwaller. Exploring chemical space using natural language processing methodologies for drug discovery. *Drug Discovery Today*, 2020.

[5] Carol Friedman, M Corn, and Thomas C. Rindflesch. Natural language processing: State of the art and prospects for significant progress, a workshop sponsored by the national library of medicine. *PubMed*, 2013.

[6] Zenun Kastrati, Ali Shariq Imran, Fisnik Dalipi, Krenare Pireva, and Mudasir Ahmad Wani. Sentiment analysis of students' feedback with nlp and deep learning: A systematic mapping study. *Applied Sciences*, 2021.

[7] Giang Nguyen, Ignacio Heredia, Ladislav Hluchý, Martin Bobák, Peter Malík, Viet Tran, Álvaro López García, and Štefan Dlugolinský. Machine learning and deep learning frameworks and libraries for large-scale data mining: a survey. *Artificial Intelligence Review*, 2019.

[8] Michail N. Giannakos, Bart Rienties, Davinia Hernández-Leo, Manolis Mavrikis, Mutlu Cukurova, Peter Brusilovsky, Roger Azevedo, Sanna Järvelä, and Yannis Dimitriadis. The promise and challenges of generative ai in education. *Behaviour and Information Technology*, 2024.

[9] Laith Alzubaidi, Amjad J. Humaidi, Ayad Q. Al-Dujaili, Jinglan Zhang, José Santamaría, Laith Farhan, Mohammed A. Fadhel, Muthana Al-Amidie, Omran Al-Shamma, and Ye Duan. Review of deep learning: concepts, cnn architectures, challenges, applications, future directions. *Journal Of Big Data*, 2021.

[10] Hao Yu and Yunyun Guo. Generative artificial intelligence empowers educational reform: current status, issues, and prospects. *Frontiers in Education*, 2023.

[11] Wojciech Samek and Klaus-Robert Müller. Towards explainable artificial intelligence. *Lecture notes in computer science*, 2019.

[12] Seyed Sajad Mousavi, Enda Howley, and Michael Schukat. Deep reinforcement learning: An overview. *Lecture notes in networks and systems*, 2017.

[13] Ning Ding, Chi-Min Chan, Fuchao Wei, Guang Yang, Hai-Tao Zheng, Jianfei Chen, Jie Tang, Jing Yi, Juanzi Li, Maosong Sun, Shengding Hu, Weilin Zhao, Weize Chen, Xiaozhi Wang, Yang Liu, Yujia Qin, Yulin Chen, Yusheng Su, Zhiyuan Liu, and Zonghan Yang. Parameter-efficient fine-tuning of large-scale pre-trained language models. *Nature Machine Intelligence*, 2023.

[14] Victoria Lin, Eli Ben-Michael, and Louis–Philippe Morency. Optimizing language models for human preferences is a causal inference problem. *arXiv preprint arXiv:2402.14979*, 2024.

[15] Shaden Smith, Brandon Norick, Bryan Catanzaro, Elton Zhang, George Zerveas, Jared Casper, Julie Bernauer, Michael E. Houston, Mohammad Shoeybi, Mostofa Patwary, Patrick LeGresley, Rewon Child, Reza Yazdani Aminabadi, Samyam Rajbhandari, Saurabh Tiwary, Shrimai Prabhumoye, Song Xia, Vijay Anand Korthikanti, Yuxiong He, and Zhun Liu. Using deepspeed and megatron to train megatron-turing nlg 530b, a large-scale generative language model. *arXiv preprint arXiv:2201.11990*, 2022.

AI-generated, for reference only.

[16] Or Sharir, Barak Peleg, and Yoav Shoham. The cost of training nlp models: A concise overview. *arXiv preprint arXiv:2004.08900*, 2020.

[17] Mohammad Shoeybi, Bryan Catanzaro, Jared Casper, Mostofa Patwary, Patrick LeGresley, and Raul Puri. Megatron-lm: Training multi-billion parameter language models using model parallelism. *arXiv preprint arXiv:1909.08053*, 2019.

[18] Nan Du, Adams Wei Yu, Andrew M. Dai, Barret Zoph, Claire Cui, Dmitry Lepikhin, Kathy Meier-Hellstern, Kellie Webster, Kevin Robinson, Kun Zhang, Liam Fedus, Lucas Dixon, Maarten Bosma, Marie Pellat, Maxim Krikun, Orhan Fırat, Quoc V. Le, Simon Tong, Tao Wang, Toju Duke, Yanping Huang, Yanqi Zhou, Yonghui Wu, Yu Emma Wang, Yuanzhong Xu, Zhifeng Chen, and Zongwei Zhou. Glam: Efficient scaling of language models with mixture-of-experts. *arXiv preprint arXiv:2112.06905*, 2021.

[19] Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for modern deep learning research. *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

[20] Sinong Wang, Belinda Z. Li, Fang Han, Hao Ma, and Madian Khabsa. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

[21] Daya Guo, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bowen Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chong Ruan, Damai Dai, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fengze Dai, Fuli Luo, Guan-Ting Chen, Guangbo Hao, Guowei Li, Hanwei Xu, Haowei Zhang, Honghui Ding, Hongjun Zhang, Huazuo Gao, Hui Li, Hui Qu, Jiagang Tu, Jiali Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jing Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaichao You, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, L. Xia, Lean Wang, Lecong Zhang, Lei Xu, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojun Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Mingxu Zhou, Ning Tian, Panpan Huang, Pei Tian, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, Rong Jin, Ruiqi Ge, Ruisong Zhang, Rui-Le Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, Sansan Li, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaoqing Wu, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shuting Pan, Tao Yun, Tianfu Wang, Tianyu Sun, Wangding Zeng, Wei Guang An, Wen Liu, Wenfeng Liang, Wenjun Gao, Wenlian Xiao, Wentao Zhang, X. Q. Li, X. Y. Shan, X.-J Su, X.G. Wang, Xiao Bi, Xiaodong Liu, Xiaohan Wang, Xiaojin Shen, Xiaokang Chen, Xiaokang Zhang, Xiaosha Chen, Xiaotao Nie, Xiaowen Sun, Xiaoxiang Wang, Xin Cheng, Xin Jin, Xin Liu, Xin Xie, Xingchao Liu, Xingkai Yu, Xinnan Song, Xinyi Zhou, Xinyu Yang, Xinyuan Li, Xuheng Lin, Y. K. Li, Y. Ma, Yajie Zou, Yang Zhang, Yangjie Ou, Yanhong Xu, Yanping Huang, Yao Li, Yao Zhao, Yaofeng Sun, Yaohui Li, Yaohui Wang, Yi Yu, Yi Zheng, Yi Zhu, Yichao Zhang, Yifan Shi, Yiliang Xiong, Ying He, Ying Tang, Yishi Piao, Yisong Wang, Yixuan Tan, Yiyang Ma, Yiyuan Liu, Yongqiang Guo, Yu Wu, Yuduan Wang, Yue Gong, Yufei Wang, Yujia He, Yukun Zha, Yunkui Xiong, Yunxie Wei, Yuting Yan, Yuxiang Luo, Yuxiang You, Yuxin Zhu, Yuxuan Liu, Yuyang Zhou, Z. L. Xu, Z. Z. Ren, Zehui Ren, Zhangli Sha, Zhe Fu, Zhen Huang, Zhen Zhang, Zhen Zhang, Zhenda Xie, Zhengyan Zhang, Zhenhua Wu, Zhewen Hao, Zhibin Gou, Zhicheng Ma, Zhigang Yan, Zhihong Shao, Zhipeng Xu, Zhiyu Wu, Zhongyu Zhang, Zhuoshu Li, Zihui Gu, Zijia Zhu, Zijun Liu, Zilin Li, Ziwei Xie, Ziyang Song, Ziyi Gao, and Zizheng Pan. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *PubMed*, 2025.

[22] Sangmin Ji, Dokkyun Yi, and Jae-Hyun Ahn. An effective optimization method for machine learning based on adam. *Applied Sciences*, 2020.

[23] Thomas Wolf, Anthony Moi, Clément Delangue, Mariama Drame, Sylvain Gugger, Jamie Brew, Yacine Jernite, Julien Chaumond, Quentin Lhoest, Lysandre Debut, Clara Ma, Morgan Funtowicz, Pierric Cistac, Julien Plu, Alexander M. Rush, Rémi Louf, Teven Le Scao, Sam Shleifer, Tim Rault, Victor Sanh, Canwen Xu, and Patrick von Platen. Huggingface's transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*, 2019.

AI-generated, for reference only.

[24] Yair Neuman, Dan Assaf, Mark Last, Newton Howard, Ophir Frieder, Shlomo Argamon, and Yohai Cohen. Metaphor identification in large texts corpora. *PLoS ONE*, 2013.

[25] Thabet Slimani. Description and evaluation of semantic similarity measures approaches. *International Journal of Computer Applications*, 2013.

[26] Michael Chary, Alex F. Manini, Edward W. Boyer, Michael Radeous, and Saumil Parikh. A review of natural language processing in medical education. *PubMed*, 2018.

[27] Ankit Kumar, Ishaan Gulrajani, James Bradbury, Mohit Iyyer, Ozan İrsoy, Peter Ondrúška, Richard Socher, Romain Paulus, and Victor W. Zhong. Ask me anything: Dynamic memory networks for natural language processing. *arXiv preprint arXiv:1506.07285*, 2015.

[28] Ray Oshikawa, Jing Qian, and William Yang Wang. A survey on natural language processing for fake news detection. *arXiv preprint arXiv:1811.00770*, 2018.

[29] Jesse Dodge, Ali Farhadi, Gabriel Ilharco, Hannaneh Hajishirzi, Noah A. Smith, and Roy Schwartz. Fine-tuning pretrained language models: Weight initializations, data orders, and early stopping. *arXiv preprint arXiv:2002.06305*, 2020.

[30] Chao Zhang, Li Deng, Xiaodong He, and Zichao Yang. Multimodal intelligence: Representation learning, information fusion, and applications. *arXiv preprint arXiv:1911.03977*, 2019.

[31] Fabio Petroni, Alexander Miller, Anton Bakhtin, Patrick Lewis, Sebastian Riedel, Tim Rocktäschel, and Yuxiang Wu. Language models as knowledge bases? 2019.

[32] Marco Cascella, Elena Bignami, Federico Semeraro, Jonathan Montomoli, Ornella Piazza, and Valentina Bellini. The breakthrough of large language models release for medical applications: 1-year timeline and perspectives. *PubMed*, 2024.

[33] Sheetal Kusal, Ajith Abraham, Jyoti Choudrie, Ketan Kotecha, Sashikala Mishra, and Shruti Patil. Ai-based conversational agents: A scoping review from technologies to future directions. *IEEE Access*, 2022.

[34] Sandeep Singh Sengar, Affan Bin Hasan, Fiona Carroll, and Sanjay Kumar. Generative artificial intelligence: a systematic review and applications. *Multimedia Tools and Applications*, 2024.

[35] Zihuai Zhao, Fei Wang, Jiatong Li, Jiliang Tang, Qing Li, Wenqi Fan, Xiangyu Zhao, Xiaowei Mei, Yiqi Wang, Yunqing Liu, and Zhen Wen. Recommender systems in the era of large language models (llms). *IEEE Transactions on Knowledge and Data Engineering*, 2024.

[36] Xu Han, Ao Zhang, Ji-Rong Wen, Jie Tang, Jiezhong Qiu, Jinhui Yuan, Jun Zhu, Liang Zhang, Minlie Huang, Ning Ding, Qin Jin, Ruihua Song, Wayne Xin Zhao, Wentao Han, Xiao Liu, Xipeng Qiu, Yang Liu, Yanyan Lan, Yuan Yao, Yuqi Huo, Yuxian Gu, Zhengyan Zhang, Zhiwu Lu, and Zhiyuan Liu. Pre-trained models: Past, present and future. *AI Open*, 2021.

[37] Mohaimenul Azam Khan Raiaan, Jubaer Ahmad, Kaniz Fatema, Md. Saddam Hossain Mukta, Mohammed Eunus Ali, Most. Marufatul Jannat Mim, Nur Mohammad Fahad, Sadman Sakib, and Sami Azam. A review on large language models: Architectures, applications, taxonomies, open issues and challenges. *IEEE Access*, 2024.

[38] Yoav Goldberg. Neural network methods for natural language processing. *Synthesis lectures on human language technologies*, 2017.

[39] Sushant Kumar Singh and Ausif Mahmood. The nlp cookbook: Modern recipes for transformer based deep learning architectures. *IEEE Access*, 2021.

[40] Bao Ge, Antong Li, Dajiang Zhu, Dingang Shen, Hao He, Jiaming Tian, Jiayue Zhang, Lin Zhao, Mengshen He, Qiang Ning, Siyuan Ma, Tianle Han, Tianming Liu, Xiang Li, Yiheng Liu, Yuanyuan Yang, Zhengliang Liu, and Zihao Wu. Summary of chatgpt-related research and perspective towards the future of large language models. *Meta-Radiology*, 2023.

[41] Guendalina Caldarini, Kenneth McGarry, and Sardar Jaf. A literature survey of recent advances in chatbots. *Information*, 2022.

AI-generated, for reference only.

[42] Badhan Chandra Das, M. Hadi Amini, and Yanzhao Wu. Security and privacy challenges of large language models: A survey. *ACM Computing Surveys*, 2025.

[43] Marina Danilevsky, Ban Kawas, Kun Qian, Prithviraj Sen, Ranit Aharonov, and Yannis Katsis. A survey of the state of explainable ai for natural language processing. 2020.

[44] Amirsina Torfi, Edward A. Fox, Nader Tavaf, Rouzbeh A. Shirvani, and Yaser Keneshloo. Natural language processing advancements by deep learning: A survey. *arXiv preprint arXiv:2003.01200*, 2020.

[45] Rajvardhan Patil and Venkat N. Gudivada. A review of current trends, techniques, and challenges in large language models (llms). *Applied Sciences*, 2024.

[46] Muhammad Taimoor Khan, Armughan Ali, Irum Inayat, Kamran Khan, Mehr Yahya Durrani, and Shehzad Khalid. Sentiment analysis and the complex natural language. *Complex Adaptive Systems Modeling*, 2016.

[47] Andrea Galassi, Marco Lippi, and Paolo Torroni. Attention in natural language processing. *PubMed*, 2020.

[48] Anne Thessen, Dmitry Mozzherin, and Hong Cui. Applications of natural language processing in biodiversity science. *PubMed*, 2012.

[49] Eduardo Soares, Plamen Angelov, Nicholas I. Arnold, Peter M. Atkinson, and Richard Jiang. Explainable artificial intelligence: an analytical review. *Wiley Interdisciplinary Reviews Data Mining and Knowledge Discovery*, 2021.

[50] Marc'Aurelio Ranzato, Michael Auli, Sumit Chopra, and Wojciech Zaremba. Sequence level training with recurrent neural networks. *arXiv preprint arXiv:1511.06732*, 2015.

[51] Xi Yang, Anthony Costa, Aokun Chen, Cheryl Martin, Christopher A. Harle, Christopher Parisien, Colin B. Compas, Duane A. Mitchell, Elizabeth Shenkman, Gloria Lipori, Hoo Chang Shin, Jiang Bian, Kaleb E Smith, Mona G. Flores, Nima PourNejatian, Tanja Magoč, William R. Hogan, Ying Zhang, and Yonghui Wu. A large language model for electronic health records. *PubMed*, 2022.

[52] Vincenzo Corvello, Bastian Burger, Dominik K. Kanbach, Matthias Breier, and Sascha Kraus. On the use of ai-based tools like chatgpt to support management research. *European Journal of Innovation Management*, 2023.

[53] Batya Friedman and Emily M. Bender. Data statements for natural language processing: Toward mitigating system bias and enabling better science. *Transactions of the Association for Computational Linguistics*, 2018.

[54] CollobertRonan, BottouLéon, KarlenMichael, KavukcuogluKoray, KuksaPavel, and WestonJason. Natural language processing (almost) from scratch. *Journal of Machine Learning Research*, 2011.

[55] Terrence J. Sejnowski. The unreasonable effectiveness of deep learning in artificial intelligence. *Proceedings of the National Academy of Sciences*, 2020.

[56] Elisabeth Bauer, Martin Greisel, Frank Fischer, Ilia Kuznetsov, Ingo Kollar, Markus Berndt, Markus Dresel, and Martin R. Fischer. Using natural language processing to support peer-feedback in the age of artificial intelligence: A cross-disciplinary framework and a research agenda. *British Journal of Educational Technology*, 2023.

[57] Dhivya Chandrasekaran and Vijay Mago. Evolution of semantic similarity—a survey. *ACM Computing Surveys*, 2021.

[58] Deepak Suresh Asudani, Naresh Kumar Nagwani, and Pradeep Singh. Impact of word embedding models on text analytics in deep learning environment: a review. *PubMed*, 2023.

[59] Leonardo Banh and Gero Strobel. Generative artificial intelligence. *Electronic Markets*, 2023.

AI-generated, for reference only.

www.SurveyX.cn

[60] Junyi Li, Wayne Xin Zhao, Yifan Du, and Zikang Liu. A survey of vision-language pre-trained models. *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence*, 2022.

[61] Igor Mordatch and Pieter Abbeel. Emergence of grounded compositional language in multi-agent populations. *arXiv preprint arXiv:1703.04908*, 2017.

[62] Liang He, Junhang Zhang, Luwei Xiao, Tianlong Ma, Xingjiao Wu, and Yixuan Sun. A survey of human-in-the-loop for machine learning. *Future Generation Computer Systems*, 2022.

[63] Emmanuel Dupoux. Cognitive science in the era of artificial intelligence: A roadmap for reverse-engineering the infant language-learner. *Cognition*, 2018.

[64] Alebachew Chiche and Betselot Yitagesu. Part of speech tagging: a systematic review of deep learning and machine learning approaches. *Journal Of Big Data*, 2022.

[65] Ruihui Mu and Xiaoqin Zeng. A review of deep learning research. *KSII Transactions on Internet and Information Systems*, 2019.

[66] Robert Malouf. A comparison of algorithms for maximum entropy parameter estimation. 2002.

[67] Shao Zhi-hong, Jiangtao Wen, Minlie Huang, Wenfei Xu, and Xiaoyan Zhu. Long and diverse text generation with planning-based hierarchical variational model. 2019.

[68] Qingyang Zhou, Chenghui Peng, Honggang Zhang, Rongpeng Li, and Zhifeng Zhao. Semantic communication with adaptive universal transformer. *IEEE Wireless Communications Letters*, 2021.

[69] Rajat Chawla, A. N. JHA, Anmol Gautam, Arkajit Datta, Ayush Vatsal, Ishaan Bhola, Mukunda NS, Sukrit Chaterjee, and Tushar Verma. Veagle: Advancements in multimodal representation learning. *arXiv preprint arXiv:2403.08773*, 2024.

[70] Zhixiang Ren, Jie Cao, Qun Liu, Yajuan Lü, and Yun Huang. Improving statistical machine translation using domain bilingual multiword expressions. 2009.

[71] Hanrui Wang, Chuang Gan, Han Cai, Ligeng Zhu, Song Han, Zhanghao Wu, and Zhijian Liu. Hat: Hardware-aware transformers for efficient natural language processing. 2020.

[72] Xinyang Zhang, Shouling Ji, Ting Wang, and Zheng Zhang. Trojaning language models for fun and profit. 2021.

[73] Rui Yan, Cheng–Te Li, Dongyan Zhao, Jian-Yun Nie, Ming Zhang, and Yiping Song. An ensemble of retrieval-based and generation-based human-computer conversation systems. 2018.

[74] , Hao Cheng, Hoifung Poon, Jianfeng Gao, Michael Lucas, Naoto Usuyama, Robert Tinn, Tristan Naumann, and Xiaodong Liu. Domain-specific language model pretraining for biomedical natural language processing. *ACM Transactions on Computing for Healthcare*, 2021.

[75] Danielle S. Bitterman, Benjamin H. Kann, Guergana Savova, Hugo J.W.L. Aerts, Michael B. Foote, Raymond H. Mak, and Shan Chen. Use of artificial intelligence chatbots for cancer treatment information. *PubMed*, 2023.

[76] Tirth Dave, Sai Anirudh Athaluri, and Satyam Singh. Chatgpt in medicine: an overview of its applications, advantages, limitations, future prospects, and ethical considerations. *PubMed*, 2023.

[77] Yi Tay, Dara Bahri, Donald Metzler, and Mostafa Dehghani. Efficient transformers: A survey. *ACM Computing Surveys*, 2022.

[78] Benyou Wang, Jiahuan Pei, Jie Fu, Prayag Tiwari, Qianqian Xie, Zhao Li, and Zhihong Chen. Pre-trained language models in biomedical domain: A systematic survey. *ACM Computing Surveys*, 2023.

AI-generated, for reference only.

www.SurveyX.cn

[79] Rajvardhan Patil, Jagadeesh Nandigam, Sorio Boit, and Venkat N. Gudivada. A survey of text representation and embedding techniques in nlp. *IEEE Access*, 2023.

[80] Lei Huang, Bing Qin, Haotian Wang, Qianglong Chen, Ting Liu, Weihong Zhong, Weihua Peng, Weijiang Yu, Weitao Ma, Xiaocheng Feng, and Zhangyin Feng. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 2024.

[81] Stefano Marrone, Carlo Sansone, and Narendra Patwardhan. Transformers in the real world: A survey on nlp applications. *Information*, 2023.

[82] Wenwen Chai. Statistical language model-based analysis of english corpora and literature. *International Journal of Advanced Computer Science and Applications*, 2023.

[83] Bonan Min, Amir Pouran Ben Veyseh, Dan Roth, Elior Sulem, Eneko Agirre, Hayley Ross, Ilana Heintz, Oscar Sainz, and Thien Huu Nguyen. Recent advances in natural language processing via large pre-trained language models: A survey. *ACM Computing Surveys*, 2023.

[84] Fengbin Zhu, Chao Wang, Jianming Zheng, Soujanya Poria, Tat-Seng Chua, and Wenqiang Lei. Retrieving and reading: A comprehensive survey on open-domain question answering. *arXiv preprint arXiv:2101.00774*, 2021.

[85] Mike Crawford, Aaron N. Richter, Hamzah Al Najada, Joseph D. Prusa, and Taghi M. Khoshgoftaar. Survey of review spam detection using machine learning techniques. *Journal Of Big Data*, 2015.

[86] Yuji Roh, Geon Heo, and Steven Euijong Whang. A survey on data collection for machine learning: A big data - ai integration perspective. *IEEE Transactions on Knowledge and Data Engineering*, 2019.

[87] Sebastian Ruder, Matthew E. Peters, Swabha Swayamdipta, and Thomas Wolf. Transfer learning in natural language processing. 2019.

[88] Qihe Liu, Chunjiang Wu, Shijie Zhou, and Shilin Qiu. Review of artificial intelligence adversarial attack and defense technologies. *Applied Sciences*, 2019.

[89] Rotem Dror, Gili Baumer, Roi Reichart, and Segev Shlomov. The hitchhiker's guide to testing statistical significance in natural language processing. 2018.

[90] Jaeyoung Choi, Jana Shafi, Kavita Kavita, Muhammad Fazal Ijaz, Pushpita Chatterjee, Sahil Verma, and Varun Dogra. A complete process of text classification system using state-of-the-art nlp models. *Computational Intelligence and Neuroscience*, 2022.

[91] Nikolaos D. Tselikas and Konstantinos I. Roumeliotis. Chatgpt and open-ai models: A preliminary review. *Future Internet*, 2023.

[92] Anthony Gillioz, Elena Mugellini, Jacky Casas, and Omar Abou Khaled. Overview of the transformer-based models for nlp tasks. *Annals of Computer Science and Information Systems*, 2020.

[93] Thanveer Shaik, Christopher Dann, Jacquie McDonald, Linda Galligan, Petrea Redmond, Xiaohui Tao, and Yan Li. A review of the trends and challenges in adopting natural language processing methods for education feedback analysis. *IEEE Access*, 2022.

[94] Peter Adebowale Olujimi and Abejide Ade-Ibijola. Nlp techniques for automating responses to customer queries: a systematic review. *Discover Artificial Intelligence*, 2023.

[95] Fatima Karzai, Charalampos S. Floudas, Dara Bracken-Clarke, Giovanni Maria Iannantuono, James L. Gulley, and Mario Roselli. Applications of large language models in cancer care: current evidence and future perspectives. *PubMed*, 2023.

[96] Yinheng Li, Han Ding, Hang Chen, and Shaofei Wang. Large language models in finance: A survey. 2023.

AI-generated, for reference only.

www.surveyx.cn

[97] James Prather, Andrew Luxton-Reilly, Andrew Petersen, Brent N. Reeves, Brett A. Becker, Hieke Keuning, Ibrahim Albluwi, Jaromír Šavelka, Juho Leinonen, Michelle Craig, Natalie Kiesler, Paul Denny, Raymond Pettit, Stephen MacNeil, and Tobias Kohn. The robots are here: Navigating the generative ai revolution in computing education. 2023.

[98] Brady Lund, Bing Nie, Nishith Reddy Mannuru, Somipam R. Shimray, Ting Wang, and Ziang Wang. Chatgpt and a new academic reality: Artificial intelligence-written research papers and the ethics of the large language models in scholarly publishing. *Journal of the Association for Information Science and Technology*, 2023.

[99] Yoav Goldberg. A primer on neural network models for natural language processing. *Journal of Artificial Intelligence Research*, 2016.

[100] Shuoheng Yang, Xiaowen Chu, and Yuxin Wang. A survey of deep learning techniques for neural machine translation. *arXiv preprint arXiv:2002.07526*, 2020.

[101] Víctor Uc-Cetina, Anabel Martín-González, Cornelius Weber, Nicolás Navarro-Guerrero, and Stefan Wermter. Survey on reinforcement learning for language processing. *Artificial Intelligence Review*, 2022.

[102] Heung-Yeung Shum, Ming Zhou, Nan Duan, and Shujie Liu. Progress in neural nlp: Modeling, learning, and reasoning. *Engineering*, 2020.

[103] Chengwei Qin, Aston Zhang, Diyi Yang, Jiaao Chen, Michihiro Yasunaga, and Zhuosheng Zhang. Is chatgpt a general-purpose natural language processing task solver? 2023.

[104] Longyue Wang, Chenyang Lyu, Dian Yu, Shuming Shi, Tianbo Ji, Zhaopeng Tu, and Zhirui Zhang. Document-level machine translation with large language models. 2023.

[105] Paul Hager, Daniel Rueckert, Friederike Jungmann, Georgios Kaissis, Inga Hubrecht, Jakob Vielhauer, Kunal Bhagat, Manuel Knauer, Marcus R. Makowski, Rickmer Braren, and Robbie Holland. Evaluation and mitigation of the limitations of large language models in clinical decision-making. *Nature Medicine*, 2024.

[106] James Finnie-Ansley, Andrew Luxton-Reilly, Brett A. Becker, James Prather, and Paul Denny. The robots are coming: Exploring the implications of openai codex on introductory programming. 2022.

[107] Qingxiu Dong, Baobao Chang, Ce Zheng, Damai Dai, Heming Xia, Jingjing Xu, Jingyuan Ma, Lei Li, Lei Li, Rui Li, Xu Sun, Zhifang Sui, and Zhiyong Wu. A survey on in-context learning. 2024.

[108] Ilya Jackson, Dmitry Ivanov, and María Jesús Sáenz. From natural language to simulations: applying ai to automate simulation modelling of logistics systems. *International Journal of Production Research*, 2023.

[109] Sébastien Jean, Kyunghyun Cho, Roland Memisevic, and Yoshua Bengio. On using very large target vocabulary for neural machine translation. 2015.

[110] Maciej P. Polak and Dane Morgan. Extracting accurate materials data from research papers with conversational language models and prompt engineering. *Nature Communications*, 2024.

[111] Di Jin, Olga Vechtomova, Rada Mihalcea, Zhijing Jin, and Zhiting Hu. Deep learning for text style transfer: A survey. *Computational Linguistics*, 2021.

[112] Kamran Kowsari, Donald Brown, Kiana Jafari Meimandi, Laura Barnes, Mojtaba Heidarysafa, and Sanjana Mendu. Text classification algorithms: A survey. *Information*, 2019.

[113] Katja Grace, Allan Dafoe, Baobao Zhang, John Salvatier, and Owain Evans. When will ai exceed human performance? evidence from ai experts. *arXiv preprint arXiv:1705.08807*, 2017.

[114] Burr Settles, Geoffrey T. LaFlair, and Masato Hagiwara. Machine learning–driven language assessment. *Transactions of the Association for Computational Linguistics*, 2020.

AI-generated, for reference only.

www.SurveyX.cn

[115] Yihan Cao, Lichao Sun, Philip S. Yu, Siyu Li, Yixin Liu, Yutong Dai, and Zhiling Yan. A comprehensive survey of ai-generated content (aigc): A history of generative ai from gan to chatgpt. *arXiv preprint arXiv:2303.04226*, 2023.

[116] Hoo-Chang Shin, Evelina Bakhturina, Mohammad Shoeybi, Mostofa Patwary, Raghav Mani, Raul Puri, and Yang Zhang. Bio-megatron: Larger biomedical domain language model. 2020.

[117] Ling Wei. Artificial intelligence in language instruction: impact on english learning achievement, l2 motivation, and self-regulated learning. *PubMed*, 2023.

www.SurveyX.cn

AI-generated, for reference only.

Disclaimer:

SurveyX is an AI-powered system designed to automate the generation of surveys. While it aims to produce high-quality, coherent, and comprehensive surveys with accurate citations, the final output is derived from the AI's synthesis of pre-processed materials, which may contain limitations or inaccuracies. As such, the generated content should not be used for academic publication or formal submissions and must be independently reviewed and verified. The developers of SurveyX do not assume responsibility for any errors or consequences arising from the use of the generated surveys.

www.SurveyX.cn

AI-generated, for reference only.