Supplementary material for: Exploiting structure to settle the bilevel benchmark: new optimality proofs, infeasibility certificates and solutions for BOBILib

Brian J. Connolly*
Independent Researcher

This document supplements the paper. It contains the proofs behind the paper's methods, the verification protocol, a map from each result to its machine-checked (Lean) proof, a description of the data package, and the per-instance tables. Notation follows the paper. Theorems, lemmas and equations are numbered by section (Theorem B.3, equation (A.1)); tables are numbered S1, S2, ... The counts quoted in the text are macros generated from the data package (`bobilib/results/`), and so are the tables of Section I. Sections B to F say for each result whether it is formalised in Lean ("Formalised:") or proved in prose only ("Not formalised").

CONTENTS

A Notation and verification protocol . . . 1
B Knapsack interdiction proofs . . . 5
C Multidimensional knapsack interdiction proofs . . . 12
D Clique interdiction proofs . . . 15
E General instances: rays, HPR bound and pipelines . . . 17
F Network interdiction . . . 20
G Formal verification map (Lean) . . . 22
H Data package and formats . . . 24
I Per-instance tables . . . 27

A. NOTATION AND VERIFICATION PROTOCOL

A.1 Notation and conventions

Bilevel problems in BOBILib form. The leader controls $x \in \mathbf{R}^{n_x}$ and the follower controls $y \in \mathbf{R}^{n_y}$. As in BOBILib,[1] the leader minimises:

$$\begin{aligned} \min_{x,y} \quad & c^\top x + d^\top y \\ \text{s.t.} \quad & Ax + By \geq a, \qquad x_i \in \mathbf{Z}\ (i \in I_u), \qquad y \in S(x), \\ S(x) = \ & \arg\min_{y'} \{ f^\top y' : Cx + Dy' \geq b,\ y'_i \in \mathbf{Z}\ (i \in I_l) \}. \end{aligned} \tag{A.1}$$

All data are rational. Variable bounds, equality rows and ranged rows of the instance files are written as pairs of rows of the form "$\geq$"; when an argument depends on the side of a row we say so. For a leader choice x the follower's problem is $P(x) = \min\{f^\top y : Cx + Dy \geq b,\ y_i \in \mathbf{Z}\ (i \in I_l)\}$ and its value is $\varphi(x) \in \mathbf{R} \cup \{-\infty, +\infty\}$ ($+\infty$ when $P(x)$ is infeasible). So $S(x) \neq \emptyset$ exactly when $\varphi(x)$ is finite and attained.

An upper-level row is a *coupling row* if it has a nonzero coefficient on a follower variable. A leader variable is a *linking variable* if its column in C is nonzero; x_L denotes the linking variables and C_L their columns, so $Cx = C_L x_L$, and $P(x)$, $\varphi(x)$ and $S(x)$ depend on x only through x_L.

*E-mail: EMAIL

Definition A.1 (Bilevel feasible point, optimistic convention)**.** A point (x,y) is *bilevel feasible* if $Ax+By \geq a$, $x_i \in \mathbf{Z}$ for $i \in I_u$, and $y \in S(x)$. The bilevel optimum OPT is the infimum of $c^\top x + d^\top y$ over bilevel feasible points ($+\infty$ if there is none).

Problem (A.1) minimises over the pair (x,y), so when $S(x)$ has several elements the follower is assumed to pick the one that is best for the leader. This is the optimistic convention, which BOBILib uses for all of its reported values. For a fixed x the optimistic choice solves the *tie-break problem*

$$\min\bigl\{c^\top x + d^\top y : Ax+By \geq a,\ y \text{ feasible for } P(x),\ f^\top y \leq \varphi(x)\bigr\}.$$

High point relaxation. The *high point relaxation* (HPR) of (A.1) drops the condition $y \in S(x)$ and keeps every row, bound and integrality requirement of both levels and the leader's objective:

$$\text{HPR} = \min\bigl\{c^\top x + d^\top y : Ax+By \geq a,\ Cx+Dy \geq b,\ x_i \in \mathbf{Z}\ (i \in I_u),\ y_i \in \mathbf{Z}\ (i \in I_l)\bigr\}.$$

Packing interdiction. Items are $N = \{1,\dots,n\}$. The leader chooses $x \in \{0,1\}^n$ subject to budget rows $Gx \leq g$ with $G \in \mathbf{Z}^{m_u \times n}_{\geq 0}$ and $g \in \mathbf{Z}^{m_u}_{\geq 0}$. The follower then solves

$$\Phi(x) = \max\bigl\{p^\top y : Wy \leq c,\ y \leq \mathbf{1} - x,\ y \in \{0,1\}^n\bigr\}$$

with profits $p \in \mathbf{Z}^n_{\geq 0}$, weights $W \in \mathbf{Z}^{m \times n}_{\geq 0}$ and capacities $c \in \mathbf{Z}^m_{\geq 0}$, and the leader solves $\text{OPT} = \min\{\Phi(x) : Gx \leq g,\ x \in \{0,1\}^n\}$. In BOBILib form the leader's objective is $p^\top y$ and the follower's is $-p^\top y$, so the game is zero-sum: every $y \in S(x)$ gives the leader the same value $\Phi(x)$, and the optimistic and pessimistic readings coincide. We identify x with the set $X = \{j : x_j = 1\}$ of interdicted items and write $q(Y) = \sum_{j \in Y} q_j$ for a vector q and a set $Y \subseteq N$. With $K(T) = \max\{p(Y) : Y \subseteq T,\ \sum_{j \in Y} W_{\cdot j} \leq c\}$ the best packing of the items in T, we have $\Phi(X) = K(N \setminus X)$.

KIP (the knapsack interdiction problem) is the case $m_u = m = 1$. There we write $\gamma_j = G_{1j}$ for the cost of interdicting item j, $\beta = g_1$ for the leader's budget, $w_j = W_{1j}$ for the follower's weights and $c = c_1$ for its capacity, so $\Phi(X) = \max\{p(Y) : Y \subseteq N \setminus X,\ w(Y) \leq c\}$ and the leader's sets satisfy $\gamma(X) \leq \beta$. MKIP (multidimensional KIP) allows $m_u \geq 1$ and $m \geq 1$. In BOBILib's OR set, variant -100 has one follower row ($m = 1$) and several leader rows; variants -0 and -50 have several follower rows. The *subset-sum class* of KIP is $p = w$; then $\Phi(X)$ is the largest subset sum of $\{w_j : j \notin X\}$ that does not exceed c.

Clique and network interdiction. For edge clique interdiction, $G = (V,E)$ is a simple graph with $n = |V|$ and $m = |E|$; the leader deletes $D \subseteq E$ with $|D| \leq k$, and the follower takes a maximum clique of $G - D = (V, E \setminus D)$, of size $\omega(G-D)$. In the attack-protect network game the leader attacks at most Φ nodes and the follower then protects at most Λ nodes (Section F; there Φ is the attack budget, as in BOBILib's row name, not a value function).

Letters with two meanings. Following the paper, a few letters are reused; the second meaning is local to one section, and the context always says which is meant: c is the leader's cost vector in (A.1) and the follower's capacity in packing interdiction; D is the follower's matrix in (A.1) and the deleted edges in Section D; G is the leader's budget matrix and the graph of Section D; m is the number of follower rows in Section C and the number of edges in Section D; k is an index or a count elsewhere (the depth of a search node in Section B, a row in Section C) and the deletion budget in Section D; w denotes follower weights, the width of a band table (Section B) and node weights (Section F); ω is the value of the online game (Sections B and C) and the clique number (Section D); Φ is the follower's value in packing interdiction and the attack budget in Section F.

A.2 Tolerances of the two checkers

BOBILib's feasibility checker (described in Section 5.2 of the BOBILib paper by Thürauf, Kleinert, Ljubić, Ralphs and Schmidt,[1] and distributed with the library as a script) accepts a solution file in three steps: (i) the HPR is feasible; (ii) the file's point passes the MIPLIB 2017 solution checker[2] (version 1.0.3) on the HPR with tolerance 10^{-4} for the linear rows and 10^{-4} for integrality, and the stated leader objective matches; (iii) the follower's problem with the leader's variables fixed to the file's values is solved to optimality (by Gurobi with feasibility tolerance 10^{-6}), giving φ_{check}, and the file's follower value φ_{sol} must satisfy

$$\frac{|\varphi_{\text{sol}} - \varphi_{\text{check}}|}{10^{-10} + |\varphi_{\text{check}}|} \leq 10^{-4}. \tag{A.2}$$

(The paper prints the denominator without the absolute value; the script uses $|\varphi_{\text{check}}|$. The script also contains an optimistic tie-break test, which its driver does not call.) Our verifier `bobi verify` checks (a) every row, bound and integrality requirement of the HPR at the file's point with absolute tolerance 10^{-6}; (b) the stated leader objective; (c) the follower's problem with the leader fixed, re-solved by an exact knapsack oracle when there is one follower row and by a HiGHS[3] MILP otherwise, against test (A.2), where differences of at most 10^{-9} count as equal. A MILP stopped at a time limit gives a verdict only when its incumbent is strictly better than the file's value by more than (A.2) allows ("not optimal") or its proven bound passes (A.2) ("optimal"); otherwise the verdict is "unproven". The follower problem contains only the follower's rows, as in BOBILib's checker; coupling rows constrain the leader. Our re-certification `bobi certify` (used for the points with coupling rows) adds the optimistic tie-break test, and both of its optimality tests use proven dual bounds and the relative tolerance 10^{-5}.

"Optimal" in this appendix means: a bilevel feasible point in the sense of Definition A.1 (checked within the tolerances above) whose value equals a proven lower bound.

A.3 Verification protocol

Every claim in the paper rests on one or more of the following checks.

1. **Solution files.** Every solution file in the data package is written in BOBILib's format and passes `bobi verify` (Section A.2): all rows, bounds and integrality requirements of the HPR within 10^{-6}; the stated leader objective; and the follower's problem with the leader fixed, re-solved by the exact knapsack oracle (one follower row) or by a HiGHS MILP built from the model (otherwise), accepted by BOBILib's relative test (A.2). This covers the 583 imported KIP files, the 16 subset-sum files, the 690 OR files (270 with one follower knapsack, 420 with several), the 64 general files, the 29 files with coupling rows, the 60 clique files and the 36 network files; all of them passed again when this supplement was assembled. The points with coupling rows also pass `bobi certify` (proven dual bounds, relative 10^{-5}, optimistic tie-break).

2. **Optimality proofs.** Each "optimal" status rests on a lower bound of one of these kinds: a published proof or published lower bound (cited, with the value matched by a verified solution file); the exact subset-sum search (Section B), whose pruning rules are proved in Lean; a theorem with a checkable certificate (Mantel, Brouwer and partitions for clique interdiction, Section D; the HPR bound with an exact model comparison, Section E); or exhaustive enumeration with checked witnesses (Section F). "No bilevel feasible point" rests on Theorem E.1 with an exact rational check (38 instances) or a floating-point check (2 instances).

3. **Independent provers for the subset-sum proofs.** Two Python provers that share no code with the Rust search, one written by the designer and one by a reviewer who read neither, parse the instance files themselves and re-prove all 16 lower bounds with only the direct rule and the per-node rule

(Theorem B.19), in integer arithmetic; both compare themselves with brute force on random small instances. Two other designs of the search, built separately, prove `interKP-200-100-6-3`, and one of them all four instances of class 6 with budget index 3. The reviewer compared every search binary with exhaustive enumeration on 2,990 random small instances (no mismatch).

4. **Tests of the code against its specification.** Unit tests compare the subset-sum search with brute force over every deletion, the threshold tables with the bitset recursion, the node tables with the online game defined directly and with enumeration of every deletion, and the table code with a direct transcription of the Lean recursion thr (also with costs not ascending, as after restricted copies). The network DP is compared with brute force over all follower points on random forests, and the whole enumeration with a brute-force bilevel optimum.

5. **Independent reviews.** The clique, network and coupled-row results were each re-derived by a separate reviewer with its own instance reader and different solvers or code: two exact maximum-clique searches, HiGHS and a branch and bound written in C for the part-size cases of Proposition D.7; a C implementation of the tree DP and a brute force based on Lemma F.1, compared with ours at all 9.3 million attacks; and a second reading of the coupled files with HiGHS's own MPS reader. The reviewers found only wording errors.

6. **Exact arithmetic where it is cheap.** The clique inequalities (Mantel, Brouwer's threshold, the size vectors of Proposition D.7), the recession directions and the comparison of each HPR with its MIPLIB model are checked with integers or exact rationals.

7. **Machine-checked lemmas.** The Lean project (Lean 4,[4] with Mathlib[5]) proves the lemmas listed in Section G. It contains no `sorry`, and `#print axioms` shows only Lean's standard axioms (`propext`, `Classical.choice`, `Quot.sound`) for each main theorem.

A.4 Threats to validity

1. **Trusted solvers.** Several verdicts come from MILP or CP solvers: follower optimality for followers with several rows and for general instances (HiGHS), the 170 infeasibility verdicts behind $w_3(G) > k$ (each reproduced by five methods, two of them solver-free), the follower optimum at the minimising attack in the network proof (HiGHS), and the dual bounds in the OR bracket (Theorem C.4). A solver bug that all methods share would go unnoticed.

2. **Floating point and tolerances.** Points are feasible within 10^{-6} and follower-optimal within BOBILib's relative 10^{-4}, not exactly. 9 coupled points use that slack (marked * in Table S11), and two coupled files are feasible only within it (Section E). The MIPLIB optima behind the five HPR-bound optima are published floating-point values (Section E). Two of the 40 ray certificates are checked only in floating point. The merged-row online bound (Theorem C.5) and the LP bracket are evaluated in double precision, so their rounding steps are in the safe direction only up to floating-point error. The window rule of the subset-sum search uses a floating-point fractional bound; the 16 proofs are independently confirmed by the integer-only provers above, which do not use that rule.

3. **Scope of the Lean proofs.** Lean proves lemmas about abstract models, not the code. That the Rust loops compute the recursions, the range shortcuts and early exits of the table code, the bitset and cache code, and the absence of integer overflow are argued in doc comments and tested, not formalised. That the instance files have the stated parameters (n, m, k, budgets) is checked by scripts, not by Lean. Section G lists what is not formalised.

4. **Results taken from the literature.** Brouwer's theorem[6] was read in the scanned 1981 report and agrees with later restatements,[7,8] but it is neither formalised nor reproved here. Published optima (Weninger and Fukasawa[9] for KIP, Fischetti et al.[10] for imkp, Lozano, Bergman and Cire[11] for OR, MIPLIB 2017 optima[2] for the HPR bounds) and the published lower bounds of the OR instances with several follower knapsacks are used as reported; for them only the points are verified here.

5. **Instance reading.** Every argument depends on reading the MPS and AUX files correctly. Each family's model is checked row by row against its expected pattern, and the key results were re-derived with independent readers (two subset-sum provers, the exact ray and HPR scripts, the reviewers' parsers).

6. **Running times.** All times were measured on a shared machine with four cores that was often oversubscribed; they are indicative only and do not affect any proof.

B. KNAPSACK INTERDICTION PROOFS

This section proves the rules behind the exact search for subset-sum knapsack interdiction (KIP with $p = w$, Section A). The search answers a yes/no question: given an integer ℓ, does every leader set within budget leave the follower at least ℓ? A "yes" proves OPT $\geq \ell$; a "no" comes with a leader set whose follower value is below ℓ. Repeating with ℓ equal to the incumbent value proves optimality (Corollary B.25).

B.1 Monotonicity and the count formulation

Lemma B.1 (Monotonicity of interdiction)**.** *Let $\mathscr{F}$ be any family of subsets of N (the follower's feasible sets) and $\Phi_{\mathscr{F}}(X) = \max\{p(Y) : Y \in \mathscr{F},\ Y \cap X = \emptyset\}$ with $p \geq 0$ (a maximum over no set is 0). If $X \subseteq X'$ then $\Phi_{\mathscr{F}}(X') \leq \Phi_{\mathscr{F}}(X)$. If $\mathscr{F}$ is closed under taking subsets, then $\Phi_{\mathscr{F}}(X) = \max\{p(Y \setminus X) : Y \in \mathscr{F}\}$. The knapsack follower $\mathscr{F} = \{Y : \sum_{j \in Y} W_{\cdot j} \leq c\}$ is closed under taking subsets because $W \geq 0$; in particular $\Phi(X') \leq \Phi(X)$ for $X \subseteq X'$.*

Proof. Every $Y \in \mathscr{F}$ that avoids X' also avoids X, so the maximum for X' is over a subfamily. For the second claim, a set $Y \in \mathscr{F}$ avoiding X has $p(Y) = p(Y \setminus X)$, which gives "$\leq$"; conversely, for $Y \in \mathscr{F}$ the set $Y \setminus X$ lies in $\mathscr{F}$ and avoids X, which gives "$\geq$". A subset of a packing has no larger weight in any row because $W \geq 0$. □

Formalised: `Bobi/Knapsack.lean`, theorems `follower_antitone`, `bestAvoiding_antitone`, `bestAvoiding_eq_sup_sdiff`, `packings_downward_closed` and `K_eq_bestAvoiding`.

Lemma B.2 (Cheapest copies first)**.** *Consider KIP and a class $Q \subseteq N$ of identical items ($p_i = p_j$ and $w_i = w_j$ for $i, j \in Q$). For every leader set X there is a leader set X' with $X' \setminus Q = X \setminus Q$, $|X' \cap Q| = |X \cap Q|$, $\gamma_a \leq \gamma_b$ for all $a \in X' \cap Q$ and $b \in Q \setminus X'$, $\gamma(X') \leq \gamma(X)$ and $\Phi(X') = \Phi(X)$.*

Proof. First a single swap: if $i \in X \cap Q$, $j \in Q \setminus X$ and $\gamma_j \leq \gamma_i$, let $X^s = (X \setminus \{i\}) \cup \{j\}$. The transposition of i and j preserves p and w and maps $N \setminus X$ onto $N \setminus X^s$, so it maps the packings avoiding X bijectively onto those avoiding X^s with the same profits; hence $\Phi(X^s) = \Phi(X)$, and $\gamma(X^s) = \gamma(X) - \gamma_i + \gamma_j \leq \gamma(X)$. Now induct on the integer $\gamma(X)$. If some $i \in X \cap Q$ and $j \in Q \setminus X$ have $\gamma_j < \gamma_i$, the swap lowers the cost strictly, keeps $X \setminus Q$, $|X \cap Q|$ and Φ, and the induction hypothesis applies to X^s. Otherwise $X' = X$ works. □

Formalised: `Bobi/Knapsack.lean`, theorems `K_map_equiv`, `swap_block` and `cheapest_first`.

Definition B.3 (Class instance)**.** A *class instance* is a list of classes $1, \ldots, L$; class i has a value $v_i \in \mathbf{Z}_{\geq 1}$ and n_i copies with deletion costs $\gamma_{i,1}, \ldots, \gamma_{i,n_i} \in \mathbf{Z}_{\geq 0}$ (in a fixed order, not necessarily ascending). Let $P_i(r) = \sum_{h \leq r} \gamma_{i,h}$ for $0 \leq r \leq n_i$. A *deletion* is a count vector $r = (r_1, \ldots, r_L)$ with $0 \leq r_i \leq n_i$; its cost is $P(r) = \sum_i P_i(r_i)$

and its survivors form the multiset $R(r)$ with $n_i - r_i$ copies of v_i for each i. For a finite multiset M of nonnegative integers, $\mathrm{SS}(M)$ is the set of sums of its sub-multisets ($0 \in \mathrm{SS}(M)$). Given integers $0 \le lo \le hi$ and a budget $\beta \ge 0$, the instance is *safe* if every deletion with $P(r) \le \beta$ has $\mathrm{SS}(R(r)) \cap [lo, hi] \ne \emptyset$; a deletion within budget with $\mathrm{SS}(R(r)) \cap [lo, hi] = \emptyset$ is *blocking*.

Proposition B.4 (Reduction of subset-sum KIP)**.** *Consider subset-sum KIP with data γ, β, w, c (all nonnegative integers). Let $F = \{j : \gamma_j = 0\}$, $\mathscr{L} = \{j \notin F : 1 \le w_j \le c\}$ and $g = \gcd\{w_j : j \in \mathscr{L}\}$ ($g = 1$ if $\mathscr{L} = \emptyset$). Group $\mathscr{L}$ into classes by the value w_j/g, with each class's costs sorted ascending, and let $hi = \lfloor c/g \rfloor$. For a deletion r let $X(r)$ be F together with the r_i cheapest items of each class. Then*

1. *$\gamma(X(r)) = P(r)$ and $\Phi(X(r)) = g \cdot \max\big(\mathrm{SS}(R(r)) \cap [0, hi]\big)$;*
2. *for every leader set X with $\gamma(X) \le \beta$ there is a deletion r with $P(r) \le \gamma(X)$ and $\Phi(X(r)) \le \Phi(X)$;*
3. *for every integer $\ell \ge 0$ with $lo = \lceil \ell/g \rceil \le hi$: $\mathrm{OPT} \ge \ell$ if and only if the class instance is safe for the band $[lo, hi]$ and budget β; and r is blocking if and only if $P(r) \le \beta$ and $\Phi(X(r)) < \ell$.*

Proof. (1) Items of F cost nothing. A packing avoiding $X(r)$ contains no item of F; an item outside $F \cup \mathscr{L}$ has $w_j = 0$ (then $p_j = 0$) or $w_j > c$ (then it is in no packing), so dropping such items changes neither weight nor profit. Every weight in $\mathscr{L}$ is g times its class value, so a set $Y \subseteq \mathscr{L}$ has $w(Y) \le c$ iff its value sum is at most $\lfloor c/g \rfloor = hi$, and the value sums of packings of $\mathscr{L} \setminus X(r)$ are exactly $\mathrm{SS}(R(r))$. (2) Let $X_1 = X \cup F$: $\gamma(X_1) = \gamma(X)$ and $\Phi(X_1) \le \Phi(X)$ by Lemma B.1. Items outside $F \cup \mathscr{L}$ do not affect Φ (as in (1)) and blocking them costs something, so remove them from X_1 (cost does not increase, Φ unchanged). Apply Lemma B.2 to each class in turn. The result blocks in each class i some r_i copies, each no costlier than every unblocked copy, so its cost in class i is the sum of the r_i smallest costs, $P_i(r_i)$, and its follower value is that of $X(r)$. (3) Since $gs \ge \ell$ iff $s \ge lo$ for integers s, (1) gives: $\Phi(X(r)) \ge \ell$ iff $\mathrm{SS}(R(r)) \cap [lo, hi] \ne \emptyset$. If the instance is safe, (2) gives $\Phi(X) \ge \Phi(X(r)) \ge \ell$ for every X within budget. If a deletion r is blocking, $X(r)$ is within budget with $\Phi(X(r)) < \ell$, so $\mathrm{OPT} < \ell$. □

Not formalised as a whole; its two ingredients are Lemmas B.1 and B.2.

If $\lceil \ell/g \rceil > hi$, the question is trivial: the leader set $F = X(0)$ costs nothing and, by part (1), $\Phi(F) \le g \cdot hi < \ell$, so $\mathrm{OPT} < \ell$ and the deletion $r = 0$ is a witness. From now on we work with a class instance, a band $[lo, hi]$ with $lo \le hi$ and a budget β. All results below hold for arbitrary nonnegative costs in the count formulation; where ascending costs are needed (deletions of arbitrary copies) we say so.

B.2 Windows of reachable sums and the stall test

Lemma B.5 (Window extension)**.** *Let M be a multiset with $[a, b] \subseteq \mathrm{SS}(M)$, $a \le b$. If a value v satisfies $v \le b - a + 1$ then $[a, b + v] \subseteq \mathrm{SS}(M \uplus \{v\})$. More generally, if values $v_1, \ldots, v_q$ satisfy $v_h \le (b - a + 1) + v_1 + \cdots + v_{h-1}$ for every h, then $[a,\, b + \sum_h v_h] \subseteq \mathrm{SS}(M \uplus \{v_1, \ldots, v_q\})$.*

Proof. A target $t \in [a, b]$ is a sum of M. A target $t \in (b, b + v]$ has $a \le t - v \le b$, because $t > b$ and $v \le b - a + 1$; so t is v plus a sum of M. The general statement follows by induction on q: after adding $v_1, \ldots, v_{h-1}$ the window is $[a, b + v_1 + \cdots + v_{h-1}]$, of width $(b - a + 1) + v_1 + \cdots + v_{h-1} \ge v_h$. □

Formalised: `Bobi/SubsetSum.lean`, theorems `window_extend` and `window_extend_all`.

Lemma B.6 (Survivors that fit)**.** *Let $[a, b] \subseteq \mathrm{SS}(M)$ with $a \le b$ and $\theta = b - a + 1$. Let $(v_1, \eta_1), \ldots, (v_q, \eta_q)$ be a list of copies with values v_h and flags $\eta_h \in \{kept, deleted\}$. Write $\mu_h = \sum_{h' < h} v_{h'}$ for the mass before copy h and δ_h for the deleted mass before copy h. If $\delta_h + v_h \le \theta + \mu_h$ for every h, then $[a,\, b + \sigma] \subseteq \mathrm{SS}(M \uplus K)$, where K is the multiset of kept copies and σ its total.*

Proof. Let h be a kept copy. The kept mass before it is $\mu_h - \delta_h$, and the hypothesis says $v_h \le \theta + (\mu_h - \delta_h)$. So the kept copies, in list order, satisfy the hypothesis of Lemma B.5. □

Formalised: `Bobi/SubsetSum.lean`, theorems `fits_survivors` and `window_survivors` (`SubsetSum.perm`: subset sums do not depend on the order).

Lemma B.7 (Fractional deletion bound)**.** *Let copies h have values $v_h > 0$ and costs $\gamma_h \ge 0$, sorted so that $\gamma_1/v_1 \le \gamma_2/v_2 \le \cdots$. For $d > 0$ let $\Psi(d) = \min\{\sum_h \gamma_h z_h : \sum_h v_h z_h \ge d,\ 0 \le z \le 1\}$ ($+\infty$ if $\sum_h v_h < d$). The greedy solution, which fills copies in this order until mass d is reached, is optimal, and every set H of copies with $\sum_{h\in H} v_h \ge d$ has $\sum_{h\in H} \gamma_h \ge \Psi(d)$.*

Proof. The indicator vector of H is feasible, which proves the last claim. Let $m_h = v_h z_h$ and $\rho_h = \gamma_h/v_h$, so the cost is $\sum_h \rho_h m_h$ with $0 \le m_h \le v_h$ and $\sum_h m_h \ge d$. Let m^* be the greedy allocation, λ the ratio of the copy where it stops, and m any feasible allocation. Then $\sum_h \rho_h(m_h - m_h^*) = \sum_h(\rho_h - \lambda)(m_h - m_h^*) + \lambda \sum_h(m_h - m_h^*)$. Each term of the first sum is nonnegative ($m_h^* = v_h \ge m_h$ when $\rho_h < \lambda$, $m_h^* = 0 \le m_h$ when $\rho_h > \lambda$), and the last term is nonnegative because $\sum_h m_h^* = d \le \sum_h m_h$ and $\lambda \ge 0$. □

Not formalised (a standard linear programming fact).

The next rule is stated for a search node (Section B.8): the decided classes have left a multiset M of survivors, $S = \mathrm{SS}(M) \cap [0, hi]$, and the remaining (undecided) classes may be deleted with residual budget β'. A *completion* is a count vector for the undecided classes of cost at most β'.

Proposition B.8 (Window rule with stall test)**.** *Order the undecided classes by ascending value, $u_1, \ldots, u_q$ (the proof works for any order; ascending value is the code's choice), and let $M_i = \sum_{i'<i} n_{u_{i'}} v_{u_{i'}}$ be the mass of the classes before u_i. Let Δ be the largest mass that a completion deletes and σ_0 the total undecided mass minus Δ. Let $[a,b] \subseteq S$ be a run of consecutive integers with $b < lo \le b + \sigma_0$ and width $\theta = b - a + 1$, and put $D_i = M_i - v_{u_i} + \theta + 1$. Suppose that for every i: $D_i > 0$, and either $i = 1$ or the fractional bound of Lemma B.7 over the copies of $u_1, \ldots, u_{i-1}$ satisfies $\Psi_i(D_i) > \beta'$. Then every completion leaves survivors R with $lo \in \mathrm{SS}(M \uplus R)$; the node is safe.*

Proof. Fix a completion and list the undecided copies class by class in the order $u_1, \ldots, u_q$, flagging the deleted ones. Let e_i be the mass the completion deletes from $u_1, \ldots, u_{i-1}$. Those deleted copies form a set of total cost at most β', so $e_i \ge D_i$ would contradict $\Psi_i(D_i) > \beta'$ by Lemma B.7; for $i = 1$, $e_1 = 0 < D_1$. Hence $e_i \le D_i - 1$. At the copy number t ($t = 0, 1, \ldots$) of class u_i, the mass before it is $M_i + t v_{u_i}$ and the deleted mass before it is at most $e_i + t v_{u_i}$, so deleted mass plus v_{u_i} is at most $D_i - 1 + (t+1)v_{u_i} = \theta + M_i + t v_{u_i}$. Lemma B.6 gives $[a, b+\sigma] \subseteq \mathrm{SS}(M \uplus R)$ with $\sigma \ge \sigma_0$ the surviving mass, and $a \le b < lo \le b + \sigma_0$ puts lo in that window. □

The per-copy hypothesis is formalised (`Bobi/SubsetSum.lean`, theorem `window_survivors`); the reduction to one test per class and the use of Lemma B.7 are argued here and in the doc comment of the code, not formalised. Δ is computed exactly by a bounded-knapsack recursion over the undecided classes.

B.3 The online relaxation

The online relaxation of Weninger and Fukasawa[9,12] (Theorem 2 in Section 3 of their preprint) applies to general KIP. Fix a list $o = (j_1, \ldots, j_L)$ of distinct items, any subset of N in any order. The *online game* on o has $2L$ rounds: at item j_h the leader first decides whether to block it (allowed if its cost fits the remaining budget); if the leader does not block it, the follower decides whether to take it (allowed if its weight fits the remaining capacity). The follower collects the profits of the items it takes. Both players see all earlier

moves. The value of this finite game of perfect information is given by backward induction: $\omega(\emptyset, \beta', \kappa) = 0$ and, for $o = (j, o')$,

$$\omega(o, \beta', \kappa) = \begin{cases} \min\{\omega(o', \beta' - \gamma_j, \kappa),\ T\} & \text{if } \gamma_j \le \beta', \\ T & \text{otherwise,} \end{cases}$$

$$T = \begin{cases} \max\{\omega(o', \beta', \kappa),\ \omega(o', \beta', \kappa - w_j) + p_j\} & \text{if } w_j \le \kappa, \\ \omega(o', \beta', \kappa) & \text{otherwise.} \end{cases}$$

Theorem B.9 (Online lower bound, any play order)**.** *For every list o of distinct items and every $X \subseteq N$ with $\gamma(X) \le \beta$, $\omega(o, \beta, c) \le K(o \setminus X) \le \Phi(X)$, where $K(T)$ is the best packing of the items of T with capacity c. Hence $\omega(o, \beta, c) \le \mathrm{OPT}$.*

Proof. In the online game the leader may adapt to the follower's earlier moves; the real game corresponds to the leader strategy "block exactly the items of X", which does not adapt. Formally, we prove by induction on the length of o, for all $\beta', \kappa \ge 0$ and all $X \subseteq o$ with $\gamma(X) \le \beta'$, that $\omega(o, \beta', \kappa) \le K_\kappa(o \setminus X)$ (best packing with capacity κ). For $o = \emptyset$ both sides are 0. Let $o = (j, o')$. If $j \in X$, then $\gamma_j \le \gamma(X) \le \beta'$, so the blocking branch is offered and $\omega(o, \beta', \kappa) \le \omega(o', \beta' - \gamma_j, \kappa) \le K_\kappa(o' \setminus X) = K_\kappa(o \setminus X)$ by induction applied to $X \setminus \{j\}$. If $j \notin X$, then $X \subseteq o'$ and $\omega(o, \beta', \kappa) \le T$. By induction $\omega(o', \beta', \kappa) \le K_\kappa(o' \setminus X)$ and, if $w_j \le \kappa$, $\omega(o', \beta', \kappa - w_j) + p_j \le K_{\kappa - w_j}(o' \setminus X) + p_j \le K_\kappa((o' \setminus X) \cup \{j\})$ (add j to an optimal packing). So in both cases of T we get $T \le K_\kappa((o' \setminus X) \cup \{j\}) = K_\kappa(o \setminus X)$. For an arbitrary X within budget apply this to $X \cap o$ (its cost is no larger and $o \setminus (X \cap o) = o \setminus X$). Finally $K(o \setminus X) \le K(N \setminus X) = \Phi(X)$ because more items can only help. □

Formalised: `Bobi/Online.lean`, theorems `online_le_K`, `online_le_K_any` and `online_lower_bound`.

Remark B.10. The bound need not be tight. In Weninger and Fukasawa's Table 1 (profits $(1,1,2)$, leader costs $(1,1,2)$, follower weights $(1,1,3)$, $\beta = 2$, $c = 3$) the online game in the play order $(1,2,3)$ is worth 1 and the bilevel optimum is 2 (Lean: `table1_online`, `table1_opt`, `table1_block`, checked by evaluation).

B.4 Robust tables with an end set

For subset-sum instances the same idea is applied class by class, in the count formulation. Let $Q = (q_1, \dots, q_L)$ be a list of classes (the *play order*) and $A \subseteq \mathbf{Z}_{\ge 0}$ an *end set*. The game $\Gamma_A(Q, \beta', t)$ starts with residual t and budget β'; at class q the leader announces $r \le n_q$ with $P_q(r)$ at most the remaining budget, then the follower takes $j \le n_q - r$ copies with jv_q at most the current residual, which decreases by jv_q; the follower wins if the final residual lies in A.

Definition B.11 (Robust tables)**.** $G_A(\emptyset, \beta') = A$ and, for $Q = (q, Q')$,

$$t \in G_A(Q, \beta') \iff \forall r \le n_q \text{ with } P_q(r) \le \beta'\ \ \exists j \le n_q - r :\ jv_q \le t \text{ and } t - jv_q \in G_A(Q', \beta' - P_q(r)).$$

So $G_A(Q, \beta')$ is the set of residuals from which the follower wins $\Gamma_A(Q, \beta', \cdot)$. The robust table is $H = G_{\{0\}}$ and the band table of width $w \ge 1$ is $G_w = G_{[0, w-1]}$.

Theorem B.12 (Soundness of the tables)**.** *If $t \in G_A(Q, \beta')$ and r is a deletion of the classes of Q with $P(r) \le \beta'$, then there are $s \in \mathrm{SS}(R(r))$ and $a \in A$ with $s + a = t$. In particular $t \in H(Q, \beta')$ gives $t \in \mathrm{SS}(R(r))$, and $t \in G_w(Q, \beta')$ gives some $s \in \mathrm{SS}(R(r))$ with $s \le t < s + w$. If each class's costs are ascending, the same holds for a deletion of arbitrary copies of total cost at most β'.*

Proof. Induction on L. For $L = 0$ take $s = 0$, $a = t$. For $Q = (q, Q')$: $P_q(r_1) \le P(r) \le \beta'$, so the definition gives $j \le n_q - r_1$ with $t - jv_q \in G_A(Q', \beta' - P_q(r_1))$, and the rest of r costs at most $\beta' - P_q(r_1)$. By induction $t - jv_q = s' + a$ with s' a subset sum of the survivors of Q'; then $s = jv_q + s'$ uses j of the $n_q - r_1$ survivors of q. For deletions of arbitrary copies with ascending costs, deleting r_i copies of class i costs at least $P_i(r_i)$, and the survivors are again $n_i - r_i$ copies of v_i. □

Formalised: `Bobi/EndTable.lean`, theorems `GA_sound`, `GA_sound_any`, `G_iff_GA`, `H_iff_GA`, `G_sound_of_GA`, `H_sound_of_GA`; `Bobi/RobustTable.lean`, `H_sound`, `H_sound_any`, `take_sum_le`, `counts_of_deletion`; `Bobi/BandTable.lean`, `G_sound`, `G_sound_any`, `G_one`, `G_sound_one`.

Proposition B.13 (Any play order)**.** *Let Q be the undecided classes in the search order and $\pi(Q)$ any permutation of them. If $t \in G_A(\pi(Q), \beta')$, the conclusion of Theorem B.12 holds for every deletion r of Q with $P(r) \le \beta'$.*

Proof. Permuting the pairs (class, count) permutes the survivors and leaves the cost unchanged, and subset sums depend only on the multiset. Apply Theorem B.12 to the permuted deletion. □

Formalised: `Bobi/EndTable.lean`, theorems `counts_perm`, `remaining_eq_flatten`, `totalCost_eq_sum`, `remaining_perm`, `totalCost_perm`, `GA_sound_perm` and `GA_sound_perm_any`.

Corollary B.14 (Root-table rules)**.** *Let M be the decided survivors and Q the undecided classes (any play order). (i) If $s \in \mathrm{SS}(M)$ and $t \in H(Q, \beta')$, every completion leaves $s + t \in \mathrm{SS}(M \uplus R)$. (ii) If $[a, b] \subseteq \mathrm{SS}(M)$, $t \in G_w(Q, \beta')$, $a + t \le \tau$ and $\tau + w \le b + t + 1$, every completion leaves $\tau \in \mathrm{SS}(M \uplus R)$. The search prunes when $s + t$, respectively τ, lies in $[lo, hi]$.*

Proof. (i) Theorem B.12 gives $t \in \mathrm{SS}(R)$. (ii) It gives $s' \in \mathrm{SS}(R)$ with $s' \le t < s' + w$; then $a \le \tau - t \le \tau - s'$ and $\tau - s' \le \tau - t + w - 1 \le b$, so $\tau - s' \in \mathrm{SS}(M)$. □

Formalised: `Bobi/RobustTable.lean`, theorem `covers_sound`; `Bobi/BandTable.lean`, `band_covers_sound`, `covers_sound_of_band`; `Bobi/Threshold.lean`, `covers_threshold_sound`, `covers_threshold_sound_perm`, `band_covers_threshold_sound`, `band_covers_threshold_sound_perm` (the same on stored thresholds).

Lemma B.15 (Antitone in the budget)**.** *If $\beta'' \le \beta'$ then $G_A(Q, \beta') \subseteq G_A(Q, \beta'')$. If $A \subseteq A'$ then $G_A(Q, \beta') \subseteq G_{A'}(Q, \beta')$.*

Proof. Induction on L; the base case does not depend on the budget. A deletion r with $P_q(r) \le \beta''$ also has $P_q(r) \le \beta'$; the answer j for budget β' leads to $G_A(Q', \beta' - P_q(r)) \subseteq G_A(Q', \beta'' - P_q(r))$ by induction. The second claim is the same induction with a larger base set. □

Formalised: `Bobi/EndTable.lean`, theorems `GA_antitone`, `G_antitone`, `H_antitone` and `GA_mono`.

B.5 Threshold form

By Lemma B.15, for each residual t the budgets at which $t \in G_A(Q, \cdot)$ form an initial segment, so one number per t describes the table. Fix a cap $\mathrm{cap} \ge 0$ (the root budget β).

Definition B.16 (Threshold)**.** $\mathrm{thr}(\emptyset, t) = \mathrm{cap}$ if $t \in A$ and -1 otherwise; for $Q = (q, Q')$ with value v and n copies,

$$\mathrm{thr}(Q, t) = \min\Big(\mathrm{cap},\ \min_{\substack{r \le n \\ P_q(r) \le \mathrm{cap}}} \Big[P_q(r) + \max\Big(-1,\ \max_{\substack{j \le n - r \\ jv \le t}} \mathrm{thr}(Q', t - jv)\Big)\Big]\Big).$$

Theorem B.17 (Threshold form)**.** *For every integer $B \geq 0$: $B \leq \mathrm{thr}(Q,t)$ if and only if $B \leq \mathrm{cap}$ and $t \in G_A(Q,B)$. Consequently $-1 \leq \mathrm{thr}(Q,t) \leq \mathrm{cap}$; $\mathrm{thr}(Q,t) = -1$ iff $t \notin G_A(Q,0)$; and otherwise $\mathrm{thr}(Q,t)$ is the largest $B \leq \mathrm{cap}$ with $t \in G_A(Q,B)$.*

Proof. Induction on L. For $L = 0$: if $t \in A$ the claim reads $B \leq \mathrm{cap}$; if $t \notin A$ both sides are false since $B \geq 0 > -1$. For $Q = (q, Q')$ write $m_r(t)$ for the inner maximum (at least -1). Then $B \leq \mathrm{thr}(Q,t)$ iff $B \leq \mathrm{cap}$ and $B \leq P_q(r) + m_r(t)$ for all r with $P_q(r) \leq \mathrm{cap}$. Assume $B \leq \mathrm{cap}$. For r with $P_q(r) > B$ the inequality holds automatically, as $B \leq P_q(r) - 1$. For r with $P_q(r) \leq B$ (these have $P_q(r) \leq \mathrm{cap}$): $B \leq P_q(r) + m_r(t)$ iff $0 \leq B - P_q(r) \leq m_r(t)$ iff some $j \leq n - r$ with $jv \leq t$ has $B - P_q(r) \leq \mathrm{thr}(Q', t - jv)$ iff, by induction (note $B - P_q(r) \leq \mathrm{cap}$), $t - jv \in G_A(Q', B - P_q(r))$. This is the definition of $t \in G_A(Q,B)$. The consequences follow by taking $B = 0$ and $B = \mathrm{thr}(Q,t)$. □

Formalised: `Bobi/Threshold.lean`, theorems `thr_iff`, `GA_iff_thr`, `thr_bounds`, `thr_eq_neg_one_iff`, `thr_greatest`, `G_iff_thr` and `H_iff_thr` (definition `thr`).

Remark B.18 (What the code computes). The recursion at residual t reads only residuals $\leq t$, so arrays indexed $0, \ldots, hi$ hold the exact thresholds of those residuals. With nonnegative costs P_q is nondecreasing, so stopping at the first r with $P_q(r) > \mathrm{cap}$ implements the filter. That the code's loops compute thr (including the shortcuts that compute only residuals in a range that can matter, and an early exit once every computed threshold is below the budget) is argued in the code's doc comments and tested against a direct transcription of Definition B.16 and against brute force; it is not formalised.

B.6 The per-node rule

At a search node the decided survivors M reach the sums $S = \mathrm{SS}(M) \cap [0, hi]$. The follower wins with any total in $[lo, hi]$, so it need not fix its target in advance. The node's end set is

$$A_{\mathrm{node}} = \{a \in [0, hi] : \exists s \in S,\ s \leq a \leq s + (hi - lo)\},$$

that is, $(S + [0, hi - lo]) \cap [0, hi]$, and the node table asks whether $hi \in G_{A_{\mathrm{node}}}(Q, \beta')$.

Theorem B.19 (Per-node rule)**.** *Let $S \subseteq \mathrm{SS}(M)$, $lo \leq hi$, A any set whose elements a each have some $s \in S$ with $s \leq a \leq s + (hi - lo)$, and $\pi(Q)$ any permutation of the undecided classes Q. If $hi \in G_A(\pi(Q), \beta')$, then every completion (a deletion r of Q with $P(r) \leq \beta'$, costs in any order) leaves some $u \in \mathrm{SS}(M \uplus R(r))$ with $lo \leq u \leq hi$. In threshold form: if $\beta' \leq \mathrm{cap}$ and $\beta' \leq \mathrm{thr}(\pi(Q), hi)$ computed with end set A_{node}, the node is safe at every budget up to $\mathrm{thr}(\pi(Q), hi)$.*

Proof. Proposition B.13 gives $x \in \mathrm{SS}(R(r))$ and $a \in A$ with $x + a = hi$. Pick $s \in S$ with $s \leq a \leq s + (hi - lo)$. Then $u = s + x$ is a subset sum of $M \uplus R(r)$ and $u = s + hi - a \in [hi - (hi - lo), hi] = [lo, hi]$. The threshold form follows from Theorem B.17 with $B = \beta'$ (and for smaller budgets, since $B \leq \mathrm{thr}$ is the same condition). The hypothesis $lo \leq hi$ is needed: with $lo > hi$ there is no target, and the code returns -1. □

Formalised: `Bobi/EndTable.lean`, theorems `node_rule`, `node_table_sound`, `node_table_sound_perm` and `node_table_sound_any` (definition `nodeEnd`); `Bobi/Threshold.lean`, `node_table_threshold_sound` and `node_table_threshold_sound_counts` (the form the search uses: count formulation, any play order, any cost order).

Remark B.20 (Strength). The per-node rule contains the rule of H in the same play order: if $s \in S$, $s \leq \tau$, $\tau \in [lo, hi]$ and $\tau - s \in H(Q, \beta')$, then $hi \in G_{A_{\mathrm{node}}}(Q, \beta')$ (shift the follower's strategy up by $hi - \tau + s$). Formalised: `Bobi/EndTable.lean`, theorem `node_table_of_H`. The analogous containment of the band rules is argued in the code's doc comment, not formalised; soundness does not need either. The play order matters only for strength; the search plays the classes in ascending order of deletion cost per unit of mass.

B.7 Restricted copies

Proposition B.21 (Restricted follower)**.** *For $k \geq 1$ let $I^{(k)}$ be the class instance in which every class i with $n_i > k$ is replaced by a class with the same value, k copies and costs $(\gamma_{i,1} + \cdots + \gamma_{i,n_i-k+1},\ \gamma_{i,n_i-k+2}, \ldots, \gamma_{i,n_i})$. If $I^{(k)}$ is safe (same band and budget), then so is the original instance.*

Proof. Map a deletion r of the original to r' with $r'_i = \max(0, r_i - (n_i - k))$ for the restricted classes and $r'_i = r_i$ otherwise. If $r'_i = 0$ its cost is $0 \leq P_i(r_i)$; otherwise it is $\gamma_{i,1} + \cdots + \gamma_{i,n_i-k+r'_i} = P_i(r_i)$. So $P'(r') \leq P(r)$. The restricted survivors number $k - r'_i = \min(k, n_i - r_i) \leq n_i - r_i$, so $R'(r') \subseteq R(r)$ as multisets and $\mathrm{SS}(R'(r')) \subseteq \mathrm{SS}(R(r))$. Safety of $I^{(k)}$ applied to r' gives a sum in $[lo, hi]$ for r. □

Not formalised. The restricted costs are not ascending, which is why the count-formulation results above make no assumption on the order of costs. (The option is off by default; no run recorded in the repository uses it.)

B.8 Why the search is exact

The search fixes an order of the classes (any order). A node at depth k has decided counts $r_1, \ldots, r_k$ with residual budget $\beta' = \beta - \sum_{i \leq k} P_i(r_i) \geq 0$, decided survivors M_k and $S_k = \mathrm{SS}(M_k) \cap [0, hi]$. The node is *safe* if every completion $(r_{k+1}, \ldots, r_L)$ with $\sum_{i>k} P_i(r_i) \leq \beta'$ has $\mathrm{SS}(M_k \uplus R_{>k}) \cap [lo, hi] \neq \emptyset$. The root ($k = 0$, $S_0 = \{0\}$) is safe iff the class instance is safe.

Lemma B.22 (Node state)**.** *Whether a node is safe depends only on (k, S_k, β'), and a node safe at β' is safe at every $\beta'' \leq \beta'$.*

Proof. $\mathrm{SS}(M \uplus R) = \mathrm{SS}(M) + \mathrm{SS}(R)$, and all values are nonnegative, so a sum in $[lo, hi]$ has its $\mathrm{SS}(M)$ part in $[0, hi]$. Hence the condition reads $(S_k + \mathrm{SS}(R_{>k})) \cap [lo, hi] \neq \emptyset$, and the completions depend only on k and β', with fewer completions for smaller budgets. □

Theorem B.23 (Sound pruning)**.** *Each of the following implies that the node (k, S_k, β') is safe.*

1. *Direct: $S_k \cap [lo, hi] \neq \emptyset$.*
2. *Guaranteed copies: with $d_i = \max\{r \leq n_i : P_i(r) \leq \beta'\}$, the multiset U with $n_i - d_i$ copies of v_i for each undecided i has $(S_k + \mathrm{SS}(U)) \cap [lo, hi] \neq \emptyset$.*
3. *Window: the hypothesis of Proposition B.8 holds for a run of S_k.*
4. *Root tables: Corollary B.14 gives a target in $[lo, hi]$, for a table built once at the root (any play order).*
5. *Node table: $\beta' \leq \mathrm{thr}(\pi(Q), hi)$ with end set A_{node} (Theorem B.19).*
6. *Cache: an entry $(k, S_k) \mapsto \beta^*$ with $\beta' \leq \beta^*$, where an entry is stored only after (k, S_k) was shown safe at β^* by one of the rules or by exhausting its children; rule 5 stores $\beta^* = \mathrm{thr}(\pi(Q), hi)$.*

Proof. (1) The decided survivors are present in every completion. (2) Costs are nonnegative, so a completion within β' has $P_i(r_i) \leq \beta'$ and, P_i being nondecreasing, $r_i \leq d_i$; at least $n_i - d_i$ copies of v_i survive, and a subset sum of a sub-multiset is a subset sum of the multiset. (3)–(5) are Proposition B.8, Corollary B.14 and Theorem B.19. (6) is Lemma B.22 together with Theorem B.19, which holds at every budget up to the stored threshold. □

Not formalised as a whole: rules (3)–(5) are the results cited in the proof (rule (3) only in part, see Proposition B.8), and rules (1), (2) and (6) and Lemma B.22 are argued here.

Theorem B.24 (Exactness)**.** *The search visits the root; at a node it returns "safe" if a rule of Theorem B.23 applies or if all children $r_{k+1} \in \{r \le n_{k+1} : P_{k+1}(r) \le \beta'\}$ return "safe"; at a leaf ($k = L$) to which no rule applies it returns "blocking" with the counts on the path. If the search ends without reaching its node limit, then "safe" at the root means the class instance is safe, and "blocking" returns a blocking deletion.*

Proof. By induction from the leaves, every node that returns "safe" is safe: for the rules this is Theorem B.23; for a node whose children are all safe, every completion within β' starts with some r_{k+1} with $P_{k+1}(r_{k+1}) \le \beta'$ (costs are nonnegative), and the rest of it is a completion of that child within $\beta' - P_{k+1}(r_{k+1})$. A leaf returning "blocking" has $S_L \cap [lo, hi] = \emptyset$ (rule 1 did not apply), and $M_L = R(r)$ for the path's deletion r, whose cost is $\beta - \beta' \le \beta$; so r is blocking. A node returns "blocking" only when a child does. □

Not formalised (the search code; see Section G). The rules it relies on are formalised as listed above, except the fractional bound of Lemma B.7.

Corollary B.25 (Exact solve)**.** *Start from any leader set X_0 within budget with $u_0 = \Phi(X_0)$ (the code uses Weninger and Fukasawa's greedy leader). For $h = 0, 1, \ldots$ run the search with $\ell = u_h$: if it returns "safe", $\mathrm{OPT} = u_h$; if it returns a blocking deletion r, set $X_{h+1} = X(r)$ and $u_{h+1} = \Phi(X(r)) < u_h$. If no search hits its node limit, this ends after at most $u_0 + 1$ searches with a proof of optimality and an optimal leader set.*

Proof. By Proposition B.4(3) and Theorem B.24, "safe" proves $\mathrm{OPT} \ge u_h = \Phi(X_h) \ge \mathrm{OPT}$, and "blocking" yields $X(r)$ within budget with $\Phi(X(r)) < u_h$. (If $\lceil u_h/g \rceil > hi$, no search is needed: $r = 0$ is blocking, as noted after Proposition B.4.) The values u_h are nonnegative integers that strictly decrease. □

For each of the 16 instances that were open in the literature the loop ended with "safe" at BOBILib's own value, so BOBILib's point was already optimal and the proof of optimality is new.

C. MULTIDIMENSIONAL KNAPSACK INTERDICTION PROOFS

We use the packing interdiction notation of Section A: leader rows $Gx \le g$, follower rows $Wy \le c$ with m rows, $p, G, g, W, c \ge 0$ integral, and $\Phi(x)$ the follower's optimum. Let

$$U(x) = \max\{p^\top y : Wy \le c,\ 0 \le y \le \mathbf{1} - x\}$$

be the value of the follower's linear programming (LP) relaxation, and $p_{\max} = \max_j p_j$.

C.1 The dualised follower LP

Lemma C.1 (Dual form of U)**.** *For $x \in \{0,1\}^n$,*

$$U(x) = \min_{\lambda \in \mathbf{R}^m_{\ge 0}} D(x, \lambda), \qquad D(x, \lambda) = c^\top \lambda + \sum_{j=1}^{n} \max\big(0,\, p_j - (W^\top \lambda)_j\big)(1 - x_j),$$

and the minimum is attained by some λ with $0 \le \lambda_k \le p_{\max}/w_k^{\min}$ for every row k, where $w_k^{\min}$ is the smallest positive entry of row k of W ($w_k^{\min} = 1$ if the row is zero).

Proof. The LP is feasible ($y = 0$, since $c \ge 0$) and bounded ($0 \le y \le \mathbf{1}$), so by LP duality $U(x) = \min\{c^\top \lambda + \sum_j (1 - x_j)\nu_j : W^\top \lambda + \nu \ge p,\ \lambda, \nu \ge 0\}$, and the minimum is attained. For fixed λ the best feasible ν_j with $x_j = 0$ is $\max(0, p_j - (W^\top \lambda)_j)$; for $x_j = 1$ the term has coefficient 0. This gives $U(x) = \min_\lambda D(x, \lambda)$. For the box: if $\lambda_k > p_{\max}/w_k^{\min}$, lower λ_k to $p_{\max}/w_k^{\min}$. Every item j with $W_{kj} > 0$ still has $(W^\top \lambda)_j \ge \lambda_k W_{kj} \ge p_{\max} \ge p_j$, so its term stays 0; items with $W_{kj} = 0$ are unaffected; and $c_k \lambda_k$ does not increase because $c_k \ge 0$. So D does not increase. □

Not formalised.

Proposition C.2 (Exact linearisation)**.** *Let $U^* = \min\{U(x) : Gx \le g,\ x \in \{0,1\}^n\}$. Then U^* is the optimal value of the MILP*

$$\begin{aligned} \min \quad & c^\top \lambda + \sum_{j:\, p_j > 0} v_j \\ s.t. \quad & v_j \ge p_j - (W^\top \lambda)_j - p_j x_j, \quad v_j \ge 0 \quad (p_j > 0), \\ & 0 \le \lambda_k \le p_{\max}/w_k^{\min} \quad (k = 1, \dots, m), \qquad Gx \le g, \quad x \in \{0,1\}^n. \end{aligned}$$

Proof. For $x_j \in \{0,1\}$ and $(W^\top \lambda)_j \ge 0$,

$$\max\big(0, p_j - (W^\top \lambda)_j\big)(1 - x_j) = \max\big(0,\, p_j - (W^\top \lambda)_j - p_j x_j\big) :$$

both sides equal $\max(0, p_j - (W^\top \lambda)_j)$ when $x_j = 0$, and both are 0 when $x_j = 1$. For fixed (x, λ) the smallest feasible v_j is this maximum, and items with $p_j = 0$ contribute 0. So the MILP's value is the minimum of $D(x, \lambda)$ over leader-feasible x and λ in the box, which is $\min_x U(x) = U^*$ by Lemma C.1. □

Not formalised.

C.2 The integrality-gap bracket

Lemma C.3 (Integrality gap of a packing problem with m rows)**.** *For every $x \in \{0,1\}^n$, with $p_{\max}(x) = \max\{p_j : x_j = 0\}$ (0 if there is no such j),*

$$U(x) - m\, p_{\max}(x) \ \le\ \Phi(x) \ \le\ U(x).$$

Proof. $\Phi(x) \le U(x)$ because the LP is a relaxation. The LP's feasible region $P = \{y : Wy \le c,\ 0 \le y_j \le 1 - x_j\}$ is a nonempty polytope, so the LP has an optimal vertex y^*. A vertex of $P \subseteq \mathbf{R}^n$ satisfies n linearly independent constraints of P with equality. Let $F = \{j : 0 < y_j^* < 1\}$; these coordinates have $x_j = 0$ and neither bound tight. The bound constraints of coordinate j are $y_j \ge 0$ and $y_j \le 1 - x_j$, with normals $\pm e_j$, so a linearly independent family of tight constraints contains at most one bound constraint per coordinate outside F and none for coordinates in F. Hence at least $|F|$ of the n independent tight constraints are rows of W, and $|F| \le m$. Let $\tilde{y}_j = 1$ if $y_j^* = 1$ and $\tilde{y}_j = 0$ otherwise. Then $\tilde{y} \le y^*$, so $W\tilde{y} \le Wy^* \le c$ (as $W \ge 0$) and $\tilde{y} \le \mathbf{1} - x$; $\tilde{y}$ is a binary follower response, and $\Phi(x) \ge p^\top \tilde{y} = U(x) - \sum_{j \in F} p_j y_j^* \ge U(x) - m\, p_{\max}(x)$. □

Not formalised.

Theorem C.4 (Bracket)**.** *Let $L \le U^*$ be any lower bound on U^* (for example a MILP solver's proven dual bound for the MILP of Proposition C.2) and let $\hat{x}$ be any leader-feasible choice. Then*

$$\lceil L - m\, p_{\max} \rceil \ \le\ \mathrm{OPT} \ \le\ \Phi(\hat{x}) \ \le\ U(\hat{x}).$$

Proof. For every leader-feasible x, Lemma C.3 gives $\Phi(x) \ge U(x) - m\, p_{\max}(x) \ge U^* - m\, p_{\max} \ge L - m\, p_{\max}$, so $\mathrm{OPT} \ge L - m\, p_{\max}$, and OPT is an integer because p is. The upper bounds hold because the leader may play $\hat{x}$ and the game is zero-sum. □

Not formalised.

For the OR instances with one follower knapsack (variant -100, $m = 1$) the lower bound is $\lceil L - p_{\max} \rceil$. With several follower rows the width $m\, p_{\max}$ makes the lower bound weak, and only the upper bounds are used.

C.3 The merged-row online bound

Theorem B.9 needs one leader row and one follower row. For one follower row ($m = 1$, weights $w_j = W_{1j}$, capacity $c = c_1$) and several leader rows, choose multipliers $\mu \in \mathbf{R}^{m_u}_{\geq 0}$ and scales $s_u, s_l > 0$, and define the integer data

$$\gamma'_j = \left\lfloor s_u \sum_i \mu_i G_{ij} \right\rfloor, \quad \beta' = \left\lceil s_u \sum_i \mu_i g_i \right\rceil, \quad w'_j = \lceil s_l w_j \rceil, \quad c' = \lfloor s_l c \rfloor.$$

Let ω' be the value of the online game of Theorem B.9 with profits p, leader costs γ', budget β', follower weights w' and capacity c', on any list of distinct items.

Theorem C.5 (Merged-row online bound)**.** *For all $\mu \geq 0$ and $s_u, s_l > 0$: $\omega' \leq$ OPT.*

Proof. The leader is relaxed. If $Gx \leq g$ then, as $x \geq 0$ and $\gamma'_j \leq s_u \sum_i \mu_i G_{ij}$,

$$\sum_j \gamma'_j x_j \leq s_u \sum_i \mu_i (Gx)_i \leq s_u \sum_i \mu_i g_i \leq \beta'.$$

So every leader-feasible set is feasible for the merged row (γ', β'). *The follower is restricted.* If $\sum_{j \in Y} w'_j \leq c'$ then $s_l\, w(Y) \leq \sum_{j \in Y} w'_j \leq c' \leq s_l c$, so $w(Y) \leq c$. Hence every packing for (w', c') is a packing for (w, c), and the best packing $K'(T)$ of a set T under (w', c') satisfies $K'(T) \leq K(T)$. *Combine.* For every leader-feasible X, Theorem B.9 for the data $(p, \gamma', \beta', w', c')$ gives $\omega' \leq K'(N \setminus X) \leq K(N \setminus X) = \Phi(X)$. Minimising over X gives $\omega' \leq$ OPT. □

The online bound itself is formalised (Theorem B.9); the merging, scaling and rounding steps are not.

Lowering leader costs and raising the leader's budget only enlarge the leader's options in the relaxed game, and raising follower weights and lowering its capacity only shrink the follower's options; both moves can only lower the value of the game, which is why the result stays a valid lower bound for any multipliers and scales. The choice of μ (coordinate ascent on a coarse table) and of the scales (which control the table size, $(\beta' + 1)(c' + 1)$ entries per item) affects only the strength of the bound. The code plays the items with positive profit in decreasing order of p_j / w_j.

C.4 Certified points

Proposition C.6 (Certified point)**.** *Let $\hat{x}$ satisfy $G\hat{x} \leq g$, and let $\hat{y}$ be a follower response at $\hat{x}$ proven optimal (by the exact knapsack oracle when $m = 1$, or by a MILP solver whose dual bound meets $p^\top \hat{y}$). Then $(\hat{x}, \hat{y})$ is bilevel feasible with value $\Phi(\hat{x})$, so* OPT $\leq \Phi(\hat{x})$. *Without an exact follower solve,* OPT $\leq \lfloor U(\hat{x}) \rfloor$ *still holds.*

Proof. $\hat{y} \in S(\hat{x})$ by definition; the game is zero-sum, so every element of $S(\hat{x})$ gives the leader the value $\Phi(\hat{x})$. The last claim is Lemma C.3 and integrality of Φ. □

Not formalised.

For several follower knapsacks the leader choice $\hat{x}$ is the minimiser found for the MILP of Proposition C.2; when HiGHS proves the follower's optimum at $\hat{x}$, the point is certified. For one follower knapsack, a first-improvement local search on the leader's choice (add an item the follower uses, or swap a blocked item for one it uses, keeping every budget row) evaluates each candidate with the exact knapsack oracle, so every incumbent it reports is a certified point. Every point reported is checked again from its file by `bobi verify` (Section A.3).

D. CLIQUE INTERDICTION PROOFS

D.1 The model

BOBILib's instance `normalClique`*n*`-`*d*`-`*i* has a graph $G=(V,E)$ with $n=|V|$, $m=|E|$, and budget $k=\lfloor m/4\rfloor$. All variables are binary. The leader has w_e for $e\in E$ and the single row $\sum_e w_e\le k$. The follower has x_v ($v\in V$) and y_e ($e\in E$) and the rows

$$x_u+x_v\le 1\ \ (uv\notin E),\qquad x_u+x_v-y_{uv}\le 1\ \ (uv\in E),\qquad w_{uv}+y_{uv}\le 1\ \ (uv\in E).$$

The leader minimises $\sum_v x_v$ and the follower minimises $-\sum_v x_v$. (Every row, coefficient and objective of the 60 files was checked against this pattern, once by the instance reader of the clique scripts and once by an independent reviewer's parser that classifies rows by their coefficients.)

Lemma D.1 (Follower's problem)**.** *Fix the leader's choice and let $D=\{e : w_e=1\}$. A vector $x\in\{0,1\}^V$ extends to a feasible follower point if and only if $\{v : x_v=1\}$ is a clique of $G-D$. Hence the follower's optimum is $\omega(G-D)$, the game is zero-sum, and the bilevel optimum is* $\min\{\omega(G-D) : D\subseteq E,\ |D|\le k\}$.

Proof. Let x be part of a feasible point and $x_u=x_v=1$. The first family of rows forces $uv\in E$. If $uv\in D$ then $w_{uv}=1$ forces $y_{uv}=0$, and the second family gives $x_u+x_v\le 1$, a contradiction. So $uv\in E\setminus D$. Conversely, for a clique of $G-D$ set $y_{uv}=1-w_{uv}$: the third family holds with equality; the second holds for $uv\notin D$ because $y_{uv}=1$, and for $uv\in D$ because a clique of $G-D$ does not contain both u and v; the first holds because a clique contains no non-edge of G. The leader's objective is minus the follower's. □

Not formalised (the Lean file states the bounds directly in terms of $\omega(G-D)$).

D.2 Lower bound 3: Mantel's theorem

Theorem D.2 (Mantel 1907, deletion form)**.** *A graph on n vertices with more than $\lfloor n^2/4\rfloor$ edges contains a triangle. Consequently, if $m-k>\lfloor n^2/4\rfloor$, then $G-D$ contains a triangle for every set D of at most k edges, and the bilevel optimum is at least* 3.

Proof. Mantel's theorem[13] is Turán's theorem[14] for K_3. After deleting at most k edges at least $m-k$ edges remain, and $m-k>\lfloor n^2/4\rfloor$. □

Formalised: `Bobi/Clique.lean`, theorems `mantel`, `mantel'` and `triangle_survives`; the instance arithmetic in `mantel_40`, `mantel_50`, `mantel_60`, `clique40`, `clique50` and `clique60`.

All 30 density-0.7 instances have $(n,m,k)\in\{(40,546,136),(50,857,214),(60,1239,309)\}$, so $m-k=410,643,930$ exceeds $\lfloor n^2/4\rfloor=400,625,900$. The density-0.9 instances satisfy the same inequality.

D.3 Upper bounds: partitions

Proposition D.3 (Partition upper bound)**.** *Let $f : V\to\{1,\dots,r\}$ and let D contain every edge of G whose ends have the same colour. Then $G-D$ has no clique on $r+1$ vertices. If at most k edges of G lie inside the colour classes, deleting exactly those edges is a leader choice, and the bilevel optimum is at most r.*

Proof. f is a proper colouring of $G-D$, and a clique on $r+1$ vertices needs $r+1$ colours. □

Formalised: `Bobi/Clique.lean`, theorem `cliqueFree_of_partition`.

For a partition $\mathscr{P}$ of V into r parts (parts may be empty) let $\mathrm{in}_G(\mathscr{P})$ be the number of edges of G inside parts, and let $w_r(G)=\min_{\mathscr{P}}\mathrm{in}_G(\mathscr{P})$. Each solution file deletes the inside edges of a 3- or 4-partition found by tabu search and states a maximum clique of the remaining graph, computed exactly (the review re-checks it with two exact clique searches[15–17]); the files pass the checks of Section A.3.

D.4 Lower bound 4: Brouwer's theorem

Let $t_r(n)$ be the number of edges of the balanced complete r-partite graph on n vertices (Turán's number), and $T(n,r) = \binom{n}{2} - t_r(n)$, the number of edges of the disjoint union of r cliques of balanced sizes.

Theorem D.4 (Brouwer 1981, Theorem 2;[6] quoted, with his G renamed H and his $m := \lfloor n/t \rfloor$ written out)**.** *Let H be a graph on n points such that $\alpha(H) \le t$, and $n > 2t$. If H has no more than $T(n,t) + \lfloor n/t \rfloor - 2$ edges, then $V(H)$ can be written as a union of t cliques. Moreover, this bound is best possible.*

Here $\alpha(H)$ is the independence number. The theorem is restated by Tyomkyn and Uzzell[7] (their equation (1) and Theorem 1.1), who credit Brouwer with the first explicit proof, and, in the complemented form below for $t \ge 2$, by Korándi, Roberts and Scott[8] (their Theorem 1.1). We use it in complemented form.

Corollary D.5 (Complement form)**.** *Let $t \ge 1$ and $n \ge 2t+1$. Every K_{t+1}-free graph F on n vertices with $e(F) \ge t_t(n) - \lfloor n/t \rfloor + 2$ is t-partite (its vertex set is the union of t independent sets, some possibly empty).*

Proof. Apply Theorem D.4 to the complement $H = \overline{F}$: $\alpha(H) = \omega(F) \le t$, $n > 2t$, and $e(H) = \binom{n}{2} - e(F) \le \binom{n}{2} - t_t(n) + \lfloor n/t \rfloor - 2 = T(n,t) + \lfloor n/t \rfloor - 2$. So V is a union of t cliques of H, that is, of t independent sets of F. Assigning each vertex to one of the sets containing it gives a partition into independent sets. □

Not formalised: Brouwer's theorem is not in Mathlib, and it is neither proved nor assumed in the Lean files. The statement above was read in the scanned report, and the translation was checked by computer (for $t = 3$: $T(n,3) + t_3(n) = \binom{n}{2}$).

Theorem D.6 (Density 0.9: value at least 4)**.** *Let $n \ge 7$, $m - k \ge t_3(n) - \lfloor n/3 \rfloor + 2$ and $w_3(G) > k$. Then $G - D$ contains a K_4 for every $D \subseteq E$ with $|D| \le k$, so the bilevel optimum is at least 4.*

Proof. Suppose $|D| \le k$ and $G - D$ is K_4-free. It has $m - |D| \ge m - k$ edges, so by Corollary D.5 with $t = 3$ ($n \ge 7 = 2t+1$) it is 3-partite with some partition $\mathscr{P}$. No edge of $G - D$ lies inside a part, so every edge of G inside a part lies in D, and $|D| \ge \mathrm{in}_G(\mathscr{P}) \ge w_3(G) > k$, a contradiction. □

Not formalised (it rests on Theorem D.4).

For the density-0.9 instances $(n,m,k) \in \{(40,702,175),(50,1102,275),(60,1593,398)\}$, so $m - k = 527,827,1195$ and $t_3(n) - \lfloor n/3 \rfloor + 2 = 522,819,1182$ ($t_3(n) = 533,833,1200$): the hypothesis holds with margins 5, 8 and 13, while $m - k < t_3(n)$, so Turán's theorem alone does not give a K_4. It remains to show $w_3(G) > k$.

D.5 Reducing $w_3(G) > k$ to finitely many part-size cases

Let $\overline{E}$ be the edge set of the complement $\overline{G}$, so $|\overline{E}| = \binom{n}{2} - m$, and for a partition $\mathscr{P}$ let $\mathrm{cut}_{\overline{G}}(\mathscr{P})$ be the number of edges of $\overline{G}$ joining different parts.

Proposition D.7 (Part-size reduction)**.** *For a partition $\mathscr{P} = (P_1, P_2, P_3)$ of V with part sizes s_1, s_2, s_3,*

$$\mathrm{in}_G(\mathscr{P}) = \sum_{i=1}^{3} \binom{s_i}{2} - |\overline{E}| + \mathrm{cut}_{\overline{G}}(\mathscr{P}).$$

Hence, with $b(s) = k + |\overline{E}| - \sum_i \binom{s_i}{2}$, $w_3(G) > k$ holds if and only if, for every size vector $s_1 \ge s_2 \ge s_3 \ge 0$ with $s_1 + s_2 + s_3 = n$ and $b(s) \ge 0$, no partition with these part sizes has $\mathrm{cut}_{\overline{G}}(\mathscr{P}) \le b(s)$.

Proof. Each of the $\sum_i \binom{s_i}{2}$ pairs inside a part is an edge of G or of $\overline{G}$, and the edges of $\overline{G}$ inside parts number $|\overline{E}| - \mathrm{cut}_{\overline{G}}(\mathscr{P})$. So $\mathrm{in}_G(\mathscr{P}) \le k$ iff $\mathrm{cut}_{\overline{G}}(\mathscr{P}) \le b(s)$. Relabelling the parts, every partition has sorted sizes, and since $\mathrm{cut}_{\overline{G}} \ge 0$, size vectors with $b(s) < 0$ admit no partition with $\mathrm{in}_G \le k$. □

Not formalised (checked in exact integer arithmetic by script, and on random partitions of every instance).

Since n, m and k are the same for all ten graphs of a group, so are the size vectors with $b(s) \geq 0$:

n	$\lvert\overline{E}\rvert$	size vectors s with $b(s)$ in brackets
40	78	(14,13,13) [6], (14,14,12) [5], (15,13,12) [4], (15,14,11) [2], (16,12,12) [1], (16,13,11) [0]
50	123	(17,17,16) [6], (18,16,16) [5], (18,17,15) [4], (19,16,15) [2], (18,18,14) [1], (19,17,14) [0]
60	177	(20,20,20) [5], (21,20,19) [4], (21,21,18) [2], (22,19,19) [2], (22,20,18) [1]

That is $10 \cdot 6 + 10 \cdot 6 + 10 \cdot 5 = 170$ cases (instance, size vector), each asking for a partition of V with prescribed part sizes and at most $b(s) \leq 6$ edges of the sparse complement between parts. All 170 were decided infeasible by five methods: CP-SAT[18] and SCIP[19] on two different models, an exact solver-free depth-first search (tested against brute force), and, by an independent reviewer, HiGHS on a third model with an explicit budget row and a separate exact branch and bound written in C (tested against brute force on 450 random graphs and on planted instances). With Theorem D.6 and Proposition D.3 (4-partitions with at most k inside edges), all 30 density-0.9 instances have value exactly 4. These solver verdicts are computations, not formalised proofs.

D.6 The three open instances

For normalClique60-70-2, -3 and -5 ($n = 60$, $m = 1239$, $k = 309$) Mantel gives value ≥ 3 and a 4-partition gives value ≤ 4. Let $\tau_4(G)$ be the fewest edges meeting every K_4 of G. By Lemma D.1 the value is 3 if and only if $\tau_4(G) \leq k$. Deleting the inside edges of a 3-partition destroys every K_4 (two of any four vertices share a part), so $\tau_4(G) \leq w_3(G)$, and $w_3(G) \leq k$ would give value 3; the best 3-partitions found have 311, 310 and 310 inside edges, against $k = 309$.

The converse argument of Theorem D.6 is not available here. It would need every K_4-free subgraph with at least $m - k = 930$ edges to be 3-partite, but $930 < t_3(60) - 20 + 2 = 1182$, so Corollary D.5 does not apply, and its conclusion is false at this edge count: the disjoint union of the wheel W_5 (a 5-cycle plus a vertex joined to all of it; 6 vertices, 10 edges, K_4-free, chromatic number 4) and any 3-partite graph with 920 edges on the other 54 vertices ($920 \leq t_3(54) = 972$) is a K_4-free graph on 60 vertices with 930 edges that is not 3-partite. So a proof of value 4 must bound $\tau_4(G)$ itself from below. Linear programming bounds on τ_4 (rows for every K_4, for maximal cliques and for vertex sets whose induced subgraph must lose a Turán excess of edges) stop near 296, below the 310 needed, and searches for a transversal with at most 309 edges that are not restricted to 3-partite remainders stop at the best 3-partition found. The three instances stay open with $3 \leq$ value ≤ 4.

E. GENERAL INSTANCES: RAYS, HPR BOUND AND PIPELINES

Notation is that of (A.1). In this section a follower row is written $\ell_i \leq C_i x + D_i y \leq h_i$ with $\ell_i \in \mathbf{R} \cup \{-\infty\}$ and $h_i \in \mathbf{R} \cup \{+\infty\}$, and the follower's variable bounds as $\ell^y_j \leq y_j \leq h^y_j$, because the direction test below depends on which sides are finite.

E.1 Unbounded followers: no bilevel feasible point

Theorem E.1 (Recession direction)**.** *Let $d \in \mathbf{Q}^{n_y}$ satisfy, for every follower row i, $D_i d \geq 0$ if $\ell_i > -\infty$ and $D_i d \leq 0$ if $h_i < +\infty$; for every follower variable j, $d_j \geq 0$ if $\ell^y_j > -\infty$ and $d_j \leq 0$ if $h^y_j < +\infty$; and $f^\top d < 0$. Then for every leader choice x (real or integral) the follower's problem $P(x)$ is infeasible or unbounded, so $S(x) = \emptyset$ and the bilevel problem has no feasible point.*

Proof. Let ν be a positive integer such that $\nu d_j \in \mathbf{Z}$ for every $j \in I_l$ (d is rational). Suppose y is feasible for $P(x)$. For every integer $t \geq 0$, $y + t\nu d$ satisfies every follower row, since $C_i x$ is a constant and $D_i(y +$

$t \vee d$) moves only in the permitted direction; it satisfies every bound for the same reason; and its integer-constrained entries stay integral. Its objective $f^\top y + t \vee f^\top d$ tends to $-\infty$. So $P(x)$ has no optimal solution whenever it is feasible. □

Not formalised.

Remark E.2 (Meyer's theorem). The theorem only needs an explicit rational direction. It is the case we need of a classical result of Meyer:[20] with rational data, the convex hull of the feasible set of a mixed-integer program is a rational polyhedron with the same recession cone as the LP relaxation, so a feasible mixed-integer program whose LP relaxation is unbounded is itself unbounded. Rationality matters: without it, a direction of the LP relaxation need not be usable by integer points. The directions here are found by an LP solver in floating point, written as decimals (which are rationals) and checked exactly.

The exact check. For each certificate, a script that reads the instance files independently of the solver code converts every entry of d to an exact rational and checks the conditions of Theorem E.1 in rational arithmetic, counting only follower variables in each follower row (leader variables enter those rows as constants). When rounding leaves tiny residuals, the direction is first projected onto the exact null space of its tight rows. This succeeds for 38 of the 40 open instances; for `supportcase42_0_100` and `supportcase42_50_50` residuals of about 10^{-12} (relative) remain, so those two certificates rest on floating point.

E.2 The HPR bound and the MIPLIB optimum

Lemma E.3 (HPR bound)**.** *Every bilevel feasible point is feasible for the HPR, so* HPR $\leq$ OPT. *If a bilevel feasible point has value* HPR*, it is optimal.*

Proof. A bilevel feasible point satisfies $Ax + By \geq a$, the integrality conditions, and, as $y \in S(x)$, also $Cx + Dy \geq b$. The HPR minimises the same objective over a superset. □

Not formalised.

BOBILib builds its general instances from a MIPLIB problem by assigning variables and rows to the two levels and keeping the problem's objective as the leader's. If nothing else changes, dropping the condition $y \in S(x)$ gives back the MIPLIB problem: the HPR *is* the MIPLIB model, and its published optimum[2] z^* is a lower bound on OPT by Lemma E.3. This is not assumed: a script reads the bilevel instance and the MIPLIB 2017 model and checks in exact rational arithmetic that they have the same variables, rows, coefficients, sides, bounds, integrality requirements and objective (up to the objective's sense). For the five instances where it holds and a verified bilevel feasible point attains the bound (`pigeon-10_0_100`, `pigeon-10_50_50`, `timtab1_0_100`, `noswot_0_100`, `noswot_50_50`), the point is optimal. The values z^* are the optima in MIPLIB 2017's solution file: $-9{,}000$ for `pigeon-10`, which both points attain; 764,771.99999978 for `timtab1` (printed as 764,772 on the MIPLIB web pages), which the point attains with row violations below 10^{-12}; and -41.00000885 for `noswot`, whose objective has integer coefficients on integer variables only, so that $\lceil z^* \rceil = -41$ is also a lower bound, attained by BOBILib's own points. The published optima were computed in floating point, so "optimal" means equal to the published optimum to its printed precision (after rounding up for `noswot`).

E.3 Feasible points without coupling rows

Proposition E.4 (HPR, follower, tie-break)**.** *Assume there are no coupling rows ($B = 0$). Let $(\hat{x}, \hat{y})$ be feasible for the HPR, and suppose $P(\hat{x})$ has an optimal solution, with value $\varphi(\hat{x})$. Then the tie-break problem at $\hat{x}$ (the optimistic choice among the follower's optima, Section A) is feasible, and for any of its feasible points y^*, the point $(\hat{x}, y^*)$ is bilevel feasible. If y^* is optimal for the tie-break problem, $(\hat{x}, y^*)$ is the best bilevel feasible point with leader part $\hat{x}$.*

Proof. $A\hat{x} \geq a$ holds because $(\hat{x}, \hat{y})$ is HPR feasible and $B = 0$, and $\hat{x}$ satisfies its integrality conditions. Any optimal solution of $P(\hat{x})$ is feasible for the tie-break problem, whose rows are those of $P(\hat{x})$, $f^\top y \leq \varphi(\hat{x})$, and $A\hat{x} + By \geq a$, which does not involve y. A feasible point y^* of it is feasible for $P(\hat{x})$ with $f^\top y^* \leq \varphi(\hat{x})$, so $y^* \in S(\hat{x})$. The bilevel feasible points with leader part $\hat{x}$ are exactly the pairs $(\hat{x}, y)$ with $y \in S(\hat{x})$, the feasible set of the tie-break problem. □

Not formalised. The existence of an optimal solution of $P(\hat{x})$ is what the follower solve establishes; the HPR point $\hat{y}$ shows that $P(\hat{x})$ is feasible. The computations accept $f^\top y \leq \varphi(\hat{x}) + 10^{-7}(1 + |\varphi(\hat{x})|)$ in the tie-break, well inside BOBILib's relative tolerance (A.2). The pipeline handles continuous linking variables, which neither of BOBILib's two solvers accepts.

E.4 Coupling rows

With coupling rows ($B \neq 0$) the follower's optima at the HPR's leader values may all violate them. Recall that $P(x)$, $\varphi(x)$ and $S(x)$ depend on x only through the linking variables x_L; write $\varphi(x_L)$. For fixed values $\bar{x}_L$ define the *best response*

$$\mathrm{BR}(\bar{x}_L) = \min\big\{c^\top x + d^\top y :\ x_L = \bar{x}_L,\ Ax + By \geq a,\ Cx + Dy \geq b,\ f^\top y \leq \varphi(\bar{x}_L),\ \text{integrality}\big\},$$

in which the other leader variables are free.

Proposition E.5 (Best response and blocked leader choices)**.** *Suppose $P(\bar{x}_L)$ has an optimal solution. Then the feasible points of $\mathrm{BR}(\bar{x}_L)$ are exactly the bilevel feasible points with linking part $\bar{x}_L$, and $\mathrm{BR}(\bar{x}_L)$ is the best value among them. If $\mathrm{BR}(\bar{x}_L)$ is infeasible, no bilevel feasible point has linking part $\bar{x}_L$ (the choice $\bar{x}_L$ is* blocked*). Consequently $\mathrm{OPT} = \inf_{\bar{x}_L} \mathrm{BR}(\bar{x}_L)$ over linking values for which $P(\bar{x}_L)$ has an optimal solution.*

Proof. (x, y) is bilevel feasible iff it satisfies the upper-level rows and integrality and $y \in S(x)$, and $y \in S(x)$ iff y is feasible for $P(x_L)$ and $f^\top y \leq \varphi(x_L)$. These are the constraints of $\mathrm{BR}(x_L)$. If $P(\bar{x}_L)$ has no optimal solution, $S(x) = \emptyset$ for every x with these linking values. □

Not formalised.

Lemma E.6 (Value-function cuts[21,22])**.** *Let $\hat{y}$ be feasible for $P(\hat{x}_L)$ with $f^\top \hat{y} = \hat{f}$. Every bilevel feasible (x, y) satisfies: $\hat{y}$ is infeasible for $P(x_L)$, or $f^\top y \leq \hat{f}$.*

Proof. If $\hat{y}$ is feasible for $P(x_L)$ then $\varphi(x_L) \leq \hat{f}$, and $y \in S(x)$ gives $f^\top y = \varphi(x_L)$. □

Not formalised.

The search for an unblocked linking choice tries, in turn within a time budget: the HPR's own x_L; best-response dynamics; the HPR with objective $c^\top x + d^\top y + \rho f^\top y$ for increasing ρ; a penalty alternating direction method after Kleinert and Schmidt;[23] moves of continuous linking variables towards the interior; the HPR with the cuts of Lemma E.6 (modelled with binary indicators, exact when every follower row's linking part takes integer values); and no-good cuts on integer linking variables. These are heuristics: none of them is needed for correctness, and the "blocked" verdicts (solver tolerances included) only steer the search; no instance is claimed to have no feasible point on that basis. What is certified is each returned point, re-checked from scratch: all rows, bounds and integrality within 10^{-6}; a fresh follower solve whose proven dual bound puts the point's follower value within relative 10^{-5} of the optimum; and the optimistic tie-break at the point's leader values within relative 10^{-5} by a proven bound. Each file then passes `bobi verify`.

In 9 of the 29 files with coupling rows the follower's value lies about 10^{-7} (relative) above its optimum, which BOBILib's test (A.2) accepts. For seven of them a point with the follower at its optimum (within

10^{-9} relative) exists at the same leader values with a slightly worse leader objective. For `pg_50_50` and `neos-2978193-inde_50_50` the coupling rows force the follower about 10^{-7} above its optimum at the files' leader values; with the non-linking leader variables free, exactly optimal responses exist, so both instances do have bilevel feasible points, but the two files are feasible only within the tolerance.

Few binary linking variables. If the linking variables are binary and few, Proposition E.5 gives the exact optimum by enumerating all $\bar{x}_L$, solving $P(\bar{x}_L)$ and $\mathrm{BR}(\bar{x}_L)$ for each. This reproduces the published optimum 299,577 of Lozano, Bergman and Cire[11] for `general30-30-10-20-20-8` (10 linking bits); with 20 bits it is too slow.

E.5 A tolerance observation

Remark E.7 (`general20-30-20-20-20-2`). Test (A.2) is relative. In the generalized interdiction instance `general20-30-20-20-20-2` the follower's objective values are near 10^8, so a response up to about 10^4 units from the follower's optimum passes. BOBILib's value for this instance rests on a follower response that is 19 units suboptimal (relative error about 2×10^{-7}). Such a point is not bilevel feasible in the sense of Definition A.1: with an exactly optimal follower response the leader's value at the same leader choice can differ. A value accepted only under a relative tolerance is therefore not proven attainable with an exactly optimal follower response.

F. NETWORK INTERDICTION

F.1 The model as encoded in the files

BOBILib's `inter-fire` instances (from Baggio, Carvalho, Lodi and Tramontani,[24] with the vaccinated nodes already removed) have a graph (V,E) and three binary variables per node v: y_v (the leader attacks v), x_v (the follower protects v) and a_v (node v is saved). The rows are

$$\sum_v y_v \le \Phi, \qquad \sum_v x_v \le \Lambda, \qquad a_v + y_v \le 1 \;\; (v \in V),$$
$$a_v - a_u - x_v \le 0 \;\text{ for both orientations } (u,v) \text{ of every edge } uv \in E.$$

The first row is the leader's; the others are the follower's. The leader minimises $\sum_v w_v a_v$ and the follower minimises $-\sum_v w_v a_v$, with $w_v = 1$ in every instance (the arguments below only use $w \ge 0$). The reader of `bobi fire` checks every row, bound and objective coefficient of each file against this pattern and rejects anything else; an independent reviewer re-derived the pattern with a separate parser. The game is zero-sum, so the optimistic tie-break plays no part. In this section Φ is the attack budget.

F.2 The follower's optimum as a closure

For an attack $Y \subseteq V$ and a protection set $X \subseteq V$, call $B \subseteq V$ *closed* if $Y \subseteq B$ and, for every edge and each ordering (u,v) of its two ends, $u \in B$ and $v \notin X$ imply $v \in B$. The intersection of closed sets is closed and V is closed, so there is a smallest closed set $B(Y,X)$: the nodes reached from Y by fire spreading through unprotected nodes.

Lemma F.1 (Closure). *For fixed $y = \mathbf{1}_Y$ and $x = \mathbf{1}_X$, a vector $a \in \{0,1\}^V$ satisfies the follower's rows if and only if $Z(a) = \{v : a_v = 0\}$ is closed. Hence the follower's best value for X is $w(V \setminus B(Y,X))$, and its optimum against the attack Y is*

$$\mathrm{sv}(Y) = \max\big\{w(V \setminus B(Y,X)) : X \subseteq V,\ |X| \le \Lambda\big\}.$$

Proof. The rows $a_v + y_v \le 1$ say $Y \subseteq Z(a)$. The row $a_v \le a_u + x_v$ for the orientation (u,v) says: if $a_u = 0$ and $x_v = 0$ then $a_v = 0$, that is, $u \in Z(a)$ and $v \notin X$ imply $v \in Z(a)$. So the feasible a are exactly the indicator vectors of complements of closed sets. Every closed set contains $B(Y,X)$, and $B(Y,X)$ is closed, so with $w \ge 0$ the best choice is $a = \mathbf{1}_{V \setminus B(Y,X)}$. □

Not formalised (checked against brute force over all (a,x) on 400 random graphs with up to 6 nodes, and used by the reviewer's brute force).

Corollary F.2 (Monotonicity in the attack)**.** *If $Y \subseteq Y'$ then* $\mathrm{sv}(Y') \le \mathrm{sv}(Y)$. *Hence, when $|V| \ge \Phi$, the minimum of* sv *over attacks with $|Y| \le \Phi$ is attained by an attack with exactly Φ nodes.*

Proof. $B(Y',X)$ is closed for Y (it contains $Y' \supseteq Y$), so $B(Y,X) \subseteq B(Y',X)$ and $w(V \setminus B(Y',X)) \le w(V \setminus B(Y,X))$ for every X. Any attack with fewer than Φ nodes can be enlarged. □

Not formalised. The enumeration below covers every attack size from 0 to Φ, so the certificate does not depend on this corollary. It explains why the least saved count falls with the attack size: for the instance `tree-50_1-5-5_006` the minima for attack sizes $0,\dots,5$ are $49, 48, 44, 38, 32, 26$.

F.3 The tree dynamic program

Suppose the graph is a forest. Root every component and hang the roots below a virtual root whose edges carry no constraint. Give every node v a state $\sigma_v = (x_v, a_v) \in \{0,1\}^2$; state σ is *allowed* at v unless $v \in Y$ and $a_v = 1$; states σ_p, σ_c of the ends of an edge pc are *compatible* if $a_c \le a_p + x_c$ and $a_p \le a_c + x_p$. For a node v with children $c_1,\dots,c_d$, a state σ and $0 \le q \le \Lambda$, let $T_v(\sigma,q)$ be the largest $\sum_u w_u a_u$ over the subtree of v among assignments of allowed states with v in state σ, compatible states on every edge of the subtree and exactly q protected nodes ($-\infty$ if there is none). With $T_v^{(0)}(\sigma,q) = w_v a(\sigma)$ if σ is allowed and $q = x(\sigma)$, and $-\infty$ otherwise,

$$T_v^{(i)}(\sigma,q) = \max_{0 \le q' \le q} \Big[T_v^{(i-1)}(\sigma, q-q') + \max_{\sigma' \text{ compatible with } \sigma} T_{c_i}(\sigma', q') \Big], \qquad T_v = T_v^{(d)}.$$

Proposition F.3 (Tree DP)**.** *T_v satisfies the definition above for every node, and the follower's optimum against Y is the best value at the virtual root over $q \le \Lambda$.*

Proof. Induction over the nodes in post-order. The follower's rows other than the budget row involve one node ($a_v + y_v \le 1$) or the two ends of one edge (the two orientations of the arc row), so an assignment of the subtree of v is feasible iff all states are allowed and every edge is compatible. The edges of the subtree of v are the edges vc_i and the edges inside the subtrees of the c_i, which share no node. Hence a feasible assignment of the subtree of v with v in state σ and q protections is the same as: a state for v, and for each i a feasible assignment of the subtree of c_i whose root state is compatible with σ, with protection counts adding up to q; and its value is the sum of the parts. The recursion maximises over exactly these choices, one child at a time. At the virtual root every child state is compatible, and the budget row is $q \le \Lambda$. □

Not formalised (tested against brute force over all (a,x) on 300 random forests, and compared at every attack with a separate C implementation by the reviewer: 9,344,902 attacks on the 40 forests).

F.4 Exhaustive enumeration and the certificate

Theorem F.4 (Certified optimum)**.** *Suppose that for every attack Y with $|Y| \le \Phi$ we have a follower point (x^Y, a^Y) that satisfies all follower rows at Y (checked against the raw model), with value* $\mathrm{dp}(Y) = w(a^Y)$. *Let Y^* minimise* dp*, and suppose the follower's optimum at Y^* is proven to equal* $\mathrm{dp}(Y^*)$. *Then the bilevel optimum is* $\mathrm{dp}(Y^*)$*, attained by Y^* and (x^{Y^*}, a^{Y^*}).*

Proof. For every attack, $\mathrm{sv}(Y) \geq \mathrm{dp}(Y) \geq \mathrm{dp}(Y^*)$, since the follower may play the checked point. The leader's feasible set is exactly $\{Y : |Y| \leq \Phi\}$, so the optimum is at least $\mathrm{dp}(Y^*)$; and $\mathrm{sv}(Y^*) = \mathrm{dp}(Y^*)$ shows it is attained. □

Not formalised.

The certificate does not rest on the DP being optimal at any attack other than Y^*, where HiGHS re-solves the follower MILP built from the raw model. For `tree-50_1-5-5_006` and `_010` the graph has 49 nodes and $\Phi = \Lambda = 5$; the enumeration visits every k-subset for $k = 0, \ldots, 5$ (the count per size is checked against $\binom{49}{k}$), $\sum_{k=0}^{5} \binom{49}{k} = 2{,}138{,}410$ attacks per instance, and both optima are 26. The reviewer obtained the same minima, the same number of optimal attacks and the same per-size minima with independent code.

G. FORMAL VERIFICATION MAP (LEAN)

The project `bobilib/lean`, written in Lean[4] (version 4.35.0) with Mathlib[5] (tag v4.35.0), proves the lemmas in Table S1. Lean file names are relative to `bobilib/lean`; Rust names are in `bobilib/src` (`Search`, `RobustTable` and `play_order` are in `robust_ss.rs`; `Kip` is in `kip.rs`). The Lean statements are about abstract models (items, weight classes, graphs); the Rust code is not verified, and the right-hand column of the table says which code relies on each statement.

Table S1. Results of this supplement with machine-checked proofs: the Lean theorems that state them and the Rust code that relies on them.

Result	Lean theorems (file)	Rust code that relies on it
Knapsack interdiction (Section B)		
Lemma B.1 (monotonicity)	`Bobi/Knapsack.lean`: `follower_antitone`, `bestAvoiding_antitone`, `bestAvoiding_eq_sup_sdiff`, `packings_downward_closed`, `K_eq_bestAvoiding`	`Kip::free_items`, `Kip::greedy`, `Kip::subset_sum_classes`; guaranteed copies in `Search::node`
Lemma B.2 (count formulation)	`Bobi/Knapsack.lean`: `K_map_equiv`, `swap_block`, `cheapest_first`	`Kip::subset_sum_classes`, `Kip::x_from_deletions`; branching on counts in `Search::node`
Lemmas B.5, B.6 (windows, stall test)	`Bobi/SubsetSum.lean`: `window_extend`, `window_extend_all`, `fits_survivors`, `window_survivors`, `SubsetSum.perm`, `Window.perm`	`Search::window_safe`
Theorem B.9 (online bound)	`Bobi/Online.lean`: `online_le_K`, `online_le_K_any`, `online_lower_bound`; example: `table1_online`, `table1_block`, `table1_opt`	`mkip::omega_root`
Theorem B.12 (table soundness)	`Bobi/RobustTable.lean`: `H_sound`, `H_sound_any`, `take_sum_le`, `counts_of_deletion`; `Bobi/BandTable.lean`: `G_sound`, `G_sound_any`, `G_one`, `G_sound_one`; `Bobi/EndTable.lean`: `GA_sound`, `GA_sound_any`, `G_iff_GA`, `H_iff_GA`, `G_sound_of_GA`, `H_sound_of_GA`	`RobustTable::build`, `RobustTable::build_band`
Proposition B.13 (play orders)	`Bobi/EndTable.lean`: `counts_perm`, `remaining_eq_flatten`, `totalCost_eq_sum`, `remaining_perm`, `totalCost_perm`, `GA_sound_perm`, `GA_sound_perm_any`	`play_order`, `RobustTable::build_suffix`, `Search::node_table_threshold`
Corollary B.14 (root-table rules)	`Bobi/RobustTable.lean`: `covers_sound`; `Bobi/BandTable.lean`: `band_covers_sound`, `covers_sound_of_band`; `Bobi/Threshold.lean`: `covers_threshold_sound`, `covers_threshold_sound_perm`, `band_covers_threshold_sound`, `band_covers_threshold_sound_perm`	`RobustTable::covers`, `RobustTable::covers_run`, `Search::tables_cover`

(continued)

Result	Lean theorems (file)	Rust code that relies on it
Lemma B.15 (antitone in the budget)	`Bobi/EndTable.lean`: `GA_antitone`, `G_antitone`, `H_antitone`, `GA_mono`	threshold storage in `RobustTable`; cache entries of `Search::remember`
Theorem B.17 (threshold form)	`Bobi/Threshold.lean`: `thr` (definition), `thr_iff`, `GA_iff_thr`, `thr_bounds`, `thr_eq_neg_one_iff`, `thr_greatest`, `G_iff_thr`, `H_iff_thr`, `le_minOver`, `le_maxOver`	`RobustTable::step`, `RobustTable::base`, `RobustTable::threshold`, `RobustTable::contains`, `RobustTable::step_range`
Theorem B.19 (per-node rule)	`Bobi/EndTable.lean`: `nodeEnd` (definition), `node_rule`, `node_table_sound`, `node_table_sound_perm`, `node_table_sound_any`; `Bobi/Threshold.lean`: `node_table_threshold_sound`, `node_table_threshold_sound_counts`	`Search::node_table_threshold`, the prune and cache entry in `Search::node`, `Search::remember`
Remark after Theorem B.19 (strength)	`Bobi/EndTable.lean`: `node_table_of_H`	none (strength, not soundness)
Edge clique interdiction (Section D)		
Theorem D.2 (Mantel, deletion form)	`Bobi/Clique.lean`: `mantel`, `mantel'`, `triangle_survives`, `mantel_40`, `mantel_50`, `mantel_60`, `clique40`, `clique50`, `clique60`	none; the arithmetic is also checked by `scripts/clique/lb.py`
Proposition D.3 (partition bound)	`Bobi/Clique.lean`: `cliqueFree_of_partition`	none; the certificates are written by `scripts/clique/ub.py`

All names in the middle column are in namespace `Bobi`. There is no `sorry`; `lean/Check.lean` prints the axioms of 72 main theorems, each of which uses at most `propext`, `Classical.choice` and `Quot.sound`.

Not formalised.

- *Subset-sum search.* The reduction of Proposition B.4 as a whole (free and unusable items, the gcd scaling; `Kip::subset_sum_classes`); the fractional deletion bound, Lemma B.7 (`Cumulative::min_cost`), the exact largest deletable mass (`Search::build_max_del`) and the reduction of the stall test to one test per class in Proposition B.8; restricted copies, Proposition B.21 (`restrict_copies`); Lemma B.22, Theorems B.23 and B.24 and Corollary B.25 as statements about the code (`Search::node`, `Search::run`, `Kip::solve_subset_sum`); that the bitset holds exactly the decided subset sums up to *hi*; that the Rust loops compute thr, including the range shortcuts and early exit of `RobustTable::step_range` and `Search::node_table_threshold`, the fallback to `RobustTable::step` for classes with more than 63 copies, the `row_max` and `blockmax` skips, and the absence of overflow in the `i32` arithmetic (all tested against a direct transcription of thr and against brute force); and the containment of the band rules in the per-node rule.

- *Multidimensional knapsack interdiction.* Lemmas C.1 and C.3, Proposition C.2 and Theorem C.4 (`PackingInterdiction::lp_follower_bound` in `mkip.rs`); the merging, scaling and rounding of Theorem C.5 (`mkip::omega_root`, `mkip::tune_mu`, `mkip::omega_scales`); the local search; all floating-point evaluation.

- *Clique interdiction.* Lemma D.1; Brouwer's theorem (Theorem D.4) and Corollary D.5, which are neither proved nor assumed in Lean; Theorem D.6; Proposition D.7 and the 170 solver verdicts; that the instance files have the stated n, m and k and that each certificate partition has at most k inside edges (Lean takes these numbers as hypotheses).

- *Network interdiction.* Lemma F.1, Corollary F.2, Proposition F.3 (`fire::TreeDp::solve`) and Theorem F.4 (`fire::enumerate`).
- *General instances.* Theorem E.1 (`general::follower_unbounded_ray`, checked exactly by `scripts/verify_ray.py`) and Meyer's theorem; Lemma E.3 and the model comparison (`scripts/compare_hpr.py`); Proposition E.4 (`general::feasible_point`, `general::optimal_response`); Proposition E.5 and Lemma E.6 (`coupled::Search::evaluate`, `coupled::Search::best_response`, `coupled::certify`).

H. DATA PACKAGE AND FORMATS

Every result in the paper is backed by a file in the data package, the folder `bobilib/results/`. The package's index, `results/README.md`, follows the repository style of the INFORMS Journal on Computing (cite, description, data, file formats, verification, replication). The index, `instances.csv`, `bobilib_update.solu` and `SHA256SUMS` are written by `paper/scripts/build_data_package.py`; `make data` in `bobilib/paper/` regenerates them, together with the macros of every number quoted in the paper and the tables of Section I. BOBILib's statuses are those of its metadata snapshot of 18 October 2026.

H.1 Layout

Path	Contents
`instances.csv`	one row per BOBILib instance (2,654 rows); Section H.2
`bobilib_update.solu`	status changes and improved values in the MIPLIB/SCIP `.solu` format; Section H.3
`SHA256SUMS`	SHA-256 checksum of every other file of the package
`summary.json`	per-instance outcome and per-family counts
`kip/`	583 knapsack interdiction solution files at the published optima of Weninger and Fukasawa[9]
`ss/`	the 16 subset-sum optima proven here; `proofs.csv` (optimum, nodes, CPU seconds, nodes of the independent prover)
`or/`	690 verified points for the 810 OR instances; the bounds of each instance; `compare.csv` (published bounds, BOBILib's value, ours, gaps)
`clique/`	60 partition certificates, solver logs of the part-size proofs, the independent review
`network/`	36 attack-protect trees certified by enumeration; `summary.csv`; the review
`rays/`	41 recession directions (the 40 open instances and one that BOBILib lists as infeasible); `ray_verify.jsonl` (exact checks)
`general/`	64 points for MIPLIB-derived instances without coupling rows (nine files over 1 MB in `large_points.tar.gz`); `hpr_optimal.csv`
`general-coupled/`	29 points for MIPLIB-derived instances with coupling rows; `summary.csv`

Each folder has its own `README.md` with the method, the columns of its tables, the commands that produced it and, where one was done, its independent review.

H.2 The instance table `instances.csv`

The file is UTF-8, comma separated, with one header row and one row per BOBILib instance. Its columns:

Column	Meaning
`instance`	BOBILib instance name
`collection`	BOBILib sub-collection (last directory of the instance path), e.g. `kp`, `or`, `miplib2017`
`family`	`knapsack`, `multidim-knapsack`, `clique`, `network`, `generalized`, `assignment` (interdiction), `general-pure`, `general-mixed`
`bobilib_status`, `bobilib_value`	BOBILib's status and best known objective value (empty: none)
`new_status`	`optimal` (proven, in published work or here), `infeasible_bilevel` (no bilevel feasible point), `feasible` (first verified point; BOBILib had none), `unchanged`, `bobilib_optimal`, `bobilib_infeasible`
`primal_value`	best upper-level value backed by a verified solution file (of this package or of BOBILib) or by a published optimum
`dual_bound`	best proven lower bound (the leader minimises), if any
`source`	citation key of the published result (Table S2), `this work`, or `ThuraufEtAl2026` (BOBILib's own value)
`method`	how the status or value was obtained
`certificate`	path, relative to `results/`, of the solution or certificate file; `ARCHIVE.tar.gz:FILE` names a member of an archive
`verified`	`yes`: the certificate passed its check (`bobi verify`, or the exact ray check); `no`: checked in floating point only (the two `supportcase42` directions); `na`: no certificate in this package
`notes`	free text, separated by semicolons

Rows per `new_status`: 1,027 `bobilib_optimal`, 33 `bobilib_infeasible`, 608 `optimal`, 40 `infeasible_bilevel`, 230 `feasible` and 716 `unchanged`. The 608 optimal rows are the 527 published optima and the 81 proven here; together with the 40 rows without a bilevel feasible point they are the 648 settled instances. The keys of the `source` column map to the references as follows.

Table S2. Citation keys of the `source` column of `instances.csv`.

Key in `source`	Reference	Optima
`ThuraufEtAl2026`	BOBILib's own value[1]	
`WeningerFukasawa2025`	Weninger and Fukasawa[9]	376
`LozanoBergmanCire2026`	Lozano, Bergman and Cire[11]	96
`FischettiEtAl2019`	Fischetti, Ljubić, Monaci and Sinnl[10]	52
`FischettiEtAl2017`	Fischetti, Ljubić, Monaci and Sinnl[25]	1
`VasquezLozanoVanHoeve2025`	Vásquez, Lozano and van Hoeve[26]	1
`BOBILibEarlierRelease`	an earlier release of BOBILib's metadata[27]	1
`this work`	a certificate in this package	81

H.3 The status file `bobilib_update.solu`

The file follows the MIPLIB/SCIP convention, one line per instance whose status differs from BOBILib's metadata or whose best value improves:

`=opt=`	*name value*	proven optimal value (published, or proven here)
`=inf=`	*name*	no bilevel feasible point (the follower is unbounded for every leader choice)
`=best=`	*name value*	best verified bilevel feasible point (a solution file here), not proven optimal
`=bestdual=`	*name value*	best proven lower bound, where this work proves a better one than any published

It has 608 `=opt=` lines (527 published, 81 from this work), 40 `=inf=`, 695 `=best=` and 194 `=bestdual=` lines. The `=bestdual=` lines are the 191 OR instances with one follower knapsack and the 3 open clique

instances; an instance can have both a `=best=` and a `=bestdual=` line. Every value is the upper-level objective $c^\top x + d^\top y$ of the minimising leader under the optimistic convention, printed at full precision (integers without a decimal point, other values as the shortest decimal that reads back as the same double). Comment lines start with `#`.

H.4 Solution files

Solution files (`*.res.json`) are in BOBILib's own format, so BOBILib's checker and `bobi verify` read them unchanged. Each is a JSON object with the fields `name`, `bilevel_type` (always `optimistic`), `status` (`optimal` or `feasible`), `difficulty`, `objective_value` (the upper-level objective, which BOBILib minimises), and `upper_level_decisions` and `lower_level_decisions`, which map every variable name of the instance to its value. A file states `optimal` only when the instance's row in `instances.csv` has `new_status optimal`.

H.5 Certificates

Recession directions. `rays/*.ray.json` maps follower variable names to the entries of a direction d (its support only), as decimal numbers; `*.exact.ray.json` holds exact rationals written as `"p/q"`. The certificate is valid if d satisfies the conditions of Theorem E.1: for every follower row, with the leader terms and right-hand side dropped, $a^\top d \leq 0$ for a row $a^\top y \leq \cdot$, $a^\top d \geq 0$ for a row $a^\top y \geq \cdot$ and $a^\top d = 0$ for an equation; $d_j \geq 0$ for a finite lower bound and $d_j \leq 0$ for a finite upper bound; and $f^\top d < 0$. `scripts/verify_ray.py` checks this in rational arithmetic and writes `rays/ray_verify.jsonl`.

Partitions. The clique solution files are the certificates: the leader deletes exactly the edges inside the parts of an r-partition (at most k of them), so the remainder is r-partite (Proposition D.3), and the follower part is a maximum clique of the remainder. `clique/summary.csv` gives per instance n, the density, m, k, BOBILib's value, the lower bound with its argument (Mantel, or Brouwer's theorem with the part-size proofs) and the upper bound with its partition. The logs of the solver runs behind the 170 part-size proofs are in `clique/logs/lb_solver_logs.tar.gz`.

Subset-sum proofs. A proof of OPT $\geq \ell$ is a computation, not a file. `ss/proofs.csv` records, per instance, the optimum, the nodes and CPU seconds of the search and the nodes of the independent prover `scripts/ss_check.py`, which re-proves the bound from the instance files (Section A.3).

Enumerations and HPR bounds. `network/summary.csv` gives per tree the attacks enumerated, the optimum, the number of optimal attacks and the cross-checks (Theorem F.4). `general/hpr_optimal.csv` lists the points that meet the MIPLIB optimum of the HPR; `scripts/compare_hpr.py` re-checks that the HPR is the MIPLIB model (Lemma E.3).

OR bounds. `or/bounds_one_knapsack.jsonl` gives, per instance with one follower knapsack, the lower bound with its two parts (merged-row online bound, Theorem C.5, and LP bracket, Theorem C.4) and the upper bound; `or/points_several_knapsacks.jsonl` gives, per instance with several follower knapsacks, the bracket minimiser's LP bound and the certified follower value.

H.6 Checksums and how to check the package

`SHA256SUMS` has one line per file of the package other than itself, sorted by path, in the format of `sha256sum`. With BOBILib's instance files in `data/collection` (from `bobilib.org`) and the `bobi` crate built, the following commands, run from `bobilib/`, repeat the checks of Section A.3:

```
(cd results && sha256sum -c SHA256SUMS)
D=data/collection
./target/release/bobi verify --instances $D results/kip results/ss results/network results/or
./target/release/bobi verify --instances $D --generic results/clique results/general \
    results/general-coupled
python3 -I scripts/verify_ray.py INSTANCE.mps.gz INSTANCE.aux results/rays/INSTANCE.ray.json
python3 -I scripts/ss_check.py INSTANCE.mps.gz INSTANCE.aux - OPTIMUM
python3 -I scripts/compare_hpr.py INSTANCE.mps.gz INSTANCE.aux MIPLIB.mps.gz
```

The nine large general points are checked after unpacking `general/large_points.tar.gz`.

I. PER-INSTANCE TABLES

The tables below are generated from the data package by `paper/scripts/gen_appendix_tables.py`. Values are upper-level objectives of the minimising leader; full-precision values and the certificate of every row are in `instances.csv` (Section H.2). The order follows the paper: published optima (Table S3); knapsack interdiction (Table S4); the OR set (Table S5); clique interdiction (Table S6); network interdiction (Tables S7 and S8); general instances without a feasible point (Table S9), with an HPR-bound optimum (Table S10) and with a first point (Table S11); and the instances whose status is unchanged (Table S12).

I.1 Published optima

Table S3. Published optima for instances BOBILib lists as feasible or open, by source (sub-collection and count). The instance names follow.

Source	Collections	Instances
Weninger and Fukasawa (2025), combinatorial branch and bound	kp 336, inter-kp 25, cclw 15	376
Lozano, Bergman and Cire (2026), decision-diagram relaxations	or 87, miplib3 5, generalized 4	96
Fischetti, Ljubić, Monaci and Sinnl (2019), interdiction cuts	imkp 52	52
earlier BOBILib release (listed optimal there)	miplib2017 1	1
Fischetti, Ljubić, Monaci and Sinnl (2017), MIX++	miplib3 1	1
Vásquez, Lozano and van Hoeve (2025), decision diagrams	miplib3 1	1
Total		527

Weninger and Fukasawa (2025), combinatorial branch and bound (376)

interdiction40-5	interKP-100-100-1-5	interKP-100-100-3-9	interKP-100-100-6-5
interdiction40-6	interKP-100-100-1-6	interKP-100-100-4-2	interKP-100-100-6-6
interdiction45-4	interKP-100-100-1-7	interKP-100-100-4-3	interKP-100-100-6-7
interdiction45-5	interKP-100-100-1-8	interKP-100-100-4-4	interKP-100-100-6-8
interdiction45-6	interKP-100-100-2-1	interKP-100-100-4-5	interKP-100-100-7-2
interdiction50-3	interKP-100-100-2-2	interKP-100-100-4-6	interKP-100-100-7-3
interdiction50-4	interKP-100-100-2-3	interKP-100-100-4-7	interKP-100-100-7-4
interdiction50-5	interKP-100-100-2-4	interKP-100-100-4-8	interKP-100-100-7-5
interdiction50-7	interKP-100-100-2-5	interKP-100-100-5-1	interKP-100-100-7-6
interdiction55-3	interKP-100-100-2-6	interKP-100-100-5-2	interKP-100-100-7-7
interdiction55-4	interKP-100-100-2-7	interKP-100-100-5-3	interKP-100-100-7-8
interdiction55-5	interKP-100-100-3-1	interKP-100-100-5-4	interKP-100-100-8-1
interdiction55-6	interKP-100-100-3-2	interKP-100-100-5-5	interKP-100-100-8-2
interdiction55-7	interKP-100-100-3-3	interKP-100-100-5-6	interKP-100-100-8-3
interdiction55-8	interKP-100-100-3-4	interKP-100-100-5-7	interKP-100-100-8-4
interKP-100-100-1-1	interKP-100-100-3-5	interKP-100-100-5-8	interKP-100-100-8-5
interKP-100-100-1-2	interKP-100-100-3-6	interKP-100-100-6-2	interKP-100-100-8-6
interKP-100-100-1-3	interKP-100-100-3-7	interKP-100-100-6-3	interKP-100-100-8-7
interKP-100-100-1-4	interKP-100-100-3-8	interKP-100-100-6-4	interKP-100-100-8-8

interKP-100-100-8-9
interKP-200-100-1-1
interKP-200-100-1-2
interKP-200-100-1-3
interKP-200-100-1-4
interKP-200-100-1-5
interKP-200-100-1-6
interKP-200-100-1-7
interKP-200-100-1-8
interKP-200-100-1-9
interKP-200-100-2-1
interKP-200-100-2-2
interKP-200-100-2-3
interKP-200-100-2-4
interKP-200-100-2-5
interKP-200-100-2-6
interKP-200-100-2-7
interKP-200-100-2-8
interKP-200-100-3-1
interKP-200-100-3-2
interKP-200-100-3-3
interKP-200-100-3-4
interKP-200-100-3-5
interKP-200-100-3-6
interKP-200-100-3-7
interKP-200-100-3-8
interKP-200-100-3-9
interKP-200-100-4-1
interKP-200-100-4-2
interKP-200-100-4-3
interKP-200-100-4-4
interKP-200-100-4-5
interKP-200-100-4-6
interKP-200-100-4-7
interKP-200-100-5-1
interKP-200-100-5-2
interKP-200-100-5-3
interKP-200-100-5-4
interKP-200-100-5-5
interKP-200-100-5-6
interKP-200-100-5-7
interKP-200-100-5-8
interKP-200-100-5-9
interKP-200-100-6-1
interKP-200-100-6-4
interKP-200-100-6-5
interKP-200-100-6-6
interKP-200-100-6-7
interKP-200-100-6-8
interKP-200-100-6-9
interKP-200-100-7-1
interKP-200-100-7-4
interKP-200-100-7-5
interKP-200-100-7-6
interKP-200-100-7-7
interKP-200-100-7-8
interKP-200-100-7-9
interKP-200-100-8-1
interKP-200-100-8-2
interKP-200-100-8-3
interKP-200-100-8-4
interKP-200-100-8-5
interKP-200-100-8-6
interKP-200-100-8-7
interKP-200-100-8-8
interKP-200-100-8-9
interKP-300-100-1-1
interKP-300-100-1-2
interKP-300-100-1-3
interKP-300-100-1-4
interKP-300-100-1-5
interKP-300-100-1-6
interKP-300-100-1-7
interKP-300-100-1-8
interKP-300-100-1-9
interKP-300-100-2-1
interKP-300-100-2-2
interKP-300-100-2-3
interKP-300-100-2-4
interKP-300-100-2-5
interKP-300-100-2-6
interKP-300-100-2-7
interKP-300-100-2-8
interKP-300-100-2-9
interKP-300-100-3-1
interKP-300-100-3-2
interKP-300-100-3-3
interKP-300-100-3-4
interKP-300-100-3-5
interKP-300-100-3-6
interKP-300-100-3-7
interKP-300-100-3-8
interKP-300-100-3-9
interKP-300-100-4-1
interKP-300-100-4-2
interKP-300-100-4-3
interKP-300-100-4-4
interKP-300-100-4-5
interKP-300-100-4-6
interKP-300-100-4-7
interKP-300-100-5-1
interKP-300-100-5-2
interKP-300-100-5-3
interKP-300-100-5-4
interKP-300-100-5-5
interKP-300-100-5-6
interKP-300-100-5-7
interKP-300-100-5-8
interKP-300-100-5-9
interKP-300-100-6-1
interKP-300-100-6-4
interKP-300-100-6-5
interKP-300-100-6-6
interKP-300-100-6-7
interKP-300-100-6-8
interKP-300-100-6-9
interKP-300-100-7-1
interKP-300-100-7-4
interKP-300-100-7-5
interKP-300-100-7-6
interKP-300-100-7-7
interKP-300-100-7-8
interKP-300-100-8-1
interKP-300-100-8-2
interKP-300-100-8-3
interKP-300-100-8-4
interKP-300-100-8-5
interKP-300-100-8-6
interKP-300-100-8-7
interKP-300-100-8-8
interKP-300-100-8-9
interKP-400-100-1-1
interKP-400-100-1-2
interKP-400-100-1-3
interKP-400-100-1-4
interKP-400-100-1-5
interKP-400-100-1-6
interKP-400-100-1-7
interKP-400-100-1-8
interKP-400-100-1-9
interKP-400-100-1-10
interKP-400-100-2-1
interKP-400-100-2-2
interKP-400-100-2-3
interKP-400-100-2-4
interKP-400-100-2-5
interKP-400-100-2-6
interKP-400-100-2-7
interKP-400-100-2-8
interKP-400-100-2-9
interKP-400-100-2-10
interKP-400-100-3-1
interKP-400-100-3-2
interKP-400-100-3-3
interKP-400-100-3-4
interKP-400-100-3-5
interKP-400-100-3-6
interKP-400-100-3-7
interKP-400-100-3-8
interKP-400-100-3-9
interKP-400-100-4-1
interKP-400-100-4-2
interKP-400-100-4-3
interKP-400-100-4-4
interKP-400-100-4-5
interKP-400-100-4-6
interKP-400-100-4-7
interKP-400-100-4-8
interKP-400-100-5-1
interKP-400-100-5-2
interKP-400-100-5-3
interKP-400-100-5-4
interKP-400-100-5-5
interKP-400-100-5-6
interKP-400-100-5-7
interKP-400-100-5-8
interKP-400-100-5-9
interKP-400-100-5-10
interKP-400-100-6-1
interKP-400-100-6-4
interKP-400-100-6-5
interKP-400-100-6-6
interKP-400-100-6-7
interKP-400-100-6-8
interKP-400-100-6-9
interKP-400-100-7-1
interKP-400-100-7-4
interKP-400-100-7-5
interKP-400-100-7-6
interKP-400-100-7-7
interKP-400-100-7-8
interKP-400-100-7-9
interKP-400-100-8-1
interKP-400-100-8-2
interKP-400-100-8-3
interKP-400-100-8-4
interKP-400-100-8-5
interKP-400-100-8-6
interKP-400-100-8-7
interKP-400-100-8-8
interKP-400-100-8-9
interKP-500-100-1-1
interKP-500-100-1-2
interKP-500-100-1-3
interKP-500-100-1-4
interKP-500-100-1-5
interKP-500-100-1-6
interKP-500-100-1-7
interKP-500-100-1-8
interKP-500-100-1-9
interKP-500-100-1-10
interKP-500-100-2-1
interKP-500-100-2-2
interKP-500-100-2-3
interKP-500-100-2-4
interKP-500-100-2-5
interKP-500-100-2-6
interKP-500-100-2-7
interKP-500-100-2-8
interKP-500-100-2-9
interKP-500-100-2-10
interKP-500-100-3-1
interKP-500-100-3-2
interKP-500-100-3-3
interKP-500-100-3-4
interKP-500-100-3-5
interKP-500-100-3-6
interKP-500-100-3-7
interKP-500-100-3-8
interKP-500-100-3-9
interKP-500-100-3-10
interKP-500-100-4-1
interKP-500-100-4-2
interKP-500-100-4-3
interKP-500-100-4-4
interKP-500-100-4-5

interKP-500-100-4-6	interKP-500-100-6-6	interKP-500-100-8-4	K5050W05.KNP
interKP-500-100-4-7	interKP-500-100-6-7	interKP-500-100-8-5	K5050W06.KNP
interKP-500-100-4-8	interKP-500-100-6-8	interKP-500-100-8-6	K5050W07.KNP
interKP-500-100-5-1	interKP-500-100-6-9	interKP-500-100-8-7	K5050W08.KNP
interKP-500-100-5-2	interKP-500-100-6-10	interKP-500-100-8-8	K5050W09.KNP
interKP-500-100-5-3	interKP-500-100-7-1	interKP-500-100-8-9	K5050W10.KNP
interKP-500-100-5-4	interKP-500-100-7-4	interKP-500-100-8-10	K5050W11.KNP
interKP-500-100-5-5	interKP-500-100-7-5	K5040W01.KNP	K5050W12.KNP
interKP-500-100-5-6	interKP-500-100-7-6	K5040W05.KNP	K5050W13.KNP
interKP-500-100-5-7	interKP-500-100-7-7	K5040W08.KNP	K5050W14.KNP
interKP-500-100-5-8	interKP-500-100-7-8	K5040W15.KNP	K5050W15.KNP
interKP-500-100-5-9	interKP-500-100-7-9	K5040W19.KNP	K5050W16.KNP
interKP-500-100-5-10	interKP-500-100-7-10	K5050W01.KNP	K5050W17.KNP
interKP-500-100-6-1	interKP-500-100-8-1	K5050W02.KNP	K5050W18.KNP
interKP-500-100-6-4	interKP-500-100-8-2	K5050W03.KNP	K5050W19.KNP
interKP-500-100-6-5	interKP-500-100-8-3	K5050W04.KNP	K5050W20.KNP

Lozano, Bergman and Cire (2026), decision-diagram relaxations (96)

general30-30-10-20-20-8	OR5x100-0.75_7.dat-50	OR5x250-0.75_5.dat-50	OR10x100-0.75_6.dat-100
general30-30-20-20-20-9	OR5x100-0.75_7.dat-100	OR5x250-0.75_5.dat-100	OR10x100-0.75_7.dat-0
general30-30-30-20-20-9	OR5x100-0.75_8.dat-0	OR5x250-0.75_6.dat-0	OR10x100-0.75_7.dat-100
general30-30-30-20-20-10	OR5x100-0.75_8.dat-50	OR5x250-0.75_6.dat-50	OR10x100-0.75_8.dat-0
lseu-0.500000	OR5x100-0.75_8.dat-100	OR5x250-0.75_6.dat-100	OR10x100-0.75_8.dat-100
OR5x100-0.75_1.dat-0	OR5x100-0.75_9.dat-0	OR5x250-0.75_7.dat-0	OR10x100-0.75_9.dat-0
OR5x100-0.75_1.dat-50	OR5x100-0.75_9.dat-50	OR5x250-0.75_7.dat-50	OR10x100-0.75_9.dat-100
OR5x100-0.75_1.dat-100	OR5x100-0.75_9.dat-100	OR5x250-0.75_7.dat-100	OR10x100-0.75_10.dat-100
OR5x100-0.75_2.dat-0	OR5x100-0.75_10.dat-0	OR5x250-0.75_8.dat-0	OR10x250-0.75_1.dat-100
OR5x100-0.75_2.dat-50	OR5x100-0.75_10.dat-50	OR5x250-0.75_8.dat-50	OR10x250-0.75_6.dat-100
OR5x100-0.75_2.dat-100	OR5x100-0.75_10.dat-100	OR5x250-0.75_8.dat-100	OR10x250-0.75_7.dat-100
OR5x100-0.75_3.dat-0	OR5x250-0.75_1.dat-0	OR5x250-0.75_9.dat-0	OR30x100-0.75_1.dat-100
OR5x100-0.75_3.dat-50	OR5x250-0.75_1.dat-50	OR5x250-0.75_9.dat-50	OR30x100-0.75_2.dat-100
OR5x100-0.75_3.dat-100	OR5x250-0.75_1.dat-100	OR5x250-0.75_9.dat-100	OR30x100-0.75_3.dat-100
OR5x100-0.75_4.dat-0	OR5x250-0.75_2.dat-0	OR5x250-0.75_10.dat-0	OR30x100-0.75_4.dat-100
OR5x100-0.75_4.dat-50	OR5x250-0.75_2.dat-50	OR5x250-0.75_10.dat-50	OR30x100-0.75_5.dat-0
OR5x100-0.75_4.dat-100	OR5x250-0.75_2.dat-100	OR5x250-0.75_10.dat-100	OR30x100-0.75_5.dat-100
OR5x100-0.75_5.dat-0	OR5x250-0.75_3.dat-0	OR10x100-0.75_1.dat-100	OR30x100-0.75_6.dat-100
OR5x100-0.75_5.dat-50	OR5x250-0.75_3.dat-50	OR10x100-0.75_2.dat-0	OR30x100-0.75_7.dat-100
OR5x100-0.75_5.dat-100	OR5x250-0.75_3.dat-100	OR10x100-0.75_2.dat-100	OR30x100-0.75_8.dat-100
OR5x100-0.75_6.dat-0	OR5x250-0.75_4.dat-0	OR10x100-0.75_3.dat-100	p0201-0.100000
OR5x100-0.75_6.dat-50	OR5x250-0.75_4.dat-50	OR10x100-0.75_4.dat-100	p0282-0.900000
OR5x100-0.75_6.dat-100	OR5x250-0.75_4.dat-100	OR10x100-0.75_5.dat-100	p0548-0.100000
OR5x100-0.75_7.dat-0	OR5x250-0.75_5.dat-0	OR10x100-0.75_6.dat-0	p0548-0.900000

Fischetti, Ljubić, Monaci and Sinnl (2019), interdiction cuts (52)

pet7.dat-0	weish17.dat-50	weish21.dat-0	weish24.dat-100	weish28.dat-50
pet7.dat-50	weish17.dat-100	weish21.dat-50	weish25.dat-0	weish28.dat-100
pet7.dat-100	weish18.dat-0	weish21.dat-100	weish25.dat-50	weish29.dat-0
sento2.dat-50	weish18.dat-50	weish22.dat-0	weish25.dat-100	weish29.dat-50
sento2.dat-100	weish18.dat-100	weish22.dat-50	weish26.dat-0	weish29.dat-100
weish14.dat-0	weish19.dat-0	weish22.dat-100	weish26.dat-50	weish30.dat-0
weish14.dat-50	weish19.dat-50	weish23.dat-0	weish26.dat-100	weish30.dat-50
weish14.dat-100	weish19.dat-100	weish23.dat-50	weish27.dat-0	weish30.dat-100
weish16.dat-0	weish20.dat-0	weish23.dat-100	weish27.dat-50	
weish16.dat-50	weish20.dat-50	weish24.dat-0	weish27.dat-100	
weish16.dat-100	weish20.dat-100	weish24.dat-50	weish28.dat-0	

Earlier BOBILib release (listed optimal there) (1)

neos-950242_0_100

Fischetti, Ljubić, Monaci and Sinnl (2017), MIX++ (1)

air03-0.100000

Vásquez, Lozano and van Hoeve (2025), decision diagrams (1)

p0282-0.500000

I.2 Knapsack interdiction

Table S4. The 16 knapsack interdiction instances without a published optimum, all proven optimal here by the robust subset-sum search. n: items; class 6: subset sum ($p = w$), class 7: even weights and odd capacity; budget index as in the instance name. Nodes and CPU seconds of `bobi ss-solve` on one thread of a shared machine; independent prover: nodes of `scripts/ss_check.py`, which shares no code with the search. BOBILib's value was already optimal in every case.

Instance	n	Class	Budget	BOBILib	Optimum	Nodes	CPU (s)	Indep. nodes
interKP-200-100-6-2	200	6	2	1,855	1,855	303	0.10	303
interKP-300-100-6-2	300	6	2	2,868	2,868	366	0.16	366
interKP-400-100-6-2	400	6	2	3,832	3,832	257	0.15	257
interKP-500-100-6-2	500	6	2	4,651	4,651	190	0.26	190
interKP-200-100-6-3	200	6	3	2,782	2,782	13,498	3.93	13,502
interKP-300-100-6-3	300	6	3	4,302	4,302	19,405	8.06	19,537
interKP-400-100-6-3	400	6	3	5,748	5,748	13,430	9.01	13,583
interKP-500-100-6-3	500	6	3	6,976	6,976	10,079	10.04	10,116
interKP-200-100-7-2	200	7	2	1,872	1,872	22	0.06	22
interKP-300-100-7-2	300	7	2	2,894	2,894	27	0.04	27
interKP-400-100-7-2	400	7	2	3,866	3,866	18	0.05	18
interKP-500-100-7-2	500	7	2	4,694	4,694	1	0.05	1
interKP-200-100-7-3	200	7	3	2,808	2,808	651	0.10	651
interKP-300-100-7-3	300	7	3	4,340	4,340	470	0.20	470
interKP-400-100-7-3	400	7	3	5,800	5,800	378	0.17	378
interKP-500-100-7-3	500	7	3	7,042	7,042	256	0.15	256

I.3 The OR set

Table S5. All 810 multidimensional knapsack interdiction instances of the OR set; names have the form `OR`*rows*`x`*items*`-`*budget*`_`*i*`.dat-`*variant*. Budget: leader budget in percent of the item weights; follower rows: knapsack rows of the follower (variant -100: one; -0 and -50: several). Published LB: Lozano, Bergman and Cire (2026); published UB: best published point; BOBILib: BOBILib's best known value; our LB: dualised follower LP bracket or merged-row online bound (one follower knapsack only); our point: verified solution file; gap: (best upper bound − best lower bound)/best upper bound in percent, where the best upper bound may be the follower LP bound at our leader choice (100: no lower bound known). Blank: none. †: the published lower bound exceeds the published point (inconsistent sources); the gap then leaves the published point out, and OR10x100-0.75_4.dat-0 is closed at 8,813, the authors' branch-and-cut bound.

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x100-0.25_1.dat-0	25	4	16,014	20,321	21,879		19,956	19.75
OR5x100-0.25_2.dat-0	25	4	15,984	20,174	22,491		19,943	19.85
OR5x100-0.25_3.dat-0	25	4	15,180	19,538	21,738		19,312	21.40

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x100-0.25_4.dat-0	25	4	16,092	20,786	22,263		20,353	20.94
OR5x100-0.25_5.dat-0	25	4	15,645	20,356	21,965		19,957	21.61
OR5x100-0.25_6.dat-0	25	4	16,312	20,774	22,601		20,235	19.39
OR5x100-0.25_7.dat-0	25	4	16,257	20,848	22,905		20,484	20.64
OR5x100-0.25_8.dat-0†	25	4	15,874	10,859	22,343		19,849	20.03
OR5x100-0.25_9.dat-0	25	4	16,103	20,661	22,294		20,382	20.99
OR5x100-0.25_10.dat-0	25	4	16,095	20,912	22,698		20,967	23.03
OR5x100-0.25_1.dat-50	25	2	17,464	21,887	23,044		21,569	19.03
OR5x100-0.25_2.dat-50	25	2	17,711	21,621	23,112		21,219	16.53
OR5x100-0.25_3.dat-50	25	2	17,082	21,405	22,880		20,930	18.39
OR5x100-0.25_4.dat-50	25	2	16,472	21,595	22,781		21,439	23.17
OR5x100-0.25_5.dat-50	25	2	16,576	21,031	21,738		20,621	19.62
OR5x100-0.25_6.dat-50	25	2	18,143	22,689	24,519		22,527	19.46
OR5x100-0.25_7.dat-50†	25	2	17,106	16,951	23,302		22,125	22.68
OR5x100-0.25_8.dat-50	25	2	17,155	21,697	22,739		21,330	19.57
OR5x100-0.25_9.dat-50	25	2	17,061	21,121	22,661		20,882	18.30
OR5x100-0.25_10.dat-50	25	2	18,212	22,642	23,881		22,543	19.21
OR5x100-0.25_1.dat-100	25	1	20,026	24,034	24,489	23,062	23,482	1.79
OR5x100-0.25_2.dat-100	25	1	18,986	22,045	22,393	21,401	21,750	1.60
OR5x100-0.25_3.dat-100	25	1	19,494	22,455	23,303	21,768	22,110	1.55
OR5x100-0.25_4.dat-100	25	1	20,713	24,754	25,202	24,026	24,260	0.96
OR5x100-0.25_5.dat-100	25	1	19,603	23,666	24,344	22,599	23,026	1.85
OR5x100-0.25_6.dat-100	25	1	19,923	23,962	24,483	23,103	23,431	1.40
OR5x100-0.25_7.dat-100	25	1	21,157	25,569	26,905	24,642	24,958	1.27
OR5x100-0.25_8.dat-100	25	1	20,006	23,937	25,286	23,135	23,514	1.61
OR5x100-0.25_9.dat-100	25	1	20,298	24,653	25,199	23,862	24,184	1.33
OR5x100-0.25_10.dat-100	25	1	19,389	23,831	24,840	22,970	23,242	1.17
OR5x100-0.50_1.dat-0	50	4	18,975	23,672	27,489		19,785	4.09
OR5x100-0.50_2.dat-0	50	4	19,757	22,821	27,526		21,265	7.09
OR5x100-0.50_3.dat-0	50	4	19,204	23,929	25,707		21,226	9.53
OR5x100-0.50_4.dat-0	50	4	20,704	24,066	30,878		21,779	4.94
OR5x100-0.50_5.dat-0	50	4	18,942	22,742	26,240		21,172	10.53
OR5x100-0.50_6.dat-0	50	4	17,608	23,765	30,318		22,019	20.03
OR5x100-0.50_7.dat-0	50	4	18,963	22,721	29,946		21,030	9.83
OR5x100-0.50_8.dat-0	50	4	20,364	23,945	29,893		22,283	8.61
OR5x100-0.50_9.dat-0	50	4	19,037	24,888	32,863		23,465	18.87
OR5x100-0.50_10.dat-0	50	4	19,569	25,360	27,107		22,596	13.40
OR5x100-0.50_1.dat-50	50	2	21,207	30,496	33,475		29,651	28.48
OR5x100-0.50_2.dat-50	50	2	20,796	30,461	32,306		28,254	26.40
OR5x100-0.50_3.dat-50	50	2	20,033	30,123	31,051		28,000	28.45
OR5x100-0.50_4.dat-50	50	2	21,539	31,945	33,225		29,334	26.57
OR5x100-0.50_5.dat-50	50	2	20,100	29,003	31,008		27,882	27.91
OR5x100-0.50_6.dat-50	50	2	19,414	27,930	30,410		27,331	28.97
OR5x100-0.50_7.dat-50	50	2	19,888	28,098	31,826		26,901	26.07
OR5x100-0.50_8.dat-50	50	2	21,341	30,971	34,206		29,952	28.75
OR5x100-0.50_9.dat-50	50	2	19,847	31,902	33,819		29,032	31.64
OR5x100-0.50_10.dat-50	50	2	19,879	31,436	31,881		29,152	31.81
OR5x100-0.50_1.dat-100	50	1	20,708	30,100	31,172	28,108	29,437	4.51
OR5x100-0.50_2.dat-100	50	1	20,894	29,084	30,477	27,660	28,530	3.05
OR5x100-0.50_3.dat-100	50	1	22,308	29,545	29,887	27,960	28,767	2.81
OR5x100-0.50_4.dat-100	50	1	21,678	31,632	32,359	29,107	30,499	4.56
OR5x100-0.50_5.dat-100	50	1	20,966	28,955	29,142	27,322	28,269	3.35
OR5x100-0.50_6.dat-100	50	1	19,588	28,598	28,746	26,699	27,621	3.34
OR5x100-0.50_7.dat-100	50	1	22,087	28,623	30,947	26,727	27,915	4.26

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x100-0.50_8.dat-100	50	1	21,521	31,740	33,174	29,358	30,424	3.50
OR5x100-0.50_9.dat-100	50	1	20,773	30,871	31,618	28,251	29,163	3.13
OR5x100-0.50_10.dat-100	50	1	23,071	30,367	30,448	28,292	29,232	3.22
OR5x100-0.75_1.dat-0	75	4	8,855	8,855	9,350		8,855	0.00
OR5x100-0.75_2.dat-0	75	4	11,323	11,323	12,841		11,323	0.00
OR5x100-0.75_3.dat-0	75	4	9,344	9,344	10,231		9,344	0.00
OR5x100-0.75_4.dat-0	75	4	9,098	9,098	10,126		9,098	0.00
OR5x100-0.75_5.dat-0	75	4	8,492	8,492	8,895		8,492	0.00
OR5x100-0.75_6.dat-0	75	4	8,775	8,775	10,651		8,775	0.00
OR5x100-0.75_7.dat-0	75	4	8,596	8,596	9,311		8,596	0.00
OR5x100-0.75_8.dat-0	75	4	9,712	9,712	10,945		9,712	0.00
OR5x100-0.75_9.dat-0	75	4	9,212	9,212	9,964		9,212	0.00
OR5x100-0.75_10.dat-0	75	4	8,785	8,785	9,089		8,785	0.00
OR5x100-0.75_1.dat-50	75	2	12,477	12,477	13,783		12,477	0.00
OR5x100-0.75_2.dat-50	75	2	13,354	13,354	14,941		13,354	0.00
OR5x100-0.75_3.dat-50	75	2	12,774	12,774	14,365		12,774	0.00
OR5x100-0.75_4.dat-50	75	2	13,086	13,086	15,331		13,086	0.00
OR5x100-0.75_5.dat-50	75	2	12,907	12,907	15,056		12,907	0.00
OR5x100-0.75_6.dat-50	75	2	12,060	12,060	13,522		12,060	0.00
OR5x100-0.75_7.dat-50	75	2	13,344	13,344	14,571		13,344	0.00
OR5x100-0.75_8.dat-50	75	2	13,364	13,364	15,170		13,364	0.00
OR5x100-0.75_9.dat-50	75	2	12,077	12,077	13,567		12,077	0.00
OR5x100-0.75_10.dat-50	75	2	12,824	12,824	14,457		12,824	0.00
OR5x100-0.75_1.dat-100	75	1	13,104	13,104	14,018	11,988	13,104	0.00
OR5x100-0.75_2.dat-100	75	1	14,603	14,603	16,122	13,373	14,603	0.00
OR5x100-0.75_3.dat-100	75	1	13,214	13,214	14,408	12,092	13,214	0.00
OR5x100-0.75_4.dat-100	75	1	13,555	13,555	15,053	12,414	13,555	0.00
OR5x100-0.75_5.dat-100	75	1	13,604	13,604	15,116	12,380	13,604	0.00
OR5x100-0.75_6.dat-100	75	1	12,929	12,929	14,960	11,795	12,929	0.00
OR5x100-0.75_7.dat-100	75	1	14,103	14,103	15,902	12,877	14,103	0.00
OR5x100-0.75_8.dat-100	75	1	14,004	14,004	15,169	12,822	14,004	0.00
OR5x100-0.75_9.dat-100	75	1	12,783	12,783	14,027	11,708	12,783	0.00
OR5x100-0.75_10.dat-100	75	1	13,322	13,322	14,702	12,137	13,322	0.00
OR5x250-0.25_1.dat-0	25	4	34,494	51,621	54,798		50,291	31.41
OR5x250-0.25_2.dat-0	25	4	36,022	53,453	56,258			31.34
OR5x250-0.25_3.dat-0	25	4	35,700	53,506	56,308			31.79
OR5x250-0.25_4.dat-0	25	4	35,239	52,573	55,907			32.97
OR5x250-0.25_5.dat-0	25	4	33,896	51,603	54,740			31.28
OR5x250-0.25_6.dat-0	25	4	34,604	51,849	55,007			33.26
OR5x250-0.25_7.dat-0	25	4	35,740	54,014	55,294		52,020	31.30
OR5x250-0.25_8.dat-0	25	4	36,632	55,028	57,526		53,918	32.06
OR5x250-0.25_9.dat-0	25	4	35,282	52,910	55,996			32.14
OR5x250-0.25_10.dat-0	25	4	35,280	52,031	55,196			30.58
OR5x250-0.25_1.dat-50	25	2	38,082	53,836	55,192		52,384	27.30
OR5x250-0.25_2.dat-50	25	2	39,285	55,748	57,851		54,668	28.14
OR5x250-0.25_3.dat-50	25	2	38,444	55,392	57,004		53,485	28.12
OR5x250-0.25_4.dat-50	25	2	38,716	56,262	57,428		54,753	29.29
OR5x250-0.25_5.dat-50	25	2	38,560	55,651	55,884		53,890	28.45
OR5x250-0.25_6.dat-50	25	2	40,088	56,250	58,016		54,875	26.95
OR5x250-0.25_7.dat-50	25	2	40,961	57,130	59,607		56,511	27.52
OR5x250-0.25_8.dat-50	25	2	39,968	58,725	60,600		57,002	29.88
OR5x250-0.25_9.dat-50	25	2	38,919	56,112	57,882		55,402	29.75
OR5x250-0.25_10.dat-50	25	2	37,815	53,686	55,473		52,645	28.17
OR5x250-0.25_1.dat-100	25	1	46,075	60,613	61,601	56,913	58,410	2.56

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x250-0.25_2.dat-100	25	1	45,538	59,501	60,499	56,239	57,402	2.03
OR5x250-0.25_3.dat-100	25	1	43,947	58,421	59,396	54,982	56,343	2.42
OR5x250-0.25_4.dat-100	25	1	44,916	59,212	59,212	55,270	56,933	2.92
OR5x250-0.25_5.dat-100	25	1	45,370	59,118	59,118	55,404	56,943	2.70
OR5x250-0.25_6.dat-100	25	1	46,901	62,072	63,066	57,987	59,284	2.19
OR5x250-0.25_7.dat-100	25	1	48,069	63,569	63,569	59,937	61,611	2.72
OR5x250-0.25_8.dat-100	25	1	45,860	60,675	60,675	57,505	58,769	2.15
OR5x250-0.25_9.dat-100	25	1	46,112	60,663	60,911	57,097	58,528	2.44
OR5x250-0.25_10.dat-100	25	1	47,795	61,775	61,847	57,576	59,133	2.63
OR5x250-0.50_1.dat-0	50	4	40,069	64,651	84,711		57,509	30.33
OR5x250-0.50_2.dat-0	50	4	38,908	62,186	85,349		54,525	28.64
OR5x250-0.50_3.dat-0	50	4	37,954	59,247	76,226		52,500	27.71
OR5x250-0.50_4.dat-0	50	4	40,005	65,156	84,713		59,307	32.55
OR5x250-0.50_5.dat-0	50	4	40,847	64,714	88,188		58,188	29.80
OR5x250-0.50_6.dat-0	50	4	40,393	63,384	84,965		55,904	27.75
OR5x250-0.50_7.dat-0	50	4	39,146	62,593	87,174		55,731	29.76
OR5x250-0.50_8.dat-0	50	4	39,927	62,174	88,969		56,029	28.74
OR5x250-0.50_9.dat-0	50	4	39,676	63,075	87,710		56,625	29.93
OR5x250-0.50_10.dat-0	50	4	38,309	60,764	90,119		54,001	29.06
OR5x250-0.50_1.dat-50	50	2	47,812	81,492	83,288		73,732	35.15
OR5x250-0.50_2.dat-50	50	2	51,097	79,739	81,981		70,644	27.67
OR5x250-0.50_3.dat-50	50	2	46,295	79,097	83,230		72,948	36.54
OR5x250-0.50_4.dat-50	50	2	48,764	80,365	82,044		72,591	32.82
OR5x250-0.50_5.dat-50	50	2	48,263	81,400	87,609		75,882	36.40
OR5x250-0.50_6.dat-50	50	2	48,037	80,543	83,800		74,496	35.52
OR5x250-0.50_7.dat-50	50	2	45,898	79,433	84,028		71,471	35.78
OR5x250-0.50_8.dat-50	50	2	47,169	81,476	85,274		73,949	36.21
OR5x250-0.50_9.dat-50	50	2	47,712	80,901	83,871		74,801	36.21
OR5x250-0.50_10.dat-50	50	2	46,116	77,653	83,708		71,580	35.57
OR5x250-0.50_1.dat-100	50	1	51,511	78,004	78,004	69,671	73,838	5.64
OR5x250-0.50_2.dat-100	50	1	51,277	74,726	74,792	66,618	70,903	6.04
OR5x250-0.50_3.dat-100	50	1	49,591	77,700	78,199	66,098	73,113	9.59
OR5x250-0.50_4.dat-100	50	1	52,652	78,077	78,738	67,268	73,498	8.48
OR5x250-0.50_5.dat-100	50	1	55,375	79,729	80,304	70,969	75,888	6.48
OR5x250-0.50_6.dat-100	50	1	52,942	78,894	78,894	68,667	75,355	8.88
OR5x250-0.50_7.dat-100	50	1	53,948	74,755	76,937	67,519	72,397	6.74
OR5x250-0.50_8.dat-100	50	1	51,525	78,290	78,290	64,771	73,554	11.94
OR5x250-0.50_9.dat-100	50	1	53,259	78,999	78,999	68,884	74,135	7.08
OR5x250-0.50_10.dat-100	50	1	52,454	74,272	75,944	65,988	72,064	8.43
OR5x250-0.75_1.dat-0	75	4	24,032	24,032	26,953		24,032	0.00
OR5x250-0.75_2.dat-0	75	4	21,799	21,799	25,425		21,799	0.00
OR5x250-0.75_3.dat-0	75	4	25,330	25,330	31,757		25,330	0.00
OR5x250-0.75_4.dat-0	75	4	23,637	23,637	28,816		23,637	0.00
OR5x250-0.75_5.dat-0	75	4	24,011	24,011	32,918		24,011	0.00
OR5x250-0.75_6.dat-0	75	4	19,766	19,766	22,525		19,766	0.00
OR5x250-0.75_7.dat-0	75	4	21,914	21,914	25,534		21,914	0.00
OR5x250-0.75_8.dat-0	75	4	23,874	23,874	30,417		23,874	0.00
OR5x250-0.75_9.dat-0	75	4	25,048	25,048	30,699		25,048	0.00
OR5x250-0.75_10.dat-0	75	4	23,965	23,965	30,455		23,965	0.00
OR5x250-0.75_1.dat-50	75	2	31,006	31,006	37,195		31,006	0.00
OR5x250-0.75_2.dat-50	75	2	31,726	31,726	36,581		31,726	0.00
OR5x250-0.75_3.dat-50	75	2	32,286	32,286	39,738		32,286	0.00
OR5x250-0.75_4.dat-50	75	2	31,989	31,989	38,905		31,989	0.00
OR5x250-0.75_5.dat-50	75	2	31,009	31,009	38,480		31,009	0.00

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x250-0.75_6.dat-50	75	2	29,841	29,841	35,169		29,841	0.00
OR5x250-0.75_7.dat-50	75	2	31,421	31,421	37,858		31,421	0.00
OR5x250-0.75_8.dat-50	75	2	30,763	30,763	36,473		30,763	0.00
OR5x250-0.75_9.dat-50	75	2	32,198	32,198	37,947		32,198	0.00
OR5x250-0.75_10.dat-50	75	2	32,569	32,569	36,519		32,569	0.00
OR5x250-0.75_1.dat-100	75	1	33,318	33,318	40,373	32,031	33,358	0.00
OR5x250-0.75_2.dat-100	75	1	33,912	33,912	38,176	32,705	33,912	0.00
OR5x250-0.75_3.dat-100	75	1	34,439	34,439	41,500	33,198	34,471	0.00
OR5x250-0.75_4.dat-100	75	1	34,306	34,306	39,445	32,946	34,339	0.00
OR5x250-0.75_5.dat-100	75	1	33,649	33,649	38,720	32,400	33,665	0.00
OR5x250-0.75_6.dat-100	75	1	31,670	31,670	36,294	30,306	31,670	0.00
OR5x250-0.75_7.dat-100	75	1	33,373	33,373	38,127	32,122	33,373	0.00
OR5x250-0.75_8.dat-100	75	1	32,417	32,417	37,313	31,260	32,417	0.00
OR5x250-0.75_9.dat-100	75	1	34,576	34,576	38,511	33,186	34,607	0.00
OR5x250-0.75_10.dat-100	75	1	33,891	33,891	39,129	32,657	33,928	0.00
OR5x500-0.25_1.dat-0	25	4	69,835	110,214	117,265			34.49
OR5x500-0.25_2.dat-0	25	4	67,484	107,643	111,973			36.71
OR5x500-0.25_3.dat-0	25	4	70,067	111,192	118,046			36.52
OR5x500-0.25_4.dat-0	25	4	69,097	110,303	120,882			35.98
OR5x500-0.25_5.dat-0	25	4	68,932	110,666	117,279			36.44
OR5x500-0.25_6.dat-0	25	4	67,351	108,756				36.14
OR5x500-0.25_7.dat-0	25	4	68,077	108,402				35.11
OR5x500-0.25_8.dat-0	25	4	67,539	108,202	112,423			34.93
OR5x500-0.25_9.dat-0	25	4	69,004	110,234	113,726			35.77
OR5x500-0.25_10.dat-0	25	4	68,019	108,009				35.73
OR5x500-0.25_1.dat-50	25	2	76,052	113,261	114,719		111,010	31.49
OR5x500-0.25_2.dat-50	25	2	75,218	111,681	114,348		112,174	32.65
OR5x500-0.25_3.dat-50	25	2	78,945	118,460	119,657		114,278	30.92
OR5x500-0.25_4.dat-50	25	2	79,508	116,473	116,473		111,381	28.62
OR5x500-0.25_5.dat-50	25	2	75,546	114,868	116,012		110,268	31.49
OR5x500-0.25_6.dat-50	25	2	77,490	114,252	116,134		111,698	30.63
OR5x500-0.25_7.dat-50	25	2	77,511	112,684	113,888		109,462	29.19
OR5x500-0.25_8.dat-50	25	2	76,353	113,134	113,597		111,252	31.37
OR5x500-0.25_9.dat-50	25	2	77,845	115,734	115,734		113,693	31.53
OR5x500-0.25_10.dat-50	25	2	76,071	113,094	114,455		109,429	30.48
OR5x500-0.25_1.dat-100	25	1	90,594	123,807	123,813	112,053	117,212	4.40
OR5x500-0.25_2.dat-100	25	1	90,110	120,379	120,379	110,468	115,579	4.42
OR5x500-0.25_3.dat-100	25	1	90,361	122,897	122,897	111,471	116,685	4.47
OR5x500-0.25_4.dat-100	25	1	93,316	126,374	126,374	113,621	119,915	5.25
OR5x500-0.25_5.dat-100	25	1	89,472	120,760	120,760	110,348	115,732	4.65
OR5x500-0.25_6.dat-100	25	1	90,508	117,619	117,619	108,350	113,962	4.92
OR5x500-0.25_7.dat-100	25	1	91,222	118,599	118,599	109,038	114,264	4.57
OR5x500-0.25_8.dat-100	25	1	90,045	117,971	117,971	106,979	112,554	4.95
OR5x500-0.25_9.dat-100	25	1	93,289	123,411	123,411	113,207	118,639	4.58
OR5x500-0.25_10.dat-100	25	1	91,103	120,024	120,024	109,797	115,683	5.09
OR5x500-0.50_1.dat-0	50	4	77,109	123,841	214,120		108,216	28.75
OR5x500-0.50_2.dat-0	50	4	74,534	124,608			109,574	31.98
OR5x500-0.50_3.dat-0	50	4	71,925	123,468	211,434		108,233	33.55
OR5x500-0.50_4.dat-0	50	4	76,000	129,661			113,945	33.30
OR5x500-0.50_5.dat-0	50	4	74,417	126,925	201,516		110,730	32.79
OR5x500-0.50_6.dat-0	50	4	76,099	125,246	197,735		111,703	31.87
OR5x500-0.50_7.dat-0	50	4	74,173	127,351	204,545		110,612	32.94
OR5x500-0.50_8.dat-0	50	4	74,840	127,420	218,814		111,627	32.96
OR5x500-0.50_9.dat-0	50	4	72,145	121,479			106,432	32.21

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR5x500-0.50_10.dat-0	50	4	76,215	129,471	196,699		115,998	34.30
OR5x500-0.50_1.dat-50	50	2	93,703	161,392	164,286		144,300	35.06
OR5x500-0.50_2.dat-50	50	2	94,588	163,727	163,727		147,077	35.69
OR5x500-0.50_3.dat-50	50	2	91,607	159,366	163,792		144,492	36.60
OR5x500-0.50_4.dat-50	50	2	94,797	167,239	168,310		150,448	36.99
OR5x500-0.50_5.dat-50	50	2	92,434	162,645	165,910		144,796	36.16
OR5x500-0.50_6.dat-50	50	2	91,819	160,755	167,066		147,365	37.69
OR5x500-0.50_7.dat-50	50	2	91,349	159,842	168,265		145,558	37.24
OR5x500-0.50_8.dat-50	50	2	93,238	161,161	161,684		146,795	36.48
OR5x500-0.50_9.dat-50	50	2	91,421	159,578	166,726		144,903	36.91
OR5x500-0.50_10.dat-50	50	2	92,710	164,190	169,033		147,553	37.17
OR5x500-0.50_1.dat-100	50	1	95,743	152,050	152,050	122,445	143,472	14.66
OR5x500-0.50_2.dat-100	50	1	96,224	152,674	152,674	123,075	145,663	15.51
OR5x500-0.50_3.dat-100	50	1	95,193	150,648	150,648	122,060	142,500	14.34
OR5x500-0.50_4.dat-100	50	1	98,696	158,065	158,065	123,483	148,736	16.98
OR5x500-0.50_5.dat-100	50	1	95,783	154,977	154,977	118,933	146,297	18.70
OR5x500-0.50_6.dat-100	50	1	96,634	154,727	154,727	121,111	146,071	17.09
OR5x500-0.50_7.dat-100	50	1	95,596	156,375	156,375	119,143	145,735	18.25
OR5x500-0.50_8.dat-100	50	1	96,324	151,145	151,145	121,654	144,375	15.74
OR5x500-0.50_9.dat-100	50	1	94,932	153,060	153,060	115,963	144,891	19.97
OR5x500-0.50_10.dat-100	50	1	95,786	152,964	155,612	116,185	147,142	21.04
OR5x500-0.75_1.dat-0	75	4	33,280	70,213	275,421		42,843	22.32
OR5x500-0.75_2.dat-0	75	4	48,611	66,550	83,975		48,617	0.01
OR5x500-0.75_3.dat-0	75	4	35,724	71,632	97,517		47,256	24.40
OR5x500-0.75_4.dat-0	75	4	35,106	71,978	100,542		48,597	27.76
OR5x500-0.75_5.dat-0	75	4	35,165	69,985	96,801		48,644	27.71
OR5x500-0.75_6.dat-0	75	4	36,713	65,198	92,928		46,868	21.67
OR5x500-0.75_7.dat-0	75	4	45,651	66,476	94,972		45,668	0.04
OR5x500-0.75_8.dat-0	75	4	34,991	66,585	82,364		46,099	24.10
OR5x500-0.75_9.dat-0	75	4	37,192	46,817	100,248		46,817	20.56
OR5x500-0.75_10.dat-0	75	4	45,895	65,644	83,529		45,921	0.06
OR5x500-0.75_1.dat-50	75	2	44,989	61,770	97,526		61,697	27.08
OR5x500-0.75_2.dat-50	75	2	59,252	62,479	100,543		62,391	5.03
OR5x500-0.75_3.dat-50	75	2	59,953	61,213	91,905		61,034	1.77
OR5x500-0.75_4.dat-50	75	2	46,017	63,661	90,979		63,550	27.59
OR5x500-0.75_5.dat-50	75	2	46,155	62,096	96,309		62,048	25.61
OR5x500-0.75_6.dat-50	75	2	46,315	63,547	91,224		63,437	26.99
OR5x500-0.75_7.dat-50	75	2	61,642	61,745	99,090		61,693	0.08
OR5x500-0.75_8.dat-50	75	2	63,201	63,342	108,200		63,248	0.07
OR5x500-0.75_9.dat-50	75	2	45,302	62,819	101,695		62,717	27.77
OR5x500-0.75_10.dat-50	75	2	44,977	61,063	102,403		60,990	26.26
OR5x500-0.75_1.dat-100	75	1	53,711	64,823	91,492	63,493	64,837	2.05
OR5x500-0.75_2.dat-100	75	1	64,903	68,349	96,443	66,939	68,329	2.03
OR5x500-0.75_3.dat-100	75	1	62,448	65,458	90,500	64,125	65,432	2.00
OR5x500-0.75_4.dat-100	75	1	67,838	68,073	95,257	66,760	68,060	0.33
OR5x500-0.75_5.dat-100	75	1	62,361	65,516	93,947	64,190	65,544	2.02
OR5x500-0.75_6.dat-100	75	1	63,429	66,482	93,609	65,119	66,459	2.02
OR5x500-0.75_7.dat-100	75	1	64,910	65,076	97,773	63,786	65,065	0.24
OR5x500-0.75_8.dat-100	75	1	68,064	68,254	96,401	66,870	68,282	0.28
OR5x500-0.75_9.dat-100	75	1	63,244	66,562	91,808	65,278	66,541	1.90
OR5x500-0.75_10.dat-100	75	1	62,937	66,051	92,698	64,709	66,070	2.03
OR10x100-0.25_1.dat-0	25	9	14,537	19,029	21,555		18,761	22.51
OR10x100-0.25_2.dat-0	25	9	14,481	18,822	20,668			23.06
OR10x100-0.25_3.dat-0	25	9	14,432	18,681	20,698		18,323	21.24

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR10x100-0.25_4.dat-0	25	9	14,720	19,808	21,661		19,703	25.29
OR10x100-0.25_5.dat-0	25	9	14,857	19,281	21,437			22.94
OR10x100-0.25_6.dat-0	25	9	14,875	19,330	21,616		19,372	23.05
OR10x100-0.25_7.dat-0	25	9	13,644	18,104	20,751			24.64
OR10x100-0.25_8.dat-0	25	9	14,546	18,738	21,025		18,854	22.37
OR10x100-0.25_9.dat-0	25	9	13,989	18,348	19,917		18,154	22.94
OR10x100-0.25_10.dat-0	25	9	14,119	18,673	20,543		18,565	23.95
OR10x100-0.25_1.dat-50	25	5	15,584	20,784	23,483		20,673	24.62
OR10x100-0.25_2.dat-50	25	5	15,054	20,134	21,586		20,000	24.73
OR10x100-0.25_3.dat-50	25	5	14,995	20,097	21,085		19,736	24.02
OR10x100-0.25_4.dat-50	25	5	15,804	20,754	22,771			23.85
OR10x100-0.25_5.dat-50	25	5	15,826	20,765	22,055		20,480	22.72
OR10x100-0.25_6.dat-50	25	5	16,183	21,415	22,920		21,121	23.38
OR10x100-0.25_7.dat-50	25	5	14,361	19,438	20,736		19,009	24.45
OR10x100-0.25_8.dat-50	25	5	14,996	20,322	21,458		19,872	24.54
OR10x100-0.25_9.dat-50	25	5	14,717	19,527	21,027		19,106	22.97
OR10x100-0.25_10.dat-50	25	5	14,825	20,264	22,328		19,924	25.59
OR10x100-0.25_1.dat-100	25	1	21,158	25,534	26,730	24,632	24,994	1.45
OR10x100-0.25_2.dat-100	25	1	21,782	25,551	26,754	24,132	24,767	2.56
OR10x100-0.25_3.dat-100	25	1	20,762	25,175	27,090	23,863	24,515	2.66
OR10x100-0.25_4.dat-100	25	1	20,157	23,669	24,052	23,011	23,239	0.98
OR10x100-0.25_5.dat-100	25	1	20,096	23,151	24,424	23,016	23,417	0.58
OR10x100-0.25_6.dat-100	25	1	21,247	26,003	27,184	25,036	25,612	2.25
OR10x100-0.25_7.dat-100	25	1	20,146	24,079	25,884	23,051	23,787	3.09
OR10x100-0.25_8.dat-100	25	1	21,219	25,907	26,857	24,635	25,403	3.02
OR10x100-0.25_9.dat-100	25	1	19,077	22,758	23,084	22,091	22,525	1.93
OR10x100-0.25_10.dat-100	25	1	20,546	25,246	26,228	24,062	24,599	2.18
OR10x100-0.50_1.dat-0	50	9	15,216	22,209	26,516		20,476	25.69
OR10x100-0.50_2.dat-0	50	9	15,426	21,266	25,742		20,545	24.92
OR10x100-0.50_3.dat-0	50	9	19,112	22,787	34,196		20,916	8.62
OR10x100-0.50_4.dat-0	50	9	17,568	26,422	32,127		24,455	28.16
OR10x100-0.50_5.dat-0	50	9	15,358	22,399	29,498		20,730	25.91
OR10x100-0.50_6.dat-0	50	9	15,440	23,188	31,185		21,633	28.63
OR10x100-0.50_7.dat-0	50	9	18,533	24,346	30,828		22,981	19.36
OR10x100-0.50_8.dat-0	50	9	18,216	23,791	33,462		21,906	16.84
OR10x100-0.50_9.dat-0	50	9	16,056	23,364	28,760		21,609	25.70
OR10x100-0.50_10.dat-0	50	9	15,718	21,319	25,989		19,557	19.63
OR10x100-0.50_1.dat-50	50	5	18,370	28,595	31,221		25,614	28.28
OR10x100-0.50_2.dat-50	50	5	20,276	29,586	33,445		27,913	27.36
OR10x100-0.50_3.dat-50	50	5	19,767	31,145	33,428		28,340	30.25
OR10x100-0.50_4.dat-50	50	5	21,026	32,837	35,267		29,808	29.46
OR10x100-0.50_5.dat-50	50	5	18,568	29,650	32,485		27,197	31.73
OR10x100-0.50_6.dat-50	50	5	19,411	30,498	33,486		27,518	29.46
OR10x100-0.50_7.dat-50	50	5	19,257	29,791	33,101		27,821	30.78
OR10x100-0.50_8.dat-50	50	5	18,556	30,003	32,252		26,704	30.51
OR10x100-0.50_9.dat-50	50	5	18,731	30,808	31,770		27,713	32.41
OR10x100-0.50_10.dat-50	50	5	18,813	29,318	30,758		26,340	28.58
OR10x100-0.50_1.dat-100	50	1	19,018	29,329	29,722	26,565	27,500	3.40
OR10x100-0.50_2.dat-100	50	1	20,461	29,499	30,910	27,630	28,430	2.81
OR10x100-0.50_3.dat-100	50	1	21,243	30,415	32,149	28,023	29,356	4.54
OR10x100-0.50_4.dat-100	50	1	23,916	30,985	31,201	28,913	29,876	3.22
OR10x100-0.50_5.dat-100	50	1	20,743	28,407	29,681	26,550	27,632	3.92
OR10x100-0.50_6.dat-100	50	1	20,724	29,761	30,654	27,684	28,708	3.57
OR10x100-0.50_7.dat-100	50	1	21,211	30,595	30,595	28,508	29,565	3.58

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR10x100-0.50_8.dat-100	50	1	20,788	30,178	30,901	27,463	28,648	4.14
OR10x100-0.50_9.dat-100	50	1	19,814	30,015	30,340	27,070	28,147	3.83
OR10x100-0.50_10.dat-100	50	1	18,980	27,905	27,905	25,774	26,650	3.29
OR10x100-0.75_1.dat-0	75	9	9,389	10,212	10,334		9,426	0.39
OR10x100-0.75_2.dat-0	75	9	9,057	9,057	9,436		9,057	0.00
OR10x100-0.75_3.dat-0	75	9	8,747	9,310	9,462		8,749	0.02
OR10x100-0.75_4.dat-0[†]	75	9	8,814	8,813	9,447		8,813	0.00
OR10x100-0.75_5.dat-0	75	9	8,616	9,027	9,850		8,685	0.79
OR10x100-0.75_6.dat-0	75	9	9,638	9,638	10,426		9,638	0.00
OR10x100-0.75_7.dat-0	75	9	8,374	8,374	9,661		8,374	0.00
OR10x100-0.75_8.dat-0	75	9	8,745	8,745	9,631		8,745	0.00
OR10x100-0.75_9.dat-0	75	9	8,364	8,364	8,853		8,364	0.00
OR10x100-0.75_10.dat-0	75	9	7,632	8,183	8,950		7,671	0.51
OR10x100-0.75_1.dat-50	75	5	12,090	13,507	14,330		12,339	2.02
OR10x100-0.75_2.dat-50	75	5	12,747	13,752	14,781		12,970	1.72
OR10x100-0.75_3.dat-50	75	5	12,421	13,957	13,957		12,597	1.40
OR10x100-0.75_4.dat-50	75	5	13,358	14,742	15,110		13,571	1.57
OR10x100-0.75_5.dat-50	75	5	12,750	14,444	14,866		12,954	1.57
OR10x100-0.75_6.dat-50	75	5	14,202	15,594	16,039		14,401	1.38
OR10x100-0.75_7.dat-50	75	5	12,214	13,308	14,590		12,375	1.30
OR10x100-0.75_8.dat-50	75	5	12,851	14,951	14,993		12,996	1.12
OR10x100-0.75_9.dat-50	75	5	12,896	14,548	15,142		13,085	1.44
OR10x100-0.75_10.dat-50	75	5	11,983	13,232	13,232		12,240	2.10
OR10x100-0.75_1.dat-100	75	1	13,599	13,599	14,962	12,582	13,599	0.00
OR10x100-0.75_2.dat-100	75	1	14,155	14,155	15,768	12,895	14,317	0.00
OR10x100-0.75_3.dat-100	75	1	14,216	14,216	15,618	12,996	14,216	0.00
OR10x100-0.75_4.dat-100	75	1	15,290	15,290	16,627	13,869	15,332	0.00
OR10x100-0.75_5.dat-100	75	1	14,439	14,439	15,413	13,360	14,439	0.00
OR10x100-0.75_6.dat-100	75	1	15,347	15,347	16,867	14,256	15,347	0.00
OR10x100-0.75_7.dat-100	75	1	13,934	13,934	14,996	12,688	13,984	0.00
OR10x100-0.75_8.dat-100	75	1	14,137	14,137	15,508	13,006	14,137	0.00
OR10x100-0.75_9.dat-100	75	1	14,185	14,185	15,078	12,968	14,252	0.00
OR10x100-0.75_10.dat-100	75	1	13,814	13,814	15,169	12,728	13,814	0.00
OR10x250-0.25_1.dat-0	25	9	29,491	52,379				40.38
OR10x250-0.25_2.dat-0	25	9	28,790	51,927				41.88
OR10x250-0.25_3.dat-0	25	9	31,377	51,223				34.80
OR10x250-0.25_4.dat-0	25	9	33,546	53,025				35.61
OR10x250-0.25_5.dat-0	25	9						100.00
OR10x250-0.25_6.dat-0	25	9	32,947	52,205				34.00
OR10x250-0.25_7.dat-0	25	9	32,666	53,579				37.05
OR10x250-0.25_8.dat-0	25	9	31,028	51,707				38.65
OR10x250-0.25_9.dat-0	25	9	31,302	51,439				36.94
OR10x250-0.25_10.dat-0	25	9	33,079	52,856				35.43
OR10x250-0.25_1.dat-50	25	5	33,844	53,502	54,589			33.89
OR10x250-0.25_2.dat-50	25	5	34,108	53,382	56,458			35.76
OR10x250-0.25_3.dat-50	25	5	33,876	52,024	54,475			33.43
OR10x250-0.25_4.dat-50	25	5	35,545	54,623	57,372			33.41
OR10x250-0.25_5.dat-50	25	5	34,172	53,530	56,657			33.51
OR10x250-0.25_6.dat-50	25	5	35,036	53,835	57,033			32.52
OR10x250-0.25_7.dat-50	25	5	35,749	55,317	58,507			32.44
OR10x250-0.25_8.dat-50	25	5	34,152	53,363	55,998			33.62
OR10x250-0.25_9.dat-50	25	5	33,469	53,427	56,737			35.30
OR10x250-0.25_10.dat-50	25	5	34,721	54,167	58,614			33.22
OR10x250-0.25_1.dat-100	25	1	45,733	60,741	60,741	57,006	58,509	2.57

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR10x250-0.25_2.dat-100	25	1	45,395	61,073	62,057	56,593	58,389	3.08
OR10x250-0.25_3.dat-100	25	1	47,383	62,082	63,543	57,819	60,158	3.89
OR10x250-0.25_4.dat-100	25	1	45,811	61,629	61,629	57,008	58,720	2.92
OR10x250-0.25_5.dat-100	25	1	47,078	63,531	64,835	58,258	60,139	3.13
OR10x250-0.25_6.dat-100	25	1	46,276	61,727	62,410	56,557	58,847	3.89
OR10x250-0.25_7.dat-100	25	1	47,040	61,136	61,691	56,755	58,419	2.85
OR10x250-0.25_8.dat-100	25	1	45,924	60,648	61,592	56,036	57,691	2.87
OR10x250-0.25_9.dat-100	25	1	47,463	61,503	61,503	57,741	59,446	2.87
OR10x250-0.25_10.dat-100	25	1	46,128	62,297	63,736	57,528	59,535	3.37
OR10x250-0.50_1.dat-0	50	9					57,818	100.00
OR10x250-0.50_2.dat-0	50	9	38,126	62,818			54,748	30.36
OR10x250-0.50_3.dat-0	50	9	37,856	61,853			54,326	30.32
OR10x250-0.50_4.dat-0	50	9	37,582	59,368			52,717	28.71
OR10x250-0.50_5.dat-0	50	9	38,115	62,987			58,115	34.41
OR10x250-0.50_6.dat-0	50	9	39,300	62,837			56,345	30.25
OR10x250-0.50_7.dat-0	50	9	37,201	61,372			53,302	30.21
OR10x250-0.50_8.dat-0	50	9	36,697	60,043			52,577	30.20
OR10x250-0.50_9.dat-0	50	9	36,004	57,088			49,519	27.29
OR10x250-0.50_10.dat-0	50	9	35,602	57,134			49,964	28.74
OR10x250-0.50_1.dat-50	50	5	46,783	83,614	90,802		73,119	36.02
OR10x250-0.50_2.dat-50	50	5	45,093	79,698	87,145		71,142	36.62
OR10x250-0.50_3.dat-50	50	5	45,192	46,801	87,484		71,263	3.44
OR10x250-0.50_4.dat-50	50	5	46,428	83,324	86,634		72,536	35.99
OR10x250-0.50_5.dat-50	50	5	45,521	81,995	85,921		69,837	34.82
OR10x250-0.50_6.dat-50	50	5	46,130	78,957	88,255		71,000	35.03
OR10x250-0.50_7.dat-50	50	5	44,281	78,565	84,387		68,581	35.43
OR10x250-0.50_8.dat-50	50	5	44,289	79,996	86,485		68,859	35.68
OR10x250-0.50_9.dat-50	50	5	45,700	81,071	90,949		70,068	34.78
OR10x250-0.50_10.dat-50	50	5	43,973	77,887	81,253		67,139	34.50
OR10x250-0.50_1.dat-100	50	1	54,353	80,190	80,190	70,254	75,854	7.38
OR10x250-0.50_2.dat-100	50	1	50,538	74,852	74,852	66,529	70,788	6.02
OR10x250-0.50_3.dat-100	50	1	47,200	75,120	75,120	66,152	70,219	5.79
OR10x250-0.50_4.dat-100	50	1	53,571	76,382	76,382	67,648	72,297	6.43
OR10x250-0.50_5.dat-100	50	1	48,841	76,790	76,790	68,015	72,938	6.75
OR10x250-0.50_6.dat-100	50	1	47,428	76,052	76,052	67,528	71,923	6.11
OR10x250-0.50_7.dat-100	50	1	48,261	73,743	73,743	65,056	69,311	6.14
OR10x250-0.50_8.dat-100	50	1	49,499	73,301	73,403	64,555	68,763	6.12
OR10x250-0.50_9.dat-100	50	1	52,821	79,259	79,836	69,811	74,526	6.33
OR10x250-0.50_10.dat-100	50	1	46,410	71,374	71,374	63,747	67,988	6.24
OR10x250-0.75_1.dat-0	75	9	22,839	25,765			22,888	0.21
OR10x250-0.75_2.dat-0	75	9	21,009	23,182			21,041	0.15
OR10x250-0.75_3.dat-0	75	9	22,398	25,879			22,460	0.28
OR10x250-0.75_4.dat-0	75	9	23,056	25,999			23,083	0.12
OR10x250-0.75_5.dat-0	75	9	23,022	26,190			23,031	0.04
OR10x250-0.75_6.dat-0	75	9	23,154	25,506			23,173	0.08
OR10x250-0.75_7.dat-0	75	9	23,248	25,986			23,276	0.12
OR10x250-0.75_8.dat-0	75	9	22,123	25,242			22,156	0.15
OR10x250-0.75_9.dat-0	75	9	22,775	25,768	143,153		22,794	0.08
OR10x250-0.75_10.dat-0	75	9	22,613	25,872			22,631	0.08
OR10x250-0.75_1.dat-50	75	5	32,053	36,970	38,491		32,193	0.43
OR10x250-0.75_2.dat-50	75	5	31,550	37,354	38,526		31,710	0.50
OR10x250-0.75_3.dat-50	75	5	32,078	36,456	38,500		32,237	0.49
OR10x250-0.75_4.dat-50	75	5	32,823	38,496	40,143		32,914	0.28
OR10x250-0.75_5.dat-50	75	5	32,161	34,949	39,199		32,305	0.45

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR10x250-0.75_6.dat-50	75	5	32,547	36,905	38,195		32,655	0.33
OR10x250-0.75_7.dat-50	75	5	31,906	37,389	37,389		32,012	0.33
OR10x250-0.75_8.dat-50	75	5	32,573	38,048	39,745		32,696	0.38
OR10x250-0.75_9.dat-50	75	5	32,563	37,021	40,293		32,743	0.55
OR10x250-0.75_10.dat-50	75	5	32,629	37,946	39,600		32,753	0.38
OR10x250-0.75_1.dat-100	75	1	34,846	34,846	38,358	33,561	34,846	0.00
OR10x250-0.75_2.dat-100	75	1	34,304	34,351	40,332	33,042	34,419	0.14
OR10x250-0.75_3.dat-100	75	1	35,647	35,699	39,734	34,336	35,711	0.15
OR10x250-0.75_4.dat-100	75	1	35,302	35,355	41,019	33,997	35,501	0.15
OR10x250-0.75_5.dat-100	75	1	35,887	35,920	40,366	34,662	36,042	0.09
OR10x250-0.75_6.dat-100	75	1	35,101	35,101	39,878	33,724	35,188	0.00
OR10x250-0.75_7.dat-100	75	1	35,021	35,021	40,501	33,697	35,071	0.00
OR10x250-0.75_8.dat-100	75	1	36,089	36,139	41,139	34,875	36,209	0.14
OR10x250-0.75_9.dat-100	75	1	34,584	34,625	38,456	33,260	34,714	0.12
OR10x250-0.75_10.dat-100	75	1	34,852	34,889	40,957	33,600	34,935	0.11
OR10x500-0.25_1.dat-0	25	9						100.00
OR10x500-0.25_2.dat-0	25	9						100.00
OR10x500-0.25_3.dat-0	25	9						100.00
OR10x500-0.25_4.dat-0	25	9						100.00
OR10x500-0.25_5.dat-0	25	9						100.00
OR10x500-0.25_6.dat-0	25	9						100.00
OR10x500-0.25_7.dat-0	25	9						100.00
OR10x500-0.25_8.dat-0	25	9						100.00
OR10x500-0.25_9.dat-0	25	9						100.00
OR10x500-0.25_10.dat-0	25	9						100.00
OR10x500-0.25_1.dat-50	25	5	67,440	113,396				36.39
OR10x500-0.25_2.dat-50	25	5	67,265	112,795				38.06
OR10x500-0.25_3.dat-50	25	5	67,129	113,842				38.00
OR10x500-0.25_4.dat-50	25	5	67,267	113,364				36.00
OR10x500-0.25_5.dat-50[†]	25	5	67,175	20,909				36.89
OR10x500-0.25_6.dat-50	25	5	66,729	112,484				37.63
OR10x500-0.25_7.dat-50	25	5	66,534	113,266				38.07
OR10x500-0.25_8.dat-50	25	5	67,532	113,484				37.37
OR10x500-0.25_9.dat-50	25	5	66,584	112,885				37.55
OR10x500-0.25_10.dat-50	25	5	66,920	113,424				38.21
OR10x500-0.25_1.dat-100	25	1	94,743	127,585	127,585	115,162	121,246	5.02
OR10x500-0.25_2.dat-100	25	1	95,933	127,453	127,453	115,492	122,627	5.82
OR10x500-0.25_3.dat-100	25	1	94,994	125,471	125,471	113,509	119,730	5.20
OR10x500-0.25_4.dat-100	25	1	89,911	123,364	123,364	111,864	117,808	5.05
OR10x500-0.25_5.dat-100	25	1	91,545	120,705	120,705	108,352	114,902	5.70
OR10x500-0.25_6.dat-100	25	1	87,880	117,664	117,664	107,695	112,855	4.57
OR10x500-0.25_7.dat-100	25	1	89,663	117,580	117,580	108,463	115,125	5.79
OR10x500-0.25_8.dat-100	25	1	88,272	118,222	118,222	108,534	113,884	4.70
OR10x500-0.25_9.dat-100	25	1	94,528	123,911	123,911	112,103	118,877	5.70
OR10x500-0.25_10.dat-100	25	1	91,633	125,687	125,687	113,444	119,347	4.95
OR10x500-0.50_1.dat-0	50	9					110,228	100.00
OR10x500-0.50_2.dat-0	50	9					108,994	100.00
OR10x500-0.50_3.dat-0	50	9					109,258	100.00
OR10x500-0.50_4.dat-0	50	9					109,277	100.00
OR10x500-0.50_5.dat-0	50	9					109,764	100.00
OR10x500-0.50_6.dat-0	50	9					109,294	100.00
OR10x500-0.50_7.dat-0	50	9					108,537	100.00
OR10x500-0.50_8.dat-0	50	9					111,621	100.00
OR10x500-0.50_9.dat-0	50	9					107,753	100.00

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR10x500-0.50_10.dat-0	50	9					111,864	100.00
OR10x500-0.50_1.dat-50	50	5	90,553	168,280			143,800	37.03
OR10x500-0.50_2.dat-50	50	5	89,644	168,134			144,652	38.03
OR10x500-0.50_3.dat-50	50	5	88,559	167,065			142,099	37.68
OR10x500-0.50_4.dat-50	50	5	89,058	165,223			138,428	35.66
OR10x500-0.50_5.dat-50	50	5	88,025	165,182			141,199	37.66
OR10x500-0.50_6.dat-50	50	5	88,666	163,977			140,895	37.07
OR10x500-0.50_7.dat-50	50	5	89,541	165,363			142,685	37.25
OR10x500-0.50_8.dat-50	50	5	90,548	171,282			139,449	35.07
OR10x500-0.50_9.dat-50	50	5	88,168	163,683			136,827	35.56
OR10x500-0.50_10.dat-50	50	5	91,352	171,052			144,345	36.71
OR10x500-0.50_1.dat-100	50	1	94,989	151,252	151,252	126,056	143,544	12.18
OR10x500-0.50_2.dat-100	50	1	95,347	152,805	152,805	126,165	144,228	12.52
OR10x500-0.50_3.dat-100	50	1	93,960	150,071	150,081	124,877	141,697	11.87
OR10x500-0.50_4.dat-100	50	1	92,771	144,641	144,641	124,705	139,035	10.31
OR10x500-0.50_5.dat-100	50	1	93,142	149,765	149,765	124,880	140,684	11.23
OR10x500-0.50_6.dat-100	50	1	92,805	147,967	148,618	123,818	139,239	11.08
OR10x500-0.50_7.dat-100	50	1	93,245	149,764	149,764	124,042	141,572	12.38
OR10x500-0.50_8.dat-100	50	1	94,131	147,014	147,020	124,989	140,147	10.82
OR10x500-0.50_9.dat-100	50	1	91,805	149,977	149,977	123,180	140,613	12.40
OR10x500-0.50_10.dat-100	50	1	95,673	155,420	155,420	128,690	146,691	12.27
OR10x500-0.75_1.dat-0	75	9	33,983	52,026			45,235	24.87
OR10x500-0.75_2.dat-0	75	9					45,759	100.00
OR10x500-0.75_3.dat-0	75	9					46,872	100.00
OR10x500-0.75_4.dat-0	75	9					43,498	100.00
OR10x500-0.75_5.dat-0	75	9					46,681	100.00
OR10x500-0.75_6.dat-0	75	9					47,558	100.00
OR10x500-0.75_7.dat-0	75	9					47,506	100.00
OR10x500-0.75_8.dat-0	75	9					42,652	100.00
OR10x500-0.75_9.dat-0	75	9					44,192	100.00
OR10x500-0.75_10.dat-0	75	9					45,448	100.00
OR10x500-0.75_1.dat-50	75	5	63,789	74,925			63,888	0.15
OR10x500-0.75_2.dat-50	75	5	63,960	74,542			64,075	0.18
OR10x500-0.75_3.dat-50	75	5	46,714	77,304	290,174		65,792	29.00
OR10x500-0.75_4.dat-50	75	5	45,938	74,701			63,697	27.88
OR10x500-0.75_5.dat-50	75	5	45,616	75,575			65,907	30.79
OR10x500-0.75_6.dat-50	75	5	64,635	74,937			64,738	0.16
OR10x500-0.75_7.dat-50	75	5	63,946	74,679	101,020		64,068	0.19
OR10x500-0.75_8.dat-50	75	5	63,071	74,193	299,817		63,159	0.14
OR10x500-0.75_9.dat-50	75	5	45,646	74,809			63,140	27.71
OR10x500-0.75_10.dat-50	75	5	46,380	77,141	96,962		65,197	28.86
OR10x500-0.75_1.dat-100	75	1	69,335	69,713	96,504	68,272	69,743	0.54
OR10x500-0.75_2.dat-100	75	1	68,643	69,027	98,003	67,621	69,069	0.56
OR10x500-0.75_3.dat-100	75	1	54,281	70,802	94,624	69,492	70,802	1.85
OR10x500-0.75_4.dat-100	75	1	68,445	68,843	95,396	67,373	68,881	0.58
OR10x500-0.75_5.dat-100	75	1	69,744	70,096	94,674	68,543	69,998	0.36
OR10x500-0.75_6.dat-100	75	1	70,268	70,641	95,464	69,207	70,720	0.53
OR10x500-0.75_7.dat-100	75	1	69,661	70,123	97,355	68,671	70,134	0.66
OR10x500-0.75_8.dat-100	75	1	68,849	68,975	93,518	67,667	69,081	0.18
OR10x500-0.75_9.dat-100	75	1	67,835	68,188	95,135	66,816	68,228	0.52
OR10x500-0.75_10.dat-100	75	1	69,841	70,117	98,288	68,727	70,190	0.39
OR30x100-0.25_1.dat-0	25	29	12,896	18,176	20,967			28.58
OR30x100-0.25_2.dat-0	25	29	11,887	19,013	20,883			34.52
OR30x100-0.25_3.dat-0	25	29	12,408	17,619	20,050			29.58

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR30x100-0.25_4.dat-0	25	29		19,822				100.00
OR30x100-0.25_5.dat-0	25	29		20,626				100.00
OR30x100-0.25_6.dat-0	25	29	13,153	18,387				28.47
OR30x100-0.25_7.dat-0	25	29	12,125	18,688				32.94
OR30x100-0.25_8.dat-0	25	29		19,967				100.00
OR30x100-0.25_9.dat-0	25	29		21,618				100.00
OR30x100-0.25_10.dat-0	25	29	974	18,151	19,939			94.58
OR30x100-0.25_1.dat-50	25	15	14,358	19,539	21,678			26.52
OR30x100-0.25_2.dat-50	25	15	13,955	19,468	20,351			28.32
OR30x100-0.25_3.dat-50	25	15	13,826	18,956	20,892			27.06
OR30x100-0.25_4.dat-50	25	15	13,997	19,452	20,591			27.69
OR30x100-0.25_5.dat-50	25	15	14,772	20,202	22,158			26.88
OR30x100-0.25_6.dat-50	25	15	14,488	19,788	21,075			26.78
OR30x100-0.25_7.dat-50	25	15	14,106	19,498	21,055		19,443	27.45
OR30x100-0.25_8.dat-50	25	15	14,328	19,699	21,345			27.27
OR30x100-0.25_9.dat-50	25	15	15,173	20,935	21,651			27.52
OR30x100-0.25_10.dat-50	25	15	13,710	18,470	20,780			25.77
OR30x100-0.25_1.dat-100	25	1	19,857	24,023	24,689	22,442	23,431	4.22
OR30x100-0.25_2.dat-100	25	1	21,423	25,500	26,280	23,845	24,863	4.09
OR30x100-0.25_3.dat-100	25	1	18,927	23,033	23,988	21,604	22,607	4.44
OR30x100-0.25_4.dat-100	25	1	19,203	23,311	24,900	22,150	23,073	4.00
OR30x100-0.25_5.dat-100	25	1	20,638	25,265	27,414	24,017	24,955	3.76
OR30x100-0.25_6.dat-100	25	1	20,272	24,540	25,644	23,099	24,116	4.22
OR30x100-0.25_7.dat-100	25	1	22,418	27,396	28,746	25,726	26,993	4.69
OR30x100-0.25_8.dat-100	25	1	19,527	23,856	25,096	22,336	23,319	4.22
OR30x100-0.25_9.dat-100	25	1	23,302	27,345	28,174	25,753	26,760	3.76
OR30x100-0.25_10.dat-100	25	1	19,848	24,084	24,908	22,825	23,762	3.94
OR30x100-0.50_1.dat-0	50	29	14,360	22,276	28,821		20,246	29.07
OR30x100-0.50_2.dat-0	50	29	15,060	23,891	37,927		21,279	29.23
OR30x100-0.50_3.dat-0	50	29	15,798	25,271			23,024	31.38
OR30x100-0.50_4.dat-0	50	29	15,637	24,998	29,193		22,792	31.39
OR30x100-0.50_5.dat-0	50	29	14,858	22,171			20,805	28.58
OR30x100-0.50_6.dat-0	50	29	15,306	23,182	35,501		21,594	29.12
OR30x100-0.50_7.dat-0	50	29	15,351	24,028	31,149		21,739	29.38
OR30x100-0.50_8.dat-0	50	29	16,082	24,989	39,030		23,398	31.27
OR30x100-0.50_9.dat-0	50	29	15,390	24,269	31,571		22,260	30.86
OR30x100-0.50_10.dat-0	50	29	14,678	22,218	29,171		20,776	29.35
OR30x100-0.50_1.dat-50	50	15	18,108	30,596	32,058		27,226	33.49
OR30x100-0.50_2.dat-50	50	15	18,572	31,150	34,004		27,576	32.65
OR30x100-0.50_3.dat-50	50	15	18,267	30,402	32,721		27,358	33.23
OR30x100-0.50_4.dat-50	50	15	18,029	30,630	31,866		26,504	31.98
OR30x100-0.50_5.dat-50	50	15	18,421	31,891	33,177		27,982	34.17
OR30x100-0.50_6.dat-50	50	15	17,915	29,987	30,968		27,098	33.89
OR30x100-0.50_7.dat-50	50	15	18,097	30,614	32,053		27,330	33.78
OR30x100-0.50_8.dat-50	50	15	18,584	31,674	32,923		28,026	33.69
OR30x100-0.50_9.dat-50	50	15	18,432	31,308	32,481		27,966	34.09
OR30x100-0.50_10.dat-50	50	15	18,020	29,750	30,905		27,420	34.28
OR30x100-0.50_1.dat-100	50	1	19,936	29,647	29,647	25,597	27,647	7.41
OR30x100-0.50_2.dat-100	50	1	20,863	29,888	31,795	27,075	28,969	6.54
OR30x100-0.50_3.dat-100	50	1	20,153	29,784	30,364	26,400	28,282	6.65
OR30x100-0.50_4.dat-100	50	1	19,939	28,972	28,972	25,836	27,529	6.15
OR30x100-0.50_5.dat-100	50	1	21,653	30,673	30,673	27,834	29,571	5.87
OR30x100-0.50_6.dat-100	50	1	21,042	30,180	31,040	27,033	28,618	5.54
OR30x100-0.50_7.dat-100	50	1	20,283	30,451	30,452	26,681	28,877	7.60

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR30x100-0.50_8.dat-100	50	1	20,947	29,461	30,154	27,156	28,624	5.13
OR30x100-0.50_9.dat-100	50	1	21,885	29,984	30,731	27,090	28,534	5.06
OR30x100-0.50_10.dat-100	50	1	20,037	30,229	30,229	27,100	28,530	5.01
OR30x100-0.75_1.dat-0	75	29	9,652	10,302	10,772		9,657	0.05
OR30x100-0.75_2.dat-0	75	29	9,301	9,756	10,657		9,397	1.02
OR30x100-0.75_3.dat-0	75	29	9,041	9,545	10,543		9,157	1.27
OR30x100-0.75_4.dat-0	75	29	10,023	10,623	10,847		10,119	0.95
OR30x100-0.75_5.dat-0	75	29	7,334	7,334	8,411		7,334	0.00
OR30x100-0.75_6.dat-0	75	29	8,783	9,699	9,906		8,785	0.02
OR30x100-0.75_7.dat-0	75	29	9,261	9,757	9,757		9,307	0.49
OR30x100-0.75_8.dat-0	75	29	9,225	9,562	10,097		9,274	0.53
OR30x100-0.75_9.dat-0	75	29	9,660	10,089	10,937		9,733	0.75
OR30x100-0.75_10.dat-0	75	29	8,612	9,138	9,138		8,688	0.87
OR30x100-0.75_1.dat-50	75	15	13,858	15,421	15,421		14,319	3.22
OR30x100-0.75_2.dat-50	75	15	14,431	16,556	16,626		14,835	2.72
OR30x100-0.75_3.dat-50	75	15	14,312	16,042	16,731		14,622	2.12
OR30x100-0.75_4.dat-50	75	15	14,154	16,050	16,716		14,599	3.05
OR30x100-0.75_5.dat-50	75	15	13,870	15,596	16,815		14,321	3.15
OR30x100-0.75_6.dat-50	75	15	14,160	15,919	15,919		14,557	2.73
OR30x100-0.75_7.dat-50	75	15	10,328	15,766	16,527		14,263	27.59
OR30x100-0.75_8.dat-50	75	15	13,826	15,902	16,438		14,368	3.77
OR30x100-0.75_9.dat-50	75	15	14,221	15,871	15,871		14,668	3.05
OR30x100-0.75_10.dat-50	75	15	14,605	16,851	17,182		15,050	2.96
OR30x100-0.75_1.dat-100	75	1	15,145	15,145	16,706	13,665	15,235	0.00
OR30x100-0.75_2.dat-100	75	1	15,901	15,901	17,154	14,421	15,931	0.00
OR30x100-0.75_3.dat-100	75	1	15,501	15,501	16,795	14,020	15,561	0.00
OR30x100-0.75_4.dat-100	75	1	15,693	15,693	16,687	14,349	15,704	0.00
OR30x100-0.75_5.dat-100	75	1	15,066	15,066	16,563	13,726	15,066	0.00
OR30x100-0.75_6.dat-100	75	1	15,608	15,608	17,235	14,204	15,608	0.00
OR30x100-0.75_7.dat-100	75	1	14,810	14,810	16,254	13,330	14,815	0.00
OR30x100-0.75_8.dat-100	75	1	15,300	15,300	16,672	13,793	15,339	0.00
OR30x100-0.75_9.dat-100	75	1	12,626	15,543	16,977	14,059	15,588	9.55
OR30x100-0.75_10.dat-100	75	1	12,507	16,354	17,842	14,845	16,383	9.23
OR30x250-0.25_1.dat-0	25	29						100.00
OR30x250-0.25_2.dat-0	25	29						100.00
OR30x250-0.25_3.dat-0	25	29						100.00
OR30x250-0.25_4.dat-0	25	29						100.00
OR30x250-0.25_5.dat-0	25	29						100.00
OR30x250-0.25_6.dat-0	25	29						100.00
OR30x250-0.25_7.dat-0	25	29						100.00
OR30x250-0.25_8.dat-0	25	29						100.00
OR30x250-0.25_9.dat-0	25	29						100.00
OR30x250-0.25_10.dat-0	25	29						100.00
OR30x250-0.25_1.dat-50	25	15						100.00
OR30x250-0.25_2.dat-50	25	15						100.00
OR30x250-0.25_3.dat-50	25	15						100.00
OR30x250-0.25_4.dat-50	25	15						100.00
OR30x250-0.25_5.dat-50	25	15						100.00
OR30x250-0.25_6.dat-50	25	15						100.00
OR30x250-0.25_7.dat-50	25	15						100.00
OR30x250-0.25_8.dat-50	25	15						100.00
OR30x250-0.25_9.dat-50	25	15						100.00
OR30x250-0.25_10.dat-50	25	15						100.00
OR30x250-0.25_1.dat-100	25	1	47,685	62,454	62,454	57,151	59,568	4.06

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR30x250-0.25_2.dat-100	25	1	47,281	63,145	63,145	57,589	60,467	4.76
OR30x250-0.25_3.dat-100	25	1	44,762	61,389	61,552	55,280	58,423	5.38
OR30x250-0.25_4.dat-100	25	1	44,104	59,622	59,622	54,631	57,031	4.21
OR30x250-0.25_5.dat-100	25	1	49,566	64,027	64,027	59,421	62,358	4.71
OR30x250-0.25_6.dat-100	25	1	46,755	62,882	64,184	56,954	59,705	4.61
OR30x250-0.25_7.dat-100	25	1	48,882	63,143	63,143	57,442	60,532	5.10
OR30x250-0.25_8.dat-100	25	1	45,023	60,008	60,008	55,218	57,832	4.52
OR30x250-0.25_9.dat-100	25	1	49,081	65,036	65,036	58,335	61,704	5.46
OR30x250-0.25_10.dat-100	25	1	44,752	60,515	60,515	55,118	57,781	4.61
OR30x250-0.50_1.dat-0	50	29					57,878	100.00
OR30x250-0.50_2.dat-0	50	29					55,862	100.00
OR30x250-0.50_3.dat-0	50	29					53,747	100.00
OR30x250-0.50_4.dat-0	50	29					53,794	100.00
OR30x250-0.50_5.dat-0	50	29					51,556	100.00
OR30x250-0.50_6.dat-0	50	29					54,634	100.00
OR30x250-0.50_7.dat-0	50	29					52,579	100.00
OR30x250-0.50_8.dat-0	50	29					55,431	100.00
OR30x250-0.50_9.dat-0	50	29					54,788	100.00
OR30x250-0.50_10.dat-0	50	29					53,757	100.00
OR30x250-0.50_1.dat-50	50	15					69,476	100.00
OR30x250-0.50_2.dat-50	50	15					71,164	100.00
OR30x250-0.50_3.dat-50	50	15					69,324	100.00
OR30x250-0.50_4.dat-50	50	15					70,897	100.00
OR30x250-0.50_5.dat-50	50	15					68,846	100.00
OR30x250-0.50_6.dat-50	50	15					71,186	100.00
OR30x250-0.50_7.dat-50	50	15					67,987	100.00
OR30x250-0.50_8.dat-50	50	15					67,765	100.00
OR30x250-0.50_9.dat-50	50	15					69,846	100.00
OR30x250-0.50_10.dat-50	50	15					68,031	100.00
OR30x250-0.50_1.dat-100	50	1	47,439	66,391	76,643	66,200	71,552	0.29
OR30x250-0.50_2.dat-100	50	1	51,684	78,437	78,796	66,953	72,889	8.14
OR30x250-0.50_3.dat-100	50	1	47,608	77,047	77,047	66,136	72,226	8.43
OR30x250-0.50_4.dat-100	50	1	46,976	74,221	74,221	65,658	70,800	7.26
OR30x250-0.50_5.dat-100	50	1	46,896	75,191	75,191	65,974	71,547	7.79
OR30x250-0.50_6.dat-100	50	1	52,961	75,033	75,033	66,853	71,874	6.99
OR30x250-0.50_7.dat-100	50	1	51,425	74,651	74,651	65,133	70,073	7.05
OR30x250-0.50_8.dat-100	50	1	45,524	72,609	72,609	63,845	68,983	7.45
OR30x250-0.50_9.dat-100	50	1	51,372	73,939	73,939	65,269	70,341	7.21
OR30x250-0.50_10.dat-100	50	1	51,170	72,859	72,859	64,963	69,569	6.62
OR30x250-0.75_1.dat-0	75	29					20,531	100.00
OR30x250-0.75_2.dat-0	75	29					23,922	100.00
OR30x250-0.75_3.dat-0	75	29					22,432	100.00
OR30x250-0.75_4.dat-0	75	29					24,409	100.00
OR30x250-0.75_5.dat-0	75	29	17,158	24,747			21,944	21.81
OR30x250-0.75_6.dat-0	75	29					22,434	100.00
OR30x250-0.75_7.dat-0	75	29					22,141	100.00
OR30x250-0.75_8.dat-0	75	29					22,793	100.00
OR30x250-0.75_9.dat-0	75	29					22,874	100.00
OR30x250-0.75_10.dat-0	75	29	17,213	27,191			23,629	27.15
OR30x250-0.75_1.dat-50	75	15	23,195	40,774			34,678	33.11
OR30x250-0.75_2.dat-50	75	15	23,642	41,815			34,967	32.39
OR30x250-0.75_3.dat-50	75	15	23,943	40,383			34,184	29.96
OR30x250-0.75_4.dat-50	75	15	23,596	41,271			35,785	34.06
OR30x250-0.75_5.dat-50	75	15	24,119	41,200			35,026	31.14

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR30x250-0.75_6.dat-50	75	15	23,627	40,846			35,722	33.86
OR30x250-0.75_7.dat-50	75	15	23,374	40,010			34,015	31.28
OR30x250-0.75_8.dat-50	75	15	24,081	41,760			35,598	32.35
OR30x250-0.75_9.dat-50	75	15	23,681	41,135			35,634	33.54
OR30x250-0.75_10.dat-50	75	15	23,516	41,566			34,659	32.15
OR30x250-0.75_1.dat-100	75	1	35,895	36,063	40,966	34,538	36,237	0.47
OR30x250-0.75_2.dat-100	75	1	36,220	36,430	40,815	34,945	36,504	0.58
OR30x250-0.75_3.dat-100	75	1	36,391	36,609	41,476	35,083	36,684	0.60
OR30x250-0.75_4.dat-100	75	1	36,846	37,032	41,307	35,193	37,261	0.50
OR30x250-0.75_5.dat-100	75	1	36,130	36,271	41,647	34,861	36,418	0.39
OR30x250-0.75_6.dat-100	75	1	36,439	36,648	41,492	35,080	36,771	0.57
OR30x250-0.75_7.dat-100	75	1	35,243	35,461	40,829	33,960	35,508	0.61
OR30x250-0.75_8.dat-100	75	1	37,215	37,353	42,512	35,944	37,562	0.37
OR30x250-0.75_9.dat-100	75	1	36,702	36,862	41,515	34,968	37,109	0.43
OR30x250-0.75_10.dat-100	75	1	36,601	36,808	41,351	35,348	36,915	0.56
OR30x500-0.25_1.dat-0	25	29						100.00
OR30x500-0.25_2.dat-0	25	29						100.00
OR30x500-0.25_3.dat-0	25	29						100.00
OR30x500-0.25_4.dat-0	25	29						100.00
OR30x500-0.25_5.dat-0	25	29						100.00
OR30x500-0.25_6.dat-0	25	29						100.00
OR30x500-0.25_7.dat-0	25	29						100.00
OR30x500-0.25_8.dat-0	25	29						100.00
OR30x500-0.25_9.dat-0	25	29						100.00
OR30x500-0.25_10.dat-0	25	29						100.00
OR30x500-0.25_1.dat-50	25	15						100.00
OR30x500-0.25_2.dat-50	25	15						100.00
OR30x500-0.25_3.dat-50	25	15						100.00
OR30x500-0.25_4.dat-50	25	15						100.00
OR30x500-0.25_5.dat-50	25	15						100.00
OR30x500-0.25_6.dat-50	25	15						100.00
OR30x500-0.25_7.dat-50	25	15						100.00
OR30x500-0.25_8.dat-50	25	15						100.00
OR30x500-0.25_9.dat-50	25	15						100.00
OR30x500-0.25_10.dat-50	25	15						100.00
OR30x500-0.25_1.dat-100	25	1	89,570	122,025	122,025	110,666	117,538	5.85
OR30x500-0.25_2.dat-100	25	1	91,797	121,733	121,733	109,040	116,234	6.19
OR30x500-0.25_3.dat-100	25	1	95,947	127,974	127,974	115,167	123,627	6.84
OR30x500-0.25_4.dat-100	25	1	92,444	123,519	123,519	110,414	117,614	6.12
OR30x500-0.25_5.dat-100	25	1	91,811	121,916	121,916	110,217	116,721	5.57
OR30x500-0.25_6.dat-100	25	1	92,537	127,402	127,402	112,511	120,018	6.25
OR30x500-0.25_7.dat-100	25	1	86,807	118,761	118,761	106,181	113,072	6.09
OR30x500-0.25_8.dat-100	25	1	88,265	123,281	123,281	107,987	114,185	5.43
OR30x500-0.25_9.dat-100	25	1	88,718	121,264	121,264	108,776	115,608	5.91
OR30x500-0.25_10.dat-100	25	1	93,353	124,000	124,000	111,669	119,793	6.78
OR30x500-0.50_1.dat-0	50	29					108,021	100.00
OR30x500-0.50_2.dat-0	50	29					107,585	100.00
OR30x500-0.50_3.dat-0	50	29					103,067	100.00
OR30x500-0.50_4.dat-0	50	29					108,935	100.00
OR30x500-0.50_5.dat-0	50	29					108,370	100.00
OR30x500-0.50_6.dat-0	50	29					109,852	100.00
OR30x500-0.50_7.dat-0	50	29					101,196	100.00
OR30x500-0.50_8.dat-0	50	29					104,091	100.00
OR30x500-0.50_9.dat-0	50	29					109,002	100.00

continued on the next page

(continued)

Instance	Budget	Foll. rows	Publ. LB	Publ. UB	BOBILib	Our LB	Our point	Gap (%)
OR30x500-0.50_10.dat-0	50	29					109,755	100.00
OR30x500-0.50_1.dat-50	50	15					142,560	100.00
OR30x500-0.50_2.dat-50	50	15					140,696	100.00
OR30x500-0.50_3.dat-50	50	15					140,130	100.00
OR30x500-0.50_4.dat-50	50	15					140,690	100.00
OR30x500-0.50_5.dat-50	50	15					139,185	100.00
OR30x500-0.50_6.dat-50	50	15					140,397	100.00
OR30x500-0.50_7.dat-50	50	15					137,570	100.00
OR30x500-0.50_8.dat-50	50	15					138,542	100.00
OR30x500-0.50_9.dat-50	50	15					143,174	100.00
OR30x500-0.50_10.dat-50	50	15					138,253	100.00
OR30x500-0.50_1.dat-100	50	1	92,736	148,902	148,902	121,643	140,962	13.71
OR30x500-0.50_2.dat-100	50	1	92,207	147,816	147,816	123,890	138,905	10.81
OR30x500-0.50_3.dat-100	50	1	92,248	148,928	148,928	123,199	139,553	11.72
OR30x500-0.50_4.dat-100	50	1	94,098	147,747	147,747	125,054	141,383	11.55
OR30x500-0.50_5.dat-100	50	1	92,187	145,957	145,957	123,385	138,983	11.22
OR30x500-0.50_6.dat-100	50	1	93,745	147,913	147,913	125,045	142,158	12.04
OR30x500-0.50_7.dat-100	50	1	92,239	147,833	147,833	125,268	140,414	10.79
OR30x500-0.50_8.dat-100	50	1	92,092	146,197	146,197	120,078	137,682	12.79
OR30x500-0.50_9.dat-100	50	1	92,908	147,501	147,501	123,625	139,773	11.55
OR30x500-0.50_10.dat-100	50	1	91,157	146,327	146,435	121,197	137,127	11.62
OR30x500-0.75_1.dat-0	75	29					43,478	100.00
OR30x500-0.75_2.dat-0	75	29					44,990	100.00
OR30x500-0.75_3.dat-0	75	29					42,837	100.00
OR30x500-0.75_4.dat-0	75	29					44,294	100.00
OR30x500-0.75_5.dat-0	75	29					46,644	100.00
OR30x500-0.75_6.dat-0	75	29					45,373	100.00
OR30x500-0.75_7.dat-0	75	29					45,390	100.00
OR30x500-0.75_8.dat-0	75	29					48,711	100.00
OR30x500-0.75_9.dat-0	75	29					43,827	100.00
OR30x500-0.75_10.dat-0	75	29					45,775	100.00
OR30x500-0.75_1.dat-50	75	15					68,720	100.00
OR30x500-0.75_2.dat-50	75	15					69,640	100.00
OR30x500-0.75_3.dat-50	75	15					67,961	100.00
OR30x500-0.75_4.dat-50	75	15					68,523	100.00
OR30x500-0.75_5.dat-50	75	15					70,609	100.00
OR30x500-0.75_6.dat-50	75	15					68,309	100.00
OR30x500-0.75_7.dat-50	75	15					70,946	100.00
OR30x500-0.75_8.dat-50	75	15					69,553	100.00
OR30x500-0.75_9.dat-50	75	15					69,181	100.00
OR30x500-0.75_10.dat-50	75	15					69,553	100.00
OR30x500-0.75_1.dat-100	75	1	70,260	71,066	102,997	69,453	71,091	1.13
OR30x500-0.75_2.dat-100	75	1	54,615	72,321	102,633	70,617	72,265	2.28
OR30x500-0.75_3.dat-100	75	1	69,924	70,774	97,761	69,109	70,777	1.20
OR30x500-0.75_4.dat-100	75	1	70,645	71,580	95,980	68,950	71,456	1.13
OR30x500-0.75_5.dat-100	75	1	72,234	73,108	103,856	70,425	73,245	1.20
OR30x500-0.75_6.dat-100	75	1	70,312	71,195	95,892	69,397	71,025	1.00
OR30x500-0.75_7.dat-100	75	1	72,604	74,658	92,638	70,376	73,314	0.97
OR30x500-0.75_8.dat-100	75	1	70,708	71,683	103,231	69,876	71,592	1.23
OR30x500-0.75_9.dat-100	75	1	71,479	72,484	96,781	70,708	72,384	1.25
OR30x500-0.75_10.dat-100	75	1	71,384	72,146	91,017	70,444	72,101	0.99

I.4 Clique interdiction

Table S6. Edge clique interdiction, BOBILib set `clique`: n vertices, density d, m edges, budget k (the leader deletes at most k edges). Lower bound: Mantel's theorem ($m-k > \lfloor n^2/4 \rfloor$, so a triangle survives) or Brouwer's 1981 Theorem 2 ($m-k \geq t_3(n) - \lfloor n/3 \rfloor + 2$, so a K_4-free remainder is 3-partite) together with exact solver proofs that every 3-partition has more than k edges inside its parts ($w_3(G) > k$). Upper bound: the solution file deletes the edges inside an r-partition (certificate: r and the number of inside edges, at most k), leaving an r-partite graph. Open: the best 3-partitions found for normalClique60-70-2, normalClique60-70-3, normalClique60-70-5 have 311, 310, 310 inside edges, more than $k = 309$, so only $3 \leq$ value ≤ 4 is known.

Instance	n	d	m	k	BOBILib	LB	Argument	UB	Certificate	Status
normalClique40-70-1	40	0.7	546	136	6	3	Mantel	3	3-partition, 125	optimal
normalClique40-70-2	40	0.7	546	136	6	3	Mantel	3	3-partition, 125	optimal
normalClique40-70-3	40	0.7	546	136	6	3	Mantel	3	3-partition, 126	optimal
normalClique40-70-4	40	0.7	546	136	5	3	Mantel	3	3-partition, 125	optimal
normalClique40-70-5	40	0.7	546	136	7	3	Mantel	3	3-partition, 128	optimal
normalClique40-70-6	40	0.7	546	136	6	3	Mantel	3	3-partition, 126	optimal
normalClique40-70-7	40	0.7	546	136	5	3	Mantel	3	3-partition, 123	optimal
normalClique40-70-8	40	0.7	546	136	6	3	Mantel	3	3-partition, 126	optimal
normalClique40-70-9	40	0.7	546	136	6	3	Mantel	3	3-partition, 125	optimal
normalClique40-70-10	40	0.7	546	136	6	3	Mantel	3	3-partition, 125	optimal
normalClique40-90-1	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 131	optimal
normalClique40-90-2	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 129	optimal
normalClique40-90-3	40	0.9	702	175	9	4	Brouwer $+ w_3(G) > k$	4	4-partition, 128	optimal
normalClique40-90-4	40	0.9	702	175	9	4	Brouwer $+ w_3(G) > k$	4	4-partition, 127	optimal
normalClique40-90-5	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 128	optimal
normalClique40-90-6	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 127	optimal
normalClique40-90-7	40	0.9	702	175	9	4	Brouwer $+ w_3(G) > k$	4	4-partition, 127	optimal
normalClique40-90-8	40	0.9	702	175	11	4	Brouwer $+ w_3(G) > k$	4	4-partition, 129	optimal
normalClique40-90-9	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 130	optimal
normalClique40-90-10	40	0.9	702	175	10	4	Brouwer $+ w_3(G) > k$	4	4-partition, 130	optimal
normalClique50-70-1	50	0.7	857	214	7	3	Mantel	3	3-partition, 205	optimal
normalClique50-70-2	50	0.7	857	214	7	3	Mantel	3	3-partition, 205	optimal
normalClique50-70-3	50	0.7	857	214	7	3	Mantel	3	3-partition, 208	optimal
normalClique50-70-4	50	0.7	857	214	7	3	Mantel	3	3-partition, 203	optimal
normalClique50-70-5	50	0.7	857	214	7	3	Mantel	3	3-partition, 205	optimal
normalClique50-70-6	50	0.7	857	214	8	3	Mantel	3	3-partition, 209	optimal
normalClique50-70-7	50	0.7	857	214	8	3	Mantel	3	3-partition, 205	optimal
normalClique50-70-8	50	0.7	857	214	7	3	Mantel	3	3-partition, 204	optimal
normalClique50-70-9	50	0.7	857	214	7	3	Mantel	3	3-partition, 210	optimal
normalClique50-70-10	50	0.7	857	214	8	3	Mantel	3	3-partition, 208	optimal
normalClique50-90-1	50	0.9	1,102	275	11	4	Brouwer $+ w_3(G) > k$	4	4-partition, 210	optimal
normalClique50-90-2	50	0.9	1,102	275	11	4	Brouwer $+ w_3(G) > k$	4	4-partition, 212	optimal
normalClique50-90-3	50	0.9	1,102	275	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 210	optimal
normalClique50-90-4	50	0.9	1,102	275	11	4	Brouwer $+ w_3(G) > k$	4	4-partition, 210	optimal
normalClique50-90-5	50	0.9	1,102	275	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 212	optimal
normalClique50-90-6	50	0.9	1,102	275	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 212	optimal
normalClique50-90-7	50	0.9	1,102	275	11	4	Brouwer $+ w_3(G) > k$	4	4-partition, 210	optimal
normalClique50-90-8	50	0.9	1,102	275	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 211	optimal
normalClique50-90-9	50	0.9	1,102	275	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 209	optimal
normalClique50-90-10	50	0.9	1,102	275	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 209	optimal
normalClique60-70-1	60	0.7	1,239	309	8	3	Mantel	3	3-partition, 306	optimal
normalClique60-70-2	60	0.7	1,239	309	9	3	Mantel	4	4-partition, 202	**open**
normalClique60-70-3	60	0.7	1,239	309	9	3	Mantel	4	4-partition, 200	**open**
normalClique60-70-4	60	0.7	1,239	309	9	3	Mantel	3	3-partition, 309	optimal
normalClique60-70-5	60	0.7	1,239	309	8	3	Mantel	4	4-partition, 202	**open**
normalClique60-70-6	60	0.7	1,239	309	9	3	Mantel	3	3-partition, 306	optimal
normalClique60-70-7	60	0.7	1,239	309	8	3	Mantel	3	3-partition, 307	optimal
normalClique60-70-8	60	0.7	1,239	309	8	3	Mantel	3	3-partition, 308	optimal

continued on the next page

(continued)

Instance	n	d	m	k	BOBILib	LB	Argument	UB	Certificate	Status
normalClique60-70-9	60	0.7	1,239	309	8	3	Mantel	3	3-partition, 307	optimal
normalClique60-70-10	60	0.7	1,239	309	8	3	Mantel	3	3-partition, 308	optimal
normalClique60-90-1	60	0.9	1,593	398	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 314	optimal
normalClique60-90-2	60	0.9	1,593	398	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 312	optimal
normalClique60-90-3	60	0.9	1,593	398	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 311	optimal
normalClique60-90-4	60	0.9	1,593	398	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 313	optimal
normalClique60-90-5	60	0.9	1,593	398	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 311	optimal
normalClique60-90-6	60	0.9	1,593	398	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 314	optimal
normalClique60-90-7	60	0.9	1,593	398	13	4	Brouwer $+ w_3(G) > k$	4	4-partition, 313	optimal
normalClique60-90-8	60	0.9	1,593	398	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 310	optimal
normalClique60-90-9	60	0.9	1,593	398	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 312	optimal
normalClique60-90-10	60	0.9	1,593	398	12	4	Brouwer $+ w_3(G) > k$	4	4-partition, 317	optimal

I.5 Network interdiction

Table S7. The two attack-protect games (`inter-fire`) BOBILib lists as feasible, proven optimal by enumerating every attack of at most Φ nodes, with the follower (protect at most Λ nodes) solved exactly by a tree dynamic program and the minimiser re-solved by HiGHS. Time: wall seconds of the enumeration on one thread of a loaded machine.

Instance	Nodes	Edges	Φ	Λ	Attacks	Optimum	Optimal attacks	BOBILib	Time (s)
tree-50_1-5-5_006	49	42	5	5	2,138,410	26	4	26	80
tree-50_1-5-5_010	49	44	5	5	2,138,410	26	28	26	70

Table S8. The 34 tree instances BOBILib lists as optimal, re-derived by the same enumeration: instances per group, nodes (after removing the vaccinated ones), budgets, attacks per instance, the optimal values found, and how many equal BOBILib's value with a certified solution file.

Group	Inst.	Nodes	Φ	Λ	Attacks	Optima	Agree
tree-25_1-3-3	4	24	3	3	2,325	12, 13, 13, 13	4/4
tree-25_2-2-2	4	23	2	2	277	17, 17, 17, 18	4/4
tree-25_3-3-3	4	22	3	3	1,794	15, 16, 16, 17	4/4
tree-50_1-3-3	4	49	3	3	19,650	28, 28, 30, 32	4/4
tree-50_1-5-5	2	49	5	5	2,138,410	24, 25	2/2
tree-50_3-3-1	4	47	3	1	17,344	26, 27, 30, 31	4/4
tree-80_2-2-2	4	78	2	2	3,082	56, 57, 61, 63	4/4
tree-80_3-3-1	4	77	3	1	76,154	45, 45, 48, 48	4/4
tree-80_3-3-3	4	77	3	3	76,154	55, 56, 56, 58	4/4

I.6 General instances

Table S9. The 40 open MIPLIB-derived instances with no bilevel feasible point: the follower's own rows admit a recession direction d (follower variables only) with $f^\top d < 0$, for every leader choice (Meyer 1974). Support: nonzero entries of d; $f^\top d$ rounded to four decimals; exact: checked in exact rational arithmetic by `scripts/verify_ray.py` (the two supportcase42 directions leave residuals of about 10^{-12} relative and rest on floating point).

Instance	Collection	Support	$f^\top d$	Exact
biella1_50_50	miplib2010	621	−444,178,600	yes
binkar10_1_50_50	miplib2010	208	−90,000,000	yes

continued on the next page

(continued)

Instance	Collection	Support	$f^\top d$	Exact
brazil3_0_100	miplib2017	3	−1	yes
brazil3_50_50	miplib2017	11	−1	yes
buildingenergy_0_100	miplib2017	17	−10,766.212	yes
buildingenergy_50_50	miplib2017	8,777	−11,236.372	yes
core2536-691_50_50	miplib2010	9	−200.9	yes
cost266-UUE_50_50	miplib2017	2,024	−13,041.23	yes
gen-ip054_0_100	miplib2017	9	−1,475.2477	yes
gen-ip054_50_50	miplib2017	13	−2,718.065	yes
highschool1-aigio_0_100	miplib2017	3	−1	yes
irish-electricity_0_100	miplib2017	5,206	−5,206	yes
irish-electricity_50_50	miplib2017	5,206	−5,206	yes
lotsize_50_50	miplib2017	297	−871	yes
mad_0_100	miplib2017	20	−20	yes
mad_50_50	miplib2017	20	−20	yes
neos-476283_0_100	miplib2010	369	−369	yes
neos-476283_50_50	miplib2010	369	−369	yes
neos-1396125_0_100	miplib2010	3	−240	yes
neos-1396125_50_50	miplib2010	3	−240	yes
neos-3627168-kasai_50_50	miplib2017	3	−3	yes
neos-5093327-huahum_0_100	miplib2017	3,968	−3,968	yes
neos-5093327-huahum_50_50	miplib2017	3,968	−3,968	yes
nu25-pr12_0_100	miplib2017	36	−9,000	yes
rail507_0_100	miplib2010	10	−201	yes
rail507_50_50	miplib2010	10	−201	yes
rmatr100-p5_0_100	miplib2010	4,392	−117,792	yes
rmatr100-p5_50_50	miplib2010	4,392	−117,792	yes
rmatr100-p10_0_100	miplib2010	3,679	−61,179	yes
rmatr100-p10_50_50	miplib2010	3,679	−61,179	yes
rmatr200-p5_0_100	miplib2017	18,908	−988,708	yes
rmatr200-p5_50_50	miplib2017	18,908	−988,708	yes
snp-02-004-104_0_100	miplib2017	104	−10,400,000	yes
snp-02-004-104_50_50	miplib2017	104	−10,400,000	yes
supportcase40_0_100	miplib2017	3,360	−338,410.0838	yes
supportcase40_50_50	miplib2017	3,360	−338,410.0838	yes
supportcase42_0_100	miplib2017	9,733	−8,706	no (floating point)
supportcase42_50_50	miplib2017	9,733	−8,706	no (floating point)
tr12-30_50_50	miplib2017	180	−405	yes
trento1_50_50	miplib2017	655	−33,097,000	yes

Table S10. Five MIPLIB-derived instances whose high point relaxation is exactly the MIPLIB model they were built from (checked in exact arithmetic by `scripts/compare_hpr.py`), so the published MIPLIB optimum (MIPLIB 2017's solution file) is a lower bound; a verified bilevel feasible point at that value is optimal. The objective of noswot takes integer values only, so its bound rounds up to −41. Status: BOBILib's before this work. (neos-950242_0_100 meets its bound too, but was already listed as optimal in an earlier BOBILib release and is counted as published.)

Instance	BOBILib	MIPLIB instance	MIPLIB optimum	Bilevel optimum	Point from
noswot_0_100	feasible	noswot	−41.00000885	−41	BOBILib's solution file
noswot_50_50	feasible	noswot	−41.00000885	−41	BOBILib's solution file
pigeon-10_0_100	open	pigeon-10	−9,000	−9,000	`bobi general`
timtab1_0_100	open	timtab1	764,771.99999978	764,771.99999978	`bobi general`
pigeon-10_50_50	open	pigeon-10	−9,000	−9,000	`bobi coupled`

Table S11. The 90 first bilevel feasible points for open MIPLIB-derived instances (BOBILib lists no point). Coupling: whether leader rows contain follower variables. Method: `hpr-f-t`, the high point relaxation, then the follower solved with the leader fixed, then an optimistic tie-break (`bobi general`); `hpr`, `penalty`, `follow`: the part of the `bobi coupled` portfolio that found the point (the HPR's own leader values, a penalised HPR, best-response dynamics). Values rounded to four decimals (full precision in `instances.csv`); the leader minimises, so does the follower. *: the follower's value is about 10^{-7} relative above its optimum, inside BOBILib's tolerance of 10^{-4}. Three further points are optimal (Table S10).

Instance	Collection	Coupling	Method	Leader value	Follower value
air05-0.900000	miplib3	no	hpr-f-t	64,955	−63,283
beasleyC3_0_100	miplib2010	no	hpr-f-t	6,844	−6,844
beasleyC3_50_50	miplib2010	yes	hpr	6,844	−6,844
binkar10_1_0_100	miplib2010	no	hpr-f-t	5,006,810.58	−5,000,741.3199
cap6000-0.500000	miplib3	no	hpr-f-t	−1,169,217	0
cap6000-0.900000	miplib3	no	hpr-f-t	−100,780	45,829
cmflsp50-24-8-8_0_100	miplib2017	no	hpr-f-t	59,480,213.4006	−12,534,896.7844
core2536-691_0_100	miplib2010	no	hpr-f-t	9,999,999,000	−9,999,998,544
cost266-UUE_0_100	miplib2017	no	hpr-f-t	35,801,080.9569	−10,431,020.9769
ex10_0_100	miplib2017	no	hpr-f-t	100	−51
exp-1-500-5-5_0_100	miplib2017	no	hpr-f-t	912,510.9121	−879,351.9121
h80x6320d_0_100	miplib2017	no	hpr-f-t	12,461.7042	−10,960.0714
ic97_potential_0_100	miplib2017	no	hpr-f-t	4,003	−353
ic97_potential_50_50*	miplib2017	yes	penalty	4,196.9999	−591.9999
lotsize_0_100	miplib2017	no	hpr-f-t	3,691,725	−3,059,545
mc11_0_100	miplib2017	no	hpr-f-t	128,960	−128,960
mc11_50_50	miplib2017	yes	hpr	128,960	−128,960
mik-250-1-100-1_0_100	miplib2010	no	hpr-f-t	890,671	−1,000,000
mik-250-1-100-1_50_50	miplib2010	yes	hpr	890,671	−1,000,000
mik-250-20-75-4_0_100	miplib2017	no	hpr-f-t	663,799	−750,000
mik-250-20-75-4_50_50	miplib2017	yes	hpr	663,799	−750,000
mitre-0.500000	miplib3	no	hpr-f-t	147,075	−96,600
mitre-0.900000	miplib3	no	hpr-f-t	169,500	−169,500
mushroom-best_0_100	miplib2017	no	hpr-f-t	4,230.0553	−4,230
mushroom-best_50_50	miplib2017	yes	hpr	4,230.0553	−4,230
n4-3_0_100	miplib2010	no	hpr-f-t	34,802,892.5199	−34,801,022.5199
n4-3_50_50*	miplib2010	yes	penalty	50,621,405.7289	−42,710,510.7289
n5-3_0_100	miplib2017	no	hpr-f-t	30,001,631.9999	−30,000,661.9999
n5-3_50_50*	miplib2017	yes	hpr	30,001,771.9999	−30,000,801.9999
n9-3_0_100	miplib2017	no	hpr-f-t	50,404,627.9598	−50,401,623.9598
n9-3_50_50*	miplib2017	yes	penalty	74,423,848.7588	−62,411,798.7588
neos17_0_100	miplib2017	no	hpr-f-t	0.6872	−0.564
neos17_50_50*	miplib2017	yes	hpr	0.6872	−0.564
neos-631710_0_100	miplib2017	no	hpr-f-t	556	−556
neos-827175_0_100	miplib2017	no	hpr-f-t	122.0015	−122
neos-827175_50_50	miplib2017	yes	hpr	122.0015	−122
neos-860300_0_100	miplib2017	no	hpr-f-t	5,920	−3,702
neos-873061_0_100	miplib2017	no	hpr-f-t	258,644.394	−258,644.1675
neos-916792_0_100	miplib2010	no	hpr-f-t	32.6951	−5.6656
neos-933966_0_100	miplib2017	no	hpr-f-t	326	−189
neos-933966_50_50	miplib2017	yes	hpr	47,506	−224
neos-934278_0_100	miplib2010	no	hpr-f-t	6,339	−267
neos-934278_50_50	miplib2010	yes	hpr	32,490	−299
neos-950242_50_50	miplib2017	yes	follow	24	−24
neos-1122047_0_100	miplib2017	no	hpr-f-t	472	−472
neos-1337307_50_50	miplib2010	yes	hpr	−201,272	27,257
neos-1445765_0_100	miplib2017	no	hpr-f-t	−17,783	17,783
neos-1445765_50_50	miplib2017	yes	penalty	0	0

continued on the next page

(continued)

Instance	Collection	Coupling	Method	Leader value	Follower value
neos-1456979_0_100	miplib2017	no	hpr-f-t	250	−157
neos-2978193-inde_0_100	miplib2017	no	hpr-f-t	61.454	−62.3292
neos-2978193-inde_50_50*	miplib2017	yes	hpr	69.275	−69.5863
neos-3216931-puriri_0_100	miplib2017	no	hpr-f-t	81,430	900
neos-3627168-kasai_0_100	miplib2017	no	hpr-f-t	1,591,085.62	−1,591,085.62
neos-3754480-nidda_0_100	miplib2017	no	hpr-f-t	13,973.2905	−2,052,644.3591
neos-4300652-rahue_0_100	miplib2017	no	hpr-f-t	6.4075	−2.3316
neos-4722843-widden_0_100	miplib2017	no	hpr-f-t	25,109.6634	−7,400
neos-4763324-toguru_0_100	miplib2017	no	hpr-f-t	17,296.7271	−13,725.617
neos-4954672-berkel_0_100	miplib2017	no	hpr-f-t	8,891,491	−7,334,836
neos-4954672-berkel_50_50	miplib2017	yes	hpr	8,861,094	−7,334,836
neos-5188808-nattai_0_100	miplib2017	no	hpr-f-t	6.1216	−6.1216
neos-5188808-nattai_50_50	miplib2017	yes	hpr	8.1556	−8.1556
netdiversion_0_100	miplib2010	no	hpr-f-t	19,850,249	−19,850,249
ns1830653_0_100	miplib2010	no	hpr-f-t	23,622	−1,910
opm2-z10-s4_0_100	miplib2017	no	hpr-f-t	−11,630	4,812
p200x1188c_0_100	miplib2017	no	hpr-f-t	3,584,430	−3,584,430
p200x1188c_50_50	miplib2017	yes	hpr	3,584,430	−3,584,430
p0548-0.500000	miplib3	no	hpr-f-t	22,197	−17,695
pg5_34_0_100	miplib2010	no	hpr-f-t	−11,516.287	1,824.4401
pg5_34_50_50	miplib2010	yes	penalty	−11,591.1699	0
pg_0_100	miplib2017	no	hpr-f-t	−5,364.2594	2,018.3422
pg_50_50*	miplib2017	yes	follow	−6,061.0721	575.8462
ran16x16_0_100	miplib2010	no	hpr-f-t	43,000	−42,126
ran16x16_50_50	miplib2010	yes	hpr	43,000	−42,126
rmine6_0_100	miplib2010	no	hpr-f-t	−440.6503	201.3995
rmine6_50_50	miplib2010	yes	follow	−153.7498	119.897
s100_0_100	miplib2017	no	hpr-f-t	−0.0758	0
s250r10_0_100	miplib2017	no	hpr-f-t	−0.0608	0.0035
satellites1-25_0_100	miplib2010	no	hpr-f-t	32	−32
satellites2-40_0_100	miplib2017	no	hpr-f-t	0	0
seymour1_0_100	miplib2017	no	hpr-f-t	959.536	−685.9999
seymour1_50_50*	miplib2017	yes	hpr	960.6331	−685.9999
sing44_0_100	miplib2017	no	hpr-f-t	10,059,257.3791	−112,109.371
sing326_0_100	miplib2017	no	hpr-f-t	20,652,331.0689	−181,252.322
sp150x300d_0_100	miplib2017	no	hpr-f-t	300	−300
sp150x300d_50_50	miplib2017	yes	hpr	300	−300
supportcase12_0_100	miplib2017	no	hpr-f-t	−1,811.9515	0
timtab1_50_50	miplib2010	yes	hpr	764,774	−20,655.996
tr12-30_0_100	miplib2017	no	hpr-f-t	201,018.9907	−92,640.9907
uct-subprob_0_100	miplib2017	no	hpr-f-t	827.9999	−681.9999
uct-subprob_50_50*	miplib2017	yes	hpr	847.9999	−681.9999

I.7 Unchanged instances

Table S12. Instances whose BOBILib status is unchanged, by family: BOBILib status (feasible or open), and how many now have a verified point better than BOBILib's (marked * in the lists below).

Family	Collections	Feasible	Open	Better point	Total
multidimensional knapsack interdiction	or 582	503	79	462	582
general, pure integer	miplib2017 42, miplib3 20, miplib2010 13, misc 1	60	16	0	76
general, mixed integer	miplib2017 41, miplib2010 6	11	36	0	47

continued on the next page

(continued)

Family	Collections	Feasible	Open	Better point	Total
generalized interdiction	generalized 8	8	0	0	8
clique interdiction	clique 3	3	0	3	3
Total		585	131	465	716

Multidimensional knapsack interdiction (582)

OR5x100-0.25_1.dat-0* OR5x100-0.25_1.dat-50* OR5x100-0.25_1.dat-100* OR5x100-0.25_2.dat-0* OR5x100-0.25_2.dat-50* OR5x100-0.25_2.dat-100* OR5x100-0.25_3.dat-0* OR5x100-0.25_3.dat-50* OR5x100-0.25_3.dat-100* OR5x100-0.25_4.dat-0* OR5x100-0.25_4.dat-50* OR5x100-0.25_4.dat-100* OR5x100-0.25_5.dat-0* OR5x100-0.25_5.dat-50* OR5x100-0.25_5.dat-100* OR5x100-0.25_6.dat-0* OR5x100-0.25_6.dat-50* OR5x100-0.25_6.dat-100* OR5x100-0.25_7.dat-0* OR5x100-0.25_7.dat-50* OR5x100-0.25_7.dat-100* OR5x100-0.25_8.dat-0* OR5x100-0.25_8.dat-50* OR5x100-0.25_8.dat-100* OR5x100-0.25_9.dat-0* OR5x100-0.25_9.dat-50* OR5x100-0.25_9.dat-100* OR5x100-0.25_10.dat-0* OR5x100-0.25_10.dat-50* OR5x100-0.25_10.dat-100* OR5x100-0.50_1.dat-0* OR5x100-0.50_1.dat-50* OR5x100-0.50_1.dat-100* OR5x100-0.50_2.dat-0* OR5x100-0.50_2.dat-50* OR5x100-0.50_2.dat-100* OR5x100-0.50_3.dat-0* OR5x100-0.50_3.dat-50* OR5x100-0.50_3.dat-100* OR5x100-0.50_4.dat-0* OR5x100-0.50_4.dat-50* OR5x100-0.50_4.dat-100* OR5x100-0.50_5.dat-0* OR5x100-0.50_5.dat-50* OR5x100-0.50_5.dat-100* OR5x100-0.50_6.dat-0* OR5x100-0.50_6.dat-50* OR5x100-0.50_6.dat-100* OR5x100-0.50_7.dat-0* OR5x100-0.50_7.dat-50* OR5x100-0.50_7.dat-100* OR5x100-0.50_8.dat-0* OR5x100-0.50_8.dat-50* OR5x100-0.50_8.dat-100* OR5x100-0.50_9.dat-0* OR5x100-0.50_9.dat-50* OR5x100-0.50_9.dat-100* OR5x100-0.50_10.dat-0* OR5x100-0.50_10.dat-50* OR5x100-0.50_10.dat-100* OR5x250-0.25_1.dat-0* OR5x250-0.25_1.dat-50* OR5x250-0.25_1.dat-100* OR5x250-0.25_2.dat-0 OR5x250-0.25_2.dat-50* OR5x250-0.25_2.dat-100* OR5x250-0.25_3.dat-0 OR5x250-0.25_3.dat-50* OR5x250-0.25_3.dat-100* OR5x250-0.25_4.dat-0 OR5x250-0.25_4.dat-50* OR5x250-0.25_4.dat-100* OR5x250-0.25_5.dat-0 OR5x250-0.25_5.dat-50* OR5x250-0.25_5.dat-100* OR5x250-0.25_6.dat-0 OR5x250-0.25_6.dat-50* OR5x250-0.25_6.dat-100* OR5x250-0.25_7.dat-0* OR5x250-0.25_7.dat-50* OR5x250-0.25_7.dat-100* OR5x250-0.25_8.dat-0* OR5x250-0.25_8.dat-50* OR5x250-0.25_8.dat-100* OR5x250-0.25_9.dat-0 OR5x250-0.25_9.dat-50* OR5x250-0.25_9.dat-100* OR5x250-0.25_10.dat-0 OR5x250-0.25_10.dat-50* OR5x250-0.25_10.dat-100* OR5x250-0.50_1.dat-0* OR5x250-0.50_1.dat-50* OR5x250-0.50_1.dat-100* OR5x250-0.50_2.dat-0* OR5x250-0.50_2.dat-50* OR5x250-0.50_2.dat-100* OR5x250-0.50_3.dat-0* OR5x250-0.50_3.dat-50* OR5x250-0.50_3.dat-100* OR5x250-0.50_4.dat-0* OR5x250-0.50_4.dat-50* OR5x250-0.50_4.dat-100* OR5x250-0.50_5.dat-0* OR5x250-0.50_5.dat-50* OR5x250-0.50_5.dat-100* OR5x250-0.50_6.dat-0* OR5x250-0.50_6.dat-50* OR5x250-0.50_6.dat-100* OR5x250-0.50_7.dat-0* OR5x250-0.50_7.dat-50* OR5x250-0.50_7.dat-100* OR5x250-0.50_8.dat-0* OR5x250-0.50_8.dat-50* OR5x250-0.50_8.dat-100* OR5x250-0.50_9.dat-0* OR5x250-0.50_9.dat-50* OR5x250-0.50_9.dat-100* OR5x250-0.50_10.dat-0* OR5x250-0.50_10.dat-50* OR5x250-0.50_10.dat-100* OR5x500-0.25_1.dat-0 OR5x500-0.25_1.dat-50* OR5x500-0.25_1.dat-100* OR5x500-0.25_2.dat-0 OR5x500-0.25_2.dat-50* OR5x500-0.25_2.dat-100* OR5x500-0.25_3.dat-0 OR5x500-0.25_3.dat-50* OR5x500-0.25_3.dat-100* OR5x500-0.25_4.dat-0 OR5x500-0.25_4.dat-50* OR5x500-0.25_4.dat-100* OR5x500-0.25_5.dat-0 OR5x500-0.25_5.dat-50* OR5x500-0.25_5.dat-100* OR5x500-0.25_6.dat-0 OR5x500-0.25_6.dat-50* OR5x500-0.25_6.dat-100* OR5x500-0.25_7.dat-0 OR5x500-0.25_7.dat-50* OR5x500-0.25_7.dat-100* OR5x500-0.25_8.dat-0 OR5x500-0.25_8.dat-50* OR5x500-0.25_8.dat-100* OR5x500-0.25_9.dat-0 OR5x500-0.25_9.dat-50* OR5x500-0.25_9.dat-100* OR5x500-0.25_10.dat-0 OR5x500-0.25_10.dat-50* OR5x500-0.25_10.dat-100* OR5x500-0.50_1.dat-0* OR5x500-0.50_1.dat-50* OR5x500-0.50_1.dat-100* OR5x500-0.50_2.dat-50* OR5x500-0.50_2.dat-100* OR5x500-0.50_3.dat-0* OR5x500-0.50_3.dat-50* OR5x500-0.50_3.dat-100* OR5x500-0.50_4.dat-50* OR5x500-0.50_4.dat-100* OR5x500-0.50_5.dat-0* OR5x500-0.50_5.dat-50* OR5x500-0.50_5.dat-100* OR5x500-0.50_6.dat-0* OR5x500-0.50_6.dat-50* OR5x500-0.50_6.dat-100* OR5x500-0.50_7.dat-0* OR5x500-0.50_7.dat-50* OR5x500-0.50_7.dat-100* OR5x500-0.50_8.dat-0* OR5x500-0.50_8.dat-50* OR5x500-0.50_8.dat-100* OR5x500-0.50_9.dat-50* OR5x500-0.50_9.dat-100* OR5x500-0.50_10.dat-0* OR5x500-0.50_10.dat-50* OR5x500-0.50_10.dat-100* OR5x500-0.75_1.dat-0* OR5x500-0.75_1.dat-50* OR5x500-0.75_1.dat-100* OR5x500-0.75_2.dat-0* OR5x500-0.75_2.dat-50* OR5x500-0.75_2.dat-100* OR5x500-0.75_3.dat-0* OR5x500-0.75_3.dat-50* OR5x500-0.75_3.dat-100* OR5x500-0.75_4.dat-0* OR5x500-0.75_4.dat-50* OR5x500-0.75_4.dat-100* OR5x500-0.75_5.dat-0* OR5x500-0.75_5.dat-50* OR5x500-0.75_5.dat-100*

OR5x500-0.75_6.dat-0*
OR5x500-0.75_6.dat-50*
OR5x500-0.75_6.dat-100*
OR5x500-0.75_7.dat-0*
OR5x500-0.75_7.dat-50*
OR5x500-0.75_7.dat-100*
OR5x500-0.75_8.dat-0*
OR5x500-0.75_8.dat-50*
OR5x500-0.75_8.dat-100*
OR5x500-0.75_9.dat-0*
OR5x500-0.75_9.dat-50*
OR5x500-0.75_9.dat-100*
OR5x500-0.75_10.dat-0*
OR5x500-0.75_10.dat-50*
OR5x500-0.75_10.dat-100*
OR10x100-0.25_1.dat-0*
OR10x100-0.25_1.dat-50*
OR10x100-0.25_1.dat-100*
OR10x100-0.25_2.dat-0
OR10x100-0.25_2.dat-50*
OR10x100-0.25_2.dat-100*
OR10x100-0.25_3.dat-0*
OR10x100-0.25_3.dat-50*
OR10x100-0.25_3.dat-100*
OR10x100-0.25_4.dat-0*
OR10x100-0.25_4.dat-50
OR10x100-0.25_4.dat-100*
OR10x100-0.25_5.dat-0
OR10x100-0.25_5.dat-50*
OR10x100-0.25_5.dat-100*
OR10x100-0.25_6.dat-0*
OR10x100-0.25_6.dat-50*
OR10x100-0.25_6.dat-100*
OR10x100-0.25_7.dat-0
OR10x100-0.25_7.dat-50*
OR10x100-0.25_7.dat-100*
OR10x100-0.25_8.dat-0*
OR10x100-0.25_8.dat-50*
OR10x100-0.25_8.dat-100*
OR10x100-0.25_9.dat-0*
OR10x100-0.25_9.dat-50*
OR10x100-0.25_9.dat-100*
OR10x100-0.25_10.dat-0*
OR10x100-0.25_10.dat-50*
OR10x100-0.25_10.dat-100*
OR10x100-0.50_1.dat-0*
OR10x100-0.50_1.dat-50*
OR10x100-0.50_1.dat-100*
OR10x100-0.50_2.dat-0*
OR10x100-0.50_2.dat-50*
OR10x100-0.50_2.dat-100*
OR10x100-0.50_3.dat-0*
OR10x100-0.50_3.dat-50*
OR10x100-0.50_3.dat-100*
OR10x100-0.50_4.dat-0*
OR10x100-0.50_4.dat-50*
OR10x100-0.50_4.dat-100*
OR10x100-0.50_5.dat-0*
OR10x100-0.50_5.dat-50*
OR10x100-0.50_5.dat-100*
OR10x100-0.50_6.dat-0*
OR10x100-0.50_6.dat-50*
OR10x100-0.50_6.dat-100*
OR10x100-0.50_7.dat-0*
OR10x100-0.50_7.dat-50*
OR10x100-0.50_7.dat-100*
OR10x100-0.50_8.dat-0*
OR10x100-0.50_8.dat-50*
OR10x100-0.50_8.dat-100*
OR10x100-0.50_9.dat-0*
OR10x100-0.50_9.dat-50*
OR10x100-0.50_9.dat-100*
OR10x100-0.50_10.dat-0*
OR10x100-0.50_10.dat-50*
OR10x100-0.50_10.dat-100*
OR10x100-0.75_1.dat-0*
OR10x100-0.75_1.dat-50*
OR10x100-0.75_2.dat-50*
OR10x100-0.75_3.dat-0*
OR10x100-0.75_3.dat-50*
OR10x100-0.75_4.dat-50*
OR10x100-0.75_5.dat-0*
OR10x100-0.75_5.dat-50*
OR10x100-0.75_6.dat-50*
OR10x100-0.75_7.dat-50*
OR10x100-0.75_8.dat-50*
OR10x100-0.75_9.dat-50*
OR10x100-0.75_10.dat-0*
OR10x100-0.75_10.dat-50*
OR10x250-0.25_1.dat-0
OR10x250-0.25_1.dat-50
OR10x250-0.25_1.dat-100*
OR10x250-0.25_2.dat-0
OR10x250-0.25_2.dat-50
OR10x250-0.25_2.dat-100*
OR10x250-0.25_3.dat-0
OR10x250-0.25_3.dat-50
OR10x250-0.25_3.dat-100*
OR10x250-0.25_4.dat-0
OR10x250-0.25_4.dat-50
OR10x250-0.25_4.dat-100*
OR10x250-0.25_5.dat-0
OR10x250-0.25_5.dat-50
OR10x250-0.25_5.dat-100*
OR10x250-0.25_6.dat-0
OR10x250-0.25_6.dat-50
OR10x250-0.25_6.dat-100*
OR10x250-0.25_7.dat-0
OR10x250-0.25_7.dat-50
OR10x250-0.25_7.dat-100*
OR10x250-0.25_8.dat-0
OR10x250-0.25_8.dat-50
OR10x250-0.25_8.dat-100*
OR10x250-0.25_9.dat-0
OR10x250-0.25_9.dat-50
OR10x250-0.25_9.dat-100*
OR10x250-0.25_10.dat-0
OR10x250-0.25_10.dat-50
OR10x250-0.25_10.dat-100*
OR10x250-0.50_1.dat-50*
OR10x250-0.50_1.dat-100*
OR10x250-0.50_2.dat-50*
OR10x250-0.50_2.dat-100*
OR10x250-0.50_3.dat-50*
OR10x250-0.50_3.dat-100*
OR10x250-0.50_4.dat-50*
OR10x250-0.50_4.dat-100*
OR10x250-0.50_5.dat-50*
OR10x250-0.50_5.dat-100*
OR10x250-0.50_6.dat-50*
OR10x250-0.50_6.dat-100*
OR10x250-0.50_7.dat-50*
OR10x250-0.50_7.dat-100*
OR10x250-0.50_8.dat-50*
OR10x250-0.50_8.dat-100*
OR10x250-0.50_9.dat-50*
OR10x250-0.50_9.dat-100*
OR10x250-0.50_10.dat-50*
OR10x250-0.50_10.dat-100*
OR10x250-0.75_1.dat-50*
OR10x250-0.75_2.dat-50*
OR10x250-0.75_2.dat-100*
OR10x250-0.75_3.dat-50*
OR10x250-0.75_3.dat-100*
OR10x250-0.75_4.dat-50*
OR10x250-0.75_4.dat-100*
OR10x250-0.75_5.dat-50*
OR10x250-0.75_5.dat-100*
OR10x250-0.75_6.dat-50*
OR10x250-0.75_7.dat-50*
OR10x250-0.75_8.dat-50*
OR10x250-0.75_8.dat-100*
OR10x250-0.75_9.dat-0*
OR10x250-0.75_9.dat-50*
OR10x250-0.75_9.dat-100*
OR10x250-0.75_10.dat-50*
OR10x250-0.75_10.dat-100*
OR10x500-0.25_1.dat-0
OR10x500-0.25_1.dat-50
OR10x500-0.25_1.dat-100*
OR10x500-0.25_2.dat-0
OR10x500-0.25_2.dat-50
OR10x500-0.25_2.dat-100*
OR10x500-0.25_3.dat-0
OR10x500-0.25_3.dat-50
OR10x500-0.25_3.dat-100*
OR10x500-0.25_4.dat-0
OR10x500-0.25_4.dat-50
OR10x500-0.25_4.dat-100*
OR10x500-0.25_5.dat-0
OR10x500-0.25_5.dat-50
OR10x500-0.25_5.dat-100*
OR10x500-0.25_6.dat-0
OR10x500-0.25_6.dat-50
OR10x500-0.25_6.dat-100*
OR10x500-0.25_7.dat-0
OR10x500-0.25_7.dat-50
OR10x500-0.25_7.dat-100*
OR10x500-0.25_8.dat-0
OR10x500-0.25_8.dat-50
OR10x500-0.25_8.dat-100*
OR10x500-0.25_9.dat-0
OR10x500-0.25_9.dat-50
OR10x500-0.25_9.dat-100*
OR10x500-0.25_10.dat-0
OR10x500-0.25_10.dat-50
OR10x500-0.25_10.dat-100*
OR10x500-0.50_1.dat-100*
OR10x500-0.50_2.dat-100*
OR10x500-0.50_3.dat-100*
OR10x500-0.50_4.dat-100*
OR10x500-0.50_5.dat-100*
OR10x500-0.50_6.dat-100*
OR10x500-0.50_7.dat-100*
OR10x500-0.50_8.dat-100*
OR10x500-0.50_9.dat-100*
OR10x500-0.50_10.dat-100*
OR10x500-0.75_1.dat-100*
OR10x500-0.75_2.dat-100*
OR10x500-0.75_3.dat-50*
OR10x500-0.75_3.dat-100*
OR10x500-0.75_4.dat-100*
OR10x500-0.75_5.dat-100*
OR10x500-0.75_6.dat-100*
OR10x500-0.75_7.dat-50*
OR10x500-0.75_7.dat-100*
OR10x500-0.75_8.dat-50*
OR10x500-0.75_8.dat-100*
OR10x500-0.75_9.dat-100*
OR10x500-0.75_10.dat-50*
OR10x500-0.75_10.dat-100*
OR30x100-0.25_1.dat-0
OR30x100-0.25_1.dat-50
OR30x100-0.25_1.dat-100*
OR30x100-0.25_2.dat-0
OR30x100-0.25_2.dat-50
OR30x100-0.25_2.dat-100*
OR30x100-0.25_3.dat-0
OR30x100-0.25_3.dat-50
OR30x100-0.25_3.dat-100*
OR30x100-0.25_4.dat-0
OR30x100-0.25_4.dat-50
OR30x100-0.25_4.dat-100*
OR30x100-0.25_5.dat-0
OR30x100-0.25_5.dat-50
OR30x100-0.25_5.dat-100*
OR30x100-0.25_6.dat-0
OR30x100-0.25_6.dat-50
OR30x100-0.25_6.dat-100*
OR30x100-0.25_7.dat-0
OR30x100-0.25_7.dat-50*
OR30x100-0.25_7.dat-100*
OR30x100-0.25_8.dat-0
OR30x100-0.25_8.dat-50
OR30x100-0.25_8.dat-100*
OR30x100-0.25_9.dat-0

OR30x100-0.25_9.dat-50
OR30x100-0.25_9.dat-100*
OR30x100-0.25_10.dat-0
OR30x100-0.25_10.dat-50
OR30x100-0.25_10.dat-100*
OR30x100-0.50_1.dat-0*
OR30x100-0.50_1.dat-50*
OR30x100-0.50_1.dat-100*
OR30x100-0.50_2.dat-0*
OR30x100-0.50_2.dat-50*
OR30x100-0.50_2.dat-100*
OR30x100-0.50_3.dat-50*
OR30x100-0.50_3.dat-100*
OR30x100-0.50_4.dat-0*
OR30x100-0.50_4.dat-50*
OR30x100-0.50_4.dat-100*
OR30x100-0.50_5.dat-50*
OR30x100-0.50_5.dat-100*
OR30x100-0.50_6.dat-0*
OR30x100-0.50_6.dat-50*
OR30x100-0.50_6.dat-100*
OR30x100-0.50_7.dat-0*
OR30x100-0.50_7.dat-50*
OR30x100-0.50_7.dat-100*
OR30x100-0.50_8.dat-0*
OR30x100-0.50_8.dat-50*
OR30x100-0.50_8.dat-100*
OR30x100-0.50_9.dat-0*
OR30x100-0.50_9.dat-50*
OR30x100-0.50_9.dat-100*
OR30x100-0.50_10.dat-0*
OR30x100-0.50_10.dat-50*
OR30x100-0.50_10.dat-100*
OR30x100-0.75_1.dat-0*
OR30x100-0.75_1.dat-50*
OR30x100-0.75_2.dat-0*
OR30x100-0.75_2.dat-50*
OR30x100-0.75_3.dat-0*
OR30x100-0.75_3.dat-50*
OR30x100-0.75_4.dat-0*
OR30x100-0.75_4.dat-50*
OR30x100-0.75_5.dat-50*
OR30x100-0.75_6.dat-0*
OR30x100-0.75_6.dat-50*
OR30x100-0.75_7.dat-0*
OR30x100-0.75_7.dat-50*
OR30x100-0.75_8.dat-0*
OR30x100-0.75_8.dat-50*
OR30x100-0.75_9.dat-0*
OR30x100-0.75_9.dat-50*
OR30x100-0.75_9.dat-100*
OR30x100-0.75_10.dat-0*
OR30x100-0.75_10.dat-50*
OR30x100-0.75_10.dat-100*
OR30x250-0.25_1.dat-0
OR30x250-0.25_1.dat-50
OR30x250-0.25_1.dat-100*
OR30x250-0.25_2.dat-0
OR30x250-0.25_2.dat-50
OR30x250-0.25_2.dat-100*
OR30x250-0.25_3.dat-0
OR30x250-0.25_3.dat-50
OR30x250-0.25_3.dat-100*
OR30x250-0.25_4.dat-0
OR30x250-0.25_4.dat-50
OR30x250-0.25_4.dat-100*
OR30x250-0.25_5.dat-0
OR30x250-0.25_5.dat-50
OR30x250-0.25_5.dat-100*
OR30x250-0.25_6.dat-0
OR30x250-0.25_6.dat-50
OR30x250-0.25_6.dat-100*
OR30x250-0.25_7.dat-0
OR30x250-0.25_7.dat-50
OR30x250-0.25_7.dat-100*
OR30x250-0.25_8.dat-0
OR30x250-0.25_8.dat-50
OR30x250-0.25_8.dat-100*
OR30x250-0.25_9.dat-0
OR30x250-0.25_9.dat-50
OR30x250-0.25_9.dat-100*
OR30x250-0.25_10.dat-0
OR30x250-0.25_10.dat-50
OR30x250-0.25_10.dat-100*
OR30x250-0.50_1.dat-100*
OR30x250-0.50_2.dat-100*
OR30x250-0.50_3.dat-100*
OR30x250-0.50_4.dat-100*
OR30x250-0.50_5.dat-100*
OR30x250-0.50_6.dat-100*
OR30x250-0.50_7.dat-100*
OR30x250-0.50_8.dat-100*
OR30x250-0.50_9.dat-100*
OR30x250-0.50_10.dat-100*
OR30x250-0.75_1.dat-100*
OR30x250-0.75_2.dat-100*
OR30x250-0.75_3.dat-100*
OR30x250-0.75_4.dat-100*
OR30x250-0.75_5.dat-100*
OR30x250-0.75_6.dat-100*
OR30x250-0.75_7.dat-100*
OR30x250-0.75_8.dat-100*
OR30x250-0.75_9.dat-100*
OR30x250-0.75_10.dat-100*
OR30x500-0.25_1.dat-0
OR30x500-0.25_1.dat-50
OR30x500-0.25_1.dat-100*
OR30x500-0.25_2.dat-0
OR30x500-0.25_2.dat-50
OR30x500-0.25_2.dat-100*
OR30x500-0.25_3.dat-0
OR30x500-0.25_3.dat-50
OR30x500-0.25_3.dat-100*
OR30x500-0.25_4.dat-0
OR30x500-0.25_4.dat-50
OR30x500-0.25_4.dat-100*
OR30x500-0.25_5.dat-0
OR30x500-0.25_5.dat-50
OR30x500-0.25_5.dat-100*
OR30x500-0.25_6.dat-0
OR30x500-0.25_6.dat-50
OR30x500-0.25_6.dat-100*
OR30x500-0.25_7.dat-0
OR30x500-0.25_7.dat-50
OR30x500-0.25_7.dat-100*
OR30x500-0.25_8.dat-0
OR30x500-0.25_8.dat-50
OR30x500-0.25_8.dat-100*
OR30x500-0.25_9.dat-0
OR30x500-0.25_9.dat-50
OR30x500-0.25_9.dat-100*
OR30x500-0.25_10.dat-0
OR30x500-0.25_10.dat-50
OR30x500-0.25_10.dat-100*
OR30x500-0.50_1.dat-100*
OR30x500-0.50_2.dat-100*
OR30x500-0.50_3.dat-100*
OR30x500-0.50_4.dat-100*
OR30x500-0.50_5.dat-100*
OR30x500-0.50_6.dat-100*
OR30x500-0.50_7.dat-100*
OR30x500-0.50_8.dat-100*
OR30x500-0.50_9.dat-100*
OR30x500-0.50_10.dat-100*
OR30x500-0.75_1.dat-100*
OR30x500-0.75_2.dat-100*
OR30x500-0.75_3.dat-100*
OR30x500-0.75_4.dat-100*
OR30x500-0.75_5.dat-100*
OR30x500-0.75_6.dat-100*
OR30x500-0.75_7.dat-100*
OR30x500-0.75_8.dat-100*
OR30x500-0.75_9.dat-100*
OR30x500-0.75_10.dat-100*

General, pure integer (76)

air03-0.500000
air03-0.900000
air04-0.100000
air04-0.500000
air04-0.900000
air05-0.500000
bab2_0_100
bab5_0_100
bab6_0_100
co-100_0_100
co-100_50_50
comp07-2idx_0_100
comp21-2idx_0_100
cvs16r128-89_0_100
cvs16r128-89_50_50
eilA101-2_0_100
ex10_50_50
gen-ip002_0_100
gen-ip002_50_50
harp2-0.100000
harp2-0.500000
harp2-0.900000
irp_0_100
l152lav-0.500000
l152lav-0.900000
lectsched-5-obj_50_50
milp_10_20_50_2310
mine-90-10_0_100
mine-166-5_0_100
mine-166-5_50_50
mitre-0.100000
mod010-0.500000
mod010-0.900000
neos-631710_50_50
neos-662469_0_100
neos-957323_0_100
neos-1109824_0_100
neos-1337307_0_100
neos-1582420_0_100
neos-1582420_50_50
neos-2657525-crna_0_100
neos-3024952-loue_0_100
neos-3083819-nubu_0_100
neos-5052403-cygnet_0_100
neos-5052403-cygnet_50_50
nursesched-medium-hint03_0_100
nw04-0.500000
nw04-0.900000
opm2-z7-s2_0_100
p2756-0.100000
p2756-0.500000

p2756-0.900000
reblock67_0_100
reblock115_0_100
s100_50_50
seymour-0.100000
sorrell3_0_100
sorrell3_50_50
sp97ar_0_100
sp97ar_50_50
sp98ar_0_100
sp98ar_50_50
sp98ir_0_100
square41_0_100
square41_50_50
square47_0_100
square47_50_50
supportcase6_0_100
supportcase6_50_50
supportcase19_0_100
tanglegram1_0_100
tanglegram1_50_50
tanglegram2_0_100
tanglegram2_50_50
toll-like_0_100
toll-like_50_50

General, mixed integer (47)

atlanta-ip_0_100
biella1_0_100
cmflsp50-24-8-8_50_50
drayage-25-23_0_100
drayage-100-23_0_100
exp-1-500-5-5_50_50
fiball_0_100
gmu-35-40_0_100
gmu-35-40_50_50
gmu-35-50_0_100
gmu-35-50_50_50
h80x6320d_50_50
momentum1_0_100
momentum1_50_50
neos-848589_0_100
neos-848589_50_50
neos-873061_50_50
neos-916792_50_50
neos-1122047_50_50
neos-1456979_50_50
neos-2746589-doon_0_100
neos-3216931-puriri_50_50
neos-3754224-navua_0_100
neos-3754224-navua_50_50
neos-3754480-nidda_50_50
neos-4300652-rahue_50_50
neos-4387871-tavua_0_100
neos-4387871-tavua_50_50
neos-4722843-widden_50_50
neos-4763324-toguru_50_50
neos-5049753-cuanza_0_100
neos-5049753-cuanza_50_50
neos-5104907-jarama_0_100
neos-5104907-jarama_50_50
neos-5114902-kasavu_0_100
neos-5114902-kasavu_50_50
nexp-150-20-8-5_0_100
ns1830653_50_50
ran14x18-disj-8_0_100
satellites1-25_50_50
satellites2-40_50_50
satellites2-60-fs_0_100
satellites2-60-fs_50_50
sing44_50_50
sing326_50_50
supportcase12_50_50
trento1_0_100

Generalized interdiction (8)

general20-30-20-20-20-2
general20-30-20-20-20-9
general20-30-20-20-20-10
general30-30-20-20-20-1
general30-30-20-20-20-2
general30-30-30-20-20-1
general30-30-30-20-20-2
general30-30-30-20-20-6

Clique interdiction (3)

normalClique60-70-2*
normalClique60-70-3*
normalClique60-70-5*

REFERENCES

[1] Johannes Thürauf, Thomas Kleinert, Ivana Ljubić, Ted K. Ralphs, and Martin Schmidt. BOBILib: Bilevel Optimization (Benchmark) Instance Library. *Mathematical Programming Computation*, 18(3):819–876, 2026.

[2] Ambros Gleixner, Gregor Hendel, Gerald Gamrath, Tobias Achterberg, Michael Bastubbe, Timo Berthold, Philipp Christophel, Kati Jarck, Thorsten Koch, Jeff Linderoth, Marco Lübbecke, Hans D. Mittelmann, Derya Ozyurt, Ted K. Ralphs, Domenico Salvagnin, and Yuji Shinano. MIPLIB 2017: data-driven compilation of the 6th mixed-integer programming library. *Mathematical Programming Computation*, 13(3):443–490, 2021.

[3] Q. Huangfu and J. A. J. Hall. Parallelizing the dual revised simplex method. *Mathematical Programming Computation*, 10(1):119–142, 2018.

[4] Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In André Platzer and Geoff Sutcliffe, editors, *Automated Deduction – CADE 28*, volume 12699 of *Lecture Notes in Computer Science*, pages 625–635, Cham, 2021. Springer.

[5] The mathlib Community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020)*, pages 367–381, New York, NY, 2020. ACM.

[6] A. E. Brouwer. Some lotto numbers from an extension of Turán's theorem. Afdeling Zuivere Wiskunde report ZW 152/81, Mathematisch Centrum, Amsterdam, March 1981.

[7] Mykhaylo Tyomkyn and Andrew J. Uzzell. Strong Turán stability. *The Electronic Journal of Combinatorics*, 22(3):P3.9, 2015.

[8] Dániel Korándi, Alexander Roberts, and Alex Scott. Exact stability for Turán's theorem. *Advances in Combinatorics*, 2021(9):1–17, 2021.

[9] Noah Weninger and Ricardo Fukasawa. A fast combinatorial algorithm for the bilevel knapsack problem with interdiction constraints. *Mathematical Programming*, 210(1–2):847–879, 2025.

[10] Matteo Fischetti, Ivana Ljubić, Michele Monaci, and Markus Sinnl. Interdiction games and monotonicity, with application to knapsack problems. *INFORMS Journal on Computing*, 31(2):390–410, 2019.

[11] Leonardo Lozano, David Bergman, and Andre A. Cire. Network relaxations for combinatorial bilevel optimization under linear interactions. *Operations Research*, 2026. Articles in Advance, published online 26 August 2026.

[12] Noah Weninger and Ricardo Fukasawa. A fast combinatorial algorithm for the bilevel knapsack problem with interdiction constraints. In Alberto Del Pia and Volker Kaibel, editors, *Integer Programming and Combinatorial Optimization (IPCO 2023)*, volume 13904 of *Lecture Notes in Computer Science*, pages 438–452, Cham, 2023. Springer.

[13] W. Mantel. Problem 28 (solution by H. Gouwentak, W. Mantel, J. Teixeira de Mattes, F. Schuh and W. A. Wythoff). *Wiskundige Opgaven*, 10:60–61, 1907.

[14] Paul Turán. Egy gráfelméleti szélsőértékfeladatról [On an extremal problem in graph theory]. *Matematikai és Fizikai Lapok*, 48:436–452, 1941. In Hungarian.

[15] Coen Bron and Joep Kerbosch. Algorithm 457: finding all cliques of an undirected graph. *Communications of the ACM*, 16(9):575–577, 1973.

[16] Etsuji Tomita, Akira Tanaka, and Haruhisa Takahashi. The worst-case time complexity for generating all maximal cliques and computational experiments. *Theoretical Computer Science*, 363(1):28–42, 2006.

[17] Randy Carraghan and Panos M. Pardalos. An exact algorithm for the maximum clique problem. *Operations Research Letters*, 9(6):375–382, 1990.

[18] Laurent Perron and Frédéric Didier. CP-SAT, version 9.15. Google OR-Tools, 2026.

[19] Christopher Hojny, Mathieu Besançon, Ksenia Bestuzheva, Sander Borst, Antonia Chmiela, João Dionísio, Leon Eifler, Mohammed Ghannam, Ambros Gleixner, Adrian Göß, Alexander Hoen, Rolf van der Hulst, Dominik Kamp, Thorsten Koch, Kevin Kofler, Jurgen Lentz, Stephen J. Maher, Gioni Mexi, Erik Mühmer, Marc E. Pfetsch, Sebastian Pokutta, Felipe Serrano, Yuji Shinano, Mark Turner, Stefan Vigerske, Matthias Walter, Dieter Weninger, and Liding Xu. The SCIP Optimization Suite 10.0. Technical report, Optimization Online, November 2025.

[20] R. R. Meyer. On the existence of optimal solutions to integer and mixed-integer programming problems. *Mathematical Programming*, 7(1):223–235, 1974.

[21] Alexander Mitsos. Global solution of nonlinear mixed-integer bilevel programs. *Journal of Global Optimization*, 47(4):557–582, 2010.

[22] Leonardo Lozano and J. Cole Smith. A value-function-based exact approach for the bilevel mixed-integer programming problem. *Operations Research*, 65(3):768–786, 2017.

[23] Thomas Kleinert and Martin Schmidt. Computing feasible points of bilevel problems with a penalty alternating direction method. *INFORMS Journal on Computing*, 33(1):198–215, 2021.

[24] Andrea Baggio, Margarida Carvalho, Andrea Lodi, and Andrea Tramontani. Multilevel approaches for the critical node problem. *Operations Research*, 69(2):486–508, 2021.

[25] Matteo Fischetti, Ivana Ljubić, Michele Monaci, and Markus Sinnl. A new general-purpose algorithm for mixed-integer bilevel linear programs. *Operations Research*, 65(6):1615–1637, 2017.

[26] Sebastián Vásquez, Leonardo Lozano, and Willem-Jan van Hoeve. A single-level reformulation of binary bilevel programs using decision diagrams. *Mathematical Programming*, 2025. Published online 16 December 2025.

[27] Johannes Thürauf, Thomas Kleinert, Ivana Ljubić, Ted K. Ralphs, and Martin Schmidt. BOBILib: Bilevel Optimization (Benchmark) Instance Library. Website with instances, solution files, statuses and feasibility checker, 2026. Accessed 18 October 2026.