
Amazon Inspector

API Reference

API Version 2016-02-16



Amazon Inspector: API Reference

Copyright © Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddAttributesToFindings	3
Request Syntax	3
Request Parameters	3
Response Syntax	3
Response Elements	4
Errors	4
Examples	4
See Also	5
CreateAssessmentTarget	6
Request Syntax	6
Request Parameters	6
Response Syntax	6
Response Elements	6
Errors	7
Examples	7
See Also	8
CreateAssessmentTemplate	9
Request Syntax	9
Request Parameters	9
Response Syntax	10
Response Elements	10
Errors	10
Examples	11
See Also	12
CreateExclusionsPreview	13
Request Syntax	13
Request Parameters	13
Response Syntax	13
Response Elements	13
Errors	13
See Also	14
CreateResourceGroup	15
Request Syntax	15
Request Parameters	15
Response Syntax	15
Response Elements	15
Errors	16
Examples	16
See Also	17
DeleteAssessmentRun	18
Request Syntax	18
Request Parameters	18
Response Elements	18
Errors	18
Examples	19
See Also	19
DeleteAssessmentTarget	21
Request Syntax	21
Request Parameters	21
Response Elements	21
Errors	21
Examples	22

See Also	22
DeleteAssessmentTemplate	24
Request Syntax	24
Request Parameters	24
Response Elements	24
Errors	24
Examples	25
See Also	25
DescribeAssessmentRuns	27
Request Syntax	27
Request Parameters	27
Response Syntax	27
Response Elements	28
Errors	28
Examples	29
See Also	30
DescribeAssessmentTargets	31
Request Syntax	31
Request Parameters	31
Response Syntax	31
Response Elements	31
Errors	32
Examples	32
See Also	33
DescribeAssessmentTemplates	34
Request Syntax	34
Request Parameters	34
Response Syntax	34
Response Elements	35
Errors	35
Examples	35
See Also	36
DescribeCrossAccountAccessRole	37
Response Syntax	37
Response Elements	37
Errors	37
Examples	37
See Also	38
DescribeExclusions	39
Request Syntax	39
Request Parameters	39
Response Syntax	39
Response Elements	40
Errors	40
See Also	40
DescribeFindings	42
Request Syntax	42
Request Parameters	42
Response Syntax	42
Response Elements	44
Errors	44
Examples	44
See Also	46
DescribeResourceGroups	47
Request Syntax	47
Request Parameters	47
Response Syntax	47

Response Elements	47
Errors	48
Examples	48
See Also	49
DescribeRulesPackages	50
Request Syntax	50
Request Parameters	50
Response Syntax	50
Response Elements	51
Errors	51
Examples	51
See Also	52
GetAssessmentReport	54
Request Syntax	54
Request Parameters	54
Response Syntax	54
Response Elements	55
Errors	55
See Also	56
GetExclusionsPreview	57
Request Syntax	57
Request Parameters	57
Response Syntax	58
Response Elements	58
Errors	59
See Also	59
GetTelemetryMetadata	60
Request Syntax	60
Request Parameters	60
Response Syntax	60
Response Elements	60
Errors	61
Examples	61
See Also	64
ListAssessmentRunAgents	65
Request Syntax	65
Request Parameters	65
Response Syntax	66
Response Elements	66
Errors	66
Examples	67
See Also	70
ListAssessmentRuns	71
Request Syntax	71
Request Parameters	71
Response Syntax	72
Response Elements	72
Errors	72
Examples	73
See Also	74
ListAssessmentTargets	75
Request Syntax	75
Request Parameters	75
Response Syntax	75
Response Elements	76
Errors	76
Examples	76

See Also	77
ListAssessmentTemplates	78
Request Syntax	78
Request Parameters	78
Response Syntax	79
Response Elements	79
Errors	79
Examples	80
See Also	80
ListEventSubscriptions	82
Request Syntax	82
Request Parameters	82
Response Syntax	82
Response Elements	83
Errors	83
Examples	84
See Also	84
ListExclusions	86
Request Syntax	86
Request Parameters	86
Response Syntax	86
Response Elements	87
Errors	87
See Also	87
ListFindings	89
Request Syntax	89
Request Parameters	89
Response Syntax	90
Response Elements	90
Errors	91
Examples	91
See Also	92
ListRulesPackages	93
Request Syntax	93
Request Parameters	93
Response Syntax	93
Response Elements	93
Errors	94
Examples	94
See Also	95
ListTagsForResource	96
Request Syntax	96
Request Parameters	96
Response Syntax	96
Response Elements	96
Errors	96
Examples	97
See Also	98
PreviewAgents	99
Request Syntax	99
Request Parameters	99
Response Syntax	99
Response Elements	100
Errors	100
Examples	101
See Also	101
RegisterCrossAccountAccessRole	103

Request Syntax	103
Request Parameters	103
Response Elements	103
Errors	103
Examples	104
See Also	104
RemoveAttributesFromFindings	106
Request Syntax	106
Request Parameters	106
Response Syntax	106
Response Elements	106
Errors	107
Examples	107
See Also	108
SetTagsForResource	109
Request Syntax	109
Request Parameters	109
Response Elements	109
Errors	109
Examples	110
See Also	111
StartAssessmentRun	112
Request Syntax	112
Request Parameters	112
Response Syntax	112
Response Elements	112
Errors	113
Examples	113
See Also	114
StopAssessmentRun	115
Request Syntax	115
Request Parameters	115
Response Elements	115
Errors	115
Examples	116
See Also	116
SubscribeToEvent	118
Request Syntax	118
Request Parameters	118
Response Elements	118
Errors	119
Examples	119
See Also	120
UnsubscribeFromEvent	121
Request Syntax	121
Request Parameters	121
Response Elements	121
Errors	122
Examples	122
See Also	123
UpdateAssessmentTarget	124
Request Syntax	124
Request Parameters	124
Response Elements	124
Errors	125
Examples	125
See Also	126

Data Types	127
AgentAlreadyRunningAssessment	128
Contents	128
See Also	128
AgentFilter	129
Contents	129
See Also	129
AgentPreview	130
Contents	130
See Also	131
AssessmentRun	132
Contents	132
See Also	134
AssessmentRunAgent	135
Contents	135
See Also	136
AssessmentRunFilter	137
Contents	137
See Also	138
AssessmentRunNotification	139
Contents	139
See Also	140
AssessmentRunStateChange	141
Contents	141
See Also	141
AssessmentTarget	142
Contents	142
See Also	142
AssessmentTargetFilter	144
Contents	144
See Also	144
AssessmentTemplate	145
Contents	145
See Also	146
AssessmentTemplateFilter	147
Contents	147
See Also	147
AssetAttributes	148
Contents	148
See Also	149
Attribute	150
Contents	150
See Also	150
DurationRange	151
Contents	151
See Also	151
EventSubscription	152
Contents	152
See Also	152
Exclusion	153
Contents	153
See Also	154
ExclusionPreview	155
Contents	155
See Also	155
FailedItemDetails	157
Contents	157

See Also	157
Finding	158
Contents	158
See Also	160
FindingFilter	161
Contents	161
See Also	162
InspectorServiceAttributes	163
Contents	163
See Also	163
NetworkInterface	164
Contents	164
See Also	165
Privately	166
Contents	166
See Also	166
ResourceGroup	167
Contents	167
See Also	167
ResourceGroupTag	168
Contents	168
See Also	168
RulesPackage	169
Contents	169
See Also	169
Scope	171
Contents	171
See Also	171
SecurityGroup	172
Contents	172
See Also	172
Subscription	173
Contents	173
See Also	173
Tag	174
Contents	174
See Also	174
TelemetryMetadata	175
Contents	175
See Also	175
TimestampRange	176
Contents	176
See Also	176
Common Parameters	177
Common Errors	179

Welcome

Amazon Inspector enables you to analyze the behavior of your AWS resources and to identify potential security issues. For more information, see [Amazon Inspector User Guide](#).

This document was last published on October 6, 2021.

Actions

The following actions are supported:

- [AddAttributesToFindings](#) (p. 3)
- [CreateAssessmentTarget](#) (p. 6)
- [CreateAssessmentTemplate](#) (p. 9)
- [CreateExclusionsPreview](#) (p. 13)
- [CreateResourceGroup](#) (p. 15)
- [DeleteAssessmentRun](#) (p. 18)
- [DeleteAssessmentTarget](#) (p. 21)
- [DeleteAssessmentTemplate](#) (p. 24)
- [DescribeAssessmentRuns](#) (p. 27)
- [DescribeAssessmentTargets](#) (p. 31)
- [DescribeAssessmentTemplates](#) (p. 34)
- [DescribeCrossAccountAccessRole](#) (p. 37)
- [DescribeExclusions](#) (p. 39)
- [DescribeFindings](#) (p. 42)
- [DescribeResourceGroups](#) (p. 47)
- [DescribeRulesPackages](#) (p. 50)
- [GetAssessmentReport](#) (p. 54)
- [GetExclusionsPreview](#) (p. 57)
- [GetTelemetryMetadata](#) (p. 60)
- [ListAssessmentRunAgents](#) (p. 65)
- [ListAssessmentRuns](#) (p. 71)
- [ListAssessmentTargets](#) (p. 75)
- [ListAssessmentTemplates](#) (p. 78)
- [ListEventSubscriptions](#) (p. 82)
- [ListExclusions](#) (p. 86)
- [ListFindings](#) (p. 89)
- [ListRulesPackages](#) (p. 93)
- [ListTagsForResource](#) (p. 96)
- [PreviewAgents](#) (p. 99)
- [RegisterCrossAccountAccessRole](#) (p. 103)
- [RemoveAttributesFromFindings](#) (p. 106)
- [SetTagsForResource](#) (p. 109)
- [StartAssessmentRun](#) (p. 112)
- [StopAssessmentRun](#) (p. 115)
- [SubscribeToEvent](#) (p. 118)
- [UnsubscribeFromEvent](#) (p. 121)
- [UpdateAssessmentTarget](#) (p. 124)

AddAttributesToFindings

Assigns attributes (key and value pairs) to the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "attributes": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "findingArns": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

attributes (p. 3)

The array of attributes that you want to assign to specified findings.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

findingArns (p. 3)

The ARNs that specify the findings that you want to assign attributes to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{
  "failedItems": {
    "string": {
      "failureCode": "string",
      "retryable": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 3)

Attribute details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `AddAttributesToFindings`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 189
```

```
X-Amz-Target: InspectorService.AddAttributesToFindings
X-Amz-Date: 20160329T233810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "attributes": [
    {
      "key": "Example",
      "value": "example"
    }
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-811VIEOD/run/0-Z02cjjug/finding/0-T8yM9mEU"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4c8b9c50-f607-11e5-9380-d76f0924b6d7
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:38:11 GMT
{
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTarget

Creates a new assessment target using the ARN of the resource group that is generated by [CreateResourceGroup](#) (p. 15). If resourceGroupArn is not specified, all EC2 instances in the current AWS account and region are included in the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector access to AWS Services needed to perform security assessments. You can create up to 50 assessment targets per AWS account. You can run up to 500 concurrent agents per AWS account. For more information, see [Amazon Inspector Assessment Targets](#).

Request Syntax

```
{  
  "assessmentTargetName": "string",  
  "resourceGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetName (p. 6)

The user-defined name that identifies the assessment target that you want to create. The name must be unique within the AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn (p. 6)

The ARN that specifies the resource group that is used to create the assessment target. If resourceGroupArn is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "assessmentTargetArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArn (p. 6)

The ARN that specifies the assessment target that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 129
X-Amz-Target: InspectorService.CreateAssessmentTarget
X-Amz-Date: 20160331T174054Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetName": "ExampleAssessmentTarget",
  "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b87f981e-f767-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 84
Date: Thu, 31 Mar 2016 17:40:55 GMT
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssessmentTemplate

Creates an assessment template for the assessment target that is specified by the ARN of the assessment target. If the [service-linked role](#) isn't already registered, this action also creates and registers a service-linked role to grant Amazon Inspector access to AWS Services needed to perform security assessments.

Request Syntax

```
{
  "assessmentTargetArn": "string",
  "assessmentTemplateName": "string",
  "durationInSeconds": number,
  "rulesPackageArns": [ "string" ],
  "userAttributesForFindings": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetArn (p. 9)

The ARN that specifies the assessment target for which you want to create the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateName (p. 9)

The user-defined name that identifies the assessment template that you want to create. You can create several assessment templates for an assessment target. The names of the assessment templates that correspond to a particular assessment target must be unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

durationInSeconds (p. 9)

The duration of the assessment run in seconds.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

[rulesPackageArns \(p. 9\)](#)

The ARNs that specify the rules packages that you want to attach to the assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

[userAttributesForFindings \(p. 9\)](#)

The user-defined attributes that are assigned to every finding that is generated by the assessment run that uses this assessment template. An attribute is a key and value pair (an [Attribute \(p. 150\)](#) object). Within an assessment template, each key must be unique.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Syntax

```
{  
  "assessmentTemplateArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTemplateArn \(p. 10\)](#)

The ARN that specifies the assessment template that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateAssessmentTemplate`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 335
X-Amz-Target: InspectorService.CreateAssessmentTemplate
X-Amz-Date: 20160331T175559Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
  "assessmentTemplateName": "ExampleAssessmentTemplate",
  "userAttributesForFindings": [
    {
      "key": "Example",
      "value": "example"
    }
  ],
  "durationInSeconds": 180,
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-11B9DBXp"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d3d3d58e-f769-11e5-9da0-9bde5220d15c
Content-Type: application/x-amz-json-1.1
Content-Length: 106
Date: Thu, 31 Mar 2016 17:56:00 GMT
{
  "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateExclusionsPreview

Starts the generation of an exclusions preview for the specified assessment template. The exclusions preview lists the potential exclusions (ExclusionPreview) that Inspector can detect before it runs the assessment.

Request Syntax

```
{  
  "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTemplateArn (p. 13)

The ARN that specifies the assessment template for which you want to create an exclusions preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "previewToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

previewToken (p. 13)

Specifies the unique identifier of the requested exclusions preview. You can use the unique identifier to retrieve the exclusions preview when running the GetExclusionsPreview API.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

PreviewGenerationInProgressException

The request is rejected. The specified assessment template is currently generating an exclusions preview.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceGroup

Creates a resource group using the specified set of tags (key and value pairs) that are used to select the EC2 instances to be included in an Amazon Inspector assessment target. The created resource group is then used to create an Amazon Inspector assessment target. For more information, see [CreateAssessmentTarget](#) (p. 6).

Request Syntax

```
{
  "resourceGroupTags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

resourceGroupTags (p. 15)

A collection of keys and an array of possible values, '[{"key":"key1","values":["Value1","Value2"]}, {"key":"Key2","values":["Value3"]}]'.

For example, '[{"key":"Name","values":["TestEC2Instance"]}]'.

Type: Array of [ResourceGroupTag](#) (p. 168) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{
  "resourceGroupArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resourceGroupArn (p. 15)

The ARN that specifies the resource group that is created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `CreateResourceGroup`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 67
X-Amz-Target: InspectorService.CreateResourceGroup
X-Amz-Date: 20160331T171757Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupTags": [
    {
      "key": "Name",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 8416dfb4-f764-11e5-872a-fde3682789d5
Content-Type: application/x-amz-json-1.1
Content-Length: 88
Date: Thu, 31 Mar 2016 17:17:58 GMT
{
  "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-AB6DMKnv"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentRun

Deletes the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArn (p. 18)

The ARN that specifies the assessment run that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssessmentRun.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.DeleteAssessmentRun
X-Amz-Date: 20160331T183810Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: b8494bff-f76f-11e5-9d49-6dd670a2a95d
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:38:11 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTarget

Deletes the assessment target that is specified by the ARN of the assessment target.

Request Syntax

```
{  
  "assessmentTargetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetArn (p. 21)

The ARN that specifies the assessment target that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeleteAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 85
X-Amz-Target: InspectorService.DeleteAssessmentTarget
X-Amz-Date: 20160331T184144Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 37dee3da-f770-11e5-b61e-e163adb0c30c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:41:45 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssessmentTemplate

Deletes the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{  
  "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTemplateArn (p. 24)

The ARN that specifies the assessment template that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeleteAssessmentTemplate`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 107
X-Amz-Target: InspectorService.DeleteAssessmentTemplate
X-Amz-Date: 20160331T184505Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: afcc2e7e-f770-11e5-8f9c-054cd1296cf6
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:45:06 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentRuns

Describes the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{  
  "assessmentRunArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArns (p. 27)

The ARN that specifies the assessment run that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentRuns": [  
    {  
      "arn": "string",  
      "assessmentTemplateArn": "string",  
      "completedAt": number,  
      "createdAt": number,  
      "dataCollected": boolean,  
      "durationInSeconds": number,  
      "findingCounts": {  
        "string": number  
      },  
      "name": "string",  
      "notifications": [  
        {  
          "date": number,  
          "error": boolean,  
          "event": "string",  
          "message": "string",  
          "snsPublishStatusCode": "string",  
          "snsTopicArn": "string"  
        }  
      ],  
      "rulesPackageArns": [ "string" ],  
      "startedAt": number,  
      "state": "string",  
    }  
  ]  
}
```

```
    "stateChangedAt": number,
    "stateChanges": [
      {
        "state": "string",
        "stateChangedAt": number
      }
    ],
    "userAttributesForFindings": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  },
  "failedItems": {
    "string" : {
      "failureCode": "string",
      "retryable": boolean
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRuns (p. 27)

Information about the assessment run.

Type: Array of [AssessmentRun](#) (p. 132) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems (p. 27)

Assessment run details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeAssessmentRuns.

Sample Request

```
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 120
X-Amz-Target: InspectorService.DescribeAssessmentRuns
X-Amz-Date: 20160323T213431Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0834f495-f13f-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 1156
Date: Wed, 23 Mar 2016 21:34:32 GMT
{
  "assessmentRuns": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE",
      "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw",
      "completedAt": 1458680301.4,
      "createdAt": 1458680170.035,
      "dataCollected": true,
      "durationInSeconds": 3600,
      "name": "Run 1 for ExampleAssessmentTemplate",
      "notifications": [],
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-X1KXtawP"
      ],
      "startedAt": 1458680170.161,
      "state": "COMPLETED",
      "stateChangedAt": 1458680301.4,
      "stateChanges": [
        {
          "state": "CREATED",
          "stateChangedAt": 1458680170.035
        },
        {

```

```
        "state": "START_DATA_COLLECTION_PENDING",
        "stateChangedAt": 1458680170.065
    },
    {
        "state": "START_DATA_COLLECTION_IN_PROGRESS",
        "stateChangedAt": 1458680170.096
    },
    {
        "state": "COLLECTING_DATA",
        "stateChangedAt": 1458680170.161
    },
    {
        "state": "STOP_DATA_COLLECTION_PENDING",
        "stateChangedAt": 1458680239.883
    },
    {
        "state": "DATA_COLLECTED",
        "stateChangedAt": 1458680299.847
    },
    {
        "state": "EVALUATING_RULES",
        "stateChangedAt": 1458680300.099
    },
    {
        "state": "COMPLETED",
        "stateChangedAt": 1458680301.4
    }
],
"userAttributesForFindings": []
}
],
"failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTargets

Describes the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{  
  "assessmentTargetArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetArns (p. 31)

The ARNs that specifies the assessment targets that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentTargets": [  
    {  
      "arn": "string",  
      "createdAt": number,  
      "name": "string",  
      "resourceGroupArn": "string",  
      "updatedAt": number  
    }  
  ],  
  "failedItems": {  
    "string": {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[assessmentTargets](#) (p. 31)

Information about the assessment targets.

Type: Array of [AssessmentTarget](#) (p. 142) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[failedItems](#) (p. 31)

Assessment target details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssessmentTargets`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 88
X-Amz-Target: InspectorService.DescribeAssessmentTargets
X-Amz-Date: 20160323T214315Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 407ddf01-f140-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 287
Date: Wed, 23 Mar 2016 21:43:16 GMT
{
  "assessmentTargets": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq",
      "createdAt": 1458074191.459,
      "name": "ExampleAssessmentTarget",
      "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-PyGXopAI",
      "updatedAt": 1458074191.459
    }
  ],
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssessmentTemplates

Describes the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{  
  "assessmentTemplateArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTemplateArns (p. 34)

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentTemplates": [  
    {  
      "arn": "string",  
      "assessmentRunCount": number,  
      "assessmentTargetArn": "string",  
      "createdAt": number,  
      "durationInSeconds": number,  
      "lastAssessmentRunArn": "string",  
      "name": "string",  
      "rulesPackageArns": [ "string" ],  
      "userAttributesForFindings": [  
        {  
          "key": "string",  
          "value": "string"  
        }  
      ]  
    }  
  ],  
  "failedItems": {  
    "string": {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTemplates (p. 34)

Information about the assessment templates.

Type: Array of [AssessmentTemplate](#) (p. 145) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

failedItems (p. 34)

Assessment template details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssessmentTemplates`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 110
X-Amz-Target: InspectorService.DescribeAssessmentTemplates
X-Amz-Date: 20160323T214822Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
```

```
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f73a449b-f140-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 422
Date: Wed, 23 Mar 2016 21:48:23 GMT
{
  "assessmentTemplates": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw",
      "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq",
      "createdAt": 1458074191.844,
      "durationInSeconds": 3600,
      "name": "ExampleAssessmentTemplate",
      "rulesPackageArns": [
        "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-X1KXtawP"
      ],
      "userAttributesForFindings": []
    }
  ],
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCrossAccountAccessRole

Describes the IAM role that enables Amazon Inspector to access your AWS account.

Response Syntax

```
{  
  "registeredAt": number,  
  "roleArn": "string",  
  "valid": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

registeredAt (p. 37)

The date when the cross-account access role was registered.

Type: Timestamp

roleArn (p. 37)

The ARN that specifies the IAM role that Amazon Inspector uses to access your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

valid (p. 37)

A Boolean value that specifies whether the IAM role has the necessary policies attached to enable Amazon Inspector to access your AWS account.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DescribeCrossAccountAccessRole.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.DescribeCrossAccountAccessRole
X-Amz-Date: 20160323T215330Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: aef491a7-f141-11e5-bf1e-bbcaff8bf2e
Content-Type: application/x-amz-json-1.1
Content-Length: 99
Date: Wed, 23 Mar 2016 21:53:32 GMT
{
  "registeredAt": 1458069182.826,
  "roleArn": "arn:aws:iam::123456789012:role/inspector",
  "valid": true
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeExclusions

Describes the exclusions that are specified by the exclusions' ARNs.

Request Syntax

```
{  
  "exclusionArns": [ "string" ],  
  "locale": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

exclusionArns (p. 39)

The list of ARNs that specify the exclusions that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale (p. 39)

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: `EN_US`

Required: No

Response Syntax

```
{  
  "exclusions": {  
    "string": {  
      "arn": "string",  
      "attributes": [  
        {  
          "key": "string",  
          "value": "string"  
        }  
      ],  
      "description": "string",  
      "recommendation": "string",  
      "scopes": [  
        {  
          "key": "string",
```



```
        "value": "string"
      },
    ],
    "title": "string"
  },
},
"failedItems": {
  "string" : {
    "failureCode": "string",
    "retryable": boolean
  }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusions (p. 39)

Information about the exclusions.

Type: String to [Exclusion](#) (p. 153) object map

Map Entries: Maximum number of 100 items.

Key Length Constraints: Minimum length of 1. Maximum length of 300.

failedItems (p. 39)

Exclusion details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeFindings

Describes the findings that are specified by the ARNs of the findings.

Request Syntax

```
{
  "findingArns": [ "string" ],
  "locale": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

findingArns (p. 42)

The ARN that specifies the finding that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale (p. 42)

The locale into which you want to translate a finding description, recommendation, and the short description that identifies the finding.

Type: String

Valid Values: `EN_US`

Required: No

Response Syntax

```
{
  "failedItems": {
    "string": {
      "failureCode": "string",
      "retryable": boolean
    }
  },
  "findings": [
    {
      "arn": "string",
      "assetAttributes": {
        "agentId": "string",
        "amiId": "string",
        "autoScalingGroup": "string",
```

```

    "hostname": "string",
    "ipv4Addresses": [ "string" ],
    "networkInterfaces": [
      {
        "ipv6Addresses": [ "string" ],
        "networkInterfaceId": "string",
        "privateDnsName": "string",
        "privateIpAddress": "string",
        "privateIpAddresses": [
          {
            "privateDnsName": "string",
            "privateIpAddress": "string"
          }
        ],
        "publicDnsName": "string",
        "publicIp": "string",
        "securityGroups": [
          {
            "groupId": "string",
            "groupName": "string"
          }
        ],
        "subnetId": "string",
        "vpcId": "string"
      }
    ],
    "schemaVersion": number,
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  },
  "assetType": "string",
  "attributes": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "confidence": number,
  "createdAt": number,
  "description": "string",
  "id": "string",
  "indicatorOfCompromise": boolean,
  "numericSeverity": number,
  "recommendation": "string",
  "schemaVersion": number,
  "service": "string",
  "serviceAttributes": {
    "assessmentRunArn": "string",
    "rulesPackageArn": "string",
    "schemaVersion": number
  },
  "severity": "string",
  "title": "string",
  "updatedAt": number,
  "userAttributes": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
]

```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 42)

Finding details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

findings (p. 42)

Information about the finding.

Type: Array of [Finding](#) (p. 158) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DescribeFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 133
X-Amz-Target: InspectorService.DescribeFindings
X-Amz-Date: 20160323T215809Z
```

```
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 555dbc27-f142-11e5-9dc2-6746fe4b2002
Content-Type: application/x-amz-json-1.1
Content-Length: 892
Date: Wed, 23 Mar 2016 21:58:10 GMT
{
  "failedItems": {},
  "findings": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",
      "assetAttributes": {
        "agentId": "i-092e1184e67721f24",
        "amiId": "ami-0ad99772",
        "autoScalingGroup": "auto scaling group",
        "hostname": "ec2-54-202-242-173.us-west-2.compute.amazonaws.com",
        "ipv4Addresses": [],
        "networkInterfaces": [
          {
            "ipv6Addresses": [],
            "networkInterfaceId": "eni-09b5ad02",
            "privateDnsName": "ip-172-31-36-75.us-west-2.compute.internal",
            "privateIpAddress": "172.31.36.75",
            "privateIpAddresses": [
              {
                "privateDnsName": "ip-172-31-36-75.us-
west-2.compute.internal",
                "privateIpAddress": "172.31.36.75"
              }
            ],
            "publicDnsName": "ec2-54-202-242-173.us-
west-2.compute.amazonaws.com",
            "publicIp": "54.202.242.173",
            "securityGroups": [
              {
                "groupId": "sg-48578931",
                "groupName": "default"
              }
            ],
            "subnetId": "subnet-8aeabbfc",
            "vpcId": "vpc-05515b61"
          }
        ],
        "schemaVersion": 1,
        "tags": [
          {
            "key": "scaling",
            "value": "yes"
          }
        ]
      }
    }
  ]
}
```

```
        },
        {
            "key": "aws:autoscaling:groupName",
            "value": "auto scaling group"
        },
        {
            "key": "Name",
            "value": "beta_amazon_linux_201803_scaling"
        },
        {
            "key": "beta",
            "value": "true"
        }
    ]
},
"assetType": "ec2-instance",
"attributes": [],
"confidence": 10,
"createdAt": 1458680301.37,
"description": "Amazon Inspector did not find any potential security
issues during this assessment.",
"indicatorOfCompromise": false,
"numericSeverity": 0,
"recommendation": "No remediation needed.",
"schemaVersion": 1,
"service": "Inspector",
"serviceAttributes": {
    "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
    "rulesPackageArn": "arn:aws:inspector:us-
west-2:758058086616:rulespackage/0-X1KXtawP",
    "schemaVersion": 1
},
"severity": "Informational",
"title": "No potential security issues found",
"updatedAt": 1458680301.37,
"userAttributes": []
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeResourceGroups

Describes the resource groups that are specified by the ARNs of the resource groups.

Request Syntax

```
{  
  "resourceGroupArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

resourceGroupArns (p. 47)

The ARN that specifies the resource group that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "failedItems": {  
    "string": {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  },  
  "resourceGroups": [  
    {  
      "arn": "string",  
      "createdAt": number,  
      "tags": [  
        {  
          "key": "string",  
          "value": "string"  
        }  
      ]  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 47)

Resource group details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

resourceGroups (p. 47)

Information about a resource group.

Type: Array of [ResourceGroup](#) (p. 167) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeResourceGroups`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 92
X-Amz-Target: InspectorService.DescribeResourceGroups
X-Amz-Date: 20160323T220453Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceGroupArns": [
    "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-PyGXopAI"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4636d6a9-f143-11e5-9f03-eb6e194efa59
Content-Type: application/x-amz-json-1.1
Content-Length: 191
Date: Wed, 23 Mar 2016 22:04:54 GMT
{
  "failedItems": {},
  "resourceGroups": [
    {
      "arn": "arn:aws:inspector:us-west-2:123456789012:resourcegroup/0-PyGXopAI",
      "createdAt": 1458074191.098,
      "tags": [
        {
          "key": "Name",
          "value": "example"
        }
      ]
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRulesPackages

Describes the rules packages that are specified by the ARNs of the rules packages.

Request Syntax

```
{  
  "locale": "string",  
  "rulesPackageArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

locale (p. 50)

The locale that you want to translate a rules package description into.

Type: String

Valid Values: `EN_US`

Required: No

rulesPackageArns (p. 50)

The ARN that specifies the rules package that you want to describe.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "failedItems": {  
    "string": {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  },  
  "rulesPackages": [  
    {  
      "arn": "string",  
      "description": "string",  
      "name": "string",  
      "provider": "string",  
      "version": "string"  
    }  
  ]  
}
```

```
} ]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 50)

Rules package details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackages (p. 50)

Information about the rules package.

Type: Array of [RulesPackage](#) (p. 169) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeRulesPackages`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 90
X-Amz-Target: InspectorService.DescribeRulesPackages
X-Amz-Date: 20160323T220919Z
```

```
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4a6aee0-f143-11e5-a5ad-73b7f19c946c
Content-Type: application/x-amz-json-1.1
Content-Length: 387
Date: Wed, 23 Mar 2016 22:09:20 GMT
{
  "failedItems": {},
  "rulesPackages": [
    {
      "arn": "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p",
      "description": "The rules in this package help verify whether the EC2 instances in your application are exposed to Common Vulnerabilities and Exposures (CVEs). Attacks can exploit unpatched vulnerabilities to compromise the confidentiality, integrity, or availability of your service or data. The CVE system provides a reference for publicly known information security vulnerabilities and exposures. For more information, see [https://cve.mitre.org/](https://cve.mitre.org/). If a particular CVE appears in one of the produced Findings at the end of a completed Inspector assessment, you can search [https://cve.mitre.org/](https://cve.mitre.org/) using the CVE's ID (for example, \"CVE-2009-0021\") to find detailed information about this CVE, its severity, and how to mitigate it. ",
      "name": "Common Vulnerabilities and Exposures",
      "provider": "Amazon Web Services, Inc.",
      "version": "1.1"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetAssessmentReport

Produces an assessment report that includes detailed and comprehensive results of a specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string",  
  "reportFileFormat": "string",  
  "reportType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArn (p. 54)

The ARN that specifies the assessment run for which you want to generate a report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

reportFileFormat (p. 54)

Specifies the file format (html or pdf) of the assessment report that you want to generate.

Type: String

Valid Values: HTML | PDF

Required: Yes

reportType (p. 54)

Specifies the type of the assessment report that you want to generate. There are two types of assessment reports: a finding report and a full report. For more information, see [Assessment Reports](#).

Type: String

Valid Values: FINDING | FULL

Required: Yes

Response Syntax

```
{  
  "status": "string",  
}
```

```
"url": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status (p. 54)

Specifies the status of the request to generate an assessment report.

Type: String

Valid Values: WORK_IN_PROGRESS | FAILED | COMPLETED

url (p. 54)

Specifies the URL where you can find the generated assessment report. This parameter is only returned if the report is successfully generated.

Type: String

Length Constraints: Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

AssessmentRunInProgressException

You cannot perform a specified action if an assessment run is currently in progress.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

UnsupportedFeatureException

Used by the [GetAssessmentReport](#) (p. 54) API. The request was rejected because you tried to generate a report for an assessment run that existed before reporting was supported in Amazon Inspector. You can only generate reports for assessment runs that took place or will take place after generating reports in Amazon Inspector became available.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetExclusionsPreview

Retrieves the exclusions preview (a list of ExclusionPreview objects) specified by the preview token. You can obtain the preview token by running the CreateExclusionsPreview API.

Request Syntax

```
{
  "assessmentTemplateArn": "string",
  "locale": "string",
  "maxResults": number,
  "nextToken": "string",
  "previewToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

assessmentTemplateArn (p. 57)

The ARN that specifies the assessment template for which the exclusions preview was requested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

locale (p. 57)

The locale into which you want to translate the exclusion's title, description, and recommendation.

Type: String

Valid Values: `EN_US`

Required: No

maxResults (p. 57)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 57)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the GetExclusionsPreviewRequest action. Subsequent calls to the action fill nextToken in the request with the value of nextToken from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewToken (p. 57)

The unique identifier associated of the exclusions preview.

Type: String

Pattern: [0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{
  "exclusionPreviews": [
    {
      "attributes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "description": "string",
      "recommendation": "string",
      "scopes": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "title": "string"
    }
  ],
  "nextToken": "string",
  "previewStatus": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusionPreviews (p. 58)

Information about the exclusions included in the preview.

Type: Array of [ExclusionPreview](#) (p. 155) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken (p. 58)

When a response is generated, if there is more data to be listed, this parameters is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

[previewStatus \(p. 58\)](#)

Specifies the status of the request to generate an exclusions preview.

Type: String

Valid Values: `WORK_IN_PROGRESS` | `COMPLETED`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTelemetryMetadata

Information about the data that is collected for the specified assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArn (p. 60)

The ARN that specifies the assessment run that has the telemetry data that you want to obtain.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "telemetryMetadata": [  
    {  
      "count": number,  
      "dataSize": number,  
      "messageType": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

telemetryMetadata (p. 60)

Telemetry details.

Type: Array of [TelemetryMetadata](#) (p. 175) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetTelemetryMetadata`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.GetTelemetryMetadata
X-Amz-Date: 20160329T223852Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 03ffa82f-f5ff-11e5-9cf9-9fd5e2aef2f6
Content-Type: application/x-amz-json-1.1
Content-Length: 1990
Date: Tue, 29 Mar 2016 22:38:53 GMT
```

```
{
  "telemetryMetadata": [
    {
      "count": 2,
      "dataSize": 345,
      "messageType": "InspectorDuplicateProcess"
    },
    {
      "count": 3,
      "dataSize": 255,
      "messageType": "InspectorTimeEventMsg"
    },
    {
      "count": 4,
      "dataSize": 1082,
      "messageType": "InspectorNetworkInterface"
    },
    {
      "count": 2,
      "dataSize": 349,
      "messageType": "InspectorDnsEntry"
    },
    {
      "count": 11,
      "dataSize": 2514,
      "messageType": "InspectorDirectoryInfoMsg"
    },
    {
      "count": 1,
      "dataSize": 179,
      "messageType": "InspectorTcpV6ListeningPort"
    },
    {
      "count": 101,
      "dataSize": 10949,
      "messageType": "InspectorTerminal"
    },
    {
      "count": 26,
      "dataSize": 5916,
      "messageType": "InspectorUser"
    },
    {
      "count": 282,
      "dataSize": 32148,
      "messageType": "InspectorDynamicallyLoadedCodeModule"
    },
    {
      "count": 18,
      "dataSize": 10172,
      "messageType": "InspectorCreateProcess"
    },
    {
      "count": 3,
      "dataSize": 8001,
      "messageType": "InspectorProcessPerformance"
    },
    {
      "count": 1,
      "dataSize": 360,
      "messageType": "InspectorOperatingSystem"
    },
    {
      "count": 6,
      "dataSize": 546,
      "messageType": "InspectorStopProcess"
    }
  ]
}
```

```
    },
    {
      "count": 1,
      "dataSize": 1553,
      "messageType": "InspectorInstanceMetaData"
    },
    {
      "count": 2,
      "dataSize": 434,
      "messageType": "InspectorTcpV4Connection"
    },
    {
      "count": 474,
      "dataSize": 2960322,
      "messageType": "InspectorPackageInfo"
    },
    {
      "count": 3,
      "dataSize": 2235,
      "messageType": "InspectorSystemPerformance"
    },
    {
      "count": 105,
      "dataSize": 46048,
      "messageType": "InspectorCodeModule"
    },
    {
      "count": 1,
      "dataSize": 182,
      "messageType": "InspectorUdpV6ListeningPort"
    },
    {
      "count": 2,
      "dataSize": 371,
      "messageType": "InspectorUdpV4ListeningPort"
    },
    {
      "count": 18,
      "dataSize": 8362,
      "messageType": "InspectorKernelModule"
    },
    {
      "count": 29,
      "dataSize": 48788,
      "messageType": "InspectorConfigurationInfo"
    },
    {
      "count": 1,
      "dataSize": 79,
      "messageType": "InspectorMonitoringStart"
    },
    {
      "count": 5,
      "dataSize": 0,
      "messageType": "InspectorSplitMsgBegin"
    },
    {
      "count": 51,
      "dataSize": 4593,
      "messageType": "InspectorGroup"
    },
    {
      "count": 1,
      "dataSize": 184,
      "messageType": "InspectorTcpV4ListeningPort"
    },
  ],
```



```
{
  "count": 1159,
  "dataSize": 3146579,
  "messageType": "Total"
},
{
  "count": 5,
  "dataSize": 0,
  "messageType": "InspectorSplitMsgEnd"
},
{
  "count": 1,
  "dataSize": 612,
  "messageType": "InspectorLoadImageInProgress"
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRunAgents

Lists the agents of the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArn": "string",
  "filter": {
    "agentHealthCodes": [ "string" ],
    "agentHealths": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArn (p. 65)

The ARN that specifies the assessment run whose agents you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

filter (p. 65)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AgentFilter](#) (p. 129) object

Required: No

maxResults (p. 65)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 65)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRunAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunAgents": [
    {
      "agentHealth": "string",
      "agentHealthCode": "string",
      "agentHealthDetails": "string",
      "agentId": "string",
      "assessmentRunArn": "string",
      "autoScalingGroup": "string",
      "telemetryMetadata": [
        {
          "count": number,
          "dataSize": number,
          "messageType": "string"
        }
      ]
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunAgents (p. 66)

A list of ARNs that specifies the agents returned by the action.

Type: Array of [AssessmentRunAgent](#) (p. 135) objects

Array Members: Minimum number of 0 items. Maximum number of 500 items.

nextToken (p. 66)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRunAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.ListAssessmentRunAgents
X-Amz-Date: 20160323T212138Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b752481-f13d-11e5-9f2a-87dc3189b81c
Content-Type: application/x-amz-json-1.1
Content-Length: 2206
Date: Wed, 23 Mar 2016 21:21:39 GMT
{
  "assessmentRunAgents": [
    {
      "agentHealth": "HEALTHY",
      "agentHealthCode": "HEALTHY",
      "agentId": "i-49113b93",
      "assessmentRunArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-4r1V2mAw/run/0-MKkpXXPE",
      "telemetryMetadata": [
```

```
{
  "count": 2,
  "dataSize": 345,
  "messageType": "InspectorDuplicateProcess"
},
{
  "count": 3,
  "dataSize": 255,
  "messageType": "InspectorTimeEventMsg"
},
{
  "count": 4,
  "dataSize": 1082,
  "messageType": "InspectorNetworkInterface"
},
{
  "count": 2,
  "dataSize": 349,
  "messageType": "InspectorDnsEntry"
},
{
  "count": 11,
  "dataSize": 2514,
  "messageType": "InspectorDirectoryInfoMsg"
},
{
  "count": 1,
  "dataSize": 179,
  "messageType": "InspectorTcpV6ListeningPort"
},
{
  "count": 101,
  "dataSize": 10949,
  "messageType": "InspectorTerminal"
},
{
  "count": 26,
  "dataSize": 5916,
  "messageType": "InspectorUser"
},
{
  "count": 282,
  "dataSize": 32148,
  "messageType": "InspectorDynamicallyLoadedCodeModule"
},
{
  "count": 18,
  "dataSize": 10172,
  "messageType": "InspectorCreateProcess"
},
{
  "count": 3,
  "dataSize": 8001,
  "messageType": "InspectorProcessPerformance"
},
{
  "count": 1,
  "dataSize": 360,
  "messageType": "InspectorOperatingSystem"
},
{
  "count": 6,
  "dataSize": 546,
  "messageType": "InspectorStopProcess"
},
{
```

```
"count": 1,
"dataSize": 1553,
"messageType": "InspectorInstanceMetaData"
},
{
  "count": 2,
  "dataSize": 434,
  "messageType": "InspectorTcpV4Connection"
},
{
  "count": 474,
  "dataSize": 2960322,
  "messageType": "InspectorPackageInfo"
},
{
  "count": 3,
  "dataSize": 2235,
  "messageType": "InspectorSystemPerformance"
},
{
  "count": 105,
  "dataSize": 46048,
  "messageType": "InspectorCodeModule"
},
{
  "count": 1,
  "dataSize": 182,
  "messageType": "InspectorUdpV6ListeningPort"
},
{
  "count": 2,
  "dataSize": 371,
  "messageType": "InspectorUdpV4ListeningPort"
},
{
  "count": 18,
  "dataSize": 8362,
  "messageType": "InspectorKernelModule"
},
{
  "count": 29,
  "dataSize": 48788,
  "messageType": "InspectorConfigurationInfo"
},
{
  "count": 1,
  "dataSize": 79,
  "messageType": "InspectorMonitoringStart"
},
{
  "count": 5,
  "dataSize": 0,
  "messageType": "InspectorSplitMsgBegin"
},
{
  "count": 51,
  "dataSize": 4593,
  "messageType": "InspectorGroup"
},
{
  "count": 1,
  "dataSize": 184,
  "messageType": "InspectorTcpV4ListeningPort"
},
{
  "count": 1159,
```

```
        "dataSize": 3146579,  
        "messageType": "Total"  
    },  
    {  
        "count": 5,  
        "dataSize": 0,  
        "messageType": "InspectorSplitMsgEnd"  
    },  
    {  
        "count": 1,  
        "dataSize": 612,  
        "messageType": "InspectorLoadImageInProgress"  
    }  
  ]  
}  
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentRuns

Lists the assessment runs that correspond to the assessment templates that are specified by the ARNs of the assessment templates.

Request Syntax

```
{  
  "assessmentTemplateArns": [ "string" ],  
  "filter": {  
    "completionTimeRange": {  
      "beginDate": number,  
      "endDate": number  
    },  
    "durationRange": {  
      "maxSeconds": number,  
      "minSeconds": number  
    },  
    "namePattern": "string",  
    "rulesPackageArns": [ "string" ],  
    "startTimeRange": {  
      "beginDate": number,  
      "endDate": number  
    },  
    "stateChangeTimeRange": {  
      "beginDate": number,  
      "endDate": number  
    },  
    "states": [ "string" ]  
  },  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTemplateArns (p. 71)

The ARNs that specify the assessment templates whose assessment runs you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 71)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentRunFilter](#) (p. 137) object

Required: No

maxResults (p. 71)

You can use this parameter to indicate the maximum number of items that you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 71)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentRuns** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentRunArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunArns (p. 72)

A list of ARNs that specifies the assessment runs that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 72)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentRuns.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentRuns
X-Amz-Date: 20160323T194135Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 410dabf6-f12f-11e5-8b5a-810259c0c3ae
Content-Type: application/x-amz-json-1.1
Content-Length: 215
Date: Wed, 23 Mar 2016 19:41:36 GMT
{
  "assessmentRunArns":
  [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-MKkpXXPE",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw/run/0-v5D6fI3v"
  ]
}
```

```
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTargets

Lists the ARNs of the assessment targets within this AWS account. For more information about assessment targets, see [Amazon Inspector Assessment Targets](#).

Request Syntax

```
{  
  "filter": {  
    "assessmentTargetNamePattern": "string"  
  },  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

[filter \(p. 75\)](#)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTargetFilter \(p. 144\)](#) object

Required: No

[maxResults \(p. 75\)](#)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken \(p. 75\)](#)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTargets** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
```

```
"assessmentTargetArns": [ "string" ],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTargetArns (p. 75)

A list of ARNs that specifies the assessment targets that are returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 75)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentTargets.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTargets
X-Amz-Date: 20160323T201018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 445f71f6-f133-11e5-932b-dd9c937d073a
Content-Type: application/x-amz-json-1.1
Content-Length: 87
Date: Wed, 23 Mar 2016 20:10:19 GMT
{
  "assessmentTargetArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssessmentTemplates

Lists the assessment templates that correspond to the assessment targets that are specified by the ARNs of the assessment targets.

Request Syntax

```
{
  "assessmentTargetArns": [ "string" ],
  "filter": {
    "durationRange": {
      "maxSeconds": number,
      "minSeconds": number
    },
    "namePattern": "string",
    "rulesPackageArns": [ "string" ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetArns (p. 78)

A list of ARNs that specifies the assessment targets whose assessment templates you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 78)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [AssessmentTemplateFilter](#) (p. 147) object

Required: No

maxResults (p. 78)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 78)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListAssessmentTemplates** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "assessmentTemplateArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentTemplateArns (p. 79)

A list of ARNs that specifies the assessment templates returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 79)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssessmentTemplates.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListAssessmentTemplates
X-Amz-Date: 20160323T202549Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6f406528-f135-11e5-aa71-8de73166bfa9
Content-Type: application/x-amz-json-1.1
Content-Length: 190
Date: Wed, 23 Mar 2016 20:25:50 GMT
{
  "assessmentTemplateArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-4r1V2mAw",
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/template/0-
Uza6ihLh"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventSubscriptions

Lists all the event subscriptions for the assessment template that is specified by the ARN of the assessment template. For more information, see [SubscribeToEvent](#) (p. 118) and [UnsubscribeFromEvent](#) (p. 121).

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

[maxResults](#) (p. 82)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#) (p. 82)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListEventSubscriptions** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

[resourceArn](#) (p. 82)

The ARN of the assessment template for which you want to list the existing event subscriptions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
}
```

```
"subscriptions": [  
  {  
    "eventSubscriptions": [  
      {  
        "event": "string",  
        "subscribedAt": number  
      }  
    ],  
    "resourceArn": "string",  
    "topicArn": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 82)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

subscriptions (p. 82)

Details of the returned event subscriptions.

Type: Array of [Subscription](#) (p. 173) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListEventSubscriptions.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListEventSubscriptions
X-Amz-Date: 20160331T202943Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4e21c005-f77f-11e5-823c-bd257ba1495d
Content-Type: application/x-amz-json-1.1
Content-Length: 272
Date: Thu, 31 Mar 2016 20:29:44 GMT
{
  "subscriptions": [
    {
      "eventSubscriptions": [
        {
          "event": "ASSESSMENT_RUN_COMPLETED",
          "subscribedAt": 1459455440.867
        }
      ],
      "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-7sbz2Kz0",
      "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListExclusions

List exclusions that are generated by the assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArn (p. 86)

The ARN of the assessment run that generated the exclusions that you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

maxResults (p. 86)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 100. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 86)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the ListExclusionsRequest action. Subsequent calls to the action fill nextToken in the request with the value of nextToken from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "exclusionArns": [ "string" ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exclusionArns (p. 86)

A list of exclusions' ARNs returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

nextToken (p. 86)

When a response is generated, if there is more data to be listed, this parameters is present in the response and contains the value to use for the nextToken parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListFindings

Lists findings that are generated by the assessment runs that are specified by the ARNs of the assessment runs.

Request Syntax

```
{
  "assessmentRunArns": [ "string" ],
  "filter": {
    "agentIds": [ "string" ],
    "attributes": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "autoScalingGroups": [ "string" ],
    "creationTimeRange": {
      "beginDate": number,
      "endDate": number
    },
    "ruleNames": [ "string" ],
    "rulesPackageArns": [ "string" ],
    "severities": [ "string" ],
    "userAttributes": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunArns (p. 89)

The ARNs of the assessment runs that generate the findings that you want to list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

filter (p. 89)

You can use this parameter to specify a subset of data to be included in the action's response.

For a record to match a filter, all specified filter attributes must match. When multiple values are specified for a filter attribute, any of the values can match.

Type: [FindingFilter](#) (p. 161) object

Required: No

[maxResults](#) (p. 89)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

[nextToken](#) (p. 89)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListFindings** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{
  "findingArns": [ "string" ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[findingArns](#) (p. 90)

A list of ARNs that specifies the findings returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

[nextToken](#) (p. 90)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListFindings.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListFindings
X-Amz-Date: 20160323T203109Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2df2e847-f136-11e5-b2c3-cd62ea256ca4
Content-Type: application/x-amz-json-1.1
Content-Length: 247
Date: Wed, 23 Mar 2016 20:31:10 GMT
{
  "findingArns": [
```

```
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/  
template/0-4r1V2mAw/run/0-MKkpXXPE/finding/0-HwPnsDm4",  
        "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/  
template/0-4r1V2mAw/run/0-v5D6fI3v/finding/0-tyvmqBLy"  
    ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRulesPackages

Lists all available Amazon Inspector rules packages.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

maxResults (p. 93)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 93)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **ListRulesPackages** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Syntax

```
{  
  "nextToken": "string",  
  "rulesPackageArns": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 93)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

rulesPackageArns (p. 93)

The list of ARNs that specifies the rules packages returned by the action.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListRulesPackages.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: InspectorService.ListRulesPackages
X-Amz-Date: 20160323T203727Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0e3779a9-f137-11e5-be28-e130082e2a98
Content-Type: application/x-amz-json-1.1
Content-Length: 424
Date: Wed, 23 Mar 2016 20:37:26 GMT
{
  "rulesPackageArns": [
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-9hgA516p",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-H5hpSawc",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-JJOtZiqQ",
    "arn:aws:inspector:us-west-2:758058086616:rulespackage/0-vg5GGHSD"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists all tags associated with an assessment template.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

resourceArn (p. 96)

The ARN that specifies the assessment template whose tags you want to list.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags (p. 96)

A collection of key and value pairs.

Type: Array of [Tag](#) (p. 174) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListTagsForResource.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 97
X-Amz-Target: InspectorService.ListTagsForResource
X-Amz-Date: 20160323T212838Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq/template/0-gcwFliYu"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3580d562-f13e-11e5-8a9a-395a36305628
Content-Type: application/x-amz-json-1.1
Content-Length: 50
Date: Wed, 23 Mar 2016 21:28:39 GMT
{
  "tags": [
    {
      "key": "Name",
      "value": "Example"
    }
  ]
}
```

```
}  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PreviewAgents

Previews the agents installed on the EC2 instances that are part of the specified assessment target.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "previewAgentsArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

maxResults (p. 99)

You can use this parameter to indicate the maximum number of items you want in the response. The default value is 10. The maximum value is 500.

Type: Integer

Required: No

nextToken (p. 99)

You can use this parameter when paginating results. Set the value of this parameter to null on your first call to the **PreviewAgents** action. Subsequent calls to the action fill **nextToken** in the request with the value of **NextToken** from the previous response to continue listing data.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

previewAgentsArn (p. 99)

The ARN of the assessment target whose agents you want to preview.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "agentPreviews": [  
    {  
      "agentHealth": "string",  
      "agentId": "string",  
      "agentVersion": "string",  
      "autoScalingGroup": "string",  
    }  
  ]  
}
```

```
        "hostname": "string",  
        "ipv4Address": "string",  
        "kernelVersion": "string",  
        "operatingSystem": "string"  
    }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentPreviews (p. 99)

The resulting list of agents.

Type: Array of [AgentPreview](#) (p. 130) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

nextToken (p. 99)

When a response is generated, if there is more data to be listed, this parameter is present in the response and contains the value to use for the **nextToken** parameter in a subsequent pagination request. If there is no more data to be listed, this parameter is set to null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PreviewAgents.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 82
X-Amz-Target: InspectorService.PreviewAgents
X-Amz-Date: 20160329T224634Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "previewAgentsArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-0kFIPusq"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 176c8915-f600-11e5-ac8a-bb6015f4022c
Content-Type: application/x-amz-json-1.1
Content-Length: 44
Date: Tue, 29 Mar 2016 22:46:36 GMT
{
  "agentPreviews": [
    {
      "hostname": "example",
      "agentId": "i-49113b93",
      "autoScalingGroup": "example",
      "agentHealth": HEALTHY,
      "agentVersion": "exampleversion",
      "operatingSystem": "exampleOS",
      "kernelVersion": "examplekernelversion",
      "ipv4Address": "example"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterCrossAccountAccessRole

Registers the IAM role that grants Amazon Inspector access to AWS Services needed to perform security assessments.

Request Syntax

```
{  
  "roleArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

roleArn (p. 103)

The ARN of the IAM role that grants Amazon Inspector access to AWS Services needed to perform security assessments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterCrossAccountAccessRole.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 55
X-Amz-Target: InspectorService.RegisterCrossAccountAccessRole
X-Amz-Date: 20160329T225544Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "roleArn": "arn:aws:iam::123456789012:role/inspector"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 5f553cfa-f601-11e5-a47c-b7e2de2d572c
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Tue, 29 Mar 2016 22:55:46 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveAttributesFromFindings

Removes entire attributes (key and value pairs) from the findings that are specified by the ARNs of the findings where an attribute with the specified key exists.

Request Syntax

```
{  
  "attributeKeys": [ "string" ],  
  "findingArns": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

attributeKeys (p. 106)

The array of attribute keys that you want to remove from specified findings.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

findingArns (p. 106)

The ARNs that specify the findings that you want to remove attributes from.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "failedItems": {  
    "string": {  
      "failureCode": "string",  
      "retryable": boolean  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failedItems (p. 106)

Attributes details that cannot be described. An error code is provided for each failed item.

Type: String to [FailedItemDetails](#) (p. 157) object map

Key Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `RemoveAttributesFromFindings`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 181
X-Amz-Target: InspectorService.RemoveAttributesFromFindings
X-Amz-Date: 20160329T234159Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
```

```
{
  "attributeKeys": [
    "key=Example,value=example"
  ],
  "findingArns": [
    "arn:aws:inspector:us-west-2:123456789012:target/0-0kFIPusq/
template/0-811VIEOD/run/0-Z02cjjug/finding/0-T8yM9mEU"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: d4ebb8cf-f607-11e5-94d7-d9eab7a1ae2a
Content-Type: application/x-amz-json-1.1
Content-Length: 18
Date: Tue, 29 Mar 2016 23:42:00 GMT
{
  "failedItems": {}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetTagsForResource

Sets tags (key and value pairs) to the assessment template that is specified by the ARN of the assessment template.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

resourceArn (p. 109)

The ARN of the assessment template that you want to set tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

tags (p. 109)

A collection of key and value pairs that you want to set to the assessment template.

Type: Array of [Tag](#) (p. 174) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 179).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `SetTagsForResource`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 144
X-Amz-Target: InspectorService.SetTagsForResource
X-Amz-Date: 20160331T185018Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "tags": [
    {
      "key": "Example",
      "value": "example"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6a3f5af3-f771-11e5-8599-f1b50afafb5a
Content-Type: application/x-amz-json-1.1
```

Content-Length: 0
Date: Thu, 31 Mar 2016 18:50:18 GMT

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAssessmentRun

Starts the assessment run specified by the ARN of the assessment template. For this API to function properly, you must not exceed the limit of running up to 500 concurrent agents per AWS account.

Request Syntax

```
{  
  "assessmentRunName": "string",  
  "assessmentTemplateArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentRunName (p. 112)

You can specify the name for the assessment run. The name must be unique for the assessment template whose ARN is used to start the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

assessmentTemplateArn (p. 112)

The ARN of the assessment template of the assessment run that you want to start.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Syntax

```
{  
  "assessmentRunArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

assessmentRunArn (p. 112)

The ARN of the assessment run that has been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

AgentsAlreadyRunningAssessmentException

You started an assessment run, but one of the instances is already participating in another assessment run.

HTTP Status Code: 400

InternalException

Internal server error.

HTTP Status Code: 500

InvalidCrossAccountRoleException

Amazon Inspector cannot assume the cross-account role that it needs to list your EC2 instances during the assessment run.

HTTP Status Code: 400

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `StartAssessmentRun`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 142
X-Amz-Target: InspectorService.StartAssessmentRun
X-Amz-Date: 20160331T182519Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunName": "examplerun",
  "assessmentTemplateArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: ed349455-f76d-11e5-b473-ed8493878c40
Content-Type: application/x-amz-json-1.1
Content-Length: 116
Date: Thu, 31 Mar 2016 18:25:22 GMT
{
  "assessmentRunArn": "arn:aws:inspector:us-west-2:123456789012:target/0-
nvgVhaxX/template/0-it5r2S4T/run/0-jOoroxyY"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAssessmentRun

Stops the assessment run that is specified by the ARN of the assessment run.

Request Syntax

```
{  
  "assessmentRunArn": "string",  
  "stopAction": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 177\)](#).

The request accepts the following data in JSON format.

assessmentRunArn (p. 115)

The ARN of the assessment run that you want to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

stopAction (p. 115)

An input option that can be set to either START_EVALUATION or SKIP_EVALUATION. START_EVALUATION (the default value), stops the AWS agent from collecting data and begins the results evaluation and the findings generation process. SKIP_EVALUATION cancels the assessment run immediately, after which no findings are generated.

Type: String

Valid Values: START_EVALUATION | SKIP_EVALUATION

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `StopAssessmentRun`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 117
X-Amz-Target: InspectorService.StopAssessmentRun
X-Amz-Date: 20160331T183401Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentRunArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-it5r2S4T/run/0-11LMTAVe"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 23e1a935-f76f-11e5-92d3-7ba54a65df23
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:34:02 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SubscribeToEvent

Enables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event": "string",  
  "resourceArn": "string",  
  "topicArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

event (p. 118)

The event for which you want to receive SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn (p. 118)

The ARN of the assessment template that is used during the event for which you want to receive SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn (p. 118)

The ARN of the SNS topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

LimitExceededException

The request was rejected because it attempted to create resources beyond the current AWS account limits. The error code describes the limit exceeded.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporary unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `SubscribeToEvent`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.SubscribeToEvent
X-Amz-Date: 20160331T201719Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
```



```
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 929b6c44-f77d-11e5-bcc6-cd3a7bd10be0
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:17:20 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UnsubscribeFromEvent

Disables the process of sending Amazon Simple Notification Service (SNS) notifications about a specified event to a specified SNS topic.

Request Syntax

```
{  
  "event": "string",  
  "resourceArn": "string",  
  "topicArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

event (p. 121)

The event for which you want to stop receiving SNS notifications.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED | ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

resourceArn (p. 121)

The ARN of the assessment template that is used during the event for which you want to stop receiving SNS notifications.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn (p. 121)

The ARN of the SNS topic to which SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `UnsubscribeFromEvent`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 200
X-Amz-Target: InspectorService.UnsubscribeFromEvent
X-Amz-Date: 20160331T203404Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "resourceArn": "arn:aws:inspector:us-west-2:123456789012:target/0-nvgVhaxX/template/0-7sbz2Kz0",
  "event": "ASSESSMENT_RUN_COMPLETED",
  "topicArn": "arn:aws:sns:us-west-2:123456789012:exampletopic"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e9c2e864-f77f-11e5-82d7-bb83264505be
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 20:34:06 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAssessmentTarget

Updates the assessment target that is specified by the ARN of the assessment target.

If resourceGroupArn is not specified, all EC2 instances in the current AWS account and region are included in the assessment target.

Request Syntax

```
{  
  "assessmentTargetArn": "string",  
  "assessmentTargetName": "string",  
  "resourceGroupArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 177).

The request accepts the following data in JSON format.

assessmentTargetArn (p. 124)

The ARN of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTargetName (p. 124)

The name of the assessment target that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn (p. 124)

The ARN of the resource group that is used to specify the new resource group to associate with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 179\)](#).

InternalException

Internal server error.

HTTP Status Code: 500

InvalidInputException

The request was rejected because an invalid or out-of-range value was supplied for an input parameter.

HTTP Status Code: 400

NoSuchEntityException

The request was rejected because it referenced an entity that does not exist. The error code describes the entity.

HTTP Status Code: 400

ServiceTemporarilyUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `UpdateAssessmentTarget`.

Sample Request

```
POST / HTTP/1.1
Host: inspector.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 206
X-Amz-Target: InspectorService.UpdateAssessmentTarget
X-Amz-Date: 20160331T185748Z
User-Agent: aws-cli/1.10.12 Python/2.7.9 Windows/7 botocore/1.4.3
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS
{
  "assessmentTargetArn": "arn:aws:inspector:us-
west-2:123456789012:target/0-nvgVhaxX",
  "assessmentTargetName": "Example",
  "resourceGroupArn": "arn:aws:inspector:us-
west-2:123456789012:resourcegroup/0-yNbgL5Pt"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 76bc43e7-f772-11e5-a5f3-fb6257e71620
Content-Type: application/x-amz-json-1.1
Content-Length: 0
Date: Thu, 31 Mar 2016 18:57:49 GMT
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Inspector API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AgentAlreadyRunningAssessment](#) (p. 128)
- [AgentFilter](#) (p. 129)
- [AgentPreview](#) (p. 130)
- [AssessmentRun](#) (p. 132)
- [AssessmentRunAgent](#) (p. 135)
- [AssessmentRunFilter](#) (p. 137)
- [AssessmentRunNotification](#) (p. 139)
- [AssessmentRunStateChange](#) (p. 141)
- [AssessmentTarget](#) (p. 142)
- [AssessmentTargetFilter](#) (p. 144)
- [AssessmentTemplate](#) (p. 145)
- [AssessmentTemplateFilter](#) (p. 147)
- [AssetAttributes](#) (p. 148)
- [Attribute](#) (p. 150)
- [DurationRange](#) (p. 151)
- [EventSubscription](#) (p. 152)
- [Exclusion](#) (p. 153)
- [ExclusionPreview](#) (p. 155)
- [FailedItemDetails](#) (p. 157)
- [Finding](#) (p. 158)
- [FindingFilter](#) (p. 161)
- [InspectorServiceAttributes](#) (p. 163)
- [NetworkInterface](#) (p. 164)
- [Privately](#) (p. 166)
- [ResourceGroup](#) (p. 167)
- [ResourceGroupTag](#) (p. 168)
- [RulesPackage](#) (p. 169)
- [Scope](#) (p. 171)
- [SecurityGroup](#) (p. 172)
- [Subscription](#) (p. 173)
- [Tag](#) (p. 174)
- [TelemetryMetadata](#) (p. 175)
- [TimestampRange](#) (p. 176)

AgentAlreadyRunningAssessment

Used in the exception error that is thrown if you start an assessment run for an assessment target that includes an EC2 instance that is already participating in another started assessment run.

Contents

agentId

ID of the agent that is running on an EC2 instance that is already participating in another started assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that has already been started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentFilter

Contains information about an Amazon Inspector agent. This data type is used as a request parameter in the [ListAssessmentRunAgents](#) (p. 65) action.

Contents

agentHealthCodes

The detailed health state of the agent. Values can be set to **IDLE**, **RUNNING**, **SHUTDOWN**, **UNHEALTHY**, **THROTTLED**, and **UNKNOWN**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: **IDLE** | **RUNNING** | **SHUTDOWN** | **UNHEALTHY** | **THROTTLED** | **UNKNOWN**

Required: Yes

agentHealths

The current health state of the agent. Values can be set to **HEALTHY** or **UNHEALTHY**.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Valid Values: **HEALTHY** | **UNHEALTHY** | **UNKNOWN**

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AgentPreview

Used as a response element in the [PreviewAgents](#) (p. 99) action.

Contents

agentHealth

The health status of the Amazon Inspector Agent.

Type: String

Valid Values: `HEALTHY` | `UNHEALTHY` | `UNKNOWN`

Required: No

agentId

The ID of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

agentVersion

The version of the Amazon Inspector Agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

autoScalingGroup

The Auto Scaling group for the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance on which the Amazon Inspector Agent is installed.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Address

The IP address of the EC2 instance on which the Amazon Inspector Agent is installed.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

kernelVersion

The kernel version of the operating system running on the EC2 instance on which the Amazon Inspector Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

operatingSystem

The operating system running on the EC2 instance on which the Amazon Inspector Agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRun

A snapshot of an Amazon Inspector assessment run that contains the findings of the assessment run .

Used as the response element in the [DescribeAssessmentRuns](#) (p. 27) action.

Contents

arn

The ARN of the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentTemplateArn

The ARN of the assessment template that is associated with the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

completedAt

The assessment run completion time that corresponds to the rules packages evaluation completion time or failure.

Type: Timestamp

Required: No

createdAt

The time when [StartAssessmentRun](#) (p. 112) was called.

Type: Timestamp

Required: Yes

dataCollected

A Boolean value (true or false) that specifies whether the process of collecting data from the agents is completed.

Type: Boolean

Required: Yes

durationInSeconds

The duration of the assessment run.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

findingCounts

Provides a total count of generated findings per severity.

Type: String to integer map

Valid Keys: Low | Medium | High | Informational | Undefined

Required: Yes

name

The auto-generated name for the assessment run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

notifications

A list of notifications for the event subscriptions. A notification about a particular generated finding is added to this list only once.

Type: Array of [AssessmentRunNotification](#) (p. 139) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

rulesPackageArns

The rules packages selected for the assessment run.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

startedAt

The time when [StartAssessmentRun](#) (p. 112) was called.

Type: Timestamp

Required: No

state

The state of the assessment run.

Type: String

Valid Values: CREATED | START_DATA_COLLECTION_PENDING | START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA | STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED | START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR | COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: Yes

stateChangedAt

The last time when the assessment run's state changed.

Type: Timestamp

Required: Yes

stateChanges

A list of the assessment run state changes.

Type: Array of [AssessmentRunStateChange](#) (p. 141) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding.

Type: Array of [Attribute](#) (p. 150) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunAgent

Contains information about an Amazon Inspector agent. This data type is used as a response element in the [ListAssessmentRunAgents](#) (p. 65) action.

Contents

agentHealth

The current health state of the agent.

Type: String

Valid Values: `HEALTHY` | `UNHEALTHY` | `UNKNOWN`

Required: Yes

agentHealthCode

The detailed health state of the agent.

Type: String

Valid Values: `IDLE` | `RUNNING` | `SHUTDOWN` | `UNHEALTHY` | `THROTTLED` | `UNKNOWN`

Required: Yes

agentHealthDetails

The description for the agent health code.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

agentId

The AWS account of the EC2 instance where the agent is installed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

assessmentRunArn

The ARN of the assessment run that is associated with the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

autoScalingGroup

The Auto Scaling group of the EC2 instance that is specified by the agent ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

telemetryMetadata

The Amazon Inspector application data metrics that are collected by the agent.

Type: Array of [TelemetryMetadata](#) (p. 175) objects

Array Members: Minimum number of 0 items. Maximum number of 5000 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunFilter

Used as the request parameter in the [ListAssessmentRuns](#) (p. 71) action.

Contents

completionTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **completedAt** property of the [AssessmentRun](#) (p. 132) data type.

Type: [TimestampRange](#) (p. 176) object

Required: No

durationRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentRun](#) (p. 132) data type.

Type: [DurationRange](#) (p. 151) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string containing a wildcard that is specified for this data type property must match the value of the **assessmentRunName** property of the [AssessmentRun](#) (p. 132) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **rulesPackages** property of the [AssessmentRun](#) (p. 132) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

startTimeRange

For a record to match a filter, the value that is specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **startTime** property of the [AssessmentRun](#) (p. 132) data type.

Type: [TimestampRange](#) (p. 176) object

Required: No

stateChangeTimeRange

For a record to match a filter, the value that is specified for this data type property must match the **stateChangedAt** property of the [AssessmentRun](#) (p. 132) data type.

Type: [TimestampRange](#) (p. 176) object

Required: No

states

For a record to match a filter, one of the values specified for this data type property must be the exact match of the value of the **assessmentRunState** property of the [AssessmentRun](#) (p. 132) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: CREATED | START_DATA_COLLECTION_PENDING |
START_DATA_COLLECTION_IN_PROGRESS | COLLECTING_DATA
| STOP_DATA_COLLECTION_PENDING | DATA_COLLECTED |
START_EVALUATING_RULES_PENDING | EVALUATING_RULES | FAILED | ERROR |
COMPLETED | COMPLETED_WITH_ERRORS | CANCELED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunNotification

Used as one of the elements of the [AssessmentRun](#) (p. 132) data type.

Contents

date

The date of the notification.

Type: Timestamp

Required: Yes

error

The Boolean value that specifies whether the notification represents an error.

Type: Boolean

Required: Yes

event

The event for which a notification is sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED |
ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

message

The message included in the notification.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

snsPublishStatusCode

The status code of the SNS notification.

Type: String

Valid Values: SUCCESS | TOPIC_DOES_NOT_EXIST | ACCESS_DENIED | INTERNAL_ERROR

Required: No

snsTopicArn

The SNS topic to which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentRunStateChange

Used as one of the elements of the [AssessmentRun](#) (p. 132) data type.

Contents

state

The assessment run state.

Type: String

Valid Values: `CREATED` | `START_DATA_COLLECTION_PENDING` | `START_DATA_COLLECTION_IN_PROGRESS` | `COLLECTING_DATA` | `STOP_DATA_COLLECTION_PENDING` | `DATA_COLLECTED` | `START_EVALUATING_RULES_PENDING` | `EVALUATING_RULES` | `FAILED` | `ERROR` | `COMPLETED` | `COMPLETED_WITH_ERRORS` | `CANCELED`

Required: Yes

stateChangedAt

The last time the assessment run state changed.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTarget

Contains information about an Amazon Inspector application. This data type is used as the response element in the [DescribeAssessmentTargets](#) (p. 31) action.

Contents

arn

The ARN that specifies the Amazon Inspector assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment target is created.

Type: Timestamp

Required: Yes

name

The name of the Amazon Inspector assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

resourceGroupArn

The ARN that specifies the resource group that is associated with the assessment target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

updatedAt

The time at which [UpdateAssessmentTarget](#) (p. 124) is called.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

AssessmentTargetFilter

Used as the request parameter in the [ListAssessmentTargets](#) (p. 75) action.

Contents

assessmentTargetNamePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTargetName** property of the [AssessmentTarget](#) (p. 142) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplate

Contains information about an Amazon Inspector assessment template. This data type is used as the response element in the [DescribeAssessmentTemplates](#) (p. 34) action.

Contents

arn

The ARN of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assessmentRunCount

The number of existing assessment runs associated with this assessment template. This value can be zero or a positive integer.

Type: Integer

Required: Yes

assessmentTargetArn

The ARN of the assessment target that corresponds to this assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which the assessment template is created.

Type: Timestamp

Required: Yes

durationInSeconds

The duration in seconds specified for this assessment template. The default value is 3600 seconds (one hour). The maximum value is 86400 seconds (one day).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: Yes

lastAssessmentRunArn

The Amazon Resource Name (ARN) of the most recent assessment run associated with this assessment template. This value exists only when the value of assessmentRunCount is greater than zero.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

name

The name of the assessment template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: Yes

rulesPackageArns

The rules packages that are specified for this assessment template.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

userAttributesForFindings

The user-defined attributes that are assigned to every generated finding from the assessment run that uses this assessment template.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssessmentTemplateFilter

Used as the request parameter in the [ListAssessmentTemplates](#) (p. 78) action.

Contents

durationRange

For a record to match a filter, the value specified for this data type property must inclusively match any value between the specified minimum and maximum values of the **durationInSeconds** property of the [AssessmentTemplate](#) (p. 145) data type.

Type: [DurationRange](#) (p. 151) object

Required: No

namePattern

For a record to match a filter, an explicit value or a string that contains a wildcard that is specified for this data type property must match the value of the **assessmentTemplateName** property of the [AssessmentTemplate](#) (p. 145) data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 140.

Required: No

rulesPackageArns

For a record to match a filter, the values that are specified for this data type property must be contained in the list of values of the **rulesPackageArns** property of the [AssessmentTemplate](#) (p. 145) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetAttributes

A collection of attributes of the host from which the finding is generated.

Contents

agentId

The ID of the agent that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

amiId

The ID of the Amazon Machine Image (AMI) that is installed on the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

autoScalingGroup

The Auto Scaling group of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

hostname

The hostname of the EC2 instance where the finding is generated.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ipv4Addresses

The list of IP v4 addresses of the EC2 instance where the finding is generated.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 7. Maximum length of 15.

Required: No

networkInterfaces

An array of the network interfaces interacting with the EC2 instance where the finding is generated.

Type: Array of [NetworkInterface](#) (p. 164) objects

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

tags

The tags related to the EC2 instance where the finding is generated.

Type: Array of [Tag](#) (p. 174) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Attribute

This data type is used as a request parameter in the [AddAttributesToFindings](#) (p. 3) and [CreateAssessmentTemplate](#) (p. 9) actions.

Contents

key

The attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to the attribute key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DurationRange

This data type is used in the [AssessmentTemplateFilter](#) (p. 147) data type.

Contents

maxSeconds

The maximum value of the duration range. Must be less than or equal to 604800 seconds (1 week).

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

minSeconds

The minimum value of the duration range. Must be greater than zero.

Type: Integer

Valid Range: Minimum value of 180. Maximum value of 86400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventSubscription

This data type is used in the [Subscription](#) (p. 173) data type.

Contents

event

The event for which Amazon Simple Notification Service (SNS) notifications are sent.

Type: String

Valid Values: ASSESSMENT_RUN_STARTED | ASSESSMENT_RUN_COMPLETED |
ASSESSMENT_RUN_STATE_CHANGED | FINDING_REPORTED | OTHER

Required: Yes

subscribedAt

The time at which [SubscribeToEvent](#) (p. 118) is called.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Exclusion

Contains information about what was excluded from an assessment run.

Contents

arn

The ARN that specifies the exclusion.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

attributes

The system-defined attributes for the exclusion.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

description

The description of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion pertains.

Type: Array of [Scope \(p. 171\)](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExclusionPreview

Contains information about what is excluded from an assessment run given the current state of the assessment template.

Contents

attributes

The system-defined attributes for the exclusion preview.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

description

The description of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

recommendation

The recommendation for the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

scopes

The AWS resources for which the exclusion preview pertains.

Type: Array of [Scope \(p. 171\)](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

title

The name of the exclusion preview.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedItemDetails

Includes details about the failed items.

Contents

failureCode

The status code of a failed item.

Type: String

Valid Values: INVALID_ARN | DUPLICATE_ARN | ITEM_DOES_NOT_EXIST | ACCESS_DENIED
| LIMIT_EXCEEDED | INTERNAL_ERROR

Required: Yes

retryable

Indicates whether you can immediately retry a request for this item for a specified resource.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Finding

Contains information about an Amazon Inspector finding. This data type is used as the response element in the [DescribeFindings](#) (p. 42) action.

Contents

arn

The ARN that specifies the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

assetAttributes

A collection of attributes of the host from which the finding is generated.

Type: [AssetAttributes](#) (p. 148) object

Required: No

assetType

The type of the host from which the finding is generated.

Type: String

Valid Values: `ec2-instance`

Required: No

attributes

The system-defined attributes for the finding.

Type: Array of [Attribute](#) (p. 150) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

confidence

This data element is currently not used.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

createdAt

The time when the finding was generated.

Type: Timestamp

Required: Yes

description

The description of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

id

The ID of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

indicatorOfCompromise

This data element is currently not used.

Type: Boolean

Required: No

numericSeverity

The numeric value of the finding severity.

Type: Double

Valid Range: Minimum value of 0.0. Maximum value of 10.0.

Required: No

recommendation

The recommendation for the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

service

The data element is set to "Inspector".

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

serviceAttributes

This data type is used in the [Finding \(p. 158\)](#) data type.

Type: [InspectorServiceAttributes \(p. 163\)](#) object

Required: No

severity

The finding severity. Values can be set to High, Medium, Low, and Informational.

Type: String

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

title

The name of the finding.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

updatedAt

The time when [AddAttributesToFindings \(p. 3\)](#) is called.

Type: Timestamp

Required: Yes

userAttributes

The user-defined attributes that are assigned to the finding.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FindingFilter

This data type is used as a request parameter in the [ListFindings \(p. 89\)](#) action.

Contents

agentIds

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **agentId** property of the [Finding \(p. 158\)](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 99 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

attributes

For a record to match a filter, the list of values that are specified for this data type property must be contained in the list of values of the **attributes** property of the [Finding \(p. 158\)](#) data type.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

autoScalingGroups

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **autoScalingGroup** property of the [Finding \(p. 158\)](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

creationTimeRange

The time range during which the finding is generated.

Type: [TimestampRange \(p. 176\)](#) object

Required: No

ruleNames

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **ruleName** property of the [Finding \(p. 158\)](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Maximum length of 1000.

Required: No

rulesPackageArns

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **rulesPackageArn** property of the [Finding \(p. 158\)](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

severities

For a record to match a filter, one of the values that is specified for this data type property must be the exact match of the value of the **severity** property of the [Finding \(p. 158\)](#) data type.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Valid Values: Low | Medium | High | Informational | Undefined

Required: No

userAttributes

For a record to match a filter, the value that is specified for this data type property must be contained in the list of values of the **userAttributes** property of the [Finding \(p. 158\)](#) data type.

Type: Array of [Attribute \(p. 150\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InspectorServiceAttributes

This data type is used in the [Finding](#) (p. 158) data type.

Contents

assessmentRunArn

The ARN of the assessment run during which the finding is generated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

rulesPackageArn

The ARN of the rules package that is used to generate the finding.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

schemaVersion

The schema version of this data type.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkInterface

Contains information about the network interfaces interacting with an EC2 instance. This data type is used as one of the elements of the [AssetAttributes](#) (p. 148) data type.

Contents

ipv6Addresses

The IP addresses associated with the network interface.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

networkInterfaceId

The ID of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateDnsName

The name of a private DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The private IP address associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddresses

A list of the private IP addresses associated with the network interface. Includes the `privateDnsName` and `privateIpAddress`.

Type: Array of [PrivateIp](#) (p. 166) objects

Required: No

publicDnsName

The name of a public DNS associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

publicIp

The public IP address from which the network interface is reachable.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

securityGroups

A list of the security groups associated with the network interface. Includes the groupId and groupName.

Type: Array of [SecurityGroup](#) (p. 172) objects

Required: No

subnetId

The ID of a subnet associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

vpcId

The ID of a VPC associated with the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Privatelp

Contains information about a private IP address associated with a network interface. This data type is used as a response element in the [DescribeFindings](#) (p. 42) action.

Contents

privateDnsName

The DNS name of the private IP address.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

privateIpAddress

The full IP address of the network interface.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroup

Contains information about a resource group. The resource group defines a set of tags that, when queried, identify the AWS resources that make up the assessment target. This data type is used as the response element in the [DescribeResourceGroups](#) (p. 47) action.

Contents

arn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

createdAt

The time at which resource group is created.

Type: Timestamp

Required: Yes

tags

The tags (key and value pairs) of the resource group. This data type property is used in the [CreateResourceGroup](#) (p. 15) action.

Type: Array of [ResourceGroupTag](#) (p. 168) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGroupTag

This data type is used as one of the elements of the [ResourceGroup](#) (p. 167) data type.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RulesPackage

Contains information about an Amazon Inspector rules package. This data type is used as the response element in the [DescribeRulesPackages](#) (p. 50) action.

Contents

arn

The ARN of the rules package.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

description

The description of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

name

The name of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

provider

The provider of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

version

The version ID of the rules package.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Scope

This data type contains key-value pairs that identify various Amazon resources.

Contents

key

The type of the scope.

Type: String

Valid Values: `INSTANCE_ID` | `RULES_PACKAGE_ARN`

Required: No

value

The resource identifier for the specified scope type.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityGroup

Contains information about a security group associated with a network interface. This data type is used as one of the elements of the [NetworkInterface](#) (p. 164) data type.

Contents

groupId

The ID of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

groupName

The name of the security group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 20000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Subscription

This data type is used as a response element in the [ListEventSubscriptions](#) (p. 82) action.

Contents

eventSubscriptions

The list of existing event subscriptions.

Type: Array of [EventSubscription](#) (p. 152) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

resourceArn

The ARN of the assessment template that is used during the event for which the SNS notification is sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

topicArn

The ARN of the Amazon Simple Notification Service (SNS) topic to which the SNS notifications are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A key and value pair. This data type is used as a request parameter in the [SetTagsForResource](#) (p. 109) action and a response element in the [ListTagsForResource](#) (p. 96) action.

Contents

key

A tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

A value assigned to a tag key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TelemetryMetadata

The metadata about the Amazon Inspector application data metrics collected by the agent. This data type is used as the response element in the [GetTelemetryMetadata](#) (p. 60) action.

Contents

count

The count of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: Yes

dataSize

The data size of messages that the agent sends to the Amazon Inspector service.

Type: Long

Required: No

messageType

A specific type of behavioral data that is collected by the agent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestampRange

This data type is used in the [AssessmentRunFilter](#) (p. 137) data type.

Contents

beginDate

The minimum value of the timestamp range.

Type: Timestamp

Required: No

endDate

The maximum value of the timestamp range.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400