
AWS Support

API Reference

API Version 2013-04-15



AWS Support: API Reference

Copyright © Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddAttachmentsToSet	3
Request Syntax	3
Request Parameters	3
Response Syntax	3
Response Elements	4
Errors	4
See Also	4
AddCommunicationToCase	6
Request Syntax	6
Request Parameters	6
Response Syntax	7
Response Elements	7
Errors	7
See Also	7
CreateCase	9
Request Syntax	9
Request Parameters	9
Response Syntax	11
Response Elements	11
Errors	11
See Also	11
DescribeAttachment	13
Request Syntax	13
Request Parameters	13
Response Syntax	13
Response Elements	13
Errors	14
See Also	14
DescribeCases	15
Request Syntax	15
Request Parameters	15
Response Syntax	16
Response Elements	17
Errors	17
See Also	17
DescribeCommunications	19
Request Syntax	19
Request Parameters	19
Response Syntax	20
Response Elements	20
Errors	20
See Also	21
DescribeServices	22
Request Syntax	22
Request Parameters	22
Response Syntax	22
Response Elements	23
Errors	23
See Also	23
DescribeSeverityLevels	24
Request Syntax	24
Request Parameters	24

Response Syntax	24
Response Elements	24
Errors	25
See Also	25
DescribeTrustedAdvisorCheckRefreshStatuses	26
Request Syntax	26
Request Parameters	26
Response Syntax	26
Response Elements	26
Errors	27
See Also	27
DescribeTrustedAdvisorCheckResult	28
Request Syntax	28
Request Parameters	28
Response Syntax	29
Response Elements	29
Errors	29
See Also	29
DescribeTrustedAdvisorChecks	31
Request Syntax	31
Request Parameters	31
Response Syntax	31
Response Elements	31
Errors	32
See Also	32
DescribeTrustedAdvisorCheckSummaries	33
Request Syntax	33
Request Parameters	33
Response Syntax	33
Response Elements	34
Errors	34
See Also	34
RefreshTrustedAdvisorCheck	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	35
Errors	36
See Also	36
ResolveCase	37
Request Syntax	37
Request Parameters	37
Response Syntax	37
Response Elements	37
Errors	38
See Also	38
Data Types	39
Attachment	40
Contents	40
See Also	40
AttachmentDetails	41
Contents	41
See Also	41
CaseDetails	42
Contents	42
See Also	44
Category	45

Contents	45
See Also	45
Communication	46
Contents	46
See Also	46
RecentCaseCommunications	47
Contents	47
See Also	47
Service	48
Contents	48
See Also	48
SeverityLevel	49
Contents	49
See Also	49
TrustedAdvisorCategorySpecificSummary	50
Contents	50
See Also	50
TrustedAdvisorCheckDescription	51
Contents	51
See Also	51
TrustedAdvisorCheckRefreshStatus	52
Contents	52
See Also	52
TrustedAdvisorCheckResult	53
Contents	53
See Also	53
TrustedAdvisorCheckSummary	54
Contents	54
See Also	54
TrustedAdvisorCostOptimizingSummary	55
Contents	55
See Also	55
TrustedAdvisorResourceDetail	56
Contents	56
See Also	56
TrustedAdvisorResourcesSummary	57
Contents	57
See Also	57
Common Parameters	58
Common Errors	60

Welcome

The *AWS Support API Reference* is intended for programmers who need detailed information about the AWS Support operations and data types. You can use the API to manage your support cases programmatically. The AWS Support API uses HTTP methods that return results in JSON format.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

The AWS Support service also exposes a set of [AWS Trusted Advisor](#) features. You can retrieve a list of checks and their descriptions, get check results, specify checks to refresh, and get the refresh status of checks.

The following list describes the AWS Support case management operations:

- Service names, issue categories, and available severity levels - The [DescribeServices](#) (p. 22) and [DescribeSeverityLevels](#) (p. 24) operations return AWS service names, service codes, service categories, and problem severity levels. You use these values when you call the [CreateCase](#) (p. 9) operation.
- Case creation, case details, and case resolution - The [CreateCase](#) (p. 9), [DescribeCases](#) (p. 15), [DescribeAttachment](#) (p. 13), and [ResolveCase](#) (p. 37) operations create AWS Support cases, retrieve information about cases, and resolve cases.
- Case communication - The [DescribeCommunications](#) (p. 19), [AddCommunicationToCase](#) (p. 6), and [AddAttachmentsToSet](#) (p. 3) operations retrieve and add communications and attachments to AWS Support cases.

The following list describes the operations available from the AWS Support service for Trusted Advisor:

- [DescribeTrustedAdvisorChecks](#) (p. 31) returns the list of checks that run against your AWS resources.
- Using the `checkId` for a specific check returned by [DescribeTrustedAdvisorChecks](#) (p. 31), you can call [DescribeTrustedAdvisorCheckResult](#) (p. 28) to obtain the results for the check that you specified.
- [DescribeTrustedAdvisorCheckSummaries](#) (p. 33) returns summarized results for one or more Trusted Advisor checks.
- [RefreshTrustedAdvisorCheck](#) (p. 35) requests that Trusted Advisor rerun a specified check.
- [DescribeTrustedAdvisorCheckRefreshStatuses](#) (p. 26) reports the refresh status of one or more checks.

For authentication of requests, AWS Support uses [Signature Version 4 Signing Process](#).

See [About the AWS Support API](#) in the *AWS Support User Guide* for information about how to use this service to create and manage your support cases, and how to call Trusted Advisor for results of checks on your resources.

This document was last published on October 6, 2021.

Actions

The following actions are supported:

- [AddAttachmentsToSet](#) (p. 3)
- [AddCommunicationToCase](#) (p. 6)
- [CreateCase](#) (p. 9)
- [DescribeAttachment](#) (p. 13)
- [DescribeCases](#) (p. 15)
- [DescribeCommunications](#) (p. 19)
- [DescribeServices](#) (p. 22)
- [DescribeSeverityLevels](#) (p. 24)
- [DescribeTrustedAdvisorCheckRefreshStatuses](#) (p. 26)
- [DescribeTrustedAdvisorCheckResult](#) (p. 28)
- [DescribeTrustedAdvisorChecks](#) (p. 31)
- [DescribeTrustedAdvisorCheckSummaries](#) (p. 33)
- [RefreshTrustedAdvisorCheck](#) (p. 35)
- [ResolveCase](#) (p. 37)

AddAttachmentsToSet

Adds one or more attachments to an attachment set.

An attachment set is a temporary container for attachments that you add to a case or case communication. The set is available for 1 hour after it's created. The `expiryTime` returned in the response is when the set expires.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{
  "attachments": [
    {
      "data": blob,
      "fileName": "string"
    }
  ],
  "attachmentSetId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`attachments` (p. 3)

One or more attachments to add to the set. You can add up to three attachments per set. The size limit is 5 MB per attachment.

In the `Attachment` object, use the `data` parameter to specify the contents of the attachment file. In the previous request syntax, the value for `data` appear as `blob`, which is represented as a base64-encoded string. The value for `fileName` is the name of the attachment, such as `troubleshoot-screenshot.png`.

Type: Array of [Attachment](#) (p. 40) objects

`attachmentSetId` (p. 3)

The ID of the attachment set. If an `attachmentSetId` is not specified, a new attachment set is created, and the ID of the set is returned in the response. If an `attachmentSetId` is specified, the attachments are added to the specified set, if it exists.

Type: String

Response Syntax

```
{
```



```
"attachmentSetId": "string",  
"expiryTime": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

attachmentSetId (p. 3)

The ID of the attachment set. If an `attachmentSetId` was not specified, a new attachment set is created, and the ID of the set is returned in the response. If an `attachmentSetId` was specified, the attachments are added to the specified set, if it exists.

Type: String

expiryTime (p. 3)

The time and date when the attachment set expires.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

AttachmentLimitExceeded

The limit for the number of attachment sets created in a short period of time has been exceeded.

HTTP Status Code: 400

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

AttachmentSetSizeLimitExceeded

A limit for the size of an attachment set has been exceeded. The limits are three attachments and 5 MB per attachment.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AddCommunicationToCase

Adds additional customer communication to an AWS Support case. Use the `caseId` parameter to identify the case to which to add communication. You can list a set of email addresses to copy on the communication by using the `ccEmailAddresses` parameter. The `communicationBody` value contains the text of the communication.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachmentSetId": "string",  
  "caseId": "string",  
  "ccEmailAddresses": [ "string" ],  
  "communicationBody": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`attachmentSetId` (p. 6)

The ID of a set of one or more attachments for the communication to add to the case. Create the set by calling [AddAttachmentsToSet](#) (p. 3)

Type: String

`caseId` (p. 6)

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

`ccEmailAddresses` (p. 6)

The email addresses in the CC line of an email to be added to the support case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

`communicationBody` (p. 6)

The body of an email communication to add to the support case.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Response Syntax

```
{  
  "result": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

result (p. 7)

True if [AddCommunicationToCase](#) (p. 6) succeeds. Otherwise, returns an error.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

CaseIdNotFound

The requested `caseId` couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCase

Creates a case in the AWS Support Center. This operation is similar to how you create a case in the AWS Support Center [Create Case](#) page.

The AWS Support API doesn't support requesting service limit increases. You can submit a service limit increase in the following ways:

- Submit a request from the AWS Support Center [Create Case](#) page.
- Use the Service Quotas [RequestServiceQuotaIncrease](#) operation.

A successful `CreateCase` request returns an AWS Support case number. You can use the [DescribeCases](#) (p. 15) operation and specify the case number to get existing AWS Support cases. After you create a case, use the [AddCommunicationToCase](#) (p. 6) operation to add additional communication or attachments to an existing case.

The `caseId` is separate from the `displayId` that appears in the [AWS Support Center](#). Use the [DescribeCases](#) (p. 15) operation to get the `displayId`.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{
  "attachmentSetId": "string",
  "categoryCode": "string",
  "ccEmailAddresses": [ "string" ],
  "communicationBody": "string",
  "issueType": "string",
  "language": "string",
  "serviceCode": "string",
  "severityCode": "string",
  "subject": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`attachmentSetId` (p. 9)

The ID of a set of one or more attachments for the case. Create the set by using the [AddAttachmentsToSet](#) (p. 3) operation.

Type: String

categoryCode (p. 9)

The category of problem for the support case. You also use the [DescribeServices](#) (p. 22) operation to get the category code for a service. Each AWS service defines its own set of category codes.

Type: String

ccEmailAddresses (p. 9)

A list of email addresses that AWS Support copies on case correspondence. AWS Support identifies the account that creates the case when you specify your AWS credentials in an HTTP POST method or use the [AWS SDKs](#).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

communicationBody (p. 9)

The communication body text that describes the issue. This text appears in the **Description** field on the AWS Support Center [Create Case](#) page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

issueType (p. 9)

The type of issue for the case. You can specify `customer-service` or `technical`. If you don't specify a value, the default is `technical`.

Type: String

language (p. 9)

The language in which AWS Support handles the case. You must specify the ISO 639-1 code for the `language` parameter if you want support in that language. Currently, English ("en") and Japanese ("ja") are supported.

Type: String

serviceCode (p. 9)

The code for the AWS service. You can use the [DescribeServices](#) (p. 22) operation to get the possible `serviceCode` values.

Type: String

severityCode (p. 9)

A value that indicates the urgency of the case. This value determines the response time according to your service level agreement with AWS Support. You can use the [DescribeSeverityLevels](#) (p. 24) operation to get the possible values for `severityCode`.

For more information, see [SeverityLevel](#) (p. 49) and [Choosing a Severity](#) in the *AWS Support User Guide*.

Note

The availability of severity levels depends on the support plan for the AWS account.

Type: String

subject (p. 9)

The title of the support case. The title appears in the **Subject** field on the AWS Support Center [Create Case](#) page.

Type: String

Response Syntax

```
{  
  "caseId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

caseId (p. 11)

The support case ID requested or returned in the call. The case ID is an alphanumeric string in the following format: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

CaseCreationLimitExceeded

The case creation limit for the account has been exceeded.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAttachment

Returns the attachment that has the specified ID. Attachments can include screenshots, error logs, or other files that describe your issue. Attachment IDs are generated by the case management system when you add an attachment to a case or case communication. Attachment IDs are returned in the [AttachmentDetails](#) (p. 41) objects that are returned by the [DescribeCommunications](#) (p. 19) operation.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachmentId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

attachmentId (p. 13)

The ID of the attachment to return. Attachment IDs are returned by the [DescribeCommunications](#) (p. 19) operation.

Type: String

Response Syntax

```
{  
  "attachment": {  
    "data": blob,  
    "fileName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

attachment (p. 13)

This object includes the attachment content and file name.

In the previous response syntax, the value for the `data` parameter appears as `blob`, which is represented as a base64-encoded string. The value for `fileName` is the name of the attachment, such as `troubleshoot-screenshot.png`.

Type: [Attachment](#) (p. 40) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

AttachmentIdNotFound

An attachment with the specified ID could not be found.

HTTP Status Code: 400

DescribeAttachmentLimitExceeded

The limit for the number of [DescribeAttachment](#) (p. 13) requests in a short period of time has been exceeded.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCases

Returns a list of cases that you specify by passing one or more case IDs. You can use the `afterTime` and `beforeTime` parameters to filter the cases by date. You can set values for the `includeResolvedCases` and `includeCommunications` parameters to specify how much information to return.

The response returns the following in JSON format:

- One or more [CaseDetails](#) data types.
- One or more `nextToken` values, which specify where to paginate the returned records represented by the `CaseDetails` objects.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request might return an error.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "afterTime": "string",  
  "beforeTime": "string",  
  "caseIdList": [ "string" ],  
  "displayId": "string",  
  "includeCommunications": boolean,  
  "includeResolvedCases": boolean,  
  "language": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`afterTime` (p. 15)

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

`beforeTime` (p. 15)

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

caseIdList (p. 15)

A list of ID numbers of the support cases you want returned. The maximum number of cases is 100.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

displayId (p. 15)

The ID displayed for a case in the AWS Support Center user interface.

Type: String

includeCommunications (p. 15)

Specifies whether to include communications in the `DescribeCases` response. By default, communications are included.

Type: Boolean

includeResolvedCases (p. 15)

Specifies whether to include resolved support cases in the `DescribeCases` response. By default, resolved cases aren't included.

Type: Boolean

language (p. 15)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

maxResults (p. 15)

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

nextToken (p. 15)

A resumption point for pagination.

Type: String

Response Syntax

```
{
  "cases": [
    {
      "caseId": "string",
      "categoryCode": "string",
      "ccEmailAddresses": [ "string" ],
      "displayId": "string",
      "language": "string",
      "recentCommunications": {
        "communications": [
          {
            "attachmentSet": [
              {

```

```
        "attachmentId": "string",
        "fileName": "string"
      }
    ],
    "body": "string",
    "caseId": "string",
    "submittedBy": "string",
    "timeCreated": "string"
  }
},
"nextToken": "string"
},
"serviceCode": "string",
"severityCode": "string",
"status": "string",
"subject": "string",
"submittedBy": "string",
"timeCreated": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

cases (p. 16)

The details for the cases that match the request.

Type: Array of [CaseDetails](#) (p. 42) objects

nextToken (p. 16)

A resumption point for pagination.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

CaseIdNotFound

The requested `caseId` couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCommunications

Returns communications and attachments for one or more support cases. Use the `afterTime` and `beforeTime` parameters to filter by date. You can use the `caseId` parameter to restrict the results to a specific case.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request for data might cause an error.

You can use the `maxResults` and `nextToken` parameters to control the pagination of the results. Set `maxResults` to the number of cases that you want to display on each page, and use `nextToken` to specify the resumption of pagination.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "afterTime": "string",  
  "beforeTime": "string",  
  "caseId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`afterTime` (p. 19)

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

`beforeTime` (p. 19)

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

`caseId` (p. 19)

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

maxResults (p. 19)

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

nextToken (p. 19)

A resumption point for pagination.

Type: String

Response Syntax

```
{
  "communications": [
    {
      "attachmentSet": [
        {
          "attachmentId": "string",
          "fileName": "string"
        }
      ],
      "body": "string",
      "caseId": "string",
      "submittedBy": "string",
      "timeCreated": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

communications (p. 20)

The communications for the case.

Type: Array of [Communication](#) (p. 46) objects

nextToken (p. 20)

A resumption point for pagination.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

CaseIdNotFound

The requested caseId couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeServices

Returns the current list of AWS services and a list of service categories for each service. You then use service names and categories in your [CreateCase \(p. 9\)](#) requests. Each AWS service has its own set of categories.

The service codes and category codes correspond to the values that appear in the **Service** and **Category** lists on the AWS Support Center [Create Case](#) page. The values in those fields don't necessarily match the service codes and categories returned by the `DescribeServices` operation. Always use the service codes and categories that the `DescribeServices` operation returns, so that you have the most recent set of service and category codes.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{
  "language": "string",
  "serviceCodeList": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

[language \(p. 22\)](#)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

[serviceCodeList \(p. 22\)](#)

A JSON-formatted list of service codes available for AWS services.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Response Syntax

```
{
  "services": [
    {
      "categories": [
```

```
{
  {
    "code": "string",
    "name": "string"
  },
  {
    "code": "string",
    "name": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

services (p. 22)

A JSON-formatted list of AWS services.

Type: Array of [Service](#) (p. 48) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSeverityLevels

Returns the list of severity levels that you can assign to a support case. The severity level for a case is also a field in the [CaseDetails](#) (p. 42) data type that you include for a [CreateCase](#) (p. 9) request.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

language (p. 24)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

Response Syntax

```
{  
  "severityLevels": [  
    {  
      "code": "string",  
      "name": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

severityLevels (p. 24)

The available severity levels for the support case. Available severity levels are defined by your service level agreement with AWS.

Type: Array of [SeverityLevel](#) (p. 49) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckRefreshStatuses

Returns the refresh status of the AWS Trusted Advisor checks that have the specified check IDs. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) (p. 31) operation.

Some checks are refreshed automatically, and you can't return their refresh statuses by using the `DescribeTrustedAdvisorCheckRefreshStatuses` operation. If you call this operation for these checks, you might see an `InvalidParameterValue` error.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "checkIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`checkIds` (p. 26)

The IDs of the Trusted Advisor checks to get the status.

Note

If you specify the check ID of a check that is automatically refreshed, you might see an `InvalidParameterValue` error.

Type: Array of strings

Response Syntax

```
{  
  "statuses": [  
    {  
      "checkId": "string",  
      "millisUntilNextRefreshable": number,  
      "status": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

statuses (p. 26)

The refresh status of the specified Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckRefreshStatus](#) (p. 52) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckResult

Returns the results of the AWS Trusted Advisor check that has the specified check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) (p. 31) operation.

The response contains a [TrustedAdvisorCheckResult](#) (p. 53) object, which contains these three objects:

- [TrustedAdvisorCategorySpecificSummary](#) (p. 50)
- [TrustedAdvisorResourceDetail](#) (p. 56)
- [TrustedAdvisorResourcesSummary](#) (p. 57)

In addition, the response contains these fields:

- **status** - The alert status of the check can be `ok` (green), `warning` (yellow), `error` (red), or `not_available`.
- **timestamp** - The time of the last refresh of the check.
- **checkId** - The unique identifier for the check.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "checkId": "string",  
  "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

checkId (p. 28)

The unique identifier for the Trusted Advisor check.

Type: String

language (p. 28)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

Response Syntax

```
{
  "result": {
    "categorySpecificSummary": {
      "costOptimizing": {
        "estimatedMonthlySavings": number,
        "estimatedPercentMonthlySavings": number
      }
    },
    "checkId": "string",
    "flaggedResources": [
      {
        "isSuppressed": boolean,
        "metadata": [ "string" ],
        "region": "string",
        "resourceId": "string",
        "status": "string"
      }
    ],
    "resourcesSummary": {
      "resourcesFlagged": number,
      "resourcesIgnored": number,
      "resourcesProcessed": number,
      "resourcesSuppressed": number
    },
    "status": "string",
    "timestamp": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

result (p. 29)

The detailed results of the Trusted Advisor check.

Type: [TrustedAdvisorCheckResult](#) (p. 53) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorChecks

Returns information about all available AWS Trusted Advisor checks, including the name, ID, category, description, and metadata. You must specify a language code. The AWS Support API currently supports English ("en") and Japanese ("ja"). The response contains a [TrustedAdvisorCheckDescription \(p. 51\)](#) object for each check. You must set the AWS Region to us-east-1.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).
- The names and descriptions for Trusted Advisor checks are subject to change. We recommend that you specify the check ID in your code to uniquely identify a check.

Request Syntax

```
{  
  "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

language (p. 31)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

Response Syntax

```
{  
  "checks": [  
    {  
      "category": "string",  
      "description": "string",  
      "id": "string",  
      "metadata": [ "string" ],  
      "name": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[checks](#) (p. 31)

Information about all available Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckDescription](#) (p. 51) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckSummaries

Returns the results for the AWS Trusted Advisor check summaries for the check IDs that you specified. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) (p. 31) operation.

The response contains an array of [TrustedAdvisorCheckSummary](#) (p. 54) objects.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "checkIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

checkIds (p. 33)

The IDs of the Trusted Advisor checks.

Type: Array of strings

Response Syntax

```
{  
  "summaries": [  
    {  
      "categorySpecificSummary": {  
        "costOptimizing": {  
          "estimatedMonthlySavings": number,  
          "estimatedPercentMonthlySavings": number  
        }  
      },  
      "checkId": "string",  
      "hasFlaggedResources": boolean,  
      "resourcesSummary": {  
        "resourcesFlagged": number,  
        "resourcesIgnored": number,  
        "resourcesProcessed": number,  
        "resourcesSuppressed": number  
      },  
      "status": "string",  
      "timestamp": "string"  
    }  
  ]  
}
```

```
} ]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

summaries (p. 33)

The summary information for the requested Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckSummary](#) (p. 54) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RefreshTrustedAdvisorCheck

Refreshes the AWS Trusted Advisor check that you specify using the check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) (p. 31) operation.

Note

Some checks are refreshed automatically. If you call the `RefreshTrustedAdvisorCheck` operation to refresh them, you might see the `InvalidParameterValue` error.

The response contains a [TrustedAdvisorCheckRefreshStatus](#) (p. 52) object.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "checkId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

checkId (p. 35)

The unique identifier for the Trusted Advisor check to refresh.

Note

Specifying the check ID of a check that is automatically refreshed causes an `InvalidParameterValue` error.

Type: String

Response Syntax

```
{  
  "status": {  
    "checkId": "string",  
    "millisUntilNextRefreshable": number,  
    "status": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status ([p. 35](#))

The current refresh status for a check, including the amount of time until the check is eligible for refresh.

Type: [TrustedAdvisorCheckRefreshStatus](#) ([p. 52](#)) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) ([p. 60](#)).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResolveCase

Resolves a support case. This operation takes a `caseId` and returns the initial and final state of the case.

Note

- You must have a Business or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "caseId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

`caseId` (p. 37)

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

Response Syntax

```
{  
  "finalCaseStatus": "string",  
  "initialCaseStatus": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`finalCaseStatus` (p. 37)

The status of the case after the [ResolveCase](#) (p. 37) request was processed.

Type: String

`initialCaseStatus` (p. 37)

The status of the case when the [ResolveCase](#) (p. 37) request was sent.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

CaseIdNotFound

The requested `caseId` couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Support API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Attachment](#) (p. 40)
- [AttachmentDetails](#) (p. 41)
- [CaseDetails](#) (p. 42)
- [Category](#) (p. 45)
- [Communication](#) (p. 46)
- [RecentCaseCommunications](#) (p. 47)
- [Service](#) (p. 48)
- [SeverityLevel](#) (p. 49)
- [TrustedAdvisorCategorySpecificSummary](#) (p. 50)
- [TrustedAdvisorCheckDescription](#) (p. 51)
- [TrustedAdvisorCheckRefreshStatus](#) (p. 52)
- [TrustedAdvisorCheckResult](#) (p. 53)
- [TrustedAdvisorCheckSummary](#) (p. 54)
- [TrustedAdvisorCostOptimizingSummary](#) (p. 55)
- [TrustedAdvisorResourceDetail](#) (p. 56)
- [TrustedAdvisorResourcesSummary](#) (p. 57)

Attachment

An attachment to a case communication. The attachment consists of the file name and the content of the file.

Contents

data

The content of the attachment file.

Type: Base64-encoded binary data object

fileName

The name of the attachment file.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentDetails

The file name and ID of an attachment to a case communication. You can use the ID to retrieve the attachment with the [DescribeAttachment](#) (p. 13) operation.

Contents

attachmentId

The ID of the attachment.

Type: String

fileName

The file name of the attachment.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CaseDetails

A JSON-formatted object that contains the metadata for a support case. It is contained in the response from a [DescribeCases](#) (p. 15) request. **CaseDetails** contains the following fields:

- **caseId** - The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`.
- **categoryCode** - The category of problem for the support case. Corresponds to the `CategoryCode` values returned by a call to [DescribeServices](#) (p. 22).
- **displayId** - The identifier for the case on pages in the AWS Support Center.
- **language** - The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.
- **nextToken** - A resumption point for pagination.
- **recentCommunications** - One or more [Communication](#) (p. 46) objects. Fields of these objects are `attachments`, `body`, `caseId`, `submittedBy`, and `timeCreated`.
- **serviceCode** - The identifier for the AWS service that corresponds to the service code defined in the call to [DescribeServices](#) (p. 22).
- **severityCode** - The severity code assigned to the case. Contains one of the values returned by the call to [DescribeSeverityLevels](#) (p. 24). The possible values are: `low`, `normal`, `high`, `urgent`, and `critical`.
- **status** - The status of the case in the AWS Support Center. Valid values:
 - `opened`
 - `pending-customer-action`
 - `reopened`
 - `resolved`
 - `unassigned`
 - `work-in-progress`
- **subject** - The subject line of the case.
- **submittedBy** - The email address of the account that submitted the case.
- **timeCreated** - The time the case was created, in ISO-8601 format.

Contents

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

categoryCode

The category of problem for the support case.

Type: String

ccEmailAddresses

The email addresses that receive copies of communication about the case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

displayId

The ID displayed for the case in the AWS Support Center. This is a numeric string.

Type: String

language

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

recentCommunications

The five most recent communications between you and AWS Support Center, including the IDs of any attachments to the communications. Also includes a `nextToken` that you can use to retrieve earlier communications.

Type: [RecentCaseCommunications](#) (p. 47) object

serviceCode

The code for the AWS service. You can get a list of codes and the corresponding service names by calling [DescribeServices](#) (p. 22).

Type: String

severityCode

The code for the severity level returned by the call to [DescribeSeverityLevels](#) (p. 24).

Type: String

status

The status of the case.

Valid values:

- `opened`
- `pending-customer-action`
- `reopened`
- `resolved`
- `unassigned`
- `work-in-progress`

Type: String

subject

The subject line for the case in the AWS Support Center.

Type: String

submittedBy

The email address of the account that submitted the case.

Type: String

timeCreated

The time that the case was created in the AWS Support Center.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Category

A JSON-formatted name/value pair that represents the category name and category code of the problem, selected from the [DescribeServices](#) (p. 22) response for each AWS service.

Contents

code

The category code for the support case.

Type: String

name

The category name for the support case.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Communication

A communication associated with a support case. The communication consists of the case ID, the message body, attachment information, the submitter of the communication, and the date and time of the communication.

Contents

attachmentSet

Information about the attachments to the case communication.

Type: Array of [AttachmentDetails](#) (p. 41) objects

body

The text of the communication between the customer and AWS Support.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

submittedBy

The identity of the account that submitted, or responded to, the support case. Customer entries include the role or IAM user as well as the email address. For example, "AdminRole (Role) <janedoe@example.com>". Entries from the AWS Support team display "Amazon Web Services," and don't show an email address.

Type: String

timeCreated

The time the communication was created.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecentCaseCommunications

The five most recent communications associated with the case.

Contents

communications

The five most recent communications associated with the case.

Type: Array of [Communication](#) (p. 46) objects

nextToken

A resumption point for pagination.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service

Information about an AWS service returned by the [DescribeServices](#) (p. 22) operation.

Contents

categories

A list of categories that describe the type of support issue a case describes. Categories consist of a category name and a category code. Category names and codes are passed to AWS Support when you call [CreateCase](#) (p. 9).

Type: Array of [Category](#) (p. 45) objects

code

The code for an AWS service returned by the [DescribeServices](#) (p. 22) response. The `name` element contains the corresponding friendly name.

Type: String

name

The friendly name for an AWS service. The `code` element contains the corresponding code.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SeverityLevel

A code and name pair that represents the severity level of a support case. The available values depend on the support plan for the account. For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

Contents

code

The code for case severity level.

Valid values: `low` | `normal` | `high` | `urgent` | `critical`

Type: String

name

The name of the severity level that corresponds to the severity level code.

Note

The values returned by the API are different from the values that appear in the AWS Support Center. For example, the API uses the code `low`, but the name appears as General guidance in Support Center.

The following are the API code names and how they appear in the console:

- `low` - General guidance
- `normal` - System impaired
- `high` - Production system impaired
- `urgent` - Production system down
- `critical` - Business-critical system down

For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCategorySpecificSummary

The container for summary information that relates to the category of the Trusted Advisor check.

Contents

costOptimizing

The summary information about cost savings for a Trusted Advisor check that is in the Cost Optimizing category.

Type: [TrustedAdvisorCostOptimizingSummary](#) (p. 55) object

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckDescription

The description and metadata for a Trusted Advisor check.

Contents

category

The category of the Trusted Advisor check.

Type: String

description

The description of the Trusted Advisor check, which includes the alert criteria and recommended operations (contains HTML markup).

Type: String

id

The unique identifier for the Trusted Advisor check.

Type: String

metadata

The column headings for the data returned by the Trusted Advisor check. The order of the headings corresponds to the order of the data in the **Metadata** element of the [TrustedAdvisorResourceDetail](#) (p. 56) for the check. **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

name

The display name for the Trusted Advisor check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckRefreshStatus

The refresh status of a Trusted Advisor check.

Contents

checkId

The unique identifier for the Trusted Advisor check.

Type: String

millisUntilNextRefreshable

The amount of time, in milliseconds, until the Trusted Advisor check is eligible for refresh.

Type: Long

status

The status of the Trusted Advisor check for which a refresh has been requested:

- `none` - The check is not refreshed or the non-success status exceeds the timeout
- `enqueued` - The check refresh requests has entered the refresh queue
- `processing` - The check refresh request is picked up by the rule processing engine
- `success` - The check is successfully refreshed
- `abandoned` - The check refresh has failed

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckResult

The results of a Trusted Advisor check returned by [DescribeTrustedAdvisorCheckResult](#) (p. 28).

Contents

categorySpecificSummary

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary](#) (p. 50) object

checkId

The unique identifier for the Trusted Advisor check.

Type: String

flaggedResources

The details about each resource listed in the check result.

Type: Array of [TrustedAdvisorResourceDetail](#) (p. 56) objects

resourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#) (p. 33).

Type: [TrustedAdvisorResourcesSummary](#) (p. 57) object

status

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not_available".

Type: String

timestamp

The time of the last refresh of the check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckSummary

A summary of a Trusted Advisor check result, including the alert status, last refresh, and number of resources examined.

Contents

categorySpecificSummary

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary](#) (p. 50) object

checkId

The unique identifier for the Trusted Advisor check.

Type: String

hasFlaggedResources

Specifies whether the Trusted Advisor check has flagged resources.

Type: Boolean

resourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#) (p. 33).

Type: [TrustedAdvisorResourcesSummary](#) (p. 57) object

status

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not_available".

Type: String

timestamp

The time of the last refresh of the check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCostOptimizingSummary

The estimated cost savings that might be realized if the recommended operations are taken.

Contents

estimatedMonthlySavings

The estimated monthly savings that might be realized if the recommended operations are taken.

Type: Double

estimatedPercentMonthlySavings

The estimated percentage of savings that might be realized if the recommended operations are taken.

Type: Double

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorResourceDetail

Contains information about a resource identified by a Trusted Advisor check.

Contents

isSuppressed

Specifies whether the AWS resource was ignored by Trusted Advisor because it was marked as suppressed by the user.

Type: Boolean

metadata

Additional information about the identified resource. The exact metadata and its order can be obtained by inspecting the [TrustedAdvisorCheckDescription](#) (p. 51) object returned by the call to [DescribeTrustedAdvisorChecks](#) (p. 31). **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

region

The AWS Region in which the identified resource is located.

Type: String

resourceId

The unique identifier for the identified resource.

Type: String

status

The status code for the resource identified in the Trusted Advisor check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorResourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#) (p. 33).

Contents

resourcesFlagged

The number of AWS resources that were flagged (listed) by the Trusted Advisor check.

Type: Long

resourcesIgnored

The number of AWS resources ignored by Trusted Advisor because information was unavailable.

Type: Long

resourcesProcessed

The number of AWS resources that were analyzed by the Trusted Advisor check.

Type: Long

resourcesSuppressed

The number of AWS resources ignored by Trusted Advisor because they were marked as suppressed by the user.

Type: Long

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400