
AWS Systems Manager

API Reference

API Version 2014-11-06



AWS Systems Manager: API Reference

Copyright © Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AddTagsToResource	6
Request Syntax	6
Request Parameters	6
Response Elements	7
Errors	7
Examples	8
See Also	9
AssociateOpsItemRelatedItem	10
Request Syntax	10
Request Parameters	10
Response Syntax	11
Response Elements	11
Errors	11
Examples	11
See Also	12
CancelCommand	13
Request Syntax	13
Request Parameters	13
Response Elements	13
Errors	13
Examples	14
See Also	14
CancelMaintenanceWindowExecution	16
Request Syntax	16
Request Parameters	16
Response Syntax	16
Response Elements	16
Errors	17
Examples	17
See Also	17
CreateActivation	19
Request Syntax	19
Request Parameters	19
Response Syntax	21
Response Elements	21
Errors	21
Examples	22
See Also	22
CreateAssociation	23
Request Syntax	23
Request Parameters	24
Response Syntax	28
Response Elements	29
Errors	29
Examples	30
See Also	31
CreateAssociationBatch	33
Request Syntax	33
Request Parameters	34
Response Syntax	34
Response Elements	36
Errors	36

Examples	37
See Also	39
CreateDocument	40
Request Syntax	40
Request Parameters	40
Response Syntax	43
Response Elements	44
Errors	44
Examples	45
See Also	46
CreateMaintenanceWindow	47
Request Syntax	47
Request Parameters	47
Response Syntax	49
Response Elements	50
Errors	50
Examples	50
See Also	51
CreateOpsItem	52
Request Syntax	52
Request Parameters	52
Response Syntax	55
Response Elements	55
Errors	56
Examples	56
See Also	57
CreateOpsMetadata	58
Request Syntax	58
Request Parameters	58
Response Syntax	59
Response Elements	59
Errors	59
See Also	60
CreatePatchBaseline	61
Request Syntax	61
Request Parameters	62
Response Syntax	64
Response Elements	64
Errors	64
Examples	65
See Also	66
CreateResourceDataSync	67
Request Syntax	67
Request Parameters	68
Response Elements	68
Errors	68
Examples	69
See Also	69
DeleteActivation	71
Request Syntax	71
Request Parameters	71
Response Elements	71
Errors	71
Examples	72
See Also	72
DeleteAssociation	73
Request Syntax	73

Request Parameters	73
Response Elements	74
Errors	74
Examples	74
See Also	75
DeleteDocument	76
Request Syntax	76
Request Parameters	76
Response Elements	77
Errors	77
Examples	77
See Also	78
DeleteInventory	79
Request Syntax	79
Request Parameters	79
Response Syntax	80
Response Elements	80
Errors	81
Examples	81
See Also	82
DeleteMaintenanceWindow	83
Request Syntax	83
Request Parameters	83
Response Syntax	83
Response Elements	83
Errors	83
Examples	84
See Also	84
DeleteOpsMetadata	85
Request Syntax	85
Request Parameters	85
Response Elements	85
Errors	85
See Also	86
DeleteParameter	87
Request Syntax	87
Request Parameters	87
Response Elements	87
Errors	87
Examples	87
See Also	88
DeleteParameters	89
Request Syntax	89
Request Parameters	89
Response Syntax	89
Response Elements	89
Errors	90
Examples	90
See Also	91
DeletePatchBaseline	92
Request Syntax	92
Request Parameters	92
Response Syntax	92
Response Elements	92
Errors	92
Examples	93
See Also	93

DeleteResourceDataSync	95
Request Syntax	95
Request Parameters	95
Response Elements	95
Errors	95
Examples	96
See Also	96
DeregisterManagedInstance	97
Request Syntax	97
Request Parameters	97
Response Elements	97
Errors	97
Examples	98
See Also	98
DeregisterPatchBaselineForPatchGroup	99
Request Syntax	99
Request Parameters	99
Response Syntax	99
Response Elements	99
Errors	100
Examples	100
See Also	101
DeregisterTargetFromMaintenanceWindow	102
Request Syntax	102
Request Parameters	102
Response Syntax	102
Response Elements	103
Errors	103
Examples	103
See Also	104
DeregisterTaskFromMaintenanceWindow	105
Request Syntax	105
Request Parameters	105
Response Syntax	105
Response Elements	105
Errors	106
Examples	106
See Also	107
DescribeActivations	108
Request Syntax	108
Request Parameters	108
Response Syntax	108
Response Elements	109
Errors	109
Examples	110
See Also	110
DescribeAssociation	111
Request Syntax	111
Request Parameters	111
Response Syntax	112
Response Elements	113
Errors	113
Examples	114
See Also	115
DescribeAssociationExecutions	116
Request Syntax	116
Request Parameters	116

Response Syntax	117
Response Elements	117
Errors	117
Examples	118
See Also	118
DescribeAssociationExecutionTargets	120
Request Syntax	120
Request Parameters	120
Response Syntax	121
Response Elements	121
Errors	122
Examples	122
See Also	123
DescribeAutomationExecutions	124
Request Syntax	124
Request Parameters	124
Response Syntax	124
Response Elements	126
Errors	126
Examples	127
See Also	127
DescribeAutomationStepExecutions	129
Request Syntax	129
Request Parameters	129
Response Syntax	130
Response Elements	131
Errors	131
Examples	131
See Also	132
DescribeAvailablePatches	134
Request Syntax	134
Request Parameters	134
Response Syntax	136
Response Elements	136
Errors	136
Examples	137
See Also	138
DescribeDocument	140
Request Syntax	140
Request Parameters	140
Response Syntax	140
Response Elements	141
Errors	142
Examples	142
See Also	143
DescribeDocumentPermission	144
Request Syntax	144
Request Parameters	144
Response Syntax	145
Response Elements	145
Errors	145
Examples	146
See Also	146
DescribeEffectiveInstanceAssociations	148
Request Syntax	148
Request Parameters	148
Response Syntax	148

Response Elements	149
Errors	149
Examples	149
See Also	150
DescribeEffectivePatchesForPatchBaseline	151
Request Syntax	151
Request Parameters	151
Response Syntax	151
Response Elements	152
Errors	152
Examples	153
See Also	155
DescribeInstanceAssociationsStatus	156
Request Syntax	156
Request Parameters	156
Response Syntax	156
Response Elements	157
Errors	157
Examples	158
See Also	158
DescribeInstanceInformation	160
Request Syntax	160
Request Parameters	160
Response Syntax	161
Response Elements	162
Errors	162
Examples	163
See Also	164
DescribeInstancePatches	165
Request Syntax	165
Request Parameters	165
Response Syntax	166
Response Elements	166
Errors	167
Examples	167
See Also	168
DescribeInstancePatchStates	169
Request Syntax	169
Request Parameters	169
Response Syntax	169
Response Elements	170
Errors	170
Examples	171
See Also	171
DescribeInstancePatchStatesForPatchGroup	173
Request Syntax	173
Request Parameters	173
Response Syntax	174
Response Elements	174
Errors	175
Examples	175
See Also	176
DescribeInventoryDeletions	177
Request Syntax	177
Request Parameters	177
Response Syntax	177
Response Elements	178

Errors	178
Examples	179
See Also	179
DescribeMaintenanceWindowExecutions	181
Request Syntax	181
Request Parameters	181
Response Syntax	182
Response Elements	182
Errors	182
Examples	183
See Also	183
DescribeMaintenanceWindowExecutionTaskInvocations	185
Request Syntax	185
Request Parameters	185
Response Syntax	186
Response Elements	186
Errors	187
Examples	187
See Also	188
DescribeMaintenanceWindowExecutionTasks	189
Request Syntax	189
Request Parameters	189
Response Syntax	190
Response Elements	190
Errors	190
Examples	191
See Also	191
DescribeMaintenanceWindows	193
Request Syntax	193
Request Parameters	193
Response Syntax	193
Response Elements	194
Errors	194
Examples	194
See Also	195
DescribeMaintenanceWindowSchedule	197
Request Syntax	197
Request Parameters	197
Response Syntax	198
Response Elements	198
Errors	199
Examples	199
See Also	200
DescribeMaintenanceWindowsForTarget	201
Request Syntax	201
Request Parameters	201
Response Syntax	202
Response Elements	202
Errors	202
Examples	202
See Also	203
DescribeMaintenanceWindowTargets	204
Request Syntax	204
Request Parameters	204
Response Syntax	205
Response Elements	205
Errors	205

Examples	206
See Also	207
DescribeMaintenanceWindowTasks	208
Request Syntax	208
Request Parameters	208
Response Syntax	209
Response Elements	209
Errors	210
Examples	210
See Also	211
DescribeOpsItems	213
Request Syntax	213
Request Parameters	213
Response Syntax	214
Response Elements	215
Errors	215
Examples	215
See Also	217
DescribeParameters	218
Request Syntax	218
Request Parameters	218
Response Syntax	219
Response Elements	219
Errors	220
Examples	220
See Also	222
DescribePatchBaselines	223
Request Syntax	223
Request Parameters	223
Response Syntax	224
Response Elements	224
Errors	224
Examples	224
See Also	226
DescribePatchGroups	227
Request Syntax	227
Request Parameters	227
Response Syntax	228
Response Elements	228
Errors	228
Examples	228
See Also	230
DescribePatchGroupState	231
Request Syntax	231
Request Parameters	231
Response Syntax	231
Response Elements	231
Errors	233
Examples	233
See Also	234
DescribePatchProperties	235
Request Syntax	235
Request Parameters	235
Response Syntax	236
Response Elements	237
Errors	237
Examples	237

See Also	238
DescribeSessions	239
Request Syntax	239
Request Parameters	239
Response Syntax	240
Response Elements	240
Errors	240
Examples	241
See Also	241
DisassociateOpsItemRelatedItem	243
Request Syntax	243
Request Parameters	243
Response Elements	243
Errors	243
Examples	244
See Also	244
GetAutomationExecution	246
Request Syntax	246
Request Parameters	246
Response Syntax	246
Response Elements	248
Errors	249
Examples	249
See Also	250
GetCalendarState	251
Request Syntax	251
Request Parameters	251
Response Syntax	251
Response Elements	252
Errors	252
Examples	252
See Also	253
GetCommandInvocation	254
Request Syntax	254
Request Parameters	254
Response Syntax	255
Response Elements	255
Errors	258
Examples	259
See Also	260
GetConnectionStatus	261
Request Syntax	261
Request Parameters	261
Response Syntax	261
Response Elements	261
Errors	262
Examples	262
See Also	262
GetDefaultPatchBaseline	264
Request Syntax	264
Request Parameters	264
Response Syntax	264
Response Elements	264
Errors	265
Examples	265
See Also	265
GetDeployablePatchSnapshotForInstance	267

Request Syntax	267
Request Parameters	268
Response Syntax	268
Response Elements	268
Errors	269
Examples	269
See Also	270
GetDocument	271
Request Syntax	271
Request Parameters	271
Response Syntax	272
Response Elements	272
Errors	274
Examples	274
See Also	275
GetInventory	276
Request Syntax	276
Request Parameters	276
Response Syntax	277
Response Elements	278
Errors	278
Examples	279
See Also	279
GetInventorySchema	281
Request Syntax	281
Request Parameters	281
Response Syntax	282
Response Elements	282
Errors	282
Examples	283
See Also	284
GetMaintenanceWindow	285
Request Syntax	285
Request Parameters	285
Response Syntax	285
Response Elements	285
Errors	287
Examples	288
See Also	288
GetMaintenanceWindowExecution	290
Request Syntax	290
Request Parameters	290
Response Syntax	290
Response Elements	290
Errors	291
Examples	292
See Also	292
GetMaintenanceWindowExecutionTask	293
Request Syntax	293
Request Parameters	293
Response Syntax	293
Response Elements	294
Errors	296
Examples	296
See Also	297
GetMaintenanceWindowExecutionTaskInvocation	299
Request Syntax	299

Request Parameters	299
Response Syntax	300
Response Elements	300
Errors	301
Examples	302
See Also	302
GetMaintenanceWindowTask	304
Request Syntax	304
Request Parameters	304
Response Syntax	304
Response Elements	306
Errors	308
Examples	309
See Also	310
GetOpsItem	311
Request Syntax	311
Request Parameters	311
Response Syntax	311
Response Elements	312
Errors	312
Examples	312
See Also	313
GetOpsMetadata	315
Request Syntax	315
Request Parameters	315
Response Syntax	315
Response Elements	316
Errors	316
See Also	317
GetOpsSummary	318
Request Syntax	318
Request Parameters	318
Response Syntax	319
Response Elements	320
Errors	320
Examples	321
See Also	322
GetParameter	323
Request Syntax	323
Request Parameters	323
Response Syntax	323
Response Elements	324
Errors	324
Examples	324
See Also	325
GetParameterHistory	326
Request Syntax	326
Request Parameters	326
Response Syntax	327
Response Elements	327
Errors	327
Examples	328
See Also	329
GetParameters	330
Request Syntax	330
Request Parameters	330
Response Syntax	330

Response Elements	331
Errors	331
Examples	331
See Also	332
GetParametersByPath	333
Request Syntax	333
Request Parameters	333
Response Syntax	334
Response Elements	334
Errors	335
Examples	335
See Also	336
GetPatchBaseline	338
Request Syntax	338
Request Parameters	338
Response Syntax	338
Response Elements	339
Errors	341
Examples	341
See Also	343
GetPatchBaselineForPatchGroup	344
Request Syntax	344
Request Parameters	344
Response Syntax	344
Response Elements	344
Errors	345
Examples	345
See Also	346
GetServiceSetting	347
Request Syntax	347
Request Parameters	347
Response Syntax	347
Response Elements	348
Errors	348
Examples	348
See Also	349
LabelParameterVersion	350
Request Syntax	350
Request Parameters	350
Response Syntax	351
Response Elements	351
Errors	351
Examples	352
See Also	352
ListAssociations	354
Request Syntax	354
Request Parameters	354
Response Syntax	355
Response Elements	355
Errors	355
Examples	356
See Also	357
ListAssociationVersions	358
Request Syntax	358
Request Parameters	358
Response Syntax	358
Response Elements	359

Errors	360
Examples	360
See Also	361
ListCommandInvocations	362
Request Syntax	362
Request Parameters	362
Response Syntax	363
Response Elements	364
Errors	364
Examples	365
See Also	366
ListCommands	367
Request Syntax	367
Request Parameters	367
Response Syntax	368
Response Elements	369
Errors	369
Examples	370
See Also	371
ListComplianceItems	372
Request Syntax	372
Request Parameters	372
Response Syntax	373
Response Elements	373
Errors	374
Examples	374
See Also	375
ListComplianceSummaries	376
Request Syntax	376
Request Parameters	376
Response Syntax	376
Response Elements	377
Errors	377
Examples	378
See Also	379
ListDocumentMetadataHistory	381
Request Syntax	381
Request Parameters	381
Response Syntax	382
Response Elements	382
Errors	383
Examples	383
See Also	384
ListDocuments	385
Request Syntax	385
Request Parameters	385
Response Syntax	386
Response Elements	386
Errors	387
Examples	387
See Also	388
ListDocumentVersions	389
Request Syntax	389
Request Parameters	389
Response Syntax	389
Response Elements	390
Errors	390

Examples	390
See Also	391
ListInventoryEntries	392
Request Syntax	392
Request Parameters	392
Response Syntax	393
Response Elements	393
Errors	394
Examples	395
See Also	396
ListOpsItemEvents	397
Request Syntax	397
Request Parameters	397
Response Syntax	397
Response Elements	398
Errors	398
See Also	399
ListOpsItemRelatedItems	400
Request Syntax	400
Request Parameters	400
Response Syntax	401
Response Elements	401
Errors	401
Examples	402
See Also	402
ListOpsMetadata	404
Request Syntax	404
Request Parameters	404
Response Syntax	404
Response Elements	405
Errors	405
See Also	405
ListResourceComplianceSummaries	407
Request Syntax	407
Request Parameters	407
Response Syntax	407
Response Elements	408
Errors	408
Examples	409
See Also	410
ListResourceDataSync	412
Request Syntax	412
Request Parameters	412
Response Syntax	413
Response Elements	413
Errors	414
Examples	414
See Also	415
ListTagsForResource	416
Request Syntax	416
Request Parameters	416
Response Syntax	416
Response Elements	416
Errors	417
Examples	417
See Also	418
ModifyDocumentPermission	419

Request Syntax	419
Request Parameters	419
Response Elements	420
Errors	420
Examples	421
See Also	421
PutComplianceItems	422
Request Syntax	422
Request Parameters	423
Response Elements	424
Errors	424
Examples	425
See Also	426
PutInventory	427
Request Syntax	427
Request Parameters	427
Response Syntax	427
Response Elements	428
Errors	428
Examples	429
See Also	430
PutParameter	431
Request Syntax	431
Request Parameters	431
Response Syntax	435
Response Elements	435
Errors	436
Examples	437
See Also	438
RegisterDefaultPatchBaseline	439
Request Syntax	439
Request Parameters	439
Response Syntax	439
Response Elements	439
Errors	440
Examples	440
See Also	441
RegisterPatchBaselineForPatchGroup	442
Request Syntax	442
Request Parameters	442
Response Syntax	442
Response Elements	442
Errors	443
Examples	444
See Also	444
RegisterTargetWithMaintenanceWindow	445
Request Syntax	445
Request Parameters	445
Response Syntax	447
Response Elements	447
Errors	447
Examples	448
See Also	448
RegisterTaskWithMaintenanceWindow	450
Request Syntax	450
Request Parameters	451
Response Syntax	454

Response Elements	454
Errors	455
Examples	455
See Also	456
RemoveTagsFromResource	458
Request Syntax	458
Request Parameters	458
Response Elements	459
Errors	459
Examples	459
See Also	460
ResetServiceSetting	461
Request Syntax	461
Request Parameters	461
Response Syntax	461
Response Elements	462
Errors	462
Examples	462
See Also	463
ResumeSession	464
Request Syntax	464
Request Parameters	464
Response Syntax	464
Response Elements	464
Errors	465
Examples	465
See Also	466
SendAutomationSignal	467
Request Syntax	467
Request Parameters	467
Response Elements	468
Errors	468
Examples	468
See Also	469
SendCommand	470
Request Syntax	470
Request Parameters	470
Response Syntax	474
Response Elements	474
Errors	475
Examples	476
See Also	477
StartAssociationsOnce	479
Request Syntax	479
Request Parameters	479
Response Elements	479
Errors	479
Examples	479
See Also	480
StartAutomationExecution	481
Request Syntax	481
Request Parameters	481
Response Syntax	484
Response Elements	484
Errors	484
Examples	485
See Also	486

StartChangeRequestExecution	487
Request Syntax	487
Request Parameters	488
Response Syntax	490
Response Elements	490
Errors	490
Examples	491
See Also	492
StartSession	493
Request Syntax	493
Request Parameters	493
Response Syntax	494
Response Elements	494
Errors	495
Examples	495
See Also	496
StopAutomationExecution	497
Request Syntax	497
Request Parameters	497
Response Elements	497
Errors	497
Examples	498
See Also	498
TerminateSession	499
Request Syntax	499
Request Parameters	499
Response Syntax	499
Response Elements	499
Errors	499
Examples	500
See Also	500
UnlabelParameterVersion	501
Request Syntax	501
Request Parameters	501
Response Syntax	501
Response Elements	502
Errors	502
Examples	502
See Also	503
UpdateAssociation	504
Request Syntax	504
Request Parameters	505
Response Syntax	509
Response Elements	510
Errors	510
Examples	512
See Also	513
UpdateAssociationStatus	514
Request Syntax	514
Request Parameters	514
Response Syntax	515
Response Elements	516
Errors	516
See Also	517
UpdateDocument	518
Request Syntax	518
Request Parameters	518

Response Syntax	520
Response Elements	521
Errors	521
Examples	522
See Also	523
UpdateDocumentDefaultVersion	524
Request Syntax	524
Request Parameters	524
Response Syntax	524
Response Elements	524
Errors	525
Examples	525
See Also	526
UpdateDocumentMetadata	527
Request Syntax	527
Request Parameters	527
Response Elements	527
Errors	528
Examples	528
See Also	529
UpdateMaintenanceWindow	530
Request Syntax	530
Request Parameters	530
Response Syntax	532
Response Elements	533
Errors	534
Examples	535
See Also	535
UpdateMaintenanceWindowTarget	536
Request Syntax	536
Request Parameters	536
Response Syntax	537
Response Elements	538
Errors	539
Examples	539
See Also	540
UpdateMaintenanceWindowTask	541
Request Syntax	541
Request Parameters	542
Response Syntax	546
Response Elements	547
Errors	549
Examples	550
See Also	551
UpdateManagedInstanceRole	552
Request Syntax	552
Request Parameters	552
Response Elements	552
Errors	552
Examples	553
See Also	553
UpdateOpsItem	555
Request Syntax	555
Request Parameters	555
Response Elements	558
Errors	558
Examples	559

See Also	559
UpdateOpsMetadata	561
Request Syntax	561
Request Parameters	561
Response Syntax	562
Response Elements	562
Errors	562
See Also	563
UpdatePatchBaseline	564
Request Syntax	564
Request Parameters	564
Response Syntax	567
Response Elements	567
Errors	569
Examples	570
See Also	571
UpdateResourceDataSync	572
Request Syntax	572
Request Parameters	572
Response Elements	573
Errors	573
Examples	573
See Also	574
UpdateServiceSetting	575
Request Syntax	575
Request Parameters	575
Response Elements	576
Errors	576
Examples	576
See Also	577
Data Types	578
AccountSharingInfo	582
Contents	582
See Also	582
Activation	583
Contents	583
See Also	584
Association	585
Contents	585
See Also	587
AssociationDescription	588
Contents	588
See Also	592
AssociationExecution	593
Contents	593
See Also	594
AssociationExecutionFilter	595
Contents	595
See Also	595
AssociationExecutionTarget	596
Contents	596
See Also	597
AssociationExecutionTargetsFilter	598
Contents	598
See Also	598
AssociationFilter	599
Contents	599

See Also	599
AssociationOverview	600
Contents	600
See Also	600
AssociationStatus	601
Contents	601
See Also	601
AssociationVersionInfo	602
Contents	602
See Also	605
AttachmentContent	606
Contents	606
See Also	606
AttachmentInformation	608
Contents	608
See Also	608
AttachmentsSource	609
Contents	609
See Also	609
AutomationExecution	611
Contents	611
See Also	615
AutomationExecutionFilter	617
Contents	617
See Also	617
AutomationExecutionMetadata	618
Contents	618
See Also	622
BaselineOverride	623
Contents	623
See Also	624
CloudWatchOutputConfig	625
Contents	625
See Also	625
Command	626
Contents	626
See Also	630
CommandFilter	631
Contents	631
See Also	632
CommandInvocation	633
Contents	633
See Also	636
CommandPlugin	637
Contents	637
See Also	639
ComplianceExecutionSummary	640
Contents	640
See Also	640
ComplianceItem	641
Contents	641
See Also	642
ComplianceItemEntry	643
Contents	643
See Also	643
ComplianceStringFilter	645
Contents	645

See Also	645
ComplianceSummaryItem	646
Contents	646
See Also	646
CompliantSummary	647
Contents	647
See Also	647
CreateAssociationBatchRequestEntry	648
Contents	648
See Also	651
DescribeActivationsFilter	653
Contents	653
See Also	653
DocumentDefaultVersionDescription	654
Contents	654
See Also	654
DocumentDescription	655
Contents	655
See Also	659
DocumentFilter	660
Contents	660
See Also	660
DocumentIdentifier	661
Contents	661
See Also	663
DocumentKeyValuesFilter	664
Contents	665
See Also	665
DocumentMetadataResponseInfo	666
Contents	666
See Also	666
DocumentParameter	667
Contents	667
See Also	667
DocumentRequires	668
Contents	668
See Also	668
DocumentReviewCommentSource	669
Contents	669
See Also	669
DocumentReviewerResponseSource	670
Contents	670
See Also	670
DocumentReviews	672
Contents	672
See Also	672
DocumentVersionInfo	673
Contents	673
See Also	674
EffectivePatch	675
Contents	675
See Also	675
FailedCreateAssociation	676
Contents	676
See Also	676
FailureDetails	677
Contents	677

See Also	677
InstanceAggregatedAssociationOverview	678
Contents	678
See Also	678
InstanceAssociation	679
Contents	679
See Also	679
InstanceAssociationOutputLocation	680
Contents	680
See Also	680
InstanceAssociationOutputUrl	681
Contents	681
See Also	681
InstanceAssociationStatusInfo	682
Contents	682
See Also	683
InstanceInformation	685
Contents	685
See Also	688
InstanceInformationFilter	689
Contents	689
See Also	689
InstanceInformationStringFilter	690
Contents	690
See Also	690
InstancePatchState	691
Contents	691
See Also	694
InstancePatchStateFilter	696
Contents	696
See Also	696
InventoryAggregator	698
Contents	698
See Also	698
InventoryDeletionStatusItem	699
Contents	699
See Also	700
InventoryDeletionSummary	701
Contents	701
See Also	701
InventoryDeletionSummaryItem	702
Contents	702
See Also	702
InventoryFilter	703
Contents	703
See Also	703
InventoryGroup	704
Contents	704
See Also	704
InventoryItem	705
Contents	705
See Also	706
InventoryItemAttribute	707
Contents	707
See Also	707
InventoryItemSchema	708
Contents	708

See Also	708
InventoryResultEntity	709
Contents	709
See Also	709
InventoryResultItem	710
Contents	710
See Also	711
LoggingInfo	712
Contents	712
See Also	712
MaintenanceWindowAutomationParameters	713
Contents	713
See Also	713
MaintenanceWindowExecution	715
Contents	715
See Also	716
MaintenanceWindowExecutionTaskIdentity	717
Contents	717
See Also	718
MaintenanceWindowExecutionTaskInvocationIdentity	719
Contents	719
See Also	721
MaintenanceWindowFilter	722
Contents	722
See Also	722
MaintenanceWindowIdentity	723
Contents	723
See Also	724
MaintenanceWindowIdentityForTarget	726
Contents	726
See Also	726
MaintenanceWindowLambdaParameters	727
Contents	727
See Also	727
MaintenanceWindowRunCommandParameters	729
Contents	729
See Also	731
MaintenanceWindowStepFunctionsParameters	732
Contents	732
See Also	732
MaintenanceWindowTarget	733
Contents	733
See Also	734
MaintenanceWindowTask	735
Contents	735
See Also	738
MaintenanceWindowTaskInvocationParameters	739
Contents	739
See Also	739
MaintenanceWindowTaskParameterValueExpression	740
Contents	740
See Also	740
MetadataValue	741
Contents	741
See Also	741
NonCompliantSummary	742
Contents	742

See Also	742
NotificationConfig	743
Contents	743
See Also	743
OpsAggregator	744
Contents	744
See Also	745
OpsEntity	746
Contents	746
See Also	746
OpsEntityItem	747
Contents	747
See Also	747
OpsFilter	748
Contents	748
See Also	748
OpsItem	749
Contents	749
See Also	752
OpsItemAttributeValue	753
Contents	753
See Also	753
OpsItemEventFilter	754
Contents	754
See Also	754
OpsItemEventSummary	755
Contents	755
See Also	756
OpsItemFilter	757
Contents	757
See Also	757
OpsItemIdentity	758
Contents	758
See Also	758
OpsItemNotification	759
Contents	759
See Also	759
OpsItemRelatedItemsFilter	760
Contents	760
See Also	760
OpsItemRelatedItemSummary	761
Contents	761
See Also	762
OpsItemSummary	763
Contents	763
See Also	765
OpsMetadata	766
Contents	766
See Also	766
OpsMetadataFilter	768
Contents	768
See Also	768
OpsResultAttribute	769
Contents	769
See Also	769
OutputSource	770
Contents	770

See Also	770
Parameter	771
Contents	771
See Also	772
ParameterHistory	773
Contents	773
See Also	775
ParameterInlinePolicy	776
Contents	776
See Also	776
ParameterMetadata	777
Contents	777
See Also	778
ParametersFilter	779
Contents	779
See Also	779
ParameterStringFilter	780
Contents	780
See Also	780
Patch	782
Contents	782
See Also	785
PatchBaselineIdentity	786
Contents	786
See Also	787
PatchComplianceData	788
Contents	788
See Also	789
PatchFilter	790
Contents	790
See Also	790
PatchFilterGroup	792
Contents	792
See Also	792
PatchGroupPatchBaselineMapping	793
Contents	793
See Also	793
PatchOrchestratorFilter	794
Contents	794
See Also	794
PatchRule	795
Contents	795
See Also	795
PatchRuleGroup	797
Contents	797
See Also	797
PatchSource	798
Contents	798
See Also	798
PatchStatus	800
Contents	800
See Also	800
ProgressCounters	801
Contents	801
See Also	801
RegistrationMetadataItem	803
Contents	803

See Also	803
RelatedOpsItem	804
Contents	804
See Also	804
ResolvedTargets	805
Contents	805
See Also	805
ResourceComplianceSummaryItem	806
Contents	806
See Also	807
ResourceDataSyncAwsOrganizationsSource	808
Contents	808
See Also	808
ResourceDataSyncDestinationDataSharing	809
Contents	809
See Also	809
ResourceDataSyncItem	810
Contents	810
See Also	811
ResourceDataSyncOrganizationalUnit	812
Contents	812
See Also	812
ResourceDataSyncS3Destination	813
Contents	813
See Also	814
ResourceDataSyncSource	815
Contents	815
See Also	815
ResourceDataSyncSourceWithState	817
Contents	817
See Also	818
ResultAttribute	819
Contents	819
See Also	819
ReviewInformation	820
Contents	820
See Also	820
Runbook	821
Contents	821
See Also	822
S3OutputLocation	824
Contents	824
See Also	824
S3OutputUrl	825
Contents	825
See Also	825
ScheduledWindowExecution	826
Contents	826
See Also	826
ServiceSetting	827
Contents	827
See Also	828
Session	829
Contents	829
See Also	830
SessionFilter	831
Contents	831

See Also	831
SessionManagerOutputUrl	832
Contents	832
See Also	832
SeveritySummary	833
Contents	833
See Also	833
StepExecution	835
Contents	835
See Also	838
StepExecutionFilter	839
Contents	839
See Also	839
Tag	840
Contents	840
See Also	840
Target	841
Contents	841
See Also	842
TargetLocation	843
Contents	843
See Also	844
Common Parameters	845
Common Errors	847

Welcome

AWS Systems Manager is a collection of capabilities to help you manage your applications and infrastructure running in the AWS Cloud. Systems Manager simplifies application and resource management, shortens the time to detect and resolve operational problems, and helps you manage your AWS resources securely at scale.

This reference is intended to be used with the [AWS Systems Manager User Guide](#).

To get started, verify prerequisites. For more information, see [Setting up AWS Systems Manager](#).

Related resources

- For information about how to use a Query API, see [Making API requests](#).
- For information about other API operations you can perform on EC2 instances, see the [Amazon EC2 API Reference](#).
- For information about AWS AppConfig, a capability of Systems Manager, see the [AWS AppConfig User Guide](#) and the [AWS AppConfig API Reference](#).
- For information about Incident Manager, a capability of Systems Manager, see the [Incident Manager User Guide](#) and the [Incident Manager API Reference](#).

This document was last published on June 6, 2022.

Actions

The following actions are supported:

- [AddTagsToResource \(p. 6\)](#)
- [AssociateOpsItemRelatedItem \(p. 10\)](#)
- [CancelCommand \(p. 13\)](#)
- [CancelMaintenanceWindowExecution \(p. 16\)](#)
- [CreateActivation \(p. 19\)](#)
- [CreateAssociation \(p. 23\)](#)
- [CreateAssociationBatch \(p. 33\)](#)
- [CreateDocument \(p. 40\)](#)
- [CreateMaintenanceWindow \(p. 47\)](#)
- [CreateOpsItem \(p. 52\)](#)
- [CreateOpsMetadata \(p. 58\)](#)
- [CreatePatchBaseline \(p. 61\)](#)
- [CreateResourceDataSync \(p. 67\)](#)
- [DeleteActivation \(p. 71\)](#)
- [DeleteAssociation \(p. 73\)](#)
- [DeleteDocument \(p. 76\)](#)
- [DeleteInventory \(p. 79\)](#)
- [DeleteMaintenanceWindow \(p. 83\)](#)
- [DeleteOpsMetadata \(p. 85\)](#)
- [DeleteParameter \(p. 87\)](#)
- [DeleteParameters \(p. 89\)](#)
- [DeletePatchBaseline \(p. 92\)](#)
- [DeleteResourceDataSync \(p. 95\)](#)
- [DeregisterManagedInstance \(p. 97\)](#)
- [DeregisterPatchBaselineForPatchGroup \(p. 99\)](#)
- [DeregisterTargetFromMaintenanceWindow \(p. 102\)](#)
- [DeregisterTaskFromMaintenanceWindow \(p. 105\)](#)
- [DescribeActivations \(p. 108\)](#)
- [DescribeAssociation \(p. 111\)](#)
- [DescribeAssociationExecutions \(p. 116\)](#)
- [DescribeAssociationExecutionTargets \(p. 120\)](#)
- [DescribeAutomationExecutions \(p. 124\)](#)
- [DescribeAutomationStepExecutions \(p. 129\)](#)
- [DescribeAvailablePatches \(p. 134\)](#)
- [DescribeDocument \(p. 140\)](#)
- [DescribeDocumentPermission \(p. 144\)](#)
- [DescribeEffectiveInstanceIdAssociations \(p. 148\)](#)
- [DescribeEffectivePatchesForPatchBaseline \(p. 151\)](#)
- [DescribeInstanceIdAssociationsStatus \(p. 156\)](#)
- [DescribeInstanceIdInformation \(p. 160\)](#)

- [DescribeInstancePatches \(p. 165\)](#)
- [DescribeInstancePatchStates \(p. 169\)](#)
- [DescribeInstancePatchStatesForPatchGroup \(p. 173\)](#)
- [DescribeInventoryDeletions \(p. 177\)](#)
- [DescribeMaintenanceWindowExecutions \(p. 181\)](#)
- [DescribeMaintenanceWindowExecutionTaskInvocations \(p. 185\)](#)
- [DescribeMaintenanceWindowExecutionTasks \(p. 189\)](#)
- [DescribeMaintenanceWindows \(p. 193\)](#)
- [DescribeMaintenanceWindowSchedule \(p. 197\)](#)
- [DescribeMaintenanceWindowsForTarget \(p. 201\)](#)
- [DescribeMaintenanceWindowTargets \(p. 204\)](#)
- [DescribeMaintenanceWindowTasks \(p. 208\)](#)
- [DescribeOpsItems \(p. 213\)](#)
- [DescribeParameters \(p. 218\)](#)
- [DescribePatchBaselines \(p. 223\)](#)
- [DescribePatchGroups \(p. 227\)](#)
- [DescribePatchGroupState \(p. 231\)](#)
- [DescribePatchProperties \(p. 235\)](#)
- [DescribeSessions \(p. 239\)](#)
- [DisassociateOpsItemRelatedItem \(p. 243\)](#)
- [GetAutomationExecution \(p. 246\)](#)
- [GetCalendarState \(p. 251\)](#)
- [GetCommandInvocation \(p. 254\)](#)
- [GetConnectionStatus \(p. 261\)](#)
- [GetDefaultPatchBaseline \(p. 264\)](#)
- [GetDeployablePatchSnapshotForInstance \(p. 267\)](#)
- [GetDocument \(p. 271\)](#)
- [GetInventory \(p. 276\)](#)
- [GetInventorySchema \(p. 281\)](#)
- [GetMaintenanceWindow \(p. 285\)](#)
- [GetMaintenanceWindowExecution \(p. 290\)](#)
- [GetMaintenanceWindowExecutionTask \(p. 293\)](#)
- [GetMaintenanceWindowExecutionTaskInvocation \(p. 299\)](#)
- [GetMaintenanceWindowTask \(p. 304\)](#)
- [GetOpsItem \(p. 311\)](#)
- [GetOpsMetadata \(p. 315\)](#)
- [GetOpsSummary \(p. 318\)](#)
- [GetParameter \(p. 323\)](#)
- [GetParameterHistory \(p. 326\)](#)
- [GetParameters \(p. 330\)](#)
- [GetParametersByPath \(p. 333\)](#)
- [GetPatchBaseline \(p. 338\)](#)
- [GetPatchBaselineForPatchGroup \(p. 344\)](#)
- [GetServiceSetting \(p. 347\)](#)
- [LabelParameterVersion \(p. 350\)](#)
- [ListAssociations \(p. 354\)](#)

- [ListAssociationVersions \(p. 358\)](#)
- [ListCommandInvocations \(p. 362\)](#)
- [ListCommands \(p. 367\)](#)
- [ListComplianceItems \(p. 372\)](#)
- [ListComplianceSummaries \(p. 376\)](#)
- [ListDocumentMetadataHistory \(p. 381\)](#)
- [ListDocuments \(p. 385\)](#)
- [ListDocumentVersions \(p. 389\)](#)
- [ListInventoryEntries \(p. 392\)](#)
- [ListOpsItemEvents \(p. 397\)](#)
- [ListOpsItemRelatedItems \(p. 400\)](#)
- [ListOpsMetadata \(p. 404\)](#)
- [ListResourceComplianceSummaries \(p. 407\)](#)
- [ListResourceDataSync \(p. 412\)](#)
- [ListTagsForResource \(p. 416\)](#)
- [ModifyDocumentPermission \(p. 419\)](#)
- [PutComplianceItems \(p. 422\)](#)
- [PutInventory \(p. 427\)](#)
- [PutParameter \(p. 431\)](#)
- [RegisterDefaultPatchBaseline \(p. 439\)](#)
- [RegisterPatchBaselineForPatchGroup \(p. 442\)](#)
- [RegisterTargetWithMaintenanceWindow \(p. 445\)](#)
- [RegisterTaskWithMaintenanceWindow \(p. 450\)](#)
- [RemoveTagsFromResource \(p. 458\)](#)
- [ResetServiceSetting \(p. 461\)](#)
- [ResumeSession \(p. 464\)](#)
- [SendAutomationSignal \(p. 467\)](#)
- [SendCommand \(p. 470\)](#)
- [StartAssociationsOnce \(p. 479\)](#)
- [StartAutomationExecution \(p. 481\)](#)
- [StartChangeRequestExecution \(p. 487\)](#)
- [StartSession \(p. 493\)](#)
- [StopAutomationExecution \(p. 497\)](#)
- [TerminateSession \(p. 499\)](#)
- [UnlabelParameterVersion \(p. 501\)](#)
- [UpdateAssociation \(p. 504\)](#)
- [UpdateAssociationStatus \(p. 514\)](#)
- [UpdateDocument \(p. 518\)](#)
- [UpdateDocumentDefaultVersion \(p. 524\)](#)
- [UpdateDocumentMetadata \(p. 527\)](#)
- [UpdateMaintenanceWindow \(p. 530\)](#)
- [UpdateMaintenanceWindowTarget \(p. 536\)](#)
- [UpdateMaintenanceWindowTask \(p. 541\)](#)
- [UpdateManagedInstanceRole \(p. 552\)](#)
- [UpdateOpsItem \(p. 555\)](#)
- [UpdateOpsMetadata \(p. 561\)](#)

- [UpdatePatchBaseline \(p. 564\)](#)
- [UpdateResourceDataSync \(p. 572\)](#)
- [UpdateServiceSetting \(p. 575\)](#)

AddTagsToResource

Adds or overwrites one or more tags for the specified resource. Tags are metadata that you can assign to your automations, documents, managed nodes, maintenance windows, Parameter Store parameters, and patch baselines. Tags enable you to categorize your resources in different ways, for example, by purpose, owner, or environment. Each tag consists of a key and an optional value, both of which you define. For example, you could define a set of tags for your account's managed nodes that helps you track each node's owner and stack level. For example:

- Key=Owner,Value=DbAdmin
- Key=Owner,Value=SysAdmin
- Key=Owner,Value=Dev
- Key=Stack,Value=Production
- Key=Stack,Value=Pre-Production
- Key=Stack,Value=Test

Most resources can have a maximum of 50 tags. Automations can have a maximum of 5 tags.

We recommend that you devise a set of tag keys that meets your needs for each resource type. Using a consistent set of tag keys makes it easier for you to manage your resources. You can search and filter the resources based on the tags you add. Tags don't have any semantic meaning to and are interpreted strictly as a string of characters.

For more information about using tags with Amazon Elastic Compute Cloud (Amazon EC2) instances, see [Tagging your Amazon EC2 resources](#) in the *Amazon EC2 User Guide*.

Request Syntax

```
{  
    "ResourceId": "string",  
    "ResourceType": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ResourceId (p. 6)

The resource ID you want to tag.

Use the ID of the resource. Here are some examples:

MaintenanceWindow: mw-012345abcde

PatchBaseline: pb-012345abcde

Automation: example-c160-4567-8519-012345abcde

OpsMetadata object: ResourceID for tagging is created from the Amazon Resource Name (ARN) for the object. Specifically, ResourceID is created from the strings that come after the word opsmetadata in the ARN. For example, an OpsMetadata object with an ARN of arn:aws:ssm:us-east-2:1234567890:opsmetadata/aws/ssm/MyGroup/appmanager has a ResourceID of either aws:ssm/MyGroup/appmanager or /aws:ssm/MyGroup/appmanager.

For the Document and Parameter values, use the name of the resource.

ManagedInstance: mi-012345abcde

Note

The ManagedInstance type for this API operation is only for on-premises managed nodes. You must specify the name of the managed node in the following format: mi-ID_number . For example, mi-1a2b3c4d5e6f.

Type: String

Required: Yes

ResourceType (p. 6)

Specifies the type of resource you are tagging.

Note

The ManagedInstance type for this API operation is for on-premises managed nodes. You must specify the name of the managed node in the following format: mi-ID_number . For example, mi-1a2b3c4d5e6f.

Type: String

Valid Values: Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation

Required: Yes

Tags (p. 6)

One or more tags. The value parameter is required.

Important

Don't enter personally identifiable information in this field.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

TooManyTagsError

The Targets parameter includes too many tags. Remove one or more tags and try the command again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of AddTagsToResource.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.AddTagsToResource
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200220T232503Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 122

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE",
    "Tags": [
        {
            "Key": "Stack",
            "Value": "Production"
        }
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateOpsItemRelatedItem

Associates a related item to a Systems Manager OpsCenter OpsItem. For example, you can associate an Incident Manager incident or analysis with an OpsItem. Incident Manager and OpsCenter are capabilities of AWS Systems Manager.

Request Syntax

```
{  
    "AssociationType": "string",  
    "OpsItemId": "string",  
    "ResourceType": "string",  
    "ResourceUri": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationType (p. 10)

The type of association that you want to create between an OpsItem and a resource. OpsCenter supports IsParentOf and RelatesTo association types.

Type: String

Required: Yes

OpsItemId (p. 10)

The ID of the OpsItem to which you want to associate a resource as a related item.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: Yes

ResourceType (p. 10)

The type of resource that you want to associate with an OpsItem. OpsCenter supports the following types:

`AWS::SSMIncidents::IncidentRecord`: an Incident Manager incident.

`AWS::SSM::Document`: a Systems Manager (SSM) document.

Type: String

Required: Yes

ResourceUri (p. 10)

The Amazon Resource Name (ARN) of the AWS resource that you want to associate with the OpsItem.

Type: String

Required: Yes

Response Syntax

```
{  
    "AssociationId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationId (p. 11)

The association ID.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas. For information about OpsItem quotas, see [What are the resource limits for OpsCenter?](#).

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

OpsItemRelatedItemAlreadyExistsException

The Amazon Resource Name (ARN) is already associated with the OpsItem.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of AssociateOpsItemRelatedItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.AssociateOpsItemRelatedItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/
x86_64.amzn.2 prompt/off command/ssm.associate-ops-item-related-item
X-Amz-Date: 20210804T181929Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210804/us-east-1/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 229

{
    "OpsItemId": "oi-649fExample",
    "AssociationType": "RelatesTo",
    "ResourceType": "AWS::SSMIncidents::IncidentRecord",
    "ResourceUri": "arn:aws:ssm-incidents::111122223333:incident-record/Test/c6bd8931-efae-
a4ff-7f98-4490Example"
}
```

Sample Response

```
{
    "AssociationId": "61d7178d-a30d-4bc5-9b4e-a9e74EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelCommand

Attempts to cancel the command specified by the Command ID. There is no guarantee that the command will be terminated and the underlying process stopped.

Request Syntax

```
{  
    "CommandId": "string",  
    "InstanceIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

CommandId (p. 13)

The ID of the command you want to cancel.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

InstanceIds (p. 13)

(Optional) A list of managed node IDs on which you want to cancel the command. If not provided, the command is canceled on every node on which it was requested.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CancelCommand.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CancelCommand
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200220T233525Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53

{
    "CommandId": "25173b39-c88d-4459-ba3d-8704aEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelMaintenanceWindowExecution

Stops a maintenance window execution that is already in progress and cancels any tasks in the window that haven't already started running. Tasks already in progress will continue to completion.

Request Syntax

```
{  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[WindowExecutionId \(p. 16\)](#)

The ID of the maintenance window execution to stop.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "WindowExecutionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WindowExecutionId \(p. 16\)](#)

The ID of the maintenance window execution that has been stopped.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of CancelMaintenanceWindowExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CancelMaintenanceWindowExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T010054Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 61

{
    "WindowExecutionId": "02f05632-d0bc-470d-b1e5-c59a8EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "02f05632-d0bc-470d-b1e5-c59a8EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateActivation

Generates an activation code and activation ID you can use to register your on-premises servers, edge devices, or virtual machine (VM) with AWS Systems Manager. Registering these machines with Systems Manager makes it possible to manage them using Systems Manager capabilities. You use the activation code and ID when installing SSM Agent on machines in your hybrid environment. For more information about requirements for managing on-premises machines using Systems Manager, see [Setting up AWS Systems Manager for hybrid environments](#) in the *AWS Systems Manager User Guide*.

Note

Amazon Elastic Compute Cloud (Amazon EC2) instances, edge devices, and on-premises servers and VMs that are configured for Systems Manager are all called *managed nodes*.

Request Syntax

```
{  
    "DefaultInstanceName": "string",  
    "Description": "string",  
    "ExpirationDate": number,  
    "IamRole": "string",  
    "RegistrationLimit": number,  
    "RegistrationMetadata": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DefaultInstanceName \(p. 19\)](#)

The name of the registered, managed node as it will appear in the AWS Systems Manager console or when you use the AWS command line tools to list Systems Manager resources.

Important

Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}]\p{N}_.:+=\-\@]*\$

Required: No

[Description \(p. 19\)](#)

A user-defined description of the resource that you want to register with Systems Manager.

Important

Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

[ExpirationDate \(p. 19\)](#)

The date by which this activation request should expire, in timestamp format, such as "2021-07-07T00:00:00". You can specify a date up to 30 days in advance. If you don't provide an expiration date, the activation code expires in 24 hours.

Type: Timestamp

Required: No

[IamRole \(p. 19\)](#)

The name of the AWS Identity and Access Management (IAM) role that you want to assign to the managed node. This IAM role must provide AssumeRole permissions for the AWS Systems Manager service principal `ssm.amazonaws.com`. For more information, see [Create an IAM service role for a hybrid environment](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Maximum length of 64.

Required: Yes

[RegistrationLimit \(p. 19\)](#)

Specify the maximum number of managed nodes you want to register. The default value is 1.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[RegistrationMetadata \(p. 19\)](#)

Reserved for internal use.

Type: Array of [RegistrationMetadataItem \(p. 803\)](#) objects

Required: No

[Tags \(p. 19\)](#)

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an activation to identify which servers or virtual machines (VMs) in your on-premises environment you intend to activate. In this case, you could specify the following key-value pairs:

- Key=OS, Value=Windows
- Key=Environment, Value=Production

Important

When you install SSM Agent on your on-premises servers and VMs, you specify an activation ID and code. When you specify the activation ID and code, tags assigned to the activation are automatically applied to the on-premises servers or VMs.

You can't add tags to or delete tags from an existing activation. You can tag your on-premises servers, edge devices, and VMs after they connect to Systems Manager for the first time and are assigned a managed node ID. This means they are listed in the AWS Systems Manager console with an ID that is prefixed with "mi-". For information about how to add tags to your managed nodes, see [AddTagsToResource \(p. 6\)](#). For information about how to remove tags from your managed nodes, see [RemoveTagsFromResource \(p. 458\)](#).

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{  
    "ActivationCode": "string",  
    "ActivationId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ActivationCode \(p. 21\)](#)

The code the system generates when it processes the activation. The activation code functions like a password to validate the activation ID.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 250.

[ActivationId \(p. 21\)](#)

The ID number generated by the system when it processed the activation. The activation ID functions like a user name.

Type: String

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateActivation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateActivation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T135329Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 70

{
    "IamRole": "service-role/role_name"
}
```

Sample Response

```
{
    "ActivationCode": "Fjz3/sZfSvv78EXAMPLE",
    "ActivationId": "e488f2f6-e686-4afb-8a04-ef6dfEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssociation

A State Manager association defines the state that you want to maintain on your managed nodes. For example, an association can specify that anti-virus software must be installed and running on your managed nodes, or that certain ports must be closed. For static targets, the association specifies a schedule for when the configuration is reapplied. For dynamic targets, such as an AWS resource group or an AWS autoscaling group, State Manager, a capability of AWS Systems Manager applies the configuration when new managed nodes are added to the group. The association also specifies actions to take when applying the configuration. For example, an association for anti-virus software might run once a day. If the software isn't installed, then State Manager installs it. If the software is installed, but the service isn't running, then the association might instruct State Manager to start the service.

Request Syntax

```
{  
    "ApplyOnlyAtCronInterval": boolean,  
    "AssociationName": "string",  
    "AutomationTargetParameterName": "string",  
    "CalendarNames": [ "string" ],  
    "ComplianceSeverity": "string",  
    "DocumentVersion": "string",  
    "InstanceId": "string",  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Name": "string",  
    "OutputLocation": {  
        "S3Location": {  
            "OutputS3BucketName": "string",  
            "OutputS3KeyPrefix": "string",  
            "OutputS3Region": "string"  
        }  
    },  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "ScheduleExpression": "string",  
    "ScheduleOffset": number,  
    "SyncCompliance": "string",  
    "TargetLocations": [  
        {  
            "Accounts": [ "string" ],  
            "ExecutionRoleName": "string",  
            "Regions": [ "string" ],  
            "TargetLocationMaxConcurrency": "string",  
            "TargetLocationMaxErrors": "string"  
        }  
    ],  
    "TargetMaps": [  
        {  
            "string" : [ "string" ]  
        }  
    ],  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ApplyOnlyAtCronInterval \(p. 23\)](#)

By default, when you create a new association, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

[AssociationName \(p. 23\)](#)

Specify a descriptive name for the association.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

[AutomationTargetParameterName \(p. 23\)](#)

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a capability of AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

[CalendarNames \(p. 23\)](#)

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents you want to gate your associations under. The associations only run when that change calendar is open. For more information, see [AWS Systems Manager Change Calendar](#).

Type: Array of strings

Required: No

[ComplianceSeverity \(p. 23\)](#)

The severity level to assign to the association.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED

Required: No

[DocumentVersion \(p. 23\)](#)

The document version you want to associate with the target(s). Can be a specific version or the default version.

Important

State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs the default version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared from another account, you must set the document version to default.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

InstanceId (p. 23)

The managed node ID.

Note

`InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceId` with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

MaxConcurrency (p. 23)

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100)%\$

Required: No

MaxErrors (p. 23)

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be

more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%|100%)$`

Required: No

[Name \(p. 23\)](#)

The name of the SSM Command document or Automation runbook that contains the configuration information for the managed node.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another account.

For Systems Manager documents (SSM documents) that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:partition:ssm:region:account-id:document/document-name`

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

[OutputLocation \(p. 23\)](#)

An Amazon Simple Storage Service (Amazon S3) bucket where you want to store the output details of the request.

Type: [InstanceAssociationOutputLocation \(p. 680\)](#) object

Required: No

[Parameters \(p. 23\)](#)

The parameters for the runtime configuration of the document.

Type: String to array of strings map

Required: No

[ScheduleExpression \(p. 23\)](#)

A cron expression when the association will be applied to the target(s).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

[ScheduleOffset \(p. 23\)](#)

Number of days to wait after the scheduled day to run an association. For example, if you specified a cron schedule of `cron(0 0 ? * THU#2 *)`, you could specify an offset of 3 to run the association each Sunday after the second Thursday of the month. For more information about cron schedules for associations, see [Reference: Cron and rate expressions for Systems Manager](#) in the *AWS Systems Manager User Guide*.

Note

To use offsets, you must specify the `ApplyOnlyAtCronInterval` parameter. This option tells the system not to run an association immediately after you create it.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

[SyncCompliance \(p. 23\)](#)

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the [PutComplianceItems \(p. 422\)](#) API operation. In this case, compliance data isn't managed by State Manager. It is managed by your direct call to the [PutComplianceItems \(p. 422\)](#) API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

[TargetLocations \(p. 23\)](#)

A location is a combination of AWS Regions and AWS accounts where you want to run the association. Use this action to create an association in multiple Regions and multiple accounts.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

[TargetMaps \(p. 23\)](#)

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets (p. 23)

The targets for the association. You can target managed nodes by using tags, AWS resource groups, all managed nodes in an AWS account, or individual managed node IDs. You can target all managed nodes in an AWS account by specifying the `InstanceIds` key with a value of `*`. For more information about choosing targets for an association, see [Using targets and rate controls with State Manager associations](#) in the *AWS Systems Manager User Guide*.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{  
    "AssociationDescription": {  
        "ApplyOnlyAtCronInterval": boolean,  
        "AssociationId": "string",  
        "AssociationName": "string",  
        "AssociationVersion": "string",  
        "AutomationTargetParameterName": "string",  
        "CalendarNames": [ "string" ],  
        "ComplianceSeverity": "string",  
        "Date": number,  
        "DocumentVersion": "string",  
        "InstanceId": "string",  
        "LastExecutionDate": number,  
        "LastSuccessfulExecutionDate": number,  
        "LastUpdateAssociationDate": number,  
        "MaxConcurrency": "string",  
        "MaxErrors": "string",  
        "Name": "string",  
        "OutputLocation": {  
            "S3Location": {  
                "OutputsS3BucketName": "string",  
                "OutputsS3KeyPrefix": "string",  
                "OutputsS3Region": "string"  
            }  
        },  
        "Overview": {  
            "AssociationStatusAggregatedCount": {  
                "string" : number  
            },  
            "DetailedStatus": "string",  
            "Status": "string"  
        },  
        "Parameters": {  
            "string" : [ "string" ]  
        },  
        "ScheduleExpression": "string",  
        "ScheduleOffset": number,  
        "Status": {  
            "AdditionalInfo": "string",  
            "Date": number,  
            "Message": "string",  
            "Name": "string"  
        },  
        "SyncCompliance": "string",  
        "TargetLocations": [  
    }  
}
```

```
{  
    "Accounts": [ "string" ],  
    "ExecutionRoleName": "string",  
    "Regions": [ "string" ],  
    "TargetLocationMaxConcurrency": "string",  
    "TargetLocationMaxErrors": "string"  
}  
],  
"TargetMaps": [  
    {  
        "string" : [ "string" ]  
    }  
],  
"Targets": [  
    {  
        "Key": "string",  
        "Values": [ "string" ]  
    }  
]  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription (p. 28)

Information about the association.

Type: [AssociationDescription \(p. 588\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationAlreadyExists

The specified association already exists.

HTTP Status Code: 400

AssociationLimitExceeded

You can have at most 2,000 active associations.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node ID(s). For example, you sent a document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T140427Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "Name": "AWS-UpdateSSMAgent",
    "InstanceId": "i-02573cafefEXAMPLE"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "f7d193fe-7722-4f2b-ac53-d8736EXAMPLE",
        "AssociationVersion": "1",
        "Date": 1585058668.255,
        "DocumentVersion": "$DEFAULT",
        "InstanceId": "i-02573cafefEXAMPLE",
        "LastUpdateAssociationDate": 1585058668.255,
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "DetailedStatus": "Creating",
            "Status": "Pending"
        },
        "Status": {
            "Date": 1585058668.255,
            "Message": "Associated with AWS-UpdateSSMAgent",
            "Name": "Associated"
        },
        "Targets": [
            {
                "Key": "InstanceIds",
                "Values": [
                    "i-02573cafefEXAMPLE"
                ]
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAssociationBatch

Associates the specified AWS Systems Manager document (SSM document) with the specified managed nodes or targets.

When you associate a document with one or more managed nodes using IDs or tags, AWS Systems Manager Agent (SSM Agent) running on the managed node processes the document and configures the node as specified.

If you associate a document with a managed node that already has an associated document, the system returns the `AssociationAlreadyExists` exception.

Request Syntax

```
{  
    "Entries": [  
        {  
            "ApplyOnlyAtCronInterval": boolean,  
            "AssociationName": "string",  
            "AutomationTargetParameterName": "string",  
            "CalendarNames": [ "string" ],  
            "ComplianceSeverity": "string",  
            "DocumentVersion": "string",  
            "InstanceId": "string",  
            "MaxConcurrency": "string",  
            "MaxErrors": "string",  
            "Name": "string",  
            "OutputLocation": {  
                "S3Location": {  
                    "OutputS3BucketName": "string",  
                    "OutputS3KeyPrefix": "string",  
                    "OutputS3Region": "string"  
                }  
            },  
            "Parameters": {  
                "string" : [ "string" ]  
            },  
            "ScheduleExpression": "string",  
            "ScheduleOffset": number,  
            "SyncCompliance": "string",  
            "TargetLocations": [  
                {  
                    "Accounts": [ "string" ],  
                    "ExecutionRoleName": "string",  
                    "Regions": [ "string" ],  
                    "TargetLocationMaxConcurrency": "string",  
                    "TargetLocationMaxErrors": "string"  
                }  
            ],  
            "TargetMaps": [  
                {  
                    "string" : [ "string" ]  
                }  
            ],  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ]  
        }  
    ]  
}
```

}

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Entries (p. 33)

One or more associations.

Type: Array of [CreateAssociationBatchRequestEntry \(p. 648\)](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

Response Syntax

```
{  
    "Failed": [  
        {  
            "Entry": {  
                "ApplyOnlyAtCronInterval": boolean,  
                "AssociationName": "string",  
                "AutomationTargetParameterName": "string",  
                "CalendarNames": [ "string" ],  
                "ComplianceSeverity": "string",  
                "DocumentVersion": "string",  
                "InstanceId": "string",  
                "MaxConcurrency": "string",  
                "MaxErrors": "string",  
                "Name": "string",  
                "OutputLocation": {  
                    "S3Location": {  
                        "OutputS3BucketName": "string",  
                        "OutputS3KeyPrefix": "string",  
                        "OutputS3Region": "string"  
                    }  
                },  
                "Parameters": {  
                    "string" : [ "string" ]  
                },  
                "ScheduleExpression": "string",  
                "ScheduleOffset": number,  
                "SyncCompliance": "string",  
                "TargetLocations": [  
                    {  
                        "Accounts": [ "string" ],  
                        "ExecutionRoleName": "string",  
                        "Regions": [ "string" ],  
                        "TargetLocationMaxConcurrency": "string",  
                        "TargetLocationMaxErrors": "string"  
                    }  
                ],  
                "TargetMaps": [  
                    {  
                        "string" : [ "string" ]  
                    }  
                ]  
            }  
        }  
    ]  
}
```

```

        }
    ],
    "Targets": [
        {
            "Key": "string",
            "Values": [ "string" ]
        }
    ]
},
"Fault": "string",
"Message": "string"
},
],
"Successful": [
{
    "ApplyOnlyAtCronInterval": boolean,
    "AssociationId": "string",
    "AssociationName": "string",
    "AssociationVersion": "string",
    "AutomationTargetParameterName": "string",
    "CalendarNames": [ "string" ],
    "ComplianceSeverity": "string",
    "Date": number,
    "DocumentVersion": "string",
    "InstanceId": "string",
    "LastExecutionDate": number,
    "LastSuccessfulExecutionDate": number,
    "LastUpdateAssociationDate": number,
    "MaxConcurrency": "string",
    "MaxErrors": "string",
    "Name": "string",
    "OutputLocation": {
        "S3Location": {
            "OutputS3BucketName": "string",
            "OutputS3KeyPrefix": "string",
            "OutputS3Region": "string"
        }
    },
    "Overview": {
        "AssociationStatusAggregatedCount": {
            "string" : number
        },
        "DetailedStatus": "string",
        "Status": "string"
    },
    "Parameters": {
        "string" : [ "string" ]
    },
    "ScheduleExpression": "string",
    "ScheduleOffset": number,
    "Status": {
        "AdditionalInfo": "string",
        "Date": number,
        "Message": "string",
        "Name": "string"
    },
    "SyncCompliance": "string",
    "TargetLocations": [
        {
            "Accounts": [ "string" ],
            "ExecutionRoleName": "string",
            "Regions": [ "string" ],
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string"
        }
    ],
}
]
}

```

```
"TargetMaps": [  
    {  
        "string" : [ "string" ]  
    }  
,  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Failed (p. 34)

Information about the associations that failed.

Type: Array of [FailedCreateAssociation \(p. 676\)](#) objects

Successful (p. 34)

Information about the associations that succeeded.

Type: Array of [AssociationDescription \(p. 588\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationLimitExceeded

You can have at most 2,000 active associations.

HTTP Status Code: 400

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node ID(s). For example, you sent a document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateAssociationBatch.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateAssociationBatch
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T142446Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 151

{
    "Entries": [
        {
            "InstanceId": "i-0471e04240EXAMPLE",
            "Name": "AWS-UpdateSSMAgent"
        },
        {
            "InstanceId": "i-07782c72faEXAMPLE",
            "Name": "AWS-UpdateSSMAgent"
        }
    ]
}
```

Sample Response

```
{
    "Failed": [],
    "Successful": [
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "33858bec-0c55-4547-a054-eb5fcEXAMPLE",
            "AssociationVersion": "1",
            "Date": 1585059887.692,
            "DocumentVersion": "$DEFAULT",
            "InstanceId": "i-0471e04240EXAMPLE",
            "LastUpdateAssociationDate": 1585059887.692,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "DetailedStatus": "Creating",
                "Status": "Pending"
            },
            "Status": {
                "Date": 1585059887.692,
                "Message": "Associated with AWS-UpdateSSMAgent",
                "Name": "Associated"
            },
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-0471e04240EXAMPLE"
                    ]
                }
            ]
        },
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "e0e0a062-3dcb-4b3e-bb2b-d01b4EXAMPLE",
            "AssociationVersion": "1",
            "Date": 1585059887.692,
            "DocumentVersion": "$DEFAULT",
            "InstanceId": "i-07782c72faEXAMPLE",
            "LastUpdateAssociationDate": 1585059887.692,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "DetailedStatus": "Creating",
                "Status": "Pending"
            },
            "Status": {
                "Date": 1585059887.692,
                "Message": "Associated with AWS-UpdateSSMAgent",
                "Name": "Associated"
            },
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-07782c72faEXAMPLE"
                    ]
                }
            ]
        }
    ]
}
```

```
"Date": 1585059887.726,
"DocumentVersion": "$DEFAULT",
"InstanceId": "i-07782c72faEXAMPLE",
"LastUpdateAssociationDate": 1585059887.726,
"Name": "AWS-UpdateSSMAgent",
"Overview": {
    "DetailedStatus": "Creating",
    "Status": "Pending"
},
>Status": {
    "Date": 1585059887.726,
    "Message": "Associated with AWS-UpdateSSMAgent",
    "Name": "Associated"
},
"Targets": [
    {
        "Key": "InstanceIds",
        "Values": [
            "i-07782c72faEXAMPLE"
        ]
    }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDocument

Creates a AWS Systems Manager (SSM document). An SSM document defines the actions that Systems Manager performs on your managed nodes. For more information about SSM documents, including information about supported schemas, features, and syntax, see [AWS Systems Manager Documents](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "Attachments": [  
        {  
            "Key": "string",  
            "Name": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "Content": "string",  
    "DisplayName": "string",  
    "DocumentFormat": "string",  
    "DocumentType": "string",  
    "Name": "string",  
    "Requires": [  
        {  
            "Name": "string",  
            "Version": "string"  
        }  
    ],  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "TargetType": "string",  
    "VersionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Attachments (p. 40)

A list of key-value pairs that describe attachments to a version of a document.

Type: Array of [AttachmentsSource \(p. 609\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Content (p. 40)

The content for the new SSM document in JSON or YAML format. We recommend storing the contents for your new document in an external JSON or YAML file and referencing the file in a command.

For examples, see the following topics in the *AWS Systems Manager User Guide*.

- [Create an SSM document \(AWS API\)](#)
- [Create an SSM document \(AWS CLI\)](#)
- [Create an SSM document \(API\)](#)

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

[DisplayName \(p. 40\)](#)

An optional field where you can specify a friendly name for the SSM document. This value can differ for each version of the document. You can update this value at a later time using the [UpdateDocument \(p. 518\)](#) operation.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/\]*\$

Required: No

[DocumentFormat \(p. 40\)](#)

Specify the document format for the request. The document format can be JSON, YAML, or TEXT. JSON is the default format.

Type: String

Valid Values: YAML | JSON | TEXT

Required: No

[DocumentType \(p. 40\)](#)

The type of document to create.

Note

The DeploymentStrategy document type is an internal-use-only document type reserved for AWS AppConfig.

Type: String

Valid Values: Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate

Required: No

[Name \(p. 40\)](#)

A name for the SSM document.

Important

You can't use the following strings as document name prefixes. These are reserved by AWS for use as document name prefixes:

- aws-
- amazon
- amzn

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: Yes

[Requires \(p. 40\)](#)

A list of SSM documents required by a document. This parameter is used exclusively by AWS AppConfig. When a user creates an AWS AppConfig configuration in an SSM document, the user must also specify a required document for validation purposes. In this case, an ApplicationConfiguration document requires an ApplicationConfigurationSchema document for validation purposes. For more information, see [What is AWS AppConfig?](#) in the [AWS AppConfig User Guide](#).

Type: Array of [DocumentRequires \(p. 668\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

[Tags \(p. 40\)](#)

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an SSM document to identify the types of targets or the environment where it will run. In this case, you could specify the following key-value pairs:

- Key=OS,Value=Windows
- Key=Environment,Value=Production

Note

To add tags to an existing SSM document, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

[TargetType \(p. 40\)](#)

Specify a target type to define the kinds of resources the document can run on. For example, to run a document on EC2 instances, specify the following value: /AWS::EC2::Instance. If you specify a value of '/' the document can run on all types of resources. If you don't specify a value, the document can't run on any resources. For a list of valid resource types, see [AWS resource and property types reference](#) in the [AWS CloudFormation User Guide](#).

Type: String

Length Constraints: Maximum length of 200.

Pattern: ^\//[\w\.\-\:\/\]*\$

Required: No

VersionName (p. 40)

An optional field specifying the version of the artifact you are creating with the document. For example, `Release12.1`. This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Required: No

Response Syntax

```
{  
    "DocumentDescription": {  
        "ApprovedVersion": "string",  
        "AttachmentsInformation": [  
            {  
                "Name": "string"  
            }  
        ],  
        "Author": "string",  
        "Category": [ "string" ],  
        "CategoryEnum": [ "string" ],  
        "CreatedDate": number,  
        "DefaultVersion": "string",  
        "Description": "string",  
        "DisplayName": "string",  
        "DocumentFormat": "string",  
        "DocumentType": "string",  
        "DocumentVersion": "string",  
        "Hash": "string",  
        "HashType": "string",  
        "LatestVersion": "string",  
        "Name": "string",  
        "Owner": "string",  
        "Parameters": [  
            {  
                "DefaultValue": "string",  
                "Description": "string",  
                "Name": "string",  
                "Type": "string"  
            }  
        ],  
        "PendingReviewVersion": "string",  
        "PlatformTypes": [ "string" ],  
        "Requires": [  
            {  
                "Name": "string",  
                "Version": "string"  
            }  
        ],  
        "ReviewInformation": [  
            {  
                "ReviewedTime": number,  
                "Reviewer": "string",  
                "Status": "string"  
            }  
        ],  
        "ReviewStatus": "string",  
        "SchemaVersion": "string",  
    }  
}
```

```
"Sha1": "string",
"Status": "string",
"StatusInformation": "string",
"Tags": [
    {
        "Key": "string",
        "Value": "string"
    }
],
"TargetType": "string",
"VersionName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentDescription (p. 43)

Information about the SSM document.

Type: [DocumentDescription \(p. 655\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DocumentAlreadyExists

The specified document already exists.

HTTP Status Code: 400

DocumentLimitExceeded

You can have at most 500 active SSM documents.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocumentContent

The content for the document isn't valid.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T145550Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 963

{
    "Content": "---\ndescription: \"Example\"\nschemaVersion: '0.3'\nassumeRole:
\"{{ AutomationAssumeRole }}\"--truncated--",
    "Name": "Example",
    "DocumentType": "Automation",
    "DocumentFormat": "YAML"
}
```

Sample Response

```
{
    "DocumentDescription": {
        "CreatedDate": 1585061751.738,
        "DefaultVersion": "1",
        "Description": "Custom Automation Example",
        "DocumentFormat": "YAML",
        "DocumentType": "Automation",
        "DocumentVersion": "1",
        "Hash": "0d3d879b3ca072e03c12638d0255ebd004d2c65bd318f8354fcde820dEXAMPLE",
        "HashType": "Sha256",
        "LatestVersion": "1",
        "Name": "Example",
        "Owner": "111122223333",
        "Parameters": [
            {
                "DefaultValue": "",
                "Description": "(Optional) The ARN of the role that allows Automation to
perform the actions on your behalf. If no role is specified, Systems Manager Automation
uses your IAM permissions to execute this document.",
                "Name": "AutomationAssumeRole",
                "Type": "String"
            },
            {
                "DefaultValue": "",
                "Description": "(Required) The Instance Id to create an image of.",
                "Name": "InstanceId",
                "Type": "String"
            }
        ]
}
```

```
        ],
        "PlatformTypes": [
            "Windows",
            "Linux"
        ],
        "SchemaVersion": "0.3",
        "Status": "Creating",
        "Tags": []
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateMaintenanceWindow

Creates a new maintenance window.

Note

The value you specify for `Duration` determines the specific end time for the maintenance window based on the time it begins. No maintenance window tasks are permitted to start after the resulting endtime minus the number of hours you specify for `Cutoff`. For example, if the maintenance window starts at 3 PM, the duration is three hours, and the value you specify for `Cutoff` is one hour, no maintenance window tasks can start after 5 PM.

Request Syntax

```
{  
    "AllowUnassociatedTargets": boolean,  
    "ClientToken": "string",  
    "Cutoff": number,  
    "Description": "string",  
    "Duration": number,  
    "EndDate": "string",  
    "Name": "string",  
    "Schedule": "string",  
    "ScheduleOffset": number,  
    "ScheduleTimezone": "string",  
    "StartDate": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AllowUnassociatedTargets \(p. 47\)](#)

Enables a maintenance window task to run on managed nodes, even if you haven't registered those nodes as targets. If enabled, then you must specify the unregistered managed nodes (by node ID) when you register a task with the maintenance window.

If you don't enable this option, then you must specify previously-registered targets when you register a task with the maintenance window.

Type: Boolean

Required: Yes

[ClientToken \(p. 47\)](#)

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Cutoff (p. 47)

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: Yes

Description (p. 47)

An optional description for the maintenance window. We recommend specifying a description to help you organize your maintenance windows.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Duration (p. 47)

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: Yes

EndDate (p. 47)

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become inactive. EndDate allows you to set a date and time in the future when the maintenance window will no longer run.

Type: String

Required: No

Name (p. 47)

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: Yes

Schedule (p. 47)

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

[ScheduleOffset \(p. 47\)](#)

The number of days to wait after the date and time specified by a cron expression before running the maintenance window.

For example, the following cron expression schedules a maintenance window to run on the third Tuesday of every month at 11:30 PM.

```
cron(30 23 ? * TUE#3 *)
```

If the schedule offset is 2, the maintenance window won't run until two days later.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

[ScheduleTimezone \(p. 47\)](#)

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the [Time Zone Database](#) on the IANA website.

Type: String

Required: No

[StartDate \(p. 47\)](#)

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become active. `StartDate` allows you to delay activation of the maintenance window until the specified future date.

Type: String

Required: No

[Tags \(p. 47\)](#)

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a maintenance window to identify the type of tasks it will run, the types of targets, and the environment it will run in. In this case, you could specify the following key-value pairs:

- Key=TaskType,Value=AgentUpdate
- Key=OS,Value=Windows
- Key=Environment,Value=Production

Note

To add tags to an existing maintenance window, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{
```

```
    "WindowId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WindowId \(p. 49\)](#)

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceeded

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 186
X-Amz-Target: AmazonSSM.CreateMaintenanceWindow
X-Amz-Date: 20180312T201809Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "My-Development-Maintenance-Window",
    "Cutoff": 2,
    "Schedule": "cron(0 12 ? * WED *)",
    "AllowUnassociatedTargets": true,
    "Duration": 6,
    "Tags": [
        {
            "Key": "Environment",
            "Value": "Development"
        }
    ],
    "ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOpsItem

Creates a new OpsItem. You must have permission in AWS Identity and Access Management (IAM) to create a new OpsItem. For more information, see [Getting started with OpsCenter](#) in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see [AWS Systems Manager OpsCenter](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "ActualEndTime": number,  
    "ActualStartTime": number,  
    "Category": "string",  
    "Description": "string",  
    "Notifications": [  
        {  
            "Arn": "string"  
        }  
    ],  
    "OperationalData": {  
        "string": {  
            "Type": "string",  
            "Value": "string"  
        }  
    },  
    "OpsItemType": "string",  
    "PlannedEndTime": number,  
    "PlannedStartTime": number,  
    "Priority": number,  
    "RelatedOpsItems": [  
        {  
            "OpsItemId": "string"  
        }  
    ],  
    "Severity": "string",  
    "Source": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "Title": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ActualEndTime (p. 52)

The time a runbook workflow ended. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[ActualStartTime \(p. 52\)](#)

The time a runbook workflow started. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[Category \(p. 52\)](#)

Specify a category to assign to an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^(?!\\s*\$).+

Required: No

[Description \(p. 52\)](#)

Information about the OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\\s\\S]*\\S[\\s\\S]*

Required: Yes

[Notifications \(p. 52\)](#)

The Amazon Resource Name (ARN) of an SNS topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of [OpsItemNotification \(p. 759\)](#) objects

Required: No

[OperationalData \(p. 52\)](#)

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

Important

Operational data keys *can't* begin with the following: amazon, aws, amzn, ssm, /amazon, /aws, /amzn, /ssm.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the [DescribeOpsItems \(p. 213\)](#) API operation) can view and search on the specified data.

Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the [GetOpsItem \(p. 311\)](#) API operation).

Use the /aws/resources key in OperationalData to specify a related resource in the request. Use the /aws/automations key in OperationalData to associate an Automation runbook with the

OpsItem. To view AWS CLI example commands that use these keys, see [Creating OpsItems manually in the AWS Systems Manager User Guide](#).

Type: String to [OpsItemDataValue \(p. 753\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\\s*\$).+

Required: No

[OpsItemType \(p. 52\)](#)

The type of OpsItem to create. Currently, the only valid values are /aws/changerequest and /aws/issue.

Type: String

Required: No

[PlannedEndTime \(p. 52\)](#)

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[PlannedStartTime \(p. 52\)](#)

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[Priority \(p. 52\)](#)

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

[RelatedOpsItems \(p. 52\)](#)

One or more OpsItems that share something in common with the current OpsItems. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of [RelatedOpsItem \(p. 804\)](#) objects

Required: No

[Severity \(p. 52\)](#)

Specify a severity to assign to an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\\s*$).+`

Required: No

[Source \(p. 52\)](#)

The origin of the OpsItem, such as Amazon EC2 or Systems Manager.

Note

The source name can't contain the following strings: `aws`, `amazon`, and `amzn`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\\s*$).+`

Required: Yes

[Tags \(p. 52\)](#)

Optional metadata that you assign to a resource. You can restrict access to OpsItems by using an inline IAM policy that specifies tags. For more information, see [Getting started with OpsCenter](#) in the *AWS Systems Manager User Guide*.

Tags use a key-value pair. For example:

`Key=Department,Value=Finance`

Important

To add tags to a new OpsItem, a user must have IAM permissions for both the `ssm:CreateOpsItems` operation and the `ssm:AddTagsToResource` operation. To add tags to an existing OpsItem, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

[Title \(p. 52\)](#)

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: Yes

Response Syntax

```
{  
    "OpsItemId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[OpsItemId \(p. 55\)](#)

The ID of the OpsItem.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemAlreadyExistsException

The OpsItem already exists.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas. For information about OpsItem quotas, see [What are the resource limits for OpsCenter?](#).

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateOpsItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T161257Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 80

{
    "Description": "Example Ops Item",
    "Source": "SSM",
```

```
    "Title": "DocumentDeleted"  
}
```

Sample Response

```
{  
    "OpsItemId": "oi-1f050EXAMPLE"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOpsMetadata

If you create a new application in Application Manager, AWS Systems Manager calls this API operation to specify information about the new application, including the application type.

Request Syntax

```
{  
    "Metadata": {  
        "string" : {  
            "Value": "string"  
        }  
    },  
    "ResourceId": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Metadata \(p. 58\)](#)

Metadata for a new Application Manager application.

Type: String to [MetadataValue \(p. 741\)](#) object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: ^(?!\\s*\$).+

Required: No

[ResourceId \(p. 58\)](#)

A resource ID for a new Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^(?!\\s*\$).+

Required: Yes

[Tags \(p. 58\)](#)

Optional metadata that you assign to a resource. You can specify a maximum of five tags for an OpsMetadata object. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an OpsMetadata object to identify an environment or target AWS Region. In this case, you could specify the following key-value pairs:

- Key=Environment,Value=Production
- Key=Region,Value=us-east-2

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{  
    "OpsMetadataArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsMetadataArn (p. 59)

The Amazon Resource Name (ARN) of the OpsMetadata Object or blob created by the call.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*|)

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataAlreadyExistsException

An OpsMetadata object already exists for the selected resource.

HTTP Status Code: 400

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataLimitExceededException

Your account reached the maximum number of OpsMetadata objects allowed by Application Manager. The maximum is 200 OpsMetadata objects. Delete one or more OpsMetadata object and try again.

HTTP Status Code: 400

OpsMetadataTooManyUpdatesException

The system is processing too many concurrent updates. Wait a few moments and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePatchBaseline

Creates a patch baseline.

Note

For information about valid key-value pairs in `PatchFilters` for each supported operating system type, see [PatchFilter \(p. 790\)](#).

Request Syntax

```
{  
    "ApprovalRules": {  
        "PatchRules": [  
            {  
                "ApproveAfterDays": number,  
                "ApproveUntilDate": "string",  
                "ComplianceLevel": "string",  
                "EnableNonSecurity": boolean,  
                "PatchFilterGroup": {  
                    "PatchFilters": [  
                        {  
                            "Key": "string",  
                            "Values": [ "string" ]  
                        }  
                    ]  
                }  
            }  
        ],  
        "ApprovedPatches": [ "string" ],  
        "ApprovedPatchesComplianceLevel": "string",  
        "ApprovedPatchesEnableNonSecurity": boolean,  
        "ClientToken": "string",  
        "Description": "string",  
        "GlobalFilters": {  
            "PatchFilters": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "Name": "string",  
            "OperatingSystem": "string",  
            "RejectedPatches": [ "string" ],  
            "RejectedPatchesAction": "string",  
            "Sources": [  
                {  
                    "Configuration": "string",  
                    "Name": "string",  
                    "Products": [ "string" ]  
                }  
            ],  
            "Tags": [  
                {  
                    "Key": "string",  
                    "Value": "string"  
                }  
            ]  
        }  
    }  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ApprovalRules \(p. 61\)](#)

A set of rules used to include patches in the baseline.

Type: [PatchRuleGroup \(p. 797\)](#) object

Required: No

[ApprovedPatches \(p. 61\)](#)

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[ApprovedPatchesComplianceLevel \(p. 61\)](#)

Defines the compliance level for approved patches. When an approved patch is reported as missing, this value describes the severity of the compliance violation. The default value is UNSPECIFIED.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

[ApprovedPatchesEnableNonSecurity \(p. 61\)](#)

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is false. Applies to Linux managed nodes only.

Type: Boolean

Required: No

[ClientToken \(p. 61\)](#)

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

[Description \(p. 61\)](#)

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

[GlobalFilters \(p. 61\)](#)

A set of global filters used to include patches in the baseline.

Type: [PatchFilterGroup \(p. 792\)](#) object

Required: No

[Name \(p. 61\)](#)

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9\-_\.]\{3,128\}\$

Required: Yes

[OperatingSystem \(p. 61\)](#)

Defines the operating system the patch baseline applies to. The default value is WINDOWS.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: No

[RejectedPatches \(p. 61\)](#)

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[RejectedPatchesAction \(p. 61\)](#)

The action for Patch Manager to take on patches included in the RejectedPatches list.

- **ALLOW_AS_DEPENDENCY** : A package in the Rejected patches list is installed only if it is a dependency of another package. It is considered compliant with the patch baseline, and its status is reported as InstalledOther. This is the default action if no option is specified.
- **BLOCK** : Packages in the RejectedPatches list, and packages that include them as dependencies, aren't installed under any circumstances. If a package was installed before it was added to the Rejected patches list, it is considered non-compliant with the patch baseline, and its status is reported as InstalledRejected.

Type: String

Valid Values: ALLOW_AS_DEPENDENCY | BLOCK

Required: No

Sources (p. 61)

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of [PatchSource \(p. 798\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Tags (p. 61)

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a patch baseline to identify the severity level of patches it specifies and the operating system family it applies to. In this case, you could specify the following key-value pairs:

- Key=PatchSeverity, Value=Critical
- Key=OS, Value=Windows

Note

To add tags to an existing patch baseline, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{  
    "BaselineId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId (p. 64)

The ID of the created patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreatePatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 461
X-Amz-Target: AmazonSSM.CreatePatchBaseline
X-Amz-Date: 20180309T022356Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Description": "Baseline containing all updates approved for production systems",
    "ApprovalRules": {
        "PatchRules": [
            {
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Values": [
                                "Critical",
                                "Important",
                                "Moderate"
                            ],
                            "Key": "MSRC_SEVERITY"
                        },
                        {
                            "Values": [
                                "SecurityUpdates",
                                "Updates",
                                "Patches"
                            ],
                            "Key": "TYPE"
                        }
                    ]
                }
            }
        ]
    }
}
```

```
        "UpdateRollups",
        "CriticalUpdates"
    ],
    "Key": "CLASSIFICATION"
}
]
},
"ApproveAfterDays": 7,
"ApproveUntilDate": "",
"EnableNonSecurity": true,
"ComplianceLevel": "MEDIUM"
}
]
},
"Name": "my-Windows-Server-patch-baseline",
"OperatingSystem": "WINDOWS",
"ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceDataSync

A resource data sync helps you view data from multiple sources in a single location. AWS Systems Manager offers two types of resource data sync: `SyncToDestination` and `SyncFromSource`.

You can configure Systems Manager Inventory to use the `SyncToDestination` type to synchronize Inventory data from multiple AWS Regions to a single Amazon Simple Storage Service (Amazon S3) bucket. For more information, see [Configuring resource data sync for Inventory](#) in the *AWS Systems Manager User Guide*.

You can configure Systems Manager Explorer to use the `SyncFromSource` type to synchronize operational work items (OpsItems) and operational data (OpsData) from multiple AWS Regions to a single Amazon S3 bucket. This type can synchronize OpsItems and OpsData from multiple AWS accounts and AWS Regions or `EntireOrganization` by using AWS Organizations. For more information, see [Setting up Systems Manager Explorer to display data from multiple accounts and Regions](#) in the *AWS Systems Manager User Guide*.

A resource data sync is an asynchronous operation that returns immediately. After a successful initial sync is completed, the system continuously syncs data. To check the status of a sync, use the [ListResourceDataSync](#) (p. 412).

Note

By default, data isn't encrypted in Amazon S3. We strongly recommend that you enable encryption in Amazon S3 to ensure secure data storage. We also recommend that you secure access to the Amazon S3 bucket by creating a restrictive bucket policy.

Request Syntax

```
{  
    "S3Destination": {  
        "AWSKMSKeyARN": "string",  
        "BucketName": "string",  
        "DestinationDataSharing": {  
            "DestinationDataSharingType": "string"  
        },  
        "Prefix": "string",  
        "Region": "string",  
        "SyncFormat": "string"  
    },  
    "SyncName": "string",  
    "SyncSource": {  
        "AwsOrganizationsSource": {  
            "OrganizationalUnits": [  
                {  
                    "OrganizationalUnitId": "string"  
                }  
            ],  
            "OrganizationSourceType": "string"  
        },  
        "EnableAllOpsDataSources": boolean,  
        "IncludeFutureRegions": boolean,  
        "SourceRegions": [ "string" ],  
        "SourceType": "string"  
    },  
    "SyncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

S3Destination (p. 67)

Amazon S3 configuration details for the sync. This parameter is required if the SyncType value is SyncToDestination.

Type: [ResourceDataSyncS3Destination \(p. 813\)](#) object

Required: No

SyncName (p. 67)

A name for the configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncSource (p. 67)

Specify information about the data sources to synchronize. This parameter is required if the SyncType value is SyncFromSource.

Type: [ResourceDataSyncSource \(p. 815\)](#) object

Required: No

SyncType (p. 67)

Specify SyncToDestination to create a resource data sync that synchronizes data to an S3 bucket for Inventory. If you specify SyncToDestination, you must provide a value for S3Destination. Specify SyncFromSource to synchronize data from a single account and multiple Regions, or multiple AWS accounts and AWS Regions, as listed in AWS Organizations for Explorer. If you specify SyncFromSource, you must provide a value for SyncSource. The default value is SyncToDestination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncAlreadyExistsException

A sync configuration with the same name already exists.

HTTP Status Code: 400

ResourceDataSyncCountExceededException

You have exceeded the allowed maximum sync configurations.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of CreateResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.CreateResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200327T173437Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200327/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 186

{
    "SyncName": "Example",
    "S3Destination": {
        "BucketName": "exampleBucket",
        "Prefix": "exampleSubDirectory",
        "SyncFormat": "JsonSerDe",
        "Region": "us-east-2"
    },
    "SyncType": "SyncToDestination"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteActivation

Deletes an activation. You aren't required to delete an activation. If you delete an activation, you can no longer use it to register additional managed nodes. Deleting an activation doesn't de-register managed nodes. You must manually de-register managed nodes.

Request Syntax

```
{  
    "ActivationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ActivationId (p. 71)

The ID of the activation that you want to delete.

Type: String

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidActivation

The activation isn't valid. The activation might have been deleted, or the ActivationId and the ActivationCode don't match.

HTTP Status Code: 400

InvalidActivationId

The activation ID isn't valid. Verify that you entered the correct ActivationId or ActivationCode and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteActivation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteActivation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T151218Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 56

{
    "ActivationId": "e488f2f6-e686-4afb-8a04-ef6dfEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAssociation

Disassociates the specified AWS Systems Manager document (SSM document) from the specified managed node. If you created the association by using the `Targets` parameter, then you must delete the association by using the association ID.

When you disassociate a document from a managed node, it doesn't change the configuration of the node. To change the configuration state of a managed node after you disassociate a document, you must create a new document with the desired configuration and associate it with the node.

Request Syntax

```
{  
    "AssociationId": "string",  
    "InstanceId": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AssociationId \(p. 73\)](#)

The association ID that you want to delete.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

[InstanceId \(p. 73\)](#)

The managed node ID.

Note

`InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceId` with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: No

[Name \(p. 73\)](#)

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\\$

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteAssociation.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T150348Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "33858bec-0c55-4547-a054-eb5fcEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDocument

Deletes the AWS Systems Manager document (SSM document) and all managed node associations to the document.

Before you delete the document, we recommend that you use [DeleteAssociation \(p. 73\)](#) to disassociate all managed nodes that are associated with the document.

Request Syntax

```
{  
    "DocumentVersion": "string",  
    "Force": boolean,  
    "Name": "string",  
    "VersionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentVersion \(p. 76\)](#)

The version of the document that you want to delete. If not provided, all versions of the document are deleted.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

[Force \(p. 76\)](#)

Some SSM document types require that you specify a Force flag before you can delete the document. For example, you must specify a Force flag to delete a document of type ApplicationConfigurationSchema. You can restrict access to the Force flag in an AWS Identity and Access Management (IAM) policy.

Type: Boolean

Required: No

[Name \(p. 76\)](#)

The name of the document.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: Yes

[VersionName \(p. 76\)](#)

The version name of the document that you want to delete. If not provided, all versions of the document are deleted.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.]{1,128}\$

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociatedInstances

You must disassociate a document from all managed nodes before you can delete it.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteDocument.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T151532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 19
```

```
{  
    "Name": "Example"  
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteInventory

Delete a custom inventory type or the data associated with a custom inventory type. Deleting a custom inventory type is also referred to as deleting a custom inventory schema.

Request Syntax

```
{  
    "ClientToken": "string",  
    "DryRun": boolean,  
    "SchemaDeleteOption": "string",  
    "TypeName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ClientToken \(p. 79\)](#)

User-provided idempotency token.

Type: String

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

[DryRun \(p. 79\)](#)

Use this option to view a summary of the deletion request without deleting any data or the data type. This option is useful when you only want to understand what will be deleted. Once you validate that the data to be deleted is what you intend to delete, you can run the same command without specifying the `DryRun` option.

Type: Boolean

Required: No

[SchemaDeleteOption \(p. 79\)](#)

Use the `SchemaDeleteOption` to delete a custom inventory type (schema). If you don't choose this option, the system only deletes existing inventory data associated with the custom inventory type. Choose one of the following options:

`DisableSchema`: If you choose this option, the system ignores all inventory data for the specified version, and any earlier versions. To enable this schema again, you must call the `PutInventory` operation for a version greater than the disabled version.

`DeleteSchema`: This option deletes the specified custom type from the Inventory service. You can recreate the schema later, if you want.

Type: String

Valid Values: `DisableSchema` | `DeleteSchema`

Required: No

TypeName (p. 79)

The name of the custom inventory type for which you want to delete either all previously collected data or the inventory type itself.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Required: Yes

Response Syntax

```
{  
    "DeletionId": "string",  
    "DeletionSummary": {  
        "RemainingCount": number,  
        "SummaryItems": [  
            {  
                "Count": number,  
                "RemainingCount": number,  
                "Version": "string"  
            }  
        ],  
        "TotalCount": number  
    },  
    "TypeName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeletionId (p. 80)

Every DeleteInventory operation is assigned a unique ID. This option returns a unique ID. You can use this ID to query the status of a delete operation. This option is useful for ensuring that a delete operation has completed before you begin other operations.

Type: String

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

DeletionSummary (p. 80)

A summary of the delete operation. For more information about this summary, see [Deleting custom inventory](#) in the *AWS Systems Manager User Guide*.

Type: [InventoryDeletionSummary \(p. 701\)](#) object

TypeName (p. 80)

The name of the inventory data type specified in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDeleteInventoryParametersException

One or more of the parameters specified for the delete operation isn't valid. Verify all parameters and try again.

HTTP Status Code: 400

InvalidInventoryRequestException

The request isn't valid.

HTTP Status Code: 400

InvalidOptionException

The delete inventory option specified isn't valid. Verify the option and try again.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteInventory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteInventory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.25 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/ssm.delete-
inventory
X-Amz-Date: 20210809T230226Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210809/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature39c3b3042cd2aEXAMPLE
Content-Length: 124
```

```
{  
    "TypeName": "Custom:RackInfo",  
    "SchemaDeleteOption": "DeleteSchema",  
    "ClientToken": "a7d4972c-ab3e-4b9a-b5c0-d5aExample"  
}
```

Sample Response

```
{  
    "DeletionId": "5bc2ba3b-ee6a-40fa-8d09-5e5Example",  
    "DeletionSummary": {  
        "RemainingCount": 1,  
        "SummaryItems": [  
            {  
                "Count": 1,  
                "RemainingCount": 1,  
                "Version": "1.0"  
            }  
        ],  
        "TotalCount": 1  
    },  
    "TypeName": "Custom:RackInfo"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteMaintenanceWindow

Deletes a maintenance window.

Request Syntax

```
{  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

WindowId (p. 83)

The ID of the maintenance window to delete.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "WindowId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId (p. 83)

The ID of the deleted maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DeleteMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.DeleteMaintenanceWindow
X-Amz-Date: 20180312T210257Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOpsMetadata

Delete OpsMetadata related to an application.

Request Syntax

```
{  
    "OpsMetadataArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

OpsMetadataArn (p. 85)

The Amazon Resource Name (ARN) of an OpsMetadata Object to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteParameter

Delete a parameter from the system. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

Request Syntax

```
{  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Name (p. 87)

The name of the parameter to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonSSM.DeleteParameter
X-Amz-Date: 20180316T010702Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "EC2DevServerType"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteParameters

Delete a list of parameters. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

Request Syntax

```
{  
    "Names": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Names (p. 89)

The names of the parameters to delete. After deleting a parameter, wait for at least 30 seconds to create a parameter with the same name.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Response Syntax

```
{  
    "DeletedParameters": [ "string" ],  
    "InvalidParameters": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DeletedParameters (p. 89)

The names of the deleted parameters.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

[InvalidParameters \(p. 89\)](#)

The names of parameters that weren't deleted because the parameters aren't valid.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of DeleteParameters.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 53
X-Amz-Target: AmazonSSM.DeleteParameters
X-Amz-Date: 20180316T010844Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Names": [
        "EC2TestServerType",
        "EC2ProdServerType"
    ]
}
```

Sample Response

```
{
    "DeletedParameters": [
        "EC2ProdServerType",
        "EC2TestServerType"
    ],
    "InvalidParameters": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePatchBaseline

Deletes a patch baseline.

Request Syntax

```
{  
    "BaselineId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 92)

The ID of the patch baseline to delete.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

Required: Yes

Response Syntax

```
{  
    "BaselineId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId (p. 92)

The ID of the deleted patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceInUseException

Error returned if an attempt is made to delete a patch baseline that is registered for a patch group.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeletePatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.DeletePatchBaseline
X-Amz-Date: 20180309T062407Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourceDataSync

Deletes a resource data sync configuration. After the configuration is deleted, changes to data on managed nodes are no longer synced to or from the target. Deleting a sync configuration doesn't delete data.

Request Syntax

```
{  
    "SyncName": "string",  
    "SyncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[SyncName \(p. 95\)](#)

The name of the configuration to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

[SyncType \(p. 95\)](#)

Specify the type of resource data sync to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeleteResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeleteResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T144518Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 28

{
    "SyncName": "exampleSync"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterManagedInstance

Removes the server or virtual machine from the list of registered servers. You can reregister the node again at any time. If you don't plan to use Run Command on the server, we suggest uninstalling SSM Agent first.

Request Syntax

```
{  
    "InstanceId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

InstanceId (p. 97)

The ID assigned to the managed node when you registered it using the activation process.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 124.

Pattern: (^mi-[0-9a-f]{17}\$)|(^eks_c:[0-9A-Za-z][A-Za-z0-9\-_]{0,99}\w{17}\$)

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeregisterManagedInstance`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterManagedInstance
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200220T234004Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37

{
    "InstanceId": "mi-017431b35cEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterPatchBaselineForPatchGroup

Removes a patch group from a patch baseline.

Request Syntax

```
{  
    "BaselineId": "string",  
    "PatchGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 99)

The ID of the patch baseline to deregister the patch group from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Required: Yes

PatchGroup (p. 99)

The name of the patch group that should be deregistered from the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/-+=\-\@]*\$

Required: Yes

Response Syntax

```
{  
    "BaselineId": "string",  
    "PatchGroup": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId (p. 99)

The ID of the patch baseline the patch group was deregistered from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

PatchGroup (p. 99)

The name of the patch group deregistered from the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}]\p{N}_.:/:=+\-@]*\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DeregisterPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 74
X-Amz-Target: AmazonSSM.DeregisterPatchBaselineForPatchGroup
X-Amz-Date: 20180309T062043Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
```

```
}
```

Sample Response

```
{  
    "PatchGroup": "mypatchgroup",  
    "BaselineId": "pb-0c10e65780EXAMPLE"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterTargetFromMaintenanceWindow

Removes a target from a maintenance window.

Request Syntax

```
{  
    "Safe": boolean,  
    "WindowId": string,  
    "WindowTargetId": string  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Safe \(p. 102\)](#)

The system checks if the target is being referenced by a task. If the target is being referenced, the system returns an error and doesn't deregister the target from the maintenance window.

Type: Boolean

Required: No

[WindowId \(p. 102\)](#)

The ID of the maintenance window the target should be removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

[WindowTargetId \(p. 102\)](#)

The ID of the target definition to remove.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "WindowId": string,  
    "WindowTargetId": string  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

WindowId (p. 102)

The ID of the maintenance window the target was removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

WindowTargetId (p. 102)

The ID of the removed target definition.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

TargetInUseException

You specified the `Safe` option for the `DeregisterTargetFromMaintenanceWindow` operation, but the target is still referenced in a task.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DeregisterTargetFromMaintenanceWindow`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterTargetFromMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T182719Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 94

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterTaskFromMaintenanceWindow

Removes a task from a maintenance window.

Request Syntax

```
{  
    "WindowId": "string",  
    "WindowTaskId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

WindowId (p. 105)

The ID of the maintenance window the task should be removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

WindowTaskId (p. 105)

The ID of the task to remove from the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "WindowId": "string",  
    "WindowTaskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WindowId \(p. 105\)](#)

The ID of the maintenance window the task was removed from.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

[WindowTaskId \(p. 105\)](#)

The ID of the task removed from the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DeregisterTaskFromMaintenanceWindow`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DeregisterTaskFromMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T180133Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
```

```
Content-Length: 92

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeActivations

Describes details about the activation, such as the date and time the activation was created, its expiration date, the AWS Identity and Access Management (IAM) role assigned to the managed nodes in the activation, and the number of nodes registered by using this activation.

Request Syntax

```
{  
    "Filters": [  
        {  
            "FilterKey": "string",  
            "FilterValues": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 108)

A filter to view information about your activations.

Type: Array of [DescribeActivationsFilter \(p. 653\)](#) objects

Required: No

MaxResults (p. 108)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 108)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
```

```
"ActivationList": [
    {
        "ActivationId": "string",
        "CreatedDate": number,
        "DefaultInstanceName": "string",
        "Description": "string",
        "ExpirationDate": number,
        "Expired": boolean,
        "IamRole": "string",
        "RegistrationLimit": number,
        "RegistrationsCount": number,
        "Tags": [
            {
                "Key": "string",
                "Value": "string"
            }
        ]
    },
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ActivationList \(p. 108\)](#)

A list of activations for your AWS account.

Type: Array of [Activation \(p. 583\)](#) objects

[NextToken \(p. 108\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeActivations`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeActivations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T152059Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ActivationList": [
        {
            "ActivationId": "e9136c70-ba7b-4d7d-8e31-174a7EXAMPLE",
            "CreatedDate": 1581954699.792,
            "Description": "Example",
            "ExpirationDate": 1584316800,
            "Expired": true,
            "IamRole": "service-role/RoleForManagedInstances",
            "RegistrationLimit": 5,
            "RegistrationsCount": 1
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssociation

Describes the association for the specified target or managed node. If you created the association by using the Targets parameter, then you must retrieve the association by using the association ID.

Request Syntax

```
{  
    "AssociationId": "string",  
    "AssociationVersion": "string",  
    "InstanceId": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationId (p. 111)

The association ID for which you want information.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationVersion (p. 111)

Specify the association version to retrieve. To view the latest version, either specify \$LATEST for this parameter, or omit this parameter. To view a list of all associations for a managed node, use [ListAssociations \(p. 354\)](#). To get a list of versions for a specific association, use [ListAssociationVersions \(p. 358\)](#).

Type: String

Pattern: ([\\$]LATEST)|([1-9][0-9]*)

Required: No

InstanceId (p. 111)

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: No

Name (p. 111)

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\-.:/]{3,128}\$

Required: No

Response Syntax

```
{  
    "AssociationDescription": {  
        "ApplyOnlyAtCronInterval": boolean,  
        "AssociationId": "string",  
        "AssociationName": "string",  
        "AssociationVersion": "string",  
        "AutomationTargetParameterName": "string",  
        "CalendarNames": [ "string" ],  
        "ComplianceSeverity": "string",  
        "Date": number,  
        "DocumentVersion": "string",  
        "InstanceId": "string",  
        "LastExecutionDate": number,  
        "LastSuccessfulExecutionDate": number,  
        "LastUpdateAssociationDate": number,  
        "MaxConcurrency": "string",  
        "MaxErrors": "string",  
        "Name": "string",  
        "OutputLocation": {  
            "S3Location": {  
                "OutputS3BucketName": "string",  
                "OutputS3KeyPrefix": "string",  
                "OutputS3Region": "string"  
            }  
        },  
        "Overview": {  
            "AssociationStatusAggregatedCount": {  
                "string" : number  
            },  
            "DetailedStatus": "string",  
            "Status": "string"  
        },  
        "Parameters": {  
            "string" : [ "string" ]  
        },  
        "ScheduleExpression": "string",  
        "ScheduleOffset": number,  
        "Status": {  
            "AdditionalInfo": "string",  
            "Date": number,  
            "Message": "string",  
            "Name": "string"  
        },  
        "SyncCompliance": "string",  
        "TargetLocations": [  
            {  
                "Accounts": [ "string" ],  
                "ExecutionRoleName": "string",  
                "Regions": [ "string" ],  
                "TargetLocationMaxConcurrency": "string",  
                "TargetLocationMaxErrors": "string"  
            }  
        ],  
        "TargetMaps": [  
            {  
                "string" : [ "string" ]  
            }  
        ]  
    }  
}
```

```
        ],
        "Targets": [
            {
                "Key": "string",
                "Values": [ "string" ]
            }
        ]
    }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationDescription \(p. 112\)](#)

Information about the association.

Type: [AssociationDescription \(p. 588\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAssociationVersion

The version you specified isn't valid. Use `ListAssociationVersions` to view all versions of an association according to the association ID. Or, use the `$LATEST` parameter to view the latest version of the association.

HTTP Status Code: 400

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssociation`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T153423Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
        "AssociationVersion": "1",
        "ComplianceSeverity": "UNSPECIFIED",
        "Date": 1561053271.583,
        "DocumentVersion": "$DEFAULT",
        "LastExecutionDate": 1582037438.692,
        "LastSuccessfulExecutionDate": 1582037438.692,
        "LastUpdateAssociationDate": 1561053271.583,
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "AssociationStatusAggregatedCount": {
                "Success": 3
            },
            "DetailedStatus": "Success",
            "Status": "Success"
        },
        "Parameters": {
            "allowDowngrade": [
                "false"
            ],
            "version": [
                ""
            ]
        },
        "Targets": [
            {
                "Key": "tag:ssm",
                "Values": [
                    "true"
                ]
            }
        ]
    }
}
```

```
        ]  
    }  
}  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssociationExecutions

Views all executions for a specific association ID.

Request Syntax

```
{  
    "AssociationId": "string",  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Value": "string"  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationId (p. 116)

The association ID for which you want to view execution history details.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

Filters (p. 116)

Filters for the request. You can specify the following filters and values.

ExecutionId (EQUAL)

Status (EQUAL)

CreatedTime (EQUAL, GREATER_THAN, LESS_THAN)

Type: Array of [AssociationExecutionFilter \(p. 595\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

MaxResults (p. 116)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 116\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "AssociationExecutions": [  
        {  
            "AssociationId": "string",  
            "AssociationVersion": "string",  
            "CreatedTime": number,  
            "DetailedStatus": "string",  
            "ExecutionId": "string",  
            "LastExecutionDate": number,  
            "ResourceCountByStatus": "string",  
            "Status": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationExecutions \(p. 117\)](#)

A list of the executions for the specified association ID.

Type: Array of [AssociationExecution \(p. 593\)](#) objects

[NextToken \(p. 117\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssociationExecutions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociationExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T154610Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationExecutions": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "CreatedTime": 1561053271.718,
            "DetailedStatus": "Success",
            "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
            "ResourceCountByStatus": "{Success=3}",
            "Status": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAssociationExecutionTargets

Views information about a specific execution of a specific association.

Request Syntax

```
{  
    "AssociationId": "string",  
    "ExecutionId": "string",  
    "Filters": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationId (p. 120)

The association ID that includes the execution for which you want to view details.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

ExecutionId (p. 120)

The execution ID for which you want to view details.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

Filters (p. 120)

Filters for the request. You can specify the following filters and values.

Status (EQUAL)

ResourceId (EQUAL)

ResourceType (EQUAL)

Type: Array of [AssociationExecutionTargetsFilter \(p. 598\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

[MaxResults \(p. 120\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 120\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "AssociationExecutionTargets": [  
        {  
            "AssociationId": "string",  
            "AssociationVersion": "string",  
            "DetailedStatus": "string",  
            "ExecutionId": "string",  
            "LastExecutionDate": number,  
            "OutputSource": {  
                "OutputSourceId": "string",  
                "OutputSourceType": "string"  
            },  
            "ResourceId": "string",  
            "ResourceType": "string",  
            "Status": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationExecutionTargets \(p. 121\)](#)

Information about the execution.

Type: Array of [AssociationExecutionTarget \(p. 596\)](#) objects

[NextToken \(p. 121\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

AssociationExecutionDoesNotExist

The specified execution ID doesn't exist. Verify the ID number and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAssociationExecutionTargets`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAssociationExecutionTargets
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T165104Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 112

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE"
}
```

Sample Response

```
{
    "AssociationExecutionTargets": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
```

```
"DetailedStatus": "Success",
"ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
"LastExecutionDate": 1582037438.692,
"OutputSource": {
    "OutputSourceId": "1cddb1e6-2e69-40b1-ac1d-121dcEXAMPLE",
    "OutputSourceType": "RunCommand"
},
"ResourceId": "i-02573cafccEXAMPLE",
"ResourceType": "ManagedInstance",
"Status": "Success"
},
{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "AssociationVersion": "1",
    "DetailedStatus": "Success",
    "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
    "LastExecutionDate": 1581948052.198,
    "OutputSource": {
        "OutputSourceId": "b170ae99-4959-479b-ab4d-f6ae0EXAMPLE",
        "OutputSourceType": "RunCommand"
    },
    "ResourceId": "i-0471e04240EXAMPLE",
    "ResourceType": "ManagedInstance",
    "Status": "Success"
},
{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "AssociationVersion": "1",
    "DetailedStatus": "Success",
    "ExecutionId": "d6d51ef5-4eca-48ef-9d7d-bd6ceEXAMPLE",
    "LastExecutionDate": 1561053316.711,
    "OutputSource": {
        "OutputSourceId": "89cd739c-d1a5-4dc9-af4f-8b624EXAMPLE",
        "OutputSourceType": "RunCommand"
    },
    "ResourceId": "i-07782c72faEXAMPLE",
    "ResourceType": "ManagedInstance",
    "Status": "Success"
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAutomationExecutions

Provides details about all active and terminated Automation executions.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 124\)](#)

Filters used to limit the scope of executions that are requested.

Type: Array of [AutomationExecutionFilter \(p. 617\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

[MaxResults \(p. 124\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 124\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
```

```
"AutomationExecutionMetadataList": [
  {
    "AssociationId": "string",
    "AutomationExecutionId": "string",
    "AutomationExecutionStatus": "string",
    "AutomationSubtype": "string",
    "AutomationType": "string",
    "ChangeRequestName": "string",
    "CurrentAction": "string",
    "CurrentStepName": "string",
    "DocumentName": "string",
    "DocumentVersion": "string",
    "ExecutedBy": "string",
    "ExecutionEndTime": number,
    "ExecutionStartTime": number,
    "FailureMessage": "string",
    "LogFile": "string",
    "MaxConcurrency": "string",
    "MaxErrors": "string",
    "Mode": "string",
    "OpsItemId": "string",
    "Outputs": {
      "string" : [ "string" ]
    },
    "ParentAutomationExecutionId": "string",
    "ResolvedTargets": {
      "ParameterValues": [ "string" ],
      "Truncated": boolean
    },
    "Runbooks": [
      {
        "DocumentName": "string",
        "DocumentVersion": "string",
        "MaxConcurrency": "string",
        "MaxErrors": "string",
        "Parameters": {
          "string" : [ "string" ]
        },
        "TargetLocations": [
          {
            "Accounts": [ "string" ],
            "ExecutionRoleName": "string",
            "Regions": [ "string" ],
            "TargetLocationMaxConcurrency": "string",
            "TargetLocationMaxErrors": "string"
          }
        ],
        "TargetMaps": [
          {
            "string" : [ "string" ]
          }
        ],
        "TargetParameterName": "string",
        "Targets": [
          {
            "Key": "string",
            "Values": [ "string" ]
          }
        ]
      }
    ],
    "ScheduledTime": number,
    "Target": "string",
    "TargetMaps": [
      {
        "string" : [ "string" ]
      }
    ]
  }
]
```

```
        }
    ],
    "TargetParameterName": "string",
    "Targets": [
        {
            "Key": "string",
            "Values": [ "string" ]
        }
    ]
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AutomationExecutionMetadataList \(p. 124\)](#)

The list of details about each automation execution which has occurred which matches the filter specification, if any.

Type: Array of [AutomationExecutionMetadata \(p. 618\)](#) objects

[NextToken \(p. 124\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAutomationExecutions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAutomationExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T173011Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "AutomationExecutionMetadataList": [
        {
            "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE",
            "AutomationExecutionStatus": "Success",
            "AutomationType": "Local",
            "DocumentName": "Example",
            "DocumentVersion": "1",
            "ExecutedBy": "arn:aws:sts::111122223333:assumed-role/Example",
            "ExecutionEndTime": 1585062669.053,
            "ExecutionStartTime": 1585061570.827,
            "LogFile": "",
            "Mode": "Auto",
            "Outputs": {},
            "ResolvedTargets": {
                "ParameterValues": [],
                "Truncated": false
            },
            "Targets": []
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAutomationStepExecutions

Information about all active and terminated step executions in an Automation workflow.

Request Syntax

```
{  
    "AutomationExecutionId": "string",  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ReverseOrder": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AutomationExecutionId \(p. 129\)](#)

The Automation execution ID for which you want step execution descriptions.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

[Filters \(p. 129\)](#)

One or more filters to limit the number of step executions returned by the request.

Type: Array of [StepExecutionFilter \(p. 839\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Required: No

[MaxResults \(p. 129\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 129\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[ReverseOrder \(p. 129\)](#)

Indicates whether to list step executions in reverse order by start time. The default value is 'false'.

Type: Boolean

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "StepExecutions": [  
        {  
            "Action": "string",  
            "ExecutionEndTime": number,  
            "ExecutionStartTime": number,  
            "FailureDetails": {  
                "Details": {  
                    "string" : [ "string" ]  
                },  
                "FailureStage": "string",  
                "FailureType": "string"  
            },  
            "FailureMessage": "string",  
            "Inputs": {  
                "string" : "string"  
            },  
            "IsCritical": boolean,  
            "IsEnd": boolean,  
            "MaxAttempts": number,  
            "NextStep": "string",  
            "OnFailure": "string",  
            "Outputs": {  
                "string" : [ "string" ]  
            },  
            "OverriddenParameters": {  
                "string" : [ "string" ]  
            },  
            "Response": "string",  
            "ResponseCode": "string",  
            "StepExecutionId": "string",  
            "StepName": "string",  
            "StepStatus": "string",  
            "TargetLocation": {  
                "Accounts": [ "string" ],  
                "ExecutionRoleName": "string",  
                "Regions": [ "string" ],  
                "TargetLocationMaxConcurrency": "string",  
                "TargetLocationMaxErrors": "string"  
            },  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "TimeoutSeconds": number,  
            "ValidNextSteps": [ "string" ]  
        }  
    ]  
}
```

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 130)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

StepExecutions (p. 130)

A list of details about the current state of all steps that make up an execution.

Type: Array of [StepExecution](#) (p. 835) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 847).

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeAutomationStepExecutions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeAutomationStepExecutions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T180909Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
    "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE"
}
```

Sample Response

```
{
    "StepExecutions": [
        {
            "Action": "aws:createImage",
            "ExecutionEndTime": 1585062668.968,
            "ExecutionStartTime": 1585061571.144,
            "Inputs": {
                "ImageDescription": "\"AMI for i-02573cafefEXAMPLE created on
2020-03-24_14.52.51\"",
                "ImageName": "\"i-02573cafefEXAMPLE-2020-03-24_14.52.51\"",
                "InstanceId": "\"i-02573cafefEXAMPLE\"",
                "NoReboot": "false"
            },
            "OnFailure": "Abort",
            "Outputs": {
                "ImageId": [
                    "ami-0f4706cb37EXAMPLE"
                ],
                "ImageState": [
                    "available"
                ],
                "OutputPayload": [
                    "{\"ImageId\":\"ami-0f4706cb37EXAMPLE\", \"ImageState\":\"available\"}"
                ]
            },
            "OverriddenParameters": {},
            "StepExecutionId": "eff80946-356d-4128-97b2-6a0f5EXAMPLE",
            "StepName": "createImage",
            "StepStatus": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAvailablePatches

Lists all patches eligible to be included in a patch baseline.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 134\)](#)

Each element in the array is a structure containing a key-value pair.

Windows Server

Supported keys for Windows Server managed node patches include the following:

- **PATCH_SET**

Sample values: OS | APPLICATION

- **PRODUCT**

Sample values: WindowsServer2012 | Office 2010 | MicrosoftDefenderAntivirus

- **PRODUCT_FAMILY**

Sample values: Windows | Office

- **MSRC_SEVERITY**

Sample values: ServicePacks | Important | Moderate

- **CLASSIFICATION**

Sample values: ServicePacks | SecurityUpdates | DefinitionUpdates

- **PATCH_ID**

Sample values: KB123456 | KB4516046

Linux

Important

When specifying filters for Linux patches, you must specify a key-pair for PRODUCT. For example, using the AWS Command Line Interface (AWS CLI), the following command fails:

```
aws ssm describe-available-patches --filters  
Key=CVE_ID,Values=CVE-2018-3615
```

However, the following command succeeds:

```
aws ssm describe-available-patches --filters  
Key=PRODUCT,Values=AmazonLinux2018.03 Key=CVE_ID,Values=CVE-2018-3615
```

Supported keys for Linux managed node patches include the following:

- **PRODUCT**

Sample values: AmazonLinux2018.03 | AmazonLinux2.0

- **NAME**

Sample values: kernel-headers | samba-python | php

- **SEVERITY**

Sample values: Critical | Important | Medium | Low

- **EPOCH**

Sample values: 0 | 1

- **VERSION**

Sample values: 78.6.1 | 4.10.16

- **RELEASE**

Sample values: 9.56.amzn1 | 1.amzn2

- **ARCH**

Sample values: i686 | x86_64

- **REPOSITORY**

Sample values: Core | Updates

- **ADVISORY_ID**

Sample values: ALAS-2018-1058 | ALAS2-2021-1594

- **CVE_ID**

Sample values: CVE-2018-3615 | CVE-2020-1472

- **BUGZILLA_ID**

Sample values: 1463241

Type: Array of [PatchOrchestratorFilter \(p. 794\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults (p. 134)

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 134)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Patches": [  
        {  
            "AdvisoryIds": [ "string" ],  
            "Arch": "string",  
            "BugzillaIds": [ "string" ],  
            "Classification": "string",  
            "ContentUrl": "string",  
            "CVEIds": [ "string" ],  
            "Description": "string",  
            "Epoch": number,  
            "Id": "string",  
            "KbNumber": "string",  
            "Language": "string",  
            "MsrcNumber": "string",  
            "MsrcSeverity": "string",  
            "Name": "string",  
            "Product": "string",  
            "ProductFamily": "string",  
            "Release": "string",  
            "ReleaseDate": number,  
            "Repository": "string",  
            "Severity": "string",  
            "Title": "string",  
            "Vendor": "string",  
            "Version": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 136\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[Patches \(p. 136\)](#)

An array of patches. Each entry in the array is a patch structure.

Type: Array of [Patch \(p. 782\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeAvailablePatches`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 17
X-Amz-Target: AmazonSSM.DescribeAvailablePatches
X-Amz-Date: 20180308T193543Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Filters": [
        {
            "Key": "PRODUCT",
            "Values": [
                "WindowsServer2016"
            ]
        },
        {
            "Key": "CLASSIFICATION",
            "Values": [
                "SecurityUpdates"
            ]
        },
        {
            "Key": "MSRC_SEVERITY",
            "Values": [
                "Critical"
            ]
        }
    ]
}
```

Sample Response

```
{
    "Patches": [
        {
            "Classification": "SecurityUpdates",
            "ContentUrl": "https://support.microsoft.com/en-us/kb/4074588",
            "Description": "A security issue has been identified in a Microsoft software product that could affect your system. You can help protect your system by installing this update from Microsoft. For a complete listing of the issues
```

```
that are included in this update, see the associated Microsoft Knowledge Base article. After you install this update, you may have to restart your system.",  
"Id": "11adea10-0701-430e-954f-9471595ae246",  
"KbNumber": "KB4074588",  
"Language": "All",  
"MsrcNumber": "",  
"MsrcSeverity": "Critical",  
"Product": "WindowsServer2016",  
"ProductFamily": "Windows",  
"ReleaseDate": 1518548400,  
"Title": "2018-02 Cumulative Update for Windows Server 2016 (1709) for x64-based Systems (KB4074588)",  
"Vendor": "Microsoft"  
},  
{  
    "Classification": "SecurityUpdates",  
    "ContentUrl": "https://support.microsoft.com/en-us/kb/4074590",  
    "Description": "A security issue has been identified in a Microsoft software product that could affect your system. You can help protect your system by installing this update from Microsoft. For a complete listing of the issues that are included in this update, see the associated Microsoft Knowledge Base article. After you install this update, you may have to restart your system.",  
    "Id": "f5f58231-ac5d-4640-ab1b-9dc8d857c265",  
    "KbNumber": "KB4074590",  
    "Language": "All",  
    "MsrcNumber": "",  
    "MsrcSeverity": "Critical",  
    "Product": "WindowsServer2016",  
    "ProductFamily": "Windows",  
    "ReleaseDate": 1518544805,  
    "Title": "2018-02 Cumulative Update for Windows Server 2016 for x64-based Systems (KB4074590)",  
    "Vendor": "Microsoft"  
},  
{  
    "Classification": "SecurityUpdates",  
    "ContentUrl": "https://support.microsoft.com/en-us/kb/4074595",  
    "Description": "A security issue has been identified in a Microsoft software product that could affect your system. You can help protect your system by installing this update from Microsoft. For a complete listing of the issues that are included in this update, see the associated Microsoft Knowledge Base article. After you install this update, you may have to restart your system.",  
    "Id": "754b5889-2e01-40cc-8833-edf86b35541f",  
    "KbNumber": "KB4074595",  
    "Language": "All",  
    "MsrcNumber": "",  
    "MsrcSeverity": "Critical",  
    "Product": "WindowsServer2016",  
    "ProductFamily": "Windows",  
    "ReleaseDate": 1517965209,  
    "Title": "2018-02 Security Update for Adobe Flash Player for Windows Server 2016 for x64-based Systems (KB4074595)",  
    "Vendor": "Microsoft"  
}  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDocument

Describes the specified AWS Systems Manager document (SSM document).

Request Syntax

```
{  
    "DocumentVersion": "string",  
    "Name": "string",  
    "VersionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentVersion \(p. 140\)](#)

The document version for which you want information. Can be a specific version or the default version.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

[Name \(p. 140\)](#)

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

Required: Yes

[VersionName \(p. 140\)](#)

An optional field specifying the version of the artifact associated with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{1,128}\$

Required: No

Response Syntax

```
{  
    "Document": {  
        "ApprovedVersion": "string",  
    },  
    "...
```

```

"AttachmentsInformation": [
    {
        "Name": "string"
    }
],
"Author": "string",
"Category": [ "string" ],
"CategoryEnum": [ "string" ],
"CreatedDate": number,
"DefaultVersion": "string",
"Description": "string",
"DisplayName": "string",
"DocumentFormat": "string",
"DocumentType": "string",
"DocumentVersion": "string",
"Hash": "string",
"HashType": "string",
"LatestVersion": "string",
"Name": "string",
"Owner": "string",
"Parameters": [
    {
        "DefaultValue": "string",
        "Description": "string",
        "Name": "string",
        "Type": "string"
    }
],
"PendingReviewVersion": "string",
"PlatformTypes": [ "string" ],
"Requires": [
    {
        "Name": "string",
        "Version": "string"
    }
],
"ReviewInformation": [
    {
        "ReviewedTime": number,
        "Reviewer": "string",
        "Status": "string"
    }
],
"ReviewStatus": "string",
"SchemaVersion": "string",
"Sha1": "string",
"Status": "string",
"StatusInformation": "string",
"Tags": [
    {
        "Key": "string",
        "Value": "string"
    }
],
"TargetType": "string",
"VersionName": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Document (p. 140)

Information about the SSM document.

Type: [DocumentDescription \(p. 655\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeDocument`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T182134Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 23

{
    "Name": "Example"
}
```

Sample Response

```
{
    "Document": {
        "CreatedDate": 1585061514.204,
        "DefaultVersion": "1",
```

```
"Description": "Example",
"DocumentFormat": "YAML",
"DocumentType": "Automation",
"DocumentVersion": "1",
"DisplayName": "ExampleDoc",
"Hash": "68b196e538f5a895f87a0cc15eb74614021f44b47329aa95ccc0f4f71EXAMPLE",
"HashType": "Sha256",
"LatestVersion": "1",
"Name": "Example",
"Owner": "111122223333",
"Parameters": [
    {
        "DefaultValue": "",
        "Description": "(Required) The ARN of the role that allows Automation to
perform the actions on your behalf. If no role is specified, Systems Manager Automation
uses your IAM permissions to execute this document.",
        "Name": "AutomationAssumeRole",
        "Type": "String"
    },
    {
        "DefaultValue": "",
        "Description": "(Required) The Instance Id to create an image of.",
        "Name": "InstanceId",
        "Type": "String"
    }
],
"PlatformTypes": [
    "Windows",
    "Linux"
],
"SchemaVersion": "0.3",
"Status": "Active",
"Tags": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDocumentPermission

Describes the permissions for a AWS Systems Manager document (SSM document). If you created the document, you are the owner. If a document is shared, it can either be shared privately (by specifying a user's AWS account ID) or publicly (*All*).

Request Syntax

```
{  
    "MaxResults": number,  
    "Name": "string",  
    "NextToken": "string",  
    "PermissionType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 144)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 200.

Required: No

Name (p. 144)

The name of the document for which you are the owner.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: Yes

NextToken (p. 144)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

PermissionType (p. 144)

The permission type for the document. The permission type can be *Share*.

Type: String

Valid Values: *Share*

Required: Yes

Response Syntax

```
{  
    "AccountIds": [ "string" ],  
    "AccountSharingInfoList": [  
        {  
            "AccountId": "string",  
            "SharedDocumentVersion": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountIds (p. 145)

The account IDs that have permission to use this document. The ID can be either an AWS account or *All*.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: (?i)all|[0-9]{12}

AccountSharingInfoList (p. 145)

A list of AWS accounts where the current document is shared and the version shared with each account.

Type: Array of [AccountSharingInfo \(p. 582\)](#) objects

NextToken (p. 145)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidPermissionType

The permission type isn't supported. *Share* is the only supported permission type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeDocumentPermission`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeDocumentPermission
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T182653Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "Name": "Example",
    "PermissionType": "Share"
}
```

Sample Response

```
{
    "AccountIds": [],
    "AccountSharingInfoList": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeEffectiveInstanceAssociations

All associations for the managed node(s).

Request Syntax

```
{  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

InstanceId (p. 148)

The managed node ID for which you want to view all associations.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: Yes

MaxResults (p. 148)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

NextToken (p. 148)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "Associations": [  
        {  
            "AssociationId": "string",  
            "AssociationVersion": "string",  
            "Content": "string",  
            "InstanceId": "string"
```

```
        },
        "NextToken": "string"
    }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Associations \(p. 148\)](#)

The associations for the requested managed node.

Type: Array of [InstanceAssociation \(p. 679\)](#) objects

[NextToken \(p. 148\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeEffectiveInstanceAssociations`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeEffectiveInstanceAssociations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200326T144721Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200326/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37

{
    "InstanceId": "i-02573cafccEXAMPLE"
}
```

Sample Response

```
{
    "Associations": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "InstanceId": "i-02573cafccEXAMPLE",
            "Content": "{\n                \"schemaVersion\": \"1.2\",\\n                \"description\": \"Update\nthe Amazon SSM Agent to the latest version or specified version.\",\\n--truncated--",
            "AssociationVersion": "1"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeEffectivePatchesForPatchBaseline

Retrieves the current effective patches (the patch and the approval state) for the specified patch baseline. Applies to patch baselines for Windows only.

Request Syntax

```
{  
    "BaselineId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 151)

The ID of the patch baseline to retrieve the effective patches for.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Required: Yes

MaxResults (p. 151)

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 151)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "EffectivePatches": [  
        {  
            "Patch": {  
                "ApprovalStatus": "string",  
                "BaselineId": "string",  
                "BaselineVersion": "string",  
                "LastModified": "string",  
                "PatchArn": "string",  
                "PatchFamily": "string",  
                "PatchId": "string",  
                "PatchName": "string",  
                "PatchType": "string",  
                "Severity": "string",  
                "Status": "string",  
                "Title": "string",  
                "Type": "string"  
            }  
        }  
    ]  
}
```

```
        "AdvisoryIds": [ "string" ],
        "Arch": "string",
        "BugzillaIds": [ "string" ],
        "Classification": "string",
        "ContentUrl": "string",
        "CVEIds": [ "string" ],
        "Description": "string",
        "Epoch": number,
        "Id": "string",
        "KbNumber": "string",
        "Language": "string",
        "MsrcNumber": "string",
        "MsrcSeverity": "string",
        "Name": "string",
        "Product": "string",
        "ProductFamily": "string",
        "Release": "string",
        "ReleaseDate": number,
        "Repository": "string",
        "Severity": "string",
        "Title": "string",
        "Vendor": "string",
        "Version": "string"
    },
    "PatchStatus": {
        "ApprovalDate": number,
        "ComplianceLevel": "string",
        "DeploymentStatus": "string"
    }
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EffectivePatches \(p. 151\)](#)

An array of patches and patch status.

Type: Array of [EffectivePatch \(p. 675\)](#) objects

[NextToken \(p. 151\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

UnsupportedOperatingSystem

The operating systems you specified isn't supported, or the operation isn't supported for the operating system.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeEffectivePatchesForPatchBaseline`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.DescribeEffectivePatchesForPatchBaseline
X-Amz-Date: 20180309T061447Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "EffectivePatches": [
        {
            "Patch": {
                "Classification": "SecurityUpdates",
                "ContentUrl": "https://support.microsoft.com/en-us/kb/2032276",
                "Description": "A security issue has been identified that could allow an unauthenticated remote attacker to compromise your system and gain control over it. You can help protect your system by installing this update from Microsoft. After you install this update, you may have to restart your system."
            }
        }
    ]
}
```

```
        "Id": "8692029b-a3a2-4a87-a73b-8ea881b4b4d6",
        "KbNumber": "KB2032276",
        "Language": "All",
        "MsrcNumber": "MS10-043",
        "MsrcSeverity": "Important",
        "Product": "WindowsServer2008R2",
        "ProductFamily": "Windows",
        "ReleaseDate": 1279040400,
        "Title": "Security Update for Windows Server 2008 R2 x64 Edition
(KB2032276)",
        "Vendor": "Microsoft"
    },
    "PatchStatus": {
        "ApprovalDate": 1279299600,
        "ComplianceLevel": "UNSPECIFIED",
        "DeploymentStatus": "APPROVED"
    }
},
{
    "Patch": {
        "Classification": "SecurityUpdates",
        "ContentUrl": "https://support.microsoft.com/en-us/kb/2124261",
        "Description": "A security issue has been identified that could allow an unauthenticated remote attacker to compromise your system and gain control over it. You can help protect your system by installing this update from Microsoft. After you install this update, you may have to restart your
system.",
        "Id": "12ef1bed-0dd2-4633-b3ac-60888aa8ba33",
        "KbNumber": "KB2124261",
        "Language": "All",
        "MsrcNumber": "MS10-065",
        "MsrcSeverity": "Important",
        "Product": "Windows7",
        "ProductFamily": "Windows",
        "ReleaseDate": 1284483600,
        "Title": "Security Update for Windows 7 (KB2124261)",
        "Vendor": "Microsoft"
    },
    "PatchStatus": {
        "ApprovalDate": 1284742800,
        "ComplianceLevel": "UNSPECIFIED",
        "DeploymentStatus": "APPROVED"
    }
},
{
    "Patch": {
        "Classification": "SecurityUpdates",
        "ContentUrl": "https://support.microsoft.com/en-us/kb/2124261",
        "Description": "A security issue has been identified that could allow an unauthenticated remote attacker to compromise your system and gain control over it. You can help protect your system by installing this update from Microsoft. After you install this update, you may have to restart your
system.",
        "Id": "1b571637-30ed-48d6-b2f3-24d374fdebb8",
        "KbNumber": "KB2124261",
        "Language": "All",
        "MsrcNumber": "MS10-065",
        "MsrcSeverity": "Important",
        "Product": "WindowsServer2008R2",
        "ProductFamily": "Windows",
        "ReleaseDate": 1284483600,
        "Title": "Security Update for Windows Server 2008 R2 x64 Edition
(KB2124261)",
        "Vendor": "Microsoft"
    },
    "PatchStatus": {
```

```
        "ApprovalDate": 1284742800,
        "ComplianceLevel": "UNSPECIFIED",
        "DeploymentStatus": "APPROVED"
    }
}
// There may be more content here
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInstanceAssociationsStatus

The status of the associations for the managed node(s).

Request Syntax

```
{  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

InstanceId (p. 156)

The managed node IDs for which you want association status information.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: Yes

MaxResults (p. 156)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 156)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "InstanceAssociationStatusInfos": [  
        {  
            "AssociationId": "string",  
            "AssociationName": "string",  
            "AssociationVersion": "string",  
            "DetailedStatus": "string",  
            "LastSynced": "string",  
            "LastSyncError": "string",  
            "LastSyncTime": "string",  
            "Status": "string",  
            "StatusDetails": "string",  
            "SyncToken": "string"  
        }  
    ]  
}
```

```
"DocumentVersion": "string",
"ErrorCode": "string",
"ExecutionDate": number,
"ExecutionSummary": "string",
"InstanceId": "string",
"Name": "string",
"OutputUrl": {
    "S3OutputUrl": {
        "OutputUrl": "string"
    }
},
"Status": "string"
},
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InstanceAssociationStatusInfos \(p. 156\)](#)

Status information about the association.

Type: Array of [InstanceAssociationStatusInfo \(p. 682\)](#) objects

[NextToken \(p. 156\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInstanceAssociationsStatus`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInstanceAssociationsStatus
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T185152Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 37

{
    "InstanceId": "i-02573cafccEXAMPLE"
}
```

Sample Response

```
{
    "InstanceAssociationStatusInfos": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "DetailedStatus": "Success",
            "DocumentVersion": "1",
            "ExecutionDate": 1581948052.198,
            "InstanceId": "i-02573cafccEXAMPLE",
            "Name": "AWS-UpdateSSMAgent",
            "Status": "Success"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

DescribeInstanceInformation

Describes one or more of your managed nodes, including information about the operating system platform, the version of SSM Agent installed on the managed node, node status, and so on.

If you specify one or more managed node IDs, it returns information for those managed nodes. If you don't specify node IDs, it returns information for all your managed nodes. If you specify a node ID that isn't valid or a node that you don't own, you receive an error.

Note

The `IamRole` field for this API operation is the AWS Identity and Access Management (IAM) role assigned to on-premises managed nodes. This call doesn't return the IAM role for EC2 instances.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "InstanceInformationFilterList": [  
        {  
            "key": "string",  
            "valueSet": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 160\)](#)

One or more filters. Use a filter to return a more specific list of managed nodes. You can filter based on tags applied to EC2 instances. Use this `Filters` data type instead of `InstanceInformationFilterList`, which is deprecated.

Type: Array of [InstanceInformationStringFilter \(p. 690\)](#) objects

Array Members: Minimum number of 0 items.

Required: No

[InstanceInformationFilterList \(p. 160\)](#)

This is a legacy method. We recommend that you don't use this method. Instead, use the `Filters` data type. `Filters` enables you to return node information by filtering based on tags applied to managed nodes.

Note

Attempting to use `InstanceInformationFilterList` and `Filters` leads to an exception error.

Type: Array of [InstanceInformationFilter \(p. 689\)](#) objects

Array Members: Minimum number of 0 items.

Required: No

[MaxResults \(p. 160\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 50.

Required: No

[NextToken \(p. 160\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "InstanceInformationList": [  
        {  
            "ActivationId": "string",  
            "AgentVersion": "string",  
            "AssociationOverview": {  
                "DetailedStatus": "string",  
                "InstanceAssociationStatusAggregatedCount": {  
                    "string" : number  
                }  
            },  
            "AssociationStatus": "string",  
            "ComputerName": "string",  
            "IamRole": "string",  
            "InstanceId": "string",  
            "IPAddress": "string",  
            "IsLatestVersion": boolean,  
            "LastAssociationExecutionDate": number,  
            "LastPingDateTime": number,  
            "LastSuccessfulAssociationExecutionDate": number,  
            "Name": "string",  
            "PingStatus": "string",  
            "PlatformName": "string",  
            "PlatformType": "string",  
            "PlatformVersion": "string",  
            "RegistrationDate": number,  
            "ResourceType": "string",  
            "SourceId": "string",  
            "SourceType": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceInformationList (p. 161)

The managed node information list.

Type: Array of [InstanceInformation \(p. 685\)](#) objects

NextToken (p. 161)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidInstanceInformationFilterValue

The specified filter value isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInstanceInformation`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInstanceInformation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200220T234247Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 72

{
    "Filters": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-02573cafefEXAMPLE"
            ]
        }
    ]
}
```

Sample Response

```
{
    "InstanceInformationList": [
        {
            "AgentVersion": "2.3.871.0",
            "AssociationOverview": {
                "DetailedStatus": "Failed",
                "InstanceAssociationStatusAggregatedCount": {
                    "Failed": 1,
                    "Success": 1
                }
            },
            "AssociationStatus": "Failed",
            "ComputerName": "WIN-11RMS222RPK.WORKGROUP",
            "IPAddress": "203.0.113.0",
            "InstanceId": "i-02573cafefEXAMPLE",
            "IsLatestVersion": false,
            "LastAssociationExecutionDate": 1582242019,
            "LastPingDateTime": 1582242018.094,
            "PingStatus": "Online",
            "PlatformName": "Microsoft Windows Server 2008 R2 Datacenter",
            "PlatformType": "Windows",
            "PlatformVersion": "6.1.7601",
            "ResourceType": "EC2Instance"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInstancePatches

Retrieves information about the patches on the specified managed node and their state relative to the patch baseline being used for the node.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 165\)](#)

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribeInstancePatches` include the following:

- **Classification**

Sample values: Security | SecurityUpdates

- **KBId**

Sample values: KB4480056 | java-1.7.0-openjdk.x86_64

- **Severity**

Sample values: Important | Medium | Low

- **State**

Sample values: Installed | InstalledOther | InstalledPendingReboot

Type: Array of [PatchOrchestratorFilter \(p. 794\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[InstanceId \(p. 165\)](#)

The ID of the managed node whose patch state information should be retrieved.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: Yes

[MaxResults \(p. 165\)](#)

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 165\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Patches": [  
        {  
            "Classification": "string",  
            "CVEIds": "string",  
            "InstalledTime": number,  
            "KBId": "string",  
            "Severity": "string",  
            "State": "string",  
            "Title": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 166\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[Patches \(p. 166\)](#)

Each entry in the array is a structure containing:

- Title (string)
- KBId (string)
- Classification (string)
- Severity (string)
- State (string, such as "INSTALLED" or "FAILED")
- InstalledTime (DateTime)

- `InstalledBy` (string)

Type: Array of [PatchComplianceData \(p. 788\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInstancePatches`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 37
X-Amz-Target: AmazonSSM.DescribeInstancePatches
X-Amz-Date: 20180308T205131Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
{
```

```
    "InstanceId": "i-02573cafccEXAMPLE"
}
```

Sample Response

```
{
  "Patches": [
    {
      "Title": "NetworkManager.x86_64:1:1.30.0-7.el8",
      "KBId": "NetworkManager.x86_64",
      "Classification": "Security",
      "Severity": "Moderate",
      "State": "Installed",
      "InstalledTime": "2021-05-19T10:03:07-07:00"
    },
    {
      "Title": "bash.x86_64:0:4.4.19-14.el8",
      "KBId": "bash.x86_64",
      "Classification": "Security",
      "Severity": "Low",
      "State": "Installed",
      "InstalledTime": "2021-05-19T10:03:25-07:00"
    },
    {
      "Title": "kernel-modules.x86_64:0:4.18.0-305.10.2.el8_4",
      "KBId": "kernel-modules.x86_64",
      "Classification": "Security",
      "Severity": "Important",
      "State": "Installed",
      "InstalledTime": "2021-08-04T10:45:42-07:00"
    }
    // There may be more content here
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInstancePatchStates

Retrieves the high-level patch state of one or more managed nodes.

Request Syntax

```
{  
    "InstanceIds": [ "string" ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[InstanceIds \(p. 169\)](#)

The ID of the managed node for which patch state information should be retrieved.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: Yes

[MaxResults \(p. 169\)](#)

The maximum number of managed nodes to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 169\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "InstancePatchStates": [  
        {  
            "BaselineId": "string",  
            "PatchStates": [  
                {  
                    "BaselineId": "string",  
                    "PatchName": "string",  
                    "PatchStatus": "string",  
                    "PatchVersion": "string",  
                    "Status": "string",  
                    "StatusReason": "string",  
                    "StatusReasonCode": "string",  
                    "StatusMessage": "string",  
                    "StatusTimestamp": "string",  
                    "StatusType": "string",  
                    "StatusUpdateCount": number  
                }  
            ]  
        }  
    ]  
}
```

```
    "CriticalNonCompliantCount": number,
    "FailedCount": number,
    "InstalledCount": number,
    "InstalledOtherCount": number,
    "InstalledPendingRebootCount": number,
    "InstalledRejectedCount": number,
    "InstallOverrideList": "string",
    "InstanceId": "string",
    "LastNoRebootInstallOperationTime": number,
    "MissingCount": number,
    "NotApplicableCount": number,
    "Operation": "string",
    "OperationEndTime": number,
    "OperationStartTime": number,
    "OtherNonCompliantCount": number,
    "OwnerInformation": "string",
    "PatchGroup": "string",
    "RebootOption": "string",
    "SecurityNonCompliantCount": number,
    "SnapshotId": "string",
    "UnreportedNotApplicableCount": number
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InstancePatchStates \(p. 169\)](#)

The high-level patch state for the requested managed nodes.

Type: Array of [InstancePatchState \(p. 691\)](#) objects

[NextToken \(p. 169\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInstancePatchStates`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 40
X-Amz-Target: AmazonSSM.DescribeInstancePatchStates
X-Amz-Date: 20180308T202310Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "InstanceIds": [
        "i-02573cafccEXAMPLE"
    ]
}
```

Sample Response

```
{
    "InstancePatchStates": [
        {
            "InstanceId": "i-02573cafccEXAMPLE",
            "PatchGroup": "mypatchgroup",
            "BaselineId": "pb-0c10e65780EXAMPLE",
            "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
            "CriticalNonCompliantCount": 2,
            "SecurityNonCompliantCount": 2,
            "OtherNonCompliantCount": 1,
            "InstalledCount": 123,
            "InstalledOtherCount": 334,
            "InstalledPendingRebootCount": 0,
            "InstalledRejectedCount": 0,
            "MissingCount": 1,
            "FailedCount": 2,
            "UnreportedNotApplicableCount": 11,
            "NotApplicableCount": 2063,
            "OperationStartTime": "2021-05-03T11:00:56-07:00",
            "OperationEndTime": "2021-05-03T11:01:09-07:00",
            "Operation": "Scan",
            "LastNoRebootInstallOperationTime": "2020-06-14T12:17:41-07:00",
            "RebootOption": "RebootIfNeeded"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInstancePatchStatesForPatchGroup

Retrieves the high-level patch state for the managed nodes in the specified patch group.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "PatchGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 173\)](#)

Each entry in the array is a structure containing:

- Key (string between 1 and 200 characters)
- Values (array containing a single string)
- Type (string "Equal", "NotEqual", "LessThan", "GreaterThan")

Type: Array of [InstancePatchStateFilter \(p. 696\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 4 items.

Required: No

[MaxResults \(p. 173\)](#)

The maximum number of patches to return (per page).

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 173\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[PatchGroup \(p. 173\)](#)

The name of the patch group for which the patch state information should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@]*)\$

Required: Yes

Response Syntax

```
{  
    "InstancePatchStates": [  
        {  
            "BaselineId": "string",  
            "CriticalNonCompliantCount": number,  
            "FailedCount": number,  
            "InstalledCount": number,  
            "InstalledOtherCount": number,  
            "InstalledPendingRebootCount": number,  
            "InstalledRejectedCount": number,  
            "InstallOverrideList": "string",  
            "InstanceId": "string",  
            "LastNoRebootInstallOperationTime": number,  
            "MissingCount": number,  
            "NotApplicableCount": number,  
            "Operation": "string",  
            "OperationEndTime": number,  
            "OperationStartTime": number,  
            "OtherNonCompliantCount": number,  
            "OwnerInformation": "string",  
            "PatchGroup": "string",  
            "RebootOption": "string",  
            "SecurityNonCompliantCount": number,  
            "SnapshotId": "string",  
            "UnreportedNotApplicableCount": number  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InstancePatchStates \(p. 174\)](#)

The high-level patch state for the requested managed nodes.

Type: Array of [InstancePatchState \(p. 691\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

[NextToken \(p. 174\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInstancePatchStatesForPatchGroup`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 33
X-Amz-Target: AmazonSSM.DescribeInstancePatchStatesForPatchGroup
X-Amz-Date: 20180308T204541Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup"
}
```

Sample Response

```
{
    "InstancePatchStates": [
        {
            "InstanceId": "i-02573cafccEXAMPLE",
            "PatchGroup": "mypatchgroup",
            "BaselineId": "pb-0c10e65780EXAMPLE",
            "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
            "OwnerInformation": "",
            "InstalledCount": 32,
            "InstalledOtherCount": 1,
            "InstalledPendingRebootCount": 0,
```

```
"InstalledRejectedCount": 0,  
"MissingCount": 2,  
"FailedCount": 0,  
"UnreportedNotApplicableCount": 2671,  
"NotApplicableCount": 400,  
"OperationStartTime": "2021-08-04T11:03:50.590000-07:00",  
"OperationEndTime": "2021-08-04T11:04:21.555000-07:00",  
"Operation": "Scan",  
"RebootOption": "NoReboot",  
"CriticalNonCompliantCount": 0,  
"SecurityNonCompliantCount": 1,  
"OtherNonCompliantCount": 0  
},  
{  
  
    "InstanceId": "i-0471e04240EXAMPLE",  
    "PatchGroup": "mypatchgroup",  
    "BaselineId": "pb-09ca3fb51fEXAMPLE",  
    "SnapshotId": "05d8ffb0-1bbe-4812-ba2d-d9b7bEXAMPLE",  
    "OwnerInformation": "",  
    "InstalledCount": 45,  
    "InstalledOtherCount": 3,  
    "InstalledPendingRebootCount": 1,  
    "InstalledRejectedCount": 0,  
    "MissingCount": 2,  
    "FailedCount": 1,  
    "UnreportedNotApplicableCount": 3154,  
    "NotApplicableCount": 321,  
    "OperationStartTime": "2021-08-04T11:04:30.290000-07:00",  
    "OperationEndTime": "2021-08-04T11:04:49.255000-07:00",  
    "Operation": "Scan",  
    "RebootOption": "NoReboot",  
    "CriticalNonCompliantCount": 0,  
    "SecurityNonCompliantCount": 2,  
    "OtherNonCompliantCount": 1  
}  
    // There may be more content here  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInventoryDeletions

Describes a specific delete inventory operation.

Request Syntax

```
{  
    "DeletionId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

DeletionId (p. 177)

Specify the delete inventory ID for which you want information. This ID was returned by the `DeleteInventory` operation.

Type: String

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

MaxResults (p. 177)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 177)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "InventoryDeletions": [  
        {  
            "DeletionId": "string",  
            "Status": "string",  
            "Timestamp": "string"  
        }  
    ]  
}
```

```
"DeletionStartTime": number,
"DeletionSummary": {
    "RemainingCount": number,
    "SummaryItems": [
        {
            "Count": number,
            "RemainingCount": number,
            "Version": "string"
        }
    ],
    "TotalCount": number
},
"LastStatus": "string",
"LastStatusMessage": "string",
"LastStatusUpdateTime": number,
"TypeName": "string"
},
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InventoryDeletions \(p. 177\)](#)

A list of status items for deleted inventory.

Type: Array of [InventoryDeletionStatusItem \(p. 699\)](#) objects

[NextToken \(p. 177\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDeleteIdException

The ID specified for the delete operation doesn't exist or isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeInventoryDeletions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeInventoryDeletions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.25 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
ssm.describe-inventory-deletions
X-Amz-Date: 20210810T211220Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210810/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2

{}
```

Sample Response

```
{
    "InventoryDeletions": [
        {
            "DeletionId": "5bc2ba3b-ee6a-40fa-8d09-5eExample",
            "DeletionStartTime": 1628550146,
            "DeletionSummary": {
                "RemainingCount": 0,
                "SummaryItems": [
                    {
                        "Count": 1,
                        "RemainingCount": 0,
                        "Version": "1.0"
                    }
                ],
                "TotalCount": 1
            },
            "LastStatus": "Complete",
            "LastStatusMessage": "Deletion is successful",
            "LastStatusUpdateTime": 1628550238,
            "TypeName": "Custom:RackInfo"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowExecutions

Lists the executions of a maintenance window. This includes information about when the maintenance window was scheduled to be active, and information about tasks registered and run with the maintenance window.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 181\)](#)

Each entry in the array is a structure containing:

- Key. A string between 1 and 128 characters. Supported keys include `ExecutedBefore` and `ExecutedAfter`.
- Values. An array of strings, each between 1 and 256 characters. Supported values are date/time strings in a valid ISO 8601 date/time format, such as `2021-11-04T05:00:00Z`.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 181\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 181\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[WindowId \(p. 181\)](#)

The ID of the maintenance window whose executions should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "WindowExecutions": [  
        {  
            "EndTime": number,  
            "StartTime": number,  
            "Status": "string",  
            "StatusDetails": "string",  
            "WindowExecutionId": "string",  
            "WindowId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 182\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[WindowExecutions \(p. 182\)](#)

Information about the maintenance window executions.

Type: Array of [MaintenanceWindowExecution \(p. 715\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowExecutions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutions
X-Amz-Date: 20180312T204551Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "NextToken": "AAEABbrXFUcgJpmXZxxu+AD17F+5bzlsAyqrig1EXAMPLE...pYY",
    "WindowExecutions": [
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "6027b513-64fe-4cf0-be7d-1191aEXAMPLE",
            "Status": "IN_PROGRESS",
            "StartTime": "2021-08-04T11:00:00.000000-07:00"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "ff75b750-4834-4377-8f61-b3cadEXAMPLE",
            "Status": "SUCCESS",
            "StartTime": "2021-08-03T11:00:00.000000-07:00",
            "EndTime": "2021-08-03T11:37:21.450000-07:00"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE",
            "Status": "FAILED",
            "StatusDetails": "One or more tasks in the orchestration failed.",
            "StartTime": "2021-08-02T11:00:00.000000-07:00",
            "EndTime": "2021-08-02T11:22:36.190000-07:00"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowExecutionTaskInvocations

Retrieves the individual task executions (one per target) for a particular task run as part of a maintenance window execution.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "TaskId": "string",  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 185\)](#)

Optional filters used to scope down the returned task invocations. The supported filter key is STATUS with the corresponding values PENDING, IN_PROGRESS, SUCCESS, FAILED, TIMED_OUT, CANCELLING, and CANCELLED.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 185\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 185\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[TaskId \(p. 185\)](#)

The ID of the specific task in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

[WindowExecutionId \(p. 185\)](#)

The ID of the maintenance window execution the task is part of.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "WindowExecutionTaskInvocationIdentities": [  
        {  
            "EndTime": number,  
            "ExecutionId": "string",  
            "InvocationId": "string",  
            "OwnerInformation": "string",  
            "Parameters": "string",  
            "StartTime": number,  
            "Status": "string",  
            "StatusDetails": "string",  
            "TaskExecutionId": "string",  
            "TaskType": "string",  
            "WindowExecutionId": "string",  
            "WindowTargetId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 186\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[WindowExecutionTaskInvocationIdentities \(p. 186\)](#)

Information about the task invocation results per invocation.

Type: Array of [MaintenanceWindowExecutionTaskInvocationIdentity \(p. 719\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowExecutionTaskInvocations`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutionTaskInvocations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200224T233800Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 111

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
    "TaskId": "0c9ac961-daf4-4a94-b6c7-1bef3EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionTaskInvocationIdentities": [
        {
            "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
            "TaskExecutionId": "0c9ac961-daf4-4a94-b6c7-1bef3EXAMPLE",
            "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE",
            "ExecutionId": "1203cf98-5a79-4ec3-97e9-12e0bEXAMPLE",
            "TaskType": "RUN_COMMAND",
```

```
    "Parameters": "{\"comment\": \"\", \"documentName\": \"AWS-ApplyPatchBaseline\", \"instanceIds\": [\"i-00ec29b21eEXAMPLE\", \"i-09911ddd90EXAMPLE\"], \"maxConcurrency\": \"1\", \"maxErrors\": \"1\", \"parameters\": {\"SnapshotId\": [\"\"], \"Operation\": [\"Install\"]}, \"timeoutSeconds\": 600}”,  
    “Status”: “SUCCESS”,  
    “StatusDetails”: “Success”,  
    “StartTime”: “2021-08-04T11:35:35.170000-07:00”,  
    “EndTime”: “2021-08-04T11:42:11.330000-07:00”  
}  
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowExecutionTasks

For a given maintenance window execution, lists the tasks that were run.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 189)

Optional filters used to scope down the returned tasks. The supported filter key is STATUS with the corresponding values PENDING, IN_PROGRESS, SUCCESS, FAILED, TIMED_OUT, CANCELLING, and CANCELLED.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults (p. 189)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken (p. 189)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowExecutionId (p. 189)

The ID of the maintenance window execution whose task executions should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "WindowExecutionTaskIdentities": [  
        {  
            "EndTime": number,  
            "StartTime": number,  
            "Status": "string",  
            "StatusDetails": "string",  
            "TaskArn": "string",  
            "TaskExecutionId": "string",  
            "TaskType": "string",  
            "WindowExecutionId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 190\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[WindowExecutionTaskIdentities \(p. 190\)](#)

Information about the task executions.

Type: Array of [MaintenanceWindowExecutionTaskIdentity \(p. 717\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowExecutionTasks`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowExecutionTasks
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200224T234903Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 61

{
    "WindowExecutionId": "a06e9f91-3b9c-4c3e-8bd4-246ccEXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionTaskIdentities": [
        {
            "WindowExecutionId": "a06e9f91-3b9c-4c3e-8bd4-246ccEXAMPLE",
            "TaskExecutionId": "f407ba63-998f-4b89-8467-279fcEXAMPLE",
            "Status": "SUCCESS",
            "StartTime": "2021-08-04T11:35:35.145000-07:00",
            "EndTime": "2021-08-04T11:38:09.062000-07:00",
            "TaskArn": "AWS-RunPatchBaseline",
            "TaskType": "RUN_COMMAND"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindows

Retrieves the maintenance windows in an AWS account.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 193\)](#)

Optional filters used to narrow down the scope of the returned maintenance windows. Supported filter keys are `Name` and `Enabled`. For example, `Name=MyMaintenanceWindow` and `Enabled=True`.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 193\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

[NextToken \(p. 193\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"WindowIdentities": [
    {
        "Cutoff": number,
        "Description": "string",
        "Duration": number,
        "Enabled": boolean,
        "EndDate": "string",
        "Name": "string",
        "NextExecutionTime": "string",
        "Schedule": "string",
        "ScheduleOffset": number,
        "ScheduleTimezone": "string",
        "StartDate": "string",
        "WindowId": "string"
    }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 193\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[WindowIdentities \(p. 193\)](#)

Information about the maintenance windows.

Type: Array of [MaintenanceWindowIdentity \(p. 723\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindows`.

[Sample Request](#)

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindows
X-Amz-Date: 20180312T202609Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Filters": [
        {
            "Values": [
                "true"
            ],
            "Key": "Enabled"
        }
    ]
}
```

Sample Response

```
{
    "WindowIdentities": [
        {
            "WindowId": "mw-0c5ed765acEXAMPLE",
            "Name": "Windows-Testing-Maintenance-Window",
            "Description": "Standard maintenance windows for Test Servers",
            "Enabled": true,
            "Duration": 6,
            "Cutoff": 2,
            "Schedule": "rate(2 weeks)",
            "NextExecutionTime": "2020-02-24T23:52:15.099Z"
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "Name": "Windows-Staging-Maintenance-Window",
            "Description": "Standard maintenance windows for Staging Servers",
            "Enabled": true,
            "Duration": 10,
            "Cutoff": 4,
            "Schedule": "cron(0 0 6 ? * MON *)",
            "NextExecutionTime": "2020-03-02T06:00:00.099Z"
        },
        {
            "WindowId": "mw-07f80c1841EXAMPLE",
            "Cutoff": 4,
            "Name": "Windows-Production-Maintenance-Window",
            "Description": "Standard maintenance windows for Production Servers",
            "Enabled": true,
            "Duration": 10,
            "Schedule": "cron(0 0 6 ? * WED *)",
            "NextExecutionTime": "2020-03-05T06:00:00.099Z"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowSchedule

Retrieves information about upcoming executions of a maintenance window.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResourceType": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 197\)](#)

Filters used to limit the range of results. For example, you can limit maintenance window executions to only those scheduled before or after a certain date and time.

Type: Array of [PatchOrchestratorFilter \(p. 794\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 197\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

[NextToken \(p. 197\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[ResourceType \(p. 197\)](#)

The type of resource you want to retrieve information about. For example, INSTANCE.

Type: String

Valid Values: INSTANCE | RESOURCE_GROUP

Required: No

[Targets \(p. 197\)](#)

The managed node ID or key-value pair to retrieve information about.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[WindowId \(p. 197\)](#)

The ID of the maintenance window to retrieve information about.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "ScheduledWindowExecutions": [  
        {  
            "ExecutionTime": "string",  
            "Name": "string",  
            "WindowId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 198\)](#)

The token for the next set of items to return. (You use this token in the next call.)

Type: String

[ScheduledWindowExecutions \(p. 198\)](#)

Information about maintenance window executions scheduled for the specified time range.

Type: Array of [ScheduledWindowExecution \(p. 826\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowSchedule`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowSchedule
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200224T235938Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200224/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "NextToken": "EXAMPLE/39c3b3042cd2aEXAMPLEKIAIOSFODNN7EXAMPLE==",
    "ScheduledWindowExecutions": [
        {
            "ExecutionTime": "2020-02-25T00:00:15.099Z",
            "Name": "MyMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        },
        {
    }
```

```
        "ExecutionTime": "2020-02-26T00:00:15.099Z",
        "Name": "MyMaintenanceWindow",
        "WindowId": "mw-0c50858d01EXAMPLE"
    },
{
    "ExecutionTime": "2020-02-27T00:00:15.099Z",
    "Name": "MyMaintenanceWindow",
    "WindowId": "mw-0c50858d01EXAMPLE"
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowsForTarget

Retrieves information about the maintenance window targets or tasks that a managed node is associated with.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResourceType": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 201\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

[NextToken \(p. 201\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[ResourceType \(p. 201\)](#)

The type of resource you want to retrieve information about. For example, `INSTANCE`.

Type: String

Valid Values: `INSTANCE` | `RESOURCE_GROUP`

Required: Yes

[Targets \(p. 201\)](#)

The managed node ID or key-value pair to retrieve information about.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "WindowIdentities": [  
        {  
            "Name": "string",  
            "WindowId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 202\)](#)

The token for the next set of items to return. (You use this token in the next call.)

Type: String

[WindowIdentities \(p. 202\)](#)

Information about the maintenance window targets and tasks a managed node is associated with.

Type: Array of [MaintenanceWindowIdentityForTarget \(p. 726\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowsForTarget`.

Sample Request

```
POST / HTTP/1.1  
Host: ssm.us-east-2.amazonaws.com
```

```
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowsForTarget
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T003520Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 100

{
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "ResourceType": "INSTANCE"
}
```

Sample Response

```
{
    "WindowIdentities": [
        {
            "Name": "MyFirstMaintenanceWindow",
            "WindowId": "mw-0c50858d01EXAMPLE"
        },
        {
            "Name": "MySecondMaintenanceWindow",
            "WindowId": "mw-05aaf9f490EXAMPLE"
        },
        {
            "Name": "MyThirdMaintenanceWindow",
            "WindowId": "mw-0ecb1226ddEXAMPLE"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowTargets

Lists the targets registered with the maintenance window.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 204)

Optional filters that can be used to narrow down the scope of the returned window targets. The supported filter keys are `Type`, `WindowTargetId`, and `OwnerInformation`.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults (p. 204)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken (p. 204)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

WindowId (p. 204)

The ID of the maintenance window whose targets should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\\$

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "Targets": [  
        {  
            "Description": "string",  
            "Name": "string",  
            "OwnerInformation": "string",  
            "ResourceType": "string",  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "WindowId": "string",  
            "WindowTargetId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 205\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[Targets \(p. 205\)](#)

Information about the targets in the maintenance window.

Type: Array of [MaintenanceWindowTarget \(p. 733\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowTargets`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowTargets
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T003928Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "Targets": [
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "Name": "MyTargets",
            "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE",
            "ResourceType": "INSTANCE",
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-02573cafefEXAMPLE",
                        "i-0471e04240EXAMPLE"
                    ]
                }
            ]
        },
        {
            "WindowId": "mw-0c50858d01EXAMPLE",
            "WindowTargetId": "7f4813bb-df25-4e59-b34f-c9e83EXAMPLE",
            "ResourceType": "INSTANCE",
            "Targets": [
                {
                    "Key": "InstanceIds",
                    "Values": [
                        "i-07782c72faEXAMPLE"
                    ]
                }
            ]
        }
    ]
}
```

```
        ]
    }
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMaintenanceWindowTasks

Lists the tasks in a maintenance window.

Note

For maintenance window tasks without a specified target, you can't supply values for `--max-errors` and `--max-concurrency`. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. These values don't affect the running of your task and can be ignored.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 208)

Optional filters used to narrow down the scope of the returned tasks. The supported filter keys are `WindowTaskId`, `TaskArn`, `Priority`, and `TaskType`.

Type: Array of [MaintenanceWindowFilter \(p. 722\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

MaxResults (p. 208)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

NextToken (p. 208)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[WindowId \(p. 208\)](#)

The ID of the maintenance window whose tasks should be retrieved.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "Tasks": [  
        {  
            "CutoffBehavior": "string",  
            "Description": "string",  
            "LoggingInfo": {  
                "S3BucketName": "string",  
                "S3KeyPrefix": "string",  
                "S3Region": "string"  
            },  
            "MaxConcurrency": "string",  
            "MaxErrors": "string",  
            "Name": "string",  
            "Priority": number,  
            "ServiceRoleArn": "string",  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "TaskArn": "string",  
            "TaskParameters": {  
                "string" : {  
                    "Values": [ "string" ]  
                }  
            },  
            "Type": "string",  
            "WindowId": "string",  
            "WindowTaskId": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 209\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Tasks (p. 209)

Information about the tasks in the maintenance window.

Type: Array of [MaintenanceWindowTask \(p. 735\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeMaintenanceWindowTasks`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeMaintenanceWindowTasks
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T004311Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 36

{
    "WindowId": "mw-0ecb1226dd7bEXAMPLE"
}
```

Sample Response

```
{
    "Tasks": [
        {
            "TaskArn": "arn:aws:ssm:us-east-2:123456789012:task/mw-0ecb1226dd7bEXAMPLE",
            "TaskId": "mw-0ecb1226dd7bEXAMPLE"
        }
    ]
}
```

```
"WindowId": "mw-0ecb1226ddEXAMPLE",
"WindowTaskId": "018b31c3-2d77-4b9e-bd48-c91edEXAMPLE",
"TaskArn": "AWS-RestartEC2Instance",
"TaskParameters": {},
"Type": "AUTOMATION",
"Description": "Restarting EC2 Instance for maintenance",
"MaxConcurrency": "1",
"MaxErrors": "1",
"Name": "My-Automation-Example-Task",
"Priority": 0,
"ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/AWSServiceRoleForAmazonSSM",
"Targets": [
{
    "Key": "WindowTargetIds",
    "Values": [
        "da89dcc3-7f9c-481d-ba2b-edcb7EXAMPLE"
    ]
}
],
{
    "WindowId": "mw-0ecb1226ddEXAMPLE",
    "WindowTaskId": "1943dee0-0a17-4978-9bf4-3cc2fEXAMPLE",
    "TaskArn": "AWS-DisableS3BucketPublicReadWrite",
    "TaskParameters": {},
    "Type": "AUTOMATION",
    "Description": "Automation task to disable read/write access on public S3
buckets",
    "MaxConcurrency": "10",
    "MaxErrors": "5",
    "Name": "My-Disable-S3-Public-Read-Write-Access-Automation-Task",
    "Priority": 0,
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/
ssm.amazonaws.com/AWSServiceRoleForAmazonSSM",
    "Targets": [
{
    "Key": "WindowTargetIds",
    "Values": [
        "da89dcc3-7f9c-481d-ba2b-edcb7EXAMPLE"
    ]
}
]
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeOpsItems

Query a set of OpsItems. You must have permission in AWS Identity and Access Management (IAM) to query a list of OpsItems. For more information, see [Getting started with OpsCenter in the AWS Systems Manager User Guide](#).

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see [OpsCenter](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "OpsItemFilters": [  
        {  
            "Key": "string",  
            "Operator": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 213\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 213\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

[OpsItemFilters \(p. 213\)](#)

One or more filters to limit the response.

- Key: CreatedTime

Operations: GreaterThan, LessThan

- Key: LastModifiedBy

- Operations: Contains, Equals
 - Key: LastModifiedTime
- Operations: GreaterThan, LessThan
 - Key: Priority
- Operations: Equals
 - Key: Source
- Operations: Contains, Equals
 - Key: Status
- Operations: Equals
 - Key: Title*
- Operations: Equals,Contains
 - Key: OperationalData**
- Operations: Equals
 - Key: OperationalDataKey
- Operations: Equals
 - Key: OperationalHeaderValue
- Operations: Equals, Contains
 - Key: OpsItemId
- Operations: Equals
 - Key: ResourceId
- Operations: Contains
 - Key: AutomationId
- Operations: Equals

*The Equals operator for Title matches the first 100 characters. If you specify more than 100 characters, the system returns an error that the filter value exceeds the length limit.

**If you filter the response by using the OperationalData operator, specify a key-value pair by using the following JSON format: {"key":"key_name","value":"a_value"}

Type: Array of [OpsItemFilter \(p. 757\)](#) objects

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "OpsItemSummaries": [  
        {  
            "ActualEndTime": number,  
            "ActualStartTime": number,  
            "Arn": "string",  
            "AutomationId": "string",  
            "Cause": "string",  
            "CloudWatchLogsLogGroupArn": "string",  
            "CloudWatchLogsLogStreamName": "string",  
            "Description": "string",  
            "Event": "string",  
            "EventId": "string",  
            "EventSource": "string",  
            "EventTime": "string",  
            "LastModifiedTime": "string",  
            "LogicalName": "string",  
            "OperationalData": [{"key": "string", "value": "string"}],  
            "OpsItemKey": "string",  
            "ResourceType": "string",  
            "Severity": "string",  
            "Status": "string",  
            "Title": "string",  
            "Type": "string"  
        }  
    ]  
}
```

```
    "Category": "string",
    "CreatedBy": "string",
    "CreatedTime": number,
    "LastModifiedBy": "string",
    "LastModifiedTime": number,
    "OperationalData": [
        "string" : {
            "Type": "string",
            "Value": "string"
        }
    ],
    "OpsItemId": "string",
    "OpsItemType": "string",
    "PlannedEndTime": number,
    "PlannedStartTime": number,
    "Priority": number,
    "Severity": "string",
    "Source": "string",
    "Status": "string",
    "Title": "string"
}
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 214\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[OpsItemSummaries \(p. 214\)](#)

A list of OpsItems.

Type: Array of [OpsItemSummary \(p. 763\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribeOpsItems`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeOpsItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T163154Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 80

{
    "OpsItemFilters": [
        {
            "Key": "Status",
            "Values": [
                "Open"
            ],
            "Operator": "Equal"
        }
    ]
}
```

Sample Response

```
{
    "OpsItemSummaries": [
        {
            "CreatedBy": "arn:aws:iam::111122223333:user/example",
            "CreatedTime": 1585757579.218,
            "LastModifiedBy": "arn:aws:iam::111122223333:user/example",
            "LastModifiedTime": 1585757579.218,
            "OpsItemId": "oi-1f050EXAMPLE",
            "Source": "SSM",
            "Status": "Open",
            "Title": "DocumentDeleted"
        },
        {
            "Category": "Availability",
            "CreatedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
            "CreatedTime": 1582701517.193,
            "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
            "LastModifiedTime": 1582701517.193,
            "OperationalData": {
                "/aws/dedup": {
                    "Type": "SearchableString",
                    "Value": "{\"dedupString\":\"SSMOpsItems-SSM-maintenance-window-
execution-failed\"}"
                },
                "/aws/resources": {
                    "Type": "SearchableString",
                    "Value": "[{\"arn\":\"arn:aws:ssm:us-
east-2:111122223333:maintenancewindow/mw-0e357ebdc6EXAMPLE\"}]"
                }
            },
            "OpsItemId": "oi-f99f2EXAMPLE",
            "Severity": "3",
            "Source": "SSM",
            "Title": "AWS Lambda function failed to execute due to maintenance window restrictions"
        }
    ]
}
```

```
        "Status": "Open",
        "Title": "SSM Maintenance Window execution failed"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeParameters

Get information about a parameter.

Request results are returned on a best-effort basis. If you specify `MaxResults` in the request, the response includes information up to the limit specified. The number of items returned, however, can be between zero and the value of `MaxResults`. If the service reaches an internal limit while processing the results, it stops the operation and returns the matching values up to that point and a `NextToken`. You can specify the `NextToken` in a subsequent call to get the next set of results.

Important

If you change the KMS key alias for the KMS key used to encrypt a parameter, then you must also update the key alias the parameter uses to reference KMS. Otherwise, `DescribeParameters` retrieves whatever the original key alias was referencing.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ParameterFilters": [  
        {  
            "Key": "string",  
            "Option": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 218\)](#)

This data type is deprecated. Instead, use `ParameterFilters`.

Type: Array of [ParametersFilter \(p. 779\)](#) objects

Required: No

[MaxResults \(p. 218\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 218\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[ParameterFilters \(p. 218\)](#)

Filters to limit the request results.

Type: Array of [ParameterStringFilter \(p. 780\)](#) objects

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Parameters": [  
        {  
            "AllowedPattern": "string",  
            "DataType": "string",  
            "Description": "string",  
            "KeyId": "string",  
            "LastModifiedDate": number,  
            "LastModifiedUser": "string",  
            "Name": "string",  
            "Policies": [  
                {  
                    "PolicyStatus": "string",  
                    "PolicyText": "string",  
                    "PolicyType": "string"  
                }  
            ],  
            "Tier": "string",  
            "Type": "string",  
            "Version": number  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 219\)](#)

The token to use when requesting the next set of items.

Type: String

[Parameters \(p. 219\)](#)

Parameters returned by the request.

Type: Array of [ParameterMetadata \(p. 777\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterOption

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeParameters`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 95
X-Amz-Target: AmazonSSM.DescribeParameters
X-Amz-Date: 20180316T010204Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "ParameterFilters": [
        {
            "Values": [
                "String"
            ],
        }
    ]
}
```

```
        "Key": "Type"
    },
    {
        "Values": [
            "/Branch312"
        ],
        "Key": "Name"
    }
]
```

Sample Response

```
{
    "Parameters": [
        {
            "LastModifiedDate": 1521160696.821,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer1",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160709.358,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer2",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160717.945,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "/Branch312/Dev/Engineer3",
            "Policies": [],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
        {
            "LastModifiedDate": 1521160747.499,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mary.Major",
            "Name": "/Branch312/Dev/Intern",
            "Policies": [
                {
                    "PolicyStatus": "Pending",
                    "PolicyText": "{\"Type\":\"Expiration\",\"Version\":\"1.0\"}",
                    "Attributes\":{\"Timestamp\":\"2020-03-31T17:00:00Z\"}}",
                    "PolicyType": "Expiration"
                },
                {
                    "PolicyStatus": "Pending",
                    "PolicyText": "{\"Type\":\"ExpirationNotification\",\"Version\":\"1.0\"}",
                    "Attributes\":{\"Before\":\"14\", \"Unit\":\"Days\"}}",
                    "PolicyType": "ExpirationNotification"
                }
            ],
            "Type": "String",
            "Version": 1,
            "Tier": "Standard"
        },
    ]
}
```

```
{  
    "LastModifiedDate": 1521160588.291,  
    "LastModifiedUser": "arn:aws:iam::111122223333:user/John.Stiles",  
    "Name": "/Branch312/Dev/TeamLead",  
    "Policies": [],  
    "Type": "String",  
    "Version": 1,  
    "Tier": "Standard"  
}  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePatchBaselines

Lists the patch baselines in your AWS account.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 223\)](#)

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribePatchBaselines` include the following:

- **NAME_PREFIX**

Sample values: AWS- | My-

- **OWNER**

Sample values: AWS | Self

- **OPERATING_SYSTEM**

Sample values: AMAZON_LINUX | SUSE | WINDOWS

Type: Array of [PatchOrchestratorFilter \(p. 794\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 223\)](#)

The maximum number of patch baselines to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken \(p. 223\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "BaselineIdentities": [  
        {  
            "BaselineDescription": "string",  
            "BaselineId": "string",  
            "BaselineName": "string",  
            "DefaultBaseline": boolean,  
            "OperatingSystem": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineIdentities (p. 224)

An array of `PatchBaselineIdentity` elements.

Type: Array of [PatchBaselineIdentity](#) (p. 786) objects

NextToken (p. 224)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 847).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribePatchBaselines`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribePatchBaselines
X-Amz-Date: 20180309T024139Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
{}
```

Sample Response

```
{
    "BaselineIdentities": [
        {
            "BaselineDescription": "Default Patch Baseline for Suse Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-07d8884178EXAMPLE",
            "BaselineName": "AWS-SuseDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "SUSE"
        },
        {
            "BaselineDescription": "Default Patch Baseline Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-09ca3fb51fEXAMPLE",
            "BaselineName": "AWS-DefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "WINDOWS"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Amazon Linux Provided by
AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0c10e65780EXAMPLE",
            "BaselineName": "AWS-AmazonLinuxDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "AMAZON_LINUX"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Ubuntu Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0c7e89f711EXAMPLE",
            "BaselineName": "AWS-UbuntuDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "UBUNTU"
        },
        {
            "BaselineDescription": "Default Patch Baseline for Redhat Enterprise Linux
Provided by AWS.",
            "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/
pb-0ccb3a633dEXAMPLE",
            "BaselineName": "AWS-RedHatDefaultPatchBaseline",
            "DefaultBaseline": true,
            "OperatingSystem": "REDHAT_ENTERPRISE_LINUX"
        }
    ]
    // There may be more content here
}
```

]
}

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePatchGroups

Lists all patch groups that have been registered with patch baselines.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 227\)](#)

Each element in the array is a structure containing a key-value pair.

Supported keys for `DescribePatchGroups` include the following:

- **NAME_PREFIX**

Sample values: AWS- | My-.

- **OPERATING_SYSTEM**

Sample values: AMAZON_LINUX | SUSE | WINDOWS

Type: Array of [PatchOrchestratorFilter \(p. 794\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[MaxResults \(p. 227\)](#)

The maximum number of patch groups to return (per page).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[NextToken \(p. 227\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "Mappings": [  
        {  
            "BaselineIdentity": {  
                "BaselineDescription": "string",  
                "BaselineId": "string",  
                "BaselineName": "string",  
                "DefaultBaseline": boolean,  
                "OperatingSystem": "string"  
            },  
            "PatchGroup": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Mappings \(p. 228\)](#)

Each entry in the array contains:

- PatchGroup: string (between 1 and 256 characters. Regex: ^([\p{L}\p{Z}]\p{N}_.:/=+\-\@]*\$)
- PatchBaselineIdentity: A PatchBaselineIdentity element.

Type: Array of [PatchGroupPatchBaselineMapping \(p. 793\)](#) objects

[NextToken \(p. 228\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribePatchGroups`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonSSM.DescribePatchGroups
X-Amz-Date: 20180308T211212Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
{}
```

Sample Response

```
{
    "Mappings": [
        {
            "PatchGroup": "Database Servers",
            "BaselineIdentity": {
                "BaselineName": "Windows-Server-2012R2",
                "DefaultBaseline": false,
                "BaselineDescription": "Windows Server 2012 R2, Important and Critical security updates",
                "BaselineId": "pb-0c4e592064EXAMPLE",
                "OperatingSystem": "WINDOWS"
            }
        },
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "Windows-Server-2012R2",
                "DefaultBaseline": false,
                "BaselineDescription": "Windows Server 2012 R2, Important and Critical security updates",
                "BaselineId": "pb-0c4e592064EXAMPLE",
                "OperatingSystem": "WINDOWS"
            }
        },
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "Amazon-Linux-Production",
                "DefaultBaseline": false,
                "BaselineDescription": "Patch baseline used for production instances",
                "BaselineId": "pb-022cbaf99cEXAMPLE",
                "OperatingSystem": "AMAZON_LINUX"
            }
        },
        {
            "PatchGroup": "Production",
            "BaselineIdentity": {
                "BaselineName": "RHEL-ZeroDay-Critical",
                "DefaultBaseline": false,
                "BaselineId": "pb-0ea5bc85f4EXAMPLE",
                "OperatingSystem": "REDHAT_ENTERPRISE_LINUX"
            }
        },
        {
            "PatchGroup": "Production-Demo",
            "BaselineIdentity": {
                "BaselineName": "Ubuntu-16.04-LTS",
                "DefaultBaseline": false,
                "BaselineId": "pb-034a2d8f5fEXAMPLE",
                "OperatingSystem": "UBUNTU_16_04_LTS"
            }
        }
    ]
}
```

```
        "BaselineIdentity": {
            "BaselineName": "Only-Security-Patches",
            "DefaultBaseline": false,
            "BaselineDescription": "Security updates for all versions of Windows",
            "BaselineId": "pb-08521bdf9eEXAMPLE",
            "OperatingSystem": "WINDOWS"
        }
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePatchGroupState

Returns high-level aggregated patch compliance state information for a patch group.

Request Syntax

```
{  
    "PatchGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

PatchGroup (p. 231)

The name of the patch group whose patch snapshot should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\\p{L}\\p{Z}\\p{N}_.:=/+=\\-@]*\$

Required: Yes

Response Syntax

```
{  
    "Instances": number,  
    "InstancesWithCriticalNonCompliantPatches": number,  
    "InstancesWithFailedPatches": number,  
    "InstancesWithInstalledOtherPatches": number,  
    "InstancesWithInstalledPatches": number,  
    "InstancesWithInstalledPendingRebootPatches": number,  
    "InstancesWithInstalledRejectedPatches": number,  
    "InstancesWithMissingPatches": number,  
    "InstancesWithNotApplicablePatches": number,  
    "InstancesWithOtherNonCompliantPatches": number,  
    "InstancesWithSecurityNonCompliantPatches": number,  
    "InstancesWithUnreportedNotApplicablePatches": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Instances (p. 231)

The number of managed nodes in the patch group.

Type: Integer

InstancesWithCriticalNonCompliantPatches (p. 231)

The number of managed nodes where patches that are specified as Critical for compliance reporting in the patch baseline aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is NON_COMPLIANT.

Type: Integer

InstancesWithFailedPatches (p. 231)

The number of managed nodes with patches from the patch baseline that failed to install.

Type: Integer

InstancesWithInstalledOtherPatches (p. 231)

The number of managed nodes with patches installed that aren't defined in the patch baseline.

Type: Integer

InstancesWithInstalledPatches (p. 231)

The number of managed nodes with installed patches.

Type: Integer

InstancesWithInstalledPendingRebootPatches (p. 231)

The number of managed nodes with patches installed by Patch Manager that haven't been rebooted after the patch installation. The status of these managed nodes is NON_COMPLIANT.

Type: Integer

InstancesWithInstalledRejectedPatches (p. 231)

The number of managed nodes with patches installed that are specified in a RejectedPatches list. Patches with a status of INSTALLED_REJECTED were typically installed before they were added to a RejectedPatches list.

Note

If ALLOW_AS_DEPENDENCY is the specified option for RejectedPatchesAction, the value of InstancesWithInstalledRejectedPatches will always be 0 (zero).

Type: Integer

InstancesWithMissingPatches (p. 231)

The number of managed nodes with missing patches from the patch baseline.

Type: Integer

InstancesWithNotApplicablePatches (p. 231)

The number of managed nodes with patches that aren't applicable.

Type: Integer

InstancesWithOtherNonCompliantPatches (p. 231)

The number of managed nodes with patches installed that are specified as other than Critical or Security but aren't compliant with the patch baseline. The status of these managed nodes is NON_COMPLIANT.

Type: Integer

[InstancesWithSecurityNonCompliantPatches \(p. 231\)](#)

The number of managed nodes where patches that are specified as Security in a patch advisory aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is NON_COMPLIANT.

Type: Integer

[InstancesWithUnreportedNotApplicablePatches \(p. 231\)](#)

The number of managed nodes with NotApplicable patches beyond the supported limit, which aren't reported by name to Inventory. Inventory is a capability of AWS Systems Manager.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribePatchGroupState`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 33
X-Amz-Target: AmazonSSM.DescribePatchGroupState
X-Amz-Date: 20180308T205757Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180308/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup"
}
```

Sample Response

```
{
```

```
"Instances": 12,  
"InstancesWithCriticalNonCompliantPatches": 1,  
"InstancesWithFailedPatches": 2,  
"InstancesWithInstalledOtherPatches": 3,  
"InstancesWithInstalledPatches": 12,  
"InstancesWithInstalledPendingRebootPatches": 2,  
"InstancesWithInstalledRejectedPatches": 1,  
"InstancesWithMissingPatches": 3,  
"InstancesWithNotApplicablePatches": 0,  
"InstancesWithOtherNonCompliantPatches": 0,  
"InstancesWithSecurityNonCompliantPatches": 1,  
"InstancesWithUnreportedNotApplicablePatches": 0  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePatchProperties

Lists the properties of available patches organized by product, product family, classification, severity, and other properties of available patches. You can use the reported properties in the filters you specify in requests for operations such as [CreatePatchBaseline \(p. 61\)](#), [UpdatePatchBaseline \(p. 564\)](#), [DescribeAvailablePatches \(p. 134\)](#), and [DescribePatchBaselines \(p. 223\)](#).

The following section lists the properties that can be used in filters for each major operating system type:

AMAZON_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

AMAZON_LINUX_2

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

CENTOS

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

DEBIAN

Valid properties: PRODUCT | PRIORITY

MACOS

Valid properties: PRODUCT | CLASSIFICATION

ORACLE_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

REDHAT_ENTERPRISE_LINUX

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

SUSE

Valid properties: PRODUCT | CLASSIFICATION | SEVERITY

UBUNTU

Valid properties: PRODUCT | PRIORITY

WINDOWS

Valid properties: PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | MSRC_SEVERITY

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "OperatingSystem": "string",  
    "PatchSet": "string",  
    "Property": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 235\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 235\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[OperatingSystem \(p. 235\)](#)

The operating system type for which to list patches.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: Yes

[PatchSet \(p. 235\)](#)

Indicates whether to list patches for the Windows operating system or for applications released by Microsoft. Not applicable for the Linux or macOS operating systems.

Type: String

Valid Values: OS | APPLICATION

Required: No

[Property \(p. 235\)](#)

The patch property for which you want to view patch details.

Type: String

Valid Values: PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | MSRC_SEVERITY | PRIORITY | SEVERITY

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "Properties": [  
        {  
            "string" : "string"  
    ]  
}
```

```
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 236\)](#)

The token for the next set of items to return. (You use this token in the next call.)

Type: String

[Properties \(p. 236\)](#)

A list of the properties for patches matching the filter request parameters.

Type: Array of string to string maps

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `DescribePatchProperties`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 95
X-Amz-Target: AmazonSSM.DescribePatchProperties
X-Amz-Date: 20190312T010204Z
User-Agent: aws-cli/1.16.96 Python/2.7.15 Windows/10 botocore/1.12.86
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20190312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
{
```

```
        "OperatingSystem": "Windows",
        "Property": "PRODUCT",
        "PatchSet": "OS"
    }
```

Sample Response

```
{
    "Properties": [
        {
            "Name": "WindowsServer2012",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2012R2",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2016",
            "ProductFamily": "Windows"
        },
        {
            "Name": "WindowsServer2019",
            "ProductFamily": "Windows"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSessions

Retrieves a list of all active sessions (both connected and disconnected) or terminated sessions from the past 30 days.

Request Syntax

```
{  
    "Filters": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "State": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 239\)](#)

One or more filters to limit the type of sessions returned by the request.

Type: Array of [SessionFilter \(p. 831\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Required: No

[MaxResults \(p. 239\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 200.

Required: No

[NextToken \(p. 239\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[State \(p. 239\)](#)

The session status to retrieve a list of sessions for. For example, "Active".

Type: String

Valid Values: Active | History

Required: Yes

Response Syntax

```
{  
    "NextToken": "string",  
    "Sessions": [  
        {  
            "Details": "string",  
            "DocumentName": "string",  
            "EndDate": number,  
            "MaxSessionDuration": "string",  
            "OutputUrl": {  
                "CloudWatchOutputUrl": "string",  
                "S3OutputUrl": "string"  
            },  
            "Owner": "string",  
            "Reason": "string",  
            "SessionId": "string",  
            "StartDate": number,  
            "Status": "string",  
            "Target": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 240\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

[Sessions \(p. 240\)](#)

A list of sessions meeting the request parameters.

Type: Array of [Session \(p. 829\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `DescribeSessions`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DescribeSessions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T175636Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 20

{
    "State": "History"
}
```

Sample Response

```
{
    "Sessions": [
        {
            "EndDate": 1582069847.807,
            "OutputUrl": {
                "S3OutputUrl": "https://us-east-2.console.aws.amazon.com/s3/object/doc-
example-bucket/session-data/Mary-Major-0ab177d470EXAMPLE.log"
            },
            "Owner": "arn:aws:iam::111122223333:user/Mary-Major",
            "SessionId": "Mary-Major-0ab177d470EXAMPLE",
            "StartDate": 1582068633.188,
            "Status": "Terminated",
            "Target": "i-07782c72faEXAMPLE"
        }
        // There may be more content here
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateOpsItemRelatedItem

Deletes the association between an OpsItem and a related item. For example, this API operation can delete an Incident Manager incident from an OpsItem. Incident Manager is a capability of AWS Systems Manager.

Request Syntax

```
{  
    "AssociationId": "string",  
    "OpsItemId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AssociationId \(p. 243\)](#)

The ID of the association for which you want to delete an association between the OpsItem and a related item.

Type: String

Required: Yes

[OpsItemId \(p. 243\)](#)

The ID of the OpsItem for which you want to delete an association between the OpsItem and a related item.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

OpsItemRelatedItemAssociationNotFoundException

The association wasn't found using the parameters you specified in the call. Verify the information and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of DisassociateOpsItemRelatedItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.DisassociateOpsItemRelatedItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/x86_64.amzn.2 prompt/off command/ssm.disassociate-ops-item-related-item
X-Amz-Date: 20210910T182919Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210910/us-east-1/ssm/aws4_request, SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 89

{
    "OpsItemId": "oi-f99f2EXAMPLE",
    "AssociationId": "e2036148-ccb-490e-ac2a-390e5EXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAutomationExecution

Get detailed information about a particular Automation execution.

Request Syntax

```
{  
    "AutomationExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AutomationExecutionId (p. 246)

The unique identifier for an existing automation execution to examine. The execution ID is returned by StartAutomationExecution when the execution of an Automation runbook is initiated.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Response Syntax

```
{  
  "AutomationExecution": {  
    "AssociationId": "string",  
    "AutomationExecutionId": "string",  
    "AutomationExecutionStatus": "string",  
    "AutomationSubtype": "string",  
    "ChangeRequestName": "string",  
    "CurrentAction": "string",  
    "CurrentStepName": "string",  
    "DocumentName": "string",  
    "DocumentVersion": "string",  
    "ExecutedBy": "string",  
    "ExecutionEndTime": number,  
    "ExecutionStartTime": number,  
    "FailureMessage": "string",  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Mode": "string",  
    "OpsItemId": "string",  
    "Outputs": {  
      "string" : [ "string" ]  
    },  
    "Parameters": {  
      "string" : [ "string" ]  
    },  
    "ParentAutomationExecutionId": "string"  
  }  
}
```

```
"ProgressCounters": {  
    "CancelledSteps": number,  
    "FailedSteps": number,  
    "SuccessSteps": number,  
    "TimedOutSteps": number,  
    "TotalSteps": number  
},  
"ResolvedTargets": {  
    "ParameterValues": [ "string" ],  
    "Truncated": boolean  
},  
"Runbooks": [  
    {  
        "DocumentName": "string",  
        "DocumentVersion": "string",  
        "MaxConcurrency": "string",  
        "MaxErrors": "string",  
        "Parameters": {  
            "string": [ "string" ]  
        },  
        "TargetLocations": [  
            {  
                "Accounts": [ "string" ],  
                "ExecutionRoleName": "string",  
                "Regions": [ "string" ],  
                "TargetLocationMaxConcurrency": "string",  
                "TargetLocationMaxErrors": "string"  
            }  
        ],  
        "TargetMaps": [  
            {  
                "string": [ "string" ]  
            }  
        ],  
        "TargetParameterName": "string",  
        "Targets": [  
            {  
                "Key": "string",  
                "Values": [ "string" ]  
            }  
        ]  
    }  
],  
"ScheduledTime": number,  
"StepExecutions": [  
    {  
        "Action": "string",  
        "ExecutionEndTime": number,  
        "ExecutionStartTime": number,  
        "FailureDetails": {  
            "Details": {  
                "string": [ "string" ]  
            },  
            "FailureStage": "string",  
            "FailureType": "string"  
        },  
        "FailureMessage": "string",  
        "Inputs": {  
            "string": "string"  
        },  
        "IsCritical": boolean,  
        "IsEnd": boolean,  
        "MaxAttempts": number,  
        "NextStep": "string",  
        "OnFailure": "string",  
        "Outputs": {  
            "string": "string"  
        }  
    }  
]
```

```
        "string" : [ "string" ]
    },
    "OverriddenParameters": {
        "string" : [ "string" ]
    },
    "Response": "string",
    "ResponseCode": "string",
    "StepExecutionId": "string",
    "StepName": "string",
    "StepStatus": "string",
    "TargetLocation": {
        "Accounts": [ "string" ],
        "ExecutionRoleName": "string",
        "Regions": [ "string" ],
        "TargetLocationMaxConcurrency": "string",
        "TargetLocationMaxErrors": "string"
    },
    "Targets": [
        {
            "Key": "string",
            "Values": [ "string" ]
        }
    ],
    "TimeoutSeconds": number,
    "ValidNextSteps": [ "string" ]
}
},
"StepExecutionsTruncated": boolean,
"Target": "string",
"TargetLocations": [
    {
        "Accounts": [ "string" ],
        "ExecutionRoleName": "string",
        "Regions": [ "string" ],
        "TargetLocationMaxConcurrency": "string",
        "TargetLocationMaxErrors": "string"
    }
],
"TargetMaps": [
    {
        "string" : [ "string" ]
    }
],
"TargetParameterName": "string",
"Targets": [
    {
        "Key": "string",
        "Values": [ "string" ]
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecution (p. 246)

Detailed information about the current state of an automation execution.

Type: AutomationExecution (p. 611) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetAutomationExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T185532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
    "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE"
}
```

Sample Response

```
{
    "AutomationExecution": {
        "AutomationExecutionId": "8a5f5be8-5d93-437a-adbb-394f7EXAMPLE",
        "AutomationExecutionStatus": "Success",
        "DocumentName": "CreateImage",
        "DocumentVersion": "1",
        "ExecutedBy": "arn:aws:sts::111122223333:assumed-role/Example",
        "ExecutionEndTime": 1585062669.053,
        "ExecutionStartTime": 1585061570.827,
        "Mode": "Auto",
        "Outputs": {},
        "Parameters": {
            "InstanceId": [
                "i-02573cafefEXAMPLE"
            ]
        },
        "ResolvedTargets": {

```

```
        "ParameterValues": [],
        "Truncated": false
    },
    "StepExecutions": [
        {
            "Action": "aws:createImage",
            "ExecutionEndTime": 1585062668.968,
            "ExecutionStartTime": 1585061571.144,
            "Inputs": {
                "ImageDescription": "\"AMI for i-02573cafefEXAMPLE created on 2020-03-24_14.52.51\"",
                "ImageName": "\"i-02573cafefEXAMPLE-2020-03-24_14.52.51\"",
                "InstanceId": "\"i-02573cafefEXAMPLE\"",
                "NoReboot": "false"
            },
            "OnFailure": "Abort",
            "Outputs": {
                "ImageId": [
                    "ami-0f4706cb37EXAMPLE"
                ],
                "ImageState": [
                    "available"
                ],
                "OutputPayload": [
                    "{\"ImageId\":\"ami-0f4706cb37EXAMPLE\", \"ImageState\":\"available\"}"
                ]
            },
            "OverriddenParameters": {},
            "StepExecutionId": "eff80946-356d-4128-97b2-6a0f5EXAMPLE",
            "StepName": "createImage",
            "StepStatus": "Success"
        }
    ],
    "StepExecutionsTruncated": false,
    "Targets": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCalendarState

Gets the state of a AWS Systems Manager change calendar at the current time or a specified time. If you specify a time, `GetCalendarState` returns the state of the calendar at that specific time, and returns the next time that the change calendar state will transition. If you don't specify a time, `GetCalendarState` uses the current time. Change Calendar entries have two possible states: OPEN or CLOSED.

If you specify more than one calendar in a request, the command returns the status of OPEN only if all calendars in the request are open. If one or more calendars in the request are closed, the status returned is CLOSED.

For more information about Change Calendar, a capability of AWS Systems Manager, see [AWS Systems Manager Change Calendar](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "AtTime": "string",  
    "CalendarNames": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AtTime (p. 251)

(Optional) The specific time for which you want to get calendar state information, in [ISO 8601](#) format. If you don't specify a value or `AtTime`, the current time is used.

Type: String

Required: No

CalendarNames (p. 251)

The names or Amazon Resource Names (ARNs) of the Systems Manager documents (SSM documents) that represent the calendar entries for which you want to get the state.

Type: Array of strings

Required: Yes

Response Syntax

```
{  
    "AtTime": "string",  
    "NextTransitionTime": "string",  
    "State": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AtTime (p. 251)

The time, as an [ISO 8601](#) string, that you specified in your command. If you don't specify a time, `GetCalendarState` uses the current time.

Type: String

NextTransitionTime (p. 251)

The time, as an [ISO 8601](#) string, that the calendar state will change. If the current calendar state is `OPEN`, `NextTransitionTime` indicates when the calendar state changes to `CLOSED`, and vice-versa.

Type: String

State (p. 251)

The state of the calendar. An `OPEN` calendar indicates that actions are allowed to proceed, and a `CLOSED` calendar indicates that actions aren't allowed to proceed.

Type: String

Valid Values: `OPEN` | `CLOSED`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentType

The SSM document type isn't valid. Valid document types are described in the `DocumentType` property.

HTTP Status Code: 400

UnsupportedCalendarException

The calendar entry contained in the specified SSM document isn't supported.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetCalendarState`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetCalendarState
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200224T191829Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "CalendarNames": [
        "MyCalendar"
    ],
    "AtTime": "2021-02-25T19:05:47Z"
}
```

Sample Response

```
{
    "AtTime": "2021-02-25T19:05:47Z",
    "State": "OPEN"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCommandInvocation

Returns detailed information about command execution for an invocation or plugin.

`GetCommandInvocation` only gives the execution status of a plugin in a document. To get the command execution status on a specific managed node, use [ListCommandInvocations \(p. 362\)](#). To get the command execution status across managed nodes, use [ListCommands \(p. 367\)](#).

Request Syntax

```
{  
    "CommandId": "string",  
    "InstanceId": "string",  
    "PluginName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

CommandId (p. 254)

(Required) The parent command ID of the invocation plugin.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

InstanceId (p. 254)

(Required) The ID of the managed node targeted by the command. A *managed node* can be an Amazon Elastic Compute Cloud (Amazon EC2) instance, edge device, and on-premises server or VM in your hybrid environment that is configured for AWS Systems Manager.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: Yes

PluginName (p. 254)

The name of the step for which you want detailed results. If the document contains only one step, you can omit the name and details for that step. If the document contains more than one step, you must specify the name of the step for which you want to view details. Be sure to specify the name of the step, not the name of a plugin like `aws:RunShellScript`.

To find the `PluginName`, check the document content and find the name of the step you want details for. Alternatively, use [ListCommandInvocations \(p. 362\)](#) with the `CommandId` and `Details` parameters. The `PluginName` is the `Name` attribute of the `CommandPlugin` object in the `CommandPlugins` list.

Type: String

Length Constraints: Minimum length of 4.

Required: No

Response Syntax

```
{  
    "CloudWatchOutputConfig": {  
        "CloudWatchLogGroupName": "string",  
        "CloudWatchOutputEnabled": boolean  
    },  
    "CommandId": "string",  
    "Comment": "string",  
    "DocumentName": "string",  
    "DocumentVersion": "string",  
    "ExecutionElapsed Time": "string",  
    "ExecutionEndDateTime": "string",  
    "ExecutionStartTime": "string",  
    "InstanceId": "string",  
    "PluginName": "string",  
    "ResponseCode": number,  
    "StandardErrorContent": "string",  
    "StandardErrorUrl": "string",  
    "StandardOutputContent": "string",  
    "StandardOutputUrl": "string",  
    "Status": "string",  
    "StatusDetails": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CloudWatchOutputConfig \(p. 255\)](#)

Amazon CloudWatch Logs information where Systems Manager sent the command output.

Type: [CloudWatchOutputConfig \(p. 625\)](#) object

[CommandId \(p. 255\)](#)

The parent command ID of the invocation plugin.

Type: String

Length Constraints: Fixed length of 36.

[Comment \(p. 255\)](#)

The comment text for the command.

Type: String

Length Constraints: Maximum length of 100.

[DocumentName \(p. 255\)](#)

The name of the document that was run. For example, `AWS-RunShellScript`.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

[DocumentVersion \(p. 255\)](#)

The Systems Manager document (SSM document) version used in the request.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

[ExecutionElapsedTime \(p. 255\)](#)

Duration since `ExecutionStartTime`.

Type: String

Pattern: ^([\\-]?\\d{4}(?!\\d{2}\\b))((-?)(\\0[1-9]|1[0-2])(\\3([12]\\d|0[1-9]|3[01]))?|W([0-4]\\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\\d|[12]\\d{2}|3([0-5]\\d|6[1-6])))([T\\s](([01]\\d|2[0-3])((:?)[0-5]\\d)?|24\\:00)([\\.,]\\d(?!:))?)?(\\17[0-5]\\d([\\.,]\\d)?)?([zz]|([\\-])([01]\\d|2[0-3]):?([0-5]\\d)?))?)?#\$

[ExecutionEndTime \(p. 255\)](#)

The date and time the plugin finished running. Date and time are written in ISO 8601 format. For example, June 7, 2017 is represented as 2017-06-7. The following sample AWS CLI command uses the `InvokedAfter` filter.

```
aws ssm list-commands --filters key=InvokedAfter,value=2017-06-07T00:00:00Z
```

If the plugin hasn't started to run, the string is empty.

Type: String

Pattern: ^([\\-]?\\d{4}(?!\\d{2}\\b))((-?)(\\0[1-9]|1[0-2])(\\3([12]\\d|0[1-9]|3[01]))?|W([0-4]\\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\\d|[12]\\d{2}|3([0-5]\\d|6[1-6])))([T\\s](([01]\\d|2[0-3])((:?)[0-5]\\d)?|24\\:00)([\\.,]\\d(?!:))?)?(\\17[0-5]\\d([\\.,]\\d)?)?([zz]|([\\-])([01]\\d|2[0-3]):?([0-5]\\d)?))?)?#\$

[ExecutionStartTime \(p. 255\)](#)

The date and time the plugin started running. Date and time are written in ISO 8601 format. For example, June 7, 2017 is represented as 2017-06-7. The following sample AWS CLI command uses the `InvokedBefore` filter.

```
aws ssm list-commands --filters key=InvokedBefore,value=2017-06-07T00:00:00Z
```

If the plugin hasn't started to run, the string is empty.

Type: String

Pattern: ^([\\-]?\\d{4}(?!\\d{2}\\b))((-?)(\\0[1-9]|1[0-2])(\\3([12]\\d|0[1-9]|3[01]))?|W([0-4]\\d|5[0-2])(-?[1-7])?|(00[1-9]|0[1-9]\\d|[12]\\d{2}|3([0-5]\\d|6[1-6])))([T\\s](([01]\\d|2[0-3])((:?)[0-5]\\d)?|24\\:00)([\\.,]\\d(?!:))?)?(\\17[0-5]\\d([\\.,]\\d)?)?([zz]|([\\-])([01]\\d|2[0-3]):?([0-5]\\d)?))?)?#\$

[InstanceId \(p. 255\)](#)

The ID of the managed node targeted by the command. A *managed node* can be an Amazon Elastic Compute Cloud (Amazon EC2) instance, edge device, or on-premises server or VM in your hybrid environment that is configured for AWS Systems Manager.

Type: String

Pattern: (^i-(\\w{8} | \\w{17}))\$ | (^mi-\\w{17}\$)

[PluginName \(p. 255\)](#)

The name of the plugin, or *step name*, for which details are reported. For example, `aws : RunShellScript` is a plugin.

Type: String

Length Constraints: Minimum length of 4.

[ResponseCode \(p. 255\)](#)

The error level response code for the plugin script. If the response code is `-1`, then the command hasn't started running on the managed node, or it wasn't received by the node.

Type: Integer

[StandardErrorContent \(p. 255\)](#)

The first 8,000 characters written by the plugin to `stderr`. If the command hasn't finished running, then this string is empty.

Type: String

Length Constraints: Maximum length of 8000.

[StandardErrorUrl \(p. 255\)](#)

The URL for the complete text written by the plugin to `stderr`. If the command hasn't finished running, then this string is empty.

Type: String

[StandardOutputContent \(p. 255\)](#)

The first 24,000 characters written by the plugin to `stdout`. If the command hasn't finished running, if `ExecutionStatus` is neither `Succeeded` nor `Failed`, then this string is empty.

Type: String

Length Constraints: Maximum length of 24000.

[StandardOutputUrl \(p. 255\)](#)

The URL for the complete text written by the plugin to `stdout` in Amazon Simple Storage Service (Amazon S3). If an S3 bucket wasn't specified, then this string is empty.

Type: String

[Status \(p. 255\)](#)

The status of this invocation plugin. This status can be different than `StatusDetails`.

Type: String

Valid Values: `Pending` | `InProgress` | `Delayed` | `Success` | `Cancelled` | `TimedOut` | `Failed` | `Cancelling`

[StatusDetails \(p. 255\)](#)

A detailed status of the command execution for an invocation. `StatusDetails` includes more information than `Status` because it includes states resulting from error and concurrency control parameters. `StatusDetails` can show different results than `Status`. For more information about these statuses, see [Understanding command statuses](#) in the *AWS Systems Manager User Guide*. `StatusDetails` can be one of the following values:

- `Pending`: The command hasn't been sent to the managed node.

- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.
- Delayed: The system attempted to send the command to the target, but the target wasn't available. The managed node might not be available because of network issues, because the node was stopped, or for similar reasons. The system will try to send the command again.
- Success: The command or plugin ran successfully. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's `MaxErrors` limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: The command started to run on the managed node, but the execution wasn't complete before the timeout expired. Execution timeouts count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Failed: The command wasn't run successfully on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the `MaxErrors` limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The node might not exist or might not be responding. Undeliverable invocations don't count against the parent command's `MaxErrors` limit and don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Terminated: The parent command exceeded its `MaxErrors` limit and subsequent command invocations were canceled by the system. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidPluginName

The plugin name isn't valid.

HTTP Status Code: 400

InvocationDoesNotExist

The command ID and managed node ID you specified didn't match any invocations. Verify the command ID and the managed node ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetCommandInvocation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetCommandInvocation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200220T235111Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200220/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 90

{
    "CommandId": "32d70fe0-ddbc-4a4e-943f-ffcbcEXAMPLE",
    "InstanceId": "i-02573cafefEXAMPLE"
}
```

Sample Response

```
{
    "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "",
        "CloudWatchOutputEnabled": false
    },
    "CommandId": "32d70fe0-ddbc-4a4e-943f-ffcbcEXAMPLE",
    "Comment": "b48291dd-ba76-43e0-b9df-13e11ddaac26:6960febb-2907-4b59-8e1a-d6ce8EXAMPLE",
    "DocumentName": "AWS-UpdateSSMAgent",
    "DocumentVersion": "",
    "ExecutionElapsedTime": "PT44.002S",
    "ExecutionEndDate": "2020-02-20T23:35:26.758Z",
    "ExecutionStartTime": "2020-02-20T23:34:42.758Z",
    "InstanceId": "i-02573cafefEXAMPLE",
    "PluginName": "aws:updateSsmAgent",
    "ResponseCode": 0,
    "StandardErrorContent": "",
    "StandardErrorUrl": "",
    "StandardOutputContent": "Updating amazon-ssm-agent from 2.3.842.0 to latest
\nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-east-2/
ssm-agent-manifest.json"
}
```

```
\nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-east-2/\namazon-ssm-agent-updater/2.3.871.0/amazon-ssm-agent-updater-windows-amd64.zip\n    \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-east-2/\namazon-ssm-agent/2.3.842.0/amazon-ssm-agent-windows-amd64.zip\n        \nSuccessfully downloaded https://s3.us-east-2.amazonaws.com/amazon-ssm-us-east-2/\namazon-ssm-agent/2.3.871.0/amazon-ssm-agent-windows-amd64.zip\n            \nInitiating amazon-ssm-agent update to 2.3.871.0\n                \nnamazon-ssm-agent updated successfully to 2.3.871.0",\n    "StandardOutputUrl": "",\n    "Status": "Success",\n    "StatusDetails": "Success"\n}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetConnectionStatus

Retrieves the Session Manager connection status for a managed node to determine whether it is running and ready to receive Session Manager connections.

Request Syntax

```
{  
    "Target": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Target (p. 261)

The managed node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

Response Syntax

```
{  
    "Status": "string",  
    "Target": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Status (p. 261)

The status of the connection to the managed node. For example, 'Connected' or 'Not Connected'.

Type: String

Valid Values: Connected | NotConnected

Target (p. 261)

The ID of the managed node to check connection status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetConnectionStatus.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetConnectionStatus
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T180655Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 33

{
    "Target": "i-02573cafefEXAMPLE"
}
```

Sample Response

```
{
    "Status": "connected",
    "Target": "i-02573cafefEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDefaultPatchBaseline

Retrieves the default patch baseline. AWS Systems Manager supports creating multiple default patch baselines. For example, you can create a default patch baseline for each operating system.

If you don't specify an operating system value, the default patch baseline for Windows is returned.

Request Syntax

```
{  
    "OperatingSystem": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

OperatingSystem (p. 264)

Returns the default patch baseline for the specified operating system.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: No

Response Syntax

```
{  
    "BaselineId": "string",  
    "OperatingSystem": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId (p. 264)

The ID of the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

OperatingSystem (p. 264)

The operating system for the returned patch baseline.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetDefaultPatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 35
X-Amz-Target: AmazonSSM.GetDefaultPatchBaseline
X-Amz-Date: 20180309T025228Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "OperatingSystem": "AMAZON_LINUX"
}
```

Sample Response

```
{
    "BaselineId": "arn:aws:ssm:us-east-2:111122223333:patchbaseline/pb-0c10e65780EXAMPLE",
    "OperatingSystem": "AMAZON_LINUX"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDeployablePatchSnapshotForInstance

Retrieves the current snapshot for the patch baseline the managed node uses. This API is primarily used by the AWS-RunPatchBaseline Systems Manager document (SSM document).

Note

If you run the command locally, such as with the AWS Command Line Interface (AWS CLI), the system attempts to use your local AWS credentials and the operation fails. To avoid this, you can run the command in the AWS Systems Manager console. Use Run Command, a capability of AWS Systems Manager, with an SSM document that enables you to target a managed node with a script or command. For example, run the command using the AWS-RunShellScript document or the AWS-RunPowerShellScript document.

Request Syntax

```
{  
    "BaselineOverride": {  
        "ApprovalRules": {  
            "PatchRules": [  
                {  
                    "ApproveAfterDays": number,  
                    "ApproveUntilDate": "string",  
                    "ComplianceLevel": "string",  
                    "EnableNonSecurity": boolean,  
                    "PatchFilterGroup": {  
                        "PatchFilters": [  
                            {  
                                "Key": "string",  
                                "Values": [ "string" ]  
                            }  
                        ]  
                    }  
                }  
            ]  
        },  
        "ApprovedPatches": [ "string" ],  
        "ApprovedPatchesComplianceLevel": "string",  
        "ApprovedPatchesEnableNonSecurity": boolean,  
        "GlobalFilters": {  
            "PatchFilters": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ]  
        },  
        "OperatingSystem": "string",  
        "RejectedPatches": [ "string" ],  
        "RejectedPatchesAction": "string",  
        "Sources": [  
            {  
                "Configuration": "string",  
                "Name": "string",  
                "Products": [ "string" ]  
            }  
        ]  
    },  
    "InstanceId": "string",  
    "SnapshotId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineOverride (p. 267)

Defines the basic information about a patch baseline override.

Type: [BaselineOverride \(p. 623\)](#) object

Required: No

InstanceId (p. 267)

The ID of the managed node for which the appropriate patch snapshot should be retrieved.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: Yes

SnapshotId (p. 267)

The snapshot ID provided by the user when running `AWS-RunPatchBaseline`.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "InstanceId": "string",  
    "Product": "string",  
    "SnapshotDownloadUrl": "string",  
    "SnapshotId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InstanceId (p. 268)

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

[Product \(p. 268\)](#)

Returns the specific operating system (for example Windows Server 2012 or Amazon Linux 2015.09) on the managed node for the specified patch snapshot.

Type: String

[SnapshotDownloadUrl \(p. 268\)](#)

A pre-signed Amazon Simple Storage Service (Amazon S3) URL that can be used to download the patch snapshot.

Type: String

[SnapshotId \(p. 268\)](#)

The user-defined snapshot ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

UnsupportedFeatureRequiredException

Patching for applications released by Microsoft is only available on EC2 instances and advanced instances. To patch applications released by Microsoft on on-premises servers and VMs, you must enable advanced instances. For more information, see [Enabling the advanced-instances tier](#) in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

UnsupportedOperatingSystem

The operating systems you specified isn't supported, or the operation isn't supported for the operating system.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetDeployablePatchSnapshotForInstance`.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 91
X-Amz-Target: AmazonSSM.GetDeployablePatchSnapshotForInstance
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.12 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/ssm.get-
deployable-patch-snapshot-for-instance
X-Amz-Date: 20210618T204500Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210618/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "InstanceId": "i-02573cafccEXAMPLE",
    "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE"
}
```

Sample Response

```
{
    "InstanceId": "i-02573cafccEXAMPLE",
    "SnapshotId": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE",
    "Product": "AmazonLinux2018.03",
    "SnapshotDownloadUrl": "https://doc-example-bucket.s3.us-east-2.amazonaws.com/
b7d801675252464bEXAMPLE--truncated--"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDocument

Gets the contents of the specified AWS Systems Manager document (SSM document).

Request Syntax

```
{  
    "DocumentFormat": "string",  
    "DocumentVersion": "string",  
    "Name": "string",  
    "VersionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentFormat \(p. 271\)](#)

Returns the document in the specified format. The document format can be either JSON or YAML. JSON is the default format.

Type: String

Valid Values: `YAML` | `JSON` | `TEXT`

Required: No

[DocumentVersion \(p. 271\)](#)

The document version for which you want information.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^[\d]{1-9}[\d]*$)`

Required: No

[Name \(p. 271\)](#)

The name of the SSM document.

Type: String

Pattern: `^[\w\-_\.]{3,128}$`

Required: Yes

[VersionName \(p. 271\)](#)

An optional field specifying the version of the artifact associated with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document and can't be changed.

Type: String

Pattern: `^[\w\-_\.]{1,128}$`

Required: No

Response Syntax

```
{  
    "AttachmentsContent": [  
        {  
            "Hash": "string",  
            "HashType": "string",  
            "Name": "string",  
            "Size": number,  
            "Url": "string"  
        }  
    ],  
    "Content": "string",  
    "CreatedDate": number,  
    "DisplayName": "string",  
    "DocumentFormat": "string",  
    "DocumentType": "string",  
    "DocumentVersion": "string",  
    "Name": "string",  
    "Requires": [  
        {  
            "Name": "string",  
            "Version": "string"  
        }  
    ],  
    "ReviewStatus": "string",  
    "Status": "string",  
    "StatusInformation": "string",  
    "VersionName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AttachmentsContent \(p. 272\)](#)

A description of the document attachments, including names, locations, sizes, and so on.

Type: Array of [AttachmentContent \(p. 606\)](#) objects

[Content \(p. 272\)](#)

The contents of the SSM document.

Type: String

Length Constraints: Minimum length of 1.

[CreatedDate \(p. 272\)](#)

The date the SSM document was created.

Type: Timestamp

[DisplayName \(p. 272\)](#)

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see [UpdateDocument \(p. 518\)](#).

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/\]*\$

[DocumentFormat \(p. 272\)](#)

The document format, either JSON or YAML.

Type: String

Valid Values: YAML | JSON | TEXT

[DocumentType \(p. 272\)](#)

The document type.

Type: String

Valid Values: Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate

[DocumentVersion \(p. 272\)](#)

The document version.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

[Name \(p. 272\)](#)

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

[Requires \(p. 272\)](#)

A list of SSM documents required by a document. For example, an ApplicationConfiguration document requires an ApplicationConfigurationSchema document.

Type: Array of [DocumentRequires \(p. 668\)](#) objects

Array Members: Minimum number of 1 item.

[ReviewStatus \(p. 272\)](#)

The current review status of a new custom Systems Manager document (SSM document) created by a member of your organization, or of the latest version of an existing SSM document.

Only one version of an SSM document can be in the APPROVED state at a time. When a new version is approved, the status of the previous version changes to REJECTED.

Only one version of an SSM document can be in review, or PENDING, at a time.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

[Status \(p. 272\)](#)

The status of the SSM document, such as Creating, Active, Updating, Failed, and Deleting.

Type: String

Valid Values: `Creating` | `Active` | `Updating` | `Deleting` | `Failed`

[StatusInformation \(p. 272\)](#)

A message returned by AWS Systems Manager that explains the `Status` value. For example, a `Failed` status might be explained by the `StatusInformation` message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

[VersionName \(p. 272\)](#)

The version of the artifact associated with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{1,128}$`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetDocument`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T190721Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 30
```

```
{  
    "Name": "AWS-UpdateSSMAgent"  
}
```

Sample Response

```
{  
    "Content": "{\n        \"schemaVersion\": \"1.2\",\\n        \"description\": \"Update the Amazon  
        SSM Agent to the latest version or specified version.\",--truncated--n\",  
        \"DocumentFormat\": \"JSON\",  
        \"DocumentType\": \"Command\",  
        \"DocumentVersion\": \"1\",  
        \"Name\": \"AWS-UpdateSSMAgent\",  
        \"Status\": \"Active\"\n    }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetInventory

Query inventory information. This includes managed node status, such as `Stopped` or `Terminated`.

Request Syntax

```
{  
    "Aggregators": [  
        {  
            "Aggregators": [  
                "InventoryAggregator"  
            ],  
            "Expression": "string",  
            "Groups": [  
                {  
                    "Filters": [  
                        {  
                            "Key": "string",  
                            "Type": "string",  
                            "Values": [ "string" ]  
                        }  
                    ],  
                    "Name": "string"  
                }  
            ]  
        }  
    ],  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResultAttributes": [  
        {  
            "TypeName": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Aggregators (p. 276)

Returns counts of inventory types based on one or more expressions. For example, if you aggregate by using an expression that uses the `AWS:InstanceInformation.PlatformType` type, you can see a count of how many Windows and Linux managed nodes exist in your inventoried fleet.

Type: Array of [InventoryAggregator \(p. 698\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

Filters (p. 276)

One or more filters. Use a filter to return a more specific list of results.

Type: Array of [InventoryFilter \(p. 703\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

MaxResults (p. 276)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 276)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

ResultAttributes (p. 276)

The list of inventory item types to return.

Type: Array of [ResultAttribute \(p. 819\)](#) objects

Array Members: Fixed number of 1 item.

Required: No

Response Syntax

```
{  
    "Entities": [  
        {  
            "Data": {  
                "string" : {  
                    "CaptureTime": "string",  
                    "Content": [  
                        {  
                            "string" : "string"  
                        }  
                    ],  
                    "ContentHash": "string",  
                    "SchemaVersion": "string",  
                    "TypeName": "string"  
                }  
            },  
            "Id": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entities (p. 277)

Collection of inventory entities such as a collection of managed node inventory.

Type: Array of [InventoryResultEntity](#) (p. 709) objects

NextToken (p. 277)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 847).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAggregatorException

The specified aggregator isn't valid for inventory groups. Verify that the aggregator uses a valid inventory type such as `AWS:Application` or `AWS:InstanceInformation`.

HTTP Status Code: 400

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidInventoryGroupException

The specified inventory group isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidResultAttributeException

The specified inventory item result attribute isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetInventory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetInventory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T145054Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Entities": [
        {
            "Data": {
                "Id": "i-04bf6ad63bEXAMPLE",
                "AWS:InstanceInformation": {
                    "TypeName": "AWS:InstanceInformation",
                    "SchemaVersion": "1.0",
                    "CaptureTime": "2020-03-30T14:00:57Z",
                    "Content": [
                        {
                            "AgentType": "amazon-ssm-agent",
                            "AgentVersion": "2.3.930.0",
                            "ComputerName": "EC2AMAZ-EXAMPLE.WORKGROUP",
                            "InstanceId": "i-04bf6ad63bEXAMPLE",
                            "InstanceState": "Stopped",
                            "IpAddress": "172.16.0.4",
                            "PlatformName": "Microsoft Windows Server 2016 Datacenter",
                            "PlatformType": "Windows",
                            "PlatformVersion": "10.0.14393",
                            "ResourceType": "EC2Instance"
                        }
                    ]
                }
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetInventorySchema

Return a list of inventory type names for the account, or return a list of attribute names for a specific Inventory item type.

Request Syntax

```
{  
    "Aggregator": boolean,  
    "MaxResults": number,  
    "NextToken": string,  
    "SubType": boolean,  
    "TypeName": string  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Aggregator \(p. 281\)](#)

Returns inventory schemas that support aggregation. For example, this call returns the AWS:InstanceInformation type, because it supports aggregation based on the PlatformName, PlatformType, and PlatformVersion attributes.

Type: Boolean

Required: No

[MaxResults \(p. 281\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 50. Maximum value of 200.

Required: No

[NextToken \(p. 281\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[SubType \(p. 281\)](#)

Returns the sub-type schema for a specified inventory type.

Type: Boolean

Required: No

[TypeName \(p. 281\)](#)

The type of inventory item to return.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Schemas": [  
        {  
            "Attributes": [  
                {  
                    "DataType": "string",  
                    "Name": "string"  
                }  
            ],  
            "DisplayName": "string",  
            "TypeName": "string",  
            "Version": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 282\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[Schemas \(p. 282\)](#)

Inventory schemas returned by the request.

Type: Array of [InventoryItemSchema \(p. 708\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetInventorySchema.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetInventorySchema
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T150040Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
  "Schemas": [
    {
      "Attributes": [
        {
          "Name": "Name",
          "Type": "String"
        },
        {
          "Name": "ApplicationType",
          "Type": "String"
        },
        {
          "Name": "Publisher",
          "Type": "String"
        },
        {
          "Name": "Version",
          "Type": "String"
        },
        {
          "Name": "InstalledTime",
          "Type": "String"
        },
        {
          "Name": "Architecture",
          "Type": "String"
        },
        {
          "Name": "URL",
          "Type": "String"
        }
      ]
    }
  ]
}
```

```
],
  "TypeName": "AWS:AWSComponent",
  "Version": "1.0"
},--truncated--
{
  "Attributes": [
    {
      "DataType": "STRING",
      "Name": "Name"
    },
    {
      "DataType": "STRING",
      "Name": "DisplayName"
    },
    {
      "DataType": "STRING",
      "Name": "ServiceType"
    },
    {
      "DataType": "STRING",
      "Name": "Status"
    },
    {
      "DataType": "STRING",
      "Name": "DependentServices"
    },
    {
      "DataType": "STRING",
      "Name": "ServicesDependedOn"
    },
    {
      "DataType": "STRING",
      "Name": "StartType"
    }
  ],
  "TypeName": "AWS:Service",
  "Version": "1.0"
}--truncated--
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMaintenanceWindow

Retrieves a maintenance window.

Request Syntax

```
{  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

WindowId (p. 285)

The ID of the maintenance window for which you want to retrieve information.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "AllowUnassociatedTargets": boolean,  
    "CreatedDate": number,  
    "Cutoff": number,  
    "Description": "string",  
    "Duration": number,  
    "Enabled": boolean,  
    "EndDate": "string",  
    "ModifiedDate": number,  
    "Name": "string",  
    "NextExecutionTime": "string",  
    "Schedule": "string",  
    "ScheduleOffset": number,  
    "ScheduleTimezone": "string",  
    "StartDate": "string",  
    "WindowId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AllowUnassociatedTargets \(p. 285\)](#)

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

[CreatedDate \(p. 285\)](#)

The date the maintenance window was created.

Type: Timestamp

[Cutoff \(p. 285\)](#)

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

[Description \(p. 285\)](#)

The description of the maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[Duration \(p. 285\)](#)

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

[Enabled \(p. 285\)](#)

Indicates whether the maintenance window is enabled.

Type: Boolean

[EndDate \(p. 285\)](#)

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive. The maintenance window won't run after this specified time.

Type: String

[ModifiedDate \(p. 285\)](#)

The date the maintenance window was last modified.

Type: Timestamp

[Name \(p. 285\)](#)

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

[NextExecutionTime \(p. 285\)](#)

The next time the maintenance window will actually run, taking into account any specified times for the maintenance window to become active or inactive.

Type: String

[Schedule \(p. 285\)](#)

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

[ScheduleOffset \(p. 285\)](#)

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

[ScheduleTimezone \(p. 285\)](#)

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the [Time Zone Database](#) on the IANA website.

Type: String

[StartDate \(p. 285\)](#)

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active. The maintenance window won't run before this specified time.

Type: String

[WindowId \(p. 285\)](#)

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the [Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 36
X-Amz-Target: AmazonSSM.GetMaintenanceWindow
X-Amz-Date: 20200312T203140Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

Sample Response

```
{
    "AllowUnassociatedTargets": true,
    "CreatedDate": 1515006912.957,
    "Cutoff": 1,
    "Duration": 6,
    "Enabled": true,
    "ModifiedDate": "2020-01-01T10:04:04.099Z",
    "Name": "My-Maintenance-Window",
    "Schedule": "rate(3 days)",
    "WindowId": "mw-0c50858d01EXAMPLE",
    "NextExecutionTime": "2020-02-25T00:08:15.099Z"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMaintenanceWindowExecution

Retrieves details about a specific a maintenance window execution.

Request Syntax

```
{  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

WindowExecutionId (p. 290)

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "EndTime": number,  
    "StartTime": number,  
    "Status": "string",  
    "StatusDetails": "string",  
    "TaskIds": [ "string" ],  
    "WindowExecutionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EndTime (p. 290)

The time the maintenance window finished running.

Type: Timestamp

StartTime (p. 290)

The time the maintenance window started running.

Type: Timestamp

[Status \(p. 290\)](#)

The status of the maintenance window execution.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

[StatusDetails \(p. 290\)](#)

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

[TaskIds \(p. 290\)](#)

The ID of the task executions from the maintenance window execution.

Type: Array of strings

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

[WindowExecutionId \(p. 290\)](#)

The ID of the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 61
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecution
X-Amz-Date: 20180312T205830Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "9fac7dd9-ff21-42a5-96ad-bbc4bEXAMPLE",
    "TaskIds": [
        "4b9f371e-a820-422d-b432-8dec9EXAMPLE"
    ],
    "Status": "SUCCESS",
    "StartTime": "2021-08-04T11:45:34.994000-07:00",
    "EndTime": "2021-08-04T11:48:09.123000-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMaintenanceWindowExecutionTask

Retrieves the details about a specific task run as part of a maintenance window execution.

Request Syntax

```
{  
    "TaskId": "string",  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[TaskId \(p. 293\)](#)

The ID of the specific task execution in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

[WindowExecutionId \(p. 293\)](#)

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "EndTime": number,  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Priority": number,  
    "ServiceRole": "string",  
    "StartTime": number,  
    "Status": "string",  
    "StatusDetails": "string",  
    "TaskArn": "string",  
}
```

```
"TaskExecutionId": "string",
"TaskParameters": [
    {
        "string" : {
            "Values": [ "string" ]
        }
    }
],
"Type": "string",
"WindowExecutionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EndTime \(p. 293\)](#)

The time the task execution completed.

Type: Timestamp

[MaxConcurrency \(p. 293\)](#)

The defined maximum number of task executions that could be run in parallel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)\$

[MaxErrors \(p. 293\)](#)

The defined maximum number of task execution errors allowed before scheduling of the task execution would have been stopped.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]|1|[1-9][0-9]%'|[0-9]%'|100%)\$

[Priority \(p. 293\)](#)

The priority of the task.

Type: Integer

Valid Range: Minimum value of 0.

[ServiceRole \(p. 293\)](#)

The role that was assumed when running the task.

Type: String

[StartTime \(p. 293\)](#)

The time the task execution started.

Type: Timestamp

[Status \(p. 293\)](#)

The status of the task.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

[StatusDetails \(p. 293\)](#)

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

[TaskArn \(p. 293\)](#)

The Amazon Resource Name (ARN) of the task that ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

[TaskExecutionId \(p. 293\)](#)

The ID of the specific task execution in the maintenance window task that was retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

[TaskParameters \(p. 293\)](#)

The parameters passed to the task when it was run.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

The map has the following format:

- Key: string, between 1 and 255 characters
- Value: an array of strings, each between 1 and 255 characters

Type: Array of string to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object maps

Key Length Constraints: Minimum length of 1. Maximum length of 255.

[Type \(p. 293\)](#)

The type of task that was run.

Type: String

Valid Values: RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA

[WindowExecutionId \(p. 293\)](#)

The ID of the maintenance window execution that includes the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecutionTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecutionTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T001515Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 111

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef436EXAMPLE",
    "TaskId": "0c9ac961-daf8-4a94-b6c7-1bef3EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef436EXAMPLE",
    "TaskExecutionId": "0c9ac961-daf8-4a94-b6c7-1bef3EXAMPLE",
    "TaskArn": "AWS-RunPatchBaseline",
```

```
"ServiceRole": "arn:aws:iam::111122223333:role/aws-service-role/ssm.amazonaws.com/  
AWSServiceRoleForAmazonSSM",  
    "Type": "RUN_COMMAND",  
    "TaskParameters": [  
        {  
            "BaselineOverride": {  
                "Values": [  
                    ""  
                ]  
            },  
            "InstallOverrideList": {  
                "Values": [  
                    ""  
                ]  
            },  
            "Operation": {  
                "Values": [  
                    "Scan"  
                ]  
            },  
            "RebootOption": {  
                "Values": [  
                    "RebootIfNeeded"  
                ]  
            },  
            "SnapshotId": {  
                "Values": [  
                    "{{ aws:ORCHESTRATION_ID }}"  
                ]  
            },  
            "aws:InstanceId": {  
                "Values": [  
                    "i-02573cafefEXAMPLE",  
                    "i-0471e04240EXAMPLE",  
                    "i-07782c72faEXAMPLE"  
                ]  
            }  
        }  
    ],  
    "Priority": 1,  
    "MaxConcurrency": "1",  
    "MaxErrors": "3",  
    "Status": "SUCCESS",  
    "StartTime": "2021-08-04T11:45:35.088000-07:00",  
    "EndTime": "2021-08-04T11:48:09.079000-07:00"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMaintenanceWindowExecutionTaskInvocation

Retrieves information about a specific task running on a specific target.

Request Syntax

```
{  
    "InvocationId": "string",  
    "TaskId": "string",  
    "WindowExecutionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

InvocationId (p. 299)

The invocation ID to retrieve.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

TaskId (p. 299)

The ID of the specific task in the maintenance window task that should be retrieved.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

WindowExecutionId (p. 299)

The ID of the maintenance window execution for which the task is a part.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "EndTime": number,  
    "ExecutionId": "string",  
    "InvocationId": "string",  
    "OwnerInformation": "string",  
    "Parameters": "string",  
    "StartTime": number,  
    "Status": "string",  
    "StatusDetails": "string",  
    "TaskExecutionId": "string",  
    "TaskType": "string",  
    "WindowExecutionId": "string",  
    "WindowTargetId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EndTime \(p. 300\)](#)

The time that the task finished running on the target.

Type: Timestamp

[ExecutionId \(p. 300\)](#)

The execution ID.

Type: String

[InvocationId \(p. 300\)](#)

The invocation ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

[OwnerInformation \(p. 300\)](#)

User-provided value to be included in any Amazon CloudWatch Events or Amazon EventBridge events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[Parameters \(p. 300\)](#)

The parameters used at the time that the task ran.

Type: String

[StartTime \(p. 300\)](#)

The time that the task started running on the target.

Type: Timestamp

[Status \(p. 300\)](#)

The task status for an invocation.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

[StatusDetails \(p. 300\)](#)

The details explaining the status. Details are only available for certain status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

[TaskExecutionId \(p. 300\)](#)

The task execution ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

[TaskType \(p. 300\)](#)

Retrieves the task type for a maintenance window.

Type: String

Valid Values: RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA

[WindowExecutionId \(p. 300\)](#)

The maintenance window execution ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

[WindowTargetId \(p. 300\)](#)

The maintenance window target ID.

Type: String

Length Constraints: Maximum length of 36.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowExecutionTaskInvocation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowExecutionTaskInvocation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T001923Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 167

{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
    "TaskId": "0c9ac961-dafdf-4a94-b6c7-1bef3EXAMPLE",
    "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE"
}
```

Sample Response

```
{
    "WindowExecutionId": "b40a588d-32a7-4ea7-9a6b-b4ef4EXAMPLE",
    "TaskExecutionId": "0c9ac961-dafdf-4a94-b6c7-1bef3EXAMPLE",
    "InvocationId": "0e466033-290b-4d74-9ae0-f33e3EXAMPLE",
    "ExecutionId": "1203cf98-5a79-4ec3-97e9-12e0bEXAMPLE",
    "TaskType": "RUN_COMMAND",
    "Parameters": "{\"comment\": \"\", \"documentName\": \"AWS-ApplyPatchBaseline\", \"instanceIds\": [\"i-02573cafccEXAMPLE\", \"i-0471e04240EXAMPLE\"], \"maxConcurrency\": \"1\", \"maxErrors\": \"1\", \"parameters\": {\"SnapshotId\": [\"\"], \"Operation\": [\"Install\"]}}, \"timeoutSeconds\": \"600\"}",
    "Status": "SUCCESS",
    "StatusDetails": "Success",
    "StartTime": "2021-08-04T11:45:35.141000-07:00",
    "EndTime": "2021-08-04T11:48:08.960000-07:00"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetMaintenanceWindowTask

Retrieves the details of a maintenance window task.

Note

For maintenance window tasks without a specified target, you can't supply values for `--max-errors` and `--max-concurrency`. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. These values don't affect the running of your task and can be ignored.

To retrieve a list of tasks in a maintenance window, instead use the [DescribeMaintenanceWindowTasks \(p. 208\)](#) command.

Request Syntax

```
{  
    "WindowId": "string",  
    "WindowTaskId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[WindowId \(p. 304\)](#)

The maintenance window ID that includes the task to retrieve.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

[WindowTaskId \(p. 304\)](#)

The maintenance window task ID to retrieve.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{
```

```
"CutoffBehavior": "string",
"Description": "string",
"LoggingInfo": {
    "S3BucketName": "string",
    "S3KeyPrefix": "string",
    "S3Region": "string"
},
"MaxConcurrency": "string",
"MaxErrors": "string",
"Name": "string",
"Priority": number,
"ServiceRoleArn": "string",
"Targets": [
    {
        "Key": "string",
        "Values": [ "string" ]
    }
],
"TaskArn": "string",
"TaskInvocationParameters": {
    "Automation": {
        "DocumentVersion": "string",
        "Parameters": {
            "string" : [ "string" ]
        }
    },
    "Lambda": {
        "ClientContext": "string",
        "Payload": blob,
        "Qualifier": "string"
    },
    "RunCommand": {
        "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
        },
        "Comment": "string",
        "DocumentHash": "string",
        "DocumentHashType": "string",
        "DocumentVersion": "string",
        "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
        },
        "OutputS3BucketName": "string",
        "OutputS3KeyPrefix": "string",
        "Parameters": {
            "string" : [ "string" ]
        },
        "ServiceRoleArn": "string",
        "TimeoutSeconds": number
    },
    "StepFunctions": {
        "Input": "string",
        "Name": "string"
    }
},
"TaskParameters": {
    "string" : {
        "Values": [ "string" ]
    }
},
"TaskType": "string",
"WindowId": "string",
"WindowTaskId": "string"
```

}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CutoffBehavior \(p. 304\)](#)

The action to take on tasks when the maintenance window cutoff time is reached. `CONTINUE_TASK` means that tasks continue to run. For Automation, AWS Lambda, AWS Step Functions tasks, `CANCEL_TASK` means that currently running task invocations continue, but no new task invocations are started. For Run Command tasks, `CANCEL_TASK` means the system attempts to stop the task by sending a `CancelCommand` operation.

Type: String

Valid Values: `CONTINUE_TASK` | `CANCEL_TASK`

[Description \(p. 304\)](#)

The retrieved task description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[LoggingInfo \(p. 304\)](#)

The location in Amazon Simple Storage Service (Amazon S3) where the task results are logged.

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: [LoggingInfo \(p. 712\)](#) object

[MaxConcurrency \(p. 304\)](#)

The maximum number of targets allowed to run this task in parallel.

Note

For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. This value doesn't affect the running of your task and can be ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)$`

[MaxErrors \(p. 304\)](#)

The maximum number of errors allowed before the task stops being scheduled.

Note

For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1, which may be reported in the response to this command. This value doesn't affect the running of your task and can be ignored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]|1[1-9][0-9]%^|[0-9]%^|100%)\$

[Name \(p. 304\)](#)

The retrieved task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

[Priority \(p. 304\)](#)

The priority of the task when it runs. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

[ServiceRoleArn \(p. 304\)](#)

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for maintenance window Run Command tasks.

Type: String

[Targets \(p. 304\)](#)

The targets where the task should run.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

[TaskArn \(p. 304\)](#)

The resource that the task used during execution. For `RUN_COMMAND` and `AUTOMATION` task types, the value of `TaskArn` is the SSM document name/ARN. For `LAMBDA` tasks, the value is the function name/ARN. For `STEP_FUNCTIONS` tasks, the value is the state machine ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

[TaskInvocationParameters \(p. 304\)](#)

The parameters to pass to the task when it runs.

Type: [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#) object

[TaskParameters \(p. 304\)](#)

The parameters to pass to the task when it runs.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: String to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

[TaskType \(p. 304\)](#)

The type of task to run.

Type: String

Valid Values: `RUN_COMMAND` | `AUTOMATION` | `STEP_FUNCTIONS` | `LAMBDA`

[WindowId \(p. 304\)](#)

The retrieved maintenance window ID.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

[WindowTaskId \(p. 304\)](#)

The retrieved maintenance window task ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}$`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetMaintenanceWindowTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetMaintenanceWindowTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T002532Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 92

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"
}
```

Sample Response

```
{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE",
    "Name": "MyRunCommandTask",
    "Targets": [
        {
            "Key": "WindowTargetIds",
            "Values": [
                "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-ApplyPatchBaseline",
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/ssm.amazonaws.com/
AWSServiceRoleForAmazonSSM",
    "TaskType": "RUN_COMMAND",
    "TaskParameters": {},
    "Priority": 1,
    "TaskInvocationParameters": {
        "RunCommand": {
            "Comment": "",
            "Parameters": {
                "Operation": [
                    "Install"
                ],
                "SnapshotId": [
                    ""
                ]
            },
            "TimeoutSeconds": 600
        }
    },
    "MaxConcurrency": "1",
    "MaxErrors": "1"
```

}

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOpsItem

Get information about an OpsItem by using the ID. You must have permission in AWS Identity and Access Management (IAM) to view information about an OpsItem. For more information, see [Getting started with OpsCenter](#) in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see [OpsCenter](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "OpsItemId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

OpsItemId (p. 311)

The ID of the OpsItem that you want to get.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: Yes

Response Syntax

```
{  
    "OpsItem": {  
        "ActualEndTime": number,  
        "ActualStartTime": number,  
        "Category": "string",  
        "CreatedBy": "string",  
        "CreatedTime": number,  
        "Description": "string",  
        "LastModifiedBy": "string",  
        "LastModifiedTime": number,  
        "Notifications": [  
            {  
                "Arn": "string"  
            }  
        ],  
        "OperationalData": {  
            "string" : {  
                "Type": "string",  
                "Value": "string"  
            }  
        },  
        "OpsItemId": "string",  
        "OpsItemSummary": {  
            "Category": "string",  
            "Description": "string",  
            "LastModifiedTime": number,  
            "Severity": "string",  
            "Status": "string",  
            "Title": "string",  
            "Type": "string"  
        },  
        "Source": "string",  
        "State": "string",  
        "StateChangeTime": number,  
        "StateHistory": [  
            {  
                "ChangeTime": number,  
                "NewState": "string",  
                "OldState": "string"  
            }  
        ]  
    }  
}
```

```
"OpsItemType": "string",
"PlannedEndTime": number,
"PlannedStartTime": number,
"Priority": number,
"RelatedOpsItems": [
    {
        "OpsItemId": "string"
    }
],
"Severity": "string",
"Source": "string",
"Status": "string",
"Title": "string",
"Version": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

OpsItem (p. 311)

The OpsItem.

Type: [OpsItem \(p. 749\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetOpsItem
```

```
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T153712Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 32

{
    "OpsItemId": "oi-f99f2EXAMPLE"
}
```

Sample Response

```
{
    "OpsItem": {
        "Category": "Availability",
        "CreatedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
        "CreatedTime": 1582701517.193,
        "Description": "CloudWatch Event Rule SSMOpsItems-SSM-maintenance-window-execution-
failed was triggered. Your SSM Maintenance Window execution has failed. See below for more
details.",
        "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/OpsCenterRole/
af3935bb93783f02aeea51784EXAMPLE",
        "LastModifiedTime": 1582701517.193,
        "Notifications": [],
        "OperationalData": {
            "/aws/dedup": {
                "Type": "SearchableString",
                "Value": "{\"dedupString\":\"SSMOpsItems-SSM-maintenance-window-execution-
failed\"}"
            },
            "/aws/resources": {
                "Type": "SearchableString",
                "Value": "[{\"arn\":\"arn:aws:ssm:us-east-2:111122223333:maintenancewindow/
mw-0e357ebdc6EXAMPLE\"}]"
            },
            "window-execution-id": {
                "Type": "String",
                "Value": "e79e904b-0e42-43b8-a83d-b2aedEXAMPLE"
            },
            "window-id": {
                "Type": "String",
                "Value": "mw-0e357ebdc6EXAMPLE"
            }
        },
        "OpsItemId": "oi-f99f2EXAMPLE",
        "RelatedOpsItems": [],
        "Severity": "3",
        "Source": "SSM",
        "Status": "Open",
        "Title": "SSM Maintenance Window execution failed"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOpsMetadata

View operational metadata related to an application in Application Manager.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "OpsMetadataArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 315)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

NextToken (p. 315)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

OpsMetadataArn (p. 315)

The Amazon Resource Name (ARN) of an OpsMetadata Object to view.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*|)

Required: Yes

Response Syntax

```
{  
    "Metadata": {  
        "string": {  
            "Value": "string"  
        }  
    }  
}
```

```
        },
        "NextToken": "string",
        "ResourceId": "string"
    }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Metadata \(p. 315\)](#)

OpsMetadata for an Application Manager application.

Type: String to [MetadataValue \(p. 741\)](#) object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `^(?!\\s*$).+`

[NextToken \(p. 315\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[ResourceId \(p. 315\)](#)

The resource ID of the Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOpsSummary

View a summary of operations metadata (OpsData) based on specified filters and aggregators. OpsData can include information about AWS Systems Manager OpsCenter operational workitems (OpsItems) as well as information about any AWS resource or service configured to report OpsData to AWS Systems Manager Explorer.

Request Syntax

```
{  
    "Aggregators": [  
        {  
            "Aggregators": [  
                "OpsAggregator"  
            ],  
            "AggregatorType": "string",  
            "AttributeName": "string",  
            "Filters": [  
                {  
                    "Key": "string",  
                    "Type": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "TypeName": "string",  
            "Values": {  
                "string" : "string"  
            }  
        }  
    ],  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResultAttributes": [  
        {  
            "TypeName": "string"  
        }  
    ],  
    "SyncName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Aggregators \(p. 318\)](#)

Optional aggregators that return counts of OpsData based on one or more expressions.

Type: Array of [OpsAggregator \(p. 744\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 12 items.

Required: No

[Filters \(p. 318\)](#)

Optional filters used to scope down the returned OpsData.

Type: Array of [OpsFilter \(p. 748\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[MaxResults \(p. 318\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 318\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

[ResultAttributes \(p. 318\)](#)

The OpsData data type to return.

Type: Array of [OpsResultAttribute \(p. 769\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

[SyncName \(p. 318\)](#)

Specify the name of a resource data sync to get.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{  
    "Entities": [  
        {  
            "Data": {  
                "string" : {  
                    "CaptureTime": "string",  
                    "Content": [  
                        {  
                            "string" : "string"  
                        }  
                    ]  
                }  
            }  
        }  
    ]  
}
```

```
        }
    ],
    "Id": "string"
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entities (p. 319)

The list of aggregated details and filtered OpsData.

Type: Array of [OpsEntity \(p. 746\)](#) objects

NextToken (p. 319)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAggregatorException

The specified aggregator isn't valid for inventory groups. Verify that the aggregator uses a valid inventory type such as AWS:Application or AWS:InstanceInformation.

HTTP Status Code: 400

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetOpsSummary.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetOpsSummary
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T152044Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Entities": [
        {
            "Data": {
                "AWS:OpsItem": {
                    "CaptureTime": "2020-02-26T05:59:57.430Z",
                    "Content": [
                        {
                            "AccountId": "111122223333",
                            "Category": "Availability",
                            "CreatedBy": "arn:aws:sts::111122223333:assumed-role/
OpsCenterRole/af3935bb93783f02aeea51784EXAMPLE",
                            "CreatedTime": "2020-02-26T07:18:37.193Z",
                            "Description": "CloudWatch Event Rule SSMOpsItems-SSM-
maintenance-window-execution-failed was triggered. Your SSM Maintenance Window execution
has failed. See below for more details.",
                            "LastModifiedBy": "arn:aws:sts::111122223333:assumed-role/
OpsCenterRole/af3935bb93783f02aeea51784EXAMPLE",
                            "LastModifiedTime": "2020-02-26T07:18:37.193Z",
                            "Notifications": "",
                            "OperationalData": "{\"/aws/resources\":{\"type
\":\"\\\"SearchableString\\\", \"value\":\"[{}\\\"arn\\\\\\\" :\\\\\\\"arn:aws:ssm:us-
east-2:111122223333:maintenancewindow/mw-0e357ebdc6EXAMPLE\\\\\\\"]\\\"}, \"/aws/dedup\":{\"type
\":\"\\\"SearchableString\\\", \"value\":\"[\\\\\\\"dedupString\\\\\\\" :\\\\\\\"SSMOpsItems-SSM-maintenance-
window-execution-failed\\\\\\\"]\\\"}}}",
                            "OpsItemId": "oi-f99f2EXAMPLE",
                            "RelatedItems": "",
                            "Severity": "3",
                            "Source": "SSM",
                            "Status": "Open",
                            "Title": "SSM Maintenance Window execution failed"
                        }
                    ]
                }
            }
        }
    ]
}
```

```
        ]
    },
    "Id": "oi-f99f2EXAMPLE"
},---truncated---
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetParameter

Get information about a single parameter by specifying the parameter name.

Note

To get information about more than one parameter at a time, use the [GetParameters \(p. 330\)](#) operation.

Request Syntax

```
{  
    "Name": "string",  
    "WithDecryption": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Name (p. 323)

The name of the parameter you want to query.

To query by parameter label, use "Name": "name:label". To query by parameter version, use "Name": "name:version".

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

WithDecryption (p. 323)

Return decrypted values for secure string parameters. This flag is ignored for String and StringList parameter types.

Type: Boolean

Required: No

Response Syntax

```
{  
    "Parameter": {  
        "ARN": "string",  
        "DataType": "string",  
        "LastModifiedDate": number,  
        "Name": "string",  
        "Selector": "string",  
        "SourceResult": "string",  
        "Type": "string",  
        "Value": "string",  
        "Version": number  
    }  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Parameter (p. 323)

Information about a parameter.

Type: [Parameter \(p. 771\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 29
X-Amz-Target: AmazonSSM.GetParameter
X-Amz-Date: 20180316T005724Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
```

```
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "MyGitHubPassword"
}
```

Sample Response

```
{
    "Parameter": {
        "ARN": "arn:aws:ssm:us-east-2:111122223333:parameter/MyGitHubPassword",
        "DataType": "text",
        "LastModifiedDate": 1582657288.8,
        "Name": "MyGitHubPassword",
        "Type": "SecureString",
        "Value": "AYA39c3b3042cd2aEXAMPLE/AKIAIOSFODNN7EXAMPLE/fh983hg9awEXAMPLE==",
        "Version": 3
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetParameterHistory

Retrieves the history of all changes to a parameter.

Important

If you change the KMS key alias for the KMS key used to encrypt a parameter, then you must also update the key alias the parameter uses to reference KMS. Otherwise, `GetParameterHistory` retrieves whatever the original key alias was referencing.

Request Syntax

```
{  
    "MaxResults": number,  
    "Name": "string",  
    "NextToken": "string",  
    "WithDecryption": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 326\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[Name \(p. 326\)](#)

The name of the parameter for which you want to review history.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

[NextToken \(p. 326\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[WithDecryption \(p. 326\)](#)

Return decrypted values for secure string parameters. This flag is ignored for `String` and `StringList` parameter types.

Type: Boolean

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Parameters": [  
        {  
            "AllowedPattern": "string",  
            "DataType": "string",  
            "Description": "string",  
            "KeyId": "string",  
            "Labels": [ "string" ],  
            "LastModifiedDate": number,  
            "LastModifiedUser": "string",  
            "Name": "string",  
            "Policies": [  
                {  
                    "PolicyStatus": "string",  
                    "PolicyText": "string",  
                    "PolicyType": "string"  
                }  
            ],  
            "Tier": "string",  
            "Type": "string",  
            "Value": "string",  
            "Version": number  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 327\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[Parameters \(p. 327\)](#)

A list of parameters returned by the request.

Type: Array of [ParameterHistory \(p. 773\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameterHistory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 29
X-Amz-Target: AmazonSSM.GetParameterHistory
X-Amz-Date: 20180316T005206Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Name": "EC2TestServerType"
}
```

Sample Response

```
{
    "Parameters": [
        {
            "Description": "Instance type for Test servers",
            "LastModifiedDate": 1521158745.607,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "EC2TestServerType",
            "Policies": [],
            "Type": "String",
            "Value": "t2.nano",
            "Version": 1
        },
        {
            "Description": "Instance type for Test servers",
            "LastModifiedDate": 1521158834.467,
            "LastModifiedUser": "arn:aws:iam::111122223333:user/Mateo.Jackson",
            "Name": "EC2TestServerType",
            "Policies": []
        }
    ]
}
```

```
        "Policies": [],
        "Type": "String",
        "Value": "t2.micro",
        "Version": 2
    },
    {
        "Description": "Instance type for Test servers",
        "LastModifiedDate": 1521158912.828,
        "LastModifiedUser": "arn:aws:iam::111122223333:user/Jane.Roe",
        "Name": "EC2TestServerType",
        "Policies": [],
        "Type": "String",
        "Value": "t2.large",
        "Version": 3
    }
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetParameters

Get information about one or more parameters by specifying multiple parameter names.

Note

To get information about a single parameter, you can use the [GetParameter \(p. 323\)](#) operation instead.

Request Syntax

```
{  
    "Names": [ "string" ],  
    "WithDecryption": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Names \(p. 330\)](#)

Names of the parameters for which you want to query information.

To query by parameter label, use "Name": "name:label". To query by parameter version, use "Name": "name:version".

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

[WithDecryption \(p. 330\)](#)

Return decrypted secure string value. Return decrypted values for secure string parameters. This flag is ignored for `String` and `StringList` parameter types.

Type: Boolean

Required: No

Response Syntax

```
{  
    "InvalidParameters": [ "string" ],  
    "Parameters": [  
        {  
            "ARN": "string",  
            "DataType": "string",  
            "LastModifiedDate": number,  
            "Name": "string",  
            "Selector": "string",  
            "Type": "string"  
        }  
    ]  
}
```

```
        "SourceResult": "string",
        "Type": "string",
        "Value": "string",
        "Version": number
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidParameters (p. 330)

A list of parameters that aren't formatted correctly or don't run during an execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Parameters (p. 330)

A list of details for a parameter.

Type: Array of [Parameter](#) (p. 771) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 847).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetParameters.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
```

```
Content-Length: 73
X-Amz-Target: AmazonSSM.GetParameters
X-Amz-Date: 20180316T001029Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Names": [
        "EC2DevServerType",
        "EC2TestServerType",
        "EC2ProdServerType"
    ]
}
```

Sample Response

```
{
    "InvalidParameters": [],
    "Parameters": [
        {
            "Name": "EC2DevServerType",
            "Type": "String",
            "Value": "t2.micro",
            "Version": 2
        },
        {
            "Name": "EC2ProdServerType",
            "Type": "String",
            "Value": "m4.large",
            "Version": 1
        },
        {
            "Name": "EC2TestServerType",
            "Type": "String",
            "Value": "t2.large",
            "Version": 3
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetParametersByPath

Retrieve information about one or more parameters in a specific hierarchy.

Request results are returned on a best-effort basis. If you specify `MaxResults` in the request, the response includes information up to the limit specified. The number of items returned, however, can be between zero and the value of `MaxResults`. If the service reaches an internal limit while processing the results, it stops the operation and returns the matching values up to that point and a `NextToken`. You can specify the `NextToken` in a subsequent call to get the next set of results.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "ParameterFilters": [  
        {  
            "Key": "string",  
            "Option": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "Path": "string",  
    "Recursive": boolean,  
    "WithDecryption": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 333)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

NextToken (p. 333)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ParameterFilters (p. 333)

Filters to limit the request results.

Note

The following Key values are supported for `GetParametersByPath`: `Type`, `KeyId`, and `Label`.

The following Key values aren't supported for `GetParametersByPath`: `tag`, `DataType`, `Name`, `Path`, and `Tier`.

Type: Array of [ParameterStringFilter \(p. 780\)](#) objects

Required: No

[Path \(p. 333\)](#)

The hierarchy for the parameter. Hierarchies start with a forward slash (/). The hierarchy is the parameter name except the last part of the parameter. For the API call to succeed, the last part of the parameter name can't be in the path. A parameter name hierarchy can have a maximum of 15 levels. Here is an example of a hierarchy: /Finance/Prod/IAD/WinServ2016/licensee33

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

[Recursive \(p. 333\)](#)

Retrieve all parameters within a hierarchy.

Important

If a user has access to a path, then the user can access all levels of that path. For example, if a user has permission to access path /a, then the user can also access /a/b. Even if a user has explicitly been denied access in IAM for parameter /a/b, they can still call the GetParametersByPath API operation recursively for /a and view /a/b.

Type: Boolean

Required: No

[WithDecryption \(p. 333\)](#)

Retrieve all parameters in a hierarchy with their value decrypted.

Type: Boolean

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Parameters": [  
        {  
            "ARN": "string",  
            "DataType": "string",  
            "LastModifiedDate": number,  
            "Name": "string",  
            "Selector": "string",  
            "SourceResult": "string",  
            "Type": "string",  
            "Value": "string",  
            "Version": number  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 334)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Parameters (p. 334)

A list of parameters found in the specified hierarchy.

Type: Array of [Parameter \(p. 771\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidFilterOption

The specified filter option isn't valid. Valid options are Equals and BeginsWith. For Path filter, valid options are Recursive and OneLevel.

HTTP Status Code: 400

InvalidFilterValue

The filter value isn't valid. Verify the value and try again.

HTTP Status Code: 400

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetParametersByPath`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 46
X-Amz-Target: AmazonSSM.GetParametersByPath
X-Amz-Date: 20180316T004724Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Path": "/Branch312/Dev/",
    "Recursive": true
}
```

Sample Response

```
{
    "Parameters": [
        {
            "Name": "/Branch312/Dev/Engineer1",
            "Type": "String",
            "Value": "Saanvi Sarkar",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Engineer2",
            "Type": "String",
            "Value": "Zhang Wei",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Engineer3",
            "Type": "String",
            "Value": "Alejandro Rosalez",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/Intern",
            "Type": "String",
            "Value": "Nikhil Jayashankar",
            "Version": 1
        },
        {
            "Name": "/Branch312/Dev/TeamLead",
            "Type": "String",
            "Value": "Jane Roe",
            "Version": 1
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPatchBaseline

Retrieves information about a patch baseline.

Request Syntax

```
{  
    "BaselineId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 338)

The ID of the patch baseline to retrieve.

Note

To retrieve information about an AWS managed patch baseline, specify the full Amazon Resource Name (ARN) of the baseline. For example, for the baseline AWS-AmazonLinuxDefaultPatchBaseline, specify `arn:aws:ssm:us-east-2:733109147000:patchbaseline/pb-0e392de35e7c563b7` instead of `pb-0e392de35e7c563b7`.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-\:/]{20,128}$`

Required: Yes

Response Syntax

```
{  
    "ApprovalRules": {  
        "PatchRules": [  
            {  
                "ApproveAfterDays": number,  
                "ApproveUntilDate": "string",  
                "ComplianceLevel": "string",  
                "EnableNonSecurity": boolean,  
                "PatchFilterGroup": {  
                    "PatchFilters": [  
                        {  
                            "Key": "string",  
                            "Values": [ "string" ]  
                        }  
                    ]  
                }  
            }  
        ]  
    }  
}
```

```
        },
        "ApprovedPatches": [ "string" ],
        "ApprovedPatchesComplianceLevel": "string",
        "ApprovedPatchesEnableNonSecurity": boolean,
        "BaselineId": "string",
        "CreatedDate": number,
        "Description": "string",
        "GlobalFilters": {
            "PatchFilters": [
                {
                    "Key": "string",
                    "Values": [ "string" ]
                }
            ]
        },
        "ModifiedDate": number,
        "Name": "string",
        "OperatingSystem": "string",
        "PatchGroups": [ "string" ],
        "RejectedPatches": [ "string" ],
        "RejectedPatchesAction": "string",
        "Sources": [
            {
                "Configuration": "string",
                "Name": "string",
                "Products": [ "string" ]
            }
        ]
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApprovalRules \(p. 338\)](#)

A set of rules used to include patches in the baseline.

Type: [PatchRuleGroup \(p. 797\)](#) object

[ApprovedPatches \(p. 338\)](#)

A list of explicitly approved patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

[ApprovedPatchesComplianceLevel \(p. 338\)](#)

Returns the specified compliance severity level for approved patches in the patch baseline.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

[ApprovedPatchesEnableNonSecurity \(p. 338\)](#)

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is false. Applies to Linux managed nodes only.

Type: Boolean

[BaselineId \(p. 338\)](#)

The ID of the retrieved patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

[CreatedDate \(p. 338\)](#)

The date the patch baseline was created.

Type: Timestamp

[Description \(p. 338\)](#)

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[GlobalFilters \(p. 338\)](#)

A set of global filters used to exclude patches from the baseline.

Type: [PatchFilterGroup \(p. 792\)](#) object

[ModifiedDate \(p. 338\)](#)

The date the patch baseline was last modified.

Type: Timestamp

[Name \(p. 338\)](#)

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\.]{3,128}\$

[OperatingSystem \(p. 338\)](#)

Returns the operating system specified for the patch baseline.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

[PatchGroups \(p. 338\)](#)

Patch groups included in the patch baseline.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}]\p{N}_\.:+=\-\@]*\$

[RejectedPatches \(p. 338\)](#)

A list of explicitly rejected patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

[RejectedPatchesAction \(p. 338\)](#)

The action specified to take on patches included in the `RejectedPatches` list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY` | `BLOCK`

[Sources \(p. 338\)](#)

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of [PatchSource \(p. 798\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `GetPatchBaseline`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.GetPatchBaseline
X-Amz-Date: 20180309T020232Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "ApprovalRules": {
        "PatchRules": [
            {
                "ApproveAfterDays": 1,
                "ComplianceLevel": "UNSPECIFIED",
                "EnableNonSecurity": false,
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Key": "PRODUCT",
                            "Values": [
                                "WindowsServer2012R2"
                            ]
                        },
                        {
                            "Key": "CLASSIFICATION",
                            "Values": [
                                "SecurityUpdates"
                            ]
                        },
                        {
                            "Key": "MSRC_SEVERITY",
                            "Values": [
                                "Important",
                                "Critical",
                                "Moderate"
                            ]
                        }
                    ]
                }
            }
        ],
        "ApprovedPatches": [],
        "ApprovedPatchesComplianceLevel": "HIGH",
        "ApprovedPatchesEnableNonSecurity": false,
        "BaselineId": "pb-0c10e65780EXAMPLE",
        "Description": "My Moderate, Important, and Critical security updates for Windows Server 2012 R2",
        "GlobalFilters": {
            "PatchFilters": []
        }
    }
}
```

```
"CreatedDate": 1520561435.87,  
"ModifiedDate": 1520561435.869,  
"Name": "my-Windows-Server-2012R2",  
"OperatingSystem": "WINDOWS",  
"PatchGroups": [  
    "mypatchgroup"  
,  
    "RejectedPatches": [  
        "KB3452678"  
,  
        "RejectedPatchesAction": "ALLOW_AS_DEPENDENCY",  
        "Sources": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPatchBaselineForPatchGroup

Retrieves the patch baseline that should be used for the specified patch group.

Request Syntax

```
{  
    "OperatingSystem": "string",  
    "PatchGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[OperatingSystem \(p. 344\)](#)

Returns the operating system rule specified for patch groups using the patch baseline.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: No

[PatchGroup \(p. 344\)](#)

The name of the patch group whose patch baseline should be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:=/+\\-@]*\$

Required: Yes

Response Syntax

```
{  
    "BaselineId": "string",  
    "OperatingSystem": "string",  
    "PatchGroup": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[BaselineId \(p. 344\)](#)

The ID of the patch baseline that should be used for the patch group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

[OperatingSystem \(p. 344\)](#)

The operating system rule specified for patch groups using the patch baseline.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

[PatchGroup \(p. 344\)](#)

The name of the patch group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_\.\:\=\+\-\@]*\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of GetPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 66
X-Amz-Target: AmazonSSM.GetPatchBaselineForPatchGroup
X-Amz-Date: 20180309T060906Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
```

```
{  
    "PatchGroup": "mypatchgroup",  
    "OperatingSystem": "WINDOWS"  
}
```

Sample Response

```
{  
    "BaselineId": "pb-0c10e65780EXAMPLE",  
    "OperatingSystem": "WINDOWS",  
    "PatchGroup": "mypatchgroup"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceSetting

ServiceSetting is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of `false`. This means the user can't use this feature unless they change the setting to `true` and intentionally opt in for a paid feature.

Services map a `SettingId` object to a setting value. AWS services teams define the default value for a `SettingId`. You can't create a new `SettingId`, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the [UpdateServiceSetting \(p. 575\)](#) API operation to change the default setting. Or use the [ResetServiceSetting \(p. 461\)](#) to change the value back to the original value defined by the AWS service team.

Query the current service setting for the AWS account.

Request Syntax

```
{  
    "SettingId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

SettingId ([p. 347](#))

The ID of the service setting to get. The setting ID can be one of the following.

- `/ssm/automation/customer-script-log-destination`
- `/ssm/automation/customer-script-log-group-name`
- `/ssm/documents/console/public-sharing-permission`
- `/ssm/parameter-store/default-parameter-tier`
- `/ssm/parameter-store/high-throughput-enabled`
- `/ssm/managed-instance/activation-tier`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Response Syntax

```
{  
    "ServiceSetting": {  
        "ARN": "string",  
        "LastModifiedDate": number,  
        "LastModifiedUser": "string",  
        "SettingId": "string",  
    }  
}
```

```
    "SettingValue": "string",
    "Status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ServiceSetting (p. 347)

The query result of the current service setting.

Type: [ServiceSetting \(p. 827\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of GetServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.GetServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200324T203339Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200324/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 54

{
    "SettingId": "/ssm/managed-instance/activation-tier"
}
```

Sample Response

```
{  
    "ServiceSetting": {  
        "ARN": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/managed-instance/  
activation-tier",  
        "LastModifiedDate": 1579136114.275,  
        "LastModifiedUser": "System",  
        "SettingId": "/ssm/managed-instance/activation-tier",  
        "SettingValue": "standard",  
        "Status": "Default"  
    }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

LabelParameterVersion

A parameter label is a user-defined alias to help you manage different versions of a parameter. When you modify a parameter, AWS Systems Manager automatically saves a new version and increments the version number by one. A label can help you remember the purpose of a parameter when there are multiple versions.

Parameter labels have the following requirements and restrictions.

- A version of a parameter can have a maximum of 10 labels.
- You can't attach the same label to different versions of the same parameter. For example, if version 1 has the label Production, then you can't attach Production to version 2.
- You can move a label from one version of a parameter to another.
- You can't create a label when you create a new parameter. You must attach a label to a specific version of a parameter.
- If you no longer want to use a parameter label, then you can either delete it or move it to a different version of a parameter.
- A label can have a maximum of 100 characters.
- Labels can contain letters (case sensitive), numbers, periods (.), hyphens (-), or underscores (_).
- Labels can't begin with a number, "aws" or "ssm" (not case sensitive). If a label fails to meet these requirements, then the label isn't associated with a parameter and the system displays it in the list of InvalidLabels.

Request Syntax

```
{  
    "Labels": [ "string" ],  
    "Name": "string",  
    "ParameterVersion": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Labels (p. 350)

One or more labels to attach to the specified parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Name (p. 350)

The parameter name on which you want to attach one or more labels.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

ParameterVersion (p. 350)

The specific version of the parameter on which you want to attach one or more labels. If no version is specified, the system attaches the label to the latest version.

Type: Long

Required: No

Response Syntax

```
{  
    "InvalidLabels": [ "string" ],  
    "ParameterVersion": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidLabels (p. 351)

The label doesn't meet the requirements. For information about parameter label requirements, see [Labeling parameters](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

ParameterVersion (p. 351)

The version of the parameter that has been labeled.

Type: Long

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

HTTP Status Code: 400

ParameterVersionLabelLimitExceeded

A parameter version can have a maximum of ten labels.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of LabelParameterVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.LabelParameterVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T191052Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200229/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 76

{
    "Name": "MyGitHubPassword",
    "ParameterVersion": 3,
    "Labels": [
        "March-2020"
    ]
}
```

Sample Response

```
{
    "InvalidLabels": [],
    "ParameterVersion": 3
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssociations

Returns all State Manager associations in the current AWS account and AWS Region. You can limit the results to a specific State Manager association document or managed node by specifying a filter. State Manager is a capability of AWS Systems Manager.

Request Syntax

```
{  
    "AssociationFilterList": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AssociationFilterList \(p. 354\)](#)

One or more filters. Use a filter to return a more specific list of results.

Note

Filtering associations using the `InstanceID` attribute only returns legacy associations created using the `InstanceID` attribute. Associations targeting the managed node that are part of the Target Attributes ResourceGroup or Tags aren't returned.

Type: Array of [AssociationFilter \(p. 599\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

[MaxResults \(p. 354\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 354\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "Associations": [  
        {  
            "AssociationId": "string",  
            "AssociationName": "string",  
            "AssociationVersion": "string",  
            "DocumentVersion": "string",  
            "InstanceId": "string",  
            "LastExecutionDate": number,  
            "Name": "string",  
            "Overview": {  
                "AssociationStatusAggregatedCount": {  
                    "string" : number  
                },  
                "DetailedStatus": "string",  
                "Status": "string"  
            },  
            "ScheduleExpression": "string",  
            "ScheduleOffset": number,  
            "TargetMaps": [  
                {  
                    "string" : [ "string" ]  
                }  
            ],  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ]  
        },  
        "NextToken": "string"  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Associations \(p. 355\)](#)

The associations.

Type: Array of [Association \(p. 585\)](#) objects

[NextToken \(p. 355\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssociations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListAssociations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T143814Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "Associations": [
        {
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "LastExecutionDate": 1582037438.692,
            "Name": "AWS-UpdateSSMAgent",
            "Overview": {
                "AssociationStatusAggregatedCount": {
                    "Success": 3
                },
                "DetailedStatus": "Success",
                "Status": "Success"
            },
            "Targets": [
                {
                    "Key": "tag:ssm",
                    "Values": [
                        "true"
                    ]
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssociationVersions

Retrieves all versions of an association for a specific association ID.

Request Syntax

```
{  
    "AssociationId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationId (p. 358)

The association ID for which you want to view all versions.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

MaxResults (p. 358)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 358)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "AssociationVersions": [  
        {  
            "ApplyOnlyAtCronInterval": boolean,  
            "AssociationId": "string",  
            "AssociationName": "string",  
            "AssociationVersion": "string",  
            "LastModifiedDate": "string",  
            "Status": "string",  
            "StatusReason": "string",  
            "StatusReasonCode": "string",  
            "VersionOrder": number  
        }  
    ]  
}
```

```

"CalendarNames": [ "string" ],
"ComplianceSeverity": "string",
"CreatedDate": number,
"DocumentVersion": "string",
"MaxConcurrency": "string",
"MaxErrors": "string",
"Name": "string",
"OutputLocation": {
    "S3Location": {
        "OutputS3BucketName": "string",
        "OutputS3KeyPrefix": "string",
        "OutputS3Region": "string"
    }
},
"Parameters": {
    "string" : [ "string" ]
},
"ScheduleExpression": "string",
"ScheduleOffset": number,
"SyncCompliance": "string",
"TargetLocations": [
    {
        "Accounts": [ "string" ],
        "ExecutionRoleName": "string",
        "Regions": [ "string" ],
        "TargetLocationMaxConcurrency": "string",
        "TargetLocationMaxErrors": "string"
    }
],
"TargetMaps": [
    {
        "string" : [ "string" ]
    }
],
"Targets": [
    {
        "Key": "string",
        "Values": [ "string" ]
    }
]
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationVersions \(p. 358\)](#)

Information about all versions of the association for the specified association ID.

Type: Array of [AssociationVersionInfo \(p. 602\)](#) objects

Array Members: Minimum number of 1 item.

[NextToken \(p. 358\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListAssociationVersions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListAssociationVersions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T144807Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 57

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE"
}
```

Sample Response

```
{
    "AssociationVersions": [
        {
            "ApplyOnlyAtCronInterval": false,
            "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
            "AssociationVersion": "1",
            "CreatedDate": 1561053271.583,
            "Name": "AWS-UpdateSSMAgent",
            "Parameters": {
                "allowDowngrade": [
                    "false"
                ]
            }
        }
    ]
}
```

```
        ],
        "version": [
            ""
        ],
        "Targets": [
            {
                "Key": "tag:ssm",
                "Values": [
                    "true"
                ]
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCommandInvocations

An invocation is copy of a command sent to a specific managed node. A command can apply to one or more managed nodes. A command invocation applies to one managed node. For example, if a user runs `SendCommand` against three managed nodes, then a command invocation is created for each requested managed node ID. `ListCommandInvocations` provide status about command execution.

Request Syntax

```
{  
    "CommandId": "string",  
    "Details": boolean,  
    "Filters": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[CommandId \(p. 362\)](#)

(Optional) The invocations for a specific command ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

[Details \(p. 362\)](#)

(Optional) If set this returns the response of the command executions and any command output. The default value is `false`.

Type: Boolean

Required: No

[Filters \(p. 362\)](#)

(Optional) One or more filters. Use a filter to return a more specific list of results.

Type: Array of [CommandFilter \(p. 631\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[InstanceId \(p. 362\)](#)

(Optional) The command execution details for a specific managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

[MaxResults \(p. 362\)](#)

(Optional) The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 362\)](#)

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "CommandInvocations": [  
        {  
            "CloudWatchOutputConfig": {  
                "CloudWatchLogGroupName": "string",  
                "CloudWatchOutputEnabled": boolean  
            },  
            "CommandId": "string",  
            "CommandPlugins": [  
                {  
                    "Name": "string",  
                    "Output": "string",  
                    "OutputS3BucketName": "string",  
                    "OutputS3KeyPrefix": "string",  
                    "OutputS3Region": "string",  
                    "ResponseCode": number,  
                    "ResponseFinishDateTime": number,  
                    "ResponseStartTime": number,  
                    "StandardErrorUrl": "string",  
                    "StandardOutputUrl": "string",  
                    "Status": "string",  
                    "StatusDetails": "string"  
                }  
            ],  
            "Comment": "string",  
            "DocumentName": "string",  
            "DocumentVersion": "string",  
            "InstanceId": "string",  
            "InstanceName": "string",  
            "NotificationConfig": {  
                "NotificationArn": "string",  
                "NotificationType": "string",  
                "TopicArn": "string"  
            }  
        }  
    ]  
}
```

```
        "NotificationEvents": [ "string" ],
        "NotificationType": "string"
    },
    "RequestedDateTime": number,
    "ServiceRole": "string",
    "StandardErrorUrl": "string",
    "StandardOutputUrl": "string",
    "Status": "string",
    "StatusDetails": "string",
    "TraceOutput": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CommandInvocations (p. 363)

(Optional) A list of all invocations.

Type: Array of [CommandInvocation \(p. 633\)](#) objects

NextToken (p. 363)

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.

- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListCommandInvocations.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListCommandInvocations
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T000322Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53

{
    "CommandId": "4171bb3b-fe26-48ea-94fe-d1727b4d58e5"
}
```

Sample Response

```
{
    "CommandInvocations": [
        {
            "CloudWatchOutputConfig": {
                "CloudWatchLogGroupName": "",
                "CloudWatchOutputEnabled": false
            },
            "CommandId": "4171bb3b-fe26-48ea-94fe-d1727EXAMPLE",
            "CommandPlugins": [],
            "Comment": "",
            "DocumentName": "AWS-FindWindowsUpdates",
            "DocumentVersion": "1",
            "InstanceId": "i-02573cafccEXAMPLE",
            "InstanceName": "EXAMPLE-4J5FVEG.WORKGROUP",
            "NotificationConfig": {
                "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
                "NotificationEvents": [
                    "All"
                ],
                "NotificationType": "Invocation"
            },
        }
    ]
}
```

```
"RequestedDateTime": 1579893879.775,
"ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
"StandardErrorUrl": "https://s3.us-east-2.amazonaws.com/doc-example-
bucket/my-output/1231bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-02573cafefEXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stderr",
"StandardOutputUrl": "https://s3.us-east-2.amazonaws.com/doc-example-
bucket/my-output/1231bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-02573cafefEXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stdout",
"Status": "Success",
"StatusDetails": "Success"
},
{
    "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "",
        "CloudWatchOutputEnabled": false
    },
    "CommandId": "4171bb3b-fe26-48ea-94fe-d1727EXAMPLE",
    "CommandPlugins": [],
    "Comment": "",
    "DocumentName": "AWS-FindWindowsUpdates",
    "DocumentVersion": "1",
    "InstanceId": "i-0471e04240EXAMPLE",
    "InstanceName": "EXAMPLE-A1PDOM8.WORKGROUP",
    "NotificationConfig": {
        "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
        "NotificationEvents": [
            "All"
        ],
        "NotificationType": "Invocation"
    },
    "RequestedDateTime": 1579893879.6,
    "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
    "StandardErrorUrl": "https://s3.us-east-2.amazonaws.com/doc-example-
bucket/my-output/4171bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-0471e04240EXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stderr",
    "StandardOutputUrl": "https://s3.us-east-2.amazonaws.com/doc-example-
bucket/my-output/4171bb3b-fe26-48ea-94fe-d1727EXAMPLE/i-0471e04240EXAMPLE/
awsrunPowerShellScript/0.awsrunPowerShellScript/stdout",
    "Status": "Success",
    "StatusDetails": "Success"
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCommands

Lists the commands requested by users of the AWS account.

Request Syntax

```
{  
    "CommandId": "string",  
    "Filters": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[CommandId \(p. 367\)](#)

(Optional) If provided, lists only the specified command.

Type: String

Length Constraints: Fixed length of 36.

Required: No

[Filters \(p. 367\)](#)

(Optional) One or more filters. Use a filter to return a more specific list of results.

Type: Array of [CommandFilter \(p. 631\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[InstanceId \(p. 367\)](#)

(Optional) Lists commands issued against this managed node ID.

Note

You can't specify a managed node ID in the same command that you specify `Status = Pending`. This is because the command hasn't reached the managed node yet.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

[MaxResults \(p. 367\)](#)

(Optional) The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 367\)](#)

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "Commands": [  
        {  
            "CloudWatchOutputConfig": {  
                "CloudWatchLogGroupName": "string",  
                "CloudWatchOutputEnabled": boolean  
            },  
            "CommandId": "string",  
            "Comment": "string",  
            "CompletedCount": number,  
            "DeliveryTimedOutCount": number,  
            "DocumentName": "string",  
            "DocumentVersion": "string",  
            "ErrorCount": number,  
            "ExpiresAfter": number,  
            "InstanceIds": [ "string" ],  
            "MaxConcurrency": "string",  
            "MaxErrors": "string",  
            "NotificationConfig": {  
                "NotificationArn": "string",  
                "NotificationEvents": [ "string" ],  
                "NotificationType": "string"  
            },  
            "OutputS3BucketName": "string",  
            "OutputS3KeyPrefix": "string",  
            "OutputS3Region": "string",  
            "Parameters": {  
                "string" : [ "string" ]  
            },  
            "RequestedDateTime": number,  
            "ServiceRole": "string",  
            "Status": "string",  
            "StatusDetails": "string",  
            "TargetCount": number,  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ],  
            "TimeoutSeconds": number  
        }  
    ]  
}
```

```
        },
    ],
    "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Commands (p. 368)

(Optional) The list of commands requested by the user.

Type: Array of [Command](#) (p. 626) objects

NextToken (p. 368)

(Optional) The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 847).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidCommandId

The specified command ID isn't valid. Verify the ID and try again.

HTTP Status Code: 400

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListCommands.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListCommands
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T002657Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 53

{
    "CommandId": "088e4813-f292-48b3-8180-d8be9EXAMPLE"
}
```

Sample Response

```
{
    "Commands": [
        {
            "CloudWatchOutputConfig": {
                "CloudWatchLogGroupName": "my-log-group",
                "CloudWatchOutputEnabled": true
            },
            "CommandId": "088e4813-f292-48b3-8180-d8be9EXAMPLE",
            "Comment": "",
            "CompletedCount": 0,
            "DeliveryTimedOutCount": 0,
            "DocumentName": "AWS-InstallMissingWindowsUpdates",
            "DocumentVersion": "1",
            "ErrorCount": 0,
            "ExpiresAfter": 1582248743.188,
            "InstanceIds": [],
            "Interactive": false,
            "MaxConcurrency": "2",
            "MaxErrors": "3",
            "NotificationConfig": {
                "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-
notification-arn",
                "NotificationEvents": [
                    "All"
                ],
                "NotificationType": "Command"
            },
            "OutputS3BucketName": "doc-example-bucket",
            "OutputS3KeyPrefix": "my-rc-output",
            "Parameters": {
                "ExcludeKbArticleIds": [
                    ""
                ]
            }
        }
    ]
}
```

```
        ],
        "UpdateLevel": [
            "All"
        ]
    },
    "RequestedDateTime": 1582244543.188,
    "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
    "Status": "InProgress",
    "StatusDetails": "InProgress",
    "TargetCount": 5,
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-09c350ed76EXAMPLE",
                "i-07be1baa4aEXAMPLE",
                "i-00ec29b21eEXAMPLE",
                "i-09911ddd90EXAMPLE",
                "i-017431b35cEXAMPLE"
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComplianceItems

For a specified resource ID, this API operation returns a list of compliance statuses for different resource types. Currently, you can only specify one resource ID per call. List results depend on the criteria specified in the filter.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "ResourceIds": [ "string" ],  
    "ResourceTypes": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 372)

One or more compliance filters. Use a filter to return a more specific list of results.

Type: Array of [ComplianceStringFilter \(p. 645\)](#) objects

Required: No

MaxResults (p. 372)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 372)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

ResourceIds (p. 372)

The ID for the resources from which to get compliance information. Currently, you can only specify one resource ID.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[ResourceTypes \(p. 372\)](#)

The type of resource from which to get compliance information. Currently, the only supported resource type is `ManagedInstance`.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Response Syntax

```
{  
    "ComplianceItems": [  
        {  
            "ComplianceType": "string",  
            "Details": {  
                "string" : "string"  
            },  
            "ExecutionSummary": {  
                "ExecutionId": "string",  
                "ExecutionTime": number,  
                "ExecutionType": "string"  
            },  
            "Id": "string",  
            "ResourceId": "string",  
            "ResourceType": "string",  
            "Severity": "string",  
            "Status": "string",  
            "Title": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ComplianceItems \(p. 373\)](#)

A list of compliance information for the specified resource ID.

Type: Array of [ComplianceItem \(p. 641\)](#) objects

[NextToken \(p. 373\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Invalid ResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListComplianceItems.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListComplianceItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T173645Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 40

{
    "ResourceIds": [
        "i-0cb99161f6EXAMPLE"
    ]
}
```

```
    ]  
}
```

Sample Response

```
{  
    "ComplianceItems": [  
        {  
            "ComplianceType": "Association",  
            "ResourceType": "ManagedInstance",  
            "ResourceId": "i-0cb99161f6EXAMPLE",  
            "Id": "bdf308d4-b431-440d-a2ee-dcca7EXAMPLE",  
            "Title": "",  
            "Status": "COMPLIANT",  
            "Severity": "UNSPECIFIED",  
            "ExecutionSummary": {  
                "ExecutionTime": 1585761335  
            },  
            "Details": {  
                "DocumentName": "AWS-GatherSoftwareInventory",  
                "DocumentVersion": "1"  
            }  
        },  
        {  
            "ComplianceType": "Association",  
            "ResourceType": "ManagedInstance",  
            "ResourceId": "i-0cb99161f6EXAMPLE",  
            "Id": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",  
            "Title": "",  
            "Status": "COMPLIANT",  
            "Severity": "HIGH",  
            "ExecutionSummary": {  
                "ExecutionTime": 1585761335  
            },  
            "Details": {  
                "DocumentName": "AWS-UpdateSSMAgent",  
                "DocumentVersion": "1"  
            }  
        }  
    ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComplianceSummaries

Returns a summary count of compliant and non-compliant resources for a compliance type. For example, this call can return State Manager associations, patches, or custom compliance types according to the filter criteria that you specify.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 376)

One or more compliance or inventory filters. Use a filter to return a more specific list of results.

Type: Array of [ComplianceStringFilter \(p. 645\)](#) objects

Required: No

MaxResults (p. 376)

The maximum number of items to return for this call. Currently, you can specify null or 50. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 376)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "ComplianceSummaryItems": [  
        {  
            "ComplianceType": "string",  
            "Count": number,  
            "NonCompliantCount": number  
        }  
    ]  
}
```

```
{  
    "ComplianceType": "string",  
    "CompliantSummary": {  
        "CompliantCount": number,  
        "SeveritySummary": {  
            "CriticalCount": number,  
            "HighCount": number,  
            "InformationalCount": number,  
            "LowCount": number,  
            "MediumCount": number,  
            "UnspecifiedCount": number  
        }  
    },  
    "NonCompliantSummary": {  
        "NonCompliantCount": number,  
        "SeveritySummary": {  
            "CriticalCount": number,  
            "HighCount": number,  
            "InformationalCount": number,  
            "LowCount": number,  
            "MediumCount": number,  
            "UnspecifiedCount": number  
        }  
    }  
},  
]  
,  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ComplianceSummaryItems \(p. 376\)](#)

A list of compliant and non-compliant summary counts based on compliance types. For example, this call returns State Manager associations, patches, or custom compliance types according to the filter criteria that you specified.

Type: Array of [ComplianceSummaryItem \(p. 646\)](#) objects

[NextToken \(p. 376\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListComplianceSummaries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListComplianceSummaries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T174348Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ComplianceSummaryItems": [
        {
            "ComplianceType": "FleetTotal",
            "CompliantSummary": {
                "CompliantCount": 1,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 1,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 0
                }
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 2,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 0,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 2
                }
            }
        },
        {
            "ComplianceType": "Association",
            "CompliantSummary": {
```

```
        "CompliantCount": 3,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 2,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 1
        }
    },
    "NonCompliantSummary": {
        "NonCompliantCount": 0,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 0,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 0
        }
    }
},
{
    "ComplianceType": "Patch",
    "CompliantSummary": {
        "CompliantCount": 1,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 0,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 1
        }
    },
    "NonCompliantSummary": {
        "NonCompliantCount": 2,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 0,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 2
        }
    }
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDocumentMetadataHistory

Information about approval reviews for a version of a change template in Change Manager.

Request Syntax

```
{  
    "DocumentVersion": "string",  
    "MaxResults": number,  
    "Metadata": "string",  
    "Name": "string",  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentVersion \(p. 381\)](#)

The version of the change template.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

[MaxResults \(p. 381\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[Metadata \(p. 381\)](#)

The type of data for which details are being requested. Currently, the only supported value is DocumentReviews.

Type: String

Valid Values: DocumentReviews

Required: Yes

[Name \(p. 381\)](#)

The name of the change template.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: Yes

[NextToken \(p. 381\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "Author": "string",  
    "DocumentVersion": "string",  
    "Metadata": {  
        "ReviewerResponse": [  
            {  
                "Comment": [  
                    {  
                        "Content": "string",  
                        "Type": "string"  
                    }  
                ],  
                "CreateTime": number,  
                "Reviewer": "string",  
                "ReviewStatus": "string",  
                "UpdatedTime": number  
            }  
        ]  
    },  
    "Name": "string",  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Author \(p. 382\)](#)

The user ID of the person in the organization who requested the review of the change template.

Type: String

[DocumentVersion \(p. 382\)](#)

The version of the change template.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

[Metadata \(p. 382\)](#)

Information about the response to the change template approval request.

Type: [DocumentMetadataResponseInfo \(p. 666\)](#) object

[Name \(p. 382\)](#)

The name of the change template.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

[NextToken \(p. 382\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocumentMetadataHistory.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocumentMetadataHistory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20210730T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210730/us-east-2/ssm/
aws4_request,
```

```
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68
```

```
{
    "Name": "MyChangeManagerTemplate",
    "Metadata": "DocumentReviews"
}
```

Sample Response

```
{
    "Name": "MyChangeManagerTemplate",
    "DocumentVersion": "1",
    "Author": "arn:aws:iam::111122223333:user/JohnDoe",
    "Metadata": {
        "ReviewerResponse": [
            {
                "CreateTime": "2021-07-30T11:58:28.025000-07:00",
                "UpdatedTime": "2021-07-30T12:01:19.274000-07:00",
                "ReviewStatus": "APPROVED",
                "Comment": [
                    {
                        "Type": "COMMENT",
                        "Content": "I approve this template version"
                    }
                ],
                "Reviewer": "arn:aws:iam::111122223333:user/ShirleyRodriguez"
            },
            {
                "CreateTime": "2021-07-30T11:58:28.025000-07:00",
                "UpdatedTime": "2021-07-30T11:58:28.025000-07:00",
                "ReviewStatus": "PENDING"
            }
        ]
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDocuments

Returns all Systems Manager (SSM) documents in the current AWS account and AWS Region. You can limit the results of this request by using a filter.

Request Syntax

```
{  
    "DocumentFilterList": [  
        {  
            "key": "string",  
            "value": "string"  
        }  
    ],  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentFilterList \(p. 385\)](#)

This data type is deprecated. Instead, use [Filters](#).

Type: Array of [DocumentFilter \(p. 660\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

[Filters \(p. 385\)](#)

One or more [DocumentKeyValuesFilter](#) objects. Use a filter to return a more specific list of results. For keys, you can specify one or more key-value pair tags that have been applied to a document. Other valid keys include `Owner`, `Name`, `PlatformTypes`, `DocumentType`, and `TargetType`. For example, to return documents you own use `Key=Owner,Values=Self`. To specify a custom key-value pair, use the format `Key=tag:tagName,Values=valueName`.

Note

This API operation only supports filtering documents by using a single tag key and one or more tag values. For example: `Key=tag:tagName,Values=valueName1,valueName2`

Type: Array of [DocumentKeyValuesFilter \(p. 664\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 6 items.

Required: No

[MaxResults \(p. 385\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 385\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "DocumentIdentifiers": [  
        {  
            "Author": "string",  
            "CreatedDate": number,  
            "DisplayName": "string",  
            "DocumentFormat": "string",  
            "DocumentType": "string",  
            "DocumentVersion": "string",  
            "Name": "string",  
            "Owner": "string",  
            "PlatformTypes": [ "string" ],  
            "Requires": [  
                {  
                    "Name": "string",  
                    "Version": "string"  
                }  
            ],  
            "ReviewStatus": "string",  
            "SchemaVersion": "string",  
            "Tags": [  
                {  
                    "Key": "string",  
                    "Value": "string"  
                }  
            ],  
            "TargetType": "string",  
            "VersionName": "string"  
        }  
    ],  
    "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DocumentIdentifiers \(p. 386\)](#)

The names of the SSM documents.

Type: Array of [DocumentIdentifier \(p. 661\)](#) objects

[NextToken \(p. 386\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilterKey

The specified key isn't valid.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocuments.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocuments
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T150301Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 97

{
    "Filters": [
        {
            "Key": "Owner",
            "Values": [

```

```
        "Self"
    ],
},
{
    "Key": "tag:DocUse",
    "Values": [
        "Testing"
    ]
}
]
```

Sample Response

```
{
    "DocumentIdentifiers": [
        {
            "CreatedDate": 1486594364.541,
            "DocumentFormat": "YAML",
            "DocumentType": "Automation",
            "DocumentVersion": "1",
            "DisplayName": "ExampleDoc",
            "Name": "Example",
            "Owner": "111122223333",
            "PlatformTypes": [
                "Windows",
                "Linux"
            ],
            "SchemaVersion": "0.3",
            "Tags": [
                {
                    "Key": "DocUse",
                    "Value": "Testing"
                }
            ]
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDocumentVersions

List all versions for a document.

Request Syntax

```
{  
    "MaxResults": number,  
    "Name": "string",  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 389\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[Name \(p. 389\)](#)

The name of the document. You can specify an Amazon Resource Name (ARN).

Type: String

Pattern: ^[a-zA-Z0-9_\-.:/]{3,128}\$

Required: Yes

[NextToken \(p. 389\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

Response Syntax

```
{  
    "DocumentVersions": [  
        {  
            "CreatedDate": number,  
            "DisplayName": "string",  
            "DocumentFormat": "string",  
            "DocumentVersion": "string",  
            "LastModifiedDate": number,  
            "LastModifiedBy": "string",  
            "Content": "string"  
        }  
    ]  
}
```

```
    "IsDefaultVersion": boolean,  
    "Name": "string",  
    "ReviewStatus": "string",  
    "Status": "string",  
    "StatusInformation": "string",  
    "VersionName": "string"  
}  
]  
,  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentVersions (p. 389)

The document versions.

Type: Array of [DocumentVersionInfo \(p. 673\)](#) objects

Array Members: Minimum number of 1 item.

NextToken (p. 389)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListDocumentVersions.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListDocumentVersions
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T151751Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 30

{
    "Name": "AWS-UpdateSSMAgent"
}
```

Sample Response

```
{
    "DocumentVersions": [
        {
            "CreatedDate": 1486594364.541,
            "DisplayName": "ExampleDoc",
            "DocumentFormat": "JSON",
            "DocumentVersion": "1",
            "IsDefaultVersion": true,
            "Name": "AWS-UpdateSSMAgent",
            "Status": "Active"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListInventoryEntries

A list of inventory items returned by the request.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "InstanceId": "string",  
    "MaxResults": number,  
    "NextToken": "string",  
    "TypeName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 392\)](#)

One or more filters. Use a filter to return a more specific list of results.

Type: Array of [InventoryFilter \(p. 703\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

[InstanceId \(p. 392\)](#)

The managed node ID for which you want inventory information.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: Yes

[MaxResults \(p. 392\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 392\)](#)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

[TypeName \(p. 392\)](#)

The type of inventory item for which you want information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS|Custom):.*\$

Required: Yes

Response Syntax

```
{  
    "CaptureTime": "string",  
    "Entries": [  
        {  
            "string" : "string"  
        }  
    ],  
    "InstanceId": "string",  
    "NextToken": "string",  
    "SchemaVersion": "string",  
    "TypeName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CaptureTime \(p. 393\)](#)

The time that inventory information was collected for the managed node(s).

Type: String

Pattern: ^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|0[1-9]):([0-5][0-9]):([0-5][0-9])(Z)\$

[Entries \(p. 393\)](#)

A list of inventory items on the managed node(s).

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

[InstanceId \(p. 393\)](#)

The managed node ID targeted by the request to query inventory information.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

[NextToken \(p. 393\)](#)

The token to use when requesting the next set of items. If there are no additional items to return, the string is empty.

Type: String

[SchemaVersion \(p. 393\)](#)

The inventory schema version used by the managed node(s).

Type: String

Pattern: ^([0-9]{1,6})(\.[0-9]{1,6})\$

[TypeName \(p. 393\)](#)

The type of inventory item returned by the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS|Custom):.*\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

InvalidTypeNameException

The parameter type name isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListInventoryEntries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListInventoryEntries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68

{
    "InstanceId": "i-04bf6ad63bEXAMPLE",
    "Type": "AWS:Application"
}
```

Sample Response

```
{
    "CaptureTime": "2020-03-30T15:45:32Z",
    "Entries": [
        {
            "Architecture": "i386",
            "InstalledTime": "2020-01-15T00:00:00Z",
            "Name": "AWS Tools for Windows",
            "PackageId": "{2088D019-97CC-4349-BA45-9777568EAE94}",
            "Publisher": "Amazon Web Services Developer Relations",
            "Version": "3.15.925"
        },
        {
            "Architecture": "i386",
            "Name": "Amazon SSM Agent",
            "PackageId": "{2a4673c2-68c6-4a4c-9be6-c3b1be96fdff}",
            "Publisher": "Amazon Web Services",
            "Version": "2.3.930.0"
        },
        {
            "Architecture": "x86_64",
            "InstalledTime": "2018-10-14T00:00:00Z",
            "Name": "aws-cfn-bootstrap",
            "PackageId": "{34CD0CCF-195B-4BC5-B409-D44EB9A129C8}",
            "Publisher": "Amazon Web Services",
            "Version": "1.4.31"
        }
    ]
}
```

```
},
{
    "Architecture": "x86_64",
    "InstalledTime": "2020-03-10T00:00:00Z",
    "Name": "PowerShell 7-x64",
    "PackageId": "{B324E508-9AAE-446A-BC4C-BB446E8C2A18}",
    "Publisher": "Microsoft Corporation",
    "Version": "7.0.0.0"
},
{
    "Architecture": "x86_64",
    "InstalledTime": "2019-09-06T00:00:00Z",
    "Name": "AWS PV Drivers",
    "PackageId": "{C1F68A8D-F235-4886-87B0-150107C07EDA}",
    "Publisher": "Amazon Web Services",
    "Version": "8.3.2"
},
],
"InstanceId": "i-04bf6ad63bEXAMPLE",
"SchemaVersion": "1.1",
"TypeName": "AWS:Application"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOpsItemEvents

Returns a list of all OpsItem events in the current AWS Region and AWS account. You can limit the results to events associated with specific OpsItems by specifying a filter.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Operator": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 397)

One or more OpsItem filters. Use a filter to return a more specific list of results.

Type: Array of [OpsItemEventFilter \(p. 754\)](#) objects

Required: No

MaxResults (p. 397)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 397)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "NextToken": "string",
```

```
"Summaries": [  
    {  
        "CreatedBy": {  
            "Arn": "string"  
        },  
        "CreatedTime": number,  
        "Detail": "string",  
        "DetailType": "string",  
        "EventId": "string",  
        "OpsItemId": "string",  
        "Source": "string"  
    }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 397\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[Summaries \(p. 397\)](#)

A list of event information for the specified OpsItems.

Type: Array of [OpsItemEventSummary \(p. 755\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceededException

The request caused OpsItems to exceed one or more quotas. For information about OpsItem quotas, see [What are the resource limits for OpsCenter?](#).

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOpsItemRelatedItems

Lists all related-item resources associated with a Systems Manager OpsCenter OpsItem. OpsCenter is a capability of AWS Systems Manager.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Operator": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string",  
    "OpsItemId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 400)

One or more OpsItem filters. Use a filter to return a more specific list of results.

Type: Array of [OpsItemRelatedItemsFilter \(p. 760\)](#) objects

Required: No

MaxResults (p. 400)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 400)

The token for the next set of items to return. (You received this token from a previous call.)

Type: String

Required: No

OpsItemId (p. 400)

The ID of the OpsItem for which you want to list all related-item resources.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "Summaries": [  
        {  
            "AssociationId": "string",  
            "AssociationType": "string",  
            "CreatedBy": {  
                "Arn": "string"  
            },  
            "CreatedTime": number,  
            "LastModifiedBy": {  
                "Arn": "string"  
            },  
            "LastModifiedTime": number,  
            "OpsItemId": "string",  
            "ResourceType": "string",  
            "ResourceUri": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 401\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[Summaries \(p. 401\)](#)

A list of related-item resources for the specified OpsItem.

Type: Array of [OpsItemRelatedItemSummary \(p. 761\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ListOpsItemRelatedItems`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-1.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListOpsItemRelatedItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.4 Python/3.8.8 Linux/5.4.129-72.229.amzn2int.x86_64 exe/x86_64.amzn.2 prompt/off command/ssm.list-ops-item-related-items
X-Amz-Date: 20210910T180314Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210910/us-east-1/ssm/aws4_request, SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 32

{
    "OpsItemId": "oi-f99f2EXAMPLE"
}
```

Sample Response

```
{
    "Summaries": [
        {
            "OpsItemId": "oi-f99f2EXAMPLE",
            "AssociationId": "e2036148-cccb-490e-ac2a-390e5EXAMPLE",
            "ResourceType": "AWS::SSMIncidents::IncidentRecord",
            "AssociationType": "IsParentOf",
            "ResourceUri": "arn:aws:ssm-incidents::111122223333:incident-record/example-response/64bd9b45-1d0e-2622-840d-03a87a1451fa",
            "CreatedBy": {
                "Arn": "arn:aws:sts::111122223333:assumed-role/AWSServiceRoleForIncidentManager/IncidentResponse"
            },
            "CreatedTime": "2021-08-11T18:47:14.994000+00:00",
            "LastModifiedBy": {
                "Arn": "arn:aws:sts::111122223333:assumed-role/AWSServiceRoleForIncidentManager/IncidentResponse"
            },
            "LastModifiedTime": "2021-08-11T18:47:14.994000+00:00"
        }
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOpsMetadata

AWS Systems Manager calls this API operation when displaying all Application Manager OpsMetadata objects or blobs.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Filters (p. 404)

One or more filters to limit the number of OpsMetadata objects returned by the call.

Type: Array of [OpsMetadataFilter \(p. 768\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

MaxResults (p. 404)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken (p. 404)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"OpsMetadataList": [
    {
        "CreationDate": number,
        "LastModifiedDate": number,
        "LastModifiedUser": "string",
        "OpsMetadataArn": "string",
        "ResourceId": "string"
    }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 404\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[OpsMetadataList \(p. 404\)](#)

Returns a list of OpsMetadata objects.

Type: Array of [OpsMetadata \(p. 766\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceComplianceSummaries

Returns a resource-level summary count. The summary includes information about compliant and non-compliant statuses and detailed compliance-item severity counts, according to the filter criteria you specify.

Request Syntax

```
{  
    "Filters": [  
        {  
            "Key": "string",  
            "Type": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "MaxResults": number,  
    "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[Filters \(p. 407\)](#)

One or more filters. Use a filter to return a more specific list of results.

Type: Array of [ComplianceStringFilter \(p. 645\)](#) objects

Required: No

[MaxResults \(p. 407\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 407\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{  
    "NextToken": "string",
```

```

"ResourceComplianceSummaryItems": [
    {
        "ComplianceType": "string",
        "CompliantSummary": {
            "CompliantCount": number,
            "SeveritySummary": {
                "CriticalCount": number,
                "HighCount": number,
                "InformationalCount": number,
                "LowCount": number,
                "MediumCount": number,
                "UnspecifiedCount": number
            }
        },
        "ExecutionSummary": {
            "ExecutionId": "string",
            "ExecutionTime": number,
            "ExecutionType": "string"
        },
        "NonCompliantSummary": {
            "NonCompliantCount": number,
            "SeveritySummary": {
                "CriticalCount": number,
                "HighCount": number,
                "InformationalCount": number,
                "LowCount": number,
                "MediumCount": number,
                "UnspecifiedCount": number
            }
        },
        "OverallSeverity": "string",
        "ResourceId": "string",
        "ResourceType": "string",
        "Status": "string"
    }
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 407\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[ResourceComplianceSummaryItems \(p. 407\)](#)

A summary count for specified or targeted managed nodes. Summary count includes information about compliant and non-compliant State Manager associations, patch status, or custom items according to the filter criteria that you specify.

Type: Array of [ResourceComplianceSummaryItem \(p. 806\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidFilter

The filter name isn't valid. Verify the you entered the correct name and try again.

HTTP Status Code: 400

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListResourceComplianceSummaries.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListResourceComplianceSummaries
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T185225Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ResourceComplianceSummaryItems": [
        {
            "ComplianceType": "Association",
            "CompliantSummary": {
                "CompliantCount": 3,
                "SeveritySummary": {
                    "CriticalCount": 0,
                    "HighCount": 1,
                    "InformationalCount": 0,
                    "LowCount": 0,
                    "MediumCount": 0,
                    "UnspecifiedCount": 2
                }
            },
            "ExecutionSummary": {
                "ExecutionTime": 1585766022
            },
            "NonCompliantSummary": {
                "NonCompliantCount": 0,
                "SeveritySummary": {

```

```
        "CriticalCount": 0,
        "HighCount": 0,
        "InformationalCount": 0,
        "LowCount": 0,
        "MediumCount": 0,
        "UnspecifiedCount": 0
    }
},
"OverallSeverity": "HIGH",
"ResourceId": "i-04bf6ad63bEXAMPLE",
"ResourceType": "ManagedInstance",
"Status": "COMPLIANT"
},
{
    "ComplianceType": "Patch",
    "CompliantSummary": {
        "CompliantCount": 27,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 0,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 27
        }
    },
    "ExecutionSummary": {
        "ExecutionId": "b95523e7-28e5-488e-a753-fd1d3EXAMPLE",
        "ExecutionTime": 1585244656,
        "ExecutionType": "Command"
    },
    "NonCompliantSummary": {
        "NonCompliantCount": 1,
        "SeveritySummary": {
            "CriticalCount": 0,
            "HighCount": 0,
            "InformationalCount": 0,
            "LowCount": 0,
            "MediumCount": 0,
            "UnspecifiedCount": 1
        }
    },
    "OverallSeverity": "UNSPECIFIED",
    "ResourceId": "i-04bf6ad63bEXAMPLE",
    "ResourceType": "ManagedInstance",
    "Status": "NON_COMPLIANT"
}
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceDataSync

Lists your resource data sync configurations. Includes information about the last time a sync attempted to start, the last sync status, and the last time a sync successfully completed.

The number of sync configurations might be too large to return using a single call to `ListResourceDataSync`. You can limit the number of sync configurations returned by using the `MaxResults` parameter. To determine whether there are more sync configurations to list, check the value of `NextToken` in the output. If there are more sync configurations to list, you can request them by specifying the `NextToken` returned in the call to the parameter of a subsequent call.

Request Syntax

```
{  
    "MaxResults": number,  
    "NextToken": "string",  
    "SyncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[MaxResults \(p. 412\)](#)

The maximum number of items to return for this call. The call also returns a token that you can specify in a subsequent call to get the next set of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken \(p. 412\)](#)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

[SyncType \(p. 412\)](#)

View a list of resource data syncs according to the sync type. Specify `SyncToDestination` to view resource data syncs that synchronize data to an Amazon S3 bucket. Specify `SyncFromSource` to view resource data syncs from AWS Organizations or from multiple AWS Regions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

Response Syntax

```
{  
    "NextToken": "string",  
    "ResourceDataSyncItems": [  
        {  
            "LastStatus": "string",  
            "LastSuccessfulSyncTime": number,  
            "LastSyncStatusMessage": "string",  
            "LastSyncTime": number,  
            "S3Destination": {  
                "AWSKMSKeyARN": "string",  
                "BucketName": "string",  
                "DestinationDataSharing": {  
                    "DestinationDataSharingType": "string"  
                },  
                "Prefix": "string",  
                "Region": "string",  
                "SyncFormat": "string"  
            },  
            "SyncCreatedTime": number,  
            "SyncLastModifiedTime": number,  
            "SyncName": "string",  
            "SyncSource": {  
                "AwsOrganizationsSource": {  
                    "OrganizationalUnits": [  
                        {  
                            "OrganizationalUnitID": "string"  
                        }  
                    ],  
                    "OrganizationSourceType": "string"  
                },  
                "EnableAllOpsDataSources": boolean,  
                "IncludeFutureRegions": boolean,  
                "SourceRegions": [ "string" ],  
                "SourceType": "string",  
                "State": "string"  
            },  
            "SyncType": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[NextToken \(p. 413\)](#)

The token for the next set of items to return. Use this token to get the next set of results.

Type: String

[ResourceDataSyncItems \(p. 413\)](#)

A list of your current resource data sync configurations and their statuses.

Type: Array of [ResourceDataSyncItem \(p. 810\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidNextToken

The specified token isn't valid.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ListResourceDataSync.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200330T143820Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200330/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 2
```

Sample Response

```
{
    "ResourceDataSyncItems": [
        {
            "LastStatus": "Successful",
            "LastSuccessfulSyncTime": 1585578819.829,
            "LastSyncStatusMessage": "The sync was successfully completed",
            "LastSyncTime": 1585578819.829,
            "S3Destination": {
                "BucketName": "exampleBucket",
                "Prefix": "dataSync",
                "Region": "us-east-2",
                "SyncFormat": "JsonSerDe"
            },
            "SyncCreatedTime": 1585330479.404,
            "SyncLastModifiedTime": 1585330479.404,
            "SyncStatus": "Successful"
        }
    ]
}
```

```
        "SyncName": "exampleSync"  
    ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of the tags assigned to the specified resource.

For information about the ID format for each supported resource type, see [AddTagsToResource \(p. 6\)](#).

Request Syntax

```
{  
    "ResourceId": "string",  
    "ResourceType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ResourceId (p. 416)

The resource ID for which you want to see a list of tags.

Type: String

Required: Yes

ResourceType (p. 416)

Returns a list of tags for a specific resource type.

Type: String

Valid Values: Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation

Required: Yes

Response Syntax

```
{  
    "TagList": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[TagList \(p. 416\)](#)

A list of tags.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ListTagsForResource`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ListTagsForResource
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T003710Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 71

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
```

```
"TagList": [  
    {  
        "Key": "Platform",  
        "Value": "Windows Server"  
    },  
    {  
        "Key": "Environment",  
        "Value": "Production"  
    },  
    {  
        "Key": "Region",  
        "Value": "EMEA"  
    }  
]
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ModifyDocumentPermission

Shares a AWS Systems Manager document (SSM document)publicly or privately. If you share a document privately, you must specify the Amazon Web Services user account IDs for those people who can use the document. If you share a document publicly, you must specify *All* as the account ID.

Request Syntax

```
{  
    "AccountIdsToAdd": [ "string" ],  
    "AccountIdsToRemove": [ "string" ],  
    "Name": "string",  
    "PermissionType": "string",  
    "SharedDocumentVersion": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AccountIdsToAdd \(p. 419\)](#)

The Amazon Web Services user accounts that should have access to the document. The account IDs can either be a group of account IDs or *All*.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: (?i)all|[0-9]{12}

Required: No

[AccountIdsToRemove \(p. 419\)](#)

The Amazon Web Services user accounts that should no longer have access to the document. The Amazon Web Services user account can either be a group of account IDs or *All*. This action has a higher priority than *AccountIdsToAdd*. If you specify an account ID to add and the same ID to remove, the system removes access to the document.

Type: Array of strings

Array Members: Maximum number of 20 items.

Pattern: (?i)all|[0-9]{12}

Required: No

[Name \(p. 419\)](#)

The name of the document that you want to share.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: Yes

PermissionType (p. 419)

The permission type for the document. The permission type can be *Share*.

Type: String

Valid Values: Share

Required: Yes

SharedDocumentVersion (p. 419)

(Optional) The version of the document to share. If it isn't specified, the system choose the Default version to share.

Type: String

Length Constraints: Maximum length of 8.

Pattern: ([\\$]LATEST | [\\$]DEFAULT | [\\$]ALL)

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DocumentLimitExceeded

You can have at most 500 active SSM documents.

HTTP Status Code: 400

DocumentPermissionLimit

The document can't be shared with more Amazon Web Services user accounts. You can share a document with a maximum of 20 accounts. You can publicly share up to five documents. If you need to increase this limit, contact AWS Support.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidPermissionType

The permission type isn't supported. *Share* is the only supported permission type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `ModifyDocumentPermission`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ModifyDocumentPermission
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T152441Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 78

{
    "Name": "Example",
    "PermissionType": "Share",
    "AccountIdsToAdd": [
        "44445556666"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutComplianceItems

Registers a compliance type and other compliance details on a designated resource. This operation lets you register custom compliance details with a resource. This call overwrites existing compliance information on the resource, so you must provide a full list of compliance items each time that you send the request.

ComplianceType can be one of the following:

- ExecutionId: The execution ID when the patch, association, or custom compliance item was applied.
- ExecutionType: Specify patch, association, or Custom:string.
- ExecutionTime. The time the patch, association, or custom compliance item was applied to the managed node.
- Id: The patch, association, or custom compliance ID.
- Title: A title.
- Status: The status of the compliance item. For example, approved for patches, or Failed for associations.
- Severity: A patch severity. For example, critical.
- DocumentName: An SSM document name. For example, AWS-RunPatchBaseline.
- DocumentVersion: An SSM document version number. For example, 4.
- Classification: A patch classification. For example, security updates.
- PatchBaselineId: A patch baseline ID.
- PatchSeverity: A patch severity. For example, Critical.
- PatchState: A patch state. For example, InstancesWithFailedPatches.
- PatchGroup: The name of a patch group.
- InstalledTime: The time the association, patch, or custom compliance item was applied to the resource. Specify the time by using the following format: yyyy-MM-dd'T'HH:mm:ss'Z'

Request Syntax

```
{  
    "ComplianceType": "string",  
    "ExecutionSummary": {  
        "ExecutionId": "string",  
        "ExecutionTime": number,  
        "ExecutionType": "string"  
    },  
    "ItemContentHash": "string",  
    "Items": [  
        {  
            "Details": {  
                "string" : "string"  
            },  
            "Id": "string",  
            "Severity": "string",  
            "Status": "string",  
            "Title": "string"  
        }  
    ],  
    "ResourceId": "string",  
    "ResourceType": "string",  
    "UploadType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ComplianceType \(p. 422\)](#)

Specify the compliance type. For example, specify Association (for a State Manager association), Patch, or Custom:`string`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [A-Za-z0-9_\-]\w+ | Custom:[a-zA-Z0-9_\-]\w+

Required: Yes

[ExecutionSummary \(p. 422\)](#)

A summary of the call execution that includes an execution ID, the type of execution (for example, Command), and the date/time of the execution using a datetime object that is saved in the following format: yyyy-MM-dd'T'HH:mm:ss'Z'.

Type: [ComplianceExecutionSummary \(p. 640\)](#) object

Required: Yes

[ItemContentHash \(p. 422\)](#)

MD5 or SHA-256 content hash. The content hash is used to determine if existing information should be overwritten or ignored. If the content hashes match, the request to put compliance information is ignored.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[Items \(p. 422\)](#)

Information about the compliance as defined by the resource type. For example, for a patch compliance type, Items includes information about the PatchSeverity, Classification, and so on.

Type: Array of [ComplianceItemEntry \(p. 643\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Required: Yes

[ResourceId \(p. 422\)](#)

Specify an ID for this resource. For a managed node, this is the node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

[ResourceType \(p. 422\)](#)

Specify the type of resource. `ManagedInstance` is currently the only supported resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

[UploadType \(p. 422\)](#)

The mode for uploading compliance items. You can specify `COMPLETE` or `PARTIAL`. In `COMPLETE` mode, the system overwrites all existing compliance information for the resource. You must provide a full list of compliance items each time you send the request.

In `PARTIAL` mode, the system overwrites compliance information for a specific association. The association must be configured with `SyncCompliance` set to `MANUAL`. By default, all requests use `COMPLETE` mode.

Note

This attribute is only valid for association compliance.

Type: String

Valid Values: `COMPLETE` | `PARTIAL`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

ComplianceTypeCountLimitExceededException

You specified too many custom compliance types. You can specify a maximum of 10 different types.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidItemContentException

One or more content items isn't valid.

HTTP Status Code: 400

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

ItemSizeLimitExceededException

The inventory item size has exceeded the size limit.

HTTP Status Code: 400

TotalSizeLimitExceededException

The size of inventory data has exceeded the total size limit for the resource.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PutComplianceItems.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.PutComplianceItems
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.27 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/ssm.put-
compliance-items
X-Amz-Date: 20210811T170036Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210811/us-west-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 260

{
    "ResourceId": "i-02573cafccEXAMPLE",
    "ResourceType": "ManagedInstance",
    "ComplianceType": "Custom:AVCheck",
    "ExecutionSummary": {
        "ExecutionTime": 1628697600
    },
    "Items": [
        {
            "Id": "Version2.0",
            "Title": "ScanHost",
            "Severity": "CRITICAL",
            "Status": "COMPLIANT"
        }
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutInventory

Bulk update custom inventory items on one or more managed nodes. The request adds an inventory item, if it doesn't already exist, or updates an inventory item, if it does exist.

Request Syntax

```
{  
    "InstanceId": "string",  
    "Items": [  
        {  
            "CaptureTime": "string",  
            "Content": [  
                {  
                    "string" : "string"  
                }  
            ],  
            "ContentHash": "string",  
            "Context": {  
                "string" : "string"  
            },  
            "SchemaVersion": "string",  
            "TypeName": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[InstanceId \(p. 427\)](#)

An managed node ID where you want to add or update inventory items.

Type: String

Pattern: (^i-(\w{8}|\w{17}))|(^mi-\w{17})\$)

Required: Yes

[Items \(p. 427\)](#)

The inventory items that you want to add or update on managed nodes.

Type: Array of [InventoryItem \(p. 705\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 30 items.

Required: Yes

Response Syntax

```
{
```

```
    "Message": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Message (p. 427)

Information about the request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

CustomSchemaCountLimitExceededException****

You have exceeded the limit for custom schemas. Delete one or more custom schemas and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidInventoryItemContextException****

You specified invalid keys or values in the `Context` attribute for `InventoryItem`. Verify the keys and values, and try again.

HTTP Status Code: 400

InvalidItemContentException****

One or more content items isn't valid.

HTTP Status Code: 400

InvalidTypeNameException****

The parameter type name isn't valid.

HTTP Status Code: 400

ItemContentMismatchException

The inventory item has invalid content.

HTTP Status Code: 400

ItemSizeLimitExceededException

The inventory item size has exceeded the size limit.

HTTP Status Code: 400

SubTypeCountLimitExceededException

The sub-type count exceeded the limit for the inventory type.

HTTP Status Code: 400

TotalSizeLimitExceededException

The size of inventory data has exceeded the total size limit for the resource.

HTTP Status Code: 400

UnsupportedInventoryItemContextException

The Context attribute that you specified for the `InventoryItem` isn't allowed for this inventory type. You can only use the Context attribute with inventory types like `AWS : ComplianceItem`.

HTTP Status Code: 400

UnsupportedInventorySchemaVersionException

Inventory item type schema version has to match supported versions in the service. Check output of `GetInventorySchema` to see the available schema version for each type.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `PutInventory`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.PutInventory
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T181858Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 180

{
    "InstanceId": "i-0cb99161f6EXAMPLE",
    "Items": [
        {
            "TypeName": "Custom:StageInfo",
```

```
"SchemaVersion": "1.0",
"CaptureTime": "2020-03-31T08:00:00Z",
"Content": [
    {
        "Stage": "PreProd"
    }
]
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutParameter

Add a parameter to the system.

Request Syntax

```
{  
    "AllowedPattern": "string",  
    "DataType": "string",  
    "Description": "string",  
    "KeyId": "string",  
    "Name": "string",  
    "Overwrite": boolean,  
    "Policies": "string",  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "Tier": "string",  
    "Type": "string",  
    "Value": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AllowedPattern \(p. 431\)](#)

A regular expression used to validate the parameter value. For example, for String types with values restricted to numbers, you can specify the following: AllowedPattern=`^\d+$`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

[DataType \(p. 431\)](#)

The data type for a String parameter. Supported data types include plain text and Amazon Machine Image (AMI) IDs.

The following data type values are supported.

- text
- aws:ec2:image
- aws:ssm:integration

When you create a String parameter and specify `aws:ec2:image`, AWS Systems Manager validates the parameter value is in the required format, such as `ami-12345abcdeEXAMPLE`, and that the specified AMI is available in your AWS account. For more information, see [Native parameter support for Amazon Machine Image \(AMI\) IDs](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description (p. 431)

Information about the parameter that you want to add to the system. Optional but recommended.

Important

Don't enter personally identifiable information in this field.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId (p. 431)

The AWS Key Management Service (AWS KMS) ID that you want to use to encrypt a parameter. Either the default AWS KMS key automatically assigned to your AWS account or a custom key. Required for parameters that use the `SecureString` data type.

If you don't specify a key ID, the system uses the default key associated with your AWS account.

- To use your default AWS KMS key, choose the `SecureString` data type, and do *not* specify the `Key_ID` when you create the parameter. The system automatically populates `Key_ID` with your default AWS KMS key.
- To use a custom AWS KMS key, choose the `SecureString` data type with the `Key_ID` parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([a-zA-Z0-9:_-]+)\$

Required: No

Name (p. 431)

The fully qualified name of the parameter that you want to add to the system. The fully qualified name includes the complete hierarchy of the parameter path and name. For parameters in a hierarchy, you must include a leading forward slash character (/) when you create or reference a parameter. For example: /Dev/DBServer/MySQL/db-string13

Naming Constraints:

- Parameter names are case sensitive.
- A parameter name must be unique within an AWS Region
- A parameter name can't be prefixed with "aws" or "ssm" (case-insensitive).
- Parameter names can include only the following symbols and letters: a-zA-Z0-9_.-

In addition, the slash character (/) is used to delineate hierarchies in parameter names. For example: /Dev/Production/East/Project-ABC/MyParameter

- A parameter name can't include spaces.
- Parameter hierarchies are limited to a maximum depth of fifteen levels.

For additional information about valid values for parameter names, see [Creating Systems Manager parameters](#) in the *AWS Systems Manager User Guide*.

Note

The maximum length constraint of 2048 characters listed below includes 1037 characters reserved for internal use by Systems Manager. The maximum length for a parameter name that you create is 1011 characters. This includes the characters in the ARN that precede the name you specify, such as `arn:aws:ssm:us-east-2:111122223333:parameter/`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Overwrite (p. 431)

Overwrite an existing parameter. The default value is `false`.

Type: Boolean

Required: No

Policies (p. 431)

One or more policies to apply to a parameter. This operation takes a JSON array. Parameter Store, a capability of AWS Systems Manager supports the following policy types:

Expiration: This policy deletes the parameter after it expires. When you create the policy, you specify the expiration date. You can update the expiration date and time by updating the policy. Updating the *parameter* doesn't affect the expiration date and time. When the expiration time is reached, Parameter Store deletes the parameter.

ExpirationNotification: This policy initiates an event in Amazon CloudWatch Events that notifies you about the expiration. By using this policy, you can receive notification before or after the expiration time is reached, in units of days or hours.

NoChangeNotification: This policy initiates a CloudWatch Events event if a parameter hasn't been modified for a specified period of time. This policy type is useful when, for example, a secret needs to be changed within a period of time, but it hasn't been changed.

All existing policies are preserved until you send new policies or an empty policy. For more information about parameter policies, see [Assigning parameter policies](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Tags (p. 431)

Optional metadata that you assign to a resource. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a Systems Manager parameter to identify the type of resource to which it applies, the environment, or the type of configuration data referenced by the parameter. In this case, you could specify the following key-value pairs:

- Key=Resource, Value=S3bucket
- Key=OS, Value=Windows
- Key=ParameterType, Value=LicenseKey

Note

To add tags to an existing Systems Manager parameter, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

[Tier \(p. 431\)](#)

The parameter tier to assign to a parameter.

Parameter Store offers a standard tier and an advanced tier for parameters. Standard parameters have a content size limit of 4 KB and can't be configured to use parameter policies. You can create a maximum of 10,000 standard parameters for each Region in an AWS account. Standard parameters are offered at no additional cost.

Advanced parameters have a content size limit of 8 KB and can be configured to use parameter policies. You can create a maximum of 100,000 advanced parameters for each Region in an AWS account. Advanced parameters incur a charge. For more information, see [Standard and advanced parameter tiers](#) in the *AWS Systems Manager User Guide*.

You can change a standard parameter to an advanced parameter any time. But you can't revert an advanced parameter to a standard parameter. Reverting an advanced parameter to a standard parameter would result in data loss because the system would truncate the size of the parameter from 8 KB to 4 KB. Reverting would also remove any policies attached to the parameter. Lastly, advanced parameters use a different form of encryption than standard parameters.

If you no longer need an advanced parameter, or if you no longer want to incur charges for an advanced parameter, you must delete it and recreate it as a new standard parameter.

Using the Default Tier Configuration

In `PutParameter` requests, you can specify the tier to create the parameter in. Whenever you specify a tier in the request, Parameter Store creates or updates the parameter according to that request. However, if you don't specify a tier in a request, Parameter Store assigns the tier based on the current Parameter Store default tier configuration.

The default tier when you begin using Parameter Store is the standard-parameter tier. If you use the advanced-parameter tier, you can specify one of the following as the default:

- **Advanced:** With this option, Parameter Store evaluates all requests as advanced parameters.
- **Intelligent-Tiering:** With this option, Parameter Store evaluates each request to determine if the parameter is standard or advanced.

If the request doesn't include any options that require an advanced parameter, the parameter is created in the standard-parameter tier. If one or more options requiring an advanced parameter are included in the request, Parameter Store create a parameter in the advanced-parameter tier.

This approach helps control your parameter-related costs by always creating standard parameters unless an advanced parameter is necessary.

Options that require an advanced parameter include the following:

- The content size of the parameter is more than 4 KB.
- The parameter uses a parameter policy.
- More than 10,000 parameters already exist in your AWS account in the current AWS Region.

For more information about configuring the default tier option, see [Specifying a default parameter tier](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: Standard | Advanced | Intelligent-Tiering

Required: No

Type (p. 431)

The type of parameter that you want to add to the system.

Note

SecureString isn't currently supported for AWS CloudFormation templates.

Items in a StringList must be separated by a comma (,). You can't use other punctuation or special character to escape items in the list. If you have a parameter value that requires a comma, then use the String data type.

Important

Specifying a parameter type isn't required when updating a parameter. You must specify a parameter type when creating a parameter.

Type: String

Valid Values: String | StringList | SecureString

Required: No

Value (p. 431)

The parameter value that you want to add to the system. Standard parameters have a value limit of 4 KB. Advanced parameters have a value limit of 8 KB.

Note

Parameters can't be referenced or nested in the values of other parameters. You can't include {{}} or {{ssm:parameter-name}} in a parameter value.

Type: String

Required: Yes

Response Syntax

```
{  
    "Tier": "string",  
    "Version": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tier (p. 435)

The tier assigned to the parameter.

Type: String

Valid Values: Standard | Advanced | Intelligent-Tiering

Version (p. 435)

The new version number of a parameter. If you edit a parameter value, Parameter Store automatically creates a new version and assigns this new version a unique ID. You can reference

a parameter version ID in API operations or in Systems Manager documents (SSM documents). By default, if you don't specify a specific version, the system returns the latest parameter value when a parameter is called.

Type: Long

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

HierarchyLevelLimitExceededException

A hierarchy can have a maximum of 15 levels. For more information, see [Requirements and constraints for parameter names](#) in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

HierarchyTypeMismatchException

Parameter Store doesn't support changing a parameter type in a hierarchy. For example, you can't change a parameter from a String type to a SecureString type. You must create a new, unique parameter.

HTTP Status Code: 400

IncompatiblePolicyException

There is a conflict in the policies specified for this parameter. You can't, for example, specify two Expiration policies for a parameter. Review your policies, and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAllowedPatternException

The request doesn't meet the regular expression requirement.

HTTP Status Code: 400

InvalidKeyId

The query key ID isn't valid.

HTTP Status Code: 400

InvalidPolicyAttributeException

A policy attribute or its value is invalid.

HTTP Status Code: 400

InvalidPolicyTypeException

The policy type isn't supported. Parameter Store supports the following policy types: Expiration, ExpirationNotification, and NoChangeNotification.

HTTP Status Code: 400

ParameterAlreadyExists

The parameter already exists. You can't create duplicate parameters.

HTTP Status Code: 400

ParameterLimitExceeded

You have exceeded the number of parameters for this AWS account. Delete one or more parameters and try again.

HTTP Status Code: 400

ParameterMaxVersionLimitExceeded

Parameter Store retains the 100 most recently created versions of a parameter. After this number of versions has been created, Parameter Store deletes the oldest version when a new one is created. However, if the oldest version has a *label* attached to it, Parameter Store won't delete the version and instead presents this error message:

An error occurred (ParameterMaxVersionLimitExceeded) when calling the PutParameter operation: You attempted to create a new version of *parameter-name* by calling the PutParameter API with the overwrite flag. Version *version-number*, the oldest version, can't be deleted because it has a label associated with it. Move the label to another version of the parameter, and try again.

This safeguard is to prevent parameter versions with mission critical labels assigned to them from being deleted. To continue creating new parameters, first move the label from the oldest version of the parameter to a newer one for use in your operations. For information about moving parameter labels, see [Move a parameter label \(console\)](#) or [Move a parameter label \(CLI\)](#) in the *AWS Systems Manager User Guide*.

HTTP Status Code: 400

ParameterPatternMismatchException

The parameter name isn't valid.

HTTP Status Code: 400

PoliciesLimitExceededException

You specified more than the maximum number of allowed policies for the parameter. The maximum is 10.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

UnsupportedParameterType

The parameter type isn't supported.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of PutParameter.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 136
X-Amz-Target: AmazonSSM.PutParameter
X-Amz-Date: 20180316T000626Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180316/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Overwrite": true,
    "Type": "String",
    "Name": "EC2TestServerType",
    "Value": "t2.large",
    "Description": "Instance type for Test servers"
}
```

Sample Response

```
{
    "Version": 2
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterDefaultPatchBaseline

Defines the default patch baseline for the relevant operating system.

To reset the AWS-predefined patch baseline as the default, specify the full patch baseline Amazon Resource Name (ARN) as the baseline ID value. For example, for CentOS, specify `arn:aws:ssm:us-east-2:733109147000:patchbaseline/pb-0574b43a65ea646ed` instead of `pb-0574b43a65ea646ed`.

Request Syntax

```
{  
    "BaselineId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 439)

The ID of the patch baseline that should be the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-\:/]{20,128}$`

Required: Yes

Response Syntax

```
{  
    "BaselineId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

BaselineId (p. 439)

The ID of the default patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterDefaultPatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 38
X-Amz-Target: AmazonSSM.RegisterDefaultPatchBaseline
X-Amz-Date: 20180309T025821Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterPatchBaselineForPatchGroup

Registers a patch baseline for a patch group.

Request Syntax

```
{  
    "BaselineId": "string",  
    "PatchGroup": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

BaselineId (p. 442)

The ID of the patch baseline to register with the patch group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Required: Yes

PatchGroup (p. 442)

The name of the patch group to be registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)\$

Required: Yes

Response Syntax

```
{  
    "BaselineId": "string",  
    "PatchGroup": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[BaselineId \(p. 442\)](#)

The ID of the patch baseline the patch group was registered with.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

[PatchGroup \(p. 442\)](#)

The name of the patch group registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}]\p{N}_\.:/\=+\-@]*\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AlreadyExistsException

Error returned if an attempt is made to register a patch group with a patch baseline that is already registered with a different patch baseline.

HTTP Status Code: 400

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterPatchBaselineForPatchGroup.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 74
X-Amz-Target: AmazonSSM.RegisterPatchBaselineForPatchGroup
X-Amz-Date: 20180309T060234Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

Sample Response

```
{
    "PatchGroup": "mypatchgroup",
    "BaselineId": "pb-0c10e65780EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterTargetWithMaintenanceWindow

Registers a target with a maintenance window.

Request Syntax

```
{  
    "ClientToken": "string",  
    "Description": "string",  
    "Name": "string",  
    "OwnerInformation": "string",  
    "ResourceType": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "WindowId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ClientToken \(p. 445\)](#)

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

[Description \(p. 445\)](#)

An optional description for the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[Name \(p. 445\)](#)

An optional name for the target.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

[OwnerInformation \(p. 445\)](#)

User-provided value that will be included in any Amazon CloudWatch Events events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[ResourceType \(p. 445\)](#)

The type of target being registered with the maintenance window.

Type: String

Valid Values: INSTANCE | RESOURCE_GROUP

Required: Yes

[Targets \(p. 445\)](#)

The targets to register with the maintenance window. In other words, the managed nodes to run commands on when the maintenance window runs.

Note

If a single maintenance window task is registered with multiple targets, its task invocations occur sequentially and not in parallel. If your task must run on multiple targets at the same time, register a task for each target individually and assign each task the same priority level.

You can specify targets using managed node IDs, resource group names, or tags that have been applied to managed nodes.

Example 1: Specify managed node IDs

```
Key=InstanceIds,Values=<instance-id-1>,<instance-id-2>,<instance-id-3>
```

Example 2: Use tag key-pairs applied to managed nodes

```
Key=tag:<my-tag-key>,Values=<my-tag-value-1>,<my-tag-value-2>
```

Example 3: Use tag-keys applied to managed nodes

```
Key=tag-key,Values=<my-tag-key-1>,<my-tag-key-2>
```

Example 4: Use resource group names

```
Key=resource-groups:Name,Values=<resource-group-name>
```

Example 5: Use filters for resource group types

```
Key=resource-groups:ResourceTypeFilters,Values=<resource-type-1>,<resource-type-2>
```

Note

For Key=resource-groups:ResourceTypeFilters, specify resource types in the following format

```
Key=resource-groups:ResourceTypeFilters,Values=AWS::EC2::INSTANCE,AWS::EC2::VPC
```

For more information about these examples formats, including the best use case for each one, see [Examples: Register targets with a maintenance window](#) in the *AWS Systems Manager User Guide*.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: Yes

[WindowId \(p. 445\)](#)

The ID of the maintenance window the target should be registered with.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "WindowTargetId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WindowTargetId \(p. 447\)](#)

The ID of the target definition in this maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterTargetWithMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.RegisterTargetWithMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T003144Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target,Signature=39c3b3042cd2aEXAMPLE
Content-Length: 191

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "ResourceType": "INSTANCE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "ClientToken": "aa1b2cde-27e3-42ff-9cac-99380EXAMPLE"
}
```

Sample Response

```
{
    "WindowTargetId": "7f4813bb-df25-4e59-b34f-c9e83EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterTaskWithMaintenanceWindow

Adds a new task to a maintenance window.

Request Syntax

```
{
  "ClientToken": "string",
  "CutoffBehavior": "string",
  "Description": "string",
  "LoggingInfo": {
    "S3BucketName": "string",
    "S3KeyPrefix": "string",
    "S3Region": "string"
  },
  "MaxConcurrency": "string",
  "MaxErrors": "string",
  "Name": "string",
  "Priority": number,
  "ServiceRoleArn": "string",
  "Targets": [
    {
      "Key": "string",
      "Values": [ "string" ]
    }
  ],
  "TaskArn": "string",
  "TaskInvocationParameters": {
    "Automation": {
      "DocumentVersion": "string",
      "Parameters": {
        "string" : [ "string" ]
      }
    },
    "Lambda": {
      "ClientContext": "string",
      "Payload": blob,
      "Qualifier": "string"
    },
    "RunCommand": {
      "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "string",
        "CloudWatchOutputEnabled": boolean
      },
      "Comment": "string",
      "DocumentHash": "string",
      "DocumentHashType": "string",
      "DocumentVersion": "string",
      "NotificationConfig": {
        "NotificationArn": "string",
        "NotificationEvents": [ "string" ],
        "NotificationType": "string"
      },
      "OutputS3BucketName": "string",
      "OutputS3KeyPrefix": "string",
      "Parameters": {
        "string" : [ "string" ]
      },
      "ServiceRoleArn": "string",
      "TimeoutSeconds": number
    },
    "StepFunctions": {
      "Input": "string",
      "LambdaFunctionArn": "string"
    }
  }
}
```

```
        "Name": "string"
    },
    "TaskParameters": {
        "string" : {
            "Values": [ "string" ]
        }
    },
    "TaskType": "string",
    "WindowId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ClientToken \(p. 450\)](#)

User-provided idempotency token.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

[CutoffBehavior \(p. 450\)](#)

Indicates whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

- CONTINUE_TASK: When the cutoff time is reached, any tasks that are running continue. The default value.
- CANCEL_TASK:
 - For Automation, AWS Lambda, AWS Step Functions tasks: When the cutoff time is reached, any task invocations that are already running continue, but no new task invocations are started.
 - For Run Command tasks: When the cutoff time is reached, the system sends a [CancelCommand \(p. 13\)](#) operation that attempts to cancel the command associated with the task. However, there is no guarantee that the command will be terminated and the underlying process stopped.

The status for tasks that are not completed is `TIMED_OUT`.

Type: String

Valid Values: `CONTINUE_TASK` | `CANCEL_TASK`

Required: No

[Description \(p. 450\)](#)

An optional description for the task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[LoggingInfo \(p. 450\)](#)

A structure containing information about an Amazon Simple Storage Service (Amazon S3) bucket to write managed node-level logs to.

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: [LoggingInfo \(p. 712\)](#) object

Required: No

[MaxConcurrency \(p. 450\)](#)

The maximum number of targets this task can be run for, in parallel.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)$`

Required: No

[MaxErrors \(p. 450\)](#)

The maximum number of errors allowed before this task stops being scheduled.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]^|100%)$`

Required: No

[Name \(p. 450\)](#)

An optional name for the task.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

[Priority \(p. 450\)](#)

The priority of the task in the maintenance window, the lower the number the higher the priority. Tasks in a maintenance window are scheduled in priority order with tasks that have the same priority scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

[ServiceRoleArn \(p. 450\)](#)

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses your account's service-linked role. If no service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

For more information, see the following topics in the *AWS Systems Manager User Guide*:

- [Using service-linked roles for Systems Manager](#)
- [Should I use a service-linked role or a custom service role to run maintenance window tasks?](#)

Type: String

Required: No

[Targets \(p. 450\)](#)

The targets (either managed nodes or maintenance window targets).

Note

One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see [Registering maintenance window tasks without targets](#) in the *AWS Systems Manager User Guide*.

Specify managed nodes using the following format:

`Key=InstanceIds,Values=<instance-id-1>,<instance-id-2>`

Specify maintenance window targets using the following format:

`Key=WindowTargetIds,Values=<window-target-id-1>,<window-target-id-2>`

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[TaskArn \(p. 450\)](#)

The ARN of the task to run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

[TaskInvocationParameters \(p. 450\)](#)

The parameters that the task should use during execution. Populate only the fields that match the task type. All other fields should be empty.

Type: [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#) object

Required: No

[TaskParameters \(p. 450\)](#)

The parameters that should be passed to the task when it is run.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: String to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

[TaskType \(p. 450\)](#)

The type of task being registered.

Type: String

Valid Values: `RUN_COMMAND` | `AUTOMATION` | `STEP_FUNCTIONS` | `LAMBDA`

Required: Yes

[WindowId \(p. 450\)](#)

The ID of the maintenance window the task should be added to.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `^mw-[0-9a-f]{17}$`

Required: Yes

Response Syntax

```
{  
    "WindowTaskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[WindowTaskId \(p. 454\)](#)

The ID of the task in the maintenance window.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

FeatureNotAvailableException

You attempted to register a LAMBDA or STEP_FUNCTIONS task in a region where the corresponding service isn't available.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceLimitExceededException

Error returned when the caller has exceeded the default resource quotas. For example, too many maintenance windows or patch baselines have been created.

For information about resource quotas in Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RegisterTaskWithMaintenanceWindow.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.RegisterTaskWithMaintenanceWindow
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T181553Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 362

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-02573cafccEXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-RunShellScript",
    "TaskType": "RUN_COMMAND",
    "TaskInvocationParameters": {
        "RunCommand": {
            "Parameters": {
                "commands": [
                    "df"
                ]
            }
        }
    },
    "Priority": 10,
    "MaxConcurrency": "1",
    "MaxErrors": "1",
    "ClientToken": "8a3f60db-1d39-4938-a566-c2ec2EXAMPLE"
}
```

Sample Response

```
{
    "WindowTaskId": "216ae877-0be9-4746-a19d-ed654EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RemoveTagsFromResource

Removes tag keys from the specified resource.

Request Syntax

```
{  
    "ResourceId": "string",  
    "ResourceType": "string",  
    "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ResourceId (p. 458)

The ID of the resource from which you want to remove tags. For example:

ManagedInstance: mi-012345abcde

MaintenanceWindow: mw-012345abcde

Automation: example-c160-4567-8519-012345abcde

PatchBaseline: pb-012345abcde

OpsMetadata object: ResourceID for tagging is created from the Amazon Resource Name (ARN) for the object. Specifically, ResourceID is created from the strings that come after the word `opsmetadata` in the ARN. For example, an OpsMetadata object with an ARN of `arn:aws:ssm:us-east-2:1234567890:opsmetadata/aws/ssm/MyGroup/appmanager` has a ResourceID of either `aws/ssm/MyGroup/appmanager` or `/aws/ssm/MyGroup/appmanager`.

For the Document and Parameter values, use the name of the resource.

Note

The ManagedInstance type for this API operation is only for on-premises managed nodes. Specify the name of the managed node in the following format: `mi-ID_number`. For example, `mi-1a2b3c4d5e6f`.

Type: String

Required: Yes

ResourceType (p. 458)

The type of resource from which you want to remove a tag.

Note

The ManagedInstance type for this API operation is only for on-premises managed nodes. Specify the name of the managed node in the following format: `mi-ID_number`. For example, `mi-1a2b3c4d5e6f`.

Type: String

Valid Values: Document | ManagedInstance | MaintenanceWindow | Parameter | PatchBaseline | OpsItem | OpsMetadata | Automation

Required: Yes

TagKeys (p. 458)

Tag keys that you want to remove from the specified resource.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidResourceId

The resource ID isn't valid. Verify that you entered the correct ID and try again.

HTTP Status Code: 400

InvalidResourceType

The resource type isn't valid. For example, if you are attempting to tag an EC2 instance, the instance must be a registered managed node.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of RemoveTagsFromResource.

Sample Request

```
POST / HTTP/1.1
```

```
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.RemoveTagsFromResource
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T004031Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 99

{
    "ResourceType": "PatchBaseline",
    "ResourceId": "pb-0c10e65780EXAMPLE",
    "TagKeys": [
        "Environment"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResetServiceSetting

ServiceSetting is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a SettingId object to a setting value. AWS services teams define the default value for a SettingId. You can't create a new SettingId, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the [GetServiceSetting \(p. 347\)](#) API operation to view the current value. Use the [UpdateServiceSetting \(p. 575\)](#) API operation to change the default setting.

Reset the service setting for the account to the default value as provisioned by the AWS service team.

Request Syntax

```
{  
    "SettingId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

SettingId (p. 461)

The Amazon Resource Name (ARN) of the service setting to reset. The setting ID can be one of the following.

- /ssm/automation/customer-script-log-destination
- /ssm/automation/customer-script-log-group-name
- /ssm/documents/console/public-sharing-permission
- /ssm/parameter-store/default-parameter-tier
- /ssm/parameter-store/high-throughput-enabled
- /ssm/managed-instance/activation-tier

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Response Syntax

```
{  
    "ServiceSetting": {  
        "ARN": "string",  
        "LastModifiedDate": number,  
        "LastModifiedUser": "string",  
    }  
}
```

```
    "SettingId": "string",
    "SettingValue": "string",
    "Status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ServiceSetting (p. 461)

The current, effective service setting after calling the ResetServiceSetting API operation.

Type: [ServiceSetting \(p. 827\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of ResetServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ResetServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T153659Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
```

```
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 110
```

```
{
    "SettingId": "arn:aws:ssm:us-east-2:111122223333:servicessetting/ssm/parameter-store/
high-throughput-enabled"
}
```

Sample Response

```
{
    "ServiceSetting": {
        "ARN": "arn:aws:ssm:us-east-2:111122223333:servicessetting/ssm/parameter-store/high-
throughput-enabled",
        "LastModifiedDate": 1555532571.138,
        "LastModifiedUser": "System",
        "SettingId": "/ssm/parameter-store/high-throughput-enabled",
        "SettingValue": "false",
        "Status": "Default"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResumeSession

Reconnects a session to a managed node after it has been disconnected. Connections can be resumed for disconnected sessions, but not terminated sessions.

Note

This command is primarily for use by client machines to automatically reconnect during intermittent network issues. It isn't intended for any other use.

Request Syntax

```
{  
    "SessionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[SessionId \(p. 464\)](#)

The ID of the disconnected session to resume.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: Yes

Response Syntax

```
{  
    "SessionId": "string",  
    "StreamUrl": "string",  
    "TokenValue": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SessionId \(p. 464\)](#)

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

[StreamUrl \(p. 464\)](#)

A URL back to SSM Agent on the managed node that the Session Manager client uses to send commands and receive output from the managed node. Format: `wss://ssmmessages.region.amazonaws.com/v1/data-channel/session-id?stream=(input|output)`.

region represents the Region identifier for an AWS Region supported by AWS Systems Manager, such as `us-east-2` for the US East (Ohio) Region. For a list of supported **region** values, see the [Region column in Systems Manager service endpoints](#) in the *Amazon Web Services General Reference*.

session-id represents the ID of a Session Manager session, such as `1a2b3c4dEXAMPLE`.

Type: String

[TokenValue \(p. 464\)](#)

An encrypted token value containing session and caller information. Used to authenticate the connection to the managed node.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `ResumeSession`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.ResumeSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
```

```
X-Amz-Date: 20200221T181144Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

Sample Response

```
{{
    "SessionId": "John-Doe-0402960697EXAMPLE",
    "StreamUrl": "wss://ssmmessages.us-east-2.amazonaws.com/v1/data-channel/John-
Doe-0402960697EXAMPLE?role=publish_subscribe",
    "TokenValue": "EXAMPLENPKTm3/39c3b3042cd2aEXAMPLE/a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE"
}}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendAutomationSignal

Sends a signal to an Automation execution to change the current behavior or status of the execution.

Request Syntax

```
{  
    "AutomationExecutionId": "string",  
    "Payload": {  
        "string" : [ "string" ]  
    },  
    "SignalType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AutomationExecutionId \(p. 467\)](#)

The unique identifier for an existing Automation execution that you want to send the signal to.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

[Payload \(p. 467\)](#)

The data sent with the signal. The data schema depends on the type of signal used in the request.

For `Approve` and `Reject` signal types, the payload is an optional comment that you can send with the signal type. For example:

`Comment="Looks good"`

For `StartStep` and `Resume` signal types, you must send the name of the Automation step to start or resume as the payload. For example:

`StepName="step1"`

For the `StopStep` signal type, you must send the step execution ID as the payload. For example:

`StepExecutionId="97fff367-fc5a-4299-aed8-0123456789ab"`

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

SignalType (p. 467)

The type of signal to send to an Automation execution.

Type: String

Valid Values: Approve | Reject | StartStep | StopStep | Resume

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

AutomationStepNotFoundException

The specified step name and execution ID don't exist. Verify the information and try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationSignalException

The signal isn't valid for the current Automation execution.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of SendAutomationSignal.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.SendAutomationSignal
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T162449Z
```

```
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 165

{
    "AutomationExecutionId": "b2bc0e75-4d48-4b7b-be9b-0cb5cEXAMPLE",
    "SignalType": "StopStep",
    "Payload": {
        "StepExecutionId": [
            "33d93af9-9535-4dd5-a06b-c91bdEXAMPLE"
        ]
    }
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendCommand

Runs commands on one or more managed nodes.

Request Syntax

```
{  
    "CloudWatchOutputConfig": {  
        "CloudWatchLogGroupName": "string",  
        "CloudWatchOutputEnabled": boolean  
    },  
    "Comment": "string",  
    "DocumentHash": "string",  
    "DocumentHashType": "string",  
    "DocumentName": "string",  
    "DocumentVersion": "string",  
    "InstanceIds": [ "string" ],  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "NotificationConfig": {  
        "NotificationArn": "string",  
        "NotificationEvents": [ "string" ],  
        "NotificationType": "string"  
    },  
    "OutputS3BucketName": "string",  
    "OutputS3KeyPrefix": "string",  
    "OutputS3Region": "string",  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "ServiceRoleArn": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "TimeoutSeconds": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[CloudWatchOutputConfig \(p. 470\)](#)

Enables AWS Systems Manager to send Run Command output to Amazon CloudWatch Logs. Run Command is a capability of AWS Systems Manager.

Type: [CloudWatchOutputConfig \(p. 625\)](#) object

Required: No

[Comment \(p. 470\)](#)

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

[DocumentHash \(p. 470\)](#)

The Sha256 or Sha1 hash created by the system when the document was created.

Note

Sha1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[DocumentHashType \(p. 470\)](#)

Sha256 or Sha1.

Note

Sha1 hashes have been deprecated.

Type: String

Valid Values: Sha256 | Sha1

Required: No

[DocumentName \(p. 470\)](#)

The name of the AWS Systems Manager document (SSM document) to run. This can be a public document or a custom document. To run a shared document belonging to another account, specify the document Amazon Resource Name (ARN). For more information about how to use shared documents, see [Using shared SSM documents](#) in the *AWS Systems Manager User Guide*.

Note

If you specify a document name or ARN that hasn't been shared with your account, you receive an InvalidDocument error.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.:/]{3,128}\$

Required: Yes

[DocumentVersion \(p. 470\)](#)

The SSM document version to use in the request. You can specify \$DEFAULT, \$LATEST, or a specific version number. If you run commands by using the AWS Command Line Interface (AWS CLI), then you must escape the first two options by using a backslash. If you specify a version number, then you don't need to use the backslash. For example:

```
--document-version "\$DEFAULT"
```

```
--document-version "\$LATEST"
```

```
--document-version "3"
```

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

InstanceIds (p. 470)

The IDs of the managed nodes where the command should run. Specifying managed node IDs is most useful when you are targeting a limited number of managed nodes, though you can specify up to 50 IDs.

To target a larger number of managed nodes, or if you prefer not to list individual node IDs, we recommend using the `Targets` option instead. Using `Targets`, which accepts tag key-value pairs to identify the managed nodes to send commands to, you can send command to tens, hundreds, or thousands of nodes at once.

For more information about how to use targets, see [Using targets and rate controls to send commands to a fleet](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: `(^i-(\w{8}|\w{17})$)|(^mi-\w{17}$)`

Required: No

MaxConcurrency (p. 470)

(Optional) The maximum number of managed nodes that are allowed to run the command at the same time. You can specify a number such as 10 or a percentage such as 10%. The default value is 50. For more information about how to use `MaxConcurrency`, see [Using concurrency controls](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)$`

Required: No

MaxErrors (p. 470)

The maximum number of errors allowed without the command failing. When the command fails one more time beyond the value of `MaxErrors`, the system stops sending the command to additional targets. You can specify a number like 10 or a percentage like 10%. The default value is 0. For more information about how to use `MaxErrors`, see [Using error controls](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]|100%)$`

Required: No

NotificationConfig (p. 470)

Configurations for sending notifications.

Type: [NotificationConfig \(p. 743\)](#) object

Required: No

OutputS3BucketName (p. 470)

The name of the S3 bucket where command execution responses should be stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

[OutputS3KeyPrefix \(p. 470\)](#)

The directory structure within the S3 bucket where the responses should be stored.

Type: String

Length Constraints: Maximum length of 500.

Required: No

[OutputS3Region \(p. 470\)](#)

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, Systems Manager automatically determines the AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

[Parameters \(p. 470\)](#)

The required and optional parameters specified in the document being run.

Type: String to array of strings map

Required: No

[ServiceRoleArn \(p. 470\)](#)

The ARN of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for Run Command commands.

Type: String

Required: No

[Targets \(p. 470\)](#)

An array of search criteria that targets managed nodes using a `Key`, `Value` combination that you specify. Specifying targets is most useful when you want to send a command to a large number of managed nodes at once. Using Targets, which accepts tag key-value pairs to identify managed nodes, you can send a command to tens, hundreds, or thousands of nodes at once.

To send a command to a smaller number of managed nodes, you can use the `InstanceIds` option instead.

For more information about how to use targets, see [Sending commands to a fleet](#) in the *AWS Systems Manager User Guide*.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[TimeoutSeconds \(p. 470\)](#)

If this time is reached and the command hasn't already started running, it won't run.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

Response Syntax

```
{  
    "Command": {  
        "CloudWatchOutputConfig": {  
            "CloudWatchLogGroupName": "string",  
            "CloudWatchOutputEnabled": boolean  
        },  
        "CommandId": "string",  
        "Comment": "string",  
        "CompletedCount": number,  
        "DeliveryTimedOutCount": number,  
        "DocumentName": "string",  
        "DocumentVersion": "string",  
        "ErrorCount": number,  
        "ExpiresAfter": number,  
        "InstanceIds": [ "string" ],  
        "MaxConcurrency": "string",  
        "MaxErrors": "string",  
        "NotificationConfig": {  
            "NotificationArn": "string",  
            "NotificationEvents": [ "string" ],  
            "NotificationType": "string"  
        },  
        "OutputS3BucketName": "string",  
        "OutputS3KeyPrefix": "string",  
        "OutputS3Region": "string",  
        "Parameters": {  
            "string" : [ "string" ]  
        },  
        "RequestedDateTime": number,  
        "ServiceRole": "string",  
        "Status": "string",  
        "StatusDetails": "string",  
        "TargetCount": number,  
        "Targets": [  
            {  
                "Key": "string",  
                "Values": [ "string" ]  
            }  
        ],  
        "TimeoutSeconds": number  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Command \(p. 474\)](#)

The request as it was received by Systems Manager. Also provides the command ID which can be used future references to this request.

Type: [Command \(p. 626\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DuplicateInstanceId

You can't specify a managed node ID in more than one association.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

InvalidNotificationConfig

One or more configuration items isn't valid. Verify that a valid Amazon Resource Name (ARN) was provided for an Amazon Simple Notification Service topic.

HTTP Status Code: 400

InvalidOutputFolder

The S3 bucket doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidRole

The role name can't contain invalid characters. Also verify that you specified an IAM role for notifications that includes the required trust policy. For information about configuring the IAM role for Run Command notifications, see [Configuring Amazon SNS Notifications for Run Command](#) in the [AWS Systems Manager User Guide](#).

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

UnsupportedPlatformType

The document doesn't support the platform type of the given managed node ID(s). For example, you sent an document for a Windows managed node to a Linux node.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of SendCommand.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.SendCommand
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T000322Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 153

{
    "CloudWatchOutputConfig": {
        "CloudWatchLogGroupName": "my-log-group",
        "CloudWatchOutputEnabled": true
    },
    "DocumentName": "AWS-ConfigureCloudWatch",
    "DocumentVersion": "1",
    "InstanceIds": [
        "i-07be1baa4aEXAMPLE",
        "i-017431b35cEXAMPLE",
        "i-09c350ed76EXAMPLE"
    ],
    "MaxConcurrency": "2",
    "MaxErrors": "1",
    "NotificationConfig": {
        "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-notification-
arn",
        "NotificationEvents": [
            "Failed",
            "Success"
        ],
        "NotificationType": "Command"
    },
    "OutputS3BucketName": "doc-example-bucket",
    "OutputS3KeyPrefix": "my-rc-output",
    "OutputS3Region": "us-east-2",
    "Parameters": {
        "string": []
    }
},
```

```
    "TimeoutSeconds": 3
}
```

Sample Response

```
{
  "Command": {
    "CommandId": "b94bf1dc-fe7d-4e88-851d-e85e5EXAMPLE",
    "DocumentName": "AWS-ConfigureCloudWatch",
    "DocumentVersion": "1",
    "Comment": "",
    "ExpiresAfter": 1582250177.7,
    "Parameters": {
      "properties": [
        ""
      ],
      "status": [
        "Enabled"
      ]
    },
    "InstanceIds": [],
    "Targets": [
      {
        "Key": "InstanceIds",
        "Values": [
          "i-07be1baa4aEXAMPLE",
          "i-017431b35cEXAMPLE",
          "i-09c350ed76EXAMPLE"
        ]
      }
    ],
    "RequestedDateTime": 1582245977.7,
    "Status": "Pending",
    "StatusDetails": "Pending",
    "OutputS3BucketName": "doc-example-bucket",
    "OutputS3KeyPrefix": "my-rc-output",
    "MaxConcurrency": "2",
    "MaxErrors": "1",
    "TargetCount": 0,
    "CompletedCount": 0,
    "ErrorCount": 0,
    "DeliveryTimedOutCount": 0,
    "ServiceRole": "arn:aws:iam::111122223333:role/my-SNS-notifications-role",
    "NotificationConfig": {
      "NotificationArn": "arn:aws:sns:us-east-2:111122223333:my-us-east-2-notification-arn",
      "NotificationEvents": [
        "Failed",
        "Success"
      ],
      "NotificationType": "Command"
    },
    "CloudWatchOutputConfig": {
      "CloudWatchLogGroupName": "my-log-group",
      "CloudWatchOutputEnabled": true
    }
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAssociationsOnce

Runs an association immediately and only one time. This operation can be helpful when troubleshooting associations.

Request Syntax

```
{  
    "AssociationIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationIds (p. 479)

The association IDs that you want to run immediately and only one time.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InvalidAssociation

The association isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartAssociationsOnce.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartAssociationsOnce
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T163434Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 60

{
    "AssociationIds": [
        "4332cf28-050d-4fa1-a4df-11b39EXAMPLE"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAutomationExecution

Initiates execution of an Automation runbook.

Request Syntax

```
{  
    "ClientToken": "string",  
    "DocumentName": "string",  
    "DocumentVersion": "string",  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Mode": "string",  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ],  
    "TargetLocations": [  
        {  
            "Accounts": [ "string" ],  
            "ExecutionRoleName": "string",  
            "Regions": [ "string" ],  
            "TargetLocationMaxConcurrency": "string",  
            "TargetLocationMaxErrors": "string"  
        }  
    ],  
    "TargetMaps": [  
        {  
            "string" : [ "string" ]  
        }  
    ],  
    "TargetParameterName": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ClientToken (p. 481)

User-provided idempotency token. The token must be unique, is case insensitive, enforces the UUID format, and can't be reused.

Type: String

Length Constraints: Fixed length of 36.

Pattern: [a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}

Required: No

DocumentName (p. 481)

The name of the SSM document to run. This can be a public document or a custom document. To run a shared document belonging to another account, specify the document ARN. For more information about how to use shared documents, see [Using shared SSM documents](#) in the *AWS Systems Manager User Guide*.

Type: String

Pattern: ^[a-zA-Z0-9_\-.:/]{3,128}\$

Required: Yes

DocumentVersion (p. 481)

The version of the Automation runbook to use for this execution.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

MaxConcurrency (p. 481)

The maximum number of targets allowed to run this task in parallel. You can specify a number, such as 10, or a percentage, such as 10%. The default value is 10.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)\$

Required: No

MaxErrors (p. 481)

The number of errors that are allowed before the system stops running the automation on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops running the automation when the fourth error is received. If you specify 0, then the system stops running the automation on additional targets after the first error result is returned. If you run an automation on 50 resources and set max-errors to 10%, then the system stops running the automation on additional targets when the sixth error is received.

Executions that are already running an automation when max-errors is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set max-concurrency to 1 so the executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%^|100%)\$

Required: No

[Mode \(p. 481\)](#)

The execution mode of the automation. Valid modes include the following: Auto and Interactive. The default mode is Auto.

Type: String

Valid Values: Auto | Interactive

Required: No

[Parameters \(p. 481\)](#)

A key-value map of execution parameters, which match the declared parameters in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[Tags \(p. 481\)](#)

Optional metadata that you assign to a resource. You can specify a maximum of five tags for an automation. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag an automation to identify an environment or operating system. In this case, you could specify the following key-value pairs:

- Key=environment, Value=test
- Key=OS, Value=Windows

Note

To add tags to an existing automation, use the [AddTagsToResource \(p. 6\)](#) operation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

[TargetLocations \(p. 481\)](#)

A location is a combination of AWS Regions and/or AWS accounts where you want to run the automation. Use this operation to start an automation in multiple AWS Regions and multiple AWS accounts. For more information, see [Running Automation workflows in multiple AWS Regions and AWS accounts](#) in the *AWS Systems Manager User Guide*.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

[TargetMaps \(p. 481\)](#)

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

[TargetParameterName \(p. 481\)](#)

The name of the parameter used as the target resource for the rate-controlled execution. Required if you specify targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

[Targets \(p. 481\)](#)

A key-value mapping to target resources. Required if you specify TargetParameterName.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{  
    "AutomationExecutionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AutomationExecutionId \(p. 484\)](#)

The unique ID of a newly scheduled automation execution.

Type: String

Length Constraints: Fixed length of 36.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AutomationDefinitionNotFoundException

An Automation runbook with the specified name couldn't be found.

HTTP Status Code: 400

AutomationDefinitionVersionNotFoundException

An Automation runbook with the specified name and version couldn't be found.

HTTP Status Code: 400

AutomationExecutionLimitExceededException

The number of simultaneously running Automation executions exceeded the allowable limit.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationExecutionParametersException

The supplied parameters for invoking the specified Automation runbook are incorrect. For example, they may not match the set of parameters permitted for the specified Automation document.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartAutomationExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T162110Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
```

```
Content-Length: 86

{
    "DocumentName": "Example",
    "Parameters": {
        "InstanceId": [
            "i-02573cafefEXAMPLE"
        ]
    }
}
```

Sample Response

```
{
    "AutomationExecutionId": "832a6fba-f4f0-4b2a-ab85-587adEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartChangeRequestExecution

Creates a change request for Change Manager. The Automation runbooks specified in the change request run only after all required approvals for the change request have been received.

Request Syntax

```
{  
    "AutoApprove": boolean,  
    "ChangeDetails": "string",  
    "ChangeRequestName": "string",  
    "ClientToken": "string",  
    "DocumentName": "string",  
    "DocumentVersion": "string",  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "Runbooks": [  
        {  
            "DocumentName": "string",  
            "DocumentVersion": "string",  
            "MaxConcurrency": "string",  
            "MaxErrors": "string",  
            "Parameters": {  
                "string" : [ "string" ]  
            },  
            "TargetLocations": [  
                {  
                    "Accounts": [ "string" ],  
                    "ExecutionRoleName": "string",  
                    "Regions": [ "string" ],  
                    "TargetLocationMaxConcurrency": "string",  
                    "TargetLocationMaxErrors": "string"  
                }  
            ],  
            "TargetMaps": [  
                {  
                    "string" : [ "string" ]  
                }  
            ],  
            "TargetParameterName": "string",  
            "Targets": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ]  
        }  
    ],  
    "ScheduledEndTime": number,  
    "ScheduledTime": number,  
    "Tags": [  
        {  
            "Key": "string",  
            "Value": "string"  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AutoApprove \(p. 487\)](#)

Indicates whether the change request can be approved automatically without the need for manual approvals.

If `AutoApprovable` is enabled in a change template, then setting `AutoApprove` to `true` in `StartChangeRequestExecution` creates a change request that bypasses approver review.

Note

Change Calendar restrictions are not bypassed in this scenario. If the state of an associated calendar is `CLOSED`, change freeze approvers must still grant permission for this change request to run. If they don't, the change won't be processed until the calendar state is again `OPEN`.

Type: Boolean

Required: No

[ChangeDetails \(p. 487\)](#)

User-provided details about the change. If no details are provided, content specified in the **Template information** section of the associated change template is added.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32768.

Required: No

[ChangeRequestName \(p. 487\)](#)

The name of the change request associated with the runbook workflow to be run.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

[ClientToken \(p. 487\)](#)

The user-provided idempotency token. The token must be unique, is case insensitive, enforces the UUID format, and can't be reused.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[a-fA-F0-9]{8}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{4}-[a-fA-F0-9]{12}`

Required: No

[DocumentName \(p. 487\)](#)

The name of the change template document to run during the runbook workflow.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.:/]{3,128}\$

Required: Yes

[DocumentVersion \(p. 487\)](#)

The version of the change template document to run during the runbook workflow.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

[Parameters \(p. 487\)](#)

A key-value map of parameters that match the declared parameters in the change template document.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[Runbooks \(p. 487\)](#)

Information about the Automation runbooks that are run during the runbook workflow.

Note

The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of [Runbook \(p. 821\)](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

[ScheduledEndTime \(p. 487\)](#)

The time that the requester expects the runbook workflow related to the change request to complete. The time is an estimate only that the requester provides for reviewers.

Type: Timestamp

Required: No

[ScheduledTime \(p. 487\)](#)

The date and time specified in the change request to run the Automation runbooks.

Note

The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Timestamp

Required: No

[Tags \(p. 487\)](#)

Optional metadata that you assign to a resource. You can specify a maximum of five tags for a change request. Tags enable you to categorize a resource in different ways, such as by purpose, owner, or environment. For example, you might want to tag a change request to identify an environment or target AWS Region. In this case, you could specify the following key-value pairs:

- Key=Environment, Value=Production
- Key=Region, Value=us-east-2

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

Response Syntax

```
{  
    "AutomationExecutionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AutomationExecutionId (p. 490)

The unique ID of a runbook workflow operation. (A runbook workflow is a type of Automation operation.)

Type: String

Length Constraints: Fixed length of 36.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AutomationDefinitionNotApprovedException

Indicates that the Change Manager change template used in the change request was rejected or is still in a pending state.

HTTP Status Code: 400

AutomationDefinitionNotFoundException

An Automation runbook with the specified name couldn't be found.

HTTP Status Code: 400

AutomationDefinitionVersionNotFoundException

An Automation runbook with the specified name and version couldn't be found.

HTTP Status Code: 400

AutomationExecutionLimitExceeded

The number of simultaneously running Automation executions exceeded the allowable limit.

HTTP Status Code: 400

IdempotentParameterMismatch

Error returned when an idempotent operation is retried and the parameters don't match the original call to the API with the same idempotency token.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationExecutionParametersException

The supplied parameters for invoking the specified Automation runbook are incorrect. For example, they may not match the set of parameters permitted for the specified Automation document.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartChangeRequestExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartChangeRequestExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.2.12 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/ssm.start-
change-request-execution
X-Amz-Date: 20210820T192759Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210820/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 1247

{
    "ChangeRequestName": "MyChangeRequest",
    "DocumentName": "AWS-HelloWorldChangeTemplate",
    "DocumentVersion": "$DEFAULT",
    "ScheduledTime": 1640833200,
    "ScheduledEndTime": 1640833500,
    "Tags": [
        {
            "Key": "Purpose",
            "Value": "Testing"
        }
    ],
    "Parameters": {
        "Approver": [

```

```
        "JohnDoe"
    ],
    "ApproverType": [
        "IamUser"
    ],
    "ApproverSnsTopicArn": [
        "arn:aws:sns:us-east-2:111122223333:MyNotificationTopic"
    ]
},
"Runbooks": [
{
    "DocumentName": "AWS-HelloWorld",
    "DocumentVersion": "1",
    "MaxConcurrency": "1",
    "MaxErrors": "1",
    "Parameters": {
        "AutomationAssumeRole": [
            "arn:aws:iam::111122223333:role/MyChangeManagerAssumeRole"
        ]
    }
}
],
"ChangeDetails": "### Document Name: HelloWorldChangeTemplate\n## What does this document do?\nThis change template demonstrates the feature set available for creating change templates for Change Manager. This template starts a Runbook workflow for the Automation document called AWS-HelloWorld.\n## Input Parameters\n* ApproverSnsTopicArn: (Required) Amazon Simple Notification Service ARN for approvers.\n* Approver: (Required) The name of the approver to send this request to.\n* ApproverType: (Required) The type of reviewer.\n * Allowed Values: IamUser, IamGroup, IamRole, SSOGroup, SSOUser\n## Output Parameters\nThis document has no outputs "
}
```

Sample Response

```
{
    "AutomationExecutionId": "dddd1c6c-849d-4ee0-acc1-0be9dEXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartSession

Initiates a connection to a target (for example, a managed node) for a Session Manager session. Returns a URL and token that can be used to open a WebSocket connection for sending input and receiving outputs.

Note

AWS CLI usage: `start-session` is an interactive command that requires the Session Manager plugin to be installed on the client machine making the call. For information, see [Install the Session Manager plugin for the AWS CLI](#) in the *AWS Systems Manager User Guide*.

AWS Tools for PowerShell usage: `Start-SMSSession` isn't currently supported by AWS Tools for PowerShell on Windows local machines.

Request Syntax

```
{  
    "DocumentName": "string",  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "Reason": "string",  
    "Target": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

DocumentName (p. 493)

The name of the SSM document you want to use to define the type of session, input parameters, or preferences for the session. For example, `SSM-SessionManagerRunShell`. You can call the [GetDocument \(p. 271\)](#) API to verify the document exists before attempting to start a session. If no document name is provided, a shell to the managed node is launched by default. For more information, see [Start a session](#) in the *AWS Systems Manager User Guide*.

Type: String

Pattern: `^[a-zA-Z0-9_\.:/]{3,128}$`

Required: No

Parameters (p. 493)

The values you want to specify for the parameters defined in the Session document.

Type: String to array of strings map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

Reason (p. 493)

The reason for connecting to the instance. This value is included in the details for the Amazon CloudWatch Events event created when you start the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^.{1,256}\$

Required: No

[Target \(p. 493\)](#)

The managed node to connect to for the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

Response Syntax

```
{  
    "SessionId": "string",  
    "StreamUrl": "string",  
    "TokenValue": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SessionId \(p. 494\)](#)

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

[StreamUrl \(p. 494\)](#)

A URL back to SSM Agent on the managed node that the Session Manager client uses to send commands and receive output from the node. Format: `wss://ssmmessages.region.amazonaws.com/v1/data-channel/session-id?stream=(input|output)`

region represents the Region identifier for an AWS Region supported by AWS Systems Manager, such as `us-east-2` for the US East (Ohio) Region. For a list of supported **region** values, see the [Region column in Systems Manager service endpoints](#) in the [Amazon Web Services General Reference](#).

session-id represents the ID of a Session Manager session, such as `1a2b3c4dEXAMPLE`.

Type: String

[TokenValue \(p. 494\)](#)

An encrypted token value containing session and caller information. Used to authenticate the connection to the managed node.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 300.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

TargetNotConnected

The specified target managed node for the session isn't fully configured for use with Session Manager. For more information, see [Getting started with Session Manager](#) in the *AWS Systems Manager User Guide*. This error is also returned if you attempt to start a session on a managed node that is located in a different account or Region

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StartSession.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StartSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T181823Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 33

{
    "Target": "i-02573cafefEXAMPLE"
}
```

Sample Response

```
{
    "SessionId": "John-Doe-0dc5b7af96EXAMPLE",
    "StreamUrl": "wss://ssmmessages.us-east-2.amazonaws.com/v1/data-channel/John-
Doe-0dc5b7af96EXAMPLE?role=publish_subscribe",
    "TokenValue": "a3f5ff34-9bc4-4d2c-a665-4d1c1EXAMPLE/39c3b3042cd2aEXAMPLE"
```

}

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAutomationExecution

Stop an Automation that is currently running.

Request Syntax

```
{  
    "AutomationExecutionId": "string",  
    "Type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AutomationExecutionId (p. 497)

The execution ID of the Automation to stop.

Type: String

Length Constraints: Fixed length of 36.

Required: Yes

Type (p. 497)

The stop request type. Valid types include the following: Cancel and Complete. The default type is Cancel.

Type: String

Valid Values: Complete | Cancel

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AutomationExecutionNotFoundException

There is no automation execution information for the requested automation execution ID.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAutomationStatusUpdateException

The specified update status operation isn't valid.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of StopAutomationExecution.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.StopAutomationExecution
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T171100Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 65

{
    "AutomationExecutionId": "f7d1f82d-6cde-4f7a-aa53-d485bEXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TerminateSession

Permanently ends a session and closes the data connection between the Session Manager client and SSM Agent on the managed node. A terminated session can't be resumed.

Request Syntax

```
{  
    "SessionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[SessionId \(p. 499\)](#)

The ID of the session to terminate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: Yes

Response Syntax

```
{  
    "SessionId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[SessionId \(p. 499\)](#)

The ID of the session that has been terminated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of TerminateSession.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.TerminateSession
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200221T182708Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200221/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 50

{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

Sample Response

```
{
    "SessionId": "John-Doe-0402960697EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UnlabelParameterVersion

Remove a label or labels from a parameter.

Request Syntax

```
{  
    "Labels": [ "string" ],  
    "Name": "string",  
    "ParameterVersion": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Labels (p. 501)

One or more labels to delete from the specified parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Name (p. 501)

The name of the parameter from which you want to delete one or more labels.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

ParameterVersion (p. 501)

The specific version of the parameter which you want to delete one or more labels from. If it isn't present, the call will fail.

Type: Long

Required: Yes

Response Syntax

```
{  
    "InvalidLabels": [ "string" ],  
    "RemovedLabels": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InvalidLabels (p. 501)

The labels that aren't attached to the given parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

RemovedLabels (p. 501)

A list of all labels deleted from the parameter.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ParameterNotFound

The parameter couldn't be found. Verify the name and try again.

HTTP Status Code: 400

ParameterVersionNotFound

The specified parameter version wasn't found. Verify the parameter name and version, and try again.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UnlabelParameterVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UnlabelParameterVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20210712T183221Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 67

{
    "Name": "MyParameter",
    "ParameterVersion": 2,
    "Labels": [
        "label"
    ]
}
```

Sample Response

```
{
    "InvalidLabels": [],
    "RemovedLabels": [
        "label"
    ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAssociation

Updates an association. You can update the association name and version, the document version, schedule, parameters, and Amazon Simple Storage Service (Amazon S3) output. When you call `UpdateAssociation`, the system removes all optional parameters from the request and overwrites the association with null values for those parameters. This is by design. You must specify all optional parameters in the call, even if you are not changing the parameters. This includes the `Name` parameter. Before calling this API action, we recommend that you call the [DescribeAssociation \(p. 111\)](#) API operation and make a note of all optional parameters required for your `UpdateAssociation` call.

In order to call this API operation, your AWS Identity and Access Management (IAM) user account, group, or role must be configured with permission to call the [DescribeAssociation \(p. 111\)](#) API operation. If you don't have permission to call `DescribeAssociation`, then you receive the following error: An error occurred (AccessDeniedException) when calling the `UpdateAssociation` operation: User: <user_arn> isn't authorized to perform: ssm:DescribeAssociation on resource: <resource_arn>

Important

When you update an association, the association immediately runs against the specified targets. You can add the `ApplyOnlyAtCronInterval` parameter to run the association during the next schedule run.

Request Syntax

```
{  
    "ApplyOnlyAtCronInterval": boolean,  
    "AssociationId": "string",  
    "AssociationName": "string",  
    "AssociationVersion": "string",  
    "AutomationTargetParameterName": "string",  
    "CalendarNames": [ "string" ],  
    "ComplianceSeverity": "string",  
    "DocumentVersion": "string",  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Name": "string",  
    "OutputLocation": {  
        "S3Location": {  
            "OutputS3BucketName": "string",  
            "OutputS3KeyPrefix": "string",  
            "OutputS3Region": "string"  
        }  
    },  
    "Parameters": {  
        "string" : [ "string" ]  
    },  
    "ScheduleExpression": "string",  
    "ScheduleOffset": number,  
    "SyncCompliance": "string",  
    "TargetLocations": [  
        {  
            "Accounts": [ "string" ],  
            "ExecutionRoleName": "string",  
            "Regions": [ "string" ],  
            "TargetLocationMaxConcurrency": "string",  
            "TargetLocationMaxErrors": "string"  
        }  
    ],  
    "TargetMaps": [  
        {  
            "Targets": [ "string" ]  
        }  
    ]  
}
```

```
        "string" : [ "string" ]
    },
],
"Targets": [
{
    "Key": "string",
    "Values": [ "string" ]
}
]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ApplyOnlyAtCronInterval \(p. 504\)](#)

By default, when you update an association, the system runs it immediately after it is updated and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you update it. This parameter isn't supported for rate expressions.

If you chose this option when you created an association and later you edit that association or you make changes to the SSM document on which that association is based (by using the Documents page in the console), State Manager applies the association at the next specified cron interval. For example, if you chose the Latest version of an SSM document when you created an association and you edit the association by choosing a different document version on the Documents page, State Manager applies the association at the next specified cron interval if you previously selected this option. If this option wasn't selected, State Manager immediately runs the association.

You can reset this option. To do so, specify the no-apply-only-at-cron-interval parameter when you update the association from the command line. This parameter forces the association to run immediately after updating it and according to the interval specified.

Type: Boolean

Required: No

[AssociationId \(p. 504\)](#)

The ID of the association you want to update.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

[AssociationName \(p. 504\)](#)

The name of the association that you want to update.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

[AssociationVersion \(p. 504\)](#)

This parameter is provided for concurrency control purposes. You must specify the latest association version in the service. If you want to ensure that this request succeeds, either specify `$LATEST`, or omit this parameter.

Type: String

Pattern: `([$]LATEST)|([1-9][0-9]*)`

Required: No

[AutomationTargetParameterName \(p. 504\)](#)

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a capability of AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

[CalendarNames \(p. 504\)](#)

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents you want to gate your associations under. The associations only run when that change calendar is open. For more information, see [AWS Systems Manager Change Calendar](#).

Type: Array of strings

Required: No

[ComplianceSeverity \(p. 504\)](#)

The severity level to assign to the association.

Type: String

Valid Values: `CRITICAL` | `HIGH` | `MEDIUM` | `LOW` | `UNSPECIFIED`

Required: No

[DocumentVersion \(p. 504\)](#)

The document version you want update for the association.

Important

State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs the default version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared from another account, you must set the document version to default.

Type: String

Pattern: `([$]LATEST|[$]DEFAULT|^([1-9][0-9]*$)`

Required: No

[MaxConcurrency \(p. 504\)](#)

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running MaxConcurrency associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for MaxConcurrency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%)\$

Required: No

[MaxErrors \(p. 504\)](#)

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9] %| [0-9] %| 100%)\$

Required: No

[Name \(p. 504\)](#)

The name of the SSM Command document or Automation runbook that contains the configuration information for the managed node.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another account.

For Systems Manager document (SSM document) that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:aws:ssm:region:account-id:document/document-name`

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.:/]{3,128}\$

Required: No

[OutputLocation \(p. 504\)](#)

An S3 bucket where you want to store the results of this request.

Type: [InstanceAssociationOutputLocation \(p. 680\)](#) object

Required: No

[Parameters \(p. 504\)](#)

The parameters you want to update for the association. If you create a parameter using Parameter Store, a capability of AWS Systems Manager, you can reference the parameter using `{ssm:parameter-name}`.

Type: String to array of strings map

Required: No

[ScheduleExpression \(p. 504\)](#)

The cron expression used to schedule the association that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

[ScheduleOffset \(p. 504\)](#)

Number of days to wait after the scheduled day to run an association. For example, if you specified a cron schedule of `cron(0 0 ? * THU#2 *)`, you could specify an offset of 3 to run the association each Sunday after the second Thursday of the month. For more information about cron schedules for associations, see [Reference: Cron and rate expressions for Systems Manager](#) in the *AWS Systems Manager User Guide*.

Note

To use offsets, you must specify the `ApplyOnlyAtCronInterval` parameter. This option tells the system not to run an association immediately after you create it.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

[SyncCompliance \(p. 504\)](#)

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is `COMPLIANT`. If the association execution doesn't run successfully, the association is `NON-COMPLIANT`.

In `MANUAL` mode, you must specify the `AssociationId` as a parameter for the [PutComplianceItems \(p. 422\)](#) API operation. In this case, compliance data isn't managed by State Manager, a capability of AWS Systems Manager. It is managed by your direct call to the [PutComplianceItems \(p. 422\)](#) API operation.

By default, all associations use `AUTO` mode.

Type: String

Valid Values: `AUTO` | `MANUAL`

Required: No

[TargetLocations \(p. 504\)](#)

A location is a combination of AWS Regions and AWS accounts where you want to run the association. Use this action to update an association in multiple Regions and multiple accounts.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

[TargetMaps \(p. 504\)](#)

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

[Targets \(p. 504\)](#)

The targets of the association.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

Response Syntax

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": boolean,
        "AssociationId": "string",
        "AssociationName": "string",
        "AssociationVersion": "string",
        "AutomationTargetParameterName": "string",
        "CalendarNames": [ "string" ],
        "ComplianceSeverity": "string",
        "Date": number,
        "DocumentVersion": "string",
        "InstanceId": "string",
        "LastExecutionDate": number,
        "LastSuccessfulExecutionDate": number,
        "LastUpdateAssociationDate": number,
        "MaxConcurrency": "string",
        "MaxErrors": "string",
        "Name": "string",
        "OutputLocation": {
            "S3Location": {
                "OutputS3BucketName": "string",
                "OutputS3KeyPrefix": "string",
                "OutputS3Region": "string"
            }
        },
    },
}
```

```
"Overview": {
    "AssociationStatusAggregatedCount": {
        "string" : number
    },
    "DetailedStatus": "string",
    "Status": "string"
},
"Parameters": {
    "string" : [ "string" ]
},
"ScheduleExpression": "string",
"ScheduleOffset": number,
"Status": {
    "AdditionalInfo": "string",
    "Date": number,
    "Message": "string",
    "Name": "string"
},
"SyncCompliance": "string",
"TargetLocations": [
    {
        "Accounts": [ "string" ],
        "ExecutionRoleName": "string",
        "Regions": [ "string" ],
        "TargetLocationMaxConcurrency": "string",
        "TargetLocationMaxErrors": "string"
    }
],
"TargetMaps": [
    {
        "string" : [ "string" ]
    }
],
"Targets": [
    {
        "Key": "string",
        "Values": [ "string" ]
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AssociationDescription \(p. 509\)](#)

The description of the association that was updated.

Type: [AssociationDescription \(p. 588\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

AssociationVersionLimitExceeded

You have reached the maximum number versions allowed for an association. Each association has a limit of 1,000 versions.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidAssociationVersion

The version you specified isn't valid. Use `ListAssociationVersions` to view all versions of an association according to the association ID. Or, use the `$LATEST` parameter to view the latest version of the association.

HTTP Status Code: 400

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidOutputLocation

The output location isn't valid or doesn't exist.

HTTP Status Code: 400

InvalidParameters

You must specify values for all required parameters in the AWS Systems Manager document (SSM document). You can only supply values to parameters defined in the SSM document.

HTTP Status Code: 400

InvalidSchedule

The schedule is invalid. Verify your cron or rate expression and try again.

HTTP Status Code: 400

InvalidTarget

The target isn't valid or doesn't exist. It might not be configured for Systems Manager or you might not have permission to perform the operation.

HTTP Status Code: 400

InvalidTargetMaps

TargetMap parameter isn't valid.

HTTP Status Code: 400

InvalidUpdate

The update isn't valid.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateAssociation.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateAssociation
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T171857Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 87

{
    "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
    "ComplianceSeverity": "HIGH"
}
```

Sample Response

```
{
    "AssociationDescription": {
        "ApplyOnlyAtCronInterval": false,
        "AssociationId": "fa94c678-85c6-4d40-926b-7c791EXAMPLE",
        "AssociationVersion": "2",
        "ComplianceSeverity": "HIGH",
        "Date": 1561053271.583,
        "DocumentVersion": "$DEFAULT",
        "LastExecutionDate": 1582037438.692,
        "LastSuccessfulExecutionDate": 1582037438.692,
        "LastUpdateAssociationDate": 1585156739.103,
        "Name": "AWS-UpdateSSMAgent",
        "Overview": {
            "DetailedStatus": "Creating",
            "Status": "Pending"
        },
        "Targets": [
            {
                "Key": "tag:ssm",
                "Values": [
                    "true"
                ]
            }
        ]
    }
}
```

}

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAssociationStatus

Updates the status of the AWS Systems Manager document (SSM document) associated with the specified managed node.

`UpdateAssociationStatus` is primarily used by the AWS Systems Manager Agent (SSM Agent) to report status updates about your associations and is only used for associations created with the `InstanceId` legacy parameter.

Request Syntax

```
{  
    "AssociationStatus": {  
        "AdditionalInfo": "string",  
        "Date": number,  
        "Message": "string",  
        "Name": "string"  
    },  
    "InstanceId": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

AssociationStatus (p. 514)

The association status.

Type: [AssociationStatus \(p. 601\)](#) object

Required: Yes

InstanceId (p. 514)

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: Yes

Name (p. 514)

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.:/]{3,128}\$

Required: Yes

Response Syntax

```
{
  "AssociationDescription": {
    "ApplyOnlyAtCronInterval": boolean,
    "AssociationId": "string",
    "AssociationName": "string",
    "AssociationVersion": "string",
    "AutomationTargetParameterName": "string",
    "CalendarNames": [ "string" ],
    "ComplianceSeverity": "string",
    "Date": number,
    "DocumentVersion": "string",
    "InstanceId": "string",
    "LastExecutionDate": number,
    "LastSuccessfulExecutionDate": number,
    "LastUpdateAssociationDate": number,
    "MaxConcurrency": "string",
    "MaxErrors": "string",
    "Name": "string",
    "OutputLocation": {
      "S3Location": {
        "OutputS3BucketName": "string",
        "OutputS3KeyPrefix": "string",
        "OutputS3Region": "string"
      }
    },
    "Overview": {
      "AssociationStatusAggregatedCount": {
        "string" : number
      },
      "DetailedStatus": "string",
      "Status": "string"
    },
    "Parameters": {
      "string" : [ "string" ]
    },
    "ScheduleExpression": "string",
    "ScheduleOffset": number,
    "Status": {
      "AdditionalInfo": "string",
      "Date": number,
      "Message": "string",
      "Name": "string"
    },
    "SyncCompliance": "string",
    "TargetLocations": [
      {
        "Accounts": [ "string" ],
        "ExecutionRoleName": "string",
        "Regions": [ "string" ],
        "TargetLocationMaxConcurrency": "string",
        "TargetLocationMaxErrors": "string"
      }
    ],
    "TargetMaps": [
      {
        "string" : [ "string" ]
      }
    ],
    "Targets": [
      {
        "Key": "string",
        "Values": [ "string" ]
      }
    ]
  }
}
```

```
        }  
    ]  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AssociationDescription (p. 515)

Information about the association.

Type: [AssociationDescription \(p. 588\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

AssociationDoesNotExist

The specified association doesn't exist.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

StatusUnchanged

The updated status is the same as the current status.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDocument

Updates one or more values for an SSM document.

Request Syntax

```
{  
    "Attachments": [  
        {  
            "Key": "string",  
            "Name": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "Content": "string",  
    "DisplayName": "string",  
    "DocumentFormat": "string",  
    "DocumentVersion": "string",  
    "Name": "string",  
    "TargetType": "string",  
    "VersionName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Attachments (p. 518)

A list of key-value pairs that describe attachments to a version of a document.

Type: Array of [AttachmentsSource \(p. 609\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Content (p. 518)

A valid JSON or YAML string.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

DisplayName (p. 518)

The friendly name of the SSM document that you want to update. This value can differ for each version of the document. If you don't specify a value for this parameter in your request, the existing value is applied to the new document version.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/\]*\$

Required: No

[DocumentFormat \(p. 518\)](#)

Specify the document format for the new document version. Systems Manager supports JSON and YAML documents. JSON is the default format.

Type: String

Valid Values: YAML | JSON | TEXT

Required: No

[DocumentVersion \(p. 518\)](#)

The version of the document that you want to update. Currently, Systems Manager supports updating only the latest version of the document. You can specify the version number of the latest version or use the \$LATEST variable.

Note

If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specified the apply-only-at-cron-interval parameter.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[\d]{1-9}[\d]*\$)

Required: No

[Name \(p. 518\)](#)

The name of the SSM document that you want to update.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: Yes

[TargetType \(p. 518\)](#)

Specify a new target type for the document.

Type: String

Length Constraints: Maximum length of 200.

Pattern: ^\/[\w\.\-\:\:/\]*\$

Required: No

[VersionName \(p. 518\)](#)

An optional field specifying the version of the artifact you are updating with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{1,128}\$

Required: No

Response Syntax

```
{  
    "DocumentDescription": {  
        "ApprovedVersion": "string",  
        "AttachmentsInformation": [  
            {  
                "Name": "string"  
            }  
        ],  
        "Author": "string",  
        "Category": [ "string" ],  
        "CategoryEnum": [ "string" ],  
        "CreatedDate": number,  
        "DefaultVersion": "string",  
        "Description": "string",  
        "DisplayName": "string",  
        "DocumentFormat": "string",  
        "DocumentType": "string",  
        "DocumentVersion": "string",  
        "Hash": "string",  
        "HashType": "string",  
        "LatestVersion": "string",  
        "Name": "string",  
        "Owner": "string",  
        "Parameters": [  
            {  
                "DefaultValue": "string",  
                "Description": "string",  
                "Name": "string",  
                "Type": "string"  
            }  
        ],  
        "PendingReviewVersion": "string",  
        "PlatformTypes": [ "string" ],  
        "Requires": [  
            {  
                "Name": "string",  
                "Version": "string"  
            }  
        ],  
        "ReviewInformation": [  
            {  
                "ReviewedTime": number,  
                "Reviewer": "string",  
                "Status": "string"  
            }  
        ],  
        "ReviewStatus": "string",  
        "SchemaVersion": "string",  
        "Sha1": "string",  
        "Status": "string",  
        "StatusInformation": "string",  
        "Tags": [  
            {  
                "Key": "string",  
                "Value": "string"  
            }  
        ],  
    },  
}
```

```
    "TargetType": "string",
    "VersionName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DocumentDescription (p. 520)

A description of the document that was updated.

Type: [DocumentDescription \(p. 655\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DocumentVersionLimitExceeded

The document has too many versions. Delete one or more document versions and try again.

HTTP Status Code: 400

DuplicateDocumentContent

The content of the association document matches another document. Change the content of the document and try again.

HTTP Status Code: 400

DuplicateDocumentVersionName

The version name has already been used in this document. Specify a different version name, and then try again.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentContent

The content for the document isn't valid.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

MaxDocumentSizeExceeded

The size limit of a document is 64 KB.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `UpdateDocument`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocument
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T180432Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 953

{
    "Content": "---\ndescription: \"CreateImage\"\nschemaVersion: '0.3'\nassumeRole:
\"{{ AutomationAssumeRole }}\"--truncated--",
    "Name": "CreateImage",
    "DocumentVersion": "$LATEST",
    "DocumentFormat": "YAML"
}
```

Sample Response

```
{
    "DocumentDescription": {
        "CreatedDate": 1585159474.781,
        "DefaultVersion": "1",
        "Description": "Example",
        "DisplayName": "ExampleDoc",
        "DocumentFormat": "YAML",
        "DocumentType": "Automation",
        "DocumentVersion": "2",
        "Hash": "ff7430df11be00b0593ac116b2570d488bd37a2a2fa7ddf49da67976eEXAMPLE",
        "HashType": "Sha256",
```

```
"LatestVersion": "2",
"Name": "CreateImage",
"Owner": "111122223333",
"Parameters": [
    {
        "DefaultValue": "",
        "Description": "(Optional) The ARN of the role that allows Automation to
perform the actions on your behalf. If no role is specified, Systems Manager Automation
uses your IAM permissions to execute this document.",
        "Name": "AutomationAssumeRole",
        "Type": "String"
    },
    {
        "DefaultValue": "",
        "Description": "(Required) The Instance Id whose root EBS volume you want
to restore the latest Snapshot.",
        "Name": "InstanceId",
        "Type": "String"
    }
],
"PlatformTypes": [
    "Windows",
    "Linux"
],
"SchemaVersion": "0.3",
"Status": "Updating",
"Tags": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDocumentDefaultVersion

Set the default version of a document.

Note

If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specified the `apply-only-at-cron-interval` parameter.

Request Syntax

```
{  
    "DocumentVersion": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

DocumentVersion (p. 524)

The version of a custom document that you want to set as the default version.

Type: String

Pattern: `(^[1-9][0-9]*$)`

Required: Yes

Name (p. 524)

The name of a custom document that you want to set as the default version.

Type: String

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: Yes

Response Syntax

```
{  
    "Description": {  
        "DefaultVersion": "string",  
        "DefaultVersionName": "string",  
        "Name": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description (p. 524)

The description of a custom document that you want to set as the default version.

Type: [DocumentDefaultVersionDescription \(p. 654\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentSchemaVersion

The version of the document schema isn't supported.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateDocumentDefaultVersion.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocumentDefaultVersion
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T183926Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 47

{
    "Name": "Example",
    "DocumentVersion": "2"
```

```
}
```

Sample Response

```
{  
    "Description": {  
        "DefaultVersion": "2",  
        "Name": "Example"  
    }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDocumentMetadata

Updates information related to approval reviews for a specific version of a change template in Change Manager.

Request Syntax

```
{  
    "DocumentReviews": {  
        "Action": "string",  
        "Comment": [  
            {  
                "Content": "string",  
                "Type": "string"  
            }  
        ]  
    },  
    "DocumentVersion": "string",  
    "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[DocumentReviews \(p. 527\)](#)

The change template review details to update.

Type: [DocumentReviews \(p. 672\)](#) object

Required: Yes

[DocumentVersion \(p. 527\)](#)

The version of a change template in which to update approval metadata.

Type: String

Pattern: (`[$]LATEST` | `[$]DEFAULT` | `^[1-9][0-9]*$`)

Required: No

[Name \(p. 527\)](#)

The name of the change template for which a version's metadata is to be updated.

Type: String

Pattern: `^[a-zA-Z0-9\-_]{3,128}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidDocument

The specified SSM document doesn't exist.

HTTP Status Code: 400

InvalidDocumentOperation

You attempted to delete a document while it is still shared. You must stop sharing the document before you can delete it.

HTTP Status Code: 400

InvalidDocumentVersion

The document version isn't valid or doesn't exist.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `UpdateDocumentMetadata`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateDocumentMetadata
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20210730T154930Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20210730/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 68

{
    "DocumentReviews": [
        {
            "Action": "Approve",
            "Comment": [
                {
                    "Type": "Comment",
                    "Content": "Approved!"
                }
            ]
        }
    ]
}
```

```
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMaintenanceWindow

Updates an existing maintenance window. Only specified parameters are modified.

Note

The value you specify for `Duration` determines the specific end time for the maintenance window based on the time it begins. No maintenance window tasks are permitted to start after the resulting endtime minus the number of hours you specify for `Cutoff`. For example, if the maintenance window starts at 3 PM, the duration is three hours, and the value you specify for `Cutoff` is one hour, no maintenance window tasks can start after 5 PM.

Request Syntax

```
{  
    "AllowUnassociatedTargets": boolean,  
    "Cutoff": number,  
    "Description": string,  
    "Duration": number,  
    "Enabled": boolean,  
    "EndDate": string,  
    "Name": string,  
    "Replace": boolean,  
    "Schedule": string,  
    "ScheduleOffset": number,  
    "ScheduleTimezone": string,  
    "StartDate": string,  
    "WindowId": string  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[AllowUnassociatedTargets \(p. 530\)](#)

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

Required: No

[Cutoff \(p. 530\)](#)

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: No

[Description \(p. 530\)](#)

An optional description for the update request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[Duration \(p. 530\)](#)

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

[Enabled \(p. 530\)](#)

Whether the maintenance window is enabled.

Type: Boolean

Required: No

[EndDate \(p. 530\)](#)

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become inactive. EndDate allows you to set a date and time in the future when the maintenance window will no longer run.

Type: String

Required: No

[Name \(p. 530\)](#)

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\.]{3,128}\$

Required: No

[Replace \(p. 530\)](#)

If True, then all fields that are required by the [CreateMaintenanceWindow \(p. 47\)](#) operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

[Schedule \(p. 530\)](#)

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset (p. 530)

The number of days to wait after the date and time specified by a cron expression before running the maintenance window.

For example, the following cron expression schedules a maintenance window to run the third Tuesday of every month at 11:30 PM.

```
cron(30 23 ? * TUE#3 *)
```

If the schedule offset is 2, the maintenance window won't run until two days later.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

ScheduleTimezone (p. 530)

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the [Time Zone Database](#) on the IANA website.

Type: String

Required: No

StartDate (p. 530)

The date and time, in ISO-8601 Extended format, for when you want the maintenance window to become active. `StartDate` allows you to delay activation of the maintenance window until the specified future date.

Type: String

Required: No

WindowId (p. 530)

The ID of the maintenance window to update.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

Response Syntax

```
{  
    "AllowUnassociatedTargets": boolean,  
    "Cutoff": number,  
    "Description": string,  
    "Duration": number,  
    "Enabled": boolean,  
    "EndDate": string,  
    "Name": string,  
    "Schedule": string,  
}
```

```
"ScheduleOffset": number,  
"ScheduleTimezone": "string",  
"StartDate": "string",  
"WindowId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AllowUnassociatedTargets \(p. 532\)](#)

Whether targets must be registered with the maintenance window before tasks can be defined for those targets.

Type: Boolean

[Cutoff \(p. 532\)](#)

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

[Description \(p. 532\)](#)

An optional description of the update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[Duration \(p. 532\)](#)

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

[Enabled \(p. 532\)](#)

Whether the maintenance window is enabled.

Type: Boolean

[EndDate \(p. 532\)](#)

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive. The maintenance window won't run after this specified time.

Type: String

[Name \(p. 532\)](#)

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9\-_\.]{3,128}\$

Schedule (p. 532)

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ScheduleOffset (p. 532)

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

ScheduleTimezone (p. 532)

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format. For example: "America/Los_Angeles", "UTC", or "Asia/Seoul". For more information, see the [Time Zone Database](#) on the IANA website.

Type: String

StartDate (p. 532)

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active. The maintenance window won't run before this specified time.

Type: String

WindowId (p. 532)

The ID of the created maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the [Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of `UpdateMaintenanceWindow`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 160
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindow
X-Amz-Date: 20180312T203703Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180312/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "Duration": 10,
    "WindowId": "mw-0c50858d01EXAMPLE",
    "Name": "Default-Maintenance-Window",
    "Description": "Standard maintenance windows for production servers"
}
```

Sample Response

```
{
    "AllowUnassociatedTargets": true,
    "Cutoff": 4,
    "Description": "Standard maintenance windows for production servers",
    "Duration": 10,
    "Enabled": true,
    "Name": "Default-Maintenance-Window",
    "Schedule": "rate(3 minutes)",
    "WindowId": "mw-0c50858d01EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMaintenanceWindowTarget

Modifies the target of an existing maintenance window. You can change the following:

- Name
- Description
- Owner
- IDs for an ID target
- Tags for a Tag target
- From any supported tag type to another. The three supported tag types are ID target, Tag target, and resource group. For more information, see [Target \(p. 841\)](#).

Note

If a parameter is null, then the corresponding field isn't modified.

Request Syntax

```
{  
    "Description": "string",  
    "Name": "string",  
    "OwnerInformation": "string",  
    "Replace": boolean,  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "WindowId": "string",  
    "WindowTargetId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

Description (p. 536)

An optional description for the update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name (p. 536)

A name for the update.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: No

[OwnerInformation \(p. 536\)](#)

User-provided value that will be included in any Amazon CloudWatch Events events raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[Replace \(p. 536\)](#)

If True, then all fields that are required by the [RegisterTargetWithMaintenanceWindow \(p. 445\)](#) operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

[Targets \(p. 536\)](#)

The targets to add or replace.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[WindowId \(p. 536\)](#)

The maintenance window ID with which to modify the target.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

[WindowTargetId \(p. 536\)](#)

The target ID to modify.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
  "Description": "string",
```

```
"Name": "string",
"OwnerInformation": "string",
"Targets": [
    {
        "Key": "string",
        "Values": [ "string" ]
    }
],
"WindowId": "string",
"WindowTargetId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description (p. 537)

The updated description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Name (p. 537)

The updated name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

OwnerInformation (p. 537)

The updated owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Targets (p. 537)

The updated targets.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

WindowId (p. 537)

The maintenance window ID specified in the update request.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

WindowTargetId (p. 537)

The target ID specified in the update request.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdateMaintenanceWindowTarget.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindowTarget
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T005329Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 233

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "Name": "MyNewTaskName",
```

```
    "Description": "My new task description"
}
```

Sample Response

```
{
    "Description": "My new task description",
    "Name": "MyNewTaskName",
    "Targets": [
        {
            "Key": "InstanceIds",
            "Values": [
                "i-07782c72faEXAMPLE"
            ]
        }
    ],
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTargetId": "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMaintenanceWindowTask

Modifies a task assigned to a maintenance window. You can't change the task type, but you can change the following values:

- `TaskARN`. For example, you can change a `RUN_COMMAND` task from `AWS-RunPowerShellScript` to `AWS-RunShellScript`.
- `ServiceRoleArn`
- `TaskInvocationParameters`
- `Priority`
- `MaxConcurrency`
- `MaxErrors`

Note

One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see [Registering maintenance window tasks without targets](#) in the *AWS Systems Manager User Guide*.

If the value for a parameter in `UpdateMaintenanceWindowTask` is null, then the corresponding field isn't modified. If you set `Replace` to true, then all fields required by the [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) operation are required for this request. Optional fields that aren't specified are set to null.

Important

When you update a maintenance window task that has options specified in `TaskInvocationParameters`, you must provide again all the `TaskInvocationParameters` values that you want to retain. The values you don't specify again are removed. For example, suppose that when you registered a Run Command task, you specified `TaskInvocationParameters` values for `Comment`, `NotificationConfig`, and `OutputS3BucketName`. If you update the maintenance window task and specify only a different `OutputS3BucketName` value, the values for `Comment` and `NotificationConfig` are removed.

Request Syntax

```
{  
    "CutoffBehavior": "string",  
    "Description": "string",  
    "LoggingInfo": {  
        "S3BucketName": "string",  
        "S3KeyPrefix": "string",  
        "S3Region": "string"  
    },  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Name": "string",  
    "Priority": number,  
    "Replace": boolean,  
    "ServiceRoleArn": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ]  
}
```

```
],
"TaskArn": "string",
"TaskInvocationParameters": {
    "Automation": {
        "DocumentVersion": "string",
        "Parameters": {
            "string" : [ "string" ]
        }
    },
    "Lambda": {
        "ClientContext": "string",
        "Payload": blob,
        "Qualifier": "string"
    },
    "RunCommand": {
        "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
        },
        "Comment": "string",
        "DocumentHash": "string",
        "DocumentHashType": "string",
        "DocumentVersion": "string",
        "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
        },
        "OutputS3BucketName": "string",
        "OutputS3KeyPrefix": "string",
        "Parameters": {
            "string" : [ "string" ]
        },
        "ServiceRoleArn": "string",
        "TimeoutSeconds": number
    },
    "StepFunctions": {
        "Input": "string",
        "Name": "string"
    }
},
"TaskParameters": {
    "string" : {
        "Values": [ "string" ]
    }
},
"WindowId": "string",
"WindowTaskId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

CutoffBehavior (p. 541)

Indicates whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

- CONTINUE_TASK: When the cutoff time is reached, any tasks that are running continue. The default value.

- `CANCEL_TASK`:
 - For Automation, AWS Lambda, AWS Step Functions tasks: When the cutoff time is reached, any task invocations that are already running continue, but no new task invocations are started.
 - For Run Command tasks: When the cutoff time is reached, the system sends a [CancelCommand \(p. 13\)](#) operation that attempts to cancel the command associated with the task. However, there is no guarantee that the command will be terminated and the underlying process stopped.

The status for tasks that are not completed is `TIMED_OUT`.

Type: String

Valid Values: `CONTINUE_TASK` | `CANCEL_TASK`

Required: No

[Description \(p. 541\)](#)

The new task description to specify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

[LoggingInfo \(p. 541\)](#)

The new logging location in Amazon S3 to specify.

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: [LoggingInfo \(p. 712\)](#) object

Required: No

[MaxConcurrency \(p. 541\)](#)

The new `MaxConcurrency` value you want to specify. `MaxConcurrency` is the number of targets that are allowed to run this task, in parallel.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)$`

Required: No

[MaxErrors \(p. 541\)](#)

The new `MaxErrors` value to specify. `MaxErrors` is the maximum number of errors that are allowed before the task stops being scheduled.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%^|100%)$`

Required: No

[Name \(p. 541\)](#)

The new task name to specify.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

Required: No

[Priority \(p. 541\)](#)

The new task priority to specify. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

[Replace \(p. 541\)](#)

If True, then all fields that are required by the [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

[ServiceRoleArn \(p. 541\)](#)

The Amazon Resource Name (ARN) of the IAM service role for AWS Systems Manager to assume when running a maintenance window task. If you do not specify a service role ARN, Systems Manager uses your account's service-linked role. If no service-linked role for Systems Manager exists in your account, it is created when you run `RegisterTaskWithMaintenanceWindow`.

For more information, see the following topics in the [AWS Systems Manager User Guide](#):

- [Using service-linked roles for Systems Manager](#)
- [Should I use a service-linked role or a custom service role to run maintenance window tasks?](#)

Type: String

Required: No

[Targets \(p. 541\)](#)

The targets (either managed nodes or tags) to modify. Managed nodes are specified using the format `Key=instanceids,Values=instanceID_1,instanceID_2`. Tags are specified using the format `Key>tag_name,Values>tag_value`.

Note

One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see [Registering maintenance window tasks without targets](#) in the *AWS Systems Manager User Guide*.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[TaskArn \(p. 541\)](#)

The task ARN to modify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

[TaskInvocationParameters \(p. 541\)](#)

The parameters that the task should use during execution. Populate only the fields that match the task type. All other fields should be empty.

Important

When you update a maintenance window task that has options specified in `TaskInvocationParameters`, you must provide again all the `TaskInvocationParameters` values that you want to retain. The values you don't specify again are removed. For example, suppose that when you registered a Run Command task, you specified `TaskInvocationParameters` values for `Comment`, `NotificationConfig`, and `OutputS3BucketName`. If you update the maintenance window task and specify only a different `OutputS3BucketName` value, the values for `Comment` and `NotificationConfig` are removed.

Type: [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#) object

Required: No

[TaskParameters \(p. 541\)](#)

The parameters to modify.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

The map has the following format:

Key: string, between 1 and 255 characters

Value: an array of strings, each string is between 1 and 255 characters

Type: String to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

[WindowId \(p. 541\)](#)

The maintenance window ID that contains the task to modify.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: Yes

[WindowTaskId \(p. 541\)](#)

The task ID to modify.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}\$

Required: Yes

Response Syntax

```
{  
    "CutoffBehavior": "string",  
    "Description": "string",  
    "LoggingInfo": {  
        "S3BucketName": "string",  
        "S3KeyPrefix": "string",  
        "S3Region": "string"  
    },  
    "MaxConcurrency": "string",  
    "MaxErrors": "string",  
    "Name": "string",  
    "Priority": number,  
    "ServiceRoleArn": "string",  
    "Targets": [  
        {  
            "Key": "string",  
            "Values": [ "string" ]  
        }  
    ],  
    "TaskArn": "string",  
    "TaskInvocationParameters": {  
        "Automation": {  
            "DocumentVersion": "string",  
            "Parameters": {  
                "string" : [ "string" ]  
            }  
        },  
    },  
}
```

```

    "Lambda": {
        "ClientContext": "string",
        "Payload": blob,
        "Qualifier": "string"
    },
    "RunCommand": {
        "CloudWatchOutputConfig": {
            "CloudWatchLogGroupName": "string",
            "CloudWatchOutputEnabled": boolean
        },
        "Comment": "string",
        "DocumentHash": "string",
        "DocumentHashType": "string",
        "DocumentVersion": "string",
        "NotificationConfig": {
            "NotificationArn": "string",
            "NotificationEvents": [ "string" ],
            "NotificationType": "string"
        },
        "OutputS3BucketName": "string",
        "OutputS3KeyPrefix": "string",
        "Parameters": {
            "string" : [ "string" ]
        },
        "ServiceRoleArn": "string",
        "TimeoutSeconds": number
    },
    "StepFunctions": {
        "Input": "string",
        "Name": "string"
    }
},
"TaskParameters": {
    "string" : {
        "Values": [ "string" ]
    }
},
"WindowId": "string",
"WindowTaskId": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[CutoffBehavior \(p. 546\)](#)

The specification for whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

Type: String

Valid Values: CONTINUE_TASK | CANCEL_TASK

[Description \(p. 546\)](#)

The updated task description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[LoggingInfo \(p. 546\)](#)

The updated logging information in Amazon S3.

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: [LoggingInfo \(p. 712\)](#) object

[MaxConcurrency \(p. 546\)](#)

The updated `MaxConcurrency` value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)$`

[MaxErrors \(p. 546\)](#)

The updated `MaxErrors` value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]|100%)$`

[Name \(p. 546\)](#)

The updated task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `^[a-zA-Z0-9_\-.]{3,128}$`

[Priority \(p. 546\)](#)

The updated priority value.

Type: Integer

Valid Range: Minimum value of 0.

[ServiceRoleArn \(p. 546\)](#)

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for maintenance window Run Command tasks.

Type: String

[Targets \(p. 546\)](#)

The updated target values.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

[TaskArn \(p. 546\)](#)

The updated task ARN value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

[TaskInvocationParameters \(p. 546\)](#)

The updated parameter values.

Type: [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#) object

[TaskParameters \(p. 546\)](#)

The updated parameter values.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: String to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

[WindowId \(p. 546\)](#)

The ID of the maintenance window that was updated.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

[WindowTaskId \(p. 546\)](#)

The task ID of the maintenance window that was updated.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas](#) in the *Amazon Web Services General Reference*.

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdateMaintenanceWindowTask.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateMaintenanceWindowTask
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/2.0.0 Python/3.7.5 Windows/10 botocore/2.0.0dev4
X-Amz-Date: 20200225T010531Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200225/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 244

{
    "WindowId": "mw-0c50858d01EXAMPLE",
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE",
    "Priority": 2,
    "MaxConcurrency": "10",
    "MaxErrors": "3",
    "Name": "MyRevisedMaintenanceWindowTask",
    "Description": "My updated maintenance window task",
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/ssm.amazonaws.com/
MyCustomMaintenanceWindowTaskRole"
}
```

Sample Response

```
{
    "Description": "My updated maintenance window task",
    "MaxConcurrency": "10",
    "MaxErrors": "3",
    "Name": "MyRevisedMaintenanceWindowTask",
    "Priority": 2,
    "ServiceRoleArn": "arn:aws:iam::111122223333:role/aws-service-role/ssm.amazonaws.com/
MyCustomMaintenanceWindowTaskRole",
    "Targets": [
        {
            "Key": "WindowTargetIds",
            "Values": [
                "23639a0b-ddbc-4bca-9e72-78d96EXAMPLE"
            ]
        }
    ],
    "TaskArn": "AWS-ApplyPatchBaseline",
    "TaskInvocationParameters": {
        "RunCommand": {
            "Comment": ""
        }
    }
}
```

```
"Parameters": {  
    "Operation": [  
        "Install"  
    ],  
    "SnapshotId": [  
        ""  
    ]  
},  
    "TimeoutSeconds": 600  
},  
    "TaskParameters": {},  
    "WindowId": "mw-0c50858d01EXAMPLE",  
    "WindowTaskId": "50772993-c6b5-4a2a-8d04-7bfd7EXAMPLE"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateManagedInstanceId

Changes the AWS Identity and Access Management (IAM) role that is assigned to the on-premises server, edge device, or virtual machines (VM). IAM roles are first assigned to these hybrid nodes during the activation process. For more information, see [CreateActivation \(p. 19\)](#).

Request Syntax

```
{  
    "IamRole": "string",  
    "InstanceId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

IamRole (p. 552)

The IAM role you want to assign or change.

Type: String

Length Constraints: Maximum length of 64.

Required: Yes

InstanceId (p. 552)

The ID of the managed node where you want to update the role.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 124.

Pattern: (^mi-[0-9a-f]{17}\$)|(^eks_c:[0-9A-Za-z][A-Za-z0-9\-_]{0,99}\w{17}\$)

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

InvalidInstanceId

The following problems can cause this exception:

- You don't have permission to access the managed node.
- AWS Systems Manager Agent(SSM Agent) isn't running. Verify that SSM Agent is running.
- SSM Agent isn't registered with the SSM endpoint. Try reinstalling SSM Agent.
- The managed node isn't in valid state. Valid states are: Running, Pending, Stopped, and Stopping. Invalid states are: Shutting-down and Terminated.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateManagedInstanceRole.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateManagedInstanceRole
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T191724Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 56

{
    "InstanceId": "mi-0ce084dd39EXAMPLE",
    "IamRole": "SSM"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UpdateOpsItem

Edit or change an OpsItem. You must have permission in AWS Identity and Access Management (IAM) to update an OpsItem. For more information, see [Getting started with OpsCenter](#) in the *AWS Systems Manager User Guide*.

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational issues impacting the performance and health of their AWS resources. For more information, see [OpsCenter](#) in the *AWS Systems Manager User Guide*.

Request Syntax

```
{  
    "ActualEndTime": number,  
    "ActualStartTime": number,  
    "Category": "string",  
    "Description": "string",  
    "Notifications": [  
        {  
            "Arn": "string"  
        }  
    ],  
    "OperationalData": {  
        "string": {  
            "Type": "string",  
            "Value": "string"  
        }  
    },  
    "OperationalDataToDelete": [ "string" ],  
    "OpsItemId": "string",  
    "PlannedEndTime": number,  
    "PlannedStartTime": number,  
    "Priority": number,  
    "RelatedOpsItems": [  
        {  
            "OpsItemId": "string"  
        }  
    ],  
    "Severity": "string",  
    "Status": "string",  
    "Title": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

ActualEndTime (p. 555)

The time a runbook workflow ended. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[ActualStartTime \(p. 555\)](#)

The time a runbook workflow started. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[Category \(p. 555\)](#)

Specify a new category for an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^(?!\\s*\$).+

Required: No

[Description \(p. 555\)](#)

Update the information about the OpsItem. Provide enough information so that users reading this OpsItem for the first time understand the issue.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\\s\\S]*\\S[\\s\\S]*

Required: No

[Notifications \(p. 555\)](#)

The Amazon Resource Name (ARN) of an SNS topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of [OpsItemNotification \(p. 759\)](#) objects

Required: No

[OperationalData \(p. 555\)](#)

Add new keys or edit existing key-value pairs of the OperationalData map in the OpsItem object.

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

Important

Operational data keys *can't* begin with the following: amazon, aws, amzn, ssm, /amazon, /aws, /amzn, /ssm.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the [DescribeOpsItems \(p. 213\)](#) API operation) can view and search on the specified data. Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the [GetOpsItem \(p. 311\)](#) API operation).

Use the /aws/resources key in OperationalData to specify a related resource in the request. Use the /aws/automations key in OperationalData to associate an Automation runbook with the

OpsItem. To view AWS CLI example commands that use these keys, see [Creating OpsItems manually in the AWS Systems Manager User Guide](#).

Type: String to [OpsItemDataValue \(p. 753\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\\s*$).+`

Required: No

[OperationalDataToDelete \(p. 555\)](#)

Keys that you want to remove from the OperationalData map.

Type: Array of strings

Required: No

[OpsItemId \(p. 555\)](#)

The ID of the OpsItem.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

[PlannedEndTime \(p. 555\)](#)

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[PlannedStartTime \(p. 555\)](#)

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

[Priority \(p. 555\)](#)

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

[RelatedOpsItems \(p. 555\)](#)

One or more OpsItems that share something in common with the current OpsItems. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of [RelatedOpsItem \(p. 804\)](#) objects

Required: No

[Severity \(p. 555\)](#)

Specify a new severity for an OpsItem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\\s*$).+`

Required: No

[Status \(p. 555\)](#)

The OpsItem status. Status can be Open, In Progress, or Resolved. For more information, see [Editing OpsItem details](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Rejected | Closed

Required: No

[Title \(p. 555\)](#)

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsItemAlreadyExistsException

The OpsItem already exists.

HTTP Status Code: 400

OpsItemInvalidParameterException

A specified parameter argument isn't valid. Verify the available arguments and try again.

HTTP Status Code: 400

OpsItemLimitExceeded

The request caused OpsItems to exceed one or more quotas. For information about OpsItem quotas, see [What are the resource limits for OpsCenter?](#).

HTTP Status Code: 400

OpsItemNotFoundException

The specified OpsItem ID doesn't exist. Verify the ID and try again.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateOpsItem.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateOpsItem
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200401T184738Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200401/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 54

{
    "Status": "Resolved",
    "OpsItemId": "oi-1f050EXAMPLE"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UpdateOpsMetadata

AWS Systems Manager calls this API operation when you edit OpsMetadata in Application Manager.

Request Syntax

```
{  
    "KeysToDelete": [ "string" ],  
    "MetadataToUpdate": {  
        "string" : {  
            "Value": "string"  
        }  
    },  
    "OpsMetadataArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[KeysToDelete \(p. 561\)](#)

The metadata keys to delete from the OpsMetadata object.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^(?!\\s*\$).+

Required: No

[MetadataToUpdate \(p. 561\)](#)

Metadata to add to an OpsMetadata object.

Type: String to [MetadataValue \(p. 741\)](#) object map

Map Entries: Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: ^(?!\\s*\$).+

Required: No

[OpsMetadataArn \(p. 561\)](#)

The Amazon Resource Name (ARN) of the OpsMetadata Object to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/(a-zA-Z0-9-_\.\/]*)

Required: Yes

Response Syntax

```
{  
    "OpsMetadataArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[OpsMetadataArn \(p. 562\)](#)

The Amazon Resource Name (ARN) of the OpsMetadata Object that was updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

OpsMetadataInvalidArgumentException

One of the arguments passed is invalid.

HTTP Status Code: 400

OpsMetadataKeyLimitExceededException

The OpsMetadata object exceeds the maximum number of OpsMetadata keys that you can assign to an application in Application Manager.

HTTP Status Code: 400

OpsMetadataNotFoundException

The OpsMetadata object doesn't exist.

HTTP Status Code: 400

OpsMetadataTooManyUpdatesException

The system is processing too many concurrent updates. Wait a few moments and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePatchBaseline

Modifies an existing patch baseline. Fields not specified in the request are left unchanged.

Note

For information about valid key-value pairs in `PatchFilters` for each supported operating system type, see [PatchFilter \(p. 790\)](#).

Request Syntax

```
{  
    "ApprovalRules": {  
        "PatchRules": [  
            {  
                "ApproveAfterDays": number,  
                "ApproveUntilDate": "string",  
                "ComplianceLevel": "string",  
                "EnableNonSecurity": boolean,  
                "PatchFilterGroup": {  
                    "PatchFilters": [  
                        {  
                            "Key": "string",  
                            "Values": [ "string" ]  
                        }  
                    ]  
                }  
            }  
        ]  
    },  
    "ApprovedPatches": [ "string" ],  
    "ApprovedPatchesComplianceLevel": "string",  
    "ApprovedPatchesEnableNonSecurity": boolean,  
    "BaselineId": "string",  
    "Description": "string",  
    "GlobalFilters": {  
        "PatchFilters": [  
            {  
                "Key": "string",  
                "Values": [ "string" ]  
            }  
        ]  
    },  
    "Name": "string",  
    "RejectedPatches": [ "string" ],  
    "RejectedPatchesAction": "string",  
    "Replace": boolean,  
    "Sources": [  
        {  
            "Configuration": "string",  
            "Name": "string",  
            "Products": [ "string" ]  
        }  
    ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[ApprovalRules \(p. 564\)](#)

A set of rules used to include patches in the baseline.

Type: [PatchRuleGroup \(p. 797\)](#) object

Required: No

[ApprovedPatches \(p. 564\)](#)

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[ApprovedPatchesComplianceLevel \(p. 564\)](#)

Assigns a new compliance severity level to an existing patch baseline.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

[ApprovedPatchesEnableNonSecurity \(p. 564\)](#)

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

[BaselineId \(p. 564\)](#)

The ID of the patch baseline to update.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Required: Yes

[Description \(p. 564\)](#)

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

[GlobalFilters \(p. 564\)](#)

A set of global filters used to include patches in the baseline.

Type: [PatchFilterGroup \(p. 792\)](#) object

Required: No

[Name \(p. 564\)](#)

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

[RejectedPatches \(p. 564\)](#)

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

[RejectedPatchesAction \(p. 564\)](#)

The action for Patch Manager to take on patches included in the `RejectedPatches` list.

- **ALLOW_AS_DEPENDENCY** : A package in the `Rejected patches` list is installed only if it is a dependency of another package. It is considered compliant with the patch baseline, and its status is reported as `InstalledOther`. This is the default action if no option is specified.
- **BLOCK** : Packages in the `RejectedPatches` list, and packages that include them as dependencies, aren't installed under any circumstances. If a package was installed before it was added to the `Rejected patches` list, it is considered non-compliant with the patch baseline, and its status is reported as `InstalledRejected`.

Type: String

Valid Values: `ALLOW_AS_DEPENDENCY` | `BLOCK`

Required: No

[Replace \(p. 564\)](#)

If True, then all fields that are required by the [CreatePatchBaseline \(p. 61\)](#) operation are also required for this API request. Optional fields that aren't specified are set to null.

Type: Boolean

Required: No

[Sources \(p. 564\)](#)

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of [PatchSource \(p. 798\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Response Syntax

```
{  
    "ApprovalRules": {  
        "PatchRules": [  
            {  
                "ApproveAfterDays": number,  
                "ApproveUntilDate": "string",  
                "ComplianceLevel": "string",  
                "EnableNonSecurity": boolean,  
                "PatchFilterGroup": {  
                    "PatchFilters": [  
                        {  
                            "Key": "string",  
                            "Values": [ "string" ]  
                        }  
                    ]  
                }  
            }  
        ],  
        "ApprovedPatches": [ "string" ],  
        "ApprovedPatchesComplianceLevel": "string",  
        "ApprovedPatchesEnableNonSecurity": boolean,  
        "BaselineId": "string",  
        "CreatedDate": number,  
        "Description": "string",  
        "GlobalFilters": {  
            "PatchFilters": [  
                {  
                    "Key": "string",  
                    "Values": [ "string" ]  
                }  
            ]  
        },  
        "ModifiedDate": number,  
        "Name": "string",  
        "OperatingSystem": "string",  
        "RejectedPatches": [ "string" ],  
        "RejectedPatchesAction": "string",  
        "Sources": [  
            {  
                "Configuration": "string",  
                "Name": "string",  
                "Products": [ "string" ]  
            }  
        ]  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApprovalRules \(p. 567\)](#)

A set of rules used to include patches in the baseline.

Type: [PatchRuleGroup \(p. 797\)](#) object

[ApprovedPatches \(p. 567\)](#)

A list of explicitly approved patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

[ApprovedPatchesComplianceLevel \(p. 567\)](#)

The compliance severity level assigned to the patch baseline after the update completed.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

[ApprovedPatchesEnableNonSecurity \(p. 567\)](#)

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

[BaselineId \(p. 567\)](#)

The ID of the deleted patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9\-_\.:/]{20,128}\$

[CreatedDate \(p. 567\)](#)

The date when the patch baseline was created.

Type: Timestamp

[Description \(p. 567\)](#)

A description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

[GlobalFilters \(p. 567\)](#)

A set of global filters used to exclude patches from the baseline.

Type: [PatchFilterGroup \(p. 792\)](#) object

[ModifiedDate \(p. 567\)](#)

The date when the patch baseline was last modified.

Type: Timestamp

[Name \(p. 567\)](#)

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

[OperatingSystem \(p. 567\)](#)

The operating system rule used by the updated patch baseline.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

[RejectedPatches \(p. 567\)](#)

A list of explicitly rejected patches for the baseline.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

[RejectedPatchesAction \(p. 567\)](#)

The action specified to take on patches included in the `RejectedPatches` list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: ALLOW_AS_DEPENDENCY | BLOCK

[Sources \(p. 567\)](#)

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of [PatchSource \(p. 798\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

DoesNotExistException

Error returned when the ID specified for a resource, such as a maintenance window or patch baseline, doesn't exist.

For information about resource quotas in AWS Systems Manager, see [Systems Manager service quotas in the Amazon Web Services General Reference](#).

HTTP Status Code: 400

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

Examples

Example

This example illustrates one usage of UpdatePatchBaseline.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 306
X-Amz-Target: AmazonSSM.UpdatePatchBaseline
X-Amz-Date: 20180309T023346Z
User-Agent: aws-cli/1.11.180 Python/2.7.9 Windows/8 botocore/1.7.38
Content-Type: application/x-amz-json-1.1
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20180309/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE

{
    "ApprovalRules": {
        "PatchRules": [
            {
                "PatchFilterGroup": {
                    "PatchFilters": [
                        {
                            "Values": [
                                "Critical",
                                "Important"
                            ],
                            "Key": "MSRC_SEVERITY"
                        },
                        {
                            "Values": [
                                "SecurityUpdates",
                                "Updates",
                                "UpdateRollups",
                                "CriticalUpdates"
                            ],
                            "Key": "CLASSIFICATION"
                        }
                    ]
                },
                "ApproveAfterDays": 3
            }
        ],
        "BaselineId": "pb-0c10e65780EXAMPLE"
    }
}
```

Sample Response

```
{
    "ApprovalRules": {
        "PatchRules": [
            {
                "ApproveAfterDays": 3,
```

```
"ComplianceLevel": "UNSPECIFIED",
"EnableNonSecurity": false,
"PatchFilterGroup": [
    "PatchFilters": [
        {
            "Key": "MSRC_SEVERITY",
            "Values": [
                "Critical",
                "Important"
            ]
        },
        {
            "Key": "CLASSIFICATION",
            "Values": [
                "SecurityUpdates",
                "Updates",
                "UpdateRollups",
                "CriticalUpdates"
            ]
        }
    ]
},
"ApprovedPatches": [],
"ApprovedPatchesComplianceLevel": "UNSPECIFIED",
"ApprovedPatchesEnableNonSecurity": false,
"BaselineId": "pb-0c10e65780EXAMPLE",
"Description": "Baseline containing all updates approved for production systems",
"GlobalFilters": {
    "PatchFilters": []
},
"CreatedDate": 1520562237.968,
"ModifiedDate": 1520562239.765,
"Name": "my-Windows-Server-patch-baseline",
"OperatingSystem": "WINDOWS",
"RejectedPatches": [],
"RejectedPatchesAction": "ALLOW_AS_DEPENDENCY",
"Sources": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateResourceDataSync

Update a resource data sync. After you create a resource data sync for a Region, you can't change the account options for that sync. For example, if you create a sync in the us-east-2 (Ohio) Region and you choose the `Include only the current account` option, you can't edit that sync later and choose the `Include all accounts from my AWS Organizations` configuration option. Instead, you must delete the first resource data sync, and create a new one.

Note

This API operation only supports a resource data sync that was created with a `SyncFromSource` `SyncType`.

Request Syntax

```
{  
    "SyncName": "string",  
    "SyncSource": {  
        "AwsOrganizationsSource": {  
            "OrganizationalUnits": [  
                {  
                    "OrganizationalUnitId": "string"  
                }  
            ],  
            "OrganizationSourceType": "string"  
        },  
        "EnableAllOpsDataSources": boolean,  
        "IncludeFutureRegions": boolean,  
        "SourceRegions": [ "string" ],  
        "SourceType": "string"  
    },  
    "SyncType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[SyncName \(p. 572\)](#)

The name of the resource data sync you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

[SyncSource \(p. 572\)](#)

Specify information about the data sources to synchronize.

Type: [ResourceDataSyncSource \(p. 815\)](#) object

Required: Yes

[SyncType \(p. 572\)](#)

The type of resource data sync. The supported `SyncType` is `SyncFromSource`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ResourceDataSyncConflictException

Another `UpdateResourceDataSync` request is being processed. Wait a few minutes and try again.

HTTP Status Code: 400

ResourceDataSyncInvalidConfigurationException

The specified sync configuration is invalid.

HTTP Status Code: 400

ResourceDataSyncNotFoundException

The specified sync name wasn't found.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of `UpdateResourceDataSync`.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateResourceDataSync
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200327T160454Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200327/us-east-2/ssm/
aws4_request,
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 161

{
```

```
"SyncName": "exampleSync",
"SyncType": "SyncFromSource",
"SyncSource": {
    "SourceType": "SingleAccountMultiRegions",
    "SourceRegions": [
        "us-east-2",
        "us-west-2"
    ]
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceSetting

ServiceSetting is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a SettingId object to a setting value. AWS services teams define the default value for a SettingId. You can't create a new SettingId, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the [GetServiceSetting \(p. 347\)](#) API operation to view the current value. Or, use the [ResetServiceSetting \(p. 461\)](#) to change the value back to the original value defined by the AWS service team.

Update the service setting for the account.

Request Syntax

```
{  
    "SettingId": "string",  
    "SettingValue": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 845\)](#).

The request accepts the following data in JSON format.

[SettingId \(p. 575\)](#)

The Amazon Resource Name (ARN) of the service setting to reset. For example, `arn:aws:ssm:us-east-1:111122223333:servicesetting/ssm/parameter-store/high-throughput-enabled`. The setting ID can be one of the following.

- `/ssm/automation/customer-script-log-destination`
- `/ssm/automation/customer-script-log-group-name`
- `/ssm/documents/console/public-sharing-permission`
- `/ssm/parameter-store/default-parameter-tier`
- `/ssm/parameter-store/high-throughput-enabled`
- `/ssm/managed-instance/activation-tier`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

[SettingValue \(p. 575\)](#)

The new value to specify for the service setting. The following list specifies the available values for each setting.

- `/ssm/parameter-store/default-parameter-tier`: Standard, Advanced, Intelligent-Tiering
- `/ssm/parameter-store/high-throughput-enabled`: true or false

- /ssm/managed-instance/activation-tier: true or false
- /ssm/automation/customer-script-log-destination: CloudWatch
- /ssm/automation/customer-script-log-group-name: the name of an Amazon CloudWatch Logs log group
- /ssm/documents/console/public-sharing-permission: Enable or Disable
- /ssm/managed-instance/activation-tier: standard or advanced

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 847\)](#).

InternalServerError

An error occurred on the server side.

HTTP Status Code: 500

ServiceSettingNotFound

The specified service setting wasn't found. Either the service name or the setting hasn't been provisioned by the AWS service team.

HTTP Status Code: 400

TooManyUpdates

There are concurrent updates for a resource that supports one update at a time.

HTTP Status Code: 400

Examples

Example

This example illustrates one usage of UpdateServiceSetting.

Sample Request

```
POST / HTTP/1.1
Host: ssm.us-east-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonSSM.UpdateServiceSetting
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.17.12 Python/3.6.8 Darwin/18.7.0 botocore/1.14.12
X-Amz-Date: 20200325T154927Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAIOSFODNN7EXAMPLE/20200325/us-east-2/ssm/
aws4_request,
```

```
SignedHeaders=content-type;host;x-amz-date;x-amz-target, Signature=39c3b3042cd2aEXAMPLE
Content-Length: 134
```

```
{
    "SettingId": "arn:aws:ssm:us-east-2:111122223333:servicesetting/ssm/parameter-store/
high-throughput-enabled",
    "SettingValue": "true"
}
```

Sample Response

```
{}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Systems Manager API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountSharingInfo \(p. 582\)](#)
- [Activation \(p. 583\)](#)
- [Association \(p. 585\)](#)
- [AssociationDescription \(p. 588\)](#)
- [AssociationExecution \(p. 593\)](#)
- [AssociationExecutionFilter \(p. 595\)](#)
- [AssociationExecutionTarget \(p. 596\)](#)
- [AssociationExecutionTargetsFilter \(p. 598\)](#)
- [AssociationFilter \(p. 599\)](#)
- [AssociationOverview \(p. 600\)](#)
- [AssociationStatus \(p. 601\)](#)
- [AssociationVersionInfo \(p. 602\)](#)
- [AttachmentContent \(p. 606\)](#)
- [AttachmentInformation \(p. 608\)](#)
- [AttachmentsSource \(p. 609\)](#)
- [AutomationExecution \(p. 611\)](#)
- [AutomationExecutionFilter \(p. 617\)](#)
- [AutomationExecutionMetadata \(p. 618\)](#)
- [BaselineOverride \(p. 623\)](#)
- [CloudWatchOutputConfig \(p. 625\)](#)
- [Command \(p. 626\)](#)
- [CommandFilter \(p. 631\)](#)
- [CommandInvocation \(p. 633\)](#)
- [CommandPlugin \(p. 637\)](#)
- [ComplianceExecutionSummary \(p. 640\)](#)
- [ComplianceItem \(p. 641\)](#)
- [ComplianceItemEntry \(p. 643\)](#)
- [ComplianceStringFilter \(p. 645\)](#)
- [ComplianceSummaryItem \(p. 646\)](#)
- [CompliantSummary \(p. 647\)](#)
- [CreateAssociationBatchRequestEntry \(p. 648\)](#)
- [DescribeActivationsFilter \(p. 653\)](#)
- [DocumentDefaultVersionDescription \(p. 654\)](#)
- [DocumentDescription \(p. 655\)](#)
- [DocumentFilter \(p. 660\)](#)

- [DocumentIdentifier \(p. 661\)](#)
- [DocumentKeyValuesFilter \(p. 664\)](#)
- [DocumentMetadataResponseInfo \(p. 666\)](#)
- [DocumentParameter \(p. 667\)](#)
- [DocumentRequires \(p. 668\)](#)
- [DocumentReviewCommentSource \(p. 669\)](#)
- [DocumentReviewerResponseSource \(p. 670\)](#)
- [DocumentReviews \(p. 672\)](#)
- [DocumentVersionInfo \(p. 673\)](#)
- [EffectivePatch \(p. 675\)](#)
- [FailedCreateAssociation \(p. 676\)](#)
- [FailureDetails \(p. 677\)](#)
- [InstanceAggregatedAssociationOverview \(p. 678\)](#)
- [InstanceAssociation \(p. 679\)](#)
- [InstanceAssociationOutputLocation \(p. 680\)](#)
- [InstanceAssociationOutputUrl \(p. 681\)](#)
- [InstanceAssociationStatusInfo \(p. 682\)](#)
- [InstanceInformation \(p. 685\)](#)
- [InstanceInformationFilter \(p. 689\)](#)
- [InstanceInformationStringFilter \(p. 690\)](#)
- [InstancePatchState \(p. 691\)](#)
- [InstancePatchStateFilter \(p. 696\)](#)
- [InventoryAggregator \(p. 698\)](#)
- [InventoryDeletionStatusItem \(p. 699\)](#)
- [InventoryDeletionSummary \(p. 701\)](#)
- [InventoryDeletionSummaryItem \(p. 702\)](#)
- [InventoryFilter \(p. 703\)](#)
- [InventoryGroup \(p. 704\)](#)
- [InventoryItem \(p. 705\)](#)
- [InventoryItemAttribute \(p. 707\)](#)
- [InventoryItemSchema \(p. 708\)](#)
- [InventoryResultEntity \(p. 709\)](#)
- [InventoryResultItem \(p. 710\)](#)
- [LoggingInfo \(p. 712\)](#)
- [MaintenanceWindowAutomationParameters \(p. 713\)](#)
- [MaintenanceWindowExecution \(p. 715\)](#)
- [MaintenanceWindowExecutionTaskIdentity \(p. 717\)](#)
- [MaintenanceWindowExecutionTaskInvocationIdentity \(p. 719\)](#)
- [MaintenanceWindowFilter \(p. 722\)](#)
- [MaintenanceWindowIdentity \(p. 723\)](#)
- [MaintenanceWindowIdentityForTarget \(p. 726\)](#)
- [MaintenanceWindowLambdaParameters \(p. 727\)](#)
- [MaintenanceWindowRunCommandParameters \(p. 729\)](#)
- [MaintenanceWindowStepFunctionsParameters \(p. 732\)](#)
- [MaintenanceWindowTarget \(p. 733\)](#)
- [MaintenanceWindowTask \(p. 735\)](#)

- [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#)
- [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#)
- [MetadataValue \(p. 741\)](#)
- [NonCompliantSummary \(p. 742\)](#)
- [NotificationConfig \(p. 743\)](#)
- [OpsAggregator \(p. 744\)](#)
- [OpsEntity \(p. 746\)](#)
- [OpsEntityItem \(p. 747\)](#)
- [OpsFilter \(p. 748\)](#)
- [OpsItem \(p. 749\)](#)
- [OpsItemAttributeValue \(p. 753\)](#)
- [OpsItemEventFilter \(p. 754\)](#)
- [OpsItemEventSummary \(p. 755\)](#)
- [OpsItemFilter \(p. 757\)](#)
- [OpsItemIdentity \(p. 758\)](#)
- [OpsItemNotification \(p. 759\)](#)
- [OpsItemRelatedItemsFilter \(p. 760\)](#)
- [OpsItemRelatedItemSummary \(p. 761\)](#)
- [OpsItemSummary \(p. 763\)](#)
- [OpsMetadata \(p. 766\)](#)
- [OpsMetadataFilter \(p. 768\)](#)
- [OpsResultAttribute \(p. 769\)](#)
- [OutputSource \(p. 770\)](#)
- [Parameter \(p. 771\)](#)
- [ParameterHistory \(p. 773\)](#)
- [ParameterInlinePolicy \(p. 776\)](#)
- [ParameterMetadata \(p. 777\)](#)
- [ParametersFilter \(p. 779\)](#)
- [ParameterStringFilter \(p. 780\)](#)
- [Patch \(p. 782\)](#)
- [PatchBaselineIdentity \(p. 786\)](#)
- [PatchComplianceData \(p. 788\)](#)
- [PatchFilter \(p. 790\)](#)
- [PatchFilterGroup \(p. 792\)](#)
- [PatchGroupPatchBaselineMapping \(p. 793\)](#)
- [PatchOrchestratorFilter \(p. 794\)](#)
- [PatchRule \(p. 795\)](#)
- [PatchRuleGroup \(p. 797\)](#)
- [PatchSource \(p. 798\)](#)
- [PatchStatus \(p. 800\)](#)
- [ProgressCounters \(p. 801\)](#)
- [RegistrationMetadataItem \(p. 803\)](#)
- [RelatedOpsItem \(p. 804\)](#)
- [ResolvedTargets \(p. 805\)](#)
- [ResourceComplianceSummaryItem \(p. 806\)](#)
- [ResourceDataSyncAwsOrganizationsSource \(p. 808\)](#)

- [ResourceDataSyncDestinationDataSharing \(p. 809\)](#)
- [ResourceDataSyncItem \(p. 810\)](#)
- [ResourceDataSyncOrganizationalUnit \(p. 812\)](#)
- [ResourceDataSyncS3Destination \(p. 813\)](#)
- [ResourceDataSyncSource \(p. 815\)](#)
- [ResourceDataSyncSourceWithState \(p. 817\)](#)
- [ResultAttribute \(p. 819\)](#)
- [ReviewInformation \(p. 820\)](#)
- [Runbook \(p. 821\)](#)
- [S3OutputLocation \(p. 824\)](#)
- [S3OutputUrl \(p. 825\)](#)
- [ScheduledWindowExecution \(p. 826\)](#)
- [ServiceSetting \(p. 827\)](#)
- [Session \(p. 829\)](#)
- [SessionFilter \(p. 831\)](#)
- [SessionManagerOutputUrl \(p. 832\)](#)
- [SeveritySummary \(p. 833\)](#)
- [StepExecution \(p. 835\)](#)
- [StepExecutionFilter \(p. 839\)](#)
- [Tag \(p. 840\)](#)
- [Target \(p. 841\)](#)
- [TargetLocation \(p. 843\)](#)

AccountSharingInfo

Information includes the AWS account ID where the current document is shared and the version shared with that account.

Contents

AccountId

The AWS account ID where the current document is shared.

Type: String

Pattern: (?i)all|[0-9]{12}

Required: No

SharedDocumentVersion

The version of the current document shared with the account.

Type: String

Length Constraints: Maximum length of 8.

Pattern: ([\\$]LATEST|[\\$]DEFAULT|[\\$]ALL)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Activation

An activation registers one or more on-premises servers or virtual machines (VMs) with AWS so that you can configure those servers or VMs using Run Command. A server or VM that has been registered with AWS Systems Manager is called a managed node.

Contents

ActivationId

The ID created by Systems Manager when you submitted the activation.

Type: String

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: No

CreatedDate

The date the activation was created.

Type: Timestamp

Required: No

DefaultInstanceName

A name for the managed node when it is created.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:=/+\\-@]*\$

Required: No

Description

A user defined description of the activation.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

ExpirationDate

The date when this activation can no longer be used to register managed nodes.

Type: Timestamp

Required: No

Expired

Whether or not the activation is expired.

Type: Boolean

Required: No

IamRole

The AWS Identity and Access Management (IAM) role to assign to the managed node.

Type: String

Length Constraints: Maximum length of 64.

Required: No

RegistrationLimit

The maximum number of managed nodes that can be registered using this activation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

RegistrationsCount

The number of managed nodes already registered with this activation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

Tags

Tags assigned to the activation.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Association

Describes an association of a AWS Systems Manager document (SSM document) and a managed node.

Contents

AssociationId

The ID created by the system when you create an association. An association is a binding between a document and a set of targets with a schedule.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationName

The association name.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

AssociationVersion

The association version.

Type: String

Pattern: ([\\$]LATEST)|([1-9][0-9]*)

Required: No

DocumentVersion

The version of the document used in the association. If you change a document version for a State Manager association, Systems Manager immediately runs the association unless you previously specified the `apply-only-at-cron-interval` parameter.

Important

State Manager doesn't support running associations that use a new version of a document if that document is shared from another account. State Manager always runs the `default` version of a document if shared from another account, even though the Systems Manager console shows that a new version was processed. If you want to run an association using a new version of a document shared from another account, you must set the document version to `default`.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

LastExecutionDate

The date on which the association was last run.

Type: Timestamp

Required: No

Name

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\-.:/]{3,128}\$

Required: No

Overview

Information about the association.

Type: [AssociationOverview \(p. 600\)](#) object

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs. The schedule runs in Coordinated Universal Time (UTC).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request to create an association. You can target all managed nodes in an AWS account by specifying the `InstanceIds` key with a value of `*`.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationDescription

Describes the parameters for a document.

Contents

ApplyOnlyAtCronInterval

By default, when you create a new associations, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationId

The association ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationName

The association name.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

AssociationVersion

The association version.

Type: String

Pattern: ([\\$]LATEST) | ([1-9][0-9]*)

Required: No

AutomationTargetParameterName

Choose the parameter that will define how your automation will branch out. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a capability of AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations only run when that change calendar is open. For more information, see [AWS Systems Manager Change Calendar](#).

Type: Array of strings

Required: No

ComplianceSeverity

The severity level that is assigned to the association.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED

Required: No

Date

The date when the association was made.

Type: Timestamp

Required: No

DocumentVersion

The document version.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\\$)

Required: No

LastExecutionDate

The date on which the association was last run.

Type: Timestamp

Required: No

LastSuccessfulExecutionDate

The last date on which the association was successfully run.

Type: Timestamp

Required: No

LastUpdateAssociationDate

The date when the association was last updated.

Type: Timestamp

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running MaxConcurrency associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for MaxConcurrency.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)\$

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set MaxError to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when MaxErrors is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set MaxConcurrency to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]|100%)\$

Required: No

Name

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\-.:/]{3,128}\$

Required: No

OutputLocation

An S3 bucket where you want to store the output details of the request.

Type: [InstanceAssociationOutputLocation \(p. 680\)](#) object

Required: No

Overview

Information about the association.

Type: [AssociationOverview \(p. 600\)](#) object

Required: No

Parameters

A description of the parameters for a document.

Type: String to array of strings map

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

Status

The association status.

Type: [AssociationStatus \(p. 601\)](#) object

Required: No

SyncCompliance

The mode for generating association compliance. You can specify AUTO or MANUAL. In AUTO mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is COMPLIANT. If the association execution doesn't run successfully, the association is NON-COMPLIANT.

In MANUAL mode, you must specify the `AssociationId` as a parameter for the [PutComplianceItems \(p. 422\)](#) API operation. In this case, compliance data isn't managed by State Manager, a capability of AWS Systems Manager. It is managed by your direct call to the [PutComplianceItems \(p. 422\)](#) API operation.

By default, all associations use AUTO mode.

Type: String

Valid Values: AUTO | MANUAL

Required: No

TargetLocations

The combination of AWS Regions and AWS accounts where you want to run the association.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationExecution

Includes information about the specified association.

Contents

AssociationId

The association ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationVersion

The association version.

Type: String

Pattern: ([\\$]LATEST) | ([1-9][0-9]*)

Required: No

CreatedTime

The time the execution started.

Type: Timestamp

Required: No

DetailedStatus

Detailed status information about the execution.

Type: String

Required: No

ExecutionId

The execution ID for the association.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

LastExecutionDate

The date of the last execution.

Type: Timestamp

Required: No

ResourceCountByStatus

An aggregate status of the resources in the execution based on the status type.

Type: String

Required: No

Status

The status of the association execution.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationExecutionFilter

Filters used in the request.

Contents

Key

The key value used in the request.

Type: String

Valid Values: `ExecutionId` | `Status` | `CreatedTime`

Required: Yes

Type

The filter type specified in the request.

Type: String

Valid Values: `EQUAL` | `LESS_THAN` | `GREATER_THAN`

Required: Yes

Value

The value specified for the key.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationExecutionTarget

Includes information about the specified association execution.

Contents

AssociationId

The association ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationVersion

The association version.

Type: String

Pattern: (\$LATEST) | ([1-9][0-9]*)

Required: No

DetailedStatus

Detailed information about the execution status.

Type: String

Required: No

ExecutionId

The execution ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

LastExecutionDate

The date of the last execution.

Type: Timestamp

Required: No

OutputSource

The location where the association details are saved.

Type: [OutputSource \(p. 770\)](#) object

Required: No

ResourceId

The resource ID, for example, the managed node ID where the association ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The resource type, for example, EC2.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Status

The association execution status.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationExecutionTargetsFilter

Filters for the association execution.

Contents

Key

The key value used in the request.

Type: String

Valid Values: Status | ResourceId | ResourceType

Required: Yes

Value

The value specified for the key.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationFilter

Describes a filter.

Contents

key

The name of the filter.

Note

`InstanceId` has been deprecated.

Type: String

Valid Values: `InstanceId` | `Name` | `AssociationId` | `AssociationStatusName` | `LastExecutedBefore` | `LastExecutedAfter` | `AssociationName` | `ResourceGroupName`

Required: Yes

value

The filter value.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationOverview

Information about the association.

Contents

AssociationStatusAggregatedCount

Returns the number of targets for the association status. For example, if you created an association with two managed nodes, and one of them was successful, this would return the count of managed nodes by status.

Type: String to integer map

Required: No

DetailedStatus

A detailed status of the association.

Type: String

Required: No

Status

The status of the association. Status can be: Pending, Success, or Failed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationStatus

Describes an association status.

Contents

AdditionalInfo

A user-defined string.

Type: String

Length Constraints: Maximum length of 1024.

Required: No

Date

The date when the status changed.

Type: Timestamp

Required: Yes

Message

The reason for the status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

Name

The status.

Type: String

Valid Values: Pending | Success | Failed

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssociationVersionInfo

Information about the association version.

Contents

ApplyOnlyAtCronInterval

By default, when you create a new associations, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationId

The ID created by the system when the association was created.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationName

The name specified for the association version when the association version was created.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

AssociationVersion

The association version.

Type: String

Pattern: (\$LATEST) | ([1-9][0-9]*)

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations for this version only run when that Change Calendar is open. For more information, see [AWS Systems Manager Change Calendar](#).

Type: Array of strings

Required: No

ComplianceSeverity

The severity level that is assigned to the association.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED

Required: No

CreatedDate

The date the association version was created.

Type: Timestamp

Required: No

DocumentVersion

The version of an AWS Systems Manager document (SSM document) used when the association version was created.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)\$

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%^|[0-9]%^|100%)\$

Required: No

Name

The name specified when the association was created.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.:/]{3,128}\$

Required: No

OutputLocation

The location in Amazon S3 specified for the association when the association version was created.

Type: [InstanceAssociationOutputLocation \(p. 680\)](#) object

Required: No

Parameters

Parameters specified when the association version was created.

Type: String to array of strings map

Required: No

ScheduleExpression

The cron or rate schedule specified for the association when the association version was created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify AUTO or MANUAL. In AUTO mode, the system uses the status of the association execution to determine the compliance status. If the association execution runs successfully, then the association is COMPLIANT. If the association execution doesn't run successfully, the association is NON-COMPLIANT.

In MANUAL mode, you must specify the `AssociationId` as a parameter for the [PutComplianceItems \(p. 422\)](#) API operation. In this case, compliance data isn't managed by State Manager, a capability of AWS Systems Manager. It is managed by your direct call to the [PutComplianceItems \(p. 422\)](#) API operation.

By default, all associations use AUTO mode.

Type: String

Valid Values: AUTO | MANUAL

Required: No

TargetLocations

The combination of AWS Regions and AWS accounts where you wanted to run the association when this association version was created.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets specified for the association when the association version was created.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentContent

A structure that includes attributes that describe a document attachment.

Contents

Hash

The cryptographic hash value of the document content.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HashType

The hash algorithm used to calculate the hash value.

Type: String

Valid Values: Sha256

Required: No

Name

The name of an attachment.

Type: String

Pattern: ^[a-zA-Z0-9\-_\.]{3,128}\$

Required: No

Size

The size of an attachment in bytes.

Type: Long

Required: No

Url

The URL location of the attachment content.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentInformation

An attribute of an attachment, such as the attachment name.

Contents

Name

The name of the attachment.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentsSource

Identifying information about a document attachment, including the file name and a key-value pair that identifies the location of an attachment to a document.

Contents

Key

The key of a key-value pair that identifies the location of an attachment to a document.

Type: String

Valid Values: `SourceUrl` | `S3FileUrl` | `AttachmentReference`

Required: No

Name

The name of the document attachment file.

Type: String

Pattern: `^[a-zA-Z0-9_\.]{3,128}$`

Required: No

Values

The value of a key-value pair that identifies the location of an attachment to a document. The format for **Value** depends on the type of key you specify.

- For the key `SourceUrl`, the value is an S3 bucket location. For example:

```
"Values": [ "s3://doc-example-bucket/my-folder" ]
```

- For the key `S3FileUrl`, the value is a file in an S3 bucket. For example:

```
"Values": [ "s3://doc-example-bucket/my-folder/my-file.py" ]
```

- For the key `AttachmentReference`, the value is constructed from the name of another SSM document in your account, a version number of that document, and a file attached to that document version that you want to reuse. For example:

```
"Values": [ "MyOtherDocument/3/my-other-file.py" ]
```

However, if the SSM document is shared with you from another account, the full SSM document ARN must be specified instead of the document name only. For example:

```
"Values": [ "arn:aws:ssm:us-east-2:111122223333:document/OtherAccountDocument/3/their-file.py" ]
```

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutomationExecution

Detailed information about the current state of an individual Automation execution.

Contents

AssociationId

The ID of a State Manager association used in the Automation operation.

Type: String

Required: No

AutomationExecutionId

The execution ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

AutomationExecutionStatus

The execution status of the Automation.

Type: String

Valid Values: Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure

Required: No

AutomationSubtype

The subtype of the Automation operation. Currently, the only supported value is ChangeRequest.

Type: String

Valid Values: ChangeRequest

Required: No

ChangeRequestName

The name of the Change Manager change request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

CurrentAction

The action of the step that is currently running.

Type: String

Required: No

CurrentStepName

The name of the step that is currently running.

Type: String

Required: No

DocumentName

The name of the Automation runbook used during the execution.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

DocumentVersion

The version of the document to use during execution.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

ExecutedBy

The Amazon Resource Name (ARN) of the user who ran the automation.

Type: String

Required: No

ExecutionEndTime

The time the execution finished.

Type: Timestamp

Required: No

ExecutionStartTime

The time the execution started.

Type: Timestamp

Required: No

FailureMessage

A message describing why an execution has failed, if the status is set to Failed.

Type: String

Required: No

MaxConcurrency

The MaxConcurrency value specified by the user when the execution started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)\$

Required: No

MaxErrors

The MaxErrors value specified by the user when the execution started.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]|[1-9][0-9]%|[0-9]%|100%)\$

Required: No

Mode

The automation execution mode.

Type: String

Valid Values: Auto | Interactive

Required: No

OpsItemId

The ID of an OpsItem that is created to represent a Change Manager change request.

Type: String

Required: No

Outputs

The list of execution outputs as defined in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Parameters

The key-value map of execution parameters, which were supplied when calling [StartAutomationExecution \(p. 481\)](#).

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

ParentAutomationExecutionId

The AutomationExecutionId of the parent automation.

Type: String

Length Constraints: Fixed length of 36.

Required: No

ProgressCounters

An aggregate of step execution statuses displayed in the AWS Systems Manager console for a multi-Region and multi-account Automation execution.

Type: [ProgressCounters \(p. 801\)](#) object

Required: No

ResolvedTargets

A list of resolved targets in the rate control execution.

Type: [ResolvedTargets \(p. 805\)](#) object

Required: No

Runbooks

Information about the Automation runbooks that are run as part of a runbook workflow.

Note

The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of [Runbook \(p. 821\)](#) objects

Array Members: Fixed number of 1 item.

Required: No

ScheduledTime

The date and time the Automation operation is scheduled to start.

Type: Timestamp

Required: No

StepExecutions

A list of details about the current state of all steps that comprise an execution. An Automation runbook contains a list of steps that are run in order.

Type: Array of [StepExecution \(p. 835\)](#) objects

Required: No

StepExecutionsTruncated

A boolean value that indicates if the response contains the full list of the Automation step executions. If true, use the `DescribeAutomationStepExecutions` API operation to get the full list of step executions.

Type: Boolean

Required: No

Target

The target of the execution.

Type: String

Required: No

TargetLocations

The combination of AWS Regions and/or AWS accounts where you want to run the Automation.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

The specified key-value mapping of document parameters to target resources.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The parameter name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The specified targets.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutomationExecutionFilter

A filter used to match specific automation executions. This is used to limit the scope of Automation execution information returned.

Contents

Key

One or more keys to limit the results.

Type: String

Valid Values: DocumentNamePrefix | ExecutionStatus | ExecutionId | ParentExecutionId | CurrentAction | StartTimeBefore | StartTimeAfter | AutomationType | TagKey | TargetResourceGroup | AutomationSubtype | OpsItemId

Required: Yes

Values

The values used to limit the execution information associated with the filter's key.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutomationExecutionMetadata

Details about a specific Automation execution.

Contents

AssociationId

The ID of a State Manager association used in the Automation operation.

Type: String

Required: No

AutomationExecutionId

The execution ID.

Type: String

Length Constraints: Fixed length of 36.

Required: No

AutomationExecutionStatus

The status of the execution.

Type: String

Valid Values: Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure

Required: No

AutomationSubtype

The subtype of the Automation operation. Currently, the only supported value is ChangeRequest.

Type: String

Valid Values: ChangeRequest

Required: No

AutomationType

Use this filter with [DescribeAutomationExecutions \(p. 124\)](#). Specify either Local or CrossAccount. CrossAccount is an Automation that runs in multiple AWS Regions and AWS accounts. For more information, see [Running Automation workflows in multiple AWS Regions and accounts](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: CrossAccount | Local

Required: No

ChangeRequestName

The name of the Change Manager change request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

CurrentAction

The action of the step that is currently running.

Type: String

Required: No

CurrentStepName

The name of the step that is currently running.

Type: String

Required: No

DocumentName

The name of the Automation runbook used during execution.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: No

DocumentVersion

The document version used during the execution.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

ExecutedBy

The IAM role ARN of the user who ran the automation.

Type: String

Required: No

ExecutionEndTime

The time the execution finished. This isn't populated if the execution is still in progress.

Type: Timestamp

Required: No

ExecutionStartTime

The time the execution started.

Type: Timestamp

Required: No

FailureMessage

The list of execution outputs as defined in the Automation runbook.

Type: String

Required: No

LogFile

An S3 bucket where execution information is stored.

Type: String

Required: No

MaxConcurrency

The `MaxConcurrency` value specified by the user when starting the automation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)$`

Required: No

MaxErrors

The `MaxErrors` value specified by the user when starting the automation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: `^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%^|100%)$`

Required: No

Mode

The Automation execution mode.

Type: String

Valid Values: `Auto` | `Interactive`

Required: No

OpsItemId

The ID of an OpsItem that is created to represent a Change Manager change request.

Type: String

Required: No

Outputs

The list of execution outputs as defined in the Automation runbook.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

ParentAutomationExecutionId

The execution ID of the parent automation.

Type: String

Length Constraints: Fixed length of 36.

Required: No

ResolvedTargets

A list of targets that resolved during the execution.

Type: [ResolvedTargets \(p. 805\)](#) object

Required: No

Runbooks

Information about the Automation runbooks that are run during a runbook workflow in Change Manager.

Note

The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Type: Array of [Runbook \(p. 821\)](#) objects

Array Members: Fixed number of 1 item.

Required: No

ScheduledTime

The date and time the Automation operation is scheduled to start.

Type: Timestamp

Required: No

Target

The list of execution outputs as defined in the Automation runbook.

Type: String

Required: No

TargetMaps

The specified key-value mapping of document parameters to target resources.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The list of execution outputs as defined in the Automation runbook.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The targets defined by the user when starting the automation.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BaselineOverride

Defines the basic information about a patch baseline override.

Contents

ApprovalRules

A set of rules defining the approval rules for a patch baseline.

Type: [PatchRuleGroup \(p. 797\)](#) object

Required: No

ApprovedPatches

A list of explicitly approved patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ApprovedPatchesComplianceLevel

Defines the compliance level for approved patches. When an approved patch is reported as missing, this value describes the severity of the compliance violation.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

ApprovedPatchesEnableNonSecurity

Indicates whether the list of approved patches includes non-security updates that should be applied to the managed nodes. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

GlobalFilters

A set of patch filters, typically used for approval rules.

Type: [PatchFilterGroup \(p. 792\)](#) object

Required: No

OperatingSystem

The operating system rule used by the patch baseline override.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: No

RejectedPatches

A list of explicitly rejected patches for the baseline.

For information about accepted formats for lists of approved patches and rejected patches, see [About package name formats for approved and rejected patch lists](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

RejectedPatchesAction

The action for Patch Manager to take on patches included in the RejectedPatches list. A patch can be allowed only if it is a dependency of another package, or blocked entirely along with packages that include it as a dependency.

Type: String

Valid Values: ALLOW_AS_DEPENDENCY | BLOCK

Required: No

Sources

Information about the patches to use to update the managed nodes, including target operating systems and source repositories. Applies to Linux managed nodes only.

Type: Array of [PatchSource \(p. 798\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CloudWatchOutputConfig

Configuration options for sending command output to Amazon CloudWatch Logs.

Contents

CloudWatchLogGroupName

The name of the CloudWatch Logs log group where you want to send command output. If you don't specify a group name, AWS Systems Manager automatically creates a log group for you. The log group uses the following naming format:

`aws/ssm/SystemsManagerDocumentName`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

CloudWatchOutputEnabled

Enables Systems Manager to send command output to CloudWatch Logs.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Command

Describes a command request.

Contents

CloudWatchOutputConfig

Amazon CloudWatch Logs information where you want AWS Systems Manager to send the command output.

Type: [CloudWatchOutputConfig \(p. 625\)](#) object

Required: No

CommandId

A unique identifier for this command.

Type: String

Length Constraints: Fixed length of 36.

Required: No

Comment

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

CompletedCount

The number of targets for which the command invocation reached a terminal state. Terminal states include the following: Success, Failed, Execution Timed Out, Delivery Timed Out, Cancelled, Terminated, or Undeliverable.

Type: Integer

Required: No

DeliveryTimedOutCount

The number of targets for which the status is Delivery Timed Out.

Type: Integer

Required: No

DocumentName

The name of the document requested for execution.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

DocumentVersion

The Systems Manager document (SSM document) version.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

ErrorCount

The number of targets for which the status is Failed or Execution Timed Out.

Type: Integer

Required: No

ExpiresAfter

If this time is reached and the command hasn't already started running, it won't run. Calculated based on the `ExpiresAfter` user input provided as part of the `SendCommand` API operation.

Type: Timestamp

Required: No

InstanceIds

The managed node IDs against which this command was requested.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

MaxConcurrency

The maximum number of managed nodes that are allowed to run the command at the same time. You can specify a number of managed nodes, such as 10, or a percentage of nodes, such as 10%. The default value is 50. For more information about how to use `MaxConcurrency`, see [Running commands using Systems Manager Run Command](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)\$

Required: No

MaxErrors

The maximum number of errors allowed before the system stops sending the command to additional targets. You can specify a number of errors, such as 10, or a percentage of errors, such as 10%. The default value is 0. For more information about how to use `MaxErrors`, see [Running commands using Systems Manager Run Command](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%|100%)\$

Required: No

NotificationConfig

Configurations for sending notifications about command status changes.

Type: [NotificationConfig \(p. 743\)](#) object

Required: No

OutputS3BucketName

The S3 bucket where the responses to the command executions should be stored. This was requested when issuing the command.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 directory path inside the bucket where the responses to the command executions should be stored. This was requested when issuing the command.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, Systems Manager automatically determines the AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

Parameters

The parameter values to be inserted in the document when running the command.

Type: String to array of strings map

Required: No

RequestedDateTime

The date and time the command was requested.

Type: Timestamp

Required: No

ServiceRole

The AWS Identity and Access Management (IAM) service role that Run Command, a capability of AWS Systems Manager, uses to act on your behalf when sending notifications about command status changes.

Type: String

Required: No

Status

The status of the command.

Type: String

Valid Values: Pending | InProgress | Success | Cancelled | Failed | TimedOut | Cancelling

Required: No

StatusDetails

A detailed status of the command execution. StatusDetails includes more information than Status because it includes states resulting from error and concurrency control parameters. StatusDetails can show different results than Status. For more information about these statuses, see [Understanding command statuses](#) in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to any managed nodes.
- In Progress: The command has been sent to at least one managed node but hasn't reached a final state on all managed nodes.
- Success: The command successfully ran on all invocations. This is a terminal state.
- Delivery Timed Out: The value of MaxErrors or more command invocations shows a status of Delivery Timed Out. This is a terminal state.
- Execution Timed Out: The value of MaxErrors or more command invocations shows a status of Execution Timed Out. This is a terminal state.
- Failed: The value of MaxErrors or more command invocations shows a status of Failed. This is a terminal state.
- Incomplete: The command was attempted on all managed nodes and one or more invocations doesn't have a value of Success but not enough invocations failed for the status to be Failed. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Rate Exceeded: The number of managed nodes targeted by the command exceeded the account limit for pending invocations. The system has canceled the command before running it on any managed node. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

TargetCount

The number of targets for the command.

Type: Integer

Required: No

Targets

An array of search criteria that targets managed nodes using a Key/Value combination that you specify. Targets is required if you don't provide one or more managed node IDs in the call.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TimeoutSeconds

The `TimeoutSeconds` value specified for a command.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandFilter

Describes a command filter.

Note

A managed node ID can't be specified when a command status is `Pending` because the command hasn't run on the node yet.

Contents

key

The name of the filter.

Note

The `ExecutionStage` filter can't be used with the `ListCommandInvocations` operation, only with `ListCommands`.

Type: String

Valid Values: `InvokedAfter` | `InvokedBefore` | `Status` | `ExecutionStage` | `DocumentName`

Required: Yes

value

The filter value. Valid values for each filter key are as follows:

- **InvokedAfter:** Specify a timestamp to limit your results. For example, specify `2021-07-07T00:00:00Z` to see a list of command executions occurring July 7, 2021, and later.
- **InvokedBefore:** Specify a timestamp to limit your results. For example, specify `2021-07-07T00:00:00Z` to see a list of command executions from before July 7, 2021.
- **Status:** Specify a valid command status to see a list of all command executions with that status. The status choices depend on the API you call.

The status values you can specify for `ListCommands` are:

- `Pending`
- `InProgress`
- `Success`
- `Cancelled`
- `Failed`
- `TimedOut` (this includes both Delivery and Execution time outs)
- `AccessDenied`
- `DeliveryTimedOut`
- `ExecutionTimedOut`
- `Incomplete`
- `NoInstancesInTag`
- `LimitExceeded`

The status values you can specify for `ListCommandInvocations` are:

- `Pending`
- `InProgress`
- `Delayed`
- `Success`

- `Cancelled`
- `Failed`
- `TimedOut` (this includes both Delivery and Execution time outs)
- `AccessDenied`
- `DeliveryTimedOut`
- `ExecutionTimedOut`
- `Undeliverable`
- `InvalidPlatform`
- `Terminated`
- **DocumentName:** Specify name of the AWS Systems Manager document (SSM document) for which you want to see command execution results. For example, specify `AWS-RunPatchBaseline` to see command executions that used this SSM document to perform security patching operations on managed nodes.
- **ExecutionStage:** Specify one of the following values (ListCommands operations only):
 - `Executing`: Returns a list of command executions that are currently still running.
 - `Complete`: Returns a list of command executions that have already completed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandInvocation

An invocation is a copy of a command sent to a specific managed node. A command can apply to one or more managed nodes. A command invocation applies to one managed node. For example, if a user runs `SendCommand` against three managed nodes, then a command invocation is created for each requested managed node ID. A command invocation returns status and detail information about a command you ran.

Contents

CloudWatchOutputConfig

Amazon CloudWatch Logs information where you want AWS Systems Manager to send the command output.

Type: [CloudWatchOutputConfig \(p. 625\)](#) object

Required: No

CommandId

The command against which this invocation was requested.

Type: String

Length Constraints: Fixed length of 36.

Required: No

CommandPlugins

Plugins processed by the command.

Type: Array of [CommandPlugin \(p. 637\)](#) objects

Required: No

Comment

User-specified information about the command, such as a brief description of what the command should do.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DocumentName

The document name that was requested for execution.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: No

DocumentVersion

The Systems Manager document (SSM document) version.

Type: String

Pattern: ([\$]LATEST | [\$]DEFAULT | ^[1-9][0-9]*\$)

Required: No

InstanceId

The managed node ID in which this invocation was requested.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

InstanceName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Maximum length of 255.

Required: No

NotificationConfig

Configurations for sending notifications about command status changes on a per managed node basis.

Type: [NotificationConfig \(p. 743\)](#) object

Required: No

RequestedDateTime

The time and date the request was sent to this managed node.

Type: Timestamp

Required: No

ServiceRole

The AWS Identity and Access Management (IAM) service role that Run Command, a capability of AWS Systems Manager, uses to act on your behalf when sending notifications about command status changes on a per managed node basis.

Type: String

Required: No

StandardErrorUrl

The URL to the plugin's StdErr file in Amazon Simple Storage Service (Amazon S3), if the S3 bucket was defined for the parent command. For an invocation, StandardErrorUrl is populated if there is just one plugin defined for the command, and the S3 bucket was defined for the command.

Type: String

Required: No

StandardOutputUrl

The URL to the plugin's StdOut file in Amazon Simple Storage Service (Amazon S3), if the S3 bucket was defined for the parent command. For an invocation, StandardOutputUrl is populated if there is just one plugin defined for the command, and the S3 bucket was defined for the command.

Type: String

Required: No

Status

Whether or not the invocation succeeded, failed, or is pending.

Type: String

Valid Values: Pending | InProgress | Delayed | Success | Cancelled | TimedOut | Failed | Cancelling

Required: No

StatusDetails

A detailed status of the command execution for each invocation (each managed node targeted by the command). StatusDetails includes more information than Status because it includes states resulting from error and concurrency control parameters. StatusDetails can show different results than Status. For more information about these statuses, see [Understanding command statuses](#) in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to the managed node.
- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.
- Success: The execution of the command or plugin was successfully completed. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's MaxErrors limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: Command execution started on the managed node, but the execution wasn't complete before the execution timeout expired. Execution timeouts count against the MaxErrors limit of the parent command. This is a terminal state.
- Failed: The command wasn't successful on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the MaxErrors limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The managed node might not exist or might not be responding. Undeliverable invocations don't count against the parent command's MaxErrors limit and don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Terminated: The parent command exceeded its MaxErrors limit and subsequent command invocations were canceled by the system. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

TraceOutput

Gets the trace output sent by the agent.

Type: String

Length Constraints: Maximum length of 2500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandPlugin

Describes plugin details.

Contents

Name

The name of the plugin. Must be one of the following: `aws:updateAgent`, `aws:domainjoin`, `aws:applications`, `aws:runPowerShellScript`, `aws:psmodule`, `aws:cloudWatch`, `aws:runShellScript`, or `aws:updateSSMAgent`.

Type: String

Length Constraints: Minimum length of 4.

Required: No

Output

Output of the plugin execution.

Type: String

Length Constraints: Maximum length of 2500.

Required: No

OutputS3BucketName

The S3 bucket where the responses to the command executions should be stored. This was requested when issuing the command. For example, in the following response:

```
doc-example-bucket/ab19cb99-a030-46dd-9dfc-8eSAMPLEPre-Fix/  
i-02573cafccfEXAMPLE/awsrunShellScript
```

`doc-example-bucket` is the name of the S3 bucket;

`ab19cb99-a030-46dd-9dfc-8eSAMPLEPre-Fix` is the name of the S3 prefix;

`i-02573cafccfEXAMPLE` is the managed node ID;

`awsrunShellScript` is the name of the plugin.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 directory path inside the bucket where the responses to the command executions should be stored. This was requested when issuing the command. For example, in the following response:

```
doc-example-bucket/ab19cb99-a030-46dd-9dfc-8eSAMPLEPre-Fix/  
i-02573cafccfEXAMPLE/awsrunShellScript
```

`doc-example-bucket` is the name of the S3 bucket;

`ab19cb99-a030-46dd-9dfc-8eSAMPLEPre-Fix` is the name of the S3 prefix;

i-02573cafccfEXAMPLE is the managed node ID;

awsrunShellScript is the name of the plugin.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

(Deprecated) You can no longer specify this parameter. The system ignores it. Instead, AWS Systems Manager automatically determines the S3 bucket region.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

ResponseCode

A numeric response code generated after running the plugin.

Type: Integer

Required: No

ResponseFinishDateTime

The time the plugin stopped running. Could stop prematurely if, for example, a cancel command was sent.

Type: Timestamp

Required: No

ResponseStartTime

The time the plugin started running.

Type: Timestamp

Required: No

StandardErrorUrl

The URL for the complete text written by the plugin to stderr. If execution isn't yet complete, then this string is empty.

Type: String

Required: No

StandardOutputUrl

The URL for the complete text written by the plugin to stdout in Amazon S3. If the S3 bucket for the command wasn't specified, then this string is empty.

Type: String

Required: No

Status

The status of this plugin. You can run a document with multiple plugins.

Type: String

Valid Values: Pending | InProgress | Success | TimedOut | Cancelled | Failed

Required: No

StatusDetails

A detailed status of the plugin execution. StatusDetails includes more information than Status because it includes states resulting from error and concurrency control parameters. StatusDetails can show different results than Status. For more information about these statuses, see [Understanding command statuses](#) in the *AWS Systems Manager User Guide*. StatusDetails can be one of the following values:

- Pending: The command hasn't been sent to the managed node.
- In Progress: The command has been sent to the managed node but hasn't reached a terminal state.
- Success: The execution of the command or plugin was successfully completed. This is a terminal state.
- Delivery Timed Out: The command wasn't delivered to the managed node before the delivery timeout expired. Delivery timeouts don't count against the parent command's MaxErrors limit, but they do contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Execution Timed Out: Command execution started on the managed node, but the execution wasn't complete before the execution timeout expired. Execution timeouts count against the MaxErrors limit of the parent command. This is a terminal state.
- Failed: The command wasn't successful on the managed node. For a plugin, this indicates that the result code wasn't zero. For a command invocation, this indicates that the result code for one or more plugins wasn't zero. Invocation failures count against the MaxErrors limit of the parent command. This is a terminal state.
- Cancelled: The command was terminated before it was completed. This is a terminal state.
- Undeliverable: The command can't be delivered to the managed node. The managed node might not exist, or it might not be responding. Undeliverable invocations don't count against the parent command's MaxErrors limit, and they don't contribute to whether the parent command status is Success or Incomplete. This is a terminal state.
- Terminated: The parent command exceeded its MaxErrors limit and subsequent command invocations were canceled by the system. This is a terminal state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComplianceExecutionSummary

A summary of the call execution that includes an execution ID, the type of execution (for example, Command), and the date/time of the execution using a datetime object that is saved in the following format: yyyy-MM-dd'T'HH:mm:ss'Z'.

Contents

ExecutionId

An ID created by the system when PutComplianceItems was called. For example, CommandID is a valid execution ID. You can use this ID in subsequent calls.

Type: String

Length Constraints: Maximum length of 100.

Required: No

ExecutionTime

The time the execution ran as a datetime object that is saved in the following format: yyyy-MM-dd'T'HH:mm:ss'Z'.

Type: Timestamp

Required: Yes

ExecutionType

The type of execution. For example, Command is a valid execution type.

Type: String

Length Constraints: Maximum length of 50.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComplianceItem

Information about the compliance as defined by the resource type. For example, for a patch resource type, `Items` includes information about the PatchSeverity, Classification, and so on.

Contents

ComplianceType

The compliance type. For example, Association (for a State Manager association), Patch, or Custom:string are all valid compliance types.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [A-Za-z0-9\-_]\w+ | Custom:[a-zA-Z0-9\-_]\w+

Required: No

Details

A "Key": "Value" tag combination for the compliance item.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

ExecutionSummary

A summary for the compliance item. The summary includes an execution ID, the execution type (for example, command), and the execution time.

Type: [ComplianceExecutionSummary \(p. 640\)](#) object

Required: No

Id

An ID for the compliance item. For example, if the compliance item is a Windows patch, the ID could be the number of the KB article; for example: KB4010320.

Type: String

Required: No

ResourceId

An ID for the resource. For a managed node, this is the node ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The type of resource. `ManagedInstance` is currently the only supported resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Severity

The severity of the compliance status. Severity can be one of the following: Critical, High, Medium, Low, Informational, Unspecified.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

Status

The status of the compliance item. An item is either COMPLIANT, NON_COMPLIANT, or an empty string (for Windows patches that aren't applicable).

Type: String

Valid Values: COMPLIANT | NON_COMPLIANT

Required: No

Title

A title for the compliance item. For example, if the compliance item is a Windows patch, the title could be the title of the KB article for the patch; for example: Security Update for Active Directory Federation Services.

Type: String

Length Constraints: Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComplianceItemEntry

Information about a compliance item.

Contents

Details

A "Key": "Value" tag combination for the compliance item.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

Id

The compliance item ID. For example, if the compliance item is a Windows patch, the ID could be the number of the KB article.

Type: String

Required: No

Severity

The severity of the compliance status. Severity can be one of the following: Critical, High, Medium, Low, Informational, Unspecified.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: Yes

Status

The status of the compliance item. An item is either COMPLIANT or NON_COMPLIANT.

Type: String

Valid Values: COMPLIANT | NON_COMPLIANT

Required: Yes

Title

The title of the compliance item. For example, if the compliance item is a Windows patch, the title could be the title of the KB article for the patch; for example: Security Update for Active Directory Federation Services.

Type: String

Length Constraints: Maximum length of 500.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComplianceStringFilter

One or more filters. Use a filter to return a more specific list of results.

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

Type

The type of comparison that should be performed for the value: Equal, NotEqual, BeginWith, LessThan, or GreaterThan.

Type: String

Valid Values: EQUAL | NOT_EQUAL | BEGIN_WITH | LESS_THAN | GREATER_THAN

Required: No

Values

The value for which to search.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComplianceSummaryItem

A summary of compliance information by compliance type.

Contents

ComplianceType

The type of compliance item. For example, the compliance type can be Association, Patch, or Custom:string.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [A-Za-z0-9_\-]\w+ | Custom:[a-zA-Z0-9_\-]\w+

Required: No

CompliantSummary

A list of COMPLIANT items for the specified compliance type.

Type: [CompliantSummary \(p. 647\)](#) object

Required: No

NonCompliantSummary

A list of NON_COMPLIANT items for the specified compliance type.

Type: [NonCompliantSummary \(p. 742\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CompliantSummary

A summary of resources that are compliant. The summary is organized according to the resource count for each compliance type.

Contents

CompliantCount

The total number of resources that are compliant.

Type: Integer

Required: No

SeveritySummary

A summary of the compliance severity by compliance type.

Type: [SeveritySummary \(p. 833\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateAssociationBatchRequestEntry

Describes the association of a AWS Systems Manager document (SSM document) and a managed node.

Contents

ApplyOnlyAtCronInterval

By default, when you create a new associations, the system runs it immediately after it is created and then according to the schedule you specified. Specify this option if you don't want an association to run immediately after you create it. This parameter isn't supported for rate expressions.

Type: Boolean

Required: No

AssociationName

Specify a descriptive name for the association.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

AutomationTargetParameterName

Specify the target for the association. This target is required for associations that use an Automation runbook and target resources by using rate controls. Automation is a capability of AWS Systems Manager.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

CalendarNames

The names or Amazon Resource Names (ARNs) of the Change Calendar type documents your associations are gated under. The associations only run when that Change Calendar is open. For more information, see [AWS Systems Manager Change Calendar](#).

Type: Array of strings

Required: No

ComplianceSeverity

The severity level to assign to the association.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | UNSPECIFIED

Required: No

DocumentVersion

The document version.

Type: String

Pattern: ([\\$]LATEST | [\\$]DEFAULT | ^[1-9][0-9]*\\$)

Required: No

InstanceId

The managed node ID.

Note

`InstanceId` has been deprecated. To specify a managed node ID for an association, use the `Targets` parameter. Requests that include the parameter `InstanceId` with Systems Manager documents (SSM documents) that use schema version 2.0 or later will fail. In addition, if you use the parameter `InstanceId`, you can't use the parameters `AssociationName`, `DocumentVersion`, `MaxErrors`, `MaxConcurrency`, `OutputLocation`, or `ScheduleExpression`. To use these parameters, you must use the `Targets` parameter.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

MaxConcurrency

The maximum number of targets allowed to run the association at the same time. You can specify a number, for example 10, or a percentage of the target set, for example 10%. The default value is 100%, which means all targets run the association at the same time.

If a new managed node starts and attempts to run an association while Systems Manager is running `MaxConcurrency` associations, the association is allowed to run. During the next association interval, the new managed node will process its association within the limit specified for `MaxConcurrency`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]|100%)\$

Required: No

MaxErrors

The number of errors that are allowed before the system stops sending requests to run the association on additional targets. You can specify either an absolute number of errors, for example 10, or a percentage of the target set, for example 10%. If you specify 3, for example, the system stops sending requests when the fourth error is received. If you specify 0, then the system stops sending requests after the first error is returned. If you run an association on 50 managed nodes and set `MaxError` to 10%, then the system stops sending the request when the sixth error is received.

Executions that are already running an association when `MaxErrors` is reached are allowed to complete, but some of these executions may fail as well. If you need to ensure that there won't be more than max-errors failed executions, set `MaxConcurrency` to 1 so that executions proceed one at a time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]|100%)\$

Required: No

Name

The name of the SSM document that contains the configuration information for the managed node. You can specify Command or Automation runbooks.

You can specify AWS-predefined documents, documents you created, or a document that is shared with you from another account.

For SSM documents that are shared with you from other AWS accounts, you must specify the complete SSM document ARN, in the following format:

`arn:aws:ssm:region:account-id:document/document-name`

For example:

`arn:aws:ssm:us-east-2:12345678912:document/My-Shared-Document`

For AWS-predefined documents and SSM documents you created in your account, you only need to specify the document name. For example, `AWS-ApplyPatchBaseline` or `My-Document`.

Type: String

Pattern: `^[a-zA-Z0-9_\-.:/]{3,128}$`

Required: Yes

OutputLocation

An S3 bucket where you want to store the results of this request.

Type: [InstanceAssociationOutputLocation \(p. 680\)](#) object

Required: No

Parameters

A description of the parameters for a document.

Type: String to array of strings map

Required: No

ScheduleExpression

A cron expression that specifies a schedule when the association runs.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

Number of days to wait after the scheduled day to run an association.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

SyncCompliance

The mode for generating association compliance. You can specify `AUTO` or `MANUAL`. In `AUTO` mode, the system uses the status of the association execution to determine the compliance status. If

the association execution runs successfully, then the association is COMPLIANT. If the association execution doesn't run successfully, the association is NON-COMPLIANT.

In MANUAL mode, you must specify the `AssociationId` as a parameter for the [PutComplianceItems \(p. 422\)](#) API operation. In this case, compliance data isn't managed by State Manager, a capability of AWS Systems Manager. It is managed by your direct call to the [PutComplianceItems \(p. 422\)](#) API operation.

By default, all associations use AUTO mode.

Type: String

Valid Values: AUTO | MANUAL

Required: No

TargetLocations

Use this action to create an association in multiple Regions and multiple accounts.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of document parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

The managed nodes targeted by the request.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DescribeActivationsFilter

Filter for the `DescribeActivation` API.

Contents

FilterKey

The name of the filter.

Type: String

Valid Values: `ActivationIds` | `DefaultInstanceName` | `IamRole`

Required: No

FilterValues

The filter values.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentDefaultVersionDescription

A default version of a document.

Contents

DefaultVersion

The default version of the document.

Type: String

Pattern: (`[$]LATEST` | `[$]DEFAULT` | `^[1-9][0-9]*$`)

Required: No

DefaultVersionName

The default version of the artifact associated with the document.

Type: String

Pattern: `^[a-zA-Z0-9_\.]{1,128}$`

Required: No

Name

The name of the document.

Type: String

Pattern: `^[a-zA-Z0-9_\.]{3,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentDescription

Describes an AWS Systems Manager document (SSM document).

Contents

ApprovedVersion

The version of the document currently approved for use in the organization.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

AttachmentsInformation

Details about the document attachments, including names, locations, sizes, and so on.

Type: Array of [AttachmentInformation \(p. 608\)](#) objects

Required: No

Author

The user in your organization who created the document.

Type: String

Required: No

Category

The classification of a document to help you identify and categorize its use.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Length Constraints: Maximum length of 128.

Required: No

CategoryEnum

The value that identifies a document's category.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 3 items.

Length Constraints: Maximum length of 128.

Required: No

CreatedDate

The date when the document was created.

Type: Timestamp

Required: No

DefaultVersion

The default version.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

Description

A description of the document.

Type: String

Required: No

DisplayName

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see [UpdateDocument \(p. 518\)](#).

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/\]*\$

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: YAML | JSON | TEXT

Required: No

DocumentType

The type of document.

Type: String

Valid Values: Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate

Required: No

DocumentVersion

The document version.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

Hash

The Sha256 or Sha1 hash created by the system when the document was created.

Note

Sha1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

HashType

The hash type of the document. Valid values include Sha256 or Sha1.

Note

Sha1 hashes have been deprecated.

Type: String

Valid Values: Sha256 | Sha1

Required: No

LatestVersion

The latest version of the document.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

Name

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\.:\-]{3,128}\$

Required: No

Owner

The Amazon Web Services user account that created the document.

Type: String

Required: No

Parameters

A description of the parameters for a document.

Type: Array of [DocumentParameter \(p. 667\)](#) objects

Required: No

PendingReviewVersion

The version of the document that is currently under review.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

PlatformTypes

The list of operating system (OS) platforms compatible with this SSM document.

Type: Array of strings

Valid Values: Windows | Linux | MacOS

Required: No

Requires

A list of SSM documents required by a document. For example, an [ApplicationConfiguration](#) document requires an [ApplicationConfigurationSchema](#) document.

Type: Array of [DocumentRequires \(p. 668\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

ReviewInformation

Details about the review of a document.

Type: Array of [ReviewInformation \(p. 820\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

ReviewStatus

The current status of the review.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

Required: No

SchemaVersion

The schema version.

Type: String

Pattern: ([0-9]+)\.([0-9]+)

Required: No

Sha1

The SHA1 hash of the document, which you can use for verification.

Type: String

Required: No

Status

The status of the SSM document.

Type: String

Valid Values: Creating | Active | Updating | Deleting | Failed

Required: No

StatusInformation

A message returned by AWS Systems Manager that explains the `Status` value. For example, a `Failed` status might be explained by the `StatusInformation` message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

Required: No

Tags

The tags, or metadata, that have been applied to the document.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

TargetType

The target type which defines the kinds of resources the document can run on. For example, `/AWS::EC2::Instance`. For a list of valid resource types, see [AWS resource and property types reference](#) in the *AWS CloudFormation User Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: `^[/\w\.\-\:/]*$`

Required: No

VersionName

The version of the artifact associated with the document.

Type: String

Pattern: `^[a-zA-Z0-9_\.]{1,128}$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentFilter

This data type is deprecated. Instead, use [DocumentKeyValuesFilter \(p. 664\)](#).

Contents

key

The name of the filter.

Type: String

Valid Values: Name | Owner | PlatformTypes | DocumentType

Required: Yes

value

The value of the filter.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentIdentifier

Describes the name of a SSM document.

Contents

Author

The user in your organization who created the document.

Type: String

Required: No

CreatedDate

The date the SSM document was created.

Type: Timestamp

Required: No

DisplayName

An optional field where you can specify a friendly name for the SSM document. This value can differ for each version of the document. If you want to update this value, see [UpdateDocument \(p. 518\)](#).

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/\]*\$

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: YAML | JSON | TEXT

Required: No

DocumentType

The document type.

Type: String

Valid Values: Command | Policy | Automation | Session | Package | ApplicationConfiguration | ApplicationConfigurationSchema | DeploymentStrategy | ChangeCalendar | Automation.ChangeTemplate | ProblemAnalysis | ProblemAnalysisTemplate

Required: No

DocumentVersion

The document version.

Type: String

Pattern: ([\$]LATEST | [\$]DEFAULT | ^[1-9][0-9]*\$)

Required: No

Name

The name of the SSM document.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

Required: No

Owner

The Amazon Web Services user account that created the document.

Type: String

Required: No

PlatformTypes

The operating system platform.

Type: Array of strings

Valid Values: Windows | Linux | MacOS

Required: No

Requires

A list of SSM documents required by a document. For example, an ApplicationConfiguration document requires an ApplicationConfigurationSchema document.

Type: Array of [DocumentRequires \(p. 668\)](#) objects

Array Members: Minimum number of 1 item.

Required: No

ReviewStatus

The current status of a document review.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

Required: No

SchemaVersion

The schema version.

Type: String

Pattern: ([0-9]+)\.([0-9]+)

Required: No

Tags

The tags, or metadata, that have been applied to the document.

Type: Array of [Tag \(p. 840\)](#) objects

Array Members: Maximum number of 1000 items.

Required: No

TargetType

The target type which defines the kinds of resources the document can run on. For example, /AWS::EC2::Instance. For a list of valid resource types, see [AWS resource and property types reference](#) in the *AWS CloudFormation User Guide*.

Type: String

Length Constraints: Maximum length of 200.

Pattern: ^\/[\w\.\-\:\:/]*\$

Required: No

VersionName

An optional field specifying the version of the artifact associated with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{1,128}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentKeyValuesFilter

One or more filters. Use a filter to return a more specific list of documents.

For keys, you can specify one or more tags that have been applied to a document.

You can also use AWS-provided keys, some of which have specific allowed values. These keys and their associated values are as follows:

DocumentType

- ApplicationConfiguration
- ApplicationConfigurationSchema
- Automation
- ChangeCalendar
- Command
- Package
- Policy
- Session

Owner

Note that only one Owner can be specified in a request. For example: Key=Owner,Values=Self.

- Amazon
- Private
- Public
- Self
- ThirdParty

PlatformTypes

- Linux
- Windows

Name is another AWS-provided key. If you use Name as a key, you can use a name prefix to return a list of documents. For example, in the AWS CLI, to return a list of all documents that begin with Te, run the following command:

```
aws ssm list-documents --filters Key=Name,Values=Te
```

You can also use the TargetType AWS-provided key. For a list of valid resource type values that can be used with this key, see [AWS resource and property types reference](#) in the *AWS CloudFormation User Guide*.

If you specify more than two keys, only documents that are identified by all the tags are returned in the results. If you specify more than two values for a key, documents that are identified by any of the values are returned in the results.

To specify a custom key-value pair, use the format Key=tag:tagName,Values=valueName.

For example, if you created a key called region and are using the AWS CLI to call the list-documents command:

```
aws ssm list-documents --filters Key=tag:region,Values=east,west  
Key=Owner,Values=Self
```

Contents

Key

The name of the filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The value for the filter key.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentMetadataResponseInfo

Details about the response to a document review request.

Contents

ReviewerResponse

Details about a reviewer's response to a document review request.

Type: Array of [DocumentReviewerResponseSource \(p. 670\)](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentParameter

Parameters specified in a System Manager document that run on the server when the command is run.

Contents

DefaultValue

If specified, the default values for the parameters. Parameters without a default value are required. Parameters with a default value are optional.

Type: String

Required: No

Description

A description of what the parameter does, how to use it, the default value, and whether or not the parameter is optional.

Type: String

Required: No

Name

The name of the parameter.

Type: String

Required: No

Type

The type of parameter. The type can be either String or StringList.

Type: String

Valid Values: String | StringList

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentRequires

An SSM document required by the current document.

Contents

Name

The name of the required SSM document. The name can be an Amazon Resource Name (ARN).

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

Required: Yes

Version

The document version required by the current document.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentReviewCommentSource

Information about comments added to a document review request.

Contents

Content

The content of a comment entered by a user who requests a review of a new document version, or who reviews the new version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: No

Type

The type of information added to a review request. Currently, only the value `Comment` is supported.

Type: String

Valid Values: `Comment`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentReviewerResponseSource

Information about a reviewer's response to a document review request.

Contents

Comment

The comment entered by a reviewer as part of their document review response.

Type: Array of [DocumentReviewCommentSource \(p. 669\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

CreateTime

The date and time that a reviewer entered a response to a document review request.

Type: Timestamp

Required: No

Reviewer

The user in your organization assigned to review a document request.

Type: String

Length Constraints: Maximum length of 50.

Pattern: ^[a-zA-Z0-9_\-.]{1,128}\$

Required: No

ReviewStatus

The current review status of a new custom SSM document created by a member of your organization, or of the latest version of an existing SSM document.

Only one version of a document can be in the APPROVED state at a time. When a new version is approved, the status of the previous version changes to REJECTED.

Only one version of a document can be in review, or PENDING, at a time.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

Required: No

UpdatedTime

The date and time that a reviewer last updated a response to a document review request.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentReviews

Information about a document approval review.

Contents

Action

The action to take on a document approval review request.

Type: String

Valid Values: `SendForReview` | `UpdateReview` | `Approve` | `Reject`

Required: Yes

Comment

A comment entered by a user in your organization about the document review request.

Type: Array of [DocumentReviewCommentSource \(p. 669\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DocumentVersionInfo

Version information about the document.

Contents

CreatedDate

The date the document was created.

Type: Timestamp

Required: No

DisplayName

The friendly name of the SSM document. This value can differ for each version of the document. If you want to update this value, see [UpdateDocument \(p. 518\)](#).

Type: String

Length Constraints: Maximum length of 1024.

Pattern: ^[\w\.\-\:\:/]*\$

Required: No

DocumentFormat

The document format, either JSON or YAML.

Type: String

Valid Values: YAML | JSON | TEXT

Required: No

DocumentVersion

The document version.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\$)

Required: No

IsDefaultVersion

An identifier for the default version of the document.

Type: Boolean

Required: No

Name

The document name.

Type: String

Pattern: ^[a-zA-Z0-9_\-.]{3,128}\$

Required: No

ReviewStatus

The current status of the approval review for the latest version of the document.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

Required: No

Status

The status of the SSM document, such as Creating, Active, Failed, and Deleting.

Type: String

Valid Values: Creating | Active | Updating | Deleting | Failed

Required: No

StatusInformation

A message returned by AWS Systems Manager that explains the Status value. For example, a Failed status might be explained by the StatusInformation message, "The specified S3 bucket doesn't exist. Verify that the URL of the S3 bucket is correct."

Type: String

Required: No

VersionName

The version of the artifact associated with the document. For example, "Release 12, Update 6". This value is unique across all versions of a document, and can't be changed.

Type: String

Pattern: ^[a-zA-Z0-9_\\-.]{1,128}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EffectivePatch

The `EffectivePatch` structure defines metadata about a patch along with the approval state of the patch in a particular patch baseline. The approval state includes information about whether the patch is currently approved, due to be approved by a rule, explicitly approved, or explicitly rejected and the date the patch was or will be approved.

Contents

Patch

Provides metadata for a patch, including information such as the KB ID, severity, classification and a URL for where more information can be obtained about the patch.

Type: [Patch \(p. 782\)](#) object

Required: No

PatchStatus

The status of the patch in a patch baseline. This includes information about whether the patch is currently approved, due to be approved by a rule, explicitly approved, or explicitly rejected and the date the patch was or will be approved.

Type: [PatchStatus \(p. 800\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedCreateAssociation

Describes a failed association.

Contents

Entry

The association.

Type: [CreateAssociationBatchRequestEntry \(p. 648\)](#) object

Required: No

Fault

The source of the failure.

Type: String

Valid Values: Client | Server | Unknown

Required: No

Message

A description of the failure.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailureDetails

Information about an Automation failure.

Contents

Details

Detailed information about the Automation step failure.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

FailureStage

The stage of the Automation execution when the failure occurred. The stages include the following: InputValidation, PreVerification, Invocation, PostVerification.

Type: String

Required: No

FailureType

The type of Automation failure. Failure types include the following: Action, Permission, Throttling, Verification, Internal.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAggregatedAssociationOverview

Status information about the aggregated associations.

Contents

DetailedStatus

Detailed status information about the aggregated associations.

Type: String

Required: No

InstanceAssociationStatusAggregatedCount

The number of associations for the managed node(s).

Type: String to integer map

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAssociation

One or more association documents on the managed node.

Contents

AssociationId

The association ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationVersion

Version information for the association on the managed node.

Type: String

Pattern: ([\\$]LATEST) | ([1-9][0-9]*)

Required: No

Content

The content of the association document for the managed node(s).

Type: String

Length Constraints: Minimum length of 1.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^\w{17}\$)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAssociationOutputLocation

An S3 bucket where you want to store the results of this request.

For the minimal permissions required to enable Amazon S3 output for an association, see [Creating associations](#) in the *Systems Manager User Guide*.

Contents

S3Location

An S3 bucket where you want to store the results of this request.

Type: [S3OutputLocation \(p. 824\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAssociationOutputUrl

The URL of S3 bucket where you want to store the results of this request.

Contents

S3OutputUrl

The URL of S3 bucket where you want to store the results of this request.

Type: [S3OutputUrl \(p. 825\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAssociationStatusInfo

Status information about the association.

Contents

AssociationId

The association ID.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: No

AssociationName

The name of the association applied to the managed node.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: No

AssociationVersion

The version of the association applied to the managed node.

Type: String

Pattern: ([\\$]LATEST) | ([1-9][0-9]*)

Required: No

DetailedStatus

Detailed status information about the association.

Type: String

Required: No

DocumentVersion

The association document versions.

Type: String

Pattern: ([\\$]LATEST | [\\$]DEFAULT | ^[1-9][0-9]*\$)

Required: No

ErrorCode

An error code returned by the request to create the association.

Type: String

Length Constraints: Maximum length of 10.

Required: No

ExecutionDate

The date the association ran.

Type: Timestamp

Required: No

ExecutionSummary

Summary information about association execution.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

InstanceId

The managed node ID where the association was created.

Type: String

Pattern: (^i-(\w{8}|\w{17}))\$|(^mi-\w{17}\$)

Required: No

Name

The name of the association.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

Required: No

OutputUrl

A URL for an S3 bucket where you want to store the results of this request.

Type: [InstanceAssociationOutputUrl \(p. 681\)](#) object

Required: No

Status

Status information about the association.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceInformation

Describes a filter for a specific list of managed nodes.

Contents

ActivationId

The activation ID created by AWS Systems Manager when the server or virtual machine (VM) was registered.

Type: String

Pattern: ^[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}\$

Required: No

AgentVersion

The version of SSM Agent running on your Linux managed node.

Type: String

Pattern: ^[0-9]{1,6}(\.[0-9]{1,6}){2,3}\$

Required: No

AssociationOverview

Information about the association.

Type: [InstanceAggregatedAssociationOverview \(p. 678\)](#) object

Required: No

AssociationStatus

The status of the association.

Type: String

Required: No

ComputerName

The fully qualified host name of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

IamRole

The AWS Identity and Access Management (IAM) role assigned to the on-premises Systems Manager managed node. This call doesn't return the IAM role for Amazon Elastic Compute Cloud (Amazon EC2) instances. To retrieve the IAM role for an EC2 instance, use the Amazon EC2 `DescribeInstances` operation. For information, see [DescribeInstances](#) in the *Amazon EC2 API Reference* or [describe-instances](#) in the *AWS CLI Command Reference*.

Type: String

Length Constraints: Maximum length of 64.

Required: No

InstanceId

The managed node ID.

Type: String

Pattern: (^i-(\w{8}|\w{17})\$)|(^mi-\w{17}\$)

Required: No

IPAddress

The IP address of the managed node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 46.

Required: No

IsLatestVersion

Indicates whether the latest version of SSM Agent is running on your Linux managed node. This field doesn't indicate whether or not the latest version is installed on Windows managed nodes, because some older versions of Windows Server use the EC2Config service to process Systems Manager requests.

Type: Boolean

Required: No

LastAssociationExecutionDate

The date the association was last run.

Type: Timestamp

Required: No

LastPingDateTime

The date and time when the agent last pinged the Systems Manager service.

Type: Timestamp

Required: No

LastSuccessfulAssociationExecutionDate

The last date the association was successfully run.

Type: Timestamp

Required: No

Name

The name assigned to an on-premises server, edge device, or virtual machine (VM) when it is activated as a Systems Manager managed node. The name is specified as the `DefaultInstanceName` property using the [CreateActivation \(p. 19\)](#) command. It is applied to the managed node by specifying the Activation Code and Activation ID when you install SSM Agent on the node, as explained in [Install SSM Agent for a hybrid environment \(Linux\)](#) and [Install SSM Agent for a hybrid environment \(Windows\)](#). To retrieve the Name tag of an EC2 instance, use the Amazon

EC2 `DescribeInstances` operation. For information, see [Describelnstances](#) in the *Amazon EC2 API Reference* or [describe-instances](#) in the *AWS CLI Command Reference*.

Type: String

Required: No

PingStatus

Connection status of SSM Agent.

Note

The status `Inactive` has been deprecated and is no longer in use.

Type: String

Valid Values: `Online` | `ConnectionLost` | `Inactive`

Required: No

PlatformName

The name of the operating system platform running on your managed node.

Type: String

Required: No

PlatformType

The operating system platform type.

Type: String

Valid Values: `Windows` | `Linux` | `MacOS`

Required: No

PlatformVersion

The version of the OS platform running on your managed node.

Type: String

Required: No

RegistrationDate

The date the server or VM was registered with AWS as a managed node.

Type: Timestamp

Required: No

ResourceType

The type of instance. Instances are either EC2 instances or managed instances.

Type: String

Valid Values: `ManagedInstance` | `Document` | `EC2Instance`

Required: No

SourceId

The ID of the source resource. For AWS IoT Greengrass devices, `SourceId` is the Thing name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: ^[a-zA-Z0-9:_-]*\$

Required: No

SourceType

The type of the source resource. For AWS IoT Greengrass devices, `SourceType` is `AWS::IoT::Thing`.

Type: String

Valid Values: `AWS::EC2::Instance` | `AWS::IoT::Thing` | `AWS::SSM::ManagedInstance`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceInformationFilter

Describes a filter for a specific list of managed nodes. You can filter node information by using tags. You specify tags by using a key-value mapping.

Use this operation instead of the [DescribeInstanceInformation:InstanceInformationFilterList \(p. 160\)](#) method. The `InstanceInformationFilterList` method is a legacy method and doesn't support tags.

Contents

key

The name of the filter.

Type: String

Valid Values: `InstanceIds` | `AgentVersion` | `PingStatus` | `PlatformTypes` | `ActivationIds` | `IamRole` | `ResourceType` | `AssociationStatus`

Required: Yes

valueSet

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceInformationStringFilter

The filters to describe or get information about your managed nodes.

Contents

Key

The filter key name to describe your managed nodes. For example:

"InstanceIds"|"AgentVersion"|"PingStatus"|"PlatformTypes"|"ActivationIds"|"IamRole"|"ResourceType"|"AssociationS
Key"

Important

Tag key isn't a valid filter. You must specify either tag-key or tag:keyname and a string. Here are some valid examples: tag-key, tag:123, tag:all, tag:Windows. Here are some *invalid* examples: tag-keys, Tag Key, tag:, tagKey, abc:keyname.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Values

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstancePatchState

Defines the high-level patch compliance state for a managed node, providing information about the number of installed, missing, not applicable, and failed patches along with metadata about the operation when this information was gathered for the managed node.

Contents

BaselineId

The ID of the patch baseline used to patch the managed node.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\-\:/]{20,128}\$

Required: Yes

CriticalNonCompliantCount

The number of managed nodes where patches that are specified as Critical for compliance reporting in the patch baseline aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is NON_COMPLIANT.

Type: Integer

Required: No

FailedCount

The number of patches from the patch baseline that were attempted to be installed during the last patching operation, but failed to install.

Type: Integer

Required: No

InstalledCount

The number of patches from the patch baseline that are installed on the managed node.

Type: Integer

Required: No

InstalledOtherCount

The number of patches not specified in the patch baseline that are installed on the managed node.

Type: Integer

Required: No

InstalledPendingRebootCount

The number of patches installed by Patch Manager since the last time the managed node was rebooted.

Type: Integer

Required: No

InstalledRejectedCount

The number of patches installed on a managed node that are specified in a `RejectedPatches` list. Patches with a status of `InstalledRejected` were typically installed before they were added to a `RejectedPatches` list.

Note

If `ALLOW_AS_DEPENDENCY` is the specified option for `RejectedPatchesAction`, the value of `InstalledRejectedCount` will always be 0 (zero).

Type: Integer

Required: No

InstallOverrideList

An https URL or an Amazon Simple Storage Service (Amazon S3) path-style URL to a list of patches to be installed. This patch installation list, which you maintain in an S3 bucket in YAML format and specify in the SSM document `AWS-RunPatchBaseline`, overrides the patches specified by the default patch baseline.

For more information about the `InstallOverrideList` parameter, see [About the AWS-RunPatchBaseline SSM document in the AWS Systems Manager User Guide](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^https://.+$|^s3://([^\/]+)/(.*?([^\/]+))$`

Required: No

InstanceId

The ID of the managed node the high-level patch compliance information was collected for.

Type: String

Pattern: `(^i-(\w{8}|\w{17})$)|(^\mi-\w{17}$)`

Required: Yes

LastNoRebootInstallOperationTime

The time of the last attempt to patch the managed node with `NoReboot` specified as the reboot option.

Type: Timestamp

Required: No

MissingCount

The number of patches from the patch baseline that are applicable for the managed node but aren't currently installed.

Type: Integer

Required: No

NotApplicableCount

The number of patches from the patch baseline that aren't applicable for the managed node and therefore aren't installed on the node. This number may be truncated if the list

of patch names is very large. The number of patches beyond this limit are reported in `UnreportedNotApplicableCount`.

Type: Integer

Required: No

Operation

The type of patching operation that was performed: or

- `SCAN` assesses the patch compliance state.
- `INSTALL` installs missing patches.

Type: String

Valid Values: `Scan` | `Install`

Required: Yes

OperationEndTime

The time the most recent patching operation completed on the managed node.

Type: Timestamp

Required: Yes

OperationStartTime

The time the most recent patching operation was started on the managed node.

Type: Timestamp

Required: Yes

OtherNonCompliantCount

The number of managed nodes with patches installed that are specified as other than `Critical` or `Security` but aren't compliant with the patch baseline. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

Required: No

OwnerInformation

Placeholder information. This field will always be empty in the current release of the service.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

PatchGroup

The name of the patch group the managed node belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}]\p{N}_.:=/+\\-@]*$`

Required: Yes

RebootOption

Indicates the reboot option specified in the patch baseline.

Note

Reboot options apply to `Install` operations only. Reboots aren't attempted for Patch Manager Scan operations.

- `RebootIfNeeded`: Patch Manager tries to reboot the managed node if it installed any patches, or if any patches are detected with a status of `InstalledPendingReboot`.
- `NoReboot`: Patch Manager attempts to install missing packages without trying to reboot the system. Patches installed with this option are assigned a status of `InstalledPendingReboot`. These patches might not be in effect until a reboot is performed.

Type: String

Valid Values: `RebootIfNeeded` | `NoReboot`

Required: No

SecurityNonCompliantCount

The number of managed nodes where patches that are specified as `Security` in a patch advisory aren't installed. These patches might be missing, have failed installation, were rejected, or were installed but awaiting a required managed node reboot. The status of these managed nodes is `NON_COMPLIANT`.

Type: Integer

Required: No

SnapshotId

The ID of the patch baseline snapshot used during the patching operation when this compliance data was collected.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}$`

Required: No

UnreportedNotApplicableCount

The number of patches beyond the supported limit of `NotApplicableCount` that aren't reported by name to Inventory. Inventory is a capability of AWS Systems Manager.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

InstancePatchStateFilter

Defines a filter used in [DescribeInstancePatchStatesForPatchGroup \(p. 173\)](#) to scope down the information returned by the API.

Example: To filter for all managed nodes in a patch group having more than three patches with a FailedCount status, use the following for the filter:

- Value for Key: FailedCount
- Value for Type: GreaterThan
- Value for Values: 3

Contents

Key

The key for the filter. Supported values include the following:

- InstalledCount
- InstalledOtherCount
- InstalledPendingRebootCount
- InstalledRejectedCount
- MissingCount
- FailedCount
- UnreportedNotApplicableCount
- NotApplicableCount

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Type

The type of comparison that should be performed for the value.

Type: String

Valid Values: Equal | NotEqual | LessThan | GreaterThan

Required: Yes

Values

The value for the filter. Must be an integer greater than or equal to 0.

Type: Array of strings

Array Members: Fixed number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryAggregator

Specifies the inventory type and attribute for the aggregation execution.

Contents

Aggregators

Nested aggregators to further refine aggregation for an inventory type.

Type: Array of [InventoryAggregator \(p. 698\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

Expression

The inventory type and attribute name for aggregation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

Groups

A user-defined set of one or more filters on which to aggregate inventory data. Groups return a count of resources that match and don't match the specified criteria.

Type: Array of [InventoryGroup \(p. 704\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 15 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryDeletionStatusItem

Status information returned by the `DeleteInventory` operation.

Contents

DeletionId

The deletion ID returned by the `DeleteInventory` operation.

Type: String

Pattern: [a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}

Required: No

DeletionStartTime

The UTC timestamp when the delete operation started.

Type: Timestamp

Required: No

DeletionSummary

Information about the delete operation. For more information about this summary, see [Understanding the delete inventory summary](#) in the *AWS Systems Manager User Guide*.

Type: [InventoryDeletionSummary \(p. 701\)](#) object

Required: No

LastStatus

The status of the operation. Possible values are `InProgress` and `Complete`.

Type: String

Valid Values: `InProgress` | `Complete`

Required: No

LastStatusMessage

Information about the status.

Type: String

Required: No

LastStatusUpdateTime

The UTC timestamp of when the last status report.

Type: Timestamp

Required: No

TypeName

The name of the inventory data type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryDeletionSummary

Information about the delete operation.

Contents

RemainingCount

Remaining number of items to delete.

Type: Integer

Required: No

SummaryItems

A list of counts and versions for deleted items.

Type: Array of [InventoryDeletionSummaryItem \(p. 702\)](#) objects

Required: No

TotalCount

The total number of items to delete. This count doesn't change during the delete operation.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryDeletionSummaryItem

Either a count, remaining count, or a version number in a delete inventory summary.

Contents

Count

A count of the number of deleted items.

Type: Integer

Required: No

RemainingCount

The remaining number of items to delete.

Type: Integer

Required: No

Version

The inventory type version.

Type: String

Pattern: ^([0-9]{1,6})(\.[0-9]{1,6})\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryFilter

One or more filters. Use a filter to return a more specific list of results.

Contents

Key

The name of the filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Type

The type of filter.

Note

The `Exists` filter must be used with aggregators. For more information, see [Aggregating inventory data](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `Equal` | `NotEqual` | `BeginWith` | `LessThan` | `GreaterThanOrEqual` | `Exists`

Required: No

Values

Inventory filter values. Example: inventory filter where managed node IDs are specified as values `Key=AWS:InstanceInformation.InstanceId,Values= i-a12b3c4d5e6g, i-1a2b3c4d5e6,Type=Equal`.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryGroup

A user-defined set of one or more filters on which to aggregate inventory data. Groups return a count of resources that match and don't match the specified criteria.

Contents

Filters

Filters define the criteria for the group. The `matchingCount` field displays the number of resources that match the criteria. The `notMatchingCount` field displays the number of resources that don't match the criteria.

Type: Array of [InventoryFilter \(p. 703\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Name

The name of the group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryItem

Information collected from managed nodes based on your inventory policy document

Contents

CaptureTime

The time the inventory information was collected.

Type: String

Pattern: ^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|0-1)[0-9](:[0-5][0-9])(:[0-5][0-9])(Z)\$

Required: Yes

Content

The inventory data of the inventory type.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

ContentHash

MD5 hash of the inventory item type contents. The content hash is used to determine whether to update inventory information. The PutInventory API doesn't update the inventory item type contents if the MD5 hash hasn't changed since last update.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Context

A map of associated properties for a specified inventory type. For example, with this attribute, you can specify the ExecutionId, ExecutionType, ComplianceType properties of the AWS :ComplianceItem type.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

SchemaVersion

The schema version for the inventory item.

Type: String

Pattern: ^([0-9]{1,6})(\.[0-9]{1,6})\$

Required: Yes

TypeName

The name of the inventory type. Default inventory item type names start with AWS. Custom inventory type names will start with Custom. Default inventory item types include the following: AWS:AWSComponent, AWS:Application, AWS:InstanceInformation, AWS:Network, and AWS:WindowsUpdate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS|Custom):.*\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryItemAttribute

Attributes are the entries within the inventory item content. It contains name and value.

Contents

DataType

The data type of the inventory item attribute.

Type: String

Valid Values: `string` | `number`

Required: Yes

Name

Name of the inventory item attribute.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryItemSchema

The inventory item schema definition. Users can use this to compose inventory query filters.

Contents

Attributes

The schema attributes for inventory. This contains data type and attribute name.

Type: Array of [InventoryItemAttribute \(p. 707\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

DisplayName

The alias name of the inventory type. The alias name is used for display purposes.

Type: String

Required: No

TypeName

The name of the inventory type. Default inventory item type names start with AWS. Custom inventory type names will start with Custom. Default inventory item types include the following: AWS:AWSComponent, AWS:Application, AWS:InstanceInformation, AWS:Network, and AWS:WindowsUpdate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : . *\$

Required: Yes

Version

The schema version for the inventory item.

Type: String

Pattern: ^([0-9]{1,6})(\.[0-9]{1,6})\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryResultEntity

Inventory query results.

Contents

Data

The data section in the inventory result entity JSON.

Type: String to [InventoryResultItem \(p. 710\)](#) object map

Required: No

Id

ID of the inventory result entity. For example, for managed node inventory the result will be the managed node ID. For EC2 instance inventory, the result will be the instance ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InventoryResultItem

The inventory result item.

Contents

CaptureTime

The time inventory item data was captured.

Type: String

Pattern: ^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|0-1)[0-9](:[0-5][0-9])(:[0-5][0-9])(Z)\$

Required: No

Content

Contains all the inventory data of the item type. Results include attribute names and values.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: Yes

ContentHash

MD5 hash of the inventory item type contents. The content hash is used to determine whether to update inventory information. The PutInventory API doesn't update the inventory item type contents if the MD5 hash hasn't changed since last update.

Type: String

Length Constraints: Maximum length of 256.

Required: No

SchemaVersion

The schema version for the inventory result item/

Type: String

Pattern: ^([0-9]{1,6})(\.[0-9]{1,6})\$

Required: Yes

TypeName

The name of the inventory result item type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoggingInfo

Information about an Amazon Simple Storage Service (Amazon S3) bucket to write managed node-level logs to.

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Contents

S3BucketName

The name of an S3 bucket where execution logs are stored .

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: Yes

S3KeyPrefix

(Optional) The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

S3Region

The AWS Region where the S3 bucket is located.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowAutomationParameters

The parameters for an AUTOMATION task type.

Contents

DocumentVersion

The version of an Automation runbook to use during task execution.

Type: String

Pattern: ([\\$]LATEST|[\\$]DEFAULT|^[1-9][0-9]*\\$)

Required: No

Parameters

The parameters for the AUTOMATION task.

For information about specifying and updating task parameters, see [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) and [UpdateMaintenanceWindowTask \(p. 541\)](#).

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

For AUTOMATION task types, AWS Systems Manager ignores any values specified for these parameters.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

MaintenanceWindowExecution

Describes the information about an execution of a maintenance window.

Contents

EndTime

The time the execution finished.

Type: Timestamp

Required: No

StartTime

The time the execution started.

Type: Timestamp

Required: No

Status

The status of the execution.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

Required: No

StatusDetails

The details explaining the status. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

WindowExecutionId

The ID of the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowExecutionTaskIdentity

Information about a task execution performed as part of a maintenance window execution.

Contents

EndTime

The time the task execution finished.

Type: Timestamp

Required: No

StartTime

The time the task execution started.

Type: Timestamp

Required: No

Status

The status of the task execution.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

Required: No

StatusDetails

The details explaining the status of the task execution. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

TaskArn

The Amazon Resource Name (ARN) of the task that ran.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

TaskExecutionId

The ID of the specific task execution in the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

TaskType

The type of task that ran.

Type: String

Valid Values: RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA

Required: No

WindowExecutionId

The ID of the maintenance window execution that ran the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowExecutionTaskInvocationIdentity

Describes the information about a task invocation for a particular target as part of a task execution performed as part of a maintenance window execution.

Contents

EndTime

The time the invocation finished.

Type: Timestamp

Required: No

ExecutionId

The ID of the action performed in the service that actually handled the task invocation. If the task type is RUN_COMMAND, this value is the command ID.

Type: String

Required: No

InvocationId

The ID of the task invocation.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

OwnerInformation

User-provided value that was specified when the target was registered with the maintenance window. This was also included in any Amazon CloudWatch Events events raised during the task invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Parameters

The parameters that were provided for the invocation when it was run.

Type: String

Required: No

StartTime

The time the invocation started.

Type: Timestamp

Required: No

Status

The status of the task invocation.

Type: String

Valid Values: PENDING | IN_PROGRESS | SUCCESS | FAILED | TIMED_OUT | CANCELLING | CANCELLED | SKIPPED_OVERLAPPING

Required: No

StatusDetails

The details explaining the status of the task invocation. Not available for all status values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

TaskExecutionId

The ID of the specific task execution in the maintenance window execution.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

TaskType

The task type.

Type: String

Valid Values: RUN_COMMAND | AUTOMATION | STEP_FUNCTIONS | LAMBDA

Required: No

WindowExecutionId

The ID of the maintenance window execution that ran the task.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

WindowTargetId

The ID of the target definition in this maintenance window the invocation was performed for.

Type: String

Length Constraints: Maximum length of 36.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowFilter

Filter used in the request. Supported filter keys depend on the API operation that includes the filter. API operations that use MaintenanceWindowFilter> include the following:

- [DescribeMaintenanceWindowExecutions \(p. 181\)](#)
- [DescribeMaintenanceWindowExecutionTaskInvocations \(p. 185\)](#)
- [DescribeMaintenanceWindowExecutionTasks \(p. 189\)](#)
- [DescribeMaintenanceWindows \(p. 193\)](#)
- [DescribeMaintenanceWindowTargets \(p. 204\)](#)
- [DescribeMaintenanceWindowTasks \(p. 208\)](#)

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The filter values.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowIdentity

Information about the maintenance window.

Contents

Cutoff

The number of hours before the end of the maintenance window that AWS Systems Manager stops scheduling new tasks for execution.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 23.

Required: No

Description

A description of the maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Duration

The duration of the maintenance window in hours.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 24.

Required: No

Enabled

Indicates whether the maintenance window is enabled.

Type: Boolean

Required: No

EndDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become inactive.

Type: String

Required: No

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

NextExecutionTime

The next time the maintenance window will actually run, taking into account any specified times for the maintenance window to become active or inactive.

Type: String

Required: No

Schedule

The schedule of the maintenance window in the form of a cron or rate expression.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

ScheduleOffset

The number of days to wait to run a maintenance window after the scheduled cron expression date and time.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 6.

Required: No

ScheduleTimezone

The time zone that the scheduled maintenance window executions are based on, in Internet Assigned Numbers Authority (IANA) format.

Type: String

Required: No

StartDate

The date and time, in ISO-8601 Extended format, for when the maintenance window is scheduled to become active.

Type: String

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowIdentityForTarget

The maintenance window to which the specified target belongs.

Contents

Name

The name of the maintenance window.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\.]{3,128}\$

Required: No

WindowId

The ID of the maintenance window.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowLambdaParameters

The parameters for a LAMBDA task type.

For information about specifying and updating task parameters, see [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) and [UpdateMaintenanceWindowTask \(p. 541\)](#).

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

For Lambda tasks, Systems Manager ignores any values specified for `TaskParameters` and `LoggingInfo`.

Contents

ClientContext

Pass client-specific information to the AWS Lambda function that you are invoking. You can then process the client information in your Lambda function as you choose through the `context` variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Required: No

Payload

JSON to provide to your Lambda function as input.

Type: Base64-encoded binary data object

Length Constraints: Maximum length of 4096.

Required: No

Qualifier

(Optional) Specify an Lambda function version or alias name. If you specify a function version, the operation uses the qualified function Amazon Resource Name (ARN) to invoke a specific Lambda function. If you specify an alias name, the operation uses the alias ARN to invoke the Lambda function version to which the alias points.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowRunCommandParameters

The parameters for a `RUN_COMMAND` task type.

For information about specifying and updating task parameters, see [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) and [UpdateMaintenanceWindowTask \(p. 541\)](#).

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

For `RUN_COMMAND` tasks, Systems Manager uses specified values for `TaskParameters` and `LoggingInfo` only if no values are specified for `TaskInvocationParameters`.

Contents

CloudWatchOutputConfig

Configuration options for sending command output to Amazon CloudWatch Logs.

Type: [CloudWatchOutputConfig \(p. 625\)](#) object

Required: No

Comment

Information about the commands to run.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DocumentHash

The SHA-256 or SHA-1 hash created by the system when the document was created. SHA-1 hashes have been deprecated.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DocumentHashType

SHA-256 or SHA-1. SHA-1 hashes have been deprecated.

Type: String

Valid Values: `Sha256` | `Sha1`

Required: No

DocumentVersion

The AWS Systems Manager document (SSM document) version to use in the request. You can specify `$DEFAULT`, `$LATEST`, or a specific version number. If you run commands by using the AWS CLI, then you must escape the first two options by using a backslash. If you specify a version number, then you don't need to use the backslash. For example:

```
--document-version "\$DEFAULT"  
--document-version "\$LATEST"  
--document-version "3"
```

Type: String

Pattern: (`[$]LATEST | [$]DEFAULT | ^[1-9][0-9]*$`)

Required: No

NotificationConfig

Configurations for sending notifications about command status changes on a per-managed node basis.

Type: [NotificationConfig \(p. 743\)](#) object

Required: No

OutputS3BucketName

The name of the Amazon Simple Storage Service (Amazon S3) bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

Parameters

The parameters for the `RUN_COMMAND` task execution.

Type: String to array of strings map

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for maintenance window Run Command tasks.

Type: String

Required: No

TimeoutSeconds

If this time is reached and the command hasn't already started running, it doesn't run.

Type: Integer

Valid Range: Minimum value of 30. Maximum value of 2592000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowStepFunctionsParameters

The parameters for a `STEP_FUNCTIONS` task.

For information about specifying and updating task parameters, see [RegisterTaskWithMaintenanceWindow \(p. 450\)](#) and [UpdateMaintenanceWindowTask \(p. 541\)](#).

Note

`LoggingInfo` has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

For Step Functions tasks, Systems Manager ignores any values specified for `TaskParameters` and `LoggingInfo`.

Contents

Input

The inputs for the `STEP_FUNCTIONS` task.

Type: String

Length Constraints: Maximum length of 4096.

Required: No

Name

The name of the `STEP_FUNCTIONS` task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowTarget

The target registered with the maintenance window.

Contents

Description

A description for the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

The name for the maintenance window target.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9\-_\.]{3,128}\$

Required: No

OwnerInformation

A user-provided value that will be included in any Amazon CloudWatch Events events that are raised while running tasks for these targets in this maintenance window.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

ResourceType

The type of target that is being registered with the maintenance window.

Type: String

Valid Values: INSTANCE | RESOURCE_GROUP

Required: No

Targets

The targets, either managed nodes or tags.

Specify managed nodes using the following format:

Key=instanceids,Values=<instanceid1>,<instanceid2>

Tags are specified using the following format:

Key=<tag name>,Values=<tag value>.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

WindowId

The ID of the maintenance window to register the target with.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

WindowTargetId

The ID of the target.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowTask

Information about a task defined for a maintenance window.

Contents

CutoffBehavior

The specification for whether tasks should continue to run after the cutoff time specified in the maintenance windows is reached.

Type: String

Valid Values: CONTINUE_TASK | CANCEL_TASK

Required: No

Description

A description of the task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

LoggingInfo

Information about an S3 bucket to write task-level logs to.

Note

LoggingInfo has been deprecated. To specify an Amazon Simple Storage Service (Amazon S3) bucket to contain logs, instead use the `OutputS3BucketName` and `OutputS3KeyPrefix` options in the `TaskInvocationParameters` structure. For information about how AWS Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: [LoggingInfo \(p. 712\)](#) object

Required: No

MaxConcurrency

The maximum number of targets this task can be run for, in parallel.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases. For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)\$

Required: No

MaxErrors

The maximum number of errors allowed before this task stops being scheduled.

Note

Although this element is listed as "Required: No", a value can be omitted only when you are registering or updating a [targetless task](#). You must provide a value in all other cases.

For maintenance window tasks without a target specified, you can't supply a value for this option. Instead, the system inserts a placeholder value of 1. This value doesn't affect the running of your task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%)\$

Required: No

Name

The task name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

Priority

The priority of the task in the maintenance window. The lower the number, the higher the priority. Tasks that have the same priority are scheduled in parallel.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

ServiceRoleArn

The Amazon Resource Name (ARN) of the AWS Identity and Access Management (IAM) service role to use to publish Amazon Simple Notification Service (Amazon SNS) notifications for maintenance window Run Command tasks.

Type: String

Required: No

Targets

The targets (either managed nodes or tags). Managed nodes are specified using Key=instanceids,Values=<instanceid1>,<instanceid2>. Tags are specified using Key=<tag name>,Values=<tag value>.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TaskArn

The resource that the task uses during execution. For `RUN_COMMAND` and `AUTOMATION` task types, `TaskArn` is the AWS Systems Manager (SSM document) name or ARN. For `LAMBDA` tasks, it's the function name or ARN. For `STEP_FUNCTIONS` tasks, it's the state machine ARN.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

TaskParameters

The parameters that should be passed to the task when it is run.

Note

`TaskParameters` has been deprecated. To specify parameters to pass to a task when it runs, instead use the `Parameters` option in the `TaskInvocationParameters` structure. For information about how Systems Manager handles these options for the supported maintenance window task types, see [MaintenanceWindowTaskInvocationParameters \(p. 739\)](#).

Type: String to [MaintenanceWindowTaskParameterValueExpression \(p. 740\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

Type

The type of task.

Type: String

Valid Values: `RUN_COMMAND` | `AUTOMATION` | `STEP_FUNCTIONS` | `LAMBDA`

Required: No

WindowId

The ID of the maintenance window where the task is registered.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

WindowTaskId

The task ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: ^[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowTaskInvocationParameters

The parameters for task execution.

Contents

Automation

The parameters for an AUTOMATION task type.

Type: [MaintenanceWindowAutomationParameters \(p. 713\)](#) object

Required: No

Lambda

The parameters for a LAMBDA task type.

Type: [MaintenanceWindowLambdaParameters \(p. 727\)](#) object

Required: No

RunCommand

The parameters for a RUN_COMMAND task type.

Type: [MaintenanceWindowRunCommandParameters \(p. 729\)](#) object

Required: No

StepFunctions

The parameters for a STEP_FUNCTIONS task type.

Type: [MaintenanceWindowStepFunctionsParameters \(p. 732\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MaintenanceWindowTaskParameterValueExpression

Defines the values for a task parameter.

Contents

Values

This field contains an array of 0 or more strings, each 1 to 255 characters in length.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MetadataValue

Metadata to assign to an Application Manager application.

Contents

Value

Metadata value to assign to an Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NonCompliantSummary

A summary of resources that aren't compliant. The summary is organized according to resource type.

Contents

NonCompliantCount

The total number of compliance items that aren't compliant.

Type: Integer

Required: No

SeveritySummary

A summary of the non-compliance severity by compliance type

Type: [SeveritySummary \(p. 833\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotificationConfig

Configurations for sending notifications.

Contents

NotificationArn

An Amazon Resource Name (ARN) for an Amazon Simple Notification Service (Amazon SNS) topic. Run Command pushes notifications about command status changes to this topic.

Type: String

Required: No

NotificationEvents

The different events for which you can receive notifications. To learn more about these events, see [Monitoring Systems Manager status changes using Amazon SNS notifications](#) in the *AWS Systems Manager User Guide*.

Type: Array of strings

Valid Values: All | InProgress | Success | TimedOut | Cancelled | Failed

Required: No

NotificationType

The type of notification.

- **Command:** Receive notification when the status of a command changes.
- **Invocation:** For commands sent to multiple managed nodes, receive notification on a per-node basis when the status of a command changes.

Type: String

Valid Values: Command | Invocation

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsAggregator

One or more aggregators for viewing counts of OpsData using different dimensions such as `Source`, `CreatedTime`, or `Source` and `CreatedTime`, to name a few.

Contents

Aggregators

A nested aggregator for viewing counts of OpsData.

Type: Array of [OpsAggregator \(p. 744\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 12 items.

Required: No

AggregatorType

Either a Range or Count aggregator for limiting an OpsData summary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Pattern: ^(`range` | `count` | `sum`)

Required: No

AttributeName

The name of an OpsData attribute on which to limit the count of OpsData.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Filters

The aggregator filters.

Type: Array of [OpsFilter \(p. 748\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

TypeName

The data type name to use for viewing counts of OpsData.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(`AWS` | `Custom`) : . *\$

Required: No

Values

The aggregator value.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 5 items.

Key Length Constraints: Minimum length of 1. Maximum length of 32.

Value Length Constraints: Minimum length of 0. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsEntity

The result of the query.

Contents

Data

The data returned by the query.

Type: String to [OpsEntityItem \(p. 747\)](#) object map

Required: No

Id

The query ID.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsEntityItem

The OpsData summary.

Contents

CaptureTime

The time the OpsData was captured.

Type: String

Pattern: ^(20)[0-9][0-9]-(0[1-9]|1[012])-([12][0-9]|3[01]|0[1-9])(T)(2[0-3]|0-1)[0-9](:[0-5][0-9]):[0-5][0-9])(Z)\$

Required: No

Content

The details of an OpsData summary.

Type: Array of string to string maps

Array Members: Minimum number of 0 items. Maximum number of 10000 items.

Map Entries: Minimum number of 0 items. Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Value Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsFilter

A filter for viewing OpsData summaries.

Contents

Key

The name of the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

Type

The type of filter.

Type: String

Valid Values: Equal | NotEqual | BeginWith | LessThan | GreaterThan | Exists

Required: No

Values

The filter value.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItem

Operations engineers and IT professionals use AWS Systems Manager OpsCenter to view, investigate, and remediate operational work items (OpsItems) impacting the performance and health of their AWS resources. OpsCenter is integrated with Amazon EventBridge and Amazon CloudWatch. This means you can configure these services to automatically create an OpsItem in OpsCenter when a CloudWatch alarm enters the ALARM state or when EventBridge processes an event from any AWS service that publishes events. Configuring Amazon CloudWatch alarms and EventBridge events to automatically create OpsItems allows you to quickly diagnose and remediate issues with AWS resources from a single console.

To help you diagnose issues, each OpsItem includes contextually relevant information such as the name and ID of the AWS resource that generated the OpsItem, alarm or event details, alarm history, and an alarm timeline graph. For the AWS resource, OpsCenter aggregates information from AWS Config, AWS CloudTrail logs, and EventBridge, so you don't have to navigate across multiple console pages during your investigation. For more information, see [OpsCenter](#) in the *AWS Systems Manager User Guide*.

Contents

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

Category

An OpsItem category. Category options include: Availability, Cost, Performance, Recovery, Security.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^(?!\\s*\$).+

Required: No

CreatedBy

The ARN of the AWS account that created the OpsItem.

Type: String

Required: No

CreatedTime

The date and time the OpsItem was created.

Type: Timestamp

Required: No

Description

The OpsItem description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: [\s\S]*\S[\s\S]*

Required: No

LastModifiedBy

The ARN of the AWS account that last updated the OpsItem.

Type: String

Required: No

LastModifiedTime

The date and time the OpsItem was last updated.

Type: Timestamp

Required: No

Notifications

The Amazon Resource Name (ARN) of an Amazon Simple Notification Service (Amazon SNS) topic where notifications are sent when this OpsItem is edited or changed.

Type: Array of [OpsItemNotification \(p. 759\)](#) objects

Required: No

OperationalData

Operational data is custom data that provides useful reference details about the OpsItem. For example, you can specify log files, error strings, license keys, troubleshooting tips, or other relevant data. You enter operational data as key-value pairs. The key has a maximum length of 128 characters. The value has a maximum size of 20 KB.

Important

Operational data keys *can't* begin with the following: amazon, aws, amzn, ssm, /amazon, /aws, /amzn, /ssm.

You can choose to make the data searchable by other users in the account or you can restrict search access. Searchable data means that all users with access to the OpsItem Overview page (as provided by the [DescribeOpsItems \(p. 213\)](#) API operation) can view and search on the specified data. Operational data that isn't searchable is only viewable by users who have access to the OpsItem (as provided by the [GetOpsItem \(p. 311\)](#) API operation).

Use the /aws/resources key in OperationalData to specify a related resource in the request. Use the /aws/automations key in OperationalData to associate an Automation runbook with the OpsItem. To view AWS CLI example commands that use these keys, see [Creating OpsItems manually](#) in the *AWS Systems Manager User Guide*.

Type: String to [OpsItemDataValue \(p. 753\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(?!\\s*$).+`

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: No

OpsItemType

The type of OpsItem. Currently, the only valid values are `/aws/changerequest` and `/aws/issue`.

Type: String

Required: No

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type `/aws/changerequest`.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

RelatedOpsItems

One or more OpsItems that share something in common with the current OpsItem. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Type: Array of [RelatedOpsItem \(p. 804\)](#) objects

Required: No

Severity

The severity of the OpsItem. Severity options range from 1 to 4.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\\s*\\$).+`

Required: No

Source

The origin of the OpsItem, such as Amazon EC2 or Systems Manager. The impacted resource is a subset of source.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\\s*\\$).+`

Required: No

Status

The OpsItem status. Status can be Open, In Progress, or Resolved. For more information, see [Editing OpsItem details](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Rejected | Closed

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*\\$).+`

Required: No

Version

The version of this OpsItem. Each time the OpsItem is edited the version number increments by one.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemDataValue

An object that defines the value of the key and its type in the OperationalData map.

Contents

Type

The type of key-value pair. Valid types include `SearchableString` and `String`.

Type: `String`

Valid Values: `SearchableString` | `String`

Required: No

Value

The value of the OperationalData key.

Type: `String`

Pattern: `[\s\S]*\S[\s\S]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemEventFilter

Describes a filter for a specific list of OpsItem events. You can filter event information by using tags. You specify tags by using a key-value pair mapping.

Contents

Key

The name of the filter key. Currently, the only supported value is `OpsItemId`.

Type: String

Valid Values: `OpsItemId`

Required: Yes

Operator

The operator used by the filter call. Currently, the only supported value is `Equal`.

Type: String

Valid Values: `Equal`

Required: Yes

Values

The values for the filter, consisting of one or more OpsItem IDs.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 15.

Pattern: `^(oi)-[0-9a-f]{12}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemEventSummary

Summary information about an OpsItem event or that associated an OpsItem with a related item.

Contents

CreatedBy

Information about the user or resource that created the OpsItem event.

Type: [OpsItemIdentity \(p. 758\)](#) object

Required: No

CreatedTime

The date and time the OpsItem event was created.

Type: Timestamp

Required: No

Detail

Specific information about the OpsItem event.

Type: String

Required: No

DetailType

The type of information provided as a detail.

Type: String

Required: No

EventId

The ID of the OpsItem event.

Type: String

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Required: No

Source

The source of the OpsItem event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemFilter

Describes an OpsItem filter.

Contents

Key

The name of the filter.

Type: String

Valid Values: Status | CreatedBy | Source | Priority | Title | OpsItemId
| CreatedTime | LastModifiedTime | ActualStartTime | ActualEndTime |
PlannedStartTime | PlannedEndTime | OperationalData | OperationalDataKey
| OperationalDataValue | ResourceId | AutomationId | Category | Severity
| OpsItemType | ChangeRequestByRequesterArn | ChangeRequestByRequesterName
| ChangeRequestByApproverArn | ChangeRequestByApproverName |
ChangeRequestByTemplate | ChangeRequestByTargetsResourceGroup |
InsightByType

Required: Yes

Operator

The operator used by the filter call.

Type: String

Valid Values: Equal | Contains | GreaterThan | LessThan

Required: Yes

Values

The filter value.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemIdentity

Information about the user or resource that created an OpsItem event.

Contents

Arn

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemNotification

A notification about the OpsItem.

Contents

Arn

The Amazon Resource Name (ARN) of an Amazon Simple Notification Service (Amazon SNS) topic where notifications are sent when this OpsItem is edited or changed.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemRelatedItemsFilter

Describes a filter for a specific list of related-item resources.

Contents

Key

The name of the filter key. Supported values include `ResourceUri`, `ResourceType`, or `AssociationId`.

Type: String

Valid Values: `ResourceType` | `AssociationId` | `ResourceUri`

Required: Yes

Operator

The operator used by the filter call. The only supported operator is `EQUAL`.

Type: String

Valid Values: `Equal`

Required: Yes

Values

The values for the filter.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemRelatedItemSummary

Summary information about related-item resources for an OpsItem.

Contents

AssociationId

The association ID.

Type: String

Required: No

AssociationType

The association type.

Type: String

Required: No

CreatedBy

Information about the user or resource that created an OpsItem event.

Type: [OpsItemIdentity \(p. 758\)](#) object

Required: No

CreatedTime

The time the related-item association was created.

Type: Timestamp

Required: No

LastModifiedBy

Information about the user or resource that created an OpsItem event.

Type: [OpsItemIdentity \(p. 758\)](#) object

Required: No

LastModifiedTime

The time the related-item association was last updated.

Type: Timestamp

Required: No

OpsItemId

The OpsItem ID.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: No

ResourceType

The resource type.

Type: String

Required: No

ResourceUri

The Amazon Resource Name (ARN) of the related-item resource.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsItemSummary

A count of OpsItems.

Contents

ActualEndTime

The time a runbook workflow ended. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

ActualStartTime

The time a runbook workflow started. Currently reported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

Category

A list of OpsItems by category.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^(?!\\s*\$).+

Required: No

CreatedBy

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem.

Type: String

Required: No

CreatedTime

The date and time the OpsItem was created.

Type: Timestamp

Required: No

LastModifiedBy

The Amazon Resource Name (ARN) of the IAM entity that created the OpsItem.

Type: String

Required: No

LastModifiedTime

The date and time the OpsItem was last updated.

Type: Timestamp

Required: No

OperationalData

Operational data is custom data that provides useful reference details about the OpsItem.

Type: String to [OpsItemDataValue \(p. 753\)](#) object map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^(?!\\s*\$).+

Required: No

OpsItemId

The ID of the OpsItem.

Type: String

Pattern: ^(oi)-[0-9a-f]{12}\$

Required: No

OpsItemType

The type of OpsItem. Currently, the only valid values are /aws/changerequest and /aws/issue.

Type: String

Required: No

PlannedEndTime

The time specified in a change request for a runbook workflow to end. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

PlannedStartTime

The time specified in a change request for a runbook workflow to start. Currently supported only for the OpsItem type /aws/changerequest.

Type: Timestamp

Required: No

Priority

The importance of this OpsItem in relation to other OpsItems in the system.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 5.

Required: No

Severity

A list of OpsItems by severity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^(?!\\s*$).+`

Required: No

Source

The impacted AWS resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\\s*$).+`

Required: No

Status

The OpsItem status. Status can be Open, In Progress, or Resolved.

Type: String

Valid Values: Open | InProgress | Resolved | Pending | TimedOut | Cancelling | Cancelled | Failed | CompletedWithSuccess | CompletedWithFailure | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | PendingApproval | Approved | Rejected | Closed

Required: No

Title

A short heading that describes the nature of the OpsItem and the impacted resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `^(?!\\s*$).+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsMetadata

Operational metadata for an application in Application Manager.

Contents

CreationDate

The date the OpsMetadata objects was created.

Type: Timestamp

Required: No

LastModifiedDate

The date the OpsMetadata object was last updated.

Type: Timestamp

Required: No

LastModifiedUser

The user name who last updated the OpsMetadata object.

Type: String

Required: No

OpsMetadataArn

The Amazon Resource Name (ARN) of the OpsMetadata Object or blob.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: arn:(aws[a-zA-Z-]*)?:ssm:[a-z0-9-\.]{0,63}:[a-z0-9-\.]{0,63}:opsmetadata\/([a-zA-Z0-9-_\.\/]*)

Required: No

ResourceId

The ID of the Application Manager application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^(?!s*\$).+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsMetadataFilter

A filter to limit the number of OpsMetadata objects displayed.

Contents

Key

A filter key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\\s*$).+`

Required: Yes

Values

A filter value.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OpsResultAttribute

The OpsItem data type to return.

Contents

TypeName

Name of the data type. Valid value: AWS:OpsItem, AWS:EC2InstanceInformation, AWS:OpsItemTrendline, or AWS:ComplianceSummary.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputSource

Information about the source where the association execution details are stored.

Contents

OutputSourceId

The ID of the output source, for example the URL of an S3 bucket.

Type: String

Length Constraints: Fixed length of 36.

Required: No

OutputSourceType

The type of source where the association execution details are stored, for example, Amazon S3.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Parameter

An AWS Systems Manager parameter in Parameter Store.

Contents

ARN

The Amazon Resource Name (ARN) of the parameter.

Type: String

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

LastModifiedDate

Date the parameter was last changed or updated and the parameter version was created.

Type: Timestamp

Required: No

Name

The name of the parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Selector

Either the version number or the label used to retrieve the parameter value. Specify selectors by using one of the following formats:

`parameter_name:version`

`parameter_name:label`

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

SourceResult

Applies to parameters that reference information in other AWS services. `SourceResult` is the raw result or response from the source.

Type: String

Required: No

Type

The type of parameter. Valid values include the following: `String`, `StringList`, and `SecureString`.

Note

If `type` is `StringList`, the system returns a comma-separated string with no spaces between commas in the `Value` field.

Type: `String`

Valid Values: `String` | `StringList` | `SecureString`

Required: No

Value

The parameter value.

Note

If `type` is `StringList`, the system returns a comma-separated string with no spaces between commas in the `Value` field.

Type: `String`

Required: No

Version

The parameter version.

Type: `Long`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParameterHistory

Information about parameter usage.

Contents

AllowedPattern

Parameter names can include the following letters and symbols.

a-zA-Z0-9_-.-

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description

Information about the parameter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId

The ID of the query key used for this parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([a-zA-Z0-9:/_-]+)\$

Required: No

Labels

Labels assigned to the parameter version.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

LastModifiedDate

Date the parameter was last changed or updated.

Type: `Timestamp`

Required: No

LastModifiedUser

Amazon Resource Name (ARN) of the Amazon Web Services user who last changed the parameter.

Type: `String`

Required: No

Name

The name of the parameter.

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Policies

Information about the policies assigned to a parameter.

[Assigning parameter policies](#) in the *AWS Systems Manager User Guide*.

Type: Array of [`ParameterInlinePolicy` \(p. 776\)](#) objects

Required: No

Tier

The parameter tier.

Type: `String`

Valid Values: `Standard` | `Advanced` | `Intelligent-Tiering`

Required: No

Type

The type of parameter used.

Type: `String`

Valid Values: `String` | `StringList` | `SecureString`

Required: No

Value

The parameter value.

Type: `String`

Required: No

Version

The parameter version.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParameterInlinePolicy

One or more policies assigned to a parameter.

Contents

PolicyStatus

The status of the policy. Policies report the following statuses: Pending (the policy hasn't been enforced or applied yet), Finished (the policy was applied), Failed (the policy wasn't applied), or InProgress (the policy is being applied now).

Type: String

Required: No

PolicyText

The JSON text of the policy.

Type: String

Required: No

PolicyType

The type of policy. Parameter Store, a capability of AWS Systems Manager, supports the following policy types: Expiration, ExpirationNotification, and NoChangeNotification.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParameterMetadata

Metadata includes information like the ARN of the last user and the date/time the parameter was last used.

Contents

AllowedPattern

A parameter name can include only the following letters and symbols.

a-zA-Z0-9_-

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

DataType

The data type of the parameter, such as `text` or `aws:ec2:image`. The default is `text`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Required: No

Description

Description of the parameter actions.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

KeyId

The ID of the query key used for this parameter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([a-zA-Z0-9:/_-]+)\$

Required: No

LastModifiedDate

Date the parameter was last changed or updated.

Type: Timestamp

Required: No

LastModifiedUser

Amazon Resource Name (ARN) of the Amazon Web Services user who last changed the parameter.

Type: String

Required: No

Name

The parameter name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Policies

A list of policies associated with a parameter.

Type: Array of [ParameterInlinePolicy \(p. 776\)](#) objects

Required: No

Tier

The parameter tier.

Type: String

Valid Values: Standard | Advanced | Intelligent-Tiering

Required: No

Type

The type of parameter. Valid parameter types include the following: String, StringList, and SecureString.

Type: String

Valid Values: String | StringList | SecureString

Required: No

Version

The parameter version.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParametersFilter

This data type is deprecated. Instead, use [ParameterStringFilter \(p. 780\)](#).

Contents

Key

The name of the filter.

Type: String

Valid Values: Name | Type | KeyId

Required: Yes

Values

The filter values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParameterStringFilter

One or more filters. Use a filter to return a more specific list of results.

Contents

Key

The name of the filter.

The `ParameterStringFilter` object is used by the [DescribeParameters \(p. 218\)](#) and [GetParametersByPath \(p. 333\)](#) API operations. However, not all of the pattern values listed for `Key` can be used with both operations.

For `DescribeParameters`, all of the listed patterns are valid except `Label`.

For `GetParametersByPath`, the following patterns listed for `Key` aren't valid: `tag`, `DataType`, `Name`, `Path`, and `Tier`.

For examples of AWS CLI commands demonstrating valid parameter filter constructions, see [Searching for Systems Manager parameters](#) in the *AWS Systems Manager User Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 132.

Pattern: `tag: .+ | Name | Type | KeyId | Path | Label | Tier | DataType`

Required: Yes

Option

For all filters used with [DescribeParameters \(p. 218\)](#), valid options include `Equals` and `BeginsWith`. The `Name` filter additionally supports the `Contains` option. (Exception: For filters using the key `Path`, valid options include `Recursive` and `OneLevel`.)

For filters used with [GetParametersByPath \(p. 333\)](#), valid options include `Equals` and `BeginsWith`. (Exception: For filters using `Label` as the Key name, the only valid option is `Equals`.)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Required: No

Values

The value you want to search for.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Patch

Represents metadata about a patch.

Contents

AdvisoryIds

The Advisory ID of the patch. For example, `RHSA-2020:3779`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Arch

The architecture of the patch. For example, in `example-pkg-0.710.10-2.7.abcd.x86_64`, the architecture is indicated by `x86_64`. Applies to Linux-based managed nodes only.

Type: String

Required: No

BugzillaIds

The Bugzilla ID of the patch. For example, `1600646`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Classification

The classification of the patch. For example, `SecurityUpdates`, `Updates`, or `CriticalUpdates`.

Type: String

Required: No

ContentUrl

The URL where more information can be obtained about the patch.

Type: String

Required: No

CVEIds

The Common Vulnerabilities and Exposures (CVE) ID of the patch. For example, `CVE-2011-3192`. Applies to Linux-based managed nodes only.

Type: Array of strings

Required: No

Description

The description of the patch.

Type: String

Required: No

Epoch

The epoch of the patch. For example in `pkg-example-EE-20180914-2.2.amzn1.noarch`, the epoch value is `20180914-2`. Applies to Linux-based managed nodes only.

Type: Integer

Required: No

Id

The ID of the patch. Applies to Windows patches only.

Note

This ID isn't the same as the Microsoft Knowledge Base ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

KbNumber

The Microsoft Knowledge Base ID of the patch. Applies to Windows patches only.

Type: String

Required: No

Language

The language of the patch if it's language-specific.

Type: String

Required: No

MsrcNumber

The ID of the Microsoft Security Response Center (MSRC) bulletin the patch is related to. For example, `MS14-045`. Applies to Windows patches only.

Type: String

Required: No

MsrcSeverity

The severity of the patch, such as `Critical`, `Important`, or `Moderate`. Applies to Windows patches only.

Type: String

Required: No

Name

The name of the patch. Applies to Linux-based managed nodes only.

Type: String

Required: No

Product

The specific product the patch is applicable for. For example, `WindowsServer2016` or `AmazonLinux2018.03`.

Type: String

Required: No

ProductFamily

The product family the patch is applicable for. For example, Windows or Amazon Linux 2.

Type: String

Required: No

Release

The particular release of a patch. For example, in `pkg-example-EE-20180914-2.2.amzn1.noarch`, the release is `2.amaz1`. Applies to Linux-based managed nodes only.

Type: String

Required: No

ReleaseDate

The date the patch was released.

Type: Timestamp

Required: No

Repository

The source patch repository for the operating system and version, such as `trusty-security` for Ubuntu Server 14.04 LTE and `focal-security` for Ubuntu Server 20.04 LTE. Applies to Linux-based managed nodes only.

Type: String

Required: No

Severity

The severity level of the patch. For example, CRITICAL or MODERATE.

Type: String

Required: No

Title

The title of the patch.

Type: String

Required: No

Vendor

The name of the vendor providing the patch.

Type: String

Required: No

Version

The version number of the patch. For example, in `example-pkg-1.710.10-2.7.abcd.x86_64`, the version number is indicated by `-1`. Applies to Linux-based managed nodes only.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchBaselineIdentity

Defines the basic information about a patch baseline.

Contents

BaselineDescription

The description of the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

BaselineId

The ID of the patch baseline.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-:/]{20,128}\$

Required: No

BaselineName

The name of the patch baseline.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

DefaultBaseline

Whether this is the default baseline. AWS Systems Manager supports creating multiple default patch baselines. For example, you can create a default patch baseline for each operating system.

Type: Boolean

Required: No

OperatingSystem

Defines the operating system the patch baseline applies to. The default value is WINDOWS.

Type: String

Valid Values: WINDOWS | AMAZON_LINUX | AMAZON_LINUX_2 | UBUNTU | REDHAT_ENTERPRISE_LINUX | SUSE | CENTOS | ORACLE_LINUX | DEBIAN | MACOS | RASPBIAN | ROCKY_LINUX

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchComplianceData

Information about the state of a patch on a particular managed node as it relates to the patch baseline used to patch the node.

Contents

Classification

The classification of the patch, such as `SecurityUpdates`, `Updates`, and `CriticalUpdates`.

Type: String

Required: Yes

CVEIds

The IDs of one or more Common Vulnerabilities and Exposure (CVE) issues that are resolved by the patch.

Type: String

Required: No

InstalledTime

The date/time the patch was installed on the managed node. Not all operating systems provide this level of information.

Type: Timestamp

Required: Yes

KBId

The operating system-specific ID of the patch.

Type: String

Required: Yes

Severity

The severity of the patch such as `Critical`, `Important`, and `Moderate`.

Type: String

Required: Yes

State

The state of the patch on the managed node, such as `INSTALLED` or `FAILED`.

For descriptions of each patch state, see [About patch compliance](#) in the *AWS Systems Manager User Guide*.

Type: String

Valid Values: `INSTALLED` | `INSTALLED_OTHER` | `INSTALLED_PENDING_REBOOT` |
`INSTALLED_REJECTED` | `MISSING` | `NOT_APPLICABLE` | `FAILED`

Required: Yes

Title

The title of the patch.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchFilter

Defines which patches should be included in a patch baseline.

A patch filter consists of a key and a set of values. The filter key is a patch property. For example, the available filter keys for WINDOWS are PATCH_SET, PRODUCT, PRODUCT_FAMILY, CLASSIFICATION, and MSRC_SEVERITY.

The filter values define a matching criterion for the patch property indicated by the key. For example, if the filter key is PRODUCT and the filter values are ["Office 2013", "Office 2016"], then the filter accepts all patches where product name is either "Office 2013" or "Office 2016". The filter values can be exact values for the patch property given as a key, or a wildcard (*), which matches all values.

You can view lists of valid values for the patch properties by running the [DescribePatchProperties](#) command. For information about which patch properties can be used with each major operating system, see [DescribePatchProperties \(p. 235\)](#).

Contents

Key

The key for the filter.

Run the [DescribePatchProperties \(p. 235\)](#) command to view lists of valid keys for each operating system type.

Type: String

Valid Values: ARCH | ADVISORY_ID | BUGZILLA_ID | PATCH_SET | PRODUCT | PRODUCT_FAMILY | CLASSIFICATION | CVE_ID | EPOCH | MSRC_SEVERITY | NAME | PATCH_ID | SECTION | PRIORITY | REPOSITORY | RELEASE | SEVERITY | SECURITY | VERSION

Required: Yes

Values

The value for the filter key.

Run the [DescribePatchProperties \(p. 235\)](#) command to view lists of valid values for each key based on operating system type.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

PatchFilterGroup

A set of patch filters, typically used for approval rules.

Contents

PatchFilters

The set of patch filters that make up the group.

Type: Array of [PatchFilter \(p. 790\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 4 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchGroupPatchBaselineMapping

The mapping between a patch group and the patch baseline the patch group is registered with.

Contents

BaselineIdentity

The patch baseline the patch group is registered with.

Type: [PatchBaselineIdentity \(p. 786\)](#) object

Required: No

PatchGroup

The name of the patch group registered with the patch baseline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchOrchestratorFilter

Defines a filter used in Patch Manager APIs. Supported filter keys depend on the API operation that includes the filter. Patch Manager API operations that use `PatchOrchestratorFilter` include the following:

- [DescribeAvailablePatches \(p. 134\)](#)
- [DescribeInstancePatches \(p. 165\)](#)
- [DescribePatchBaselines \(p. 223\)](#)
- [DescribePatchGroups \(p. 227\)](#)

Contents

Key

The key for the filter.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Values

The value for the filter.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchRule

Defines an approval rule for a patch baseline.

Contents

ApproveAfterDays

The number of days after the release date of each patch matched by the rule that the patch is marked as approved in the patch baseline. For example, a value of 7 means that patches are approved seven days after they are released. Not supported on Debian Server or Ubuntu Server.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 360.

Required: No

ApproveUntilDate

The cutoff date for auto approval of released patches. Any patches released on or before this date are installed automatically. Not supported on Debian Server or Ubuntu Server.

Enter dates in the format YYYY-MM-DD. For example, 2021-12-31.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Required: No

ComplianceLevel

A compliance severity level for all approved patches in a patch baseline.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

EnableNonSecurity

For managed nodes identified by the approval rule filters, enables a patch baseline to apply non-security updates available in the specified repository. The default value is `false`. Applies to Linux managed nodes only.

Type: Boolean

Required: No

PatchFilterGroup

The patch filter group that defines the criteria for the rule.

Type: [PatchFilterGroup \(p. 792\)](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchRuleGroup

A set of rules defining the approval rules for a patch baseline.

Contents

PatchRules

The rules that make up the rule group.

Type: Array of [PatchRule \(p. 795\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchSource

Information about the patches to use to update the managed nodes, including target operating systems and source repository. Applies to Linux managed nodes only.

Contents

Configuration

The value of the yum repo configuration. For example:

```
[main]  
  
name=MyCustomRepository  
  
baseurl=https://my-custom-repository  
  
enabled=1
```

Note

For information about other options available for your yum repository configuration, see [dnf.conf\(5\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

Name

The name specified to identify the patch source.

Type: String

Pattern: ^[a-zA-Z0-9_\.]{3,50}\$

Required: Yes

Products

The specific operating system versions a patch repository applies to, such as "Ubuntu16.04", "AmazonLinux2016.09", "RedhatEnterpriseLinux7.2" or "Suse12.7". For lists of supported product values, see [PatchFilter \(p. 790\)](#).

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PatchStatus

Information about the approval status of a patch.

Contents

ApprovalDate

The date the patch was approved (or will be approved if the status is PENDING_APPROVAL).

Type: Timestamp

Required: No

ComplianceLevel

The compliance severity level for a patch.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

DeploymentStatus

The approval status of a patch.

Type: String

Valid Values: APPROVED | PENDING_APPROVAL | EXPLICIT_APPROVED | EXPLICIT_REJECTED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProgressCounters

An aggregate of step execution statuses displayed in the AWS Systems Manager console for a multi-Region and multi-account Automation execution.

Contents

CancelledSteps

The total number of steps that the system cancelled in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

FailedSteps

The total number of steps that failed to run in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

SuccessSteps

The total number of steps that successfully completed in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

TimedOutSteps

The total number of steps that timed out in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

TotalSteps

The total number of steps run in all specified AWS Regions and AWS accounts for the current Automation execution.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

RegistrationMetadataItem

Reserved for internal use.

Contents

Key

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(?!\\s*$).+`

Required: Yes

Value

Reserved for internal use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^(?!\\s*$).+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RelatedOpsItem

An OpsItems that shares something in common with the current OpsItem. For example, related OpsItems can include OpsItems with similar error messages, impacted resources, or statuses for the impacted resource.

Contents

OpsItemId

The ID of an OpsItem related to the current OpsItem.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResolvedTargets

Information about targets that resolved during the Automation execution.

Contents

ParameterValues

A list of parameter values sent to targets that resolved during the Automation execution.

Type: Array of strings

Required: No

Truncated

A boolean value indicating whether the resolved target list is truncated.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceComplianceSummaryItem

Compliance summary information for a specific resource.

Contents

ComplianceType

The compliance type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: [A-Za-z0-9_\-]\w+ | Custom: [a-zA-Z0-9_\-]\w+

Required: No

CompliantSummary

A list of items that are compliant for the resource.

Type: [CompliantSummary \(p. 647\)](#) object

Required: No

ExecutionSummary

Information about the execution.

Type: [ComplianceExecutionSummary \(p. 640\)](#) object

Required: No

NonCompliantSummary

A list of items that aren't compliant for the resource.

Type: [NonCompliantSummary \(p. 742\)](#) object

Required: No

OverallSeverity

The highest severity item found for the resource. The resource is compliant for this item.

Type: String

Valid Values: CRITICAL | HIGH | MEDIUM | LOW | INFORMATIONAL | UNSPECIFIED

Required: No

ResourceId

The resource ID.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

ResourceType

The resource type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Status

The compliance status for the resource.

Type: String

Valid Values: COMPLIANT | NON_COMPLIANT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncAwsOrganizationsSource

Information about the `AwsOrganizationsSource` resource data sync source. A sync source of this type can synchronize data from AWS Organizations or, if an AWS organization isn't present, from multiple AWS Regions.

Contents

OrganizationalUnits

The AWS Organizations organization units included in the sync.

Type: Array of [ResourceDataSyncOrganizationalUnit \(p. 812\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

OrganizationSourceType

If an AWS organization is present, this is either `OrganizationalUnits` or `EntireOrganization`. For `OrganizationalUnits`, the data is aggregated from a set of organization units. For `EntireOrganization`, the data is aggregated from the entire AWS organization.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncDestinationDataSharing

Synchronize AWS Systems Manager Inventory data from multiple AWS accounts defined in AWS Organizations to a centralized Amazon S3 bucket. Data is synchronized to individual key prefixes in the central bucket. Each key prefix represents a different AWS account ID.

Contents

DestinationDataSharingType

The sharing data type. Only Organization is supported.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncItem

Information about a resource data sync configuration, including its current status and last successful sync.

Contents

LastStatus

The status reported by the last sync.

Type: String

Valid Values: Successful | Failed | InProgress

Required: No

LastSuccessfulSyncTime

The last time the sync operations returned a status of SUCCESSFUL (UTC).

Type: Timestamp

Required: No

LastSyncStatusMessage

The status message details reported by the last sync.

Type: String

Required: No

LastSyncTime

The last time the configuration attempted to sync (UTC).

Type: Timestamp

Required: No

S3Destination

Configuration information for the target S3 bucket.

Type: [ResourceDataSyncS3Destination \(p. 813\)](#) object

Required: No

SyncCreatedTime

The date and time the configuration was created (UTC).

Type: Timestamp

Required: No

SyncLastModifiedTime

The date and time the resource data sync was changed.

Type: Timestamp

Required: No

SyncName

The name of the resource data sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

SyncSource

Information about the source where the data was synchronized.

Type: [ResourceDataSyncSourceWithState \(p. 817\)](#) object

Required: No

SyncType

The type of resource data sync. If SyncType is SyncToDestination, then the resource data sync synchronizes data to an S3 bucket. If the SyncType is SyncFromSource then the resource data sync synchronizes data from AWS Organizations or from multiple AWS Regions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncOrganizationalUnit

The AWS Organizations organizational unit data source for the sync.

Contents

OrganizationalUnitId

The AWS Organizations unit ID data source for the sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^ou-[0-9a-z]{4,32}-[a-zA-Z0-9]{8,32}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncS3Destination

Information about the target S3 bucket for the resource data sync.

Contents

AWSKMSKeyARN

The ARN of an encryption key for a destination in Amazon S3. Must belong to the same Region as the destination S3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: `arn:.*`

Required: No

BucketName

The name of the S3 bucket where the aggregated data is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

DestinationDataSharing

Enables destination data sharing. By default, this field is `null`.

Type: [ResourceDataSyncDestinationDataSharing \(p. 809\)](#) object

Required: No

Prefix

An Amazon S3 prefix for the bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

Region

The AWS Region with the S3 bucket targeted by the resource data sync.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SyncFormat

A supported sync format. The following format is currently supported: `JsonSerDe`

Type: String

Valid Values: `JsonSerDe`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncSource

Information about the source of the data included in the resource data sync.

Contents

AwsOrganizationsSource

Information about the `AwsOrganizationsSource` resource data sync source. A sync source of this type can synchronize data from AWS Organizations.

Type: [ResourceDataSyncAwsOrganizationsSource \(p. 808\)](#) object

Required: No

EnableAllOpsDataSources

When you create a resource data sync, if you choose one of the AWS Organizations options, then Systems Manager automatically enables all OpsData sources in the selected AWS Regions for all AWS accounts in your organization (or in the selected organization units). For more information, see [About multiple account and Region resource data syncs](#) in the *AWS Systems Manager User Guide*.

Type: Boolean

Required: No

IncludeFutureRegions

Whether to automatically synchronize and aggregate data from new AWS Regions when those Regions come online.

Type: Boolean

Required: No

SourceRegions

The SyncSource AWS Regions included in the resource data sync.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

SourceType

The type of data source for the resource data sync. `SourceType` is either `AwsOrganizations` (if an organization is present in AWS Organizations) or `SingleAccountMultiRegions`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceDataSyncSourceWithState

The data type name for including resource data sync state. There are four sync states:

`OrganizationNotExists` (Your organization doesn't exist)

`NoPermissions` (The system can't locate the service-linked role. This role is automatically created when a user creates a resource data sync in AWS Systems Manager Explorer.)

`InvalidOrganizationalUnit` (You specified or selected an invalid unit in the resource data sync configuration.)

`TrustedAccessDisabled` (You disabled Systems Manager access in the organization in AWS Organizations.)

Contents

AwsOrganizationsSource

The field name in `SyncSource` for the `ResourceDataSyncAwsOrganizationsSource` type.

Type: [ResourceDataSyncAwsOrganizationsSource \(p. 808\)](#) object

Required: No

EnableAllOpsDataSources

When you create a resource data sync, if you choose one of the AWS Organizations options, then Systems Manager automatically enables all OpsData sources in the selected AWS Regions for all AWS accounts in your organization (or in the selected organization units). For more information, see [About multiple account and Region resource data syncs](#) in the *AWS Systems Manager User Guide*.

Type: Boolean

Required: No

IncludeFutureRegions

Whether to automatically synchronize and aggregate data from new AWS Regions when those Regions come online.

Type: Boolean

Required: No

SourceRegions

The `SyncSource` AWS Regions included in the resource data sync.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

SourceType

The type of data source for the resource data sync. `SourceType` is either `AwsOrganizations` (if an organization is present in AWS Organizations) or `singleAccountMultiRegions`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

State

The data type name for including resource data sync state. There are four sync states:

`OrganizationNotExists`: Your organization doesn't exist.

`NoPermissions`: The system can't locate the service-linked role. This role is automatically created when a user creates a resource data sync in Explorer.

`InvalidOrganizationalUnit`: You specified or selected an invalid unit in the resource data sync configuration.

`TrustedAccessDisabled`: You disabled Systems Manager access in the organization in AWS Organizations.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResultAttribute

The inventory item result attribute.

Contents

TypeName

Name of the inventory item type. Valid value: AWS:InstanceInformation. Default Value: AWS:InstanceInformation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(AWS | Custom) : .*\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReviewInformation

Information about the result of a document review request.

Contents

ReviewedTime

The time that the reviewer took action on the document review request.

Type: Timestamp

Required: No

Reviewer

The reviewer assigned to take action on the document review request.

Type: String

Length Constraints: Maximum length of 50.

Pattern: ^[a-zA-Z0-9_\\-.]{1,128}\$

Required: No

Status

The current status of the document review request.

Type: String

Valid Values: APPROVED | NOT_REVIEWED | PENDING | REJECTED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Runbook

Information about an Automation runbook used in a runbook workflow in Change Manager.

Note

The Automation runbooks specified for the runbook workflow can't run until all required approvals for the change request have been received.

Contents

DocumentName

The name of the Automation runbook used in a runbook workflow.

Type: String

Pattern: ^[a-zA-Z0-9_\.:/]{3,128}\$

Required: Yes

DocumentVersion

The version of the Automation runbook used in a runbook workflow.

Type: String

Pattern: ([\\$]LATEST|[\$]DEFAULT|^[\d]{1-9}[\d]{0-9}*\\$)

Required: No

MaxConcurrency

The MaxConcurrency value specified by the user when the operation started, indicating the maximum number of resources that the runbook operation can run on at the same time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([\d]{1-9}[\d]{0-9}*|[\d]{1-9}[\d]{0-9}%|[\d]{1-9}[%]|100%)\$

Required: No

MaxErrors

The MaxErrors value specified by the user when the execution started, indicating the maximum number of errors that can occur during the operation before the updates are stopped or rolled back.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([\d]{1-9}[\d]{0-9}*|[0]|[\d]{1-9}[\d]{0-9}%|[\d]{0-9}[%]|100%)\$

Required: No

Parameters

The key-value map of execution parameters, which were supplied when calling StartChangeRequestExecution.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

TargetLocations

Information about the AWS Regions and AWS accounts targeted by the current Runbook operation.

Type: Array of [TargetLocation \(p. 843\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

TargetMaps

A key-value mapping of runbook parameters to target resources. Both Targets and TargetMaps can't be specified together.

Type: Array of string to array of strings maps

Array Members: Minimum number of 0 items. Maximum number of 300 items.

Map Entries: Maximum number of 20 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

TargetParameterName

The name of the parameter used as the target resource for the rate-controlled runbook workflow.
Required if you specify Targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

Targets

A key-value mapping to target resources that the runbook operation performs tasks on. Required if you specify TargetParameterName.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3OutputLocation

An S3 bucket where you want to store the results of this request.

Contents

OutputS3BucketName

The name of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: No

OutputS3KeyPrefix

The S3 bucket subfolder.

Type: String

Length Constraints: Maximum length of 500.

Required: No

OutputS3Region

The AWS Region of the S3 bucket.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 20.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3OutputUrl

A URL for the AWS Systems Manager (Systems Manager) bucket where you want to store the results of this request.

Contents

OutputUrl

A URL for an S3 bucket where you want to store the results of this request.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduledWindowExecution

Information about a scheduled execution for a maintenance window.

Contents

ExecutionTime

The time, in ISO-8601 Extended format, that the maintenance window is scheduled to be run.

Type: String

Required: No

Name

The name of the maintenance window to be run.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_\\-.]{3,128}\$

Required: No

WindowId

The ID of the maintenance window to be run.

Type: String

Length Constraints: Fixed length of 20.

Pattern: ^mw-[0-9a-f]{17}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSetting

The service setting data structure.

ServiceSetting is an account-level setting for an AWS service. This setting defines how a user interacts with or uses a service or a feature of a service. For example, if an AWS service charges money to the account based on feature or service usage, then the AWS service team might create a default setting of "false". This means the user can't use this feature unless they change the setting to "true" and intentionally opt in for a paid feature.

Services map a **SettingId** object to a setting value. AWS services teams define the default value for a **SettingId**. You can't create a new **SettingId**, but you can overwrite the default value if you have the `ssm:UpdateServiceSetting` permission for the setting. Use the [UpdateServiceSetting \(p. 575\)](#) API operation to change the default setting. Or, use the [ResetServiceSetting \(p. 461\)](#) to change the value back to the original value defined by the AWS service team.

Contents

ARN

The ARN of the service setting.

Type: String

Required: No

LastModifiedDate

The last time the service setting was modified.

Type: Timestamp

Required: No

LastModifiedUser

The ARN of the last modified user. This field is populated only if the setting value was overwritten.

Type: String

Required: No

SettingId

The ID of the service setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

SettingValue

The value of the service setting.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: No

Status

The status of the service setting. The value can be Default, Customized or PendingUpdate.

- Default: The current setting uses a default value provisioned by the AWS service team.
- Customized: The current setting uses a custom value specified by the customer.
- PendingUpdate: The current setting uses a default or custom value, but a setting change request is pending approval.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Session

Information about a Session Manager connection to a managed node.

Contents

Details

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

DocumentName

The name of the Session Manager SSM document used to define the parameters and plugin settings for the session. For example, `SSM-SessionManagerRunShell`.

Type: String

Pattern: `^[a-zA-Z0-9_\\-.]{3,128}$`

Required: No

EndDate

The date and time, in ISO-8601 Extended format, when the session was terminated.

Type: Timestamp

Required: No

MaxSessionDuration

The maximum duration of a session before it terminates.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 4.

Pattern: `^([1-9]|([1-9][0-9]|([1-9][0-9][0-9][0-9])|1[0-4][0-3][0-9]|1440)$`

Required: No

OutputUrl

Reserved for future use.

Type: [SessionManagerOutputUrl \(p. 832\)](#) object

Required: No

Owner

The ID of the Amazon Web Services user account that started the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

Reason

The reason for connecting to the instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^.{1,256}\$

Required: No

SessionId

The ID of the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 96.

Required: No

StartDate

The date and time, in ISO-8601 Extended format, when the session began.

Type: Timestamp

Required: No

Status

The status of the session. For example, "Connected" or "Terminated".

Type: String

Valid Values: Connected | Connecting | Disconnected | Terminated | Terminating | Failed

Required: No

Target

The managed node that the Session Manager session connected to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionFilter

Describes a filter for Session Manager information.

Contents

key

The name of the filter.

Type: String

Valid Values: `InvokedAfter` | `InvokedBefore` | `Target` | `Owner` | `Status` | `SessionId`

Required: Yes

value

The filter value. Valid values for each filter key are as follows:

- `InvokedAfter`: Specify a timestamp to limit your results. For example, specify `2018-08-29T00:00:00Z` to see sessions that started August 29, 2018, and later.
- `InvokedBefore`: Specify a timestamp to limit your results. For example, specify `2018-08-29T00:00:00Z` to see sessions that started before August 29, 2018.
- `Target`: Specify a managed node to which session connections have been made.
- `Owner`: Specify an Amazon Web Services user account to see a list of sessions started by that user.
- `Status`: Specify a valid session status to see a list of all sessions with that status. Status values you can specify include:
 - `Connected`
 - `Connecting`
 - `Disconnected`
 - `Terminated`
 - `Terminating`
 - `Failed`
- `SessionId`: Specify a session ID to return details about the session.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 400.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SessionManagerOutputUrl

Reserved for future use.

Contents

CloudWatchOutputUrl

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2083.

Required: No

S3OutputUrl

Reserved for future use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2083.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SeveritySummary

The number of managed nodes found for each patch severity level defined in the request filter.

Contents

CriticalCount

The total number of resources or compliance items that have a severity level of critical. Critical severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

HighCount

The total number of resources or compliance items that have a severity level of high. High severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

InformationalCount

The total number of resources or compliance items that have a severity level of informational. Informational severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

LowCount

The total number of resources or compliance items that have a severity level of low. Low severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

MediumCount

The total number of resources or compliance items that have a severity level of medium. Medium severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

UnspecifiedCount

The total number of resources or compliance items that have a severity level of unspecified. Unspecified severity is determined by the organization that published the compliance items.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StepExecution

Detailed information about an the execution state of an Automation step.

Contents

Action

The action this step performs. The action determines the behavior of the step.

Type: String

Pattern: ^aws:[a-zA-Z]{3,25}\$

Required: No

ExecutionEndTime

If a step has finished execution, this contains the time the execution ended. If the step hasn't yet concluded, this field isn't populated.

Type: Timestamp

Required: No

ExecutionStartTime

If a step has begun execution, this contains the time the step started. If the step is in Pending status, this field isn't populated.

Type: Timestamp

Required: No

FailureDetails

Information about the Automation failure.

Type: [FailureDetails \(p. 677\)](#) object

Required: No

FailureMessage

If a step failed, this message explains why the execution failed.

Type: String

Required: No

Inputs

Fully-resolved values passed into the step before execution.

Type: String to string map

Required: No

IsCritical

The flag which can be used to help decide whether the failure of current step leads to the Automation failure.

Type: Boolean

Required: No

IsEnd

The flag which can be used to end automation no matter whether the step succeeds or fails.

Type: Boolean

Required: No

MaxAttempts

The maximum number of tries to run the action of the step. The default value is 1.

Type: Integer

Required: No

NextStep

The next step after the step succeeds.

Type: String

Required: No

OnFailure

The action to take if the step fails. The default value is Abort.

Type: String

Required: No

Outputs

Returned values from the execution of the step.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

OverriddenParameters

A user-specified list of parameters to override when running a step.

Type: String to array of strings map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 50.

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Response

A message associated with the response code for an execution.

Type: String

Required: No

ResponseCode

The response code returned by the execution of the step.

Type: String

Required: No

StepExecutionId

The unique ID of a step execution.

Type: String

Required: No

StepName

The name of this execution step.

Type: String

Required: No

StepStatus

The execution status for this step.

Type: String

Valid Values: Pending | InProgress | Waiting | Success | TimedOut | Cancelling | Cancelled | Failed | PendingApproval | Approved | Rejected | Scheduled | RunbookInProgress | PendingChangeCalendarOverride | ChangeCalendarOverrideApproved | ChangeCalendarOverrideRejected | CompletedWithSuccess | CompletedWithFailure

Required: No

TargetLocation

The combination of AWS Regions and AWS accounts targeted by the current Automation execution.

Type: [TargetLocation \(p. 843\)](#) object

Required: No

Targets

The targets for the step execution.

Type: Array of [Target \(p. 841\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

TimeoutSeconds

The timeout seconds of the step.

Type: Long

Required: No

ValidNextSteps

Strategies used when step fails, we support Continue and Abort. Abort will fail the automation when the step fails. Continue will ignore the failure of current step and allow automation to run the next step. With conditional branching, we add step:stepName to support the automation to go to another specific step.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StepExecutionFilter

A filter to limit the amount of step execution information returned by the call.

Contents

Key

One or more keys to limit the results. Valid filter keys include the following: StepName, Action, StepExecutionId, StepExecutionStatus, StartTimeBefore, StartTimeAfter.

Type: String

Valid Values: StartTimeBefore | StartTimeAfter | StepExecutionStatus | StepExecutionId | StepName | Action

Required: Yes

Values

The values of the filter key.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 150.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Metadata that you assign to your AWS resources. Tags enable you to categorize your resources in different ways, for example, by purpose, owner, or environment. In AWS Systems Manager, you can apply tags to Systems Manager documents (SSM documents), managed nodes, maintenance windows, parameters, patch baselines, OpsItems, and OpsMetadata.

Contents

Key

The name of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)$`

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Target

An array of search criteria that targets managed nodes using a key-value pair that you specify.

Note

One or more targets must be specified for maintenance window Run Command-type tasks. Depending on the task, targets are optional for other maintenance window task types (Automation, AWS Lambda, and AWS Step Functions). For more information about running tasks that don't specify targets, see [Registering maintenance window tasks without targets](#) in the *AWS Systems Manager User Guide*.

Supported formats include the following.

- **Key=InstanceIds,Values=<instance-id-1>,<instance-id-2>,<instance-id-3>**
- **Key=tag:<my-tag-key>,Values=<my-tag-value-1>,<my-tag-value-2>**
- **Key=tag-key,Values=<my-tag-key-1>,<my-tag-key-2>**
- **Run Command and Maintenance window targets only:** **Key=resource-groups:Name,Values=<resource-group-name>**
- **Maintenance window targets only:** **Key=resource-groups:ResourceTypeFilters,Values=<resource-type-1>,<resource-type-2>**
- **Automation targets only:** **Key=ResourceGroup;Values=<resource-group-name>**

For example:

- **Key=InstanceIds,Values=i-02573cafefEXAMPLE,i-0471e04240EXAMPLE,i-07782c72faEXAMPLE**
- **Key=tag:CostCenter,Values=CostCenter1,CostCenter2,CostCenter3**
- **Key=tag-key,Values=Name,Instance-Type,CostCenter**
- **Run Command and Maintenance window targets only:** **Key=resource-groups:Name,Values=ProductionResourceGroup**

This example demonstrates how to target all resources in the resource group **ProductionResourceGroup** in your maintenance window.

- **Maintenance window targets only:** **Key=resource-groups:ResourceTypeFilters,Values=AWS::EC2::INSTANCE,AWS::EC2::VPC**

This example demonstrates how to target only Amazon Elastic Compute Cloud (Amazon EC2) instances and VPCs in your maintenance window.

- **Automation targets only:** **Key=ResourceGroup,Values=MyResourceGroup**
- **State Manager association targets only:** **Key=InstanceIds,Values=***

This example demonstrates how to target all managed instances in the AWS Region where the association was created.

For more information about how to send commands that target managed nodes using **Key**, **Value** parameters, see [Targeting multiple instances](#) in the *AWS Systems Manager User Guide*.

Contents

Key

User-defined criteria for sending commands that target managed nodes that meet the criteria.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 163.

Pattern: ^[\p{L}\p{Z}\p{N}_.:=/-\@]*\$ | resource-groups:ResourceTypeFilters | resource-groups:Name

Required: No

Values

User-defined criteria that maps to Key. For example, if you specified tag:ServerRole, you could specify value:WebServer to run a command on instances that include EC2 tags of ServerRole,WebServer.

Depending on the type of target, the maximum number of values for a key might be lower than the global maximum of 50.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetLocation

The combination of AWS Regions and AWS accounts targeted by the current Automation execution.

Contents

Accounts

The AWS accounts targeted by the current Automation execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

ExecutionRoleName

The Automation execution role used by the currently running Automation. If not specified, the default value is `AWS-SystemsManager-AutomationExecutionRole`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\w+=, .@/-]+

Required: No

Regions

The AWS Regions targeted by the current Automation execution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

TargetLocationMaxConcurrency

The maximum number of AWS Regions and AWS accounts allowed to run the Automation concurrently.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[1-9][0-9]%|[1-9]%^|100%)\$

Required: No

TargetLocationMaxErrors

The maximum number of errors allowed before the system stops queueing additional Automation executions for the currently running Automation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 7.

Pattern: ^([1-9][0-9]*|[0]| [1-9][0-9]%|[0-9]%^|100%)\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/service/aws4_request*.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400