
AWS Single Sign-On

API Reference



AWS Single Sign-On: API Reference

Copyright © Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AttachManagedPolicyToPermissionSet	3
Request Syntax	3
Request Parameters	3
Response Elements	4
Errors	4
See Also	4
CreateAccountAssignment	6
Request Syntax	6
Request Parameters	6
Response Syntax	7
Response Elements	8
Errors	8
See Also	9
CreateInstanceAccessControlAttributeConfiguration	10
Request Syntax	10
Request Parameters	10
Response Elements	10
Errors	11
See Also	11
CreatePermissionSet	12
Request Syntax	12
Request Parameters	12
Response Syntax	13
Response Elements	13
Errors	14
See Also	14
DeleteAccountAssignment	16
Request Syntax	16
Request Parameters	16
Response Syntax	17
Response Elements	17
Errors	18
See Also	18
DeleteInlinePolicyFromPermissionSet	20
Request Syntax	20
Request Parameters	20
Response Elements	20
Errors	20
See Also	21
DeleteInstanceAccessControlAttributeConfiguration	22
Request Syntax	22
Request Parameters	22
Response Elements	22
Errors	22
See Also	23
DeletePermissionSet	24
Request Syntax	24
Request Parameters	24
Response Elements	24
Errors	24
See Also	25
DescribeAccountAssignmentCreationStatus	26

Request Syntax	26
Request Parameters	26
Response Syntax	26
Response Elements	27
Errors	27
See Also	27
DescribeAccountAssignmentDeletionStatus	29
Request Syntax	29
Request Parameters	29
Response Syntax	29
Response Elements	30
Errors	30
See Also	30
DescribeInstanceAccessControlAttributeConfiguration	32
Request Syntax	32
Request Parameters	32
Response Syntax	32
Response Elements	32
Errors	33
See Also	33
DescribePermissionSet	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	36
Errors	36
See Also	36
DescribePermissionSetProvisioningStatus	38
Request Syntax	38
Request Parameters	38
Response Syntax	38
Response Elements	39
Errors	39
See Also	39
DetachManagedPolicyFromPermissionSet	41
Request Syntax	41
Request Parameters	41
Response Elements	42
Errors	42
See Also	42
GetInlinePolicyForPermissionSet	44
Request Syntax	44
Request Parameters	44
Response Syntax	44
Response Elements	44
Errors	45
See Also	45
ListAccountAssignmentCreationStatus	47
Request Syntax	47
Request Parameters	47
Response Syntax	48
Response Elements	48
Errors	48
See Also	49
ListAccountAssignmentDeletionStatus	50
Request Syntax	50
Request Parameters	50

Response Syntax	51
Response Elements	51
Errors	51
See Also	52
ListAccountAssignments	53
Request Syntax	53
Request Parameters	53
Response Syntax	54
Response Elements	54
Errors	55
See Also	55
ListAccountsForProvisionedPermissionSet	56
Request Syntax	56
Request Parameters	56
Response Syntax	57
Response Elements	57
Errors	57
See Also	58
ListInstances	59
Request Syntax	59
Request Parameters	59
Response Syntax	59
Response Elements	59
Errors	60
See Also	60
ListManagedPoliciesInPermissionSet	62
Request Syntax	62
Request Parameters	62
Response Syntax	63
Response Elements	63
Errors	63
See Also	64
ListPermissionSetProvisioningStatus	65
Request Syntax	65
Request Parameters	65
Response Syntax	66
Response Elements	66
Errors	66
See Also	67
ListPermissionSets	68
Request Syntax	68
Request Parameters	68
Response Syntax	69
Response Elements	69
Errors	69
See Also	70
ListPermissionSetsProvisionedToAccount	71
Request Syntax	71
Request Parameters	71
Response Syntax	72
Response Elements	72
Errors	73
See Also	73
ListTagsForResource	74
Request Syntax	74
Request Parameters	74
Response Syntax	75

Response Elements	75
Errors	75
See Also	76
ProvisionPermissionSet	77
Request Syntax	77
Request Parameters	77
Response Syntax	78
Response Elements	78
Errors	78
See Also	79
PutInlinePolicyToPermissionSet	80
Request Syntax	80
Request Parameters	80
Response Elements	81
Errors	81
See Also	81
TagResource	83
Request Syntax	83
Request Parameters	83
Response Elements	84
Errors	84
See Also	84
UntagResource	86
Request Syntax	86
Request Parameters	86
Response Elements	87
Errors	87
See Also	87
UpdateInstanceAccessControlAttributeConfiguration	89
Request Syntax	89
Request Parameters	89
Response Elements	89
Errors	90
See Also	90
UpdatePermissionSet	91
Request Syntax	91
Request Parameters	91
Response Elements	92
Errors	92
See Also	93
Data Types	94
AccessControlAttribute	95
Contents	95
See Also	95
AccessControlAttributeValue	96
Contents	96
See Also	96
AccountAssignment	97
Contents	97
See Also	98
AccountAssignmentOperationStatus	99
Contents	99
See Also	100
AccountAssignmentOperationStatusMetadata	101
Contents	101
See Also	101
AttachedManagedPolicy	102

Contents	102
See Also	102
InstanceAccessControlAttributeConfiguration	103
Contents	103
See Also	103
InstanceMetadata	104
Contents	104
See Also	104
OperationStatusFilter	105
Contents	105
See Also	105
PermissionSet	106
Contents	106
See Also	107
PermissionSetProvisioningStatus	108
Contents	108
See Also	109
PermissionSetProvisioningStatusMetadata	110
Contents	110
See Also	110
Tag	111
Contents	111
See Also	111
Common Parameters	112
Common Errors	114
Document History	116

Welcome to the AWS Single Sign-On API Reference Guide

AWS Single Sign-On (SSO) is a cloud SSO service that makes it easy to centrally manage SSO access to multiple AWS accounts and business applications. This guide provides information on SSO operations which could be used for access management of AWS accounts. For information about AWS SSO features, see the [AWS Single Sign-On User Guide](#).

Many operations in the AWS SSO APIs rely on identifiers for users and groups, known as principals. For more information about how to work with principals and principal IDs in AWS SSO, see the [AWS SSO Identity Store API Reference](#).

Note

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, and more). The SDKs provide a convenient way to create programmatic access to AWS SSO and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

Actions

The following actions are supported:

- [AttachManagedPolicyToPermissionSet](#) (p. 3)
- [CreateAccountAssignment](#) (p. 6)
- [CreateInstanceAccessControlAttributeConfiguration](#) (p. 10)
- [CreatePermissionSet](#) (p. 12)
- [DeleteAccountAssignment](#) (p. 16)
- [DeleteInlinePolicyFromPermissionSet](#) (p. 20)
- [DeleteInstanceAccessControlAttributeConfiguration](#) (p. 22)
- [DeletePermissionSet](#) (p. 24)
- [DescribeAccountAssignmentCreationStatus](#) (p. 26)
- [DescribeAccountAssignmentDeletionStatus](#) (p. 29)
- [DescribeInstanceAccessControlAttributeConfiguration](#) (p. 32)
- [DescribePermissionSet](#) (p. 35)
- [DescribePermissionSetProvisioningStatus](#) (p. 38)
- [DetachManagedPolicyFromPermissionSet](#) (p. 41)
- [GetInlinePolicyForPermissionSet](#) (p. 44)
- [ListAccountAssignmentCreationStatus](#) (p. 47)
- [ListAccountAssignmentDeletionStatus](#) (p. 50)
- [ListAccountAssignments](#) (p. 53)
- [ListAccountsForProvisionedPermissionSet](#) (p. 56)
- [ListInstances](#) (p. 59)
- [ListManagedPoliciesInPermissionSet](#) (p. 62)
- [ListPermissionSetProvisioningStatus](#) (p. 65)
- [ListPermissionSets](#) (p. 68)
- [ListPermissionSetsProvisionedToAccount](#) (p. 71)
- [ListTagsForResource](#) (p. 74)
- [ProvisionPermissionSet](#) (p. 77)
- [PutInlinePolicyToPermissionSet](#) (p. 80)
- [TagResource](#) (p. 83)
- [UntagResource](#) (p. 86)
- [UpdateInstanceAccessControlAttributeConfiguration](#) (p. 89)
- [UpdatePermissionSet](#) (p. 91)

AttachManagedPolicyToPermissionSet

Attaches an IAM managed policy ARN to a permission set.

Note

If the permission set is already referenced by one or more account assignments, you will need to call [ProvisionPermissionSet](#) (p. 77) after this operation. Calling [ProvisionPermissionSet](#) applies the corresponding IAM policy updates to all assigned accounts.

Request Syntax

```
{
  "InstanceArn": "string",
  "ManagedPolicyArn": "string",
  "PermissionSetArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 3)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

ManagedPolicyArn (p. 3)

The IAM managed policy ARN to be attached to a permission set.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

PermissionSetArn (p. 3)

The ARN of the [PermissionSet](#) (p. 106) that the managed policy should be attached to.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAccountAssignment

Assigns access to a principal for a specified AWS account using a specified permission set.

Note

The term *principal* here refers to a user or group that is defined in AWS SSO.

Note

As part of a successful `CreateAccountAssignment` call, the specified permission set will automatically be provisioned to the account in the form of an IAM policy. That policy is attached to the SSO-created IAM role. If the permission set is subsequently updated, the corresponding IAM policies attached to roles in your accounts will not be updated automatically. In this case, you must call `ProvisionPermissionSet` (p. 77) to make these updates.

Request Syntax

```
{
  "InstanceArn": "string",
  "PermissionSetArn": "string",
  "PrincipalId": "string",
  "PrincipalType": "string",
  "TargetId": "string",
  "TargetType": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 6)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

PermissionSetArn (p. 6)

The ARN of the permission set that the admin wants to grant the principal access to.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-]{16}/ps-[a-zA-Z0-9-]{16}`

Required: Yes

PrincipalId (p. 6)

An identifier for an object in AWS SSO, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in AWS SSO, see the [AWS SSO Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `^([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}$`

Required: Yes

PrincipalType (p. 6)

The entity type for which the assignment will be created.

Type: String

Valid Values: `USER` | `GROUP`

Required: Yes

TargetId (p. 6)

TargetID is an AWS account identifier, typically a 10-12 digit string (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: Yes

TargetType (p. 6)

The entity type for which the assignment will be created.

Type: String

Valid Values: `AWS_ACCOUNT`

Required: Yes

Response Syntax

```
{
  "AccountAssignmentCreationStatus": {
    "CreateDate": number,
    "FailureReason": "string",
    "PermissionSetArn": "string",
    "PrincipalId": "string",
    "PrincipalType": "string",
    "RequestId": "string",
    "Status": "string",
    "TargetId": "string",
    "TargetType": "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentCreationStatus (p. 7)

The status object for the account assignment creation operation.

Type: [AccountAssignmentOperationStatus](#) (p. 99) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateInstanceAccessControlAttributeConfiguration

Enables the attributes-based access control (ABAC) feature for the specified AWS SSO instance. You can also specify new attributes to add to your ABAC configuration during the enabling process. For more information about ABAC, see [Attribute-Based Access Control](#) in the *AWS SSO User Guide*.

Request Syntax

```
{
  "InstanceAccessControlAttributeConfiguration": {
    "AccessControlAttributes": [
      {
        "Key": "string",
        "Value": {
          "Source": [ "string" ]
        }
      }
    ]
  },
  "InstanceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceAccessControlAttributeConfiguration (p. 10)

Specifies the AWS SSO identity store attributes to add to your ABAC configuration. When using an external identity provider as an identity source, you can pass attributes through the SAML assertion. Doing so provides an alternative to configuring attributes from the AWS SSO identity store. If a SAML assertion passes any of these attributes, AWS SSO will replace the attribute value with the value from the AWS SSO identity store.

Type: [InstanceAccessControlAttributeConfiguration](#) (p. 103) object

Required: Yes

InstanceArn (p. 10)

The ARN of the SSO instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePermissionSet

Creates a permission set within a specified SSO instance.

Note

To grant users and groups access to AWS account resources, use [CreateAccountAssignment \(p. 6\)](#).

Request Syntax

```
{
  "Description": "string",
  "InstanceArn": "string",
  "Name": "string",
  "RelayState": "string",
  "SessionDuration": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

Description (p. 12)

The description of the [PermissionSet \(p. 106\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: `[\u0009\u000A\u000D\u0020-\u007E\u00A0-\u00FF]*`

Required: No

InstanceArn (p. 12)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Name (p. 12)

The name of the [PermissionSet \(p. 106\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [\w+=, .@-]+

Required: Yes

RelayState (p. 12)

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: [a-zA-Z0-9&\$@#\\\/%?=-~_'"|!:,.;*+\[\\\ \(\)\{\}\}]+

Required: No

SessionDuration (p. 12)

The length of time that the application user sessions are valid in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(-?)P(?:=\d|T\d)(?:\d+Y)?(?:\d+M)?(?:\d+([DW]))?(?:T(?:\d+H)?(?:\d+M)?(?:\d+(?:\.\d+)?)S)?)?\$

Required: No

Tags (p. 12)

The tags to attach to the new [PermissionSet \(p. 106\)](#).

Type: Array of [Tag \(p. 111\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
{
  "PermissionSet": {
    "CreateDate": number,
    "Description": string,
    "Name": string,
    "PermissionSetArn": string,
    "RelayState": string,
    "SessionDuration": string
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[PermissionSet \(p. 13\)](#)

Defines the level of access on an AWS account.

Type: [PermissionSet \(p. 106\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAccountAssignment

Deletes a principal's access from a specified AWS account using a specified permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "PermissionSetArn": "string",  
  "PrincipalId": "string",  
  "PrincipalType": "string",  
  "TargetId": "string",  
  "TargetType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 16)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn (p. 16)

The ARN of the permission set that will be used to remove access.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

PrincipalId (p. 16)

An identifier for an object in AWS SSO, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in AWS SSO, see the [AWS SSO Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `^([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}$`

Required: Yes

PrincipalType (p. 16)

The entity type for which the assignment will be deleted.

Type: String

Valid Values: USER | GROUP

Required: Yes

TargetId (p. 16)

TargetID is an AWS account identifier, typically a 10-12 digit string (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: Yes

TargetType (p. 16)

The entity type for which the assignment will be deleted.

Type: String

Valid Values: AWS_ACCOUNT

Required: Yes

Response Syntax

```
{
  "AccountAssignmentDeletionStatus": {
    "CreateDate": number,
    "FailureReason": "string",
    "PermissionSetArn": "string",
    "PrincipalId": "string",
    "PrincipalType": "string",
    "RequestId": "string",
    "Status": "string",
    "TargetId": "string",
    "TargetType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentDeletionStatus (p. 17)

The status object for the account assignment deletion operation.

Type: [AccountAssignmentOperationStatus](#) (p. 99) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteInlinePolicyFromPermissionSet

Deletes the inline policy from a specified permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 20)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

PermissionSetArn (p. 20)

The ARN of the permission set that will be used to remove access.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-]{16}/ps-[a-zA-Z0-9-./]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteInstanceAccessControlAttributeConfiguration

Disables the attributes-based access control (ABAC) feature for the specified AWS SSO instance and deletes all of the attribute mappings that have been configured. Once deleted, any attributes that are received from an identity source and any custom attributes you have previously configured will not be passed. For more information about ABAC, see [Attribute-Based Access Control](#) in the *AWS SSO User Guide*.

Request Syntax

```
{  
  "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 22)

The ARN of the SSO instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePermissionSet

Deletes the specified permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 24)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

PermissionSetArn (p. 24)

The ARN of the permission set that should be deleted.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-]{16}/ps-[a-zA-Z0-9-./]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAccountAssignmentCreationStatus

Describes the status of the assignment creation request.

Request Syntax

```
{  
  "AccountAssignmentCreationRequestId": "string",  
  "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

[AccountAssignmentCreationRequestId](#) (p. 26)

The identifier that is used to track the request operation progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: Yes

[InstanceArn](#) (p. 26)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{  
  "AccountAssignmentCreationStatus": {  
    "CreateDate": number,  
    "FailureReason": "string",  
    "PermissionSetArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string",  
    "RequestId": "string",  
    "Status": "string",  
  }  
}
```

```
    "TargetId": "string",  
    "TargetType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentCreationStatus (p. 26)

The status object for the account assignment creation operation.

Type: [AccountAssignmentOperationStatus](#) (p. 99) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAccountAssignmentDeletionStatus

Describes the status of the assignment deletion request.

Request Syntax

```
{  
  "AccountAssignmentDeletionRequestId": "string",  
  "InstanceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

[AccountAssignmentDeletionRequestId](#) (p. 29)

The identifier that is used to track the request operation progress.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: Yes

[InstanceArn](#) (p. 29)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{  
  "AccountAssignmentDeletionStatus": {  
    "CreateDate": number,  
    "FailureReason": "string",  
    "PermissionSetArn": "string",  
    "PrincipalId": "string",  
    "PrincipalType": "string",  
    "RequestId": "string",  
    "Status": "string",  
  }  
}
```

```
    "TargetId": "string",  
    "TargetType": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentDeletionStatus (p. 29)

The status object for the account assignment deletion operation.

Type: [AccountAssignmentOperationStatus](#) (p. 99) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeInstanceAccessControlAttributeConfiguration

Returns the list of AWS SSO identity store attributes that have been configured to work with attributes-based access control (ABAC) for the specified AWS SSO instance. This will not return attributes configured and sent by an external identity provider. For more information about ABAC, see [Attribute-Based Access Control](#) in the *AWS SSO User Guide*.

Request Syntax

```
{
  "InstanceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 32)

The ARN of the SSO instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{
  "InstanceAccessControlAttributeConfiguration": {
    "AccessControlAttributes": [
      {
        "Key": "string",
        "Value": {
          "Source": [ "string" ]
        }
      }
    ]
  },
  "Status": "string",
  "StatusReason": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[InstanceAccessControlAttributeConfiguration \(p. 32\)](#)

Gets the list of AWS SSO identity store attributes that have been added to your ABAC configuration.

Type: [InstanceAccessControlAttributeConfiguration \(p. 103\)](#) object

[Status \(p. 32\)](#)

The status of the attribute configuration process.

Type: String

Valid Values: `ENABLED` | `CREATION_IN_PROGRESS` | `CREATION_FAILED`

[StatusReason \(p. 32\)](#)

Provides more details about the current status of the specified attribute.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePermissionSet

Gets the details of the permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 35)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn (p. 35)

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{  
  "PermissionSet": {  
    "CreateDate": number,  
    "Description": "string",  
    "Name": "string",  
    "PermissionSetArn": "string",  
    "RelayState": "string",  
    "SessionDuration": "string"  
  }  
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PermissionSet (p. 35)

Describes the level of access on an AWS account.

Type: [PermissionSet](#) (p. 106) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePermissionSetProvisioningStatus

Describes the status for the given permission set provisioning request.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "ProvisionPermissionSetRequestId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 38)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

ProvisionPermissionSetRequestId (p. 38)

The identifier that is provided by the [ProvisionPermissionSet](#) (p. 77) call to retrieve the current status of the provisioning workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: Yes

Response Syntax

```
{  
  "PermissionSetProvisioningStatus": {  
    "AccountId": "string",  
    "CreateDate": number,  
    "FailureReason": "string",  
    "PermissionSetArn": "string",  
    "RequestId": "string",  
    "Status": "string"  
  }  
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PermissionSetProvisioningStatus (p. 38)

The status object for the permission set provisioning operation.

Type: [PermissionSetProvisioningStatus](#) (p. 108) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DetachManagedPolicyFromPermissionSet

Detaches the attached IAM managed policy ARN from the specified permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "ManagedPolicyArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 41)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

ManagedPolicyArn (p. 41)

The IAM managed policy ARN to be detached from a permission set.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

PermissionSetArn (p. 41)

The ARN of the [PermissionSet](#) (p. 106) from which the policy should be detached.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetInlinePolicyForPermissionSet

Obtains the inline policy assigned to the permission set.

Request Syntax

```
{
  "InstanceArn": "string",
  "PermissionSetArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 44)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

PermissionSetArn (p. 44)

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-]{16}/ps-[a-zA-Z0-9-./]{16}`

Required: Yes

Response Syntax

```
{
  "InlinePolicy": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

InlinePolicy (p. 44)

The IAM inline policy that is attached to the permission set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10240.

Pattern: [\u0009\u000A\u000D\u0020-\u00FF]+

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListAccountAssignmentCreationStatus

Lists the status of the AWS account assignment creation requests for a specified SSO instance.

Request Syntax

```
{
  "Filter": {
    "Status": "string"
  },
  "InstanceArn": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

Filter (p. 47)

Filters results based on the passed attribute value.

Type: [OperationStatusFilter \(p. 105\)](#) object

Required: No

InstanceArn (p. 47)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

MaxResults (p. 47)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 47)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

Required: No

Response Syntax

```
{
  "AccountAssignmentsCreationStatus": [
    {
      "CreatedDate": number,
      "RequestId": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentsCreationStatus (p. 48)

The status object for the account assignment creation operation.

Type: Array of [AccountAssignmentOperationStatusMetadata \(p. 101\)](#) objects

NextToken (p. 48)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccountAssignmentDeletionStatus

Lists the status of the AWS account assignment deletion requests for a specified SSO instance.

Request Syntax

```
{
  "Filter": {
    "Status": "string"
  },
  "InstanceArn": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

Filter (p. 50)

Filters results based on the passed attribute value.

Type: [OperationStatusFilter \(p. 105\)](#) object

Required: No

InstanceArn (p. 50)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

MaxResults (p. 50)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 50)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

Required: No

Response Syntax

```
{
  "AccountAssignmentsDeletionStatus": [
    {
      "CreateDate": number,
      "RequestId": "string",
      "Status": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignmentsDeletionStatus (p. 51)

The status object for the account assignment deletion operation.

Type: Array of [AccountAssignmentOperationStatusMetadata \(p. 101\)](#) objects

NextToken (p. 51)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccountAssignments

Lists the assignee of the specified AWS account with the specified permission set.

Request Syntax

```
{  
  "AccountId": "string",  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

AccountId (p. 53)

The identifier of the AWS account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

InstanceArn (p. 53)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}

Required: Yes

MaxResults (p. 53)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 53)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+/_]*`

Required: No

PermissionSetArn (p. 53)

The ARN of the permission set from which to list assignments.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{
  "AccountAssignments": [
    {
      "AccountId": "string",
      "PermissionSetArn": "string",
      "PrincipalId": "string",
      "PrincipalType": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountAssignments (p. 54)

The list of assignments that match the input AWS account and permission set.

Type: Array of [AccountAssignment \(p. 97\)](#) objects

NextToken (p. 54)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[a-zA-Z0-9+/_]*`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccountsForProvisionedPermissionSet

Lists all the AWS accounts where the specified permission set is provisioned.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "PermissionSetArn": "string",  
  "ProvisioningStatus": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 56)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults (p. 56)

The maximum number of results to display for the [PermissionSet](#) (p. 106).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 56)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[a-zA-Z0-9+/_]*`

Required: No

PermissionSetArn (p. 56)

The ARN of the [PermissionSet](#) (p. 106) from which the associated AWS accounts will be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

ProvisioningStatus (p. 56)

The permission set provisioning status for an AWS account.

Type: String

Valid Values: `LATEST_PERMISSION_SET_PROVISIONED` | `LATEST_PERMISSION_SET_NOT_PROVISIONED`

Required: No

Response Syntax

```
{
  "AccountIds": [ "string" ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountIds (p. 57)

The list of AWS `AccountIds`.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

NextToken (p. 57)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+ =/_]*`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListInstances

Lists the SSO instances that the caller has access to.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 59)

The maximum number of results to display for the instance.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 59)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+=/_]*`

Required: No

Response Syntax

```
{
  "Instances": [
    {
      "IdentityStoreId": "string",
      "InstanceArn": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Instances (p. 59)

Lists the SSO instances that the caller has access to.

Type: Array of [InstanceMetadata \(p. 104\)](#) objects

NextToken (p. 59)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+ =/_]*`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedPoliciesInPermissionSet

Lists the IAM managed policy that is attached to a specified permission set.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

InstanceArn (p. 62)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

MaxResults (p. 62)

The maximum number of results to display for the [PermissionSet \(p. 106\)](#).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 62)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+/_]*`

Required: No

PermissionSetArn (p. 62)

The ARN of the [PermissionSet \(p. 106\)](#) whose managed policies will be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

Response Syntax

```
{
  "AttachedManagedPolicies": [
    {
      "Arn": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AttachedManagedPolicies (p. 63)

The array of the [AttachedManagedPolicy \(p. 102\)](#) data type object.

Type: Array of [AttachedManagedPolicy \(p. 102\)](#) objects

NextToken (p. 63)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[a-zA-Z0-9+/_]*`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissionSetProvisioningStatus

Lists the status of the permission set provisioning requests for a specified SSO instance.

Request Syntax

```
{
  "Filter": {
    "Status": "string"
  },
  "InstanceArn": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

Filter (p. 65)

Filters results based on the passed attribute value.

Type: [OperationStatusFilter \(p. 105\)](#) object

Required: No

InstanceArn (p. 65)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

MaxResults (p. 65)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 65)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+/_]*`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "PermissionSetsProvisioningStatus": [
    {
      "CreatedDate": number,
      "RequestId": "string",
      "Status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 66)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+/_]*`

PermissionSetsProvisioningStatus (p. 66)

The status object for the permission set provisioning operation.

Type: Array of [PermissionSetProvisioningStatusMetadata](#) (p. 110) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissionSets

Lists the [PermissionSet](#) (p. 106)s in an SSO instance.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 68)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

MaxResults (p. 68)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 68)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+/_]*`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "PermissionSets": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 69)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

PermissionSets (p. 69)

Defines the level of access on an AWS account.

Type: Array of strings

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[-a-zA-Z0-9-.]{16}/ps-[-a-zA-Z0-9-.]{16}

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 114).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissionSetsProvisionedToAccount

Lists all the permission sets that are provisioned to a specified AWS account.

Request Syntax

```
{  
  "AccountId": "string",  
  "InstanceArn": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "ProvisioningStatus": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

AccountId (p. 71)

The identifier of the AWS account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Required: Yes

InstanceArn (p. 71)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}

Required: Yes

MaxResults (p. 71)

The maximum number of results to display for the assignment.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 71)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+ = / _] *`

Required: No

ProvisioningStatus (p. 71)

The status object for the permission set provisioning operation.

Type: String

Valid Values: `LATEST_PERMISSION_SET_PROVISIONED` | `LATEST_PERMISSION_SET_NOT_PROVISIONED`

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "PermissionSets": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 72)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[-a-zA-Z0-9+ = / _] *`

PermissionSets (p. 72)

Defines the level of access that an AWS account has.

Type: Array of strings

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags that are attached to a specified resource.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "NextToken": "string",  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 74)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

NextToken (p. 74)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[a-zA-Z0-9+/_]*`

Required: No

ResourceArn (p. 74)

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:([a-zA-Z0-9-]+)?:(\d{12})?:[a-zA-Z0-9-]+/[a-zA-Z0-9-/.]+`

Required: Yes

Response Syntax

```
{
  "NextToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 75)

The pagination token for the list API. Initially the value is null. Use the output of previous API calls to make subsequent calls.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: ^[-a-zA-Z0-9+/_]*

Tags (p. 75)

A set of key-value pairs that are used to manage the resource.

Type: Array of [Tag \(p. 111\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

InternalServerError

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ProvisionPermissionSet

The process by which a specified permission set is provisioned to the specified target.

Request Syntax

```
{  
  "InstanceArn": "string",  
  "PermissionSetArn": "string",  
  "TargetId": "string",  
  "TargetType": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 77)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn (p. 77)

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

TargetId (p. 77)

TargetID is an AWS account identifier, typically a 10-12 digit string (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

TargetType (p. 77)

The entity type for which the assignment will be created.

Type: String

Valid Values: `AWS_ACCOUNT` | `ALL_PROVISIONED_ACCOUNTS`

Required: Yes

Response Syntax

```
{
  "PermissionSetProvisioningStatus": {
    "AccountId": "string",
    "CreateDate": number,
    "FailureReason": "string",
    "PermissionSetArn": "string",
    "RequestId": "string",
    "Status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

PermissionSetProvisioningStatus (p. 78)

The status object for the permission set provisioning operation.

Type: [PermissionSetProvisioningStatus \(p. 108\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutInlinePolicyToPermissionSet

Attaches an IAM inline policy to a permission set.

Note

If the permission set is already referenced by one or more account assignments, you will need to call [ProvisionPermissionSet \(p. 77\)](#) after this action to apply the corresponding IAM policy updates to all assigned accounts.

Request Syntax

```
{  
  "InlinePolicy": "string",  
  "InstanceArn": "string",  
  "PermissionSetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 112\)](#).

The request accepts the following data in JSON format.

InlinePolicy (p. 80)

The IAM inline policy to attach to a [PermissionSet \(p. 106\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10240.

Pattern: `[\u0009\u000A\u000D\u0020-\u00FF]+`

Required: Yes

InstanceArn (p. 80)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

PermissionSetArn (p. 80)

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-]{16}/ps-[a-zA-Z0-9-./]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates a set of tags with a specified resource.

Request Syntax

```
{
  "InstanceArn": "string",
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 83)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

ResourceArn (p. 83)

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:([a-zA-Z0-9-]+)?:(\d{12})?:[a-zA-Z0-9-]+/[a-zA-Z0-9-/.]+`

Required: Yes

Tags (p. 83)

A set of key-value pairs that are used to manage the resource.

Type: Array of [Tag](#) (p. 111) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ServiceQuotaExceededException

Indicates that the principal has crossed the permitted number of resources that can be created.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Disassociates a set of tags from a specified resource.

Request Syntax

```
{
  "InstanceArn": "string",
  "ResourceArn": "string",
  "TagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

InstanceArn (p. 86)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

ResourceArn (p. 86)

The ARN of the resource with the tags to be listed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:([a-zA-Z0-9-]+)?:(\d{12})?:[a-zA-Z0-9-]+/[a-zA-Z0-9-/.]+`

Required: Yes

TagKeys (p. 86)

The keys of tags that are attached to the resource.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UpdateInstanceAccessControlAttributeConfiguration

Updates the AWS SSO identity store attributes that you can use with the AWS SSO instance for attributes-based access control (ABAC). When using an external identity provider as an identity source, you can pass attributes through the SAML assertion as an alternative to configuring attributes from the AWS SSO identity store. If a SAML assertion passes any of these attributes, AWS SSO replaces the attribute value with the value from the AWS SSO identity store. For more information about ABAC, see [Attribute-Based Access Control](#) in the *AWS SSO User Guide*.

Request Syntax

```
{
  "InstanceAccessControlAttributeConfiguration": {
    "AccessControlAttributes": [
      {
        "Key": "string",
        "Value": {
          "Source": [ "string" ]
        }
      }
    ]
  },
  "InstanceArn": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

[InstanceAccessControlAttributeConfiguration](#) (p. 89)

Updates the attributes for your ABAC configuration.

Type: [InstanceAccessControlAttributeConfiguration](#) (p. 103) object

Required: Yes

[InstanceArn](#) (p. 89)

The ARN of the SSO instance under which the operation will be executed.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePermissionSet

Updates an existing permission set.

Request Syntax

```
{
  "Description": "string",
  "InstanceArn": "string",
  "PermissionSetArn": "string",
  "RelayState": "string",
  "SessionDuration": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 112).

The request accepts the following data in JSON format.

Description (p. 91)

The description of the [PermissionSet](#) (p. 106).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: `[\u0009\u000A\u000D\u0020-\u007E\u00A0-\u00FF]*`

Required: No

InstanceArn (p. 91)

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-.]{16}`

Required: Yes

PermissionSetArn (p. 91)

The ARN of the permission set.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: Yes

RelayState (p. 91)

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: [a-zA-Z0-9&\$@#\%?=_-'":!;,.*+\\[\]\ \(\)\{\}\}]+

Required: No

SessionDuration (p. 91)

The length of time that the application user sessions are valid for in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: ^(-?)P(?:=\d|T\d)(?:\d+Y)?(?:\d+M)?(?:\d+([DW]))?(?:T(?:\d+H)?(?:\d+M)?(?:\d+(?:\.\d+)?)S)?)?\$

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 114\)](#).

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

ConflictException

Occurs when a conflict with a previous successful write is detected. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 400

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure with an internal server.

HTTP Status Code: 400

ResourceNotFoundException

Indicates that a requested resource is not found.

HTTP Status Code: 400

ThrottlingException

Indicates that the principal has crossed the throttling limits of the API operations.

HTTP Status Code: 400

ValidationException

The request failed because it contains a syntax error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Single Sign-On Admin API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessControlAttribute](#) (p. 95)
- [AccessControlAttributeValue](#) (p. 96)
- [AccountAssignment](#) (p. 97)
- [AccountAssignmentOperationStatus](#) (p. 99)
- [AccountAssignmentOperationStatusMetadata](#) (p. 101)
- [AttachedManagedPolicy](#) (p. 102)
- [InstanceAccessControlAttributeConfiguration](#) (p. 103)
- [InstanceMetadata](#) (p. 104)
- [OperationStatusFilter](#) (p. 105)
- [PermissionSet](#) (p. 106)
- [PermissionSetProvisioningStatus](#) (p. 108)
- [PermissionSetProvisioningStatusMetadata](#) (p. 110)
- [Tag](#) (p. 111)

AccessControlAttribute

These are AWS SSO identity store attributes that you can configure for use in attributes-based access control (ABAC). You can create permissions policies that determine who can access your AWS resources based upon the configured attribute values. When you enable ABAC and specify `AccessControlAttributes`, AWS SSO passes the attribute values of the authenticated user into IAM for use in policy evaluation.

Contents

Key

The name of the attribute associated with your identities in your identity source. This is used to map a specified attribute in your identity source with an attribute in AWS SSO.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{Z}\p{N}_ : \ / = + \ - @] +`

Required: Yes

Value

The value used for mapping a specified attribute to an identity source.

Type: [AccessControlAttributeValue](#) (p. 96) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessControlAttributeValue

The value used for mapping a specified attribute to an identity source.

Contents

Source

The identity source to use when mapping a specified attribute to AWS SSO.

Type: Array of strings

Array Members: Fixed number of 1 item.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[\p{L}\p{Z}\p{N}_.:\/=+\-@[\]\{\}\$\\"]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountAssignment

The assignment that indicates a principal's limited access to a specified AWS account with a specified permission set.

Note

The term *principal* here refers to a user or group that is defined in AWS SSO.

Contents

AccountId

The identifier of the AWS account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: No

PrincipalId

An identifier for an object in AWS SSO, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in AWS SSO, see the [AWS SSO Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `^([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}$`

Required: No

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: `USER` | `GROUP`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountAssignmentOperationStatus

The status of the creation or deletion operation of an assignment that a principal needs to access an account.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

FailureReason

The message that contains an error or exception in case of an operation failure.

Type: String

Pattern: `[\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]*`

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: No

PrincipalId

An identifier for an object in AWS SSO, such as a user or group. PrincipalIds are GUIDs (For example, f81d4fae-7dec-11d0-a765-00a0c91e6bf6). For more information about PrincipalIds in AWS SSO, see the [AWS SSO Identity Store API Reference](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 47.

Pattern: `^([0-9a-f]{10}-|)[A-Fa-f0-9]{8}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{4}-[A-Fa-f0-9]{12}$`

Required: No

PrincipalType

The entity type for which the assignment will be created.

Type: String

Valid Values: `USER` | `GROUP`

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: `IN_PROGRESS` | `FAILED` | `SUCCEEDED`

Required: No

TargetId

TargetID is an AWS account identifier, typically a 10-12 digit string (For example, 123456789012).

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

TargetType

The entity type for which the assignment will be created.

Type: String

Valid Values: `AWS_ACCOUNT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountAssignmentOperationStatusMetadata

Provides information about the [AccountAssignment](#) (p. 97) creation request.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: `IN_PROGRESS` | `FAILED` | `SUCCEEDED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachedManagedPolicy

A structure that stores the details of the IAM managed policy.

Contents

Arn

The ARN of the IAM managed policy. For more information about ARNs, see [Amazon Resource Names \(ARNs\)](#) and [AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

Name

The name of the IAM managed policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceAccessControlAttributeConfiguration

Specifies the attributes to add to your attribute-based access control (ABAC) configuration.

Contents

AccessControlAttributes

Lists the attributes that are configured for ABAC in the specified AWS SSO instance.

Type: Array of [AccessControlAttribute](#) (p. 95) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceMetadata

Provides information about the SSO instance.

Contents

IdentityStoreId

The identifier of the identity store that is connected to the SSO instance.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9-]*`

Required: No

InstanceArn

The ARN of the SSO instance under which the operation will be executed. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OperationStatusFilter

Filters the operation status list based on the passed attribute value.

Contents

Status

Filters the list operations result based on the status attribute.

Type: String

Valid Values: `IN_PROGRESS` | `FAILED` | `SUCCEEDED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PermissionSet

An entity that contains IAM policies.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

Description

The description of the [PermissionSet](#) (p. 106).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 700.

Pattern: [\u0009\u000A\u000D\u0020-\u007E\u00A0-\u00FF]*

Required: No

Name

The name of the permission set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: [\w+=, .@-]+

Required: No

PermissionSetArn

The ARN of the permission set. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}

Required: No

RelayState

Used to redirect users within the application during the federation authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 240.

Pattern: [a-zA-Z0-9&\$@#\|/%?=\~_'"|!:,.;*+[\]\ \(\)\{\}\}]+

Required: No

SessionDuration

The length of time that the application user sessions are valid for in the ISO-8601 standard.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^(?P(=?=\d|T\d)(?:\d+)Y)?(?:\d+)M)?(?:\d+)([DW]))?(?:T(?:\d+)H)?(?:\d+)M)?(?:\d+(?:\.\d+)?)S)?)?$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PermissionSetProvisioningStatus

A structure that is used to provide the status of the provisioning operation for a specified permission set.

Contents

AccountId

The identifier of the AWS account from which to list the assignments.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

FailureReason

The message that contains an error or exception in case of an operation failure.

Type: String

Pattern: `[\p{L}\p{M}\p{Z}\p{S}\p{N}\p{P}]*`

Required: No

PermissionSetArn

The ARN of the permission set that is being provisioned. For more information about ARNs, see [Amazon Resource Names \(ARNs\) and AWS Service Namespaces](#) in the *AWS General Reference*.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::permissionSet/(sso)?ins-[a-zA-Z0-9-.]{16}/ps-[a-zA-Z0-9-.]{16}`

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: `IN_PROGRESS` | `FAILED` | `SUCCEEDED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PermissionSetProvisioningStatusMetadata

Provides information about the permission set provisioning status.

Contents

CreatedDate

The date that the permission set was created.

Type: Timestamp

Required: No

RequestId

The identifier for tracking the request operation that is generated by the universally unique identifier (UUID) workflow.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `\b[0-9a-f]{8}\b-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-\b[0-9a-f]{12}\b`

Required: No

Status

The status of the permission set provisioning process.

Type: String

Valid Values: `IN_PROGRESS` | `FAILED` | `SUCCEEDED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A set of key-value pairs that are used to manage the resource. Tags can only be applied to permission sets and cannot be applied to corresponding roles that AWS SSO creates in AWS accounts.

Contents

Key

The key for the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)$`

Required: Yes

Value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Document History

The following table describes the important changes to the documentation in this release of the *AWS SSO API Reference Guide*.

- **Latest documentation update:** September 10, 2020

Change	Description	Date Changed
New guide	This is the first release of the AWS Single Sign-On API Reference Guide.	September 10, 2020