

# Timing

## Time and intervals

Shadi Lahham - Programmazione web - Frontend - Javascript

# Timers and intervals

# Timing

We may decide not to execute a function immediately, but at a certain time.

That's called “scheduling a call”. There are two methods for it:

- `setTimeout` allows to run a function once after an interval of time.
- `setInterval` allows to run a function regularly with a specified interval.

# setTimeout

## Syntax

```
setTimeout(function, milliseconds, param1, param2, ...)
```

### **function**

Required. The function that will be executed

### **milliseconds**

Optional. The number of milliseconds to wait before executing the code. If omitted, the value 0 is used

### **param1, param2, ...**

Optional. Additional parameters to pass to the function (Not supported in IE9 and earlier)

# setTimeout

*// Named function*

```
function sayHi() {  
  console.log('Hello');  
}
```

```
setTimeout(sayHi, 1000);
```

*// Anonymous function*

```
setTimeout(function () {  
  console.log('Hello');  
}, 3000);
```

*// Anonymous arrow function*

```
setTimeout(() => {  
  console.log('Hello');  
}, 3000);
```

*// With arguments*

```
function sayHi(phrase, who) {  
  console.log(phrase + ', ' + who);  
}
```

```
setTimeout(sayHi, 1000, 'Hello', 'John');
```

*// Anonymous with arguments*

```
setTimeout(  
  function (value) {  
    console.log(value);  
  }, 1000, 'hello'  
);
```

*// Works in IE9*

```
setTimeout(function () {  
  sayHi('Hello', 'John');  
}, 1000);
```

# clearTimeout

A call to `setTimeout` returns a “timer identifier” `timerId` that we can use to cancel the execution.

## Example

```
let timerId = setTimeout(function () {  
  console.log('never happens');  
}, 1000);  
clearTimeout(timerId);
```

# setInterval

## Syntax

Method `setInterval` has the same syntax as `setTimeout`:

```
setInterval(function, milliseconds, param1, param2, ...)
```

## function

Required. The function that will be executed

## milliseconds

Required. The intervals (in milliseconds) on how often to execute the code. If the value is less than 10, the value 10 is used

## param1, param2, ...

Optional. Additional parameters to pass to the function (Not supported in IE9 and earlier)

# setInterval

*// Named function*

```
function sayHi() {  
  console.log('Hello');  
}
```

```
setInterval(sayHi, 1000);
```

*// Anonymous function*

```
setInterval(function () {  
  console.log('Hello');  
}, 3000);
```

*// Anonymous arrow function*

```
setInterval(() => {  
  console.log('Hello');  
}, 3000);
```

*// With arguments*

```
function sayHi(phrase, who) {  
  console.log(phrase + ', ' + who);  
}
```

```
setInterval(sayHi, 1000, 'Hello', 'John');
```

*// Anonymous with arguments*

```
setInterval(  
  function (value) {  
    console.log(value);  
  }, 1000, 'hello'  
);
```

*// Works in IE9*

```
setInterval(function () {  
  sayHi('Hello', 'John');  
}, 1000);
```



# clearInterval

A call to `setInterval` returns a “timer identifier” `timerId` that we can use to cancel the execution.

## Example

```
// repeat with the interval of 2 seconds
let timerId = setInterval(function () {
  console.log('tick');
}, 2000);

// after 5 seconds stop
setTimeout(function () {
  clearInterval(timerId);
  console.log('stop');
}, 5000);
```

Date and time

# The Date object

A date consists of a year, a month, a day, an hour, a minute, a second, and milliseconds.

## Syntax

```
new Date()
```

```
new Date(milliseconds)
```

```
new Date(dateString)
```

```
new Date(year, month, day, hours, minutes, seconds, milliseconds)
```

# The Date object

## Examples

```
let d = new Date();
```

```
let d = new Date("October 13, 2014 11:13:00"); // implementation-dependent; browser/version/os
```

```
let d = new Date(86400000);
```

```
let d = new Date(99, 5, 24, 11, 33, 30, 0);
```

# Displaying Dates

Javascript tries to automatically convert dates to strings if they are assigned as Strings.

```
let d = new Date();  
console.log(d);  
console.log(d.toString()); // implementation-dependent; browser/version/os  
console.log(d.toUTCString());  
console.log(d.toDateString());
```

Notice that the first two outputs are the same.

# Date formats

There are generally 4 types of JavaScript date input formats:

ISO Date      "2015-03-25" (The International Standard)

Short Date    "03/25/2015"

Long Date     "Mar 25 2015" or "25 Mar 2015"

Full Date     "Wednesday March 25 2015"

# Date get methods

```
// get date  
let d = new Date();  
console.log(d);  
console.log(d.getMonth());  
console.log(d.getMinutes());  
console.log(d.getFullYear());
```

```
new Date(); // creates a Date object representing current date/time  
new Date().valueOf(); // returns number of milliseconds since midnight 01 January, 1970 UTC  
new Date().getTime(); // same as above  
Date.now(); // same as above
```

**Complete list**

[https://www.w3schools.com/js/js\\_date\\_methods.asp](https://www.w3schools.com/js/js_date_methods.asp)

# Date set methods

```
// set date
d.setFullYear(2020, 0, 14);
d.setDate(d.getDate() + 50);

// parse valid dates
let msec = Date.parse("March 21, 2012");
let date = new Date(msec);
```

**Complete list**

[https://www.w3schools.com/js/js\\_date\\_methods.asp](https://www.w3schools.com/js/js_date_methods.asp)



# Comparing dates

Comparison operators work also on dates

```
let date1 = new Date();
let date2 = new Date("Feb 24, 2022 15:50:00");
if (date1 > date2) {
    console.log('break time');
} else {
    console.log('stay in class');
}
```

Your turn

# 1.The Timed Calculator

- We will modify ‘The Calculator’ exercise from the lesson about functions.
- Rewrite the last function that performs all 4 operations so that there is a delay of 3 seconds between one operation and the next.

## 2.Oh no you don't

- Write a function “useful” that does something useful in Javascript.
- Schedule it to run after 10 seconds.
- Write another function that cancels the scheduling of the first function.
- Use the second function to cancel the first one after 5 seconds and output ‘function cancelled’ to the console.

### 3.The Timed Temperature Converter

- We will modify ‘The Temperature Converter’ exercise from the lesson about functions.
- Call `celsiusToFahrenheit` on temperatures from 0 to 100 so that one temperature is printed to the console every second.
  - Use `setInterval` to achieve this goal.
  - Do the same thing using `setTimeout`.

## 4.Slow list

- Create an array that holds a list of 30 items (food, books, etc.)
- Print one item of the list every second until the list is completely printed.
  - Use `setInterval` to achieve this goal.
  - Do the same thing using `setTimeout`.

## 5.Weekday

- Write a function `getWeekDay(date)` to show the weekday in short format: 'MO', 'TU', 'WE', 'TH', 'FR', 'SA', 'SU'.
- Write another function that does the same in Italian.
- Add a language parameter to the function that accepts 'en' or 'it' and outputs the day in the correct language.

## 6.DateAgo

- Create a function getDateAgo(date, days) that returns the day of the month n days ago from the given date.
- For instance, if today is the 20th, then getDateAgo(new Date(), 1) should be 19th and getDateAgo(new Date(), 2) should be 18th.
- The function should work reliably with any valid Date object. Test it.



# 7.Seconds

Write two functions that based on the current date and time output the number of seconds:

- `getSecondsToday()` returns the number of seconds from the beginning of today.
- `getSecondsToTomorrow()` returns the number of seconds till tomorrow.

Bonus

## 8. My setInterval

- Pretend that `setInterval()` doesn't exist.
- Re-create it using `setTimeout` naming your function `mySetInterval`.
- Test your new function.
- Modify your function so that it automatically stops after 15 intervals.

## 9. formatDate

Write a function `formatDate(date)` that accepts a date and outputs it as follows:

- If less than a second has passed since the date, output "right now".
- If less than a minute has passed since the date, output "n sec. ago".
- If less than an hour has passed since the date, output "m min. ago".
- Otherwise, output the date in this format "DD.MM.YY HH:mm".
  - e.g. 17.04.16 10:00

# 10.Clock

- Implement a javascript clock that prints the current time to the console every second.
- The output should be in the format HH:mm:ss e.g. 17:03:06

# References

[JavaScript Timing Events](#)

[setTimeout\(\) | MDN](#)

[setInterval\(\) | MDN](#)

# References

[JavaScript Date Objects](#)

[Date\(\) constructor | MDN](#)

[JavaScript Date Reference](#)

[JavaScript Date Formats](#)

[JavaScript Date Methods](#)

[Coordinated Universal Time](#)

[Greenwich Mean Time](#)