

Project: Loving

Location: 3.125x6 GLB header

Roof Beam

[2009 International Residential Code(2005 NDS)]

3.125 IN x 6.0 IN x 5.0 FT

24F-V4 - Visually Graded Western Species - Dry Use

Section Adequate By: 74.3%

Controlling Factor: Moment

DEFLECTIONS

Center

Live Load 0.08 IN L/772

Dead Load 0.03 in

Total Load 0.11 IN L/546

Live Load Deflection Criteria: L/240 Total Load Deflection Criteria: L/180

REACTIONS

A

B

Live Load 1400 lb 1400 lb

Dead Load 579 lb 579 lb

Total Load 1979 lb 1979 lb

Bearing Length 0.97 in 0.97 in

BEAM DATA

Span Length 5 ft

Unbraced Length-Top 0 ft

Unbraced Length-Bottom 0 ft

Roof Pitch 5 :12

Roof Duration Factor 1.15

MATERIAL PROPERTIES

24F-V4 - Visually Graded Western Species

Base Values

Adjusted

Bending Stress: Fb = 2400 psi Controlled by:
Fb_cmpr = 1850 psi Fb' = 2760 psi
Cd=1.15

Shear Stress: Fv = 265 psi Fv' = 305 psi
Cd=1.15

Modulus of Elasticity: E = 1800 ksi E' = 1800 ksi

Min. Mod. of Elasticity: E_min = 930 ksi E_min' = 930 ksi

Comp. \perp to Grain: Fc \perp = 650 psi Fc \perp ' = 650 psi

Controlling Moment: 2474 ft-lb

2.5 ft from left support

Created by combining all dead and live loads.

Controlling Shear: -1583 lb

At a distance d from support.

Created by combining all dead and live loads.

Comparisons with required sections:

Req'd

Provided

Section Modulus: 10.75 in³ 18.75 in³

Area (Shear): 7.79 in² 18.75 in²

Moment of Inertia (deflection): 18.55 in⁴ 56.25 in⁴

Moment: 2474 ft-lb 4313 ft-lb

Shear: -1583 lb 3809 lb



Bonnie Higgins
Sunteriors Design & Drafting
Flagstaff, AZ


page

of

StruCalc Version 8.0.113.0

3/3/2017 21:25:17

LOADING DIAGRAM



ROOF LOADING

Side One:

Roof Live Load: LL = 40 psf

Roof Dead Load: DL = 15 psf

Tributary Width: TW = 12 ft

Side Two:

Roof Live Load: LL = 40 psf

Roof Dead Load: DL = 15 psf

Tributary Width: TW = 2 ft

Wall Load: WALL = 0 plf

SLOPE/PITCH ADJUSTED LENGTHS AND LOADS

Adjusted Beam Length: Ladj = 5 ft

Beam Self Weight: BSW = 4 plf

Beam Uniform Live Load: wL = 560 plf

Beam Uniform Dead Load: wD_adj = 232 plf

Total Uniform Load: wT = 792 plf