Solaris 2 Scheduling



Solaris Dispatch Table

priority	time quantum	time quantum expired	return from sleep
0	200	0	50
5	200	0	50
10	160	0	51
15	160	5	51
20	120	10	52
25	120	15	52
30	80	20	53
35	80	25	54
40	40	30	55
45	40	35	56
50	40	40	58
55	40	45	58
59	20	49	59

Windows XP Priorities

	real-time	high	above normal	normal	below normal	idle priority
time-critical	31	15	15	15	15	15
highest	26	15	12	10	8	6
above normal	25	14	11	9	7	5
normal	24	13	10	8	6	4
below normal	23	12	9	7	5	3
lowest	22	11	8	6	4	2
idle	16	1	1	1	1	1

Linux:
The Relationship Between Priorities and Time-slice length



List of Tasks Indexed According to Prorities



Algorithm Evaluation

- Deterministic modeling – takes a particular predetermined workload and defines the performance of each algorithm for that workload
- Queueing models
- Implementation

Simulations



End of Chapter 5

Java Thread Scheduling

- JVM Uses a Preemptive, Priority-Based Scheduling Algorithm
- FIFO Queue is Used if There Are Multiple Threads With the Same Priority

Java Thread Scheduling (cont)

JVM Schedules a Thread to Run When:

1. The Currently Running Thread Exits the Runnable State
2. A Higher Priority Thread Enters the Runnable State

* Note – the JVM Does Not Specify Whether Threads are Time-Sliced or Not

Thread Priorities

Priority	**Comment**
Thread.MIN_PRIORITY	Minimum Thread Priority
Thread.MAX_PRIORITY	Maximum Thread Priority
Thread.NORM_PRIORITY	Default Thread Priority

Chapter 6: Process Synchronization

- Background
- The Critical-Section Problem
- Peterson's Solution
- Synchronization Hardware
- Semaphores
- Classic Problems of Synchronization
- Monitors
- Synchronization Examples
- Atomic Transactions

Background

- Concurrent access to shared data may result in data inconsistency
- Maintaining data consistency requires mechanisms to ensure the orderly execution of cooperating processes
- Suppose that we wanted to provide a solution to the consumer-producer problem that fills all the buffers. We can do so by having an integer count that keeps track of the number of full buffers. Initially, count is set to 0. It is incremented by the producer after it produces a new buffer and is decremented by the consumer after it consumes a buffer.

Producer

```
while (true)

    /* produce an item and put in nextProduced*/
            while (count == BUFFER_SIZE)
                ; // do nothing
            buffer [in] = nextProduced;
            in = (in + 1) % BUFFER_SIZE;
            count++;
}
```

Consumer

```
while (1)
 {
            while (count == 0)
                ; // do nothing
            nextConsumed =  buffer[out];
            out = (out + 1) % BUFFER_SIZE;
            count--;
    /*  consume the item in nextConsumed
}
```

Race Condition

- count++ could be implemented as

```
register1 = count
register1 = register1 + 1
count = register1
```

- count-- could be implemented as

```
register2 = count
register2 = register2 - 1
count = register2
```

- Consider this execution interleaving with "count = 5" initially:
  - S0: producer execute register1 = count {register1 = 5}
  - S1: producer execute register1 = register1 + 1 {register1 = 6}
  - S2: consumer execute register2 = count {register2 = 5}
  - S3: consumer execute register2 = register2 - 1 {register2 = 4}
  - S4: producer execute count = register1 {count = 6 }
  - S5: consumer execute count = register2 {count = 4}

Solution to Critical-Section Problem

1. Mutual Exclusion - If process P_i is executing in its critical section, then no other processes can be executing in their critical sections
2. Progress - If no process is executing in its critical section and there exist some processes that wish to enter their critical section, then the selection of the processes that will enter the critical section next cannot be postponed indefinitely
3. Bounded Waiting - A bound must exist on the number of times that other processes are allowed to enter their critical sections after a process has made a request to enter its critical section and before that request is granted
   - Assume that each process executes at a nonzero speed
   - No assumption concerning relative speed of the N processes

Peterson's Solution

- Two process solution
- Assume that the LOAD and STORE instructions are atomic; that is, cannot be interrupted.
- The two processes share two variables:
  - int turn;
  - Boolean flag[2]
- The variable turn indicates whose turn it is to enter the critical section.
- The flag array is used to indicate if a process is ready to enter the critical section. flag[i] = true implies that process P_i is ready!

Algorithm for Process P_i

```
do {
    flag[i] = TRUE;
    turn = j;
    while ( flag[j] && turn == j);

        CRITICAL SECTION

    flag[i] = FALSE;

        REMAINDER SECTION

 } while (TRUE);
```