Progress on Code Verification for Collisional Plasma Dynamics

Brian A. Freno

William J. McDoniel   Christopher H. Moore

Thomas M. Smith   Duncan A. O. McGregor

Sandia National Laboratories

Direct Simulation Monte Carlo Workshop

September 28 – October 1, 2025

Outline

Outline

- Introduction
  - Collisional Plasma Dynamics
  - Verification and Validation
  - Code Verification
  - Code-Verification Goal
- Particle-in-Cell Method
- Existing Work for Collisionless Plasma Dynamics
- Approach for Collisional Plasma Dynamics
- Numerical Examples
- Summary

Collisional Plasma Dynamics

- Important for many scientific and engineering applications
  - **Hypersonic & reentry air plasmas** affecting heat loads and radiation
  - **Environmental & biomedical plasmas** for ozone, sterilization, and cleaning
  - **Electric propulsion plasmas** in Hall-effect thrusters and ion engines
  - **Semiconductor & thin-film plasmas** for etching and deposition
- Modeled via particle-in-cell (PIC) with collision algorithm (MCC/DSMC)
  - Solve Maxwell's equations to compute electromagnetic fields on grid
  - Solve particle equations of motion due to Lorentz force and collisions
  - Interpolate EM fields to particles, distribute particle properties to grid
  - Model particle collisions with direct simulation Monte Carlo (DSMC)

Verification and Validation

Credibility of computational physics codes requires verification and validation

- **Validation** assesses how well models represent physical phenomena
  - Compare computational results with experimental results
  - Assess suitability of models, model error, and bounds of validity

- **Verification** assesses accuracy of numerical solutions against expectations
  - *Solution verification* estimates numerical error for particular solution
  - *Code verification* assesses correctness of numerical-method implementation

Discretization Error

Code verification assesses correctness of numerical-method implementation

- Continuous equations are numerically discretized

$$\mathbf{r}(\mathbf{u}) = \mathbf{0} \quad \rightarrow \quad \mathbf{r}_h(\mathbf{u}_h) = \mathbf{0}$$

- Discretization error is introduced in solution

$$\mathbf{e} = \mathbf{u}_h - \mathbf{u}$$

- Discretization error should decrease as discretization is refined

$$\lim_{h \to 0} \mathbf{e} = \mathbf{0}$$

- More rigorously, should decrease at an expected rate

$$\|\mathbf{e}\| \approx Ch^p$$

- Measuring error requires exact solution – usually unavailable

Manufactured Solutions

Manufactured solutions are popular alternative

- Manufacture an arbitrary solution $\mathbf{u}_{\mathrm{MS}}$
- Insert manufactured solution into continuous equations to get residual term

$$\mathbf{r}(\mathbf{u}_{\mathrm{MS}}) \neq \mathbf{0}$$

- Add residual term to discretized equations

$$\mathbf{r}_h(\mathbf{u}_h) = \mathbf{r}(\mathbf{u}_{\mathrm{MS}})$$

  to coerce solution to manufactured solution

$$\mathbf{u}_h \to \mathbf{u}_{\mathrm{MS}}$$

Code-Verification Goal

- Existing code-verification work
  - Plasma dynamics without collisions: distribution modeled by Vlasov equation
  - Electrostatics (negligible magnetic field influence): Poisson equation
  - 1D-1V, 2D-2V
- Our code-verification goal
  - Plasma dynamics with collisions: distribution modeled by Boltzmann equation
  - Electromagnetics: Maxwell's equations
  - 3D-3V

Outline

- Introduction
- Particle-in-Cell Method
  - Overview
  - Equations of Motion for Charged Particles
  - Maxwell's Equations
- Existing Work for Collisionless Plasma Dynamics
- Approach for Collisional Plasma Dynamics
- Numerical Examples
- Summary

Overview

- Place weighted computational particles randomly in phase space (according to distribution function)
- Interpolate particle charge onto spatial mesh nodes
- Solve Maxwell's equations on spatial mesh for electromagnetic fields
- Interpolate fields onto particles
- For each particle, integrate equations of motion due to
  - Lorentz force from electromagnetic fields
  - Collisions between particles

Equations of Motion for Charged Particles (Single Species)

Equations of motion for each particle:

$$\frac{dw_p}{dt} = 0, \qquad \frac{d\mathbf{x}_p}{dt} = \mathbf{v}_p, \qquad \frac{d\mathbf{v}_p}{dt} = \frac{\mathbf{F}_p}{m} + \mathbf{a}_{\text{coll}}$$

- w_p is computational particle weight
- $\mathbf{F}_p = \dfrac{q}{m}(\mathbf{E}(\mathbf{x}_p, t) + \mathbf{v}_p \times \mathbf{B}(\mathbf{x}_p, t))$ is Lorentz force
- $\mathbf{E}$ and $\mathbf{B}$ are electric and magnetic fields
- m and q are species mass and charge
- $\mathbf{a}_{\text{coll}}$ is acceleration due to collision

Increasing N_p, distribution function evolution approaches Boltzmann equation:

$$\frac{\partial f}{\partial t} + \mathbf{v} \cdot \nabla f + \frac{\mathbf{F}}{m} \cdot \frac{\partial f}{\partial \mathbf{v}} = \left(\frac{\partial f}{\partial t}\right)_{\text{coll}}$$

- $f(\mathbf{x}_p, \mathbf{v}_p, t)$ is particle distribution function, $(\partial f/\partial t)_{\text{coll}}$ is collision term

Equations of Motion for Charged Particles (Single Species)

Equations of motion for each particle (collisionless):

$$\frac{dw_p}{dt} = 0, \qquad \frac{d\mathbf{x}_p}{dt} = \mathbf{v}_p, \qquad \frac{d\mathbf{v}_p}{dt} = \frac{\mathbf{F}_p}{m} + \cancelto{0}{\mathbf{a}_{\text{coll}}}$$

- w_p is computational particle weight
- $\mathbf{F}_p = \dfrac{q}{m}(\mathbf{E}(\mathbf{x}_p, t) + \mathbf{v}_p \times \mathbf{B}(\mathbf{x}_p, t))$ is Lorentz force
- $\mathbf{E}$ and $\mathbf{B}$ are electric and magnetic fields
- m and q are species mass and charge
- $\mathbf{a}_{\text{coll}}$ is acceleration due to collision

Increasing N_p, distribution function evolution approaches ~~Boltzmann~~ Vlasov equation:

$$\frac{\partial f}{\partial t} + \mathbf{v} \cdot \nabla f + \frac{\mathbf{F}}{m} \cdot \frac{\partial f}{\partial \mathbf{v}} = \cancelto{0}{\left(\frac{\partial f}{\partial t}\right)_{\text{coll}}}$$

- $f(\mathbf{x}_p, \mathbf{v}_p, t)$ is particle distribution function, $(\partial f/\partial t)_{\text{coll}}$ is collision term

Equations of Motion for Charged Particles (Single Species)

Equations of motion for each particle (electrostatic):

$$\frac{dw_p}{dt} = 0, \qquad \frac{d\mathbf{x}_p}{dt} = \mathbf{v}_p, \qquad \frac{d\mathbf{v}_p}{dt} = \frac{\mathbf{F}_p}{m} + \mathbf{a}_{\text{coll}}$$

- w_p is computational particle weight
- $\mathbf{F}_p = \dfrac{q}{m}(\mathbf{E}(\mathbf{x}_p, t) + \mathbf{v}_p \times \cancelto{0}{\mathbf{B}(\mathbf{x}_p, t)})$ is Lorentz force
- $\mathbf{E}$ and $\mathbf{B}$ are electric and magnetic fields
- m and q are species mass and charge
- $\mathbf{a}_{\text{coll}}$ is acceleration due to collision

Increasing N_p, distribution function evolution approaches Boltzmann equation:

$$\frac{\partial f}{\partial t} + \mathbf{v} \cdot \nabla f + \frac{\mathbf{F}}{m} \cdot \frac{\partial f}{\partial \mathbf{v}} = \left(\frac{\partial f}{\partial t}\right)_{\text{coll}}$$

- $f(\mathbf{x}_p, \mathbf{v}_p, t)$ is particle distribution function, $(\partial f/\partial t)_{\text{coll}}$ is collision term

Maxwell's Equations

Gauss's law	$\nabla \cdot \mathbf{E} = \frac{\rho}{\epsilon_0}$
Gauss's law for magnetism	$\nabla \cdot \mathbf{B} = 0$
Faraday's law of induction	$\nabla \times \mathbf{E} = -\frac{\partial \mathbf{B}}{\partial t}$
Ampère's circuital law	$\nabla \times \mathbf{B} = \mu_0 \left(\mathbf{J} + \epsilon_0 \frac{\partial \mathbf{E}}{\partial t} \right)$

- Charge conservation $\frac{\partial \rho}{\partial t} + \nabla \cdot \mathbf{J} = 0$
- Charge density $\rho(\mathbf{x}, t) = q \int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t) d\mathbf{v}$
- Electric current density $\mathbf{J}(\mathbf{x}, t) = q \int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t) \mathbf{v} d\mathbf{v}$
- ϵ_0 and μ_0 are permittivity and permeability of free space

Maxwell's Equations (Electromagnetic Case)

Gauss's law	$\nabla \cdot \mathbf{E} = \dfrac{\rho}{\epsilon_0}$	Satisfied due to charge conservation
Gauss's law for magnetism	$\nabla \cdot \mathbf{B} = 0$	

Faraday's law of induction	$\nabla \times \mathbf{E} = -\dfrac{\partial \mathbf{B}}{\partial t}$
Ampère's circuital law	$\nabla \times \mathbf{B} = \mu_0\left(\mathbf{J} + \epsilon_0 \dfrac{\partial \mathbf{E}}{\partial t}\right)$

- Charge conservation $\dfrac{\partial \rho}{\partial t} + \nabla \cdot \mathbf{J} = 0$
- Charge density $\rho(\mathbf{x}, t) = q \displaystyle\int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t) d\mathbf{v}$
- Electric current density $\mathbf{J}(\mathbf{x}, t) = q \displaystyle\int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t) \mathbf{v} d\mathbf{v}$
- ϵ_0 and μ_0 are permittivity and permeability of free space

Maxwell's Equations (Electrostatic Case)

Gauss's law	$\boxed{\nabla \cdot \mathbf{E} = \frac{\rho}{\epsilon_0}}$	$\rightarrow$	$\boxed{\Delta\phi = -\frac{\rho}{\epsilon_0}}$
Gauss's law for magnetism	$\nabla \cdot \mathbf{B} = 0$		$\uparrow$
Faraday's law of induction	$\boxed{\nabla \times \mathbf{E} = -\frac{\partial \cancel{\mathbf{B}}\,\mathbf{0}}{\partial t}}$	$\rightarrow$	$\mathbf{E} = -\nabla\phi$
Ampère's circuital law	$\nabla \times \mathbf{B} = \mu_0\left(\mathbf{J} + \epsilon_0\frac{\partial \mathbf{E}}{\partial t}\right)$		

- Charge conservation $\frac{\partial \rho}{\partial t} + \nabla \cdot \mathbf{J} = 0$
- Charge density $\rho(\mathbf{x}, t) = q\int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t)d\mathbf{v}$
- Electric current density $\mathbf{J}(\mathbf{x}, t) = q\int_{-\infty}^{\infty} f(\mathbf{x}, \mathbf{v}, t)\mathbf{v}d\mathbf{v}$
- ϵ_0 and μ_0 are permittivity and permeability of free space

Outline

- Introduction
- Particle-in-Cell Method
- Existing Work for Collisionless Plasma Dynamics
  - Collisionless, Electrostatic Plasma Dynamics
  - Manufactured Solutions
- Approach for Collisional Plasma Dynamics
- Numerical Examples
- Summary

Collisionless, Electrostatic Plasma Dynamics

Collisionless electrostatic plasma dynamics:

$$\frac{dw_p}{dt} = 0, \qquad \frac{d\mathbf{x}_p}{dt} = \mathbf{v}_p, \qquad \frac{d\mathbf{v}_p}{dt} = \frac{q}{m}\mathbf{E}_p, \qquad \Delta\phi = -\frac{\rho}{\epsilon_0}$$

- Riva et al., *Physics of Plasmas* (2017)
  - 1D, electrons
  - Maximum error in $\mathbf{E}$ computed over all $\mathbf{x}_p$ and t
  - Multiple approaches with varying expense to measure error in f
  - Results convincingly converge at expected rates
- Tranquilli et al., *Journal of Computational Physics* (2022)
  - 2D, electrons and ions
  - L^2 norm of error in ρ, $\mathbf{E}$, and ϕ
  - Argues against the need to measure error in f

Manufactured Solutions

Manufacture

- Particle distribution function $f_M(\mathbf{x},\mathbf{v},t) = f_{\mathbf{x}}(\mathbf{x},t) f_{\mathbf{v}}(\mathbf{v})$
- Electromagnetic field $\mathbf{E}_M(\mathbf{x},t)$

Compute source terms based on Vlasov and Poisson equations

$$S_f(\mathbf{x},\mathbf{v},t) = \frac{\partial f_M}{\partial t} + \mathbf{v}\cdot\nabla f_M + \frac{q}{m}\mathbf{E}_M\cdot\frac{\partial f_M}{\partial \mathbf{v}}, \qquad S_{\mathbf{E}}(\mathbf{x},t) = \nabla\cdot\mathbf{E}_M - \frac{\rho}{\epsilon_0}$$

Modify weight evolution equation to be

$$\frac{d}{dt}w_p(t) = \frac{\frac{d}{dt}f_M(\mathbf{x}_p(t),\mathbf{v}_p(t),0)}{f_0(\mathbf{x}_p(0),\mathbf{v}_p(0))}w_p(0) = \frac{S_f(\mathbf{x}_p(t),\mathbf{v}_p(t),t)}{f_0(\mathbf{x}_p(0),\mathbf{v}_p(0))}w_p(0), \qquad w_p(0) = \frac{f_M(\mathbf{x}_p(0),\mathbf{v}_p(0),0)}{f_0(\mathbf{x}_p(0),\mathbf{v}_p(0))}$$

- Particles move without regard to manufactured distribution function
- $\mathbf{x}_p$ and $\mathbf{v}_p$, when weighted by w_p, approach f_M
- Risk of negative weights

Outline

- Introduction
- Particle-in-Cell Method
- Existing Work for Collisionless Plasma Dynamics
- Approach for Collisional Plasma Dynamics
  - Manufactured Particle Distribution Function
  - Collisionless Plasma Dynamics
  - Collisional Plasma Dynamics
- Numerical Examples
- Summary

Manufactured Particle Distribution Function

Assume f_M takes the form of 3D analog of previous work:

$$f_M(\mathbf{x}, \mathbf{v}, t) = f_{\mathbf{x}}(\mathbf{x}, t) f_{\mathbf{v}}(\mathbf{v}),$$

where

$$f_{\mathbf{x}}(\mathbf{x}, t) = N \prod_{i=1}^{3} f_{x_i}(x_i, t), \qquad f_{\mathbf{v}}(\mathbf{v}) = \prod_{i=1}^{3} f_v(v_i), \qquad f_v(v_i) = \frac{2}{\sqrt{\pi}} \frac{v_i^2}{\bar{v}^3} e^{-v_i^2/\bar{v}^2},$$

and

$$\int_0^{L_{x_i}} f_{x_i}(x_i, t) dx_i = 1, \qquad \int_{-\infty}^{\infty} f_v(v_i) dv_i = 1, \qquad \int_V f_{\mathbf{x}}(\mathbf{x}, t) d\mathbf{x} = N$$

- N is the number of physical particles in the volume
- $V = \prod_{i=1}^{3} L_{x_i}$ is the volume

Collisionless Plasma Dynamics

- Follow approach of Riva et al., start with 1D electrostatic plasma dynamics
- After achieving expected convergence rates, generalize to account for
  - Additional dimensions
  - Magnetic field influence
  - Multiple species

Collisional Plasma Dynamics without Lorentz Force

Apply method of manufactured solutions to equations of motion:

$$\dot{\mathbf{x}}_p = \mathbf{v}_p + \dot{\mathbf{x}}_M - \mathbf{v}_M, \qquad \dot{\mathbf{v}}_p = \left(\frac{\Delta \mathbf{v}_p}{\Delta t}\right)_{\text{coll}} + \cancelto{0}{\dot{\mathbf{v}}_M} - \left(\frac{\Delta \mathbf{v}_M}{\Delta t}\right)_{\text{coll}}$$

- Avoids negative weights
- $\mathbf{x}_M$ and $\mathbf{v}_M$ obtained from uniform random samples $F_{\mathbf{x}_p}, F_{\mathbf{v}_p} \in [0,\, 1]$
- Inversely query cumulative distribution functions $F_{\mathbf{x}}(\mathbf{x}_p, t)$ and $F_{\mathbf{v}}(\mathbf{v}_p)$
- Obtain $\mathbf{x}_M$ and $\mathbf{v}_M$ for each computational particle at each time step
- In general, $\dot{\mathbf{x}}_M \neq \mathbf{v}_M$
- $\dot{\mathbf{v}}_M = \mathbf{0}$ since $f_{\mathbf{v}}(\mathbf{v})$ does not depend on time
- $(\Delta \mathbf{v}_M/\Delta t)_{\text{coll}}$ represents analytic expression for the change due to collisions

Example time discretization (forward Euler):

$$\mathbf{x}_p^{n+1} = \mathbf{x}_p^n + \mathbf{v}_p^{n+1}\Delta t + \mathbf{x}_M^{n+1} - (\mathbf{x}_M^n + \mathbf{v}_M \Delta t), \qquad \mathbf{v}_p^{n+1} = \mathbf{v}_p^n + \underbrace{(\Delta \mathbf{v}_p)_{\text{coll}}^n}_{\text{stochastic}} - \underbrace{(\Delta \mathbf{v}_M)_{\text{coll}}^n}_{\text{deterministic}}$$

Source Term for Binary Elastic Collisions (same mass)

Post-collision velocities are obtained from conservation of momentum and energy:

$$\mathbf{v}' = \frac{1}{2}(\mathbf{v}_1 + \mathbf{v} - g\mathbf{n}), \qquad \mathbf{v}_1' = \frac{1}{2}(\mathbf{v}_1 + \mathbf{v} + g\mathbf{n}), \qquad \mathbf{n} = \begin{Bmatrix} \cos\epsilon \sin\chi \\ \sin\epsilon \sin\chi \\ \cos\chi \end{Bmatrix},$$

where $g = |\mathbf{v} - \mathbf{v}_1| = |\mathbf{v}' - \mathbf{v}_1'|$ is the relative speed

For a given particle, the change in velocity is $\Delta\mathbf{v} = \mathbf{v}' - \mathbf{v} = \dfrac{1}{2}(\mathbf{v}_1 - \mathbf{v} - g\mathbf{n})$

Compute expected change in velocity for particle across possible collision partners:

$$\langle \Delta\mathbf{v}_M \rangle_{\text{coll}} = \frac{\frac{1}{2}\int_V \int_{-\infty}^{\infty} \int_0^{2\pi} \int_0^{\pi} P_{\text{coll}}(g)(N_p - 1)(\mathbf{v}_1 - \mathbf{v}_p - g\mathbf{n}) f_M(\mathbf{x}, \mathbf{v}_1, t) p(\chi, \epsilon) d\chi d\epsilon d\mathbf{v}_1 d\mathbf{x}}{\int_V \int_{-\infty}^{\infty} \int_0^{2\pi} \int_0^{\pi} f_M(\mathbf{x}, \mathbf{v}_1, t) p(\chi, \epsilon) d\chi d\epsilon d\mathbf{v}_1 d\mathbf{x}},$$

$P_{\text{coll}}(g)$ is likelihood of collision happening, $p(\chi, \epsilon)$ is probability density function

$\langle \Delta\mathbf{v}_M \rangle_{\text{coll}}$ is deterministic, should be computed analytically – complicated by g

Manufactured Anisotropy (to avoid dependency on g due to $\mathbf{n}p$)

Model probability density function as separable: $p(\chi, \epsilon) = p_\chi(\chi) p_\epsilon(\epsilon)$, where

$$\int_0^{2\pi}\int_0^{\pi} p(\chi,\epsilon)d\chi d\epsilon = 1, \qquad \int_0^{2\pi} p_\epsilon(\epsilon)d\epsilon = 1, \qquad \int_0^{\pi} p_\chi(\chi)d\chi = 1$$

Azimuthally symmetric scattering: $p_\epsilon(\epsilon) = \dfrac{1}{2\pi}$

In expression for $\langle \Delta \mathbf{v}_M \rangle_{\text{coll}}$,

$$g\int_0^{2\pi}\int_0^{\pi} \mathbf{n}p(\chi,\epsilon)d\chi d\epsilon = \frac{g}{2\pi}\int_0^{2\pi}\int_0^{\pi} \mathbf{n}p_\chi(\chi)d\chi d\epsilon = g\left\{0,\, 0,\, \underbrace{\int_0^{\pi} p_\chi(\chi)\cos\chi d\chi}_{=0}\right\}$$

Avoid dependency on g from anisotropy: $\displaystyle\int_0^{\pi} p_\chi(\chi)\cos\chi d\chi = 0$

Avoid isotropy: $p_\chi(\chi) \neq \dfrac{\sin\chi}{2}$

For $F_{p_\chi}^{-1}$, use ansatz $p_\chi(\chi) = (C_0 + C_1\cos\chi + C_2\cos^2\chi + C_3\cos^3\chi)\sin\chi$

C_2 and C_3 satisfy constraint, C_0 and C_1 minimize $\displaystyle\int_0^{\pi}\left(p_\chi(\chi) - \bar{p}_\chi(\chi)\right)^2 d\chi$

Manufactured Cross Section (to evaluate $\langle \Delta \mathbf{v}_M \rangle_{\text{coll}}$ exactly)

With $\int_0^\pi p_\chi(\chi) \cos\chi d\chi = 0$,

$$\langle \Delta \mathbf{v}_M \rangle_{\text{coll}} = \frac{w_p \Delta t (N_p - 1)}{2V} \int_{-\infty}^{\infty} \sigma(g) g(\mathbf{v}_1 - \mathbf{v}_p) f_{\mathbf{v}}(\mathbf{v}_1) d\mathbf{v}_1$$

If $\sigma(g) = \sum_{n=0}^{N_\sigma - 1} \sigma_n g^{2n-1}$,

$$\langle \Delta \mathbf{v}_M \rangle_{\text{coll}} = \frac{w_p \Delta t (N_p - 1)}{2V} \sum_{n=0}^{N_\sigma - 1} \sigma_n \mathbf{f}_n(\mathbf{v}_p),$$

where $\mathbf{f}_n(\mathbf{v}_p) = \int_{-\infty}^{\infty} g^{2n}(\mathbf{v}_1 - \mathbf{v}_p) f_{\mathbf{v}}(\mathbf{v}_1) d\mathbf{v}_1$ can be computed exactly:

$$\mathbf{f}_0(\mathbf{v}_p) = -\mathbf{v}_p, \qquad \mathbf{f}_1(\mathbf{v}_p) = -\frac{1}{2}(15\bar{v}^2 + 2v_p^2)\mathbf{v}_p, \qquad \mathbf{f}_2(\mathbf{v}_p) = -\frac{1}{4}(231\bar{v}^4 + 84\bar{v}^2 v_p^2 + 4v_p^4)\mathbf{v}_p$$

Velocity Evolution

$$\mathbf{v}_p^{n+1} = \mathbf{v}_p^n + \underbrace{\left(\Delta\mathbf{v}_p\right)_{\text{coll}}^n}_{\text{stochastic}} - \underbrace{\left\langle\Delta\mathbf{v}_M\right\rangle_{\text{coll}}^n}_{\text{deterministic}}$$

- $\left\langle\Delta\mathbf{v}_M\right\rangle_{\text{coll}}^n$ is evaluated analytically
- $\left(\Delta\mathbf{v}_p\right)_{\text{coll}}^n$ is computed from a collision algorithm
- Collision algorithms are stochastic – consider random subset of collisions
- Run collision algorithm N_{avg} times, average outcome for each particle

Summary

- Get uniform random samples for each position and velocity component
- Integrate equations of motion
- Each time step, get $\mathbf{x}_M$ and $\mathbf{v}_M$ from inverse of time-varying CDF
- Measure discrete L^p norm of particle position and velocity errors

  $\rightarrow$ One simulation per refinement

Refinement Ratios

Measure discrete L^p norm of particle position and velocity errors

- Discretization error depends on Δt, $\Delta \mathbf{x}$, N_p, N_{avg}, h_{interp}
- Refinement ratios: $r_{\Delta t} = \dfrac{\Delta t_1}{\Delta t_2}$, $r_{N_p} = \frac{N_{p_2}}{N_{p_1}}$, $r_{N_{\text{avg}}} = \frac{N_{\text{avg}_2}}{N_{\text{avg}_1}}$, $r_{h_{\text{interp}}} = \frac{h_{\text{interp}_1}}{h_{\text{interp}_2}}$
- Time integration error is locally $\mathcal{O}(\Delta t^2)$, globally $\mathcal{O}(\Delta t)$
  - Decrease N_p error at same rate as global time error
  - Decrease N_{coll} error at same rate as local time error
- Error due to N_p is $\mathcal{O}(N_p^{-1/2})$ (central limit theorem) $\rightarrow$ $r_{N_p} = r_{\Delta t}^2$
- Error due to the collisions is $\mathcal{O}(N_{\text{coll}}^{-1/2})$, $N_{\text{coll}} \sim N_{\text{avg}} N_p \Delta t$ $\rightarrow$ $r_{N_{\text{avg}}} = r_{\Delta t}^3$
- Error due to interpolating inverse CDFs is $\mathcal{O}(h_{\text{interp}}^2)$ $\rightarrow$ $r_{h_{\text{interp}}} = r_{\Delta t}$

Outline

- Introduction
- Particle-in-Cell Method
- Existing Work for Collisionless Plasma Dynamics
- Approach for Collisional Plasma Dynamics
- Numerical Examples
  - Overview
  - Results
- Summary

Manufactured Cross Section and Anisotropy





- **Cross section** $\sigma(g) = \sum_{n=0}^{N_\sigma - 1} \sigma_n g^{2n-1}, \qquad N_\sigma = 3$
  - Log-scale least squares fitting of data from Itikawa *J. Phys. Chem. Ref.* (2009)
- **Anisotropy** $F_{p_\chi}^{-1}, \quad p_\chi(\chi) = (C_0 + C_1 \cos\chi + C_2 \cos^2\chi + C_3 \cos^3\chi)\sin\chi$
  - $\bar{p}_\chi(\chi) = \alpha \cos(\chi/2)^{2\alpha-1}\sin(\chi/2), \qquad 1 \le \alpha \le 2, \qquad$ (variable soft sphere)
  - Isotropic ($\alpha = 1$), anisotropic ($\alpha > 1$)

Manufactured Distribution Function and Discretizations

- Particle distribution function $f_M(\mathbf{x}, \mathbf{v}, t) = f_\mathbf{x}(\mathbf{x}, t) f_\mathbf{v}(\mathbf{v})$,

$$f_\mathbf{x}(\mathbf{x}, t) = N \prod_{i=1}^{3} f_{x_i}(x_i, t), \qquad f_\mathbf{v}(\mathbf{v}) = \prod_{i=1}^{3} f_v(v_i)$$

- $\bar{v} = 10^6$ m/s, $\quad L_{x_i} = 3/2$ m, $\quad T = L_{x_i}/(10\bar{v})$, $\quad$ periodic BCs

- Discretizations

Disc.	N_p	$T/\Delta t$	N_{avg}	$1/h_{\text{interp}}$
1	50	10	50	1000
2	200	20	400	2000
3	800	40	3200	4000
4	3200	80	25600	8000
5	12800	160	204800	16000

Particle Distribution Function $f_M(\mathbf{x},\mathbf{v},t) = f_\mathbf{x}(\mathbf{x},t)f_\mathbf{v}(\mathbf{v})$



Particle Distribution Function $f_M(\mathbf{x},\mathbf{v},T) = f_{\mathbf{x}}(\mathbf{x},T)f_{\mathbf{v}}(\mathbf{v})$



Error Convergence at $t = T$





- Discrete L^p error norms for particle positions and velocities: $p = 1, 2, \infty$
- Each component converges at expected rate $\mathcal{O}(h)$

$$h \sim \Delta t \sim N_p^{-1/2} \sim N_{\text{avg}}^{-1/3}$$



Outline

- Introduction
- Particle-in-Cell Method
- Existing Work for Collisionless Plasma Dynamics
- Approach for Collisional Plasma Dynamics
- Numerical Examples
- Summary
  - Closing Remarks

Closing Remarks

- Presented code-verification progress for 3D-3V collisional plasma dynamics
- Add manufactured source terms to equations of motion, weights unmodified
- Manufacture distribution function, cross section, and anisotropy
- Analytically compute manufactured source terms, average collisions
- Achieved expected convergence rates without Lorentz force

Questions?

bafreno@sandia.gov brianfreno.github.io

References

- F. Riva and C. Beadle and P. Ricci
  A methodology for the rigorous verification of particle-in-cell simulations
  Physics of Plasmas (2017)

- P. Tranquilli and L. Ricketson and L. Chacón
  A deterministic verification strategy for electrostatic particle-in-cell algorithms in arbitrary spatial dimensions using the method of manufactured solutions
  Journal of Computational Physics (2022)