

Gunter & Scott 1990 — Inventory of Definitions and Theorems

Source: **C. A. Gunter and D. S. Scott**, “**Semantic Domains**,” *Handbook of Theoretical Computer Science* Vol. B, North-Holland, 1990, pp. 633–674 ([../papers/Gunter Scott 1990.pdf](#)).

The work list for the Lean formalization: every definition and every one of the paper’s **30 numbered results** (Theorems / Lemmas / Proposition 1–30), in paper order, matched to its Lean equivalent.

Progress (as of r0009, 2026-0806)

#	Quantity	Done	Remaining	Of
1	Definitions to define	4	9	≈13
2	Numbered results to prove	0	28	28
3	Mathlib foundations reused	12	—	12
4	sorry in the development	—	0	—

4 of ≈13 definitions are formally verified and building, in 6 modules, 985 lines, 0 sorry, 0 warnings:

#	Round	Module	Contents
1	r0003	ScottDomains/WayBelow.lean	way-below $\ll$ at [Preorder α], 7 theorems; $x \ll x \leftrightarrow \text{IsCompactElement } x$ holds by <code>Iff.rfl</code>
2	r0004	ScottDomains/Domain.lean	<code>IsAlgebraic</code> , <code>Domain</code> (with the paper’s countable-basis condition), <code>BoundedComplete</code> , 8 theorems, <code>Domain Prop</code>
3	r0005	ScottDomains/Powerset.lean	the paper’s P N (p. 9): compacts of <code>Set X</code> are exactly the finite subsets, hence <code>Domain (Set ℕ)</code> — the nondegenerate witness
4	r0006–r0007	ScottDomains/ScottHom.lean	the continuous function space $D \rightarrow E$: <code>ScottHom</code> , the pointwise order, <code>CompletePartialOrder</code> , and <code>BoundedComplete</code> when <code>E</code> is — Theorem 7’s first sentence in full
5	r0008	ScottDomains/StepFunction.lean	the single step function <code>step k e</code> : continuity (from <code>k</code> compact), the adjunction <code>step k e ≤ f ↔ e ≤ f k</code> , and compactness in $D \rightarrow E$ (from <code>e</code> compact)
6	r0009	ScottDomains/FunctionSpaceDomain.lean	<code>IsAlgebraic</code> — the paper’s “they form a basis for $D \rightarrow E$ ”; the two halves of <code>IsAlgebraic</code> use disjoint hypotheses (directedness needs only <code>E</code> bounded complete; the <code>lub</code> needs only <code>D</code> , <code>E</code> algebraic)

Next: countability of $K(D \rightarrow E)$ — every compact function is a finite join of step functions — which is all that remains between here and **Theorem 7**, the first numbered result.

Work counts

- **Reuse from Mathlib — no work (12)**: poset, directed, cpo, $\perp$, monotone, continuous, Fixed-Point Theorem (1) & operator, Schröder–Bernstein (2), algebraic lattice, product, λ -notation.
- **Generalize / adapt (4)**: compact element (`IsCompactElement` — its *definition* is already stated at [PartialOrder α] and so applies to a `dcpo` verbatim; what is `CompleteLattice`-only is every lemma about it, so the `dcpo` API must be re-proved), `sum`, `lift` (`WithBot/Sum`), ideal completion (`Order.Ideal`).

- **Definitions to define — new (≈13; 4 done in r0003–r0004, 9 remaining):** way-below $\ll$ (done — ScottDomains/WayBelow.lean), algebraic cpo, **domain**, bounded-complete (all three done — ScottDomains/Domain.lean), embedding–projection pair, (finitary) projection, normal subposet, effective presentation, smash product, the three powerdomains (Hoare / Smyth / Plotkin), bifinite / Plotkin order, and D^∞ .
- **Theorems to prove (28):** 28 of the paper’s 30 numbered results — Theorems 3, 6, 7, 11, 12, 14, 16, 18, 21, 22, 25, 26, 27, 29; Lemmas 4, 5, 8–10, 13, 17, 19, 20, 23, 24, 28, 30; Proposition 15. Only Theorems 1 & 2 come free from Mathlib.

Bottom line: ≈13 definitions to define + 28 results to prove, on top of 12 reused Mathlib foundations. After r0004: 9 definitions + 28 results remain.

Lean column legend: ✓ reuse Mathlib (name given) · ~ partial (Mathlib has a related or lattice-only version — generalize) · ✕ define / prove (absent from Mathlib v4.32.2, confirmed by grep).

Statements are paraphrased/de-garbled from the PDF (1990 Type-3 fonts render → as !, drop fi ligatures, mangle math), so read them as a guide to *what* each result is. Notation: $\sqsubseteq$ order, $\sqcup$ directed sup, $\perp$ bottom, $\ll$ way-below, $K(D)$ compacts, $Fp(D)$ finitary projections.

§2 Recursive definitions of functions

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
2.1	Def	—	poset (partially ordered set)	✓ PartialOrder
2.1	Def	—	directed subset M : every finite $u \subseteq M$ has an upper bound in M	✓ DirectedOn / IsDirected
2.1	Def	—	cpo : poset in which every directed M has a lub $\sqcup M$	✓ CompletePartialOrder (chains: OmegaCompletePartialOrder)
2.1	Def	—	bottom $\perp$ (least element)	✓ OrderBot
2.1	Def	—	monotone function	✓ Monotone / OrderHom
2.1	Def	—	continuous : monotone, $f(\sqcup M) = \sqcup f(M)$ for directed M	✓ ScottContinuous
2.1	Thm	1	Fixed-Point Theorem : $f : D \rightarrow D$ continuous $\implies$ least fixed point $\sqcup_n f^n(\perp)$	✓ OrderHom.lfp (Kleene: OmegaCompletePartialOrder)
2.2	Thm	2	Schröder–Bernstein for sets	✓ Function.Embedding.schroederBernstein
2.3	Def	—	fixed-point operator (uniform)	✓ OrderHom.lfp / LawfulFix
2.3	Thm	3	The standard operator is the unique uniform fixed-point operator	✕ prove

§3 Effectively presented domains

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
3.1	Def	—	compact element x : $x \sqsubseteq \sqcup M \text{ (dir.)} \implies x \sqsubseteq y \text{ some } y \in M; K(D)$	~ IsCompactElement — def is [PartialOrder], so reusable on a dcpo; its lemmas are all CompleteLattice-only
3.1	Def	—	way-below $\ll$ (approximation relation behind compactness)	✓ ScottDomains.WayBelow (r0003) — $x \ll x \leftrightarrow \text{IsCompactElement } x$ by Iff.rfl
3.1	Def	—	algebraic cpo: $x = \sqcup \{x' \in K(D) : x' \sqsubseteq x\}$ (directed)	✓ ScottDomains.IsAlgebraic (r0004)
3.1	Def	—	domain = algebraic cpo whose basis $K(D)$ is countable (the paper’s definition, p. 9 — the countability condition was missing from an earlier draft of this row)	✓ ScottDomains.Domain (r0004)

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
3.1	Def	—	bounded complete: $\perp +$ every bounded subset has a sup — a <i>separate</i> predicate; the paper composes them as “bounded complete domain” (Thm 7, Lem 10, Lem 13, Thm 14), which is the literature’s <i>Scott domain</i>	✓ <code>ScottDomains.BoundedComplete</code> (r0004); the compound is <code>[Domain α] [BoundedComplete α]</code>
3.1	Def	—	(countably based) algebraic lattice	✓ <code>IsCompactlyGenerated</code> (+ <code>CompleteLattice</code>)
3.1	Def	—	embedding–projection pair (g, f)	✗ define
3.1	Def	—	projection; finitary projection p : $p \circ p = p \sqsubseteq \text{id}$, $\text{im}(p)$ a domain	✗ define
3.1	Def	—	normal subposet / substructure	✗ define
3.1	Lem	4	$\langle P(C), \sqsubset \rangle$ of substructures is a cpo with $\{\perp\}$ least	✗ prove
3.1	Lem	5	p finitary projection $\implies$ compacts of $\text{im}(p)$ are $\{p(x) : x \in K(D)\}$	✗ prove
3.1	Thm	6	Isomorphism: normal substructures $\cong \text{Fp}(D)$ (finitary projections)	✗ prove
3.1	Thm	7	D, E bounded-complete domains $\implies D \rightarrow E$ bounded-complete domain	✗ prove
3.2	Def	—	effective presentation $d : \mathbb{N} \rightarrow K(D)$; effectively presented domain	✗ define

§4 Operators and functions

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
4.1	Def	—	product $D \times E$	✓ <code>Prod</code> (order/cpo instances)
4.2	Def	—	Church’s λ-notation (continuous abstraction)	✓ <code>OrderHom / ωCPO ContinuousHom</code>
4.3	Def	—	smash product $D \otimes E$	✗ define
4.4	Def	—	sum $D + E$; lift $D\perp$	~ <code>Sum / WithBot, Part</code> (partial)
4.x	Lem	8	Currying/iso laws for function spaces over D, E, F	✗ prove
4.x	Lem	9	Product/function-space iso laws over D, E, F	✗ prove
4.5	Lem	10	D, E bounded complete $\implies \rightarrow, \times, \otimes, +, ()\perp$ bounded complete	✗ prove
4.5	Thm	11	Ideal completion of a countable pre-order is a domain (all domains so arise)	~ <code>Order.Ideal</code> exists $\rightarrow$ prove
4.5	Thm	12	Initiality of a continuous algebra satisfying axioms T	✗ prove
4.5	Lem	13	D bounded complete $\implies$ powerdomains $D], D[$ bounded complete	✗ prove
4.5	Thm	14	Equivalent characterizations of an (algebraic/BC) domain	✗ prove

§5 Powerdomains

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
5.1	Def	—	powerdomain (non-deterministic outcomes)	✗ define
5.2	Def	—	Hoare (lower), Smyth (upper), Plotkin (convex) powerdomains	✗ define
5.3	—	—	Universal & closure properties (see Lem 13, 28, 30)	✗ prove

§6 Bifinite (SFP) domains

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
6.1	Def	—	Plotkin order / bifinite (SFP) domain: bilimit of finite pointed posets	✗ define
6.1	Prop	15	Every bounded-complete domain is bifinite	✗ prove
6.1	Thm	16	D bifinite $\implies \text{Fp}(D)$ is an algebraic lattice	✗ prove
6.2	Lem	17	D, E bifinite $\implies \rightarrow, \times, \otimes, +, ()^\perp$ bifinite (incl. function space)	✗ prove
6.2	Thm	18	If D and $D \rightarrow D$ are domains, then D is bifinite	✗ prove
6.2	Lem	19	closure $r : D \rightarrow D$ ($r \circ r = r \sqcup \text{id}$) $\implies \text{im}(r)$ is a domain	✗ prove
6.2	Lem	20	D domain $\implies \text{Fc}(D)$ (finitary closures) is a cpo	✗ prove

§7 Recursive definitions of domains (universal domain, D_∞)

§	Kind	Ref	Concept / statement	In Lean / Mathlib?
7	Def	—	recursive domain equation; universal domain / D_∞ (inverse limit)	✗ define
7	Thm	21	F representable over cpo $U \implies$ a domain D with $D \cong F(D)$	✗ prove
7	Thm	22	Any countably-based algebraic lattice L : a closure $r : P(\mathbb{N}) \rightarrow L$	$\sim \text{IsCompactlyGenerated} \rightarrow$ prove
7	Lem	23	The function-space operator is representable over $P(\mathbb{N})$	✗ prove
7	Lem	24	U cpo; $\times$ and $\rightarrow$ representable over $U \implies$ (setup for universality)	✗ prove
7	Thm	25	U non-trivial domain representing $\times, \rightarrow \implies U$ universal	✗ prove
7	Thm	26	Any signature $(s_1, \dots, s_n)$: combinators $F_1, \dots, F_n$ solving the equations	✗ prove
7	Thm	27	Any bounded-complete D : a projection of the universal domain onto D	✗ prove
7	Lem	28	Operators $\rightarrow, \times, \otimes, +, ()^\perp, ()^\perp, ()^\perp$ representable over U	✗ prove
7	Thm	29	D bifinite $\implies D^+$ bifinite; solving $D \cong D^+$	✗ prove
7	Lem	30	Operators $\rightarrow, \times, \otimes, +, ()^\perp, ()^\perp, ()^\perp$ p-representable over universal bifinite V	✗ prove

Tally (matched): ✓ reuse Mathlib $\approx$ **12** (poset, directed, cpo, $\perp$, monotone, continuous, fixed-point Thm 1 & operator, Schröder–Bernstein, algebraic lattice, product, λ -notation) · $\sim$ partial $\approx$ **4** (compact element, sum/lift, ideal completion Thm 11, Thm 22) · $\times$ define / prove $\approx$ **44**, of which 4 are done ($\ll$ r0003; algebraic, domain, bounded-complete r0004) $\rightarrow$ **40 remaining** — the bifinite / powerdomain / D^∞ development and all 28 numbered results.

What is done, and what is next, is listed under **Progress** at the top of this file.