

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

# Powerdomains in Isabelle / HOLCF

Brian Huffman

Portland State University

February 8, 2008

# Outline

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

## 1 Overview of domain theory

- 1 Basics: partial orders, cpos, continuity, fixed points
- 2 Advanced: compactness, bifinite cpos, compact bases

## 2 Properties of powerdomains

## 3 Formalization using ideal completion

## 4 Applications: interleaving and concurrency

# Information Ordering

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

Information order relation:  $\sqsubseteq$

- $x \sqsubseteq y$  means that  $x$  approximates  $y$
- $\sqsubseteq$  is a partial order (reflexive, transitive, antisymmetric)
- $\perp$  denotes the least element:  $\forall x. \perp \sqsubseteq x$

Example: Haskell List datatype

- $\perp \sqsubseteq (1 : \perp) \sqsubseteq (1 : 2 : \perp) \sqsubseteq (1 : 2 : 3 : \perp) \sqsubseteq (1 : 2 : 3 : [])$
- Constructors preserve ordering:  
$$x : xs \sqsubseteq y : ys \iff x \sqsubseteq y \wedge xs \sqsubseteq ys$$

# Completeness

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

A **chain** is a sequence  $a$  with increasing information:

$$\blacksquare a_0 \sqsubseteq a_1 \sqsubseteq a_2 \sqsubseteq a_3 \sqsubseteq a_4 \sqsubseteq \dots$$

A **cpo** has **least upper bounds** for all chains:

$$\blacksquare a_0 \sqsubseteq a_1 \sqsubseteq a_2 \sqsubseteq a_3 \sqsubseteq a_4 \sqsubseteq \dots \rightsquigarrow \bigsqcup_n a_n$$

Example: lub of partial lists may be an infinite list

$$\blacksquare a_0 = \perp, a_1 = 1 : \perp, a_2 = 1 : 1 : \perp, a_3 = 1 : 1 : 1 : \perp, \dots$$

$$\blacksquare \bigsqcup_n a_n = \text{ones} = 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : 1 : \dots$$

# Continuity

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory  
Basics  
Advanced

Powerdomains  
Powerset  
Ordering  
Varieties

Formalization  
Compact basis  
Defining operations  
Properties

Applications

A **continuous** function  $f$  preserves least upper bounds:

- $f(\bigsqcup_n a_n) = (\bigsqcup_n f(a_n))$

Continuous functions must also be **monotone**:

- $x \sqsubseteq y$  implies  $f(x) \sqsubseteq f(y)$
- Monotonicity ensures that  $f(a_n)$  is a chain

Every continuous  $f$  over a pointed cpo has a **least fixed point**:

- $\perp \sqsubseteq f(\perp) \sqsubseteq f(f(\perp)) \sqsubseteq f(f(f(\perp))) \sqsubseteq \dots \rightsquigarrow \text{fix}(f)$

# Admissibility

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory  
Basics  
Advanced

Powerdomains  
Powerset  
Ordering  
Varieties

Formalization  
Compact basis  
Defining operations  
Properties

Applications

An **admissible** predicate  $P$  is preserved by lubs:

- $(\forall n. P(a_n)) \implies P(\bigsqcup_n a_n)$  for any chain  $a$

Many constructions preserve admissibility:

- $(\lambda x. P(x) \wedge Q(x))$  is admissible if  $P$  and  $Q$  are
- $(\lambda x. P(x) \vee Q(x))$  is admissible if  $P$  and  $Q$  are
- $(\lambda x. f(x) = g(x))$  is admissible for continuous  $f$  and  $g$
- $(\lambda x. f(x) \sqsubseteq g(x))$  is admissible for continuous  $f$  and  $g$

Admissibility is important for **fixed point induction**:

- For admissible  $P$ , if  $P(\perp)$  and  $\forall x. P(x) \implies P(f(x))$ , then  $P(\text{fix}(f))$

# Compactness

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

An infinite value may be the lub of a chain of strictly smaller values:

$$\blacksquare \perp \sqsubseteq 1 : \perp \sqsubseteq 1 : 1 : \perp \sqsubseteq 1 : 1 : 1 : \perp \sqsubseteq \dots \rightsquigarrow \text{ones}$$

But a **compact** value  $k$  cannot be written this way:

- Any chain with lub  $k$  must contain  $k$
- $k \sqsubseteq (\bigsqcup_n a_n) \sqsubseteq k \implies \exists n. k \sqsubseteq a_n$
- $(\lambda x. x \neq k)$  and  $(\lambda x. x \not\sqsubseteq k)$  are admissible
- Intuitively,  $k$  has a finite amount of information

Example: ordinal numbers

- Successor ordinals are compact, limit ordinals are not

# Finite approximation

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

**Bifinite cpos** admit a notion of finite approximation:

- $\text{take}_0(x) \sqsubseteq \text{take}_1(x) \sqsubseteq \text{take}_2(x) \sqsubseteq \text{take}_3(x) \sqsubseteq \dots \rightsquigarrow x$
- $\text{take}_n(\text{take}_n(x)) = \text{take}_n(x)$
- Each function  $\text{take}_n$  should have finite range
- $\text{take}_n(x)$  is compact for any  $x$
- $x$  is compact iff  $\exists n. \text{take}_n(x) = x$

Example: Haskell list type

- $\text{take}_0(xs) = \perp$
- $\text{take}_{n+1}(x : xs) = \text{take}_n(x) : \text{take}_n(xs)$
- $\text{take}_3(\text{ones}) = 1 : 1 : 1 : \perp$



# Directed sets and Ideals

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

A **directed set**  $S$  contains an upper bound for every finite subset:

$$\blacksquare \forall \text{finite } M \subseteq S. \exists z \in S. \forall x \in M. x \sqsubseteq z$$

Equivalently,  $S$  is nonempty and has an upper bound for every pair of elements:

$$\blacksquare \exists x \in S \text{ and } \forall x \in S. \forall y \in S. \exists z \in S. x \sqsubseteq z \wedge y \sqsubseteq z$$

A directed set  $S$  is an **ideal** if it is also downward-closed:

$$\blacksquare \forall x y. x \sqsubseteq y \implies y \in S \implies x \in S$$

$\blacksquare$  For any  $x$ , the set  $x \downarrow = \{y. y \sqsubseteq x\}$  is an ideal, called a principal ideal

# Ideal Completion

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory  
Basics  
Advanced

Powerdomains  
Powerset  
Ordering  
Varieties

Formalization  
Compact basis  
Defining operations  
Properties

Applications

Let  $(A, \sqsubseteq)$  be a partial order, but not a cpo

- Some chains do not have least upper bounds
- Can we extend it to a cpo by adding the missing lubs?

Yes! The set  $\text{Ideal}(A)$  of ideals over  $A$  is a cpo:

- Let  $\sqsubseteq$  be the subset ordering on ideals
- The union of a chain of ideals is an ideal
- Principal ideals are exactly the compact elements

We say that  $A$  is a **compact basis** for  $\text{Ideal}(A)$

- $K(\text{Ideal}(A)) \simeq A$
- $\text{Ideal}(K(B)) \simeq B$  for a bifinite cpo  $B$

# Examples of Ideal Completion

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

## Natural numbers with $\leq$ :

- The naturals with  $\leq$  form a partial order, but not a cpo (some chains like  $1, 2, 3, 4, 5, \dots$  have no least upper bound)
- Ideals over  $\text{nat}$  are nonempty, downward-closed sets
- Most ideals are principal, like  $\{0\}$ ,  $\{0, 1\}$ ,  $\{0, 1, 2, 3\}$
- There is one non-principal ideal —  $\omega$ . The addition of  $\omega$  at the top of the ordering turns the naturals into a cpo.

## Lists with the prefix ordering:

- Infinite chains like  $[], [1], [1, 2], [1, 2, 3], \dots$  are unbounded
- Non-principal ideals represent infinite lists

# Compact Bases

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

Some more notes about compact bases and bifinite cpos:

- The set  $K(x)$  of compact approximations to  $x$  is an ideal
- $x$  is the least upper bound of  $K(x)$
- A continuous function is completely determined by its values on compact inputs
- If admissible predicate  $P$  holds for all compact  $x$ , then it holds for all  $x$

# Outline

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

- 1 Overview of domain theory
- 2 **Properties of powerdomains**
  - 1 Powerset monad
  - 2 Information ordering on powerdomains
  - 3 Varieties: convex, upper, and lower
- 3 Formalization using ideal completion
- 4 Applications: interleaving and concurrency

# Powerset monad

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

**Powerset**  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

A nondeterministic function can be modeled as a function that returns a set of possible results.

# Powerset monad

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

## Operations:

- $\text{unit} :: A \rightarrow \wp(A)$   
 $\text{unit}(x) = \{x\}$
- $\text{bind} :: \wp(A) \rightarrow (A \rightarrow \wp(B)) \rightarrow \wp(B)$   
 $\text{bind}(m, f) = \bigcup_{x \in m} f(x)$
- $\text{mplus} :: \wp(A) \rightarrow \wp(A) \rightarrow \wp(A)$   
 $\text{mplus}(m, n) = m \cup n$

## Properties:

- unit and bind satisfy the monad laws
- mplus is associative, commutative, and idempotent

# Powerset monad

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

**Powerset**  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

Can we make the powerset monad into a cpo?

- This would let us combine nondeterminism with recursion

Possibility: use subset ordering

- Ordering is complete (use set-union for lubs)
- However, unit operation  $x \mapsto \{x\}$  is not monotone!

Information ordering on  $\wp(A)$  must respect ordering on  $A$



# Powerdomain ordering

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

Requirements for a powerdomain ordering:

- ordering must give a cpo
- unit, bind, and mplus must be monotone and continuous

Examples:

- $\{\perp, 1\} \sqsubseteq \{1, 1\} = \{1\}$
- $\{\perp\} = \{\perp, \perp\} \sqsubseteq \{1, \perp\} = \{1, \perp, \perp\} \sqsubseteq \{1, 2, \perp\} \dots$

Powerdomain ordering identifies sets with the same convex closure:

- assume  $x \sqsubseteq y \sqsubseteq z$
- $\{x, z\} = \{x, x, z\} \sqsubseteq \{x, y, z\}$
- $\{x, y, z\} \sqsubseteq \{x, z, z\} = \{x, z\}$

# Free Continuous Algebras

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

Consider the free continuous algebra over  $\{-\}$  and  $\uplus$ , modulo these laws:

- $\sqsubseteq$  is a partial order
- $x \sqsubseteq y \implies \{x\} \sqsubseteq \{y\}$
- $a \sqsubseteq a' \wedge b \sqsubseteq b' \implies a \uplus b \sqsubseteq a' \uplus b'$
- $(a \uplus (b \uplus c)) = ((a \uplus b) \uplus c)$
- $a \uplus b = b \uplus a$
- $a \uplus a = a$

(bind can be defined uniquely in terms of unit and mplus)  
This specifies a powerdomain called the **convex powerdomain**.

# Varieties of powerdomains

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

We can add extra laws to create more varieties:

- Adding  $a \uplus b \sqsubseteq a$  gives the **upper powerdomain**
- Adding  $a \sqsubseteq a \uplus b$  gives the **lower powerdomain**

If  $a$  and  $b$  are finite (i.e. finite combinations of  $\{-\}$  and  $\uplus$ ) then:

- $a \sqsubseteq b$  in upper powerdomain iff  $\forall y \in b. \exists x \in a. x \sqsubseteq y$
- $a \sqsubseteq b$  in lower powerdomain iff  $\forall x \in a. \exists y \in b. x \sqsubseteq y$
- $a \sqsubseteq b$  in convex powerdomain iff  $\forall y \in b. \exists x \in a. x \sqsubseteq y$   
and  $\forall x \in a. \exists y \in b. x \sqsubseteq y$

# Outline

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations  
Properties

Applications

- 1 Overview of domain theory
- 2 Specification of powerdomains
- 3 **Formalization using ideal completion**
  - 1 Compact basis for powerdomains
  - 2 Defining operations using compact basis
  - 3 Transferring properties from basis
- 4 Applications: interleaving and concurrency

# Compact Basis for Powerdomains

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

Compact elements of the powerdomain are finite, nonempty sets of compact elements:

```
typedef 'a pd_basis =  
  {S::K('a) set. finite S ∧ nonempty S}
```

We also define the unit and mplus operations on the basis:

```
basis_unit x = {x}  
basis_mplus t u = t ∪ u
```

The ordering for the convex powerdomain is defined thus:

$$t \sqsubseteq u = (\forall x \in t. \exists y \in u. x \sqsubseteq y) \wedge (\forall y \in u. \exists x \in t. x \sqsubseteq y)$$

The ordering is not antisymmetric, but we can quotient by equivalence.

# Defining Powerdomain by Ideal Completion

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

Now we can define the convex powerdomain type constructor:

```
typedef 'a convex_pd =  
  {S::'a pd_basis set. ideal S}
```

We can also define a function for embedding basis elements:

```
principal :: 'a pd_basis => 'a convex_pd  
principal x = Abs_convex_pd {y. y  $\sqsubseteq$  x}
```

# Defining Functions on a Basis

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

To define a function from  $A$  to  $B$ , if  $A$  has compact basis  $C$ :

- First define a monotone function from  $C$  to  $B$
- Uniquely extend that function to all of  $A$

Definition:

$$\text{basis\_fun } f \ x = (\bigsqcup a \in K(x). \ f(x))$$

Desired property:

$$\text{basis\_fun } f \ (\text{principal } a) = f \ a$$

How do we know the lub exists? This is equivalent:

$$\begin{aligned} \text{basis\_fun } f \ x = \\ (\bigsqcup n. \ \bigsqcup a \in \text{take } n \ ' \ K(x). \ f(x)) \end{aligned}$$

- inner lub exists because the set is finite and directed
- outer lub exists because it is a chain

# Defining Powerdomain Operations

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

To define unit, mplus:

```
unit = basis_fun ( $\lambda$ x.  
  principal (basis_unit x))
```

```
mplus = basis_fun ( $\lambda$ t.  
  basis_fun ( $\lambda$ u.  
    principal (basis_mplus t u)))
```



# Defining Powerdomain Operations

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

To define bind:

```
basis_bind (basis_unit x) = ( $\lambda f.$  f x)
```

```
basis_bind (basis_mplus a b) =
```

```
( $\lambda f.$  mplus (basis_bind a f)
```

```
(basis_bind b f))
```

```
bind = basis_fun basis_bind
```

# Proving Properties of Operations

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics  
Advanced

Powerdomains

Powerset  
Ordering  
Varieties

Formalization

Compact basis  
Defining operations

Properties

Applications

We can lift many properties from `pd_basis` to `convex_pd` using this rule:

```
lemma principal_induct:  
  adm P ==>  
    (∀t. P (principal t)) ==>  
    (∀a. P a)
```

For example:

```
∀a b. mplus a b = mplus b a  
∀t b. mplus (principal t) b  
      = mplus b (principal t)  
∀t u. mplus (principal t) (principal u)  
      = mplus (principal u) (principal t)
```

# Applications: Interleaving and Concurrency

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

The convex powerdomain constructor can model nondeterminism directly.

It can also model concurrency, when used together with a resumption monad transformer:

- Use resumptions to model waiting threads
- Use mplus operator to nondeterministically choose which thread to run
- Powerdomain models the set of possible interleavings

# Applications: Interleaving and Concurrency

Powerdomains  
in Isabelle /  
HOLCF

Brian  
Huffman

Domain theory

Basics

Advanced

Powerdomains

Powerset

Ordering

Varieties

Formalization

Compact basis

Defining operations

Properties

Applications

I formalized a resumption monad transformer in HOLCF a while back

- Combined with powerdomains, we can now formalize interesting results about monads with concurrency, state, nondeterminism, etc.
- Having an axiomatic constructor class for powerdomains means that it is easy to try different varieties of powerdomain