


SIM7020-TE Kit_User Guide_V1.0





Document Title:	SIM7020-TE Kit_User Guide
Version:	1.0
Date:	2018-01-19
Status:	Release
Document Control ID:	SIM7020-TE Kit_User Guide_V1.0

General Notes

SIMCom offers this information as a service to its customers, to support application and engineering efforts that use the products designed by SIMCom. The information provided is based upon requirements specifically provided to SIMCom by the customers. SIMCom has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by SIMCom within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

Copyright

This document contains proprietary technical information which is the property of SIMCom Limited., copying of this document and giving it to others and the using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights reserved in the event of grant of a patent or the registration of a utility model or design. All specification supplied herein are subject to change without notice at any time.

Copyright © Shanghai SIMCom Wireless Solutions Ltd. 2018



1 Contents

1	Conte	nts	3
2	Versio	n History	5
3	SIM7020-TE		
	3.1	USB interface	8
	3.2	RF connectors	8
	3 3	Test Points	9



Figure Index

FIGURE 1: SIM7020-TE TOP VIEW	6
FIGURE 2: SIM7020-TE BOTTOM VIEW	7
FIGURE 3: USB INTERFACE	8
FIGURE 4: USB TERMINALS	8
FIGURE 5: RF CONNECTORS	8
FIGURE 6: TEST POINTS FOR EXTERNAL POWER SUPPLY	g



2 Version History

Data	Version	Description of change	Author
2018-01-19	1.0	Origin	Ming.zhu

SCOPE

SIM7020-TE is equipped with SIMCOM-EVB. The main function of TE board is connection between module and SIMCOM-EVB. This document describes helpful information to use SIM7020-TE.

This document is subject to change without notice at any time.



3 SIM7020-TE




Figure 1: SIM7020-TE TOP view






Figure 2: SIM7020-TE BOTTOM view

- A: RF connectors for LTE antenna
- B: SIM7020
- C: USB connector
- D: WakeUp Switch for PSM mode which contect to RTC_EINT
- E: USB Download Switch (useless)
- F: Connector for SIMCOM-EVB
- G: Connector for SIMCOM-EVB



3.1 USB interface

SIM7020-TE provide a USB interface, which is used for debuging. This interface is compliant with the USB1.1 specification.




Figure 3: USB interface




Figure 4: USB terminals

3.2 RF connectors




Figure 5: RF connectors

As the R103 presenced, the default RF connector is J102.



3.3 Test Points

There are two test points for external power supply. Customers can use external power supply for SIM7020 when R104 is unpresenced. The power range should apply to SIM7020's VBAT range, typ 3V3.




Figure 6: Test Points for external power supply



Contact us

Shanghai SIMCom Wireless Solutions Ltd.

Address: Building A, SIM Technology Building, No.633, Jinzhong Road, Changning District, Shanghai 200335

Tel: 86-21-32523300 Fax: 86-21-32523020 Email: simcom@sim.com

Website:www.simcomm2m.com