


Ethanol Blending in Gasoline - Ecuador

July 2026



20 F St. NW, Suite 900 \ Washington, DC 20001
202-789-0789 \ www.grains.org

FARO90



www.faro90.com
+52 55 6122 2255

Ethanol Blending in Latin America

There are important fuel quality and environmental impact of vehicle emission challenges in the Region.

- The use of ethanol improves gasoline quality and creates flexibility in gasoline production.
- Ethanol use is a cost-effective way to increase gasoline octane and to replace more expensive gasoline components.
- Ethanol contributes to transport decarbonization and air quality improvement.
- There are opportunities across Latin America to increase the ethanol blend level and implement new policies on the use of gasoline-ethanol blends.

Sixteen countries with potential and additional use of ethanol were studied: 1) gasoline market profiles; 2) Optimization of gasoline blends with ethanol and 3) Environmental impact of gasolines blended with ethanol.




Ethanol Blending in Gasoline - Ecuador



In 2025, gasoline consumption in Ecuador was 1,205 million gallons (4,561 million liters). A new plan was established to implement new grades of gasoline: four grades with 5 different types according to the current quality norm (NTE INEN 935:2021): Extra (RON 85), Ecopais E10 (RON 85), Ecoplus (RON 89), Súper (RON 92) and Super Premium (RON 95). Super Premium (RON 95) will gradually substitute Super (RON 92). Gasoline Ecoplus (RON 89) was recently introduced in the market. Ecuador has local production and imports naphtha (unfinished gasolines) to supply national demand.


There is no specific mandate for ethanol blending, however there is a permit to blend it with gasoline. Ethanol has been blending in gasoline since 2009. Today the usual blend is E10 for Ecoplus and Super. Ecopais gasoline is supplied in some provinces with an ethanol content between 3-4%. Gasoline Ethanol is produced, consumed and exported to neighboring countries for fuel and industrial use.

Gasoline Demand in Ecuador




Source: EP PETROEQUADOR, 2024

Gasoline Production in Ecuador




Source: EP PETROEQUADOR, 2024

Gasoline Imports in Ecuador



Source: EP PETROEQUADOR, 2024

Ethanol Balance in Ecuador




Source: EP PETROECUADOR, 2024; CEDRSSA, 2020

Gasoline Quality in Ecuador

Name	NTE INEN 935:2021				EN 228:2012 + A1:2017 (Euro 6 enabling)			
Implementation Date	2021				2017			
Applicability	Whole country	Whole country	Whole country	Whole country	All countries			
Selected Grade	RON 85	RON 89	RON 92	RON 93	RON 95 E5	RON 95 E10	RON 98 E5	RON 98 E10
Benzene Content	< 1 %v/v	< 2 %v/v	<2 %v/v	<1,3 %v/v	< 1 %v/v	< 1 %v/v	< 1 %v/v	< 1 %v/v
Aromatics	< 30 %v/v	< 35 %v/v	< 35 %v/v	< 35 %v/v	< 35 %v/v	< 35 %v/v	< 35 %v/v	< 35 %v/v
Olefins	< 18 %v/v	< 25 %v/v	< 25 %v/v	< 25 %v/v	< 18 %v/v	< 18 %v/v	< 18 %v/v	< 18 %v/v
Lead Content	< 0 mg/l	< 0 mg/l	< 0 mg/l	< 0 mg/l	< 5 mg/l	< 5 mg/l	< 5 mg/l	< 5 mg/l
Manganese	0 mg/l	0 mg/l	0 mg/l	0 mg/l	< 2,0 mg/l	< 2,0 mg/l	< 2,0 mg/l	< 2,0 mg/l
RON	85	89	92	95	> 95	> 95	> 98	> 98
MON					> 85	> 88	> 85	> 88
AKI								
Sulfur Content	650 mg/kg	650 mg/kg	450 mg/kg	<300 mg/kg	< 10 mg/kg	< 10 mg/kg	< 10 mg/kg	< 10 mg/kg
Oxygen Content	< 2,7 %m/m	< 2,7 %m/m	< 2,7 %m/m	< 2,7 %m/m	<2,7 % m/m	<3,7 % m/m	<2,7 % m/m	<3,7 % m/m
Ethanol (EtOH)					<5 %v/v	<10 %v/v	<5 %v/v	<10 %v/v
RVP 37.8°C (Summer)	<60 kPa	<60 kPa	<60 kPa	<62 kPa	<> 60 - 70 kPa *Depends on the country, RVP is regulated in the EU Fuel Quality Directive			
RVP 37.8 °C(Winter)								
RVP 37.8°C (Transition)								
MTBE					-	-	-	-
Ethers 5 or more C Atoms	-	-	-	-	Based on oxygen content	<22 %v/v	Based on oxygen content	<22 %v/v

Gasoline Component Blending in Latin America

Gasoline is a blend of a base gasoline and other components. This blending is usually done at blending terminals as only 30% of the world's finished gasoline is distributed directly from refineries. Each component provides different properties to the final blend, for example, isomerates, alkylates and butanes increase the octane. The components commonly used in Latin America are:




Gasoline Blending Optimization

In some parts of the world, ethanol is added to gasoline as a blending component. The advantages of ethanol include that it is a renewable fuel made of biomass; that it is an octane booster that helps to dilute sulfur; and that it allows the fulfillment of environmental objectives. To determine the optimal components to be blended with ethanol, a **blending model** was used. This model selects the components to add in the gasoline/ethanol blend based on:


- Components prices,
- Properties each component affects,
- Quality parameters by country, and
- Component availability by country.

Through iterations, the model obtains the %v/v of the components to be blended with 10%, 15%, 20%, 25% and 30% of ethanol, in such a way that the final blend complies with the required properties of a finished gasoline by country.



The blending model uses gasoline component spot average prices 2025 and provides fuel prices that do not include country distribution costs, local taxes and subsidies and import or gas station margins.



Available Blending Components




Ecuador –RON 85 Gasoline – Constant Octane





Octane (RON)	85.0	85.9	87.9	89.6	91.0	92.5
Price (US\$/gal)	\$ 1.925	\$ 1.860	\$ 1.849	\$ 1.826	\$ 1.797	\$ 1.773

Ecuador – RON 89 Gasoline– Constant Octane




Octane (RON)	89.0	89.0	89.0	89.6	91.0	92.5
Price (US\$/gal)	\$ 1.992	\$ 1.896	\$ 1.849	\$ 1.821	\$ 1.797	\$ 1.773

Ecuador – RON 92 Gasoline – Constant Octane





Octane (RON)	92.0	92.0	92.0	92.0	92.0	92.1
Price (US\$/gal)	\$ 2.123	\$ 1.958	\$ 1.901	\$ 1.853	\$ 1.805	\$ 1.764

Ecuador – RON 95 Gasoline – Constant Octane





Octane (RON)	95.0	95.0	95.0	95.0	95.0	95.0
Price (US\$/gal)	\$ 2.287	\$ 2.087	\$ 1.993	\$ 1.903	\$ 1.853	\$ 1.806

Ecuador – RON 85 Gasoline – Increased Octane





Octane (RON)	85.0	92.7	94.9	97.1	99.1	100.1
Price (US\$/gal)	\$ 1.925	\$ 2.086	\$ 2.086	\$ 2.086	\$ 2.086	\$ 2.086

Ecuador – Gasoline RON 89 – Increased Octane




Octane (RON)	89.0	93.0	94.6	94.4	97.0	98.6
Price (US\$/gal)	\$ 1.992	\$ 1.992	\$ 1.992	\$ 1.992	\$ 1.992	\$ 1.992

Ecuador – RON 92 Gasoline – Increased Octane



Octane (RON)	92.0	95.5	97.3	99.1	100.8	101.4
Price (US\$/gal)	\$ 2.116	\$ 2.123	\$ 2.123	\$ 2.123	\$ 2.123	\$ 2.123

Ecuador – RON 95 Gasoline – increased Octane



Octane (RON)	95.0	98.4	99.9	101.8	103.5	104.8
Price (US\$/gal)	\$ 2.287	\$ 2.287	\$ 2.287	\$ 2.287	\$ 2.275	\$ 2.246

Vehicle Emission Impact for Ethanol Gasoline Blending

The model used in this analysis takes as a reference the [International Vehicle Emissions Model \(IVE\)](#).


The model uses the Base Emission Rates from IVE model, as well as its Adjustment Factors based on:

- Vehicle technology (cars, trucks, buses, motorcycles),
- Vehicle fleet average age,
- Average traveled distance per vehicle by country, as well as
- Geographical and climatic conditions (altitude, humidity, temperature).

Emissions of criteria pollutants, toxic pollutants, and greenhouse gases (GHG) were calculated and calibrated with emission inventories, using real gasoline quality data. The reduction rates for gasoline/ethanol blends were obtained from various sources (IPCC, US Grains, among others).

Emission estimations for different pollutants for gasoline and gasoline/ethanol blends (10%, 15%, 20%, 25% and 30% ethanol) were determined using the IVE Model. A comparison between the results and the European (Euro 6) requirements is made. Results are also compared with real emissions of the United States vehicle fleet*.

Main Results



*Source: Bureau of transportation statistics.

Gasoline Vehicle Fleet - Ecuador

Vehicle type	Engine	Exhaust	Recovery	Age	Number of vehicles
Light automobiles	Electric	-	-	Any	7,904
	Multi FI-Pt	Hybrid	PVC Tank	Any	74,475
	Multi FI-Pt	Euro VI		< 4 years, < 80 tkm	560,856
		Euro V		4-8 years, 80-160 tkm	35054
				> 8 years, > 160 tkm	75949
				Euro IV	> 8 years, > 160 tkm
	Euro III	> 8 years, > 160 tkm		245375	
	multi	3-Ways		> 8 years, > 160 tkm	72444
	single	3-Ways		> 8 years, > 160 tkm	32717
	carbon	3-Ways		> 8 years, > 160 tkm	74781
Medium automobiles	Multi FI-Pt	Euro VI	PCV Tank	< 4 years, < 80 tkm	766222
		Euro V		4-8 years, 80-160 tkm	47889
				> 8 years, > 160 tkm	103759
				Euro IV	> 8 years, > 160 tkm
	Euro III	> 8 years, > 160 tkm		335222	
	multi	3-Ways		> 8 years, > 160 tkm	98970
	single	3-Ways		> 8 years, > 160 tkm	44696
	carbon	3-Ways		> 8 years, > 160 tkm	102163
Small Engines	Electric	-	-	Any	777
	Multi FI-Pt	Hybrid	PCV	Any	6
	FI 4-cycles	Euro V		< 4 years, < 80 tkm	1126726
		Euro IV		4-8 years, 80-160 tkm	180656
				> 8 years, > 160 tkm	85574
				> 8 years, > 160 tkm	0
		Euro III		> 8 years, > 160 tkm	71312
		Euro II		> 8 years, > 160 tkm	115684
		none		> 8 years, > 160 tkm	797107
Heavy	Electric	-	-	Any	2,253
	Multi FI-Pt	Hybrid	PCV	Any	1,551
	FI	Euro VI		< 4 years, < 80 tkm	70366
		Euro V		4-8 years, 80-160 tkm	86280
				> 8 years, > 160 tkm	49410
				Euro IV	> 8 years, > 160 tkm
		Euro III		> 8 years, > 160 tkm	30745
		3-Ways		> 8 years, > 160 tkm	15402








Vehicle Fleet: **4,986,666**

Age: 13 years


Source: CINAIE, 2023; analysis de Faro90

Ecuador – Vehicular Emissions

United States
Euro 6



Ecuador – Gasoline Vehicle Emissions



Vehicular Fleet Emissions (kg/day)	Eq E0	E5	E10	E15	E20	E25	E30	Reduction (%)	
								E10	E20
CO	866,631	820,176	773,721	739,588	707,051	682,578	647,991	-11%	-18%
CO2	23,349,725	22,749,304	22,182,239	21,736,259	21,515,571	21,390,678	20,996,386	-5%	-8%
VOC	106,789	102,613	98,437	95,802	93,512	91,861	89,272	-8%	-12%
NOx	51,967	47,982	45,211	43,779	41,495	39,694	37,580	-13%	-20%
SOx	266	246	226	209	192	175	156	-15%	-28%
NH3	8,890	8,802	8,714	8,755	8,853	8,923	8,980	-2%	0%
N2O	468	466	464	466	476	481	486	-1%	2%
CH4	23,868	23,868	23,868	24,226	24,751	25,205	25,634	0%	4%
Lead	-	-	-	-	-	-	-	0%	0%
Butadiene	920	892	863	848	837	830	816	-6%	-9%
Acetaldehyde	2,386	2,739	4,019	6,120	8,337	9,527	11,257	68%	249%
Formaldehyde	9,034	8,783	10,239	12,022	12,595	13,934	15,169	13%	39%
Benzene	1,408	1,353	1,282	1,262	1,252	1,197	1,158	-9%	-11%
PM2.5	1,325	1,205	1,084	978	875	763	647	-18%	-34%
PM10	4,452	4,047	3,642	3,286	2,938	2,564	2,173	-18%	-34%


Life Cycle GHG Emissions

The Global Agenda for Climate Action calls for countries, cities and regions, businesses, and members of civil society around the world to achieve a low-carbon and climate-resilient economies in support of the Paris Agreement. Road Transportation accounts for 15% of total GHG emissions (IPCC,2023).


Ethanol gasoline blends are an internationally adopted practice that offer significant short-term benefits. Biofuels are an important solution to achieve reduction targets in the transportation sector.

Country GHG emission reductions are calculated using **RED II/III** and **GREET** life cycle emission methodologies and the **International Vehicular Emissions Model (IVE)**. Results are compared to the current country targets for 2035. Current 2025 country emission are those published by **IPCC**.


Current GHG Global Emissions Distribution



IPCC Transport Sector Sustainable Development Goals and climate policies Scenario, 2023



Ecuador – Gasoline Vehicle Fleet GEI Emissions



Country Emissions 2025 (MMT/year)	101.4
2035 Target (MMT/year)	71.0
Delta	30.4

%Reduction vs E0	E0	E10	E15	E20	E25	E30
GREET 2025	0.0%	10.0%	13.5%	17.1%	20.3%	24.4%
RED II/III	0.0%	7.5%	10.3%	13.2%	15.7%	18.8%

% 2035 Target	E0	E10	E15	E20	E25	E30
GREET 2025	0.0%	5.6%	7.6%	9.6%	11.4%	13.6%
RED II/III	0.0%	7.0%	9.6%	12.2%	14.5%	17.3%