



IDR IN REAL-TIME – WEBSITE VISITORS

IMPLEMENTATION GUIDE

Audience Acuity provides a direct path for identity resolution for both authenticated and unauthenticated website visitor traffic. This is a 2-step process. First, website visitors are individually identified using anonymized metadata collected by a pixel or JS tag provided by Audience Acuity. This metadata is then linked to an MD5 hashed email that is returned to the client environment in real-time. Next, the MD5 hashed email is used to append profile information (name, address, email, phone, demographics) contained within the Audience Acuity Super Identity Graph using the Audience Acuity Append API.

There are two implementation options for the website visitor identity resolution service. Once an option is selected, Audience Acuity will create the associated configuration specific to each client account.

Pixel

This is a lighter weight implementation that uses a pixel to collect visitor data and provides a real-time response to a client provided endpoint which includes the MD5 hashed email as well as any parameters encoded in the pixel.

- No domain authentication is required.
- This option is typically used when JavaScript is prohibited from being deployed on the website or if the user does not have direct access/management of the website where the tracking occurs.

Distributor Tag

Uses a JavaScript tag and script and provides a real-time response in the webpage session, returning an MD5 hashed email if the visitor is resolved.

- The JavaScript option yields a higher resolution rate than the Pixel implementation.
- Domain authentication is required for the API call using a BearerToken.
- This option can be selected when JavaScript is allowed, and the user has direct access to the browser session data to capture the responses.

STEP 1

Setting Up Your Tag Type

Pixel Implementation

Step 1: Provide Audience Acuity with the URL to an endpoint which receives the response:

- ✓ Only GET requests are supported.

Sample endpoint URL: <https://api.clientendpoint.com/data?anyvalue=xxxxxxx&md5=xxxxxxx>

- ✓ You will need to confirm what should occur if we can't resolve the MD5 for the visitor.

Option 1: Return a blank value

Option 2: Send nothing

- ✓ Using parameters, you can capture and carry through other information such as a session ID, cookie ID, web page name, etc. You will need to confirm the parameter name(s) of any of these values which will then be encoded in the pixel.

Step 2: Audience Acuity will provide the website pixel for deployment:

- ✓ Audience Acuity will provide a pixel for deployment on client websites. The pixel can be deployed via a tag management system or placed directly on a webpage like any image pixel.

Sample pixel: https://i.liadm.com/s/12345?bidder_id=123456&anyvalue=xxxxxxx

- ✓ Any values added after the bidder_id value will be returned in the redirect URL with the MD5 hashed email. *Note: Passed values are not stored or processed.*

Distributor Tag Implementation

Step 1: Audience Acuity will provide a tag and Distributor ID

Distributor tag example: <https://d-code.liadm.com/did-xxxx.min.js>

- ✓ The did-xxxx value is the Distributor ID and is used in the tag, website code and authorization. A unique Distributor ID will be provided by Audience Acuity as part of account setup.

Step 2: Tag installation

- ✓ Install the Distributor tag on the required websites to load on all pages. The Distributor tag can be deployed by adding it to the global header of the website through a tag manager or can be directly added into the HTML.

Step 3: Domain Authorization

- ✓ The Distributor tag can be used across multiple website domains.
- ✓ In order to make use of the tag each website domain (apexdomain) must be authorized.
- ✓ Please refer to the external API guide <https://distributors.liveintent.com/api-guide> for details about domain authorization.
- ✓ Audience Acuity will provide the required clientID and clientsecret as part of account setup.

Step 4: Resolve

- ✓ Once domains are authorized, call the resolve method to get the data back.
- ✓ The below code is used to resolve to a MD5 hashed email. Replace xxxx with the specific id code in your Distributor tag.

```
<script type="text/javascript">
var scriptTag = document.createElement('script');
scriptTag.src = 'https://d-code.liadm.com/did-xxxx.min.js';
scriptTag['onload'] = function(e) {
window.liQd_did_xxxx.resolve(function(result) { if
(result) console.log(result); }, function(err) {
console.error(err); },
{resolve: "md5"});
}
document.head.appendChild(scriptTag);
</script>
```

STEP 2

Connecting to the Audience Acuity API to Match the MD5s

What do you need to know:

- ✓ The API uses secure, RESTful Web services and HTTP/1.1.
- ✓ The Web services payload is implemented using a JavaScript object notation (JSON) document. Both the Request, as well as its Response, use a JSON document for the payload.
- ✓ The Web services Response calls from our endpoint URI using the POST method.
- ✓ Our WS Gateway is hosted in AWS and use Clis the AWS Cognito identity management platform.
- ✓ We use the Amazon Web Services (AWS) Cognito implementation of the OAuth2 standard for authentication and access control.
- ✓ The API user must provide a WS endpoint to which Audience Acuity directs the Response to their Request. The API user WS endpoint should replicate the communications functionality provided by the Audience Acuity endpoint.

Note: *If the user is unable to provide their own endpoint, Audience Acuity can provide an endpoint through the Realink platform and provide batch file processing to resolve identities.*

Note: *There is no separate test or sandbox instance. If needed, Audience Acuity can provide a separate set of client IDs to track test queries separate from billable queries.*

- ✓ The following keys indicate the relevant resource names included in the URI:

"GetDataBy" indicates the resources dedicated to processing of Requests and Responses

"{AppendType}" indicates the type of data sent in the Request for matching, i.e., Md5, Phone, Email, Id, Pii

For website visitor resolution you will use: **GetDataBy/Md5**

For example: <https://aws-prod-dataapi-v1.audacu-api.com/GetDataBy/GetDataBy/Md5>

The table below provides the format requirements for the query request inputs by {AppendType}

AppendType	Query Attributes to Identify a Single Individual
Hashed Email (Md5)	Query contains an email address, hashed with MD5 hashing algorithms. Email before the hash is applied is all lowercase text.

For complete detailed information about our API and implementation, please see this document:
Audience Acuity API ICD_v062023