

IBM Cúram Social Program Management  
8.0.0

*Integrating with IBM Watson Assistant*



**Note**

Before using this information and the product it supports, read the information in [“Notices” on page 10](#)

**Edition**

This edition applies to IBM® Cúram Social Program Management 8.0.0.

Licensed Materials - Property of IBM.

© **Copyright International Business Machines Corporation 2021.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

---

# Contents

|  |           |
|--|-----------|
| <b>Chapter 1. Integrating with Watson Assistant.....</b>                   | <b>1</b>  |
| <b>Chapter 2. Configuring Watson Assistant settings.....</b>               | <b>2</b>  |
| <b>Chapter 3. Generating the JWT keystore and certificates.....</b>        | <b>3</b>  |
| Adding the public key to Watson Assistant.....                             | 4         |
| <b>Chapter 4. Configuring application servers for JSON Web Tokens.....</b> | <b>5</b>  |
| Configuring WebSphere Application Server for JWT.....                      | 5         |
| Configuring WebLogic Server for JWT.....                                   | 6         |
| Configuring WebSphere Liberty for JWT.....                                 | 6         |
| <b>Chapter 5. Getting started with your virtual assistant.....</b>         | <b>9</b>  |
| <b>Notices.....</b>  | <b>10</b> |
| Privacy Policy considerations.....   | 11        |
| Trademarks.....  | 11        |



---

# Chapter 1. Integrating with Watson Assistant

Use IBM Watson™ Assistant to build your own live virtual assistant into IBM Cúram Social Program Management. A sample caseworker assistant helps caseworkers to find information about client verifications and caseworker procedures to deliver an engaging and simplified experience to caseworkers for specific tasks.

## Chapter 2. Configuring Watson Assistant settings

Complete the following steps to configure IBM Watson Assistant settings in IBM Cúram Social Program Management.

### About this task

For more information about Watson Assistant web chat configuration, see [Configuration](#).

For more information about the issuer for Watson Assistant, see [Securing the web chat](#).

### Procedure

1. Log in to Social Program Management as a system administrator.
2. Select **System Configurations** > **Shortcuts** > **Application Data**.
3. Select the **Watson Assistant Configuration** category and click **Search**.
4. To update any of the following properties, select ... > **Edit Value** to update the value and click **Save**.

| Property   | Value  |
|--|--|
| <b>curam.watson.assistant.accepted.application.codes</b> | The application codes for the user workspaces where you want the web chat to be displayed. You can specify multiple workspaces with a comma-separated list. For example, you can specify DefaultApp, CustomApp to show the web chat to users of the DefaultApp and CustomApp applications. Application codes are not case-sensitive. |
| <b>curam.watson.assistant.enabled</b>                    | Set to true to enable the Watson Assistant web chat widget to be displayed in the specified workspaces.  |
| <b>curam.watson.assistant.integration.id</b>             | The integration ID of your web chat integration, which is a UUID, such as 250058a9-11f5-4deb-a91e-7ac24878c6a3.  |
| <b>curam.watson.assistant.issuer</b>                     | The issuer of the JSON Web Tokens (JWT).   |
| <b>curam.watson.assistant.region</b>                     | The data center where your web integration was created. For example, us-south.   |
| <b>curam.watson.assistant.service.instance.id</b>        | The service instance ID of the assistant that hosts your web chat integration, which is a UUID such as fba14cb7-95da-45e3-bf4a-e61d80e46598. You can find it in the Assistant URL.   |

5. Click **Publish** to publish your changes.

---

## Chapter 3. Generating the JWT keystore and certificates

A JSON Web Token (JWT) is used to secure requests between IBM Cúram Social Program Management and IBM Watson Assistant. The JWT is digitally signed by the Social Program Management application by using a public/private key pair, which is stored in a keystore.

The private key in the keystore must be accessible by the Social Program Management runtime code so the JWT can be generated and signed when an outbound request to Watson Assistant is made.

You must add the public key in two locations:

- Watson Assistant needs the public key so that requests from Social Program Management to Watson Assistant are trusted.
- The Social Program Management application server's truststore, so if Watson Assistant needs to make an API call back into Social Program Management to retrieve data in order to answer questions, the JWT that is passed along with the request is accepted. For more information about configuring the application server to allow authentication with JWT, see the *Configuring application servers for JSON Web Tokens* related link.

### Self-signed certificates for development and test

For development and test environments, you can generate a keystore with a self-signed cert with Social Program Management Ant build scripts if needed.

For production environments, a keystore with a certificate that is signed by a Trusted Certificate Authority is recommended.

To generate and use a self-signed cert, use the `configtest` or `configure` Ant build scripts. These scripts generate a keystore and self-signed cert by using the properties that are specified in the `/EJBServer/project/properties/JWTKeystore.properties` file. Both the generated keystore and properties file are added to a `JWTCryptoConfig.jar` file, which is placed in the `JAVA_HOME/jre/lib/ext` directory. The public certificate is also exported to this directory, so it can be retrieved later and added to Watson Assistant. The `configure` build script also imports the public certificate into the application servers truststore.

The values that are used for the keystore and certificate are in the file `/EJBServer/project/properties/JWTKeystore.properties` as shown in this example.

```
KEYSTORE PROPERTIES
jwt.keystore.filename=jwtkeystore.p12
jwt.keystore.location= (Leave empty when you use the generated self-signed certificate)
jwt.keystore.password=password
jwt.keystore.type=PKCS12

jwt.key.alias=jwtkeyalias (The alias name for the private key used for signing the JWT)
jwt.cert.alias=jwtcertalias (The alias name of the public cert in the truststore)
jwt.public.cert.filename=jwtcert.cer (The name of the file that will be created which contains
the cert's public key)

CERTIFICATE PROPERTIES
(These are used to create a self-signed cert, if using the default generated keystore, at build
time.
These properties are not required if using an existing keystore with existing certificate).
jwt.cert.common.name=JWT
jwt.cert.organisation.unit=
jwt.cert.organisation=
jwt.cert.locality=
jwt.cert.state=
jwt.cert.country=
jwt.cert.key.validity=1825
jwt.key.alg=RSA
jwt.key.size=2048
```

## Use existing keystore and certificate

You can use an existing keystore and certificate instead of the default keystore and self-signed certificate by updating the appropriate properties in the `/EJBServer/project/properties/JWTKeystore.properties` file.

1. If needed, customize the properties in the `/EJBServer/project/properties/JWTKeystore.properties` file.

```
jwt.keystore.filename= (The name of the keystore file)
jwt.keystore.location= (The absolute path to the keystore file)
jwt.keystore.password= (The password of the keystore)
jwt.keystore.type= (The type of the keystore)
jwt.key.alias= (The alias of the private key to use for signing the JWT)
```

2. From EJBServer directory, run the `configtest` build target to generate the `JWTCrypto.jar` file and the public key `jwtcert.cer` in the `$JAVA_HOME/jre/lib/ext/` directory.

## Troubleshooting

### Rerunning `configtest` build target and reimporting the JWT public certificate into the truststore

If you rerun the `configtest` build target after you followed the steps for importing the JWT certificate into the truststore, you must reimport the certificate again because the original certificate is no longer valid. Reimporting the certificate again applies only to applications deployed on WebSphere® or on WebSphere® Liberty.

For more information, see the *Configuring application servers for JSON Web Tokens* related link.

### Starting the Watson Assistant chatbot

If you can't start Watson Assistant chatbot, search for all files that start with 'jwtcert'. Where there are multiple entries, delete the old files. Then, rerun the build `configtest` target.

### Related concepts

[Configuring application servers for JSON Web Tokens](#)

You must configure the application server in your development or test environment to accept JSON Web Tokens for the integration with IBM Watson Assistant.

## Adding the public key to Watson Assistant

---

Complete the following steps to add your public key to IBM Watson Assistant.

### About this task

For more information about security for Watson Assistant, see [Securing the web chat](#).

### Procedure

1. Open the `$JAVA_HOME/jre/lib/ext/jwtcert.cer` file with a text editor to copy the public key details.
2. Log in to IBM Cloud and open your Watson Assistant service.
3. Click the **Launch Watson Assistant** button and select **Integrations** for your assistant.
4. Under **Integrations**, select **Web chat**.
5. Select the **Security** tab, paste the public key in the **Your public key** section, and save.



---

## Chapter 4. Configuring application servers for JSON Web Tokens

You must configure the application server in your development or test environment to accept JSON Web Tokens for the integration with IBM Watson Assistant.

---

### Configuring WebSphere Application Server for JWT

---

Complete the following steps to configure IBM WebSphere Application Server to accept JSON Web Tokens (JWT).

Complete the following steps in the WebSphere Application Server documentation, see [Configuring authentication with JSON Web Tokens \(JWT\)](#).

When you configure the new interceptor, add the following relying party custom properties for IBM Cúram Social Program Management.

- The following properties are required for JWT authentication.
  - `provider_<id>.useJwtFromRequest`: (must be set to required)
  - `provider_<id>.identifier`
  - `provider_<id>.issuerIdentifier` This value must match the `iss` attribute value in the JWT token.
- Configure the following property to obtain the JWT signer certificate.
  - `provider_<id>.signVerifyAlias` This value must match the alias name that is used to import the signer certificate into the truststore.
- Configure the following property to enable the OIDC TAI to intercept requests.
  - `provider_<id>.filter` `Authorization%=Bearer`  
If the request includes a header that is called `Authorization` and that contains `Bearer` in the value, use the TAI interceptor.

#### Import the JWT signer's public certificate into the default truststore Using the default self-signed certificate

The `configtest`, `configure`, `installapp`, and `configurewebserverplugin` ant build scripts all generate a self-signed certificate that is used to sign the JWT. The `configure` build script also imports the corresponding public certificate into the application server's default truststore. However, where the other build scripts are run after the `configure` build script then a new self-signed certificate is generated. The newer public certificate must be imported into the truststore.

The following list outlines how to use the default self-signed certificate:

1. In the administrative console, click **Security > SSL certificate and key management > Key stores and certificates > NodeDefaultTrustStore > Signer certificates**.
2. Click **jwtcertalias**, where an entry of this name exists, and click **Delete**.
3. Click **Add**.
4. Enter **jwtcertalias** for the **Alias** field. The name must also match the alias name that you specified for the `signVerifyAlias` TAI custom property.
5. Enter the absolute path to the public certificate for the **File name** field. When the self-signed certificate was created, a file that contains the public certificate was created in the directory `<JAVA_HOME>/jre/lib/ext` . For example: `<JAVA_HOME>/jre/lib/ext/jwtcert.cer`.

#### Using an existing keystore and signer certificate

If you are using an existing keystore and signer certificate instead of the generated self-signed certificate, use the preceding steps to import the public certificate into the application server's truststore. Ensure that you first run the `configtest` ant build script. The script exports the public key certificate to `<JAVA_HOME>/jre/lib/ext/jwcert.cer`.

## Configuring WebLogic Server for JWT

---

Complete the following steps to configure Oracle WebLogic Server to accept JSON Web Tokens (JWT).

### Procedure

1. From the WebLogic Server **Admin** pane, select **Security Realms**.
2. Select **myrealm** in the **Realms** list.
3. Select the **Providers** tab.
4. Select the **Authentication** tab.
5. Click **New**.
6. Enter these values for the following fields:
  - **Name:** The name of your new provider.
  - **Type:** `CuramJWTIdentityAsserter`
7. Click **OK**.
8. Click **Save**.
9. Restart the server.

## Configuring WebSphere Liberty for JWT

---

Import the JWT signer's public certificate into the default truststore and then update the `server.xml` configuration file.

### Importing the JWT signer's public certificate into the default truststore Using the default self-signed certificate

The `configtest`, `configure`, `installapp`, and `configurewebserverplugin` ant build scripts all generate a self-signed certificate that is used to sign the JWT. The `configure` build script also imports the corresponding public certificate into the application server's default truststore. However, where the other build scripts are run after the `configure` build script then a new self-signed certificate is generated. The newer public certificate must be imported into the truststore.

First, delete any existing public certificate entries with the alias name `jwcertalias`, or the value that is used in the `jwt.cert.alias` property in the `/EJBServer/project/properties/JWTKeystore.properties` file where it was updated.

To do this, run the `keytool` command that is provided with the Java™ SE Development Kit, or equivalent. For example:

```
keytool -delete -alias <alias_name> -keystore <keystore_file> -storetype <store_type>
-storepass <store_password>
```

Then, import the new public certificate file into the application server's keystore. For example:

```
keytool -import -trustcacerts -alias <alias_name> -storetype <store_type> -storepass
<store_password> -keystore <keystore_file> -file <certificate_file>
```

where:

- `<alias_name>` is the string identifier for the truststore entry. This is defined in the `jwt.cert.alias` property in the `/EJBServer/project/properties/JWTKeystore.properties` file. The default name is `jwcertalias`.

- `<keystore_file>` is the absolute path to a keystore or truststore file that is used by the application server. The simplest option is to use the default keystore, which is already defined in the `<keystore>` element in the `${server.config.dir}/adc_conf/server_security.xml` configuration file. The default keystore is located in the directory `${server.config.dir}/resources/security`.
- `<store_type>` is the type of keystore, for example JKS or PKCS12.
- `<store_password>` is the password of the keystore or truststore.
- `<certificate_file>` is the absolute path to the file that contains the public certificate. When the self-signed cert was created, a file that contains the public certificate is created in the `<JAVA_HOME>/jre/lib/ext` directory. For example: `<JAVA_HOME>/jre/lib/ext/jwtcert.cer`.

### Using an existing keystore and signer certificate

If you are using an existing keystore and signer certificate instead of the generated self-signed certificate, use the preceding steps to import the public certificate into the application server's truststore. Ensure that you first run the `configtest` ant build script. The script exports the public key certificate to `<JAVA_HOME>/jre/lib/ext/jwtcert.cer`.

### Updating the `server.xml` configuration file

The following list outlines the changes that you must make to the `server.xml` configuration file:

1. Add these features to the `<featureManager>` element:

```
<feature>openidConnectClient-1.0</feature>
<feature>transportSecurity-1.0</feature>
```

2. Add a new `<authFilter>` element:

```
<authFilter id="jwtAuthFilter">
  <requestHeader id="authHeader" name="Authorization" value="Bearer" matchType="contains"/>
</authFilter>
```

This defines a filter for any incoming requests that contain the Authorization request header, by using the Bearer scheme. This is used so that OpenIDConnect functionality is applied only to incoming requests that include this header.

3. Add a new `<openidConnectClient>` element:

```
<openidConnectClient
  id="unique_id"
  inboundPropagation="required"
  issuerIdentifier="issuer_identifier"
  audiences="ALL_AUDIENCES"
  signatureAlgorithm="RS256"
  trustStoreRef="keystore_ref"
  trustAliasName="alias_name"
  authFilterRef="jwtAuthFilter"
/>
```

where:

- `<unique_id>` can be any string ID for the element.
  - `<keystore_ref>` is the reference ID of the keystore that contains the public certificate. For default configurations, this is `defaultKeyStore` as defined in the `/adc_conf/server_security.xml` configuration file.
  - `<alias_name>` is the alias of the entry in the keystore or truststore for the public certificate and it must match the alias name that is given when the public certificate was imported. This is `jwtcertalias` for default configurations that use the generated self-signed certificate.
4. `<issuer_identifier>` must exactly match the value of the `iss` field of the JWT. This value is configured by using the `curam.watson.assistant.issuer` system property in IBM Curam Social Program Management. When the token is generated, the value is added to the JWT.

5. Restart the server.

---

## Chapter 5. Getting started with your virtual assistant

To help you get started, see the open-source GitHub repository that provides sample code and guidance for a caseworker assistant called Case Assistant. Case Assistant enables caseworkers to get information more quickly, reducing the amount of navigation to complete their tasks. Caseworkers can ask about verifications on a case or client, and about caseworker policies and procedures.

Use Case Assistant and Watson Assistant to build your own live virtual assistant into Social Program Management. Refer to the sample dialog skills and cloud functions, and see how to query Social Program Management data with REST APIs. For more information, see the *IBM Cúram Social Program Management Virtual Assistant Cookbook* related link.

### **Related information**

[IBM Cúram Social Program Management Virtual Assistant Cookbook](#)

## Notices

---

This information was developed for products and services offered in the United States.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US*

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

*Intellectual Property Licensing Legal and Intellectual Property Law IBM Japan Ltd. 19-21, Nihonbashi-Hakozakicho, Chuo-ku Tokyo 103-8510, Japan*

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

*IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US*

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

All IBM prices shown are IBM's suggested retail prices, are current and are subject to change without notice. Dealer prices may vary.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

#### COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

## Privacy Policy considerations

---

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies or other similar technologies that collect each user's name, user name, password, and/or other personally identifiable information for purposes of session management, authentication, enhanced user usability, single sign-on configuration and/or other usage tracking and/or functional purposes. These cookies or other similar technologies cannot be disabled.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

## Trademarks

---

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/copytrade.shtml>.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

The registered trademark Linux is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other names may be trademarks of their respective owners. Other company, product, and service names may be trademarks or service marks of others.







Part Number:

(1P) P/N: