Projet 1

Fichier extensions.conf

```
[general]
static=yes
writeprotect=no
clearglobalvars=no
[globals]
CONSOLE=Console/dsp
IAXINFO=guest
TRUNK=DAHDI/G2
language=fr
,Contexte de l'administration
[ADMIN]
exten => _1XXX,1,NoOp(Call from $(CallerID(number)) -> ${EXTEN})
same => n,Dial(PJSIP/${EXTEN},8)
same => n,set(${CHANNEL(language)=fr})
same => n,VoiceMail(${EXTEN}@ADMIN)
same => n,Hangup()
exten => 1000,1,Answer()
same => n,Set(CHANNEL(language)=fr)
same => n,VoiceMailMain(${CALLERID(num)}@ADMIN)
,contexte du developpement
[DEV]
exten => _3XX,1,NoOp(Call from $(CallerID(number)) -> ${EXTEN})
```

```
same => n,Dial(PJSIP/${EXTEN},8)
same => n,set(${CHANNEL(language)=fr})
same => n,VoiceMail(${EXTEN}@DEV)
same => n,Hangup()
exten => 300, Answer()
same => n,Set(CHANNEL(language)=fr)
same => n,VoiceMailMain(${CALLERID(num)}@DEV)
,Contexte de la securite
[SECU]
exten => _7XXX,1,NoOp(Call from $(CallerID(number)) -> ${EXTEN})
same => n,Dial(PJSIP/${EXTEN},8)
same => n,set(${CHANNEL(language)=fr})
same => n,VoiceMail(${EXTEN}@SECU)
same => n,Hangup()
exten => 7000,1,Answer()
same => n,Set(CHANNEL(language)=fr)
same => n,VoiceMailMain(${CALLERID(num)}@SECU)
```