

# Apply filters to SQL queries

## Project description

An organization is working to make their system more secure. It is my job to ensure the system is safe. As well as investigate all potential security issues, and update employee computers as needed.

The following steps provide examples of how I used SQL with filters to perform security-related tasks.

## Retrieve after hours failed login attempts

There was a potential security incident that occurred after business hours (after 18:00). All after hours login attempts that aren't successful need to be investigated. The following code demonstrates how I created a SQL query to filter for failed login attempts that occurred after business hours.

```
MariaDB [organization]> SELECT *
-> FROM log_in_attempts
-> WHERE login_time > '18:00' AND success = FALSE;
+-----+-----+-----+-----+-----+-----+-----+
--+
| event_id | username | login_date | login_time | country | ip_address | success |
+-----+-----+-----+-----+-----+-----+-----+
--+
| 2 | apatel | 2022-05-10 | 20:27:27 | CAN | 192.168.205.12 | 0 |
| 18 | pwashing | 2022-05-11 | 19:28:50 | US | 192.168.66.142 | 0 |
| 20 | tshah | 2022-05-12 | 18:56:36 | MEXICO | 192.168.109.50 | 0 |
| 28 | aestrada | 2022-05-09 | 19:28:12 | MEXICO | 192.168.27.57 | 0 |
| 34 | drosas | 2022-05-11 | 21:02:04 | US | 192.168.45.93 | 0 |
| 42 | cgriffin | 2022-05-09 | 23:04:05 | US | 192.168.4.157 | 0 |
| 52 | cjackson | 2022-05-10 | 22:07:07 | CAN | 192.168.58.57 | 0 |
| 69 | wjaffrey | 2022-05-11 | 19:55:15 | USA | 192.168.100.17 | 0 |
```

## Retrieve login attempts on specific dates

The event occurred on 2022-05-09. Any login activity that happened on 2022-05-09 or on the day prior needs to be investigated. The following code demonstrates how I created a SQL query to filter for login attempts that occurred on the dates in question.

```

MariaDB [organization]> SELECT *
  -> FROM log_in_attempts
  -> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
+-----+-----+-----+-----+-----+-----+-----+
| event_id | username | login_date | login_time | country | ip_address | success |
+-----+-----+-----+-----+-----+-----+-----+
| 1 | jrafael | 2022-05-09 | 04:56:27 | CAN | 192.168.243.140 | 1 |
| 3 | dkot | 2022-05-09 | 06:47:41 | USA | 192.168.151.162 | 1 |
| 4 | dkot | 2022-05-08 | 02:00:39 | USA | 192.168.178.71 | 0 |
| 8 | bisles | 2022-05-08 | 01:30:17 | US | 192.168.119.173 | 0 |
| 12 | dkot | 2022-05-08 | 09:11:34 | USA | 192.168.100.158 | 1 |
| 15 | lyamamot | 2022-05-09 | 17:17:26 | USA | 192.168.183.51 | 0 |
| 24 | arusso | 2022-05-09 | 06:49:39 | MEXICO | 192.168.171.192 | 1 |
| 25 | sbaelish | 2022-05-09 | 07:04:02 | US | 192.168.33.137 | 1 |
| 26 | apatel | 2022-05-08 | 17:27:00 | CANADA | 192.168.123.105 | 1 |
| 28 | aestrada | 2022-05-09 | 19:28:12 | MEXICO | 192.168.27.57 | 0 |
| 30 | yappiah | 2022-05-09 | 03:22:22 | MEX | 192.168.124.48 | 1 |
| 32 | acook | 2022-05-09 | 02:52:02 | CANADA | 192.168.142.239 | 0 |
| 36 | asundara | 2022-05-08 | 09:00:42 | US | 192.168.78.151 | 1 |
| 38 | sbaelish | 2022-05-09 | 14:40:01 | USA | 192.168.60.42 | 1 |

```

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all login attempts that occurred on 2022-05-09 or 2022-05-08. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `OR` operator to filter my results to output only login attempts that occurred on either 2022-05-09 or 2022-05-08. The first condition is `login_date = '2022-05-09'`, which filters for logins on 2022-05-09. The second condition is `login_date = '2022-05-08'`, which filters for logins on 2022-05-08.

## Retrieve login attempts outside of Mexico

After investigating the organization's data on login attempts, I believe there is an issue with the login attempts that occurred outside of Mexico. These login attempts should be investigated. The following code demonstrates how I created a SQL query to filter for login attempts that occurred outside of Mexico.

```
MariaDB [organization]> SELECT *
-> FROM log_in_attempts
-> WHERE NOT coutry LIKE 'MEX%';
ERROR 1054 (42S22): Unknown column 'coutry' in 'where clause'
MariaDB [organization]> SELECT *
-> FROM log_in_attempts
-> WHERE NOT country LIKE 'MEX%' ;
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all login attempts that occurred in countries other than Mexico. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with `NOT` to filter for countries other than Mexico. I used `LIKE` with `MEX%` as the pattern to match because the dataset represents Mexico as `MEX` and `MEXICO`. The percentage sign (%) represents any number of unspecified characters when used with `LIKE`.

## Retrieve employees in Marketing

My team wants to update the computers for certain employees in the Marketing department. To do this, I have to get information on which employee machines to update. The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Marketing department in the East building.

```

MariaDB [organization]> SELECT *
->
-> FROM employees
->
-> WHERE department = 'Marketing' AND office LIKE 'East%';
+-----+-----+-----+-----+-----+
| employee_id | device_id | username | department | office |
+-----+-----+-----+-----+-----+
| 1000 | a320b137c219 | elarson | Marketing | East-170 |
| 1052 | a192b174c940 | jdarosa | Marketing | East-195 |
| 1075 | x573y883z772 | fbautist | Marketing | East-267 |
| 1088 | k865l965m233 | rgosh | Marketing | East-157 |
| 1103 | NULL | randerss | Marketing | East-460 |
| 1156 | a184b775c707 | dellery | Marketing | East-417 |
| 1163 | h679i515j339 | cwilliam | Marketing | East-216 |
+-----+-----+-----+-----+-----+
7 rows in set (0.001 sec)

```

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Marketing department in the East building. First, I started by selecting all data from the employees table. Then, I used a WHERE clause with AND to filter for employees who work in the Marketing department and in the East building. I used LIKE with `East%` as the pattern to match because the data in the office column represents the East building with the specific office number. The First condition is the `department = 'Marketing'` portion, which filters for employees in the Marketing department. The second condition is the `office LIKE 'East%'` portion, which filters for employees in the East building.

## Retrieve employees in Finance or Sales

The machines for employees in the Finance and Sales departments also need to be updated. Since a different security update is needed, I have to get information on employees only from these two departments. The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Finance or Sales departments.

```

MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department = 'Finance' OR department = 'Sales' ;
+-----+-----+-----+-----+-----+
| employee_id | device_id | username | department | office |
+-----+-----+-----+-----+-----+
| 1003 | d394e816f943 | sgilmore | Finance | South-153 |
| 1007 | h174i497j413 | wjaffrey | Finance | North-406 |
| 1008 | i858j583k571 | abernard | Finance | South-170 |
| 1009 | NULL | lrodriqu | Sales | South-134 |
| 1010 | k242l212m542 | jlansky | Finance | South-109 |
| 1011 | l748m120n401 | drosas | Sales | South-292 |
| 1015 | p611q262r945 | jsoto | Finance | North-271 |
| 1017 | r550s824t230 | jclark | Finance | North-188 |
| 1018 | s310t540u653 | abellmas | Finance | North-403 |
| 1009 | 007-400-567 | | Finance | North-465 |

```

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Finance and Sales departments. First, I started by selecting all data from the employees table. Then, I used a `WHERE` clause with `OR` to filter for employees who are in the Finance and Sales departments. I used the `OR` operator instead of `AND` because I want all employees who are in either department. The first condition is `department = 'Finance'`, which filters for employees from the Finance department. The second condition is `department = 'Sales'`, which filters for employees from the Sales department.

## Retrieve all employees not in IT

My team needs to make one more security update on employees who are not in the Information Technology department. To make the update, I first have to get information on these employees. The following demonstrates how I created a SQL query to filter for employee machines from employees not in the Information Technology department.

```

MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE NOT department = 'Information Technology' ;

```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229

The first part of the screenshot is my query, and the second part is a portion of the output. The query returns all employees not in the Information Technology department. First, I started by selecting all data from the employees table. Then, I used a `WHERE` clause with `NOT` to filter for employees not in this department.

## Summary

I applied filters to SQL queries to get specific information on login attempts and employee machines. I used two different tables, `log_in_attempts` and `employees`. I used the `AND`, `OR`, and `NOT` operators to filter for the specific information needed for each task. I also used `LIKE` and the percentage sign (%) wildcard to filter for patterns.