



The following figure shows the static configuration of our component-based sample system:



To Run samples in our distribution (conup-0.9.0-DU/samples) in your virtual machine, you need to make sure the following things:

1. Download all things in tags/conup-0.9.0-DU
2. Run `mvn install` in root directory of your all download files.




3. Then go to distribution folder, you will see conup-0.9.0-DU folder, this folder is uncompressed from conup-0.9.0-DU.tar.gz in the same folder.

4. Setup your environment path
`export TUSCANY_HOME=/home/xxx/conup-0.9.0-DU`
`export PATH=$PATH:${TUSCANY_HOME}/bin`

after doing all these settings, please check them.

5. Change ip address in all projects in modules/samples/ authUpdate folder.

The default ip is 10.0.2.15, please change it to your host ip address. For example, in conup-sample-auth you need to change auth.composite file. Other three nodes, you also need to change.(you do not need to change port!)



There are other project in moudules/samples/ authUpdate, you should do the following things:

In **conup-sample-configuration-client**, you need to change ip addresses in `ConfServiceImpl.java` and `configuration.composite`.

In **conup-sample-visitor**, you need to change ip addresses in `visitor.composite`.

After doing all these changes, you need to run `mvn install`, the created jars will be automatically copied to `TUSCANY_HOME/samples/xxxx`, then we can move to next step.

6. Start all four nodes in your terminals like the following figures.

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0.0-U/samples/db/conup-sample-db.jar
```

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0.0-U/samples/auth/conup-sample-auth.jar
```

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0.0-U/samples/proc/conup-sample-proc.jar
```

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0.0-U/samples/portal/conup-sample-portal.jar
```

7. After all nodes are started, we can type "installed" in terminal to see which nodes we have started

```
Dec 27, 2012 1:46:45 PM org.apache.tuscany.sca.registry.hazelcast.HazelcastDomainRegistry entryAdded
INFO: Remote endpoint added: (@1883954431)Endpoint: URI = AuthComponent#service-binding(TokenService/TokenService)
Dec 27, 2012 1:46:45 PM org.apache.tuscany.sca.registry.hazelcast.HazelcastDomainRegistry entryAdded
INFO: Remote endpoint added: (@1123230449)Endpoint: URI = AuthComponent#service-binding(VerificationService/VerificationService)
Dec 27, 2012 1:46:48 PM org.apache.tuscany.sca.registry.hazelcast.HazelcastDomainRegistry entryAdded
INFO: Remote endpoint added: (@1752899213)Endpoint: URI = ProcComponent#service-binding(ProcService/ProcService)
installed
conup-sample-proc
conup-sample-portal
conup-sample-auth
conup-sample-db
```

8. Invoke services

- Invoke PortalComponent's PortalService in portal node's terminal using the following command.

invoke PortalComponent/PortalService execute BEGIN nju cs

"execute" is the service method name; "BEGIN, nju, cs" are the three parameters that are required by this method. In our example, we will display all execution path in our result string like the following figure.

```
default> invoke PortalComponent/PortalService execute BEGIN nju cs
Dec 25, 2012 1:54:10 PM cn.edu.nju.moon.conup.ext.tx.manager.TxDepMonitorImpl r
otTxEnd
INFO: aa2cbb89-ec24-4074-a4a6-d07660f99b1d:BEGINPortalComponent.execute.version
1, AuthComponent.getToken.version.1, ProcComponent.process.version.1, AuthCompo
ent.verify.version.1, DBComponent.dbOperation.version.1
```


INFO: aa2cbb89-ec24-4074-a4a6-d07660f99b1d:BEGINPortalComponent.execute.version.1, AuthComponent.getToken.version.1, ProcComponent.process.version.1, AuthComponent.verify.version.1, DBComponent.dbOperation.version.1

The Green color string is root transaction id; the blue color string is our input parameter which is used to identify the start of execution; the black color string is our execution path, in the execution path we will also display the implementation's version

In every component implementation, we have added a variable which was used to identify implementation's version number. We use this number to test whether our algorithm is right or not.

- Send update command to AuthComponent.

In paper example, we update AuthComponent, we have put our new version of the component implementation :



Attention: here the new version of the component implementation is in the form of a .class file with its package name sub-folder.

invoke ConfigComponent/ConfService update AuthComponent

/home/artemis/Documents/20121225-distribution/tuscany-sca-2.0-DU/samples/update

For simplicity, here we send update command to AuthComponent, the first parameter is the target component, next parameter is the new version class where you place(In your environment, the new version classes should be /xxx/xxx/conup-0.9.0-DU/samples/update). when you finish updating, you can invoke Portal service to test whether your update is right.

```
invoke PortalComponent/PortalService execute BEGIN nju cs
Dec 25, 2012 3:53:43 PM cn.edu.nju.moon.conup.ext.tx.manager.TxDepMonitorImpl ro
otTxEnd
INFO: 478a0224-4b7f-4cd8-9e82-ff096e33180f:BEGINPortalComponent.execute.version.
1, AuthComponent.getToken.version.2, ProcComponent.process.version.1, AuthCompon
ent.verify.version.2, DBComponent.dbOperation.version.1
```

9. We have implement a service access tool to help you make some tests on our algorithm.

- a. Start four nodes: portal, proc, auth, db
- b. Start config node:

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0-DU/sam
ples/config/conup-sample-configuration-client.jar
```

- c. Start service visitor node:

```
artemis@ubuntu:~$ tuscany.sh ~/Documents/20121225-distribution/tuscany-sca-2.0-D
U/samples/visitor/conup-sample-visitor-2.0.1-DU-SNAPSHOT.jar
```

After start this node, you can specify the time of accessing specify service like the following figure: the last parameter is the times that you want to access.

```
invoke VisitorComponent/VisitorService visitPortal 10
```

During the service invoking, you can use config node to send update request to AuthComponent.

If you want to use different algorithm and strategy, you can change them in Conup.xml which locates in bin folder in our distribution.