```
Code by Robert E Bridges
This library is intended to be used to create your own Nextion Library. Most of it is done for you.
The function that you will mostly alter is the "respondToReply()" function.
I developed this library to control the valves in my Home Heating system, so there are functions that pertain to the opening/closing of valves. This can
be used as an example as to how to use/develop the Library.
I mostly communicate with the nextion through the passing of data into/from numeric variables.
I have a TimerEvent which runs at 600mS intervals, slow I know but fast enough for my current needs.
When, for example this timer notices that the numeric variable "SetTime" is not zero it takes the value from this variable and sets the time. The format
of the data in this variable is (in HEX) "HHMMSS".
After having set the time the variable is set back to 0 again.
Other variables are interrogated and responded to in a similar way by the code for this Timer Event.
An example is to give an impressionof a flashing led, turning on or off a radio button with a different colour for on and off.

   Below is the Nextion code snippet to set the RTC time.

                         //=================================
                         //Set RTC time if SetTime > 0  NOTE: Variables declared in Nextion Programs.s
                         //=================================
                         if(SetTime!=0)
                         {
                           xx=SetTime
                           xx=xx>>16
                           rtc3=xx                              // Set the hour
                           xx=SetTime
                           xx=xx&0xFF00
                           xx=xx>>8                             // Set the minutes
                           rtc4=xx
                           xx=SetTime&0xFF
                           rtc5=xx                              // Set the seconds
                           SetTime=0
                         }
```

Revision	Date	Author	Description
1.0	16/04/2022	Robert E Bridges	- Initial release
1.1	17/04/2022	Robert E Bridges	- Added printMoreTextToNextion and improved explanation.
1.15	18/04/2022	Robert E Bridges	- Changed to reflect Nextion use of Global Variables in Program.s
1.20	22/04/2022	Robert E Bridges	- Added nextionError. Set when Nextion returns an error or an invalid number of characters returned
			- Added errorCode. Set to the Nextion returned error or thr error code for invalid num chars. errorCode is cleared if getReply() is called and there are chars from Nextion.
			- All the following added: preserveTopTextLine writeToTopTextLine

```
                                          releaseTopTextLine
                                          clearTextScreen
                                          clearTopTextLine
                                          setBackLight
                                          getNumVarValue
                                          setNumVarValue
   1.25              01/05/2022    Robert E Bridges     - Completed respondToReply. Now handles the return of Text from the Nextion.
                                                        - Added setTextBuffer. Adds a text buffer where text data is placed from Nextion.
   1.30              08/05/2022    Robert E Bridges     - Added askSerialBufferClear      use   THIS
                                                          and isSerialBufferClear      before THIS
   1.35              09/05/2022    Robert E Bridges     - Added setBkcmdLevel and handling of successful command completion when bkcmd = 1 or 3.
                                                          see setBkcmdLevel for explanation.
   1.40              10/05/2022    Robert E Bridges     - Added lastComdCompletedOk as a complement to setBkcmdLevel above.
                                                        - Added timeout to getReply
   1.50              25/05/2022    Robert E Bridges     - Added turnscreenTime
                                                        - Changed getNumVarValue error return to -1 from 0xFFFF.
                                                        - Added a const char revision to reflect the revision.
                                                          duplicated with revisionNum to better allow checking/comparison.
   1.55              29/05/2022    Robert E Bridges     - Added gotoPage.
   1.56              03/06/2022    Robert E Bridges     - Inseted MISSING break in Nextion reset code.
   1.60              04/06/2022    Robert E Bridges     - Added getNumVarFloat and second form of getNumVarValue.
                                                        - Added setStrVarValue.
                                                        - Added viewDebugText (or NOT).
                                                        - Corrected getNumVarValue - previously did not wait long enough for some numbers
                                                        - getNumVarValue sets it's own error code on error and also sets nextionError
                                                        - Introduced a variable timeout for getNumVarValue, initially at 1000 ms;
                                                        - Introduced a variable timeout for getStringVarValue, initially at 1000 ms;
                                                        - getNumVarValue sets it's own error code on error and also sets nextionError
                                                        - getStringVarValue corrected.
                                                        - gotoPage corrected.
                                                        - Tidied up various timeout values.
   1.65              05/06/2022    Robert E Bridges     - Added setNumVarFloat.
   1.66              11/04/2023    Robert E Bridges     - Minor change to remove compiler warning for Nextion.behin cpp file.*/
   1.67              13/09/2023    Robert E Bridges     - Minor change onOffFlashingTyp off, on, flashing changed to ledOn, ledOff, ledFlashing.
                                                        - programmer may have used off and on elsewhere and may conflict.
   1.68              29/09/2023    Robert E Bridges     - setTextBuffer changed from
                                                                    void setTextBuffer( const char* textBuffer, uint8_t textBufferSize);
                                                           to
                                                                    void setTextBuffer(       char* textBuffer, uint8_t textBufferSize);
   1.69              06/02/2024    Robert E Bridges     - Added SetDate to complement SetTime.
   1.70              18/02/2024    Robert E Bridges     - Added variables and functions associated with getting date/time from Nextion:
                                                        -     added getDateTime() to get date/time from Nextion   - works with the NEW example HMI.
                                                        -   added setMcuDateTimeCallback,                          - works with the NEW example HMI.
                                                        -     added variables nextionDateTimeUpdt, packedDateTime - works with the NEW example HMI.
                                                        - Added variable and function to get EEprom data from Nextion:
                                                        -   added fns setEEPromDataBuffer and getEEPromData       - works with the NEW example HMI.
                                                        -     added eepromDataChanged                             - works with the NEW example HMI.
(*********************************************************************************************************************
(*                                       Below at vs 1.71 is a MAJOR Potential Error Fix
                                *)
(*********************************************************************************************************************
   1.71              19/02/2024    Robert E Bridges     - GetReply() changed. An error could occur if the Nextion data was coming too fast.
                                                        - Added getPage()                                        - works with the NEW example HMI.
   1.72              22/02/2024    Robert E Bridges     - Added getDaylightSavingOn(), setSystemResetCallback(), setButtonPressCallback(),
                                                          setGlobalNumVarValue(), setGlobalStrVarValue(), click() .. a Nextion object
```

```c
/*************************************************************************************************
*              These are all the data types used to communicate with the Nextion. More correctly    *
*              they are the data types for data returned FROM the Nextion display.                   *
*              Some data returns only need 4 bytes, the Id and the Nextion terminating string,       *
*              \0xFF\0xFF\0xFF, whilst others require much more right up to the reset function        *
*              which returns two data sets in one go i.e. startUp message and ready message          *
*              |----- Start up message ----| |- Ready Message -|                                     *
*              0x00 0x00 0x00 0xFF 0xFF 0xFF  0x88 0xFF 0xFF 0xFF                                     *
*                                                                                                    *
*              All the comms are put int the variable nextionEvent which is of nextionEventType.     *
*              this consists of the Id of the message which is returned in nextionEvent.Id. The      *
*              remaining bytes are put into nextionEvent.reply3, or nextionEvent.reply4 etc.         *
*              The relevant reply type is examined to interpret the data.                            *
*              Infact when data is returned from the Nextion it is placed in                         *
*              nextionEvent.resetReply because this is the lartgest structure and can accommodate    *
*              all types of reply.                                                                   *
*              Note that there is sometimes the need to convert from little endian to big endian     *
*              due to Teensy and Nextion using different endians.                                     *
*************************************************************************************************/

struct rep3Type {
        uint32_t        nextTerm;  // = 0xFFFFFF swap little endian to big endian =  0xFFFFFF00
};
struct rep4Type {
        uint8_t         pageNum;
        uint32_t        nextTerm;
};
struct rep5Type {
        uint8_t         ans[2];
        uint32_t        nextTerm;
};
struct rep6Type {
        uint8_t         pageNum;
        uint8_t         component;
        uint8_t         pressed;
        uint32_t        nextTerm;
};
struct rep7Type {

        union {
                uint8_t         ans[4];
                uint16_t        num[2];
                uint32_t        number32bit;
        };
        uint32_t                nextTerm;
};
struct rep7IntType {
        union {
                uint8_t         ans[4];
                uint16_t        num[2];
                int32_t         number32bitInt;
        };
        uint32_t        nextTerm;
```

```c
};

struct rep8Type {
        union {
                uint8_t x[2];
                uint16_t        xPos;
        };
        union {
                uint8_t y[2];
                uint16_t        yPos;
        };
        uint8_t                 pressed;
        uint32_t                nextTerm;
};
                                        // After Reset Nextion Returns 00 00 00 FF FF followed by 88 FF FF FF
struct resetReplyType {                 // first 00 in nextionEvent char Id
        uint32_t        startup4Bytes; // 00 00 FF FF swap little endian to big endian = 0x0FFFF0000
        uint8_t         startupByte;   // FF
        uint32_t        readyReply;    // 88 FF FF FF swap little endian to big endian = 0x0FFFFFF88
        uint32_t        overflow;      // Just to allow a 4 byte buffer if extra erroneous bytes are
};                                      //      sent during "reset" (Have Seen It in error conditions)

struct nextionEventType {
        char id;
        union {
                rep3Type                reply3;
                rep4Type                reply4;
                rep5Type                reply5;
                rep6Type                reply6;
                rep7Type                reply7;
                rep7IntType             reply7int;
                rep8Type                reply8;
                resetReplyType          resetReply;     //-- The largest Type
                uint8_t                 data[sizeof(resetReplyType)]; // Just so that data can be analysed for debug purposes
        };
}; // nextionEvent;
#pragma pack(pop)

enum onOffFlashingType {
        off = 0,
        on,             // = 1,
        flashing        // = 2
};
enum topMidBottmType {
        top = 0,
        mid,            // = 1,
        bottom          // = 2,
};
```

```
/**************************************************************************************
*                                                                                   *
*          This is an explanation of the data returned from the Nextion.            *
*          I think it's self explanatory, but then I wrote it!!                      *
*          There is the Id returned by the Nextion, followed by the number of following bytes,*
*          followed by an explanation of those bytes. It is only because we have this        *
*          information that this library was able to be written. All is based upon this info. *
*                                                                                   *
***************************************************************************************/
/*                                              /--------   Id Codes Returned by Nextion
                                               /
                                              /        /----------- Number of Char/Bytes returned after Id Char/Byte
                                             /        /
                                            /        /                   /-------- Char/Bytes returned after Id Char/Byte
                                           /        /                   /
                                          /        /        |------------------------------------|   */
const uint8_t  nextionStartUp         = 0x00; //    5        0x00 0x00 0x00 0xFF 0xFF 0xFF          Returned when Nextion has started or
                                      //                                                           reset
const uint8_t  instructionSuccess     = 0x01; //    3        0x01 0xFF 0xFF 0xFF                    (ONLY SENT WHEN bkcmd = 1 or 3)
const uint8_t  touchEvent             = 0x65; //    6        0x65 0x00 0x01 0x01 0xFF 0xFF 0xFF    Returned when Touch occurs
                                      //                     data: Page 0, Component 1, Pressed    Returns page, component and pressed
                                      //                                                           or not, 0 or 1
const uint8_t  currentPageNumber      = 0x66; //    4        0x66 0x01 0xFF 0xFF 0xFF               Returned when the sendme command is used.
                                      //                           data : page 1
const uint8_t  touchCoordinateAwake   = 0X67; //    8        0x67 0x00 0x7A 0x00 0x1E 0x01 0xFF 0xFF 0xFF Returned when sendxy = 1 and not
                                      //                           data: (122, 30) Pressed                in sleep mode
const uint8_t  touchCoordinateSleep   = 0X68; //    8        0x68 0x00 0x7A 0x00 0x1E 0x01 0xFF 0xFF 0xFF Returned when sendxy = 1 and
                                      //                           data: (122, 30) Pressed (0 for NOT pressed)   exiting sleep
                                      //
const uint8_t  stringDataEnclosed     = 0x70; //    0        means variable amount
                                      //                     0x70 0x61 0x62 0x31 0x32 0x33 0xFF 0xFF 0xFF Returned when using get command
                                      //                           data: ab123                              for string.
                                      //                                                               Each byte is converted to char.
const uint8_t  numericDataEnclosed    = 0x71; //    7        0x71 0x01 0x02 0x03 0x04 0xFF 0xFF 0xFF      Returned when get command to
                                      //                      data: 67305985                  return a number
                                      //                                                      4 byte 32 bit value in little endian Order.
const uint8_t  autoEnteredSleepMode   = 0x86; //    3        0x86 0xFF 0xFF 0xFF                    Returned when Nextion enters sleep
                                      //                                                              automatically.
                                      //                                                      Using sleep = 1 will not return an 0x86
const uint8_t  autoAwakeFromSleepMode = 0x87; //    3        0x87 0xFF 0xFF 0xFF                    Returned when Nextion leaves sleep
                                      //                                                              automatically
                                      //                                                      Using sleep = 0 will not return an 0x87
const uint8_t  nextionReady           = 0x88; //    3        0x88 0xFF 0xFF 0xFF                    Returned when Nextion has powered up and is
                                      //                                                      now initialized successfully
const uint8_t  powerOnMicroSDCardDet  = 0x89; //    3        0x89 0xFF 0xFF 0xFF                    Returned when power on detects inserted
                                      //                                                      microSD and begins Upgrade by microSD process.
const uint8_t  transparentDataFin     = 0xFD; //    3        0xFD 0xFF 0xFF 0xFF                    Returned when all requested bytes of
                                      //                                                      Transparent Data mode have been received,
                                      //                                                      and is now leaving transparent data mode
                                      //                                                              (See 1.16)
const uint8_t  transparentDataReady   = 0xFE; //    3        0xFE 0xFF 0xFF 0xFF                    Returned when requesting Transparent Data
     `                                //                                                      mode, and device is now ready to begin
                                      //                            (see 1.16)                receiving the specified quantity of data
```

```c
/*********************************************************************************************
*                                                                                           *
*           Below are the error codes returned by the Nextion                               *
*           Whether they are returned or not depends upon the value by the Nextion bkcmd.   *
*           This can be set to Level 0 ... to Level 3. Below are shown the bkcmd level at which *
*           the error/state message is returned. The default is Level 2.                    *
*                                                                                           *
*********************************************************************************************/

/* Error/event codes (ONLY 0x01 is an event code)
                                            /------------ Error/Event Code
                                           /
                                          /          /------- Error/Event Code returned when bkcmd equals value shown
                                         /          /
                                        /     |--------|  */
const uint8_t invalidInstruction            = 0x00; // bkcmd 2,3   0x00 0xFF 0xFF 0xFF   Returned when instruction sent by user has failed
//const uint8_t instructionSuccess          = 0x01; // bkcmd 1,3   0x01 0xFF 0xFF 0xFF   (ONLY SENT WHEN bkcmd = 1 or 3 )
const uint8_t invalidComponentId            = 0x02; // bkcmd 2,3   0x02 0xFF 0xFF 0xFF   Returned when invalid Component ID or name was used
const uint8_t invalidPageId                 = 0x03; // bkcmd 2,3   0x03 0xFF 0xFF 0xFF   Returned when invalid Page ID or name was used
const uint8_t invalidPictureId              = 0x04; // bkcmd 2,3   0x04 0xFF 0xFF 0xFF   Returned when invalid Picture ID was used
const uint8_t invalidFontId                 = 0x05; // bkcmd 2,3   0x05 0xFF 0xFF 0xFF   Returned when invalid Font ID was used
const uint8_t invalidFileOperation          = 0x06; // bkcmd 2,3   0x06 0xFF 0xFF 0xFF   Returned when File operation fails
const uint8_t invalidCrc                    = 0x09; // bkcmd 2,3   0x09 0xFF 0xFF 0xFF   Returned when Instructions with CRC validation fails
                                            //                                          their CRC check
const uint8_t invalidBaudRateSetting        = 0x11; // bkcmd 2,3   0x11 0xFF 0xFF 0xFF   Returned when invalid Baud rate was used
const uint8_t invalidWaveformIdChan         = 0x12; // bkcmd 2,3   0x12 0xFF 0xFF 0xFF   Returned when invalid Waveform ID or Channel # was used
const uint8_t invalidVarNameAttrib          = 0x1A; // bkcmd 2,3   0x1A 0xFF 0xFF 0xFF   Returned when invalid Variable name or invalid
                                            //                                          attribute was  used
const uint8_t invalidVarOperation           = 0x1B; // bkcmd 2,3   0x1B 0xFF 0xFF 0xFF   Returned when Operation of Variable is invalid.
                                            //                                          ie: Text assignment t0.txt = abc or t0.txt = 23,
                                            //                                          or    Numeric assignment j0.val = "50? or j0.val = abc
const uint8_t assignmentFailed              = 0x1C; // bkcmd 2,3   0x1C 0xFF 0xFF 0xFF   Returned when attribute assignment failed to assign
const uint8_t EEPROMOperationFailed         = 0x1D; // bkcmd 2,3   0x1D 0xFF 0xFF 0xFF   Returned when an EEPROM Operation has failed
const uint8_t invalidQtyParams              = 0x1E; // bkcmd 2,3   0x1E 0xFF 0xFF 0xFF   Returned when the number of instruction parameters is
                                            //                                          invalid
const uint8_t ioOperationFailed             = 0x1F; // bkcmd 2,3   0x1F 0xFF 0xFF 0xFF   Returned when an IO operation has failed
const uint8_t invalidEscapeChar             = 0x20; // bkcmd 2,3   0x20 0xFF 0xFF 0xFF   Returned when an unsupported escape uint8_tacter is used
const uint8_t variableNameToLong            = 0x23; // bkcmd 2,3   0x23 0xFF 0xFF 0xFF   Returned when variable name is too long.Max length is
                                            //                                          29 characters: 14 for page + "." + 14 for component.
const uint8_t serialBufferOverflow          = 0x24; //  always     0x24 0xFF 0xFF 0xFF   Returned when a Serial Buffer overflow occurs
                                            //                                          Buffer will continue to receive the current instruction,
                                            //                                          all previous instructions are lost.
/*
* Error code generated by this library when incorrect number of characters returned by Nextion
*/
const uint8_t errorReadingNumber_1    = 0x3D;
const uint8_t errorReadingNumber_2    = 0x3E;
const uint8_t invalidNumCharsReturned = 0x3F;
```

```cpp
enum bkcmdStateType {
        noReturn,//     = 0,
        onSuccess,      // = 1,
        onFailure,      // = 2 Default
        always          // = 3
};

const uint8_t boilerButton    = 5;
const uint8_t hwButton        = 6;

class Stream;

class Nextion {

        public:

                typedef void (*setNextionBaudCallbackFunc) (uint32_t);                // create function pointer type
                typedef void (*nextionTurnValveOnOffCallbackFunc) (uint32_t, bool); // create function pointer type
                typedef void (*setMcuDateTimeCallbackFunc) ();                                   // create function pointer type
                typedef void (*systemResetCallbackFunc) ();                                      // create function pointer type

                const char     revision[5]          = "1.72";
                const uint16_t revisionNum          = 172;

                uint32_t       baudRate             = 9600;
                const uint32_t resetNextionBaud     = baudRate;
                uint32_t       recoveryBaudRate      = baudRate;        // used for recovery when changing baud rate does not work
                bool           nextionError         = false;
                bool           comdExecOk           = false;                 // only used for bkcmd = 1 or 3
                bool           stringWaiting         = false;
                uint8_t        errorCode            = instructionSuccess;
                bkcmdStateType bkcmd                = onFailure;
                uint32_t       getNumVarTimeout     = 1000;
                uint32_t       getStrVarTimeout     = 1000;
                uint32_t       getEPromDataTimeout  = 1000;
                bool           eepromDataChanged    = true;
                bool           nextionDateTimeUpdt  = false;
                uint32_t       packedDateTime       = 0;
                int32_t        sndDateTimeHotSPage   = 0;
                bool           daylightSaving        = false;

                nextionEventType nextionEvent;

                Nextion(Stream* s); //      s is the serial stream to use e.g. Serial1
```

```
/*************************************************************************************************
*                                              ``                                               *
*                               Description of Nextion Public Variables                         *
*                                                                                               *
*************************************************************************************************
*                                                                                               *
*       baudRate                       = 9600;      The baud rate used for Nextion Comms.        *
*       resetNextionBaud               = baudRate;  The baud rate used after a reset. Needs to match *
*                                                   the value used in Program.s if changed from the default 9600*
*       recoveryBaudRate               = baudRate;  Used for recovery when changing baud rate doesn't work. *
*       nextionError                   = false;     Returns true if a Nextion error has occured   *
*       comdExecOk                     = false;     // only used for bkcmd = 1 or 3              *
*       stringWaiting                  = false;     Returns true if a string has been collected from Nextion. *
*       errorCode                      = instructionSuccess; Error code returned if nextionError is true. *
*       bkcmd                          = onFailure; NOT TESTED FOR CHANGE FROM THIS DEFAULT SETTING. *
*       getNumVarTimeout               = 1000;      Timeout (mS) for getting numeric value from Nextion *
*       getStrVarTimeout               = 1000;      Timeout (mS) for getting string result from Nextion *
*       getEPromDataTimeout            = 1000;      Timeout (mS) for getting Eeprom data from Nextion. *
*       eepromDataChanged              = true;      Returns true if Eeprom data has changed and should be read *
*                                                   from Nextion using getEEPromData.            *
*                                                   Using this sets eepromDataChanged to false.  *
*       packedDateTime                 = 0;         The variable used to hold the packed date/time returned *
*                                                   from the Nextion.                            *
*       nextionDateTimeUpdt            = false;     The date/time has been changed on the Nextion. *
*                                                   and automatically collected into packedDateTime. *
*                                                   If setMcuDateTimeCallback() has been used the CallBack fn *
*                                                   will be used to set the mcuDate/Time.         *
*                                                   If false getDateTime() will need to be used to get the *
*                                                   date/time.                                    *
*                                                   This will set nextionDateTimeUpdt to false.   *
*       sndDateTimeHotSPage            = 0          The page nuumber holding the sndDateTime Hotspot. *
*       daylightSaving                 = false      Set when time from Nextion packedDateTime decoded. *
*                                                                                               *
*************************************************************************************************/


/*************************************************************************************************
*                                                                                               *
*                               Description of Nextion functions                                *
*                                                                                               *
*************************************************************************************************/


/*************************************************************************************************
*           begin(uint32_t br, setNextionBaudCallbackFunc func = nullptr) - passes the Nextion  *
*           baud rate to the library. This is put into the variable baudRate. No changes to the *
*           baudRate are made by this Function. Also, if passed, sets the call back function     *
*           so that this library can have control over the Teensy baudrate.                      *
*           Turns on automatic control of Teensy baudrate if passed.                            *
*-----------------------------------------------------------------------------------------------*
*           Usage:                                                                              *
*                   begin( baudRate ) - autoSetting of Teensy baud rate set off.                *
*                   begin( baudRate, setNextionBaud ) - passes the baud rate and function to change *
*                                                       Teensy baudRate.                         *
*************************************************************************************************/
            void begin(uint32_t br, setNextionBaudCallbackFunc func = nullptr);
```

```
/********************************************************************************************
*            sendCommand(const char* command); - Sends command to Nextion.                 *
*            sendCommand(const char* command, uint32_t num); - Sends command & num to Nextion. *
*            sendCommand(const char* command, uint32_t txt, encloseText); - Sends command & txt *
*------------------------------------------------------------------------------------------*
*            In the 3rd form above, if encloseTxt is true then txt is enclosed between      *
*            quotation marks ".                                                             *
*            So sendCommand( "page0.CommentBox.txt=","Hello There",true); results in        *
*            page0.CommentBox.txt="Hello There"\xFF\xFF\xFF being sent to the Nextion.       *
*------------------------------------------------------------------------------------------*
*            Sends the command to Nextion. If bkcmd level has been set to 1 or 3 the code is *
*            setup to look for a response from the Nextion.                                 *
*            if bkcmd set to 1 or 3, use the command lastComdCompletedOk(uint32_t timeout)   *
*            below after a command or before the next command to determine that the (last)   *
*            command completed ok.                                                           *
********************************************************************************************/
            void sendCommand(const char* command);
            void sendCommand(const char* command, uint32_t num);
            void sendCommand(const char* command, const char* txt, bool encloseText);


/********************************************************************************************
*            setBkCmdLevel(bkcmdStateType level) - Sets Nextion bkcmd value                 *
*------------------------------------------------------------------------------------------*
*            The default value is onFailure (2)                                             *
*            When set to 1 or 3, use the command bool lastComdCompletedOk(uint32_t timeout)  *
*            below after a command or before the next command to determine that the (last)   *
*            command completed ok.                                                           *
*            level is ONLY allowed to be 1 or 3 if compiled with #define bkcmd1or3allowed in *
*            Nextiopn.cpp.                                                                    *
********************************************************************************************/
            void setBkCmdLevel(bkcmdStateType level);


/********************************************************************************************
*            setNextionBaudRate(uint32_t br) - Sets the baud rate on Nextion and Teensy.     *
*------------------------------------------------------------------------------------------*
*            This routine saves the current baud rate in a variable recoveryBaudRate so that *
*            this recoveryBaudRate can be tried first by the recoverNextionComms() function   *
*            thus saving some time in the recovery.                                          *
*            In order for this function to work correctly it requires that the              *
*            setNextionBaudCallbackFunc was passed to the Library with the Nextion.display.begin *
*            function. If not it will be the responsibility of the calling program to set the *
*            Teensy BaudRate accordingly.                                                    *
********************************************************************************************/
            void setNextionBaudRate(uint32_t br);
```

```
/****************************************************************************************
*              lastComdCompletedOk(uint32_t timeout) - ret true/false if last comd completed ok      *
*--------------------------------------------------------------------------------------*
*              This command is to be used if bkcmd level is set to 1 or 3 and ONLY where a          *
*              command is used to set a state on the Nextion.                                        *
*              Where a request for information      is sent to nextion, as in "get varName", the    *
*              returned value is the handshake.                                                      *
*              If other values are used (0 or 2) it is transparent and will return true.            *
*              This is not an indication that the command completed ok as handshaking is off.       *
****************************************************************************************/
              bool lastComdCompletedOk(uint32_t timeout);


/****************************************************************************************
*              Set the Text Area to be used for the Return of Text data from Nextion               *
*              If text is sent from the Nextion (following the 0x70 identifier) it will be          *
*              sent to SerialUsb if this function has not been used to specify a variable           *
*              to hold the text data. The parameter must be the size of the textBuffer             *
*              variable. If more text is returned than there is space for in textBuffer            *
*              it will be sent to the SerialUsb.                                                     *
*--------------------------------------------------------------------------------------*
*              Usage:  setTextBuffer( textBuffer, sizeof( textBuffer ));                             *
****************************************************************************************/
              void setTextBuffer(/*const*/ char* textBuffer, uint8_t textBufferSize);

/****************************************************************************************
*              Set the EEProm Data Area to be used for the Return of EEProm data from Nextion by   *
*              the fn bool getEEPromData(uint32_t start, uint32_t len)                               *
*--------------------------------------------------------------------------------------*
*       Usage:  setEEPromDataBuffer( eepromDataBuffer, sizeof(eepromDataBuffer));                   *
****************************************************************************************/
              void setEEPromDataBuffer(/*const*/ char* eepromDataBuffer, uint8_t eepromBufferSize);

/****************************************************************************************
*              clearBuffer() - Clears the Teensy (Nextion) serial input.                            *
*              Use where things have perhaps gone wrong and you need to clear out erroneous         *
*              replies.                                                                              *
****************************************************************************************/
              void clearBuffer();


/****************************************************************************************
*              commsOk() - Checks that valid communications exist with the Nextion Display.         *
*              It sends the command "sendme\xFF\xFF\xFF" and looks for a reply. It does not look    *
*              for the page number for a reply, because comms may have been lost due to using       *
*              the wrong baud rate, in which case a reply might be 0x23FFFFFF - variable name        *
*              too long or some other error reply. Instead it looks for any valid reply.            *
****************************************************************************************/
              bool commsOk();
```

```
/*******************************************************************************************
*            reset(baudRate) - Resets the Nextion Display and sets the baud rate to "baudRate"     *
*-----------------------------------------------------------------------------------------*
*            Sends a reset command to the Nextion. Sets the Teensy baud rate to 9600 if that       *
*            baud rate NOT already in use. ( upon reset the Nextion defaults to this baud rate )    *
*            and waits for a valid reply. The Teensy baud rate is set using the callBack            *
*            function registered using the display.begin function.                                  *
*            When a valid reply has been seen the Nextion AND Teensy have the buadRate changed       *
*            to the baud rate passed in the function call.                                           *
*            The function returns true if valid comms with the Nextion can be established.           *
*            Sets bkcmd to onFailure (Default)                                                        *
*-----------------------------------------------------------------------------------------*
*            Usage:                                                                                  *
*                reset() - If no baud rate is passed then the baudRate defaults to the reset 9600    *
*                reset(1) - Sets the Baud Rate to that in use at the entry to the Reset function.    *
*                reset(115200) - Will do a reset and set the baudRate to 115200.                     *
*******************************************************************************************/
            bool reset(uint32_t br = 0);


/*******************************************************************************************
*            recoverNextionComms() - attempts to recover Nextion Comms once they have been lost     *
*-----------------------------------------------------------------------------------------*
*            First sets the Teensy baud rate to the recoverBaudRate (see setNextionBaudRate         *
*             below). Uses the commsOK function to determine that comms have been re-established.    *
*            If that does not work then all the baud rates that the Nextion might use are cycled     *
*            through until a valid baud rate can be found.                                            *
*            Returns the value of the baud rate found.                                               *
*            If NO valid baud rate can be found then returns 0.                                       *
*******************************************************************************************/
            uint32_t recoverNextionComms();
/*******************************************************************************************
*            Check if char(s) returned from Nextion. If not do something else and come back          *
*            later to check again. Wait for timeout. Default is 0..don't wait.                        *
*-----------------------------------------------------------------------------------------*
*            If there is a reply from Nextion then the Reply Char is received and the required        *
*            number of following char/bytes dependent upon the value of the Id.                       *
*            The Id char is placed in nextionEvent.id.                                                 *
*            The remaining chars are placed in nextionEvent.reply8 ready to be decoded.               *
*            True is returned if there is an Id char and the required number of chars                  *
*            are returned. Otherwise, false is returned.                                               *
*            If the first char is received within timeout a further timeout of 1 second               *
*            is allowed for remaining characters.                                                       *
*            This proc does NOT get any strings returned from Nextion,Use respondToReply()             *
*            for that.                                                                                  *
*******************************************************************************************/
            bool getReply(uint32_t timeout = 0);
```

```
/*******************************************************************************************
*           respondToReply() - returns true if something needs responding to.              *
*------------------------------------------------------------------------------------------*
*           This is where you need to put your code. Use getReply() to get any info from the *
*           Nextion (see above) and this function to decode the reply and respond to it.     *
*           It returns true if further response is needed.                                   *
*------------------------------------------------------------------------------------------*
*           I like to have requests from the Nextion Display embedded into numbers.    Within this *
*           code I want to turn valves on or off. The number returned by the Nextion contains *
*           the valve to be moved and whether it should be opened or closed (0 or 1)        *
*           If you have handled the Nextion response fully then set needsResponse to false. *
*******************************************************************************************/
            bool respondToReply();


/*******************************************************************************************
*           printAnyReturnCharacters(uint32_t nextionTime, uint8_t id).                     *
*           This function is intended to be used in debugging your code. It prints out to the *
*           SerialUsb the value "nextionTime" and "Id", both values that might be useful in   *
*           tracking down where your error occurred, followed by any values that are in the  *
*           Serial input stream from the Nextion.                                            *
*           It might be that you have used "respondToReply", with your code in it, but still  *
*           there is something being returned that needs to be responded to. Use this function *
*           to see what unexpected data is being sent from the Nextion Display.              *
*           ALL data is output in HEX.                                                       *
*******************************************************************************************/
            void printAnyReturnCharacters(uint32_t nextionTime, uint8_t id);


/*******************************************************************************************
*           setNextionBaudRate(uint32_t br) - Sets the baud rate on Nextion and Teensy.     *
*------------------------------------------------------------------------------------------*
*           This routine saves the current baud rate in a variable recoveryBaudRate so that  *
*           recoveryBaudRate can be tried first by the recoverNextionComms() function,       *
*           thus saving some time in the recovery.                                           *
*           In order for this function to work correctly it requires that the               *
*           setNextionBaudCallbackFunc was passed to the Library with the Nextion.display.begin *
*           function. If not it will be the responsibility of the calling program to set the *
*           Teensy BaudRate accordingly.                                                     *
*******************************************************************************************/
            void setNextionBaudRate(uint32_t br);


/*******************************************************************************************
*           gotoPage(uint32_t which); - Sets which is active displayed page.                *
*******************************************************************************************/
            void gotoPage(uint32_t which);


/*******************************************************************************************
*           getPage(); - Returns the number of the active displayed page.                   *
*******************************************************************************************/
            int32_t getPage();
```

```
/********************************************************************************************
*              setBackLight(uint32_t backLight) - Sets the display BackLight(0..100).      *
*------------------------------------------------------------------------------------------*
*              Any value greater than 100 will default to 100.                             *
*              0 is off 100 is MAX brightness.                                             *
********************************************************************************************/
              void setBackLight(uint32_t backLight);


/********************************************************************************************
*                                                                                          *
*              getNumVarValue(const char* varName) - Gets the value of Nextion Variable.   *
*              getNumVarValue(const char* varName, const char* suffixName) - Gets the value *
*                                                 of the Variable suffix.                   *
*------------------------------------------------------------------------------------------*
*              Waits for up to 1000ms for a reply. If no reply returns -1.                  *
*              The wait time is controlled by the variable getNumVarTimeout which is        *
*              initially set to 1000 ms.                                                    *
*              Since -1 can alse be a valid return value nextionError is set on error and   *
*              the error is reported in errorCode as errorReadingNumber_1 or                *
*              errorReadingNumber_2 dependant upon which form of getNumVarValue is used.    *
*------------------------------------------------------------------------------------------*
*              In reality this command should only be sent when the Nextion Serial buffer is *
*              empty, otherwise, any reply may be from previously stacked up Nextion commands *
*              and therefore be erroneous.                                                  *
*------------------------------------------------------------------------------------------*
*              In the second case returns the value of a variable suffix as in:             *
*              getNumVarValue( "x0","ws1") to get the number of dp for a Nextion float variable. *
*              NOTE that the "." in "x0.ws1" is provided by the function.                   *
*------------------------------------------------------------------------------------------*
*              NOTE that, if appropriate, the ".val" varName suffix MUST be sent. Program.S *
*              variables DO NOT need the ".val" suffix whereas Nextion Display variables do. *
*                                                                                          *
*              For example to get a sys value just use getNumVarValue("sys"); but for a Display *
*              variable va2, use getNumVarValue("va2.val"); OR getNumVarValue("va2","val"); *
*------------------------------------------------------------------------------------------*
*              The varName MUST exist.                                                      *
********************************************************************************************/
              int32_t getNumVarValue(const char* varName);
              int32_t getNumVarValue(const char* varName, const char* suffixName);


/********************************************************************************************
*              getNumVarFloat(const char* varName) - Gets the value of Nextion Float Variable. *
*------------------------------------------------------------------------------------------*
*              getNumVarFloat uses getNumVarValue to get the various components of a Nextion *
*              float. Wait times will be a combination of the two betNumVarValue wait times. *
*              If an error occurs nextionError will be set to true and the returned value   *
*              should NOT be relied upon.                                                   *
*              The error is reported in errorCode as errorReadingNumber_2                   *
*------------------------------------------------------------------------------------------*
*              In reality this command should only be sent when the Nextion Serial buffer is *
*              empty otherwise, any reply may be from previously stacked up Nextion commands *
*              and therefore be erroneous.                                                  *
*              The varName MUST exist.                                                      *
********************************************************************************************/
              float_t getNumVarFloat(const char* varName);
```

```
/********************************************************************************************
*               getStringVarValue(const char* varName) - Gets the text from Nextion Variable.      *
*-------------------------------------------------------------------------------------------*
*               Waits for up to 1000ms for a reply. If no reply returns false.              *
*               The wait time is controlled by the variable getStrVarTimeout which is initially    *
*               set to 1000 ms.                                                             *
*-------------------------------------------------------------------------------------*
*               In reality this command should only be sent when the Nextion Serial buffer is      *
*               empty, otherwise any reply may be from previously stacked up Nextion commands       *
*               and therefore be erroneous.                                                 *
*               The varName MUST exist.                                                     *
*-------------------------------------------------------------------------------------------*
*               The result is placed in the string setup with the setTextBuffer function.   *
*               If no string has been setup it will simply be echoed to the screen (Serial).*
*               Returns true if string returned successfully. stringWaiting is also set to true.   *
*-------------------------------------------------------------------------------------------*
*               NOTE there is no need to send the ".txt" suffix to the string variable.     *
*               getStringVarValue("va0") will send "get va0.txtFFFFFF" to the Nextion and wait for  *
*               an answer.                                                                  *
********************************************************************************************/
                bool getStringVarValue(const char* varName);


/********************************************************************************************
*               bool getEEPromData(uint32_t start, uint32_t len) - Gets the EEProm data from start for     *
*                                                                                 len bytes.*
*-------------------------------------------------------------------------------------------*
*           Waits for up to 1000ms for a reply. If no reply returns false.                  *
*               The wait time is controlled by the variable getEPromDataTimeout which is initially set to  *
*                                                                                  1000 ms. *
*-------------------------------------------------------------------------------------------*
*           In reality this command should only be sent when the Nextion Serial buffer is   *
*           empty, otherwise any reply may be from previously stacked up Nextion commands    *
*               and therefore be erroneous.                                                 *
*-------------------------------------------------------------------------------------  *
*               The result is placed in the EEPromDataBuffer setup with the setEEPromDataBuffer     *
*               fn returned true if len bytes collected. The number of bytes collected is placed in *
*               the global variable eepromBytesRead.                                         *
*               A valid getEpromData also sets eepromDataChanged to false.                   *
*               Initially it is set to true to force initial collection of Nextion eeprom data.    *
*               If no EEPromDataBuffer has been setup it will simply return false.           *
********************************************************************************************/
                bool getEEPromData(uint32_t start, uint8_t len);


/********************************************************************************************
*               setNumVarValue(const char* varName, int32_t var ) - Sets Nextion Variable to var.  *
*-------------------------------------------------------------------------------------------*
*               NOTE that, if appropriate, the ".val" varName suffix MUST be sent. Program.S *
*               variables DO NOT need the ".val" suffix whereas Nextion Display variables do.*
*-------------------------------------------------------------------------------------------*
*               For example to set a sys value just use setNumVarValue("sys",100); but for a *
*               display variable va2, use setNumVarValue("va2.val",100);                    *
*-------------------------------------------------------------------------------------------*
*               The varName MUST exist.                                                     *
********************************************************************************************/
                bool setNumVarValue(const char* varName, int32_t var);
```

```
/********************************************************************************************
 *              setGlobalNumVarValue( uint8_t p, uint8_t b, int32_t var);                   *
 *-----------------------------------------------------------------------------------------*
 *              Sends p[p].b[b].val=var is sent to the nextion.                            *
 *              This fn CANNOT be used for Program.S variables                             *
 *-----------------------------------------------------------------------------------------*
 *              The p and b id's MUST exist and be appropriate for the type of data being sent. *
 *              NOTE that p and vb numbers can change when items are added or deleted from  *
 *              the Nextion display rendering your program invalid.                        *
 *              Much care MUST be taken when using global variables.                       *
 ********************************************************************************************/
              bool setGlobalNumVarValue(uint8_t p, uint8_t b, int32_t var);


/********************************************************************************************
 *              bool setNumVarFloat(const char* varName, float_t fvar, uint8_t dp, bool round) *
 *                      - Sets Nextion Variable to fvar, with dp decimal points rounded to dp (or not). *
 *-----------------------------------------------------------------------------------------*
 *              NOTE that the ".val" varName suffix MUST NOT be sent.                      *
 *-----------------------------------------------------------------------------------------*
 *              Usage:                                                                      *
 *                      if (display.setNumVarFloat( "x0", 1234.5678, 2, true ) {.... displays 1234.57 in x0.*
 *                      if (display.setNumVarFloat( "x0", 1234.5678, 2, false ) {... displays 1234.56 in x0.*
 *-----------------------------------------------------------------------------------------*
 *              The varName MUST exist.                                                     *
 ********************************************************************************************/
              bool setNumVarFloat(const char* varName, float_t fvar, uint8_t dp, bool round);


/********************************************************************************************
 *              setStrVarValue(const char* varName, const char* var ) - Sets String Variable to var. *
 *-----------------------------------------------------------------------------------------*
 *              NOTE that there is no need to send the variable suffix ".txt".             *
 *              setStrVarValue("va0","this is a string") will send:                        *
 *                      va0.txt="this is a string"FFFFFF to the Nextion.                   *
 *-----------------------------------------------------------------------------------------*
 *              The varName MUST exist.                                                     *
 ********************************************************************************************/
              bool setStrVarValue(const char* varName, const char* var);


/********************************************************************************************
 *              setGlobalStrVarValue( uint8_t p, uint8_t b, const char* var);               *
 *-----------------------------------------------------------------------------------------*
 *              Sends p[p].b[b].txt="var" is sent to the nextion.                          *
 *-----------------------------------------------------------------------------------------*
 *              The p and b id's MUST exist and be appropriate for the type of data being sent. *
 *              NOTE that p and vb numbers can change when items are added or deleted from  *
 *              the Nextion display rendering your program invalid.                        *
 *              Much care MUST be taken when using global variables.                       *
 ********************************************************************************************/
              bool setGlobalStrVarValue(uint8_t p, uint8_t b, const char* var);
```

```
/********************************************************************************************
*            askSerialBufferClear() - Ask Nextion if Serial Buffer Clear (Empty)          *
*------------------------------------------------------------------------------------------*
*            Sends "get clrBufr" to Nextion. Nextion will reply with 0xFDFD when it gets to *
*            this request in the SerialBuffer, indicating it has executed this last command *
*            in the Serial Buffer. If other commands are sent after this one the Serial      *
*            Buffer WILL NOT BE CLEAR.                                                       *
*            Use the command isSerialBufferClear(), below to confirm Serial Buffer Clear.    *
*            Requires this line "int clrBufr=65021" in Nextion Program.s                     *
********************************************************************************************/
            void askSerialBufferClear();


/********************************************************************************************
*            isSerialBufferClear() - Query answer from askSerialBufferClear() above        *
*------------------------------------------------------------------------------------------*
*            NOTE that if other commands are stacked up which will give a reply from Nextion,*
*            then they will be handled by the calls to getReply and respondToReply used by   *
*            this function. They may return a reply, but if it is NOT a Numeric reply with    *
*            0xFDFD they will NOT return true.                                                *
********************************************************************************************/
            bool isSerialBufferClear();


/********************************************************************************************
*
*            bool askSerialBufferClear(uint32_t timeout) - As above but waits for a reply   *
*------------------------------------------------------------------------------------------*
*            Combines askSerialBufferClear() and isSerialBufferClear() with a timeout to    *
*            determine if the Nextion input Serial Buffer is Clear.                          *
********************************************************************************************/
            bool askSerialBufferClear(uint32_t timeout);
/********************************************************************************************
*            turnNextionButton(uint8_t which, bool on)                                      *
*            I have Nextion buttons named Sw0..Sw6. I use this function to set the relevant  *
*            button on (1) or off (0)                                                        *
*            I have ghosted this function with the phrase "turnNextionValve" since some of the*
*            buttons are controlling valves and it makes more sense in the code to refer to  *
*            them as valves.                                                                 *
********************************************************************************************/
#define     turnNextionValve turnNextionButton
            void turnNextionButton(uint8_t which, bool on);


/********************************************************************************************
*            setHotWaterOnForMins(uint8_t howLong)                                          *
*------------------------------------------------------------------------------------------*
*            This is somewhat clever. Teensy sets the hot water on and sends a command to the*
*            Nextion to turn off the hot water in "howLong" minutes.                         *
*            When the Nextion receives this command (via a numeric value in a Number Variable)*
*            it turns the display for the valve open "on" and when the timeout occurs it sends*
*            a command to the Teensy to turn off the hot water. This is done via the callback *
*            setup via the setValveCallBack(nextionTurnValveOnOffCallbackFunc func)function.  *
*            Thus some timing control is offloaded to the Nextion.                           *
********************************************************************************************/
            void setHotWaterOnForMins(uint8_t howLong);
```

```
/********************************************************************************************
*           setTime(uint32_t time) - Sets the time on the Nextion.                         *
*------------------------------------------------------------------------------------------*
*           The time is sent as HEX HHMMSS in the variable "SetTime=HHMMSS0xFF0xFF0xFF"     *
*           When the Nextion sees that SetTime is not zero it sets the Nextion time.        *
*           The SetTime variable is then set to 0.                                          *
*------------------------------------------------------------------------------------------*
*           Usage:                                                                          *
*                   uint32_t time = Hours * 0x10000 + Minutes * 0x100 + Seconds             *
*                   display.setTime(time)                                                   *
********************************************************************************************/
            void setTime(uint32_t time);


/********************************************************************************************
*           setDate(uint32_t date) - Sets the date on the Nextion.                         *
*------------------------------------------------------------------------------------------*
*           The time is sent as HEX YYMMDD in the variable "page0.SetDate=YYMMDD0xFF0xFF0xFF" *
*           When the Nextion sees that StDate is not zero it sets the Nextion date.         *
*           The StDate variable is then set to 0.                                           *
*------------------------------------------------------------------------------------------*
*           Usage:                                                                          *
*                   uint32_t date = (Year-2000) * 0x10000 + Month * 0x100 + Day             *
*                   display.setDate(date)                                                   *
********************************************************************************************/
            void setDate(uint32_t date);
/********************************************************************************************
*           getDateTime() - Gets the date and Time from Nextion.                           *
*------------------------------------------------------------------------------------------*
*           Gets the Date/Time set in the Nextion.                                         *
*           The packed date/time is placed in the global variable packedDateTime.          *
*           It can be decoded as shown below:                                              *
*------------------------------------------------------------------------------------------*
*                   dow    =   packedDateTime >> 29;      // (sun=0)                        *
*                   dst    = ( packedDateTime >> 28 ) & 0x01;    (known as BST in the UK)   *
*                   year   = ( packedDateTime >> 21 ) & 0x7F + 2000;                        *
*                   month  = ( packedDateTime >> 17 ) & 0x0F;                               *
*                   day    = ( packedDateTime >> 12 ) & 0x1F;                               *
*                   hour   = ( packedDateTime >>  6 ) & 0x1F;                               *
*                   minute = ( packedDateTime )       & 0x3F;                               *
*------------------------------------------------------------------------------------------*
*           NOTE: This fn should only be called when the page holding the hotspot SndDateTime *
*           is displayed. On the new example HMI file it is on page 0.                      *
*------------------------------------------------------------------------------------------*
*           Usage:                                                                          *
*                   display.getDateTime()                                                   *
********************************************************************************************/
            bool getDateTime();
```

```
/********************************************************************************************
*               turnDebugOn(bool on) - Turn Nextion debug variable on or off                *
*-------------------------------------------------------------------------------------------*
*               Usage:                                                                       *
*                   turnDebugOn( true )  - Turn debug on                                     *
*                   turnDebugOn( false ) - Turn debug off                                    *
********************************************************************************************/
               bool turnDebugOn(bool on);


/********************************************************************************************
*               setScreenDimTime(uint32_t dimTime) - Sets the time, in seconds, after which the   *
*                                               screen will dim if screen dimming is turned on.    *
*                                               The default is 3 minutes.                    *
********************************************************************************************/
               bool setScreenDimTime(uint32_t dimTime);


/********************************************************************************************
*               turnScreenDimOn(bool on) - Turn Nextion dimAllowed variable on or off        *
*-------------------------------------------------------------------------------------------*
*               Usage:                                                                       *
*                   turnScreenDimOn( true )  - Turn Dim on                                   *
*                   turnScreenDimOn( false ) - Turn Dim off                                  *
********************************************************************************************/
               bool turnScreenDimOn(bool on);


/********************************************************************************************
*               printAnyReturnCharacters(uint32_t nextionTime, uint8_t id).                  *
*               This function is intended to be used in debugging your code. It prints out to the  *
*               SerialUsb the value "nextionTime" and "Id", both values that might be useful in     *
*               tracking down where your error occurred, followed by any values that are in the     *
*               Serial input stream from the Nextion.                                        *
*               It might be that you have used "respondToReply", with your code in it, but still    *
*               there is something being returned that needs to be responded to. Use this function  *
*               to see what unexpected data is being sent from the Nextion Display.          *
*               ALL data is output in HEX.                                                    *
********************************************************************************************/
               void printAnyReturnCharacters(uint32_t nextionTime, uint8_t id);


/********************************************************************************************
*               setValveCallBack(nextionTurnValveOnOffCallbackFunc func) - passes the Nextion the  *
*               call back function    tu turn a valve on or off                              *
********************************************************************************************/
               void setValveCallBack(nextionTurnValveOnOffCallbackFunc func);


/********************************************************************************************
*               setMcuDateTimeCallback(setMcuDateTimeCallbackFunc func) - passes the Nextion the    *
*               call back fn to Set the MCU date and time. It also sets autoUpdateDateTime to true.  *
*               This setMcuDateTimeCallbackFunc is called when Nextion reports a change in date/time *
********************************************************************************************/
               void setMcuDateTimeCallback(setMcuDateTimeCallbackFunc func);
```

```
/******************************************************************************************
*            setSystemResetCallback(systemResetCallbackFunc func) - passes the Nextion the        *
*            call back fn to carry out a System Reset.                                     *
******************************************************************************************/
            void setSystemResetCallback(systemResetCallbackFunc func);


/******************************************************************************************
*            setButtonPressCallback(buttonPressCallbackFunc func) - passesm to Nextion then        *
*            call back fn to carry out a button # which press event.                       *
******************************************************************************************/
            void setButtonPressCallback(buttonPressCallbackFunc func);


/******************************************************************************************
*            setLedState - Sets the state of the leds in top, middle or bottom Row.        *
*            which = led (0..7) and state is on (1), off (0) or flashing (2).              *
*----------------------------------------------------------------------------------------*
*            Just sets the state in variable holding leds row state. There is no change    *
*            to the leds display until setNextionLeds( row ) is used.                      *
*----------------------------------------------------------------------------------------*
*            Usage:   setLedState( mid, 4, flashing );                                     *
******************************************************************************************/
            void setLedState(topMidBottmType whichLed, uint8_t which/*0..7*/, onOffFlashingType state);


/******************************************************************************************
*            setNextionLeds actually sends command to Nextion to change the state of       *
*            which leds ( top, middle or bottom row ) set with setLedState function above.  *
*----------------------------------------------------------------------------------------*
*            Usage:   setNextionLeds( top );                                               *
******************************************************************************************/
            void setNextionLeds(topMidBottmType which);


/******************************************************************************************
*            clearLeds sets the leds state variable to all (top, middle and bottom) off.    *
*            Uses setNextionLeds to send command to update all rows on Nextion.             *
******************************************************************************************/
            void clearLeds();


/******************************************************************************************
*            click(const char* objectToClick, bool touch)                                  *
*            click(uint8_t page, const char* objectToClick, bool touch)                    *
*----------------------------------------------------------------------------------------*
*            Two options, the first assumes that the Nextion is on the page where the item to be   *
*            clicked is located, trhe second version will actually change to the page given  *
*            before execuring the click function.                                          *
*----------------------------------------------------------------------------------------*
*       Usage: click("MyFavouriteHotspot", true ) sends click MyFavouriteHotSpot,1         *
*            to cause a Touch Press Event, passing false would cause a TouchRelease event.   *
*            Or: click(4, "MyFavouriteHotspot", true ) sends:-                              *
*                                  page(4)                                                  *
*                                  click MyFavouriteHotSpot,1                               *
******************************************************************************************/
            bool click(const char* objectToClick, bool touch);
            bool click(uint8_t page, const char* objectToClick, bool touch);
```

```
/*************************************************************************************
*               printTimeEmbeddedTextToNextion - Sends Text to Nextion to be placed in variable     *
*               page0.msg.txt. If transmit is set to true the text is terminated with a "            *
*               character and m0,1 is clicked to cause the screen on page1 to be updated using       *
*               the finishNextionTextTransmittion() command (see below).                             *
*               The procedure sends page0.msg.txt=" to the Nextion followed by the text.             *
*-----------------------------------------------------------------------------------*
*       Usage: printTimeEmbeddedTextToNextion( "This is a load of text for page1", true );           *
*-----------------------------------------------------------------------------------*
*               A string representing the Nextion time in the format " HH:MM:SS " is inserted        *
*               AFTER the first character.         This is carried out by the Nextion display.       *
*************************************************************************************/
               void printTimeEmbeddedTextToNextion(const char* p, bool transmit);


/*************************************************************************************
*               printTextToNextion - Sends Text to Nextion to be placed in variable                  *
*               page1.va0.txt. If transmit is set to true the text is terminated with a "            *
*               character and m0,0 is clicked to cause the screen on page1 to be updated using       *
*               the finishNextionTextTransmittion() command (see below).                             *
*               The procedure sends page1.va0.txt=" to the Nextion followed by the text.             *
*-----------------------------------------------------------------------------------*
*               Usage:  printTextToNextion( "This is a load of text for page1", true );              *
*************************************************************************************/
               void printTextToNextion(const char* p, bool transmit);


/*************************************************************************************
*               printMoreTextToNextion - It is the same as the printTextToNextion function except    *
*               that the page0.msg.txt=" is NOT sent.                                                 *
*-----------------------------------------------------------------------------------*
*               Usage:  printMoreTextToNextion( "This is a load of text for page1", true );          *
*               NOTE: DO NOT use this without first using printTextToNextion( "text", false );       *
*************************************************************************************/
               void printMoreTextToNextion(const char* p, bool transmit) {


/*************************************************************************************
*               printNumericText - Sends number to Nextion. This command MUST have been preceded     *
*               by the printTextToNextion command shown above. If transmit is set to true the text   *
*               is terminated with a "character and m0 is clicked to cause the screen on page1 to     *
*               be updated using the finishNextionTextTransmittion() command (see below).            *
*-----------------------------------------------------------------------------------*
*               Usage:   printNumericText( n, true ); // where n is a uint32_t                        *
*               NOTE: DO NOT use this without first using printTextToNextion( "text", false );       *
*************************************************************************************/
               void printNumericText(uint32_t num, bool transmit);


/*************************************************************************************
*                                                                                                    *
*               finishNextionTextTransmittion() - Terminate the text transmitted to Nextion with a   *
*               " character and terminate the command correctly. Also issues the relevant            *
*               click m0 command dependant upon which printText command was used to cause the        *
*               screen on page1 to be updated.                                                       *
*               ( Uses "click m0,1" or "click m0,0" as appropriate )                                 *
*-----------------------------------------------------------------------------------*
*               Usage:   finishNextionTextTransmittion()                                             *
*************************************************************************************/
               void finishNextionTextTransmittion();
```

```
/********************************************************************************
*              I like to keep a monitor of what has happened in the system. This display is on    *
*              page1 of the Nextion display. I use the first character position to indicate the    *
*              type of message/source of message. e.g. C for command, E for error message. After   *
*              this character I inser the Time in " HH:MM:SS " format. This is done by the          *
*              Nextion Display.                                                                     *
*------------------------------------------------------------------------------*
*              printCommandOrErrorTextMessage - sends the commandOrError charater followed by the   *
*              textMessage to the Nextion using the printTextToNextion command above.               *
*              If transmit is set to true the text  is terminated with a "character and m0 is       *
*              clicked to cause the screen on page1 to      be updated using the                    *
*              finishNextionTextTransmittion() command (see above).                                 *
********************************************************************************/
              void printCommandOrErrorTextMessage(const char* commandOrError, const char* textMessage, bool transmit);


/********************************************************************************
*              preserveTopTextLine() - Top text line writing inhibited.                             *
*------------------------------------------------------------------------------*
*              All general text commands do not use top line if this command actuated.              *
********************************************************************************/
              void preserveTopTextLine();

/********************************************************************************
*              writeToTopTextLine(const char* textMessage)                                          *
********************************************************************************/
              void writeToTopTextLine(const char* textMessage);

/********************************************************************************
*              releaseTopTextLine() - Allows writing to the Top Text Line                           *
*------------------------------------------------------------------------------*
*              All general text commands can use top line again (Default Setting).                  *
********************************************************************************/
              void releaseTopTextLine();

/********************************************************************************
*              clearTextScreen()- Clears the Nextion Text Screen (page1)                            *
*----------------------------- ------------------------------------------------*
*              If the Top Line is preserved that is not cleared, use clearTopTextLine instead.      *
********************************************************************************/
              void clearTextScreen();


/********************************************************************************

*              clearTopTextLine() - Clears the Nextion Text Screen Top Text Line                    *
********************************************************************************/
              void clearTopTextLine();
/********************************************************************************
*              setDaylightSavingOn( on) - Turn Nextion daylight saving variable on or off           *
*------------------------------------------------------------------------------*
*              Usage:                                                                               *
*                 setDaylightSavingOn( true )  - Turn on                                            *
*                 setDaylightSavingOn( false ) - Turn off                                           *
********************************************************************************/
              bool setDaylightSavingOn( bool on);
```

```
/****************************************************************************************
*                getDaylightSavingOn() - Returns Nextion daylight saving variable (true=on)      *
*--------------------------------------------------------------------------------------*
*                Usage:                                                                 *
*                    getDaylightSavingOn()                                              *
****************************************************************************************/
              bool getDaylightSavingOn();


/****************************************************************************************
*                viewDebugText(bool view) - Displays the debugTxt Text Line (or NOT)    *
****************************************************************************************/
              void viewDebugText(bool view);
```