Friends, not Foes – Synthesizing Existing Transport Strategies for Data Center Networks

Ali Munir Michigan State University

Ghufran Baig, Syed M. Irteza, Ihsan A. Qazi, Alex X. Liu, Fahad R. Dogar








Data Center (DC) Applications

Distributed applications
 Components interact via the network

e.g., a bing search query touches > 100 machines



Network impacts performance "10% of search responses observe 1 to 14 ms of network queuing delay" [DCTCP, SIGCOMM 10]



DC Network Resource Allocation

Fair Sharing


Equal bandwidth sharing among jobs [TCP, DCTCP]


- Increases completion time for everyone
- Traditional "fairness" metrics less relevant

QoS Aware

Prioritize some jobs over other jobs (Priority Scheduling)

- Minimize flow completion times [pFabric, L2DCT]
- Meet flow deadlines [D³, D²TCP]





DCTCP

Deployment Friendly but Suboptimal

D²TCP SIGCOMM'12 pFabric

Near Optimal but not Deployment Friendly (Changes in data plane)

DCTCP

Deployment Friendly but Suboptimal

D²TCP SIGCOMM'12 pFabric

Near Optimal but not Deployment Friendly (Changes in data plane)

Step back and ask

How can we design a deployment friendly and near optimal data center transport while leveraging the insights offered by existing proposals?



Ston hack and ack

How can we optimal dat insigh

PASE

iendly and near leveraging the oposals?

Rest of the Talk ...

- DC Transport Strategies
- PASE Design
- Evaluation

Rest of the Talk ...

- DC Transport Strategies
- PASE Design
- Evaluation

DC Transport Strategies

- Self-adjusting endpoints e.g., TCP, DCTCP, L²DCT
 - senders make independent decisions and adjust rate by themselves
- Arbitration

e.g., D³, PDQ

- a common network entity (e.g., a switch) allocates rates to each flow
- In-network prioritization e.g., pFabric
 - switches schedule and drop packets based on the packet priority

DC Transport Strategies

- Self-adjusting endpoints e.g., TCP, DCTCP, L²DCT
 - senders make independent decisions and adjust rate by themselves

es

- Ar
 - Existing DC transport proposals use only one of these strategies
- In-network prioritization e.g., pFabric
 - switches schedule and drop packets based on the packet priority

Transport Strategy	Example	Pros	Cons
Self- Adjusting Endpoints	DCTCP, D ² TCP, L ² DCT		
Arbitration	PDQ, D³		
In-network Prioritization	pFabric		

Transport Strategy	Example	Pros	Cons
Self- Adjusting Endpoints	DCTCP, D ² TCP, L ² DCT	Ease of deployment	No strict priority scheduling
Arbitration	PDQ, D³		
In-network Prioritization	pFabric		

Transport Strategy	Example	Pros	Cons
Self- Adjusting Endpoints	DCTCP, D ² TCP, L ² DCT	Ease of deployment	No strict priority scheduling
Arbitration	PDQ, D³	Strict priority scheduling	 High flow switching overhead Hard to compute precise rates
In-network Prioritization	pFabric		


Transport Strategy	Example	Pros	Cons
Self- Adjusting Endpoints	DCTCP, D ² TCP, L ² DCT	Ease of deployment	No strict priority scheduling
Arbitration	PDQ, D³	Strict priority scheduling	 High flow switching overhead Hard to compute precise rates
In-network Prioritization	pFabric	Low flow switching overhead	Switch-local decisionsLimited # of priorityqueues

Transport Strategy	Example	Pros	Cons
Self- Adjusting Endpoints	DCTCP, D ² TCP, L ² DCT	Ease of deployment	No strict priority scheduling
Arbitration	PDQ, D³	Strict priority scheduling	 High flow switching overhead Hard to compute precise rates
In-network Prioritization	pFabric	Low flow switching overhead	Switch-local decisionsLimited # of priority queues

In-network Prioritization Alone

Limited # of queues

More # of flows (priorities)




In-network Prioritization Alone

Limited # of queues

More # of flows (priorities)

Flow Multiplexing
Limited performance gains!



Any static mapping mechanism degrades performance!

In-network Prioritization + Arbitration

Arbitrator

Dynamic mapping of flows to queues



Idea

As a flow's turn comes, map it to the highest priority queue!

In-network Prioritization + Arbitration


Arbitrator

Dynamic mapping of flows to queues



Idea


As a flow's turn comes, map it to the highest priority queue!



In-network Prioritization + Arbitration


Arbitrator

Dynamic mapping of flows to queues




Idea

As a flow's turn comes, map it to the highest priority queue!



In-network Prioritization + Arbitration




Rest of the Talk ...


- DC Transport Strategies
- PASE Design
- Evaluation

PASE Design Principle

Each transport strategy should focus on what it is best at doing!


- Arbitrators
 - Do inter-flow prioritization at coarse time-scales
- Endpoints
 - Probe for any spare link capacity
- In-network prioritization
 - Do per-packet prioritization at sub-RTT timescales





Arbitration: Control plane

Calculate "reference rate" and "priority queue"




Arbitration: Control plane

Calculate "reference rate" and "priority queue"

Self-Adjusting Endpoints: Guided rate control

Use arbitrator feedback as a pivot




Arbitration: Control plane

Calculate "reference rate" and "priority queue"

Self-Adjusting Endpoints: Guided rate control

Use arbitrator feedback as a pivot

In-network Prioritization: Existing priority queues



Arbitration: Control plane


Calculate "reference rate" and "priority queue"

Self-Adjusting Endpoints: Guided rate control


Use arbitrator feedback as a pivot

In-network Prioritization: Existing priority queues

Key Components








Distributed Arbitration

- per link arbitration done in control plane
- existing protocols implement in data plane




Distributed Arbitration

- per link arbitration done in control plane
- existing protocols implement in data plane

Arbitrator Location

- at the end hosts (e.g., for their own links to the switch) OR
- on dedicated hosts inside the DC




Distributed Arbitration

- per link arbitration done in control plane
- existing protocols implement in data plane

Arbitrator Location

- at the end hosts (e.g., for their own links to the switch) OR
- on dedicated hosts inside the DC



Distributed Arbitration

- per link arbitration done in control plane
- existing protocols implement in data plane

Arbitrator Location

- at the end hosts (e.g., for their own links to the switch) OR
- on dedicated hosts inside the DC

PASE Arbitration – Challenges

Challenges

- Arbitration latency
- Processing overhead
- Network overhead

PASE Arbitration – Challenges

Challenges

- Arbitration latency
- Processing overhead
- Network overhead

Solution: Leverage the tree-like structure of typical DC topologies

 Leverage Tree Structure from leaves up to the root

Leverage Tree Structure from leaves up to the root
Aggregation
ToR
Inter-Rack
Receiver

Receiver

Arbitration Message


Leverage Tree Structure
from leaves up to the root
 Aggregation
 ToR
 Inter-Rack

Sender


Receiver


Arbitration Message

 Leverage Tree Structure from leaves up to the root



 Leverage Tree Structure from leaves up to the root






Core **Leverage Tree Structure** from leaves up to the root Aggregation Aggregation ToR ToR **ToR** Sender Receiver Inter-Rack Intra-Rack Sender Receiver Arbitration Message No external arbitrators Receiver Response required!

Facilitates inter-rack optimizations (early pruning & delegation) to reduce arbitration overhead.

Early Pruning



Arbitration involves sorting flows and picking top k for immediate scheduling


Flows that won't make it to top k queues should be pruned at lower levels

Early Pruning




top k queues should be pruned at lower levels

Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators




Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators



Algorithm
Link capacity C is split in N
virtual links

Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators




> Algorithm

Link capacity C is split in N virtual links

Parent arbitrator delegates virtual link to child arbitrator

Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators




> Algorithm

Link capacity C is split in N virtual links

Parent arbitrator delegates virtual link to child arbitrator

Child arbitrator does arbitration for virtual link

Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators



> Algorithm


Link capacity C is split in N virtual links

Parent arbitrator delegates virtual link to child arbitrator

Child arbitrator does arbitration for virtual link

Virtual link capacity is periodically updated based on the top k flows of all child arbitrators

Key Idea: Divide a link into virtual links and delegate responsibility to child arbitrators



ToRs

Make arbitration decision close to the sources


> Child arbitrator does arbitration for virtual link

ates

ator

Virtual link capacity is periodically updated based on the top k flows of all child arbitrators

PASE Overview



- Arbitration: Control plane
 Calculate "reference rate" and "priority queue"
- Self-Adjusting Endpoints: Guided rate control Use arbitrator feedback as a pivot
- In-network Prioritization: Existing priority queues

PASE Endhost Transport

Rate Control

Loss Recovery Mechanism

PASE Endhost Transport

Rate Control

Use reference rate and priority feedback from arbitrators

- Use reference-rate as pivot, and
- Follow DCTCP control laws
- Loss Recovery Mechanism

PASE Endhost Transport

Rate Control


Use reference rate and priority feedback from arbitrators

- Use reference-rate as pivot, and
- Follow DCTCP control laws

Loss Recovery Mechanism

- Packets in lower priority queues can be delayed for several RTTs
 - large RTO OR small probe to avoid spurious retransmissions

PASE -- Putting it Together



- Efficient arbitration control plane
- Simple TCP-like transport
- Existing priority queues inside switches


Rest of the Talk ...

- DC Transport Strategies
- PASE Design
- Evaluation


Evaluation

- Platforms
 - Small scale testbed
 - **NS2**
- Workloads
 - Web search (DCTCP), Data mining (VL2)
- Comparison with deployment friendly
 - DCTCP, D²TCP, L²DCT
- Comparison with state of the art
 - pFabric

Simulation Setup



Comparison with Deployment Friendly




Settings similar to D2TCP

• Flow Sizes: 100-500KB

Deadlines: 5-25msec

Comparison with Deployment Friendly




Settings similar to D²TCP

Flow Sizes: 100-500KB

Deadlines: 5-25msec

PASE is deployment friendly yet performs
BETTER than existing protocols!


Comparison with State of the Art



Settings

- Flow Sizes: 2-98KB
- Left-to-right traffic

Comparison with State of the Art



Settings

- Flow Sizes: 2-98KB
- Left-to-right traffic

PASE performs comparable and does not require changes to data plane

Summary

- Key Strategies for Existing DC Transport
 - Arbitration, in-network Prioritization, Self-Adjusting Endpoints
 - Complimentary rather than substitutes

PASE

- Combines the three strategies
- Efficient arbitration control plane; simple TCP-like transport;
 leverages existing priority queues inside switches

Performance

 Comparable to or better than earlier proposals that even require changes to the network fabric Thank you!