



Dynamic Bandwidth Allocation for Multiple Network Connections:

Improving User QoE and Network Usage of YouTube in Mobile Broadband


Florian Wamser, Thomas Zinner, Phuoc Tran-Gia
University of Würzburg, Germany



Jing Zhu
Intel Labs, Hillsboro, OR, United States







Competing Applications at a Bottleneck Link




Impact on Application Quality

► Content unaware networks

- Fair share with respect to QoS (throughput)
- Bulk data download performance: good 
- YouTube quality: bad 



Influence on
YouTube



Application-Aware Networking

► Tasks and objectives

- Integrating application needs' in network resource management
- Add or re-allocate resources on demand

1. Application and network monitoring


- Collects information with high correlation to QoE
- Example: YouTube monitor (YoMo), browsing monitor, etc.

2. Decision entity


- Evaluates the information and decides about appropriate resource management action

3. Dynamic resource management

- Enforces resource management actions
- Example: resource allocation, scheduling, traffic prioritization, access technology selection, ...



Resource Management: Dual Connectivity of Devices





► More than just one transmission technology is available at current mobile devices

- Wi-Fi Communications
- Cellular Communications

Framework for Intelligent Bandwidth Aggregation

- ▶ Virtual access network (VAN) to aggregate multiple networks into single IP pipe
- ▶ Technical implementation: TCP/IP over UDP tunneling (mobile IP-like approach)
- ▶ Features of Intel's OTT VAN
 - Configurable bandwidth aggregation for multiple networks
 - (TCP) packet reordering (re-sequencing)
- ▶ Missing features
 - Smart algorithms for dynamic offloading
 - Application specific guidelines




Client



- ▶ Virtual network device provides tunneling functionality
- ▶ Access technologies
 - Wi-Fi communications (limited to max. 2 Mbps)
 - Mobile communications (limited to 4 Mbps)

Server

- ▶ Tunnel endpoint
- ▶ Implements re-sequencing buffer
- ▶ Enforces resource management




Resource Management Algorithms

- ▶ Adjust offload ratio between Wi-Fi and 3G cellular traffic, based on a **required throughput**
- ▶ Always use Wi-Fi and dynamically add 3G
 - If current throughput < required throughput
 - Increase 3G bandwidth 
 - If current throughput > required throughput
 - Decrease 3G bandwidth 

Resource Management Algorithms for YouTube


► Algorithm 1: Static Offloading Based on Video Request

- Defines required throughput based on requested video quality
- Detects uplink request by YouTube with DPI




► Algorithm 2: Dynamic Offloading Based on Buffer Estimation

- Constant monitoring of the buffer level
- Adaption of the required throughput based on the buffer level



► Algorithm 3: Burst-wise Offloading Based on Buffer Estimation


- Make use of the complete bandwidth until the buffer is filled
- Disables 3G link until the buffer gets low



Time Series of Algorithm 1


► Time series of one video with 1080p resolution

- Wi-Fi and 3G available
- Static req. throughput = 6 Mbps




Time Series of Algorithm 2

- ▶ Algorithm 2 dynamically adjusts required throughput according to video playback buffer



Comparison of Algorithm 1 and 2

- Consumption of 3G bandwidth
 - per 1000 seconds playtime





	Resolution based		Buffer based
720p	98 MB	-64,3%	35 MB
1080p	321 MB	-30,5%	223 MB

Comparison of Algorithm 1 and 2

- Average amount of consumed energy
 - per 1000 seconds playtime


J. Huang et al. „A close examination of performance and power characteristics of 4g lte networks”



	Resolution based		Buffer based
720p	1180 J	$\xrightarrow{-49,9\%}$	591 J
1080p	1404 J	$\xrightarrow{-7,5\%}$	1299 J

Time Series of Algorithm 3



- ▶ Algorithm 3 activates 3G link in bursts



Comparison of Algorithm 2 and 3

► Average amount of consumed energy

■ per 1000 seconds playtime



	Dynamic buffer		Burst-wise buffer
720p	591 J	-12,2% →	519 J
1080p	1299 J	-8,9% →	1183 J

Conclusion and Outlook

► Contribution of the work

- Assessment and quantification of the benefits of cross-layer resource management on the example of YouTube
- Analysis of three application-aware algorithms which differ in complexity and impact on user and network

► Results of the evaluation

- The application-aware algorithms can
 - enhance the QoE level for end users (if both networks provide enough resources)
 - save costs in terms of energy & Cellular resources

► Future work

- Investigations on scalability of our approach and field trials with many users
- Providing a holistic resource allocation for popular applications with respect to their instantaneous needs

<http://dl.acm.org/authorize?N71341>

Florian Wamser, Thomas Zinner, Phuoc Tran-Gia and Jing Zhu
**Dynamic Bandwidth Allocation for Multiple Network
Connections: Improving User QoE and Network Usage of
YouTube in Mobile Broadband**



ACM SIGCOMM Capacity Sharing
Workshop (CSWS 2014)

In conjunction with ACM SIGCOMM 2014 conference, on August 18, Chicago, USA.



<http://dl.acm.org/authorize?N71209>

Florian Wamser, Thomas Zinner, Lukas Iffländer, Phuoc Tran-Gia
**Demonstrating the Prospects of Dynamic Application-Aware
Networking in a Home Environment**



ACM SIGCOMM 2014

SIGCOMM is the flagship annual conference of the ACM Special Interest Group on Data Communication (SIGCOMM) on the applications, technologies, architectures, and protocols for computer communication.



<http://dl.acm.org/authorize?N71235>

Steffen Gebert, David Hock, Thomas Zinner, Phuoc Tran-Gia (University of Würzburg); Marco Hoffmann, Michael Jarschel, Ernst-Dieter Schmidt (Nokia); Ralf-Peter Braun (Deutsche Telekom T-Labs), Christian Banse (Fraunhofer AISEC); Andreas Kopsel (BISDN)

Demonstrating the Optimal Placement of Virtualized Cellular Network Functions in Case of Large Crowd Events



Fraunhofer
AISEC

NOKIA



ACM SIGCOMM 2014

SIGCOMM is the flagship annual conference of the ACM Special Interest Group on Data Communication (SIGCOMM) on the applications, technologies, architectures, and protocols for computer communication.