How Much Junk Do Rules Catch? Evaluating pygarble, a Dependency-Free Gibberish Screener, on Survey Responses and Social-Media Text

Ujjwal Singh Rao
ujjwalsrao@gmail.com
https://github.com/brightertiger/pygarble

October 2026

Abstract

Text that reaches a language model, a survey database or a training corpus is not always text. Keyboard mashing, random strings and placeholder answers are common, and the usual detectors for them are either trained classifiers with model downloads or hand-written rules that nobody has measured. pygarble is a Python library with no runtime dependencies that screens text with 32 rule-based and statistical strategies combined into named profiles. We evaluate it on two public datasets: a Kaggle collection of 3,513 free-text survey responses labelled as junk, and a Hugging Face collection of 9,971 English rows that pairs 4,000 random strings with 5,971 tweets. Two CPU baselines are run under the same conditions, a character Markov-chain gibberish detector and a language identifier, with every method at its own default decision. The `english_fusion` profile captures 89.5 % of the survey junk and recalls 99.1 % of the random strings at a precision of 0.906, from a 1.05 MB install that processes a thousand short texts in 62.0 ms. The Markov baseline flags fewer tweets but misses more junk; the language identifier captures the most junk at the highest install cost. A post hoc variant of the default profile that drops its two encoding-damage checks shows that the ensemble adapts to a domain by removing strategies: its false-positive rate on tweets falls from 33.2 % to 18.2 % with no change in recall. Code, per-row predictions and a verification script are released so that every number can be recomputed.

1 Introduction

Free-text fields collect junk. Respondents mash the keyboard to reach the next page of a survey, bots submit random strings to sign-up forms, and scraped text carries encoding damage. Each of these costs something downstream: a coder reads it, a model is trained on it, or an analysis counts it as an answer. The problem has become more visible with large language models, where unreadable input wastes tokens, degrades retrieval, and in guardrail settings is itself a signal that something upstream has gone wrong. The author's own motivation for pygarble is exactly this guardrail role: a cheap, local check that runs on every prompt and every model output before anything more expensive does.

Two families of tools exist for the task. Trained classifiers, such as the DistilBERT gibberish model used in open-source LLM guardrail frameworks [3], are accurate on the distribution they were trained on but need a model download and a deep-learning runtime, and their decisions are hard to explain row by row. Rule-based detectors, from character Markov models [4] to the nonsense evaluator Nostril [2] and the quality heuristics used to filter web corpora [5, 6], are cheap, local and explainable, and are often the first filter a team writes by hand. What is rarely reported is how much junk such rules actually catch on real data, and how much good text they wrongly flag.

This paper measures one such library. pygarble [7] packages 32 strategies, each a function from a string to a score in $[0, 1]$, together with voting rules that combine them into profiles. It has no runtime dependencies and ships its English reference tables inside the wheel. We ask a plain question: at default settings, on data its author never saw, how much junk does it capture, how much legitimate text does it flag, and what does it cost compared with two common alternatives?

The contributions are:

- A benchmark on two public datasets of short text, one of real human junk from survey research and one of random strings against tweets, with a frozen protocol, saved per-row predictions and a script that recomputes every reported number.
- A comparison of pygarble's default and `english_fusion` profiles with a character Markov-chain detector and a language identifier, all at their default decisions, on capture rate, precision, recall, false-positive rate, speed and install size.
- A post hoc, domain-specific tuning of the default profile, reported separately from the main results,

Table 1: Strategy families in pygarble. Counts sum to 32.

Family	Count	What it detects	Examples
Character statistics	8	Letter mixes English rarely produces	`vowel_ratio`, `symbol_ratio`
English character models	5	Unlikely letter sequences	`markov_chain`, `rare_trigram`
Word-level checks	6	Unknown words, missing English word patterns	`word_lookup`, `word_anomaly`
Structure and pattern checks	6	Repeats, keyboard mash, hex, local corruption	`repetition`, `hex_string`
Encoding and script checks	3	Mojibake, control characters, spoofing	`mojibake`, `unicode_script`
English-reference window statistics	4	Distance from synthetic English	`cross_parsing`, `ngram_rank`

showing how the ensemble is adapted by removing strategies.

- A description of pygarble's strategy families and profiles, with the full strategy list in the appendix.

2 pygarble

pygarble targets Python 3.8 and later and has no runtime dependencies. The installed package, including its embedded English tables, is 1.05 MB. Besides gibberish detection it scans text for secrets, personal data and profanity and can redact them; those features are outside this paper.

2.1 Strategies

A *strategy* is a function from a string to a score in $[0, 1]$ and a binary decision, with a flag that says whether the strategy applies to the input at all. A strategy that finds no Latin letters, or too few characters to measure, reports that it does not apply rather than returning a score, so that absence of evidence is not counted as evidence of junk. The 32 strategies fall into six families (Table 1; the full list with one-line descriptions is in Appendix A).

Character statistics measure properties of the character stream that English rarely violates: the vowel ratio, Shannon entropy, the longest consonant run, the letter-frequency profile, the symbol share, and whether tokens are pronounceable.

English character models compare the text with tables learned from English: a character Markov chain over novel tokens, bigram and trigram probabilities, a rare-trigram count, and a log-likelihood ratio of English against a uniform reference.

Word-level checks look words up in an embedded dictionary and measure the unknown fraction, the fraction of anomalous tokens, the density of English function words, the presence of English affixes, the plausibility of adjacent word pairs, and whether the word-frequency profile conforms to Zipf's law.

Structure and pattern checks target forms of junk that are not statistical: repeated substrings, keyboard-row walks and adjacent-key sequences, hexadecimal strings, built-in patterns such as a letter repeated four or more times or a five-key keyboard-row walk (with optional user-supplied patterns), and local anomalies inside otherwise ordinary text.

Encoding and script checks fire on damage rather than on meaning: mojibake byte signatures left by a wrong decoding, control characters, and mixed or confusable Unicode scripts.

English-reference window statistics compare a window of the text with frequent English rather than applying a hand-written rule: cross parsing, primed compression, n-gram rank and a permutation test. Each statistic is measured against synthetic English of the same length, and a score of 0.5 sits beyond the 99th percentile of that reference.

2.2 Ensembles, voting and profiles

`EnsembleDetector` runs a list of strategies and combines them under a voting rule. With `any` voting, one applicable member firing flags the text; `all`, `majority`, `average` and `weighted` voting behave as their names say. `fisher` voting treats each member's score as a test statistic: a table shipped with the package records what that member scores on synthetic English word salads of matched length, the member's p-value is the smallest tail probability whose threshold the score exceeds, and the p-values are combined with Fisher's method [1]. A text is flagged when the combined score reaches the threshold, 0.5 by default. Named member lists are called *profiles*; Appendix B lists all seven. Two are measured here:

- `english`, the default: Markov chain, log-likelihood ratio, word anomaly, mojibake, keyboard adjacency and control characters, under `any` voting. One member firing is enough.
- `english_fusion`, opt-in: word lookup, log-likelihood ratio and cross parsing under `fisher` voting. Because each member's p-value is floored at

0.001, at least two members must exceed their null thresholds before a text is flagged, which is what gives this profile its lower false-positive rate.

A user can also pass any list of strategies, which is how the tuned variant in Section 5.3 is built. The English profiles score English plausibility; they are not language identifiers, and meaningful text in other Latin-script languages can be flagged. Scores are heuristic, not calibrated probabilities.

3 Datasets

3.1 Survey Junk

The Kaggle dataset *Gibberish Text Classification* [10] was compiled by a market-research practitioner from free-text responses of poor-quality survey respondents. Its junk file holds 3,767 rows, every one labelled as junk; despite its `.xls` extension it is a Windows-1252 CSV. We strip each response, drop empty rows and drop exact duplicates, leaving 3,513 rows. Typical rows are keyboard mashes such as runs of adjacent keys, repeated letters, and letters mixed with digits. The median response is ten characters long and most are a single token.

Because the file has no clean rows, the only metric on this dataset is the *capture rate*: the share of rows a method flags. The licence is listed as unknown on Kaggle, so the repository stores row indices and hashes, never the text.

3.2 Tweets vs. Random Strings

The Hugging Face dataset *gibberish_multilingual* [8] (Apache-2.0) pairs random character strings with social-media posts in seven languages. We pool its train, validation and test files and keep the 9,971 non-empty rows whose language field is English: 4,000 random strings, labelled junk, and 5,971 tweets, labelled clean. Labels are used exactly as given and duplicates are kept (215 rows repeat an earlier text). The random strings are lowercase letter sequences such as `edkylxhboa`; the tweets carry hashtags, handles and, in 26.4 % of cases, mojibake byte signatures from a UTF-8 emoji decoded as Latin-1. The dataset labels those tweets clean because it was built to separate random strings from posts.

On this dataset we report precision, recall and the false-positive rate (FPR), the share of tweets flagged.

4 Experimental setup

Methods. pygarble 0.11.0 is used with its defaults frozen at commit `e3135ed`; no default or threshold was changed after any result was seen. Two baselines run on CPU with pinned versions:

- **gibberish-detector** 0.1.1 [4], a character Markov model and, at the time of writing, the most downloaded gibberish detector on PyPI. The package ships no model, so one is trained with its own trainer on the corpus its README uses, and a text is flagged when its score exceeds the command-line default of 4.0.
- **lingua** 2.2.0 [9], a language identifier, under the policy "not detected as English is junk".

There are no neural baselines; the DistilBERT gibberish model was excluded to keep the comparison to tools that run with no model download.

Decisions. Every method is scored at its own default decision, the binary output it gives with default settings. No threshold is fitted on either dataset.

Intervals. Uncertainty is given as 95 % percentile intervals from 1,000 bootstrap resamples of rows, drawn with a fixed seed and shared by all methods.

Pilot and protocol changes. Before the protocol was written, both datasets were scored once with pygarble's defaults to judge feasibility. The `english_fusion` numbers from that pilot are the ones reported here, because nothing in the package changed afterwards. The first version of the protocol also fitted thresholds at fixed false-positive rates on a development split of the tweets dataset and compared more baselines and pygarble configurations; both were computed and then removed from the paper's scope (Section 7). The tuned variant in Section 5.3 was added after the results were seen and is reported as post hoc.

Environment. All runs are single-threaded on an Apple M2 with Python 3.12.2. Hardware, package versions and the pygarble commit are recorded with the results.

5 Results

5.1 Survey Junk

Table 2 gives the capture rates. `english_fusion` flags 89.5 % of the junk responses (0.884–0.905), and the default `english` profile 83.0 %. The Markov baseline captures 72.2 %, and lingua, which flags anything it does not identify as English, captures 98.9 %.

The ordering follows what each method can see. Keyboard mashes and random letters have improbable character transitions and no dictionary words, so every method catches most of them. Lingua's near-complete capture comes from the policy rather than from junk detection: a ten-character mash is not confidently English, so it is flagged, and Section 5.2 shows what that policy costs on real text. The Markov baseline misses the




Figure 1: Top: capture rate on Survey Junk (3,513 responses labelled as junk). Bottom: precision and recall on Tweets vs. Random Strings (4,000 random strings, 5,971 tweets). Every method at its default decision, with 95 % bootstrap intervals. The tuned row below the dashed rule is post hoc (Section 5.3).

Table 2: Capture rate on Survey Junk: the share of 3,513 junk responses each method flags at its default decision, with 95 % bootstrap intervals. Typewriter names are pygarble profiles. Lingua flags a text when the detected language is not English. The last row is post hoc (Section 5.3).

Method	Capture rate	95% CI
`english` (default)	0.830	[0.817, 0.843]
`english_fusion`	0.895	[0.884, 0.905]
gibberish-detector	0.722	[0.707, 0.736]
lingua	0.989	[0.985, 0.992]
`english`, tuned	0.830	[0.817, 0.843]

rows whose transitions happen to be plausible, such as repeated syllables. The 369 rows that `english_fusion` misses are mostly one to three characters long, letters mixed with digits, strings with no letters at all, or a short syllable or punctuation mark repeated; a few are real words or short phrases, which read as English to character and word statistics.

The dataset is used as labelled, and it has some label noise: 15 rows are flagged by none of the four untuned methods, and on inspection many are meaningful low-effort answers such as a thanks or a short positive phrase. The capture rates therefore have a ceiling below one.

5.2 Tweets vs. Random Strings

Table 3 gives precision, recall and false-positive rate. The random strings are easy for every method: `english_fusion` recalls 99.1 % of them and lingua 99.4 %. What separates the methods is how many tweets they flag. `english_fusion` flags 6.8 % of tweets, for a precision of 0.906. The Markov baseline flags only 0.3 %, the lowest of any method, and reaches a precision of

Table 3: Precision, recall and false-positive rate on Tweets vs. Random Strings (4,000 random strings as junk, 5,971 tweets as clean), every method at its default decision; each cell shows the value with its 95 % bootstrap interval beneath. FPR is the share of tweets flagged. Typewriter names are pygarble profiles. Lingua flags a text when the detected language is not English. The last row is post hoc (Section 5.3).

Method	Precision	Recall	FPR
`english` (default)	0.656	0.947	0.332
	[0.645, 0.670]	[0.940, 0.954]	[0.320, 0.344]
`english_fusion`	0.906	0.991	0.068
	[0.898, 0.915]	[0.987, 0.993]	[0.062, 0.075]
gibberish-detector	0.995	0.822	0.003
	[0.993, 0.997]	[0.809, 0.833]	[0.002, 0.004]
lingua	0.876	0.994	0.094
	[0.867, 0.886]	[0.991, 0.996]	[0.087, 0.101]
`english`, tuned	0.777	0.947	0.182
	[0.766, 0.789]	[0.940, 0.954]	[0.173, 0.192]

0.995, but at the cost of recalling only 82.2 % of the random strings. Lingua flags 9.4 % of tweets, since short informal posts with hashtags and handles are often not confidently English. The default `english` profile flags 33.2 % of tweets, the highest rate in the table; the next subsection explains why and what a user does about it.

This dataset is a measure of false positives on informal English more than of recall on realistic junk: its junk is random strings, which share almost nothing with English, so any character model separates them.

5.3 Domain-specific tuning

The default `english` profile contains two strategies that target encoding damage: mojibake and control characters. On this dataset they fire on the 26.4 % of tweets that carry mojibake, which the labels treat as clean, and the control-character check fires on the C1 control codes that the same mis-decoding produces. A user screening social-media text for gibberish, who does not care about encoding damage, would remove both. We built that variant, the `english` profile without mojibake and control characters, with the same `any` voting and threshold; the package was not changed. The variant was constructed after seeing the results above, so it is post hoc and reported as such.

Its results sit in the last row of Tables 2 and 3. Capture on Survey Junk and recall on Tweets vs. Random Strings are unchanged at 83.0 % and 94.7 %, because no junk row in either dataset depended on the two encoding checks. The false-positive rate on tweets falls from 33.2 % to 18.2 %, and precision rises from 0.656 to 0.777. The point is not this particular variant but the mechanism: a profile is a list of strategies, each targeting one kind of junk, and a domain that does not count some kind as junk removes the strategies that target it, without retraining anything. `english_fusion` contains no

Table 4: Footprint. Time is the default decision over all 9,971 texts of Tweets vs. Random Strings on one thread of an Apple M2, median of five runs after a warm-up. Install size counts the installed files of the distribution and its runtime dependencies, plus the training corpus gibberish-detector's model is built from. Import time covers the import statement only; lingua loads its models when the detector is built, which is counted in the per-text time.

Method	ms/1k	Import (s)	Install (MB)	Deps
`english` (default)	66.4	0.021	1.05	none
`english_fusion`	62.0	0.021	1.05	none
gibberish-detector	6.8	0.039	6.51	none[a]
lingua	1039.0	0.001	307.47	none[b]
`english`, tuned	52.7	0.021	1.05	none

[a] Ships no model; trains one from a text corpus at start-up (the benchmark uses the project's `big.txt`, counted in its install size).
[b] Bundles its language models in the wheel.

encoding check, so it has no such variant.

5.4 Cost

Table 4 lists time per 1,000 texts, import time and install size. pygarble scores a thousand short texts in 62.0 ms with `english_fusion` and installs in 1.05 MB with nothing else. The Markov baseline is the fastest at 6.8 ms and 6.51 MB. Lingua needs 1039.0 ms and 307.47 MB of language models. All three run offline once installed. Timings depend on the machine.

6 Discussion

What the results support. At default settings pygarble's `english_fusion` profile captures about nine in ten real survey junk responses and nearly every random string, while flagging about one tweet in fifteen, from a one-megabyte install with no dependencies. Among the three tools it is the only one that is strong on both datasets: the Markov baseline flags far fewer tweets but misses more than a quarter of the survey junk, and lingua captures almost all junk but flags more tweets and needs three hundred megabytes of language models.

Where pygarble is beaten. The Markov baseline has the lowest false-positive rate on tweets, 0.3 % against 6.8 %; when wrongly flagging a real post costs much more than missing junk, it is the better default. Lingua captures more survey junk, 98.9 % against 89.5 %, under its aggressive policy. The default `english` profile is not suitable for informal text as shipped: it flags a third of tweets, and still 18.2 % after the tuning in Section 5.3, because its Markov member alone flags many posts with handles and hashtags.

Guidance. For screening survey or form free text, use `english_fusion`; add a minimum-length rule if one- and two-character answers count as junk. For a new domain, start from a profile and remove the strategies whose target the domain does not treat as junk, as in Section 5.3. When false positives are costly, prefer the Markov baseline at default settings, or measure a threshold on labelled rows of your own data. For multilingual input, route by language first; a language identifier answers that question, and it is not a junk detector.

7 Limitations

Two public datasets are measured, both English and both short text; the behaviour on long documents is not measured. Survey Junk has only junk, so it measures capture and nothing about false positives; Tweets vs. Random Strings has random strings as its only junk, which are easier than real junk. There are two baselines and no neural one. Each method is run once at its default decision, so the results say how the tools behave out of the box, not how well they can be tuned; the one tuned variant is post hoc and was chosen with knowledge of the tweets results. A comparison at a matched false-positive rate, with thresholds fitted on a development split, was computed in an earlier version of the protocol and removed from the paper's scope; in it the Markov baseline captured more survey junk than `english_fusion`. It remains in the repository history.

8 Reproducibility

The benchmark code, the frozen protocol with its dated deviations file, and the results are in the repository under `paper/`. The manifest records the SHA-256 hash of each raw file (for Survey Junk, beginning `091d5d3895f035d5`) and every row id; no dataset text is committed. Per-row scores and decisions for every method are committed, so every number in this paper can be recomputed without the raw data:

```
make benchmark-verify PYTHON=<venv>/bin/python
make preprint PYTHON=<venv>/bin/python
```

The first command recomputes the metrics from the saved predictions and fails on any difference. The second regenerates the figure, the tables and the number macros this paper is typeset from, then builds the PDF. Re-scoring from the raw files is described in the benchmark README; scores are deterministic.

AI assistance

Claude Code agents running Claude Opus 5.5 and Claude Fable 5.1 wrote the benchmark code, ran the experiments and drafted this text under the author's direction and review. Commit trailers in the repository record the model behind each commit.

References

[1] Ronald A. Fisher. *Statistical Methods for Research Workers*. Oliver and Boyd, Edinburgh, 1925.

[2] Michael Hucka. Nostril: A nonsense string evaluator written in Python. *Journal of Open Source Software*, 3(25):596, 2018. doi: 10.21105/joss.00596.

[3] Madhur Jindal. autonlp-gibberish-detector-492513457. Hugging Face model, `https://huggingface.co/madhurjindal/autonlp-Gibberish-Detector-492513457`. DistilBERT classifier; accessed 2026-10-11.

[4] Aaron Loo. gibberish-detector. `https://github.com/domanchi/gibberish-detector`, 2021. Version 0.1.1 on PyPI; a port of `https://github.com/rrenaud/Gibberish-Detector`; accessed 2026-10-11.

[5] Jack W. Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, et al. Scaling language models: Methods, analysis and insights from training Gopher. *arXiv preprint arXiv:2112.11446*, 2021.

[6] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21 (140):1–67, 2020.

[7] Ujjwal Singh Rao. pygarble: local screening of text for secrets, PII, profanity and gibberish. `https://github.com/brightertiger/pygarble`, 2026. Version 0.11.0, commit e3135ed.

[8] Sowmya15. gibberish_multilingual. Hugging Face dataset, `https://huggingface.co/datasets/Sowmya15/gibberish_multilingual`, 2024. Apache-2.0; accessed 2026-10-11.

[9] Peter M. Stahl. Lingua: the most accurate natural language detection library for Python. `https://github.com/pemistahl/lingua-py`, 2026. Package lingua-language-detector, version 2.2.0; accessed 2026-10-11.

[10] John Wackerow. Gibberish text classification. Kaggle dataset, `https://www.kaggle.com/datasets/johnwdata/gibberish-text-classification`, 2019. File `Gibberish.xls`; licence listed as Unknown; accessed 2026-10-11.

A Strategies

Table 5 lists every strategy by family with what it measures and which of the two measured profiles it belongs to; Table 6 lists the seven named profiles.

B Profiles

Table 5: The 32 strategies of pygarble by family. A strategy *fires* when its default configuration scores at least 0.5. Profile: E, member of `english` (the default); F, member of `english_fusion`. Words "in the dictionary" are those in the embedded list of 49,330 English words; checks restricted to non-dictionary words also skip short all-capital acronyms and structured tokens such as URLs and numbers.

Strategy	Profile	What it measures and when it fires
Character statistics		
`vowel_ratio`		Share of vowels in words of three or more letters and the longest consonant run in a word; fires when vowels are under about 7.5% or over about 82% of letters, or a word has six consonants in a row.
`entropy_based`		Blend of low Shannon entropy of the letters (40%) and low mean English bigram log-probability (60%); fires when the blend reaches 0.5, as on repetitive or improbable letter strings.
`consonant_sequence`		Longest run of consonants inside a word, with *y* counted as a vowel and short all-capital acronyms skipped; fires on a run of seven or more.
`letter_frequency`		Chi-squared distance of the letters of non-dictionary words from English letter frequencies, plus rare-letter excess, missing common letters and one dominant letter; fires at a per-letter distance of 2 or two extreme signs.
`vowel_pattern`		Runs of consecutive vowels within words; fires on a run of five or more vowels that is not on a short list of valid English runs such as *ueue*.
`symbol_ratio`		Share of non-space characters that are neither letters nor digits, after collapsing runs of one repeated symbol such as rulers; fires when symbols are more than half of the text.
`letter_position`		Non-dictionary, non-capitalised words that end in a letter English words never end in or start with a pair English words never start with; fires when a quarter of these checks fail across two or more violations or words.
`pronounceability`		English phonotactics of non-dictionary, non-capitalised words of four or more letters; fires on two forbidden consonant clusters at word edges, mostly invalid word-initial clusters, or almost no vowels.
English character models		
`markov_chain`	E	Mean log-probability per letter transition of the non-dictionary words under an English character bigram model; fires when it falls below −3.5.
`bigram_probability`		Share of within-word letter pairs on a curated list of pairs that English essentially never uses; fires when that share reaches a quarter.
`ngram_frequency`		Share of the letter trigrams of non-dictionary words that are on a list of common English trigrams; fires when fewer than 30% are.
`rare_trigram`		Share of within-word letter trigrams on a curated list of combinations that English essentially never uses; fires when that share reaches 15%.
`log_likelihood_ratio`	E, F	Mean log-likelihood ratio per letter pair of all words, English bigram model against uniform letters; fires when the mean falls below −1, so the text fits English clearly worse than random letters.
Word-level checks		
`word_lookup`	F	Share of words of two or more letters that are not in the dictionary, unknown capitalised words counting half; fires when half or more are unknown.
`word_anomaly`	E	Share of words of four or more letters that are non-dictionary and have mean bigram log-probability below −4.6; fires when a quarter of the words are anomalous, so one mashed word in four suffices.
`function_word_density`		Share of English function words such as *the*, *of* and *is*; fires only when ten or more words contain none and the text is not mostly Title Case.
`affix_detection`		Share of words of four or more letters that carry a common English prefix or suffix on a stem with a vowel; fires only on twenty or more such words when fewer than about one in six do.
`word_collocation`		Adjacent word pairs found in a list of common English pairs such as *of the*; fires when twenty or more words, not mostly Title Case, contain no such pair, or fifteen or more have under 2% hits.
`zipf_conformity`		Type-token ratio and share of once-only words in texts of thirty or more words; fires on a flat distribution only when the text also has no function words and mostly non-dictionary words.

Table 5: The 32 strategies of pygarble by family (continued).

Strategy	Profile	What it measures and when it fires
Structure and pattern checks		
`repetition`		Runs of one repeated letter, repeated two- or three-character units, one word dominating the text or a repeating cycle of words, and low character diversity; fires, for example, on a letter repeated five times.
`keyboard_pattern`		Letter trigrams of non-dictionary words that follow keyboard sequences, a shortage of common English trigrams, and a two-letter unit repeated three times inside one word; fires when keyboard trigrams reach 15% or on the repeated unit.
`keyboard_adjacency`	E	Chains of physically adjacent QWERTY keys within words; fires when a word of five or more characters is a straight row walk, or a non-dictionary word has a six-key adjacent chain or six same-row keys with at most one vowel.
`hex_string`		Hexadecimal and encoded data; fires on an MD5 or SHA-256 hash, a base64-like string, a UUID standing alone, a run of sixteen or more hex digits including a letter, or a long token that is mostly hex digits.
`pattern_matching`		Built-in regular expressions (a letter four or more times in a row, five-key keyboard-row walks, five consonants in a row in a non-dictionary word, alternating letter pairs) plus optional user patterns; fires on any of these, while runs of symbols, capitals or digits only add weight.
`local_anomaly`		Severely improbable non-dictionary words inside otherwise ordinary text; fires when one such word has eight or more letters or two fall within any four consecutive words.
Encoding and script checks		
`mojibake`	E	Signatures of text decoded with the wrong encoding; fires on a replacement character U+FFFD, a known sequence such as Ã© or â€™, double encoding, or a dense run of such byte pairs.
`control_characters`	E	Raw control characters other than tab, carriage return and newline, lone surrogates, U+FFFD, and runs of more than eight combining marks; fires on any one of them.
`unicode_script`		Mixing of Unicode scripts; fires on any word of three or more letters that mixes Latin, Cyrillic and Greek letters, as homoglyph spoofing does, or on text that uses more than two scripts.
English-reference window statistics (each fires when its median over windows of up to 127 characters lies beyond the 99th percentile of synthetic English of the same length)		
`cross_parsing`	F	Number of pieces needed to spell the text from the longest substrings of a reference built from frequent English words (Ziv–Merhav cross parsing); invented or mashed text breaks into many short pieces.
`primed_compression`		Compressed size per character when deflate is primed with frequent English words as a preset dictionary; English compresses well against it and invented text does not.
`ngram_rank`		Out-of-place distance between the frequency ranks of the text's one- to three-letter sequences and their ranks in English (Cavnar–Trenkle).
`permutation_test`		How much likelier the text's letter order is under an English bigram model than eight fixed shuffles of the same letters; catches mash and random letters but often misses pronounceable invented words.

Table 6: The seven named profiles, their members and voting rules.

Profile	Members	Voting
`english` (default)	`markov_chain`, `log_likelihood_ratio`, `word_anomaly`, `mojibake`, `keyboard_adjacency`, `control_characters`	any
`english_extended`	the six `english` members, `pattern_matching`, `local_anomaly`, `repetition`	any
`legacy`	`markov_chain`, `log_likelihood_ratio`, `word_anomaly`	any
`corruption`	`mojibake`, `control_characters`	any
`spoofing`	`unicode_script`	any
`llm_output`	`repetition`, `control_characters`, `mojibake`, `local_anomaly`	any
`english_fusion`	`word_lookup`, `log_likelihood_ratio`, `cross_parsing`	Fisher

any: the text is flagged when any applicable member scores 0.5 or more. *Fisher*: each member's score is read as a tail p-value against synthetic English, the p-values are combined by Fisher's method, and the text is flagged at a combined $p \leq 0.001$.