ProgramBench: Can Language Models Rebuild Programs From Scratch?

John Yang[1,3*], **Kilian Lieret**[1*], **Jeffrey Ma**[1,4], **Parth Thakkar**[1], **Dmitrii Pedchenko**[1], **Sten Sootla**[1], **Emily McMilin**[1], **Pengcheng Yin**[2], **Rui Hou**[2], **Gabriel Synnaeve**[1], **Diyi Yang**[3], **Ofir Press**[1]

[1]Meta FAIR, [2]Meta TBD, [3]Stanford University, [4]Harvard University
[*]Equal Contribution

Turning ideas into full software projects from scratch has become a popular use case for language models. Agents are being deployed to seed, maintain, and grow codebases over extended periods with minimal human oversight. Such settings require models to make high-level software architecture decisions. However, existing benchmarks measure focused, limited tasks such as fixing a single bug or developing a single, specified feature. We therefore introduce ProgramBench to measure the ability of software engineering agents to develop software holisitically. In ProgramBench, given only a program and its documentation, agents must architect and implement a codebase that matches the reference executable's behavior. End-to-end behavioral tests are generated via agent-driven fuzzing, enabling evaluation without prescribing implementation structure. Our 200 tasks range from compact CLI tools to widely used software such as `FFmpeg`, `SQLite`, and the `PHP` interpreter. We evaluate 9 LMs and find that none fully resolve any task, with the best model passing 95% of tests on only 3% of tasks. Models favor monolithic, single-file implementations that diverge sharply from human-written code.

Date: May 5, 2026
Correspondence: John Yang at johnby@meta.com, Kilian Lieret at klieret@meta.com
Code: https://github.com/facebookresearch/ProgramBench

Meta

1 Introduction

Language Models (LMs) are increasingly being used to turn ideas expressed in natural language into full-fledged code repositories (Carlini, 2026; Lin, 2026; Replit, 2026). Unlike smaller scope tasks such as function generation (Hendrycks et al., 2021) or GitHub issue resolution (Jimenez et al., 2024), which typically demand understanding a pre-existing codebase well enough to make localized changes, building a functional application from scratch requires models to engage heavily with software design (Jansen and Bosch, 2005).




Figure 1 ProgramBench evaluates models on their ability to write software projects from scratch. Given a software program (e.g., executable) and its documentation, a software engineering agent (SWE-agent) is tasked with producing source code and a build script that reconstructs the original program's behavior.

To understand what this entails, consider how a human programmer approaches the same task. Before a single line is written, she asks herself a series of important questions: What programming language and build system should be used? How should the codebase be organized? What data structures should represent the program's core entities? How should errors be detected and communicated? Such requisite questions, which developers constantly revisit throughout the development lifecycle, lead to pivotal design decisions that shape the codebase far more profoundly than any individual code change. Although we are progressively entrusting LMs to similarly build software from the ground up, the ability of LMs to make such architectural decisions, choose abstractions, and decompose a system into coherent modules has not been studied extensively.

To bridge this gap, we introduce ProgramBench, a benchmark that challenges software engineering (SWE) agents to produce code that recovers the functionality of a software program (e.g., executables, `.dmg`'s, `.pkg`'s). Given a program and documentation, a SWE-agent, defined as an LM equipped with an agent scaffold to interact with a terminal environment (Yang et al., 2024a), must write source code and a compile script that reproduces the original program's behavior. Every software design decision is entirely the model's to make.

We synthesize ProgramBench tasks from open-source GitHub repositories. First, we identify repositories written in compiled languages (e.g., C/C++, Golang, Rust, Java) that build a program. Next, to convert a repository into a task instance, we compile the program, then strip away all source code and tests, leaving only the program and its documentation as the task's starting point.

To evaluate a model's solution, we generate behavioral tests by prompting a SWE-agent to systematically probe the original program with varied inputs and codify the observed input-output behavior into assertions that a candidate reconstruction must satisfy. Crucially, these tests are never revealed to the task worker. Since tests target executable behavior rather than source code, evaluation is entirely implementation agnostic; a model may use different algorithms, abstractions, or even programming languages than the original codebase, and still pass as long as the input-output behavior matches. While any test suite necessarily under-approximates an executable's full specification, we empirically demonstrate that our test generation pipeline creates large suites that reliably capture core functionality.

Using our pipeline, we collect 200 task instances, ranging from compact CLI tools to complex, widely used software including language interpreters (`PHP`, `Lua`, `tinycc`), databases (`DuckDB`, `SQLite`), media and compression utilities (`FFmpeg`, `zstd`, `xz`), and developer tools (`ripgrep`, `fzf`, `jq`). We evaluate 9 language models equipped with `mini-SWE-agent`, a widely adopted coding agent scaffold for open source SWE-agent research. The results resoundingly confirm ProgramBench's difficulty for today's models; no task instance is fully resolved. However, test pass rates are significantly different between models. The best model, Opus 4.7, manages to pass 95% of tests for 3% of task instances. Further analysis reveals that model-written codebases diverge significantly from human-written ones, favoring monolithic file structures with longer functions. Our trajectory analyses showcase how models vary in the length and make up of the way they develop software.

We open source ProgramBench to enable the community to reproduce and build upon our investigations.

2 ProgramBench

This section describes ProgramBench in detail. We first formalize the task (§2.1), then explain how task instances are semi-automatically constructed from open-source repositories (§2.2). Finally, we review benchmark statistics (§2.3) and distinguishing features (§2.4).

2.1 Task Formulation

Given a gold (reference) executable and its usage documentation, a task worker is asked to write source code and a build script that constructs a candidate executable which should reproduce the behavior of the gold executable. The task worker does not have access to the internet and is free to implement the solution in any programming language. The task worker is informed of these conditions via the initial prompt, and no-internet is enforced by running the Docker container without internet.

To evaluate, we run a generated test suite, where each test checks whether the candidate executable exhibits the same observable behavior as the gold executable for a given input (e.g., matching standard output, exit




Figure 2 ProgramBench task collection pipeline. To turn a GitHub repository into an ProgramBench task, we use a SWE-agent to compile an executable, generate behavioral tests, and strip away implementation details. The sourcing workflow only requires a repository to produce an executable or program, making it extensible to many codebases.

codes, or file system side effects). The test suite is never revealed at any point to the task worker. While any test suite checks a finite set of inputs and therefore necessarily under-approximates the gold executable's full specification, ProgramBench's framing makes extending test coverage trivial.

2.2 Benchmark Construction

Next, we discuss our four-stage pipeline for converting open source GitHub repositories into ProgramBench task instances, as visualized in Figure 2. All construction steps use the `mini-SWE-agent`[1] harness with Claude Sonnet 4.5, operating inside a Docker container based on `ubuntu:22.04`.

Identify candidate repositories. We synthesize ProgramBench tasks from open source GitHub repositories. First, we filter for repositories that may produce a standalone executable or program. A strong heuristic is to look for projects written in compiled languages (e.g., C/C++, Golang, Rust).

Construct executable from source. Given a repository, we task a SWE-agent with compiling the gold executable and, if successful, record the commands that reproduce the build in a single build script (Step 1 in Figure 2).

Generate behavioral tests. We use an agent to explore the program, its source code, existing tests, and documentation, and then generate behavioral tests (Step 2 of Figure 2). The test assertions target externally observable effects rather than source-level internals. For example, a test might assert that specific strings appear in stdout or stderr, or that an invocation produces expected files. The agent is also prompted to identify and include in its test suite any existing behavioral tests defined in the repository (*harvesting*).

The agent continuously measures the line coverage of the current test suite and iteratively writes new tests to invoke missing code paths, attempting to achieve full coverage.

Some tests may have missing or trivially true assertions. Therefore, to ensure assertion quality, tests are flagged if they fail the gold binary or trigger our assertion quality linter (Appendix A.3.5), which detects structurally weak assertion patterns such as exit-code-only checks, short substring matches, and disjunctive assertions. The agent is prompted to revise all flagged tests. At the end, any remaining tests that do not pass with the gold binary deterministically or pass a dummy binary are discarded. More details in §A.3.

Prior work has shown that coding benchmarks, such as SWE-bench, have some test suites with one of the following two shortcomings (Chowdhury et al., 2024). First, a task's test suite could be overly stringent, meaning it checks for criteria not apparent from the initial task definition. Second, a task's test suite might not fully check whether a solution actually solves the initially stated task. For the first case, ProgramBench tests assert only on observable behavior of the reference executable, precluding overspecification of source-level internals. A subtler concern is whether tests demand exact reproduction of implementation-dependent output (e.g., floating point precision or rendering discretization). We address this directly: the model has full access to the gold executable at inference time, so any behavior a behavioral test expects is discoverable by running that same command. An audit of all 200 task instances found zero tests that invoke flags or subcommands not surfaced by the executable's documentation, and only 5 instances where implementation-dependent output could plausibly appear, none of which contained such assertions in practice (§A.3.4). For the second case, a finite test suite necessarily under-approximates an executable's full specification (Liu et al., 2023; Le Goues

[1] https://mini-swe-agent.com




Figure 3 Distribution of programming languages across ProgramBench task instances. To solve the task, models may write their solution in any language they choose.

Metric	Median	Min	Max
Code lines	8,635	212	2,701,283
Code files	50	1	5,342
Runtime dependencies	10	0	113
Max directory depth	3	0	13
Tests	770	224	14,645
GitHub stars	2,124	202	79,693
Contributors	22	1	422
Commits	646	13	145,991
Repo age (years)	7.9	0.3	17.8

Table 1 Summary statistics for the 200 ProgramBench task instances, illustrating the diversity of the dataset across codebase scale, dependency complexity, and development history. Top rows cover codebase statistics, while bottom rows quantify community contribution.

et al., 2015). We quantify this risk in §5: our generated suites achieve line coverage broadly comparable to the native test suites shipped by developers in the same repositories.

Build an inference environment. The starting state for each task consists of the gold executable and usage-related documentation. To construct the Docker image for the starting state, we first obtain usage-related documentation removing source code and any implementation details from the repository with a SWE-agent (Step 3 in Figure 2). The compiled executable is then injected into an independent docker image as the only artifact carried over from the build step (Step 1). The reason for copying the executable over, rather than simply rebuilding from source code, is to ensure there are no local build artifacts or dependency caches that could reveal the original program's implementation. The executable is also set to execute-only permissions to prevent reading or reverse engineering of the binary with a tool like `ghidra`[2]. Lastly, we also include test assets that a model cannot reasonably synthesize on its own (e.g., images, domain-specific binary formats). We review inference guidelines thoroughly in §A.2.

2.3 Dataset Statistics

We created 200 task instances from open-source repositories spanning compression, language interpreters, visualization, linting, text processing, and more (Figure 3, Table 1). Tasks range from small CLI tools to large-scale projects such as FFmpeg and the PHP interpreter, and are mostly written in Rust, Go, or C/C++, with one project in Java and one in Haskell. Our evaluation suite totals 248,853 test functions across all instances (median 770 per task); additional test generation analyses and dataset statistics in §A.3 and §A.4.

2.4 Task Features

Open-ended software design. In ProgramBench, models receive only an executable and documentation. Every architectural decision, from choice of language to module decomposition to data structure design, is the model's to make. There is no skeleton, mandated abstractions, or preset file organization. Because evaluation compares executable behavior rather than source code, ProgramBench admits many valid solutions; a model may choose entirely different languages, algorithms, or architecture and still pass, making models' design choices directly comparable across the same task. This is what makes ProgramBench a test of software design, not just implementation alone.

Burden to discover specifications. In ProgramBench, the executable serves as a comprehensive but opaque oracle. Expected behavior is fully encoded, but must be queried to be understood. Importantly, the model is not probing blindly: it has access to the program's documentation and help output, which surface available flags and subcommands (§2.2). In practice, interacting with the executable resembles how a developer

[2] https://github.com/nationalsecurityagency/ghidra

queries a product manager: "when a user runs `X` with flag `-y`, what should the output be?" The model must decide which questions to ask and in what order. This setting tests a model's ability to infer behavior through systematic, hypothesis-driven exploration, mirroring challenges developers routinely face when probing partially documented APIs or onboarding to unfamiliar systems by observing behavior in the absence of complete specifications.

Simple collection criteria. Our collection pipeline requires only that a repository produce a standalone executable. No existing test suite, language-specific AST tooling, or ecosystem-reliant test frameworks are needed. The benchmark is therefore straightforward to extend with new instances over time, a valuable property for sustaining benchmark relevance (Deng et al., 2025; Zhang et al., 2025). The same pipeline can also generate training data, similar to how prior benchmark collection schemas have been repurposed for training (Badertdinov et al., 2025; Pham et al., 2025; Yang et al., 2025).

3 Experiments

Models. We evaluate 9 recent language models that are regarded as strong coding models based on rank on existing benchmarks, including SWE-bench and Terminal-bench. These include Claude Opus 4.7, Claude Opus 4.6, Claude Sonnet 4.6, Claude Haiku 4.5, Gemini 3.1 Pro, Gemini 3 Flash, GPT 5.4, GPT 5.4 mini, and GPT 5 mini. All models use vendor-default hyperparameters.

Agent scaffold. We use `mini-SWE-agent` because it is both widely adopted as a baseline by other benchmarks (SWE-bench Verified, Multilingual[2], Terminal-bench[3]), and deliberately minimal in its scaffolding, reducing confounds between model capability and harness design. Each model runs inside a container with 20 CPUs and 60GB RAM, with a limit of 1,000 steps and 6 hours per run; full configuration details are in §B.1.

Metrics. We primarily report **% Resolved**, which refers to the percentage of task instances where the model's codebase passes *all* associated test cases and is not flagged as cheating. Due to the challenging nature of this benchmark, we also report **% Tests Passed** per task instance, which captures partial progress even when no task is fully resolved. However, we note that this softer metric is only meaningful for relative comparisons between models; even a single failed test can imply a fundamental flaw in a model's solution. As discussed in §2.2, % Tests Passed also does not reliably correlate with percentage of working functionality.

4 Results

Our main results are shown in Table 2. ProgramBench is extremely challenging; across the board, no model fully solves any single ProgramBench task instance. That said, from Figure 4, we find that models make meaningful progress on a significant proportion of tasks, with Claude Opus 4.7 achieving the highest proportion of solutions that pass 95+% of tests, at 3.0%.

Task difficulty is largely model-agnostic. As shown in Figure 5, models consistently score higher on simpler CLI utilities like `nnn`, `fzf`, and `gron`, while complex systems such as `FFmpeg`, `php-src`, `typst`, and `ast-grep` remain out of reach. These trends suggest that ProgramBench captures intrinsic variation in task difficulty that is independent of model choice. The rank order of tasks by pass rate is broadly consistent across models.

4.1 Ablations

We review two alternative evaluation settings to investigate the impact the availability of certain tools and resources has on solutions and cheating rates.

Different-language constraint. In this setting, we force models to implement their solutions in a different programming language from the reference repository. In theory, this measure should obviate models' ability to simply regurgitate reference code from their pre-training corpora, requiring them to demonstrate deep understanding of program behavior rather than surface-level recall.

[3] https://tbench.ai

Model	% Res.	% Almost	Calls	$
Claude Opus 4.7	0.0%	3.0%	93	3.81
Claude Opus 4.6	0.0%	2.5%	260	11.38
Claude Sonnet 4.6	0.0%	1.6%	475	27.09
Claude Haiku 4.5	0.0%	0.0%	124	0.80
Gemini 3.1 Pro	0.0%	0.0%	94	1.51
Gemini 3 Flash	0.0%	0.0%	89	0.33
GPT 5.4	0.0%	0.0%	16	0.33
GPT 5.4 mini	0.0%	0.0%	18	0.04
GPT 5 mini	0.0%	0.0%	15	0.03

Table 2 Main results on ProgramBench. % Resolved is the primary metric: the fraction of 200 tasks where all tests pass. % Almost relaxes this to instances with ≥95% of tests passing. We also report average API calls and cost per task.




Figure 4 Cumulative distribution of test pass rates across models on ProgramBench.




Figure 5 Per-task pass rates for the 40 most-starred repositories in ProgramBench, grouped by reference language and sorted by average model score within each group. Each cell shows one model's test pass rate on one task.

Unexpectedly, the constraint does not uniformly decrease scores. As shown in Figure 6, while Claude Opus 4.7 and 4.6 see meaningful drops, all three GPT models surprisingly each improve by 4.2%. Remaining models are roughly unchanged. Under this constraint, we observe a noticeable shift towards Python as the implementation language of choice, from 36% of main result runs (Figure 8) to an outstanding majority of 51% runs in this setting (Figure 27). The mixed results suggest that models may not have a reliable sense of which implementation language best suits a given task and their own capabilities; forcing a language switch can inadvertently steer a model toward a language it has more success with.

Open internet with cheating detection. We repeat evaluation for one model per provider family with a key distinction: models are given unrestricted internet access. Note that in the system prompt, we still explicitly tell models that cheating is disallowed. To detect cheating, we run an LM-as-a-judge pipeline where 9 judges independently inspect a trajectory for whether the model looked up source code or submitted a wrapper around the reference executable as a solution; a task is flagged if a majority identify a violation. With this setting, our goals are to understand, first, how often models cheat, and second, how reliable our cheating detection mechanisms are.

As shown in Table 3, cheating is widespread: 20–36% of tasks are flagged for the three stronger models, with source code lookup accounting for the vast majority of violations. At the same time, judges disagree on 40–57% of tasks for these models, indicating that even with 9 judges across three model families, reliable detection remains elusive. The combination of high cheating rates and unreliable detection gives us confidence that blocking internet access entirely is the appropriate default for ProgramBench. We document additional details about the evolution of our mitigation efforts in §A.2.




Figure 6 Effect of requiring a different implementation language. Filled circles show default scores; open circles show scores under the constraint.

Model	% Cheat
Claude Sonnet 4.6	36%
Claude Opus 4.6	21%
Gemini 3 Flash	20%
GPT 5 mini	1%

Table 3 Cheating rates when models are given internet access, as flagged by majority vote of 9 LM judges. Source code lookup is the dominant strategy, accounting for 79–95% of flagged runs.




Figure 7 Line coverage of our generated test suites versus project size (source lines excluding dependencies) for a sample of 100 tasks.

Repository	Gen.	Native	Δ
ariga/atlas	54.15	28.25	+25.90
johnkerl/miller	85.90	72.18	+13.72
stacked-git/stgit	85.54	82.43	+3.11
rvben/rumdl	68.23	66.80	+1.43
facebook/zstd	76.32	75.10	+1.22
jqlang/jq	82.15	81.69	+0.46
php/php-src	61.60	64.60	−3.00
stranger6667/jsonschema	72.63	78.79	−6.16
doxygen/doxygen	13.00	24.80	−11.80
ffmpeg/ffmpeg	46.70	58.97	−12.27
jesseduffield/lazygit	62.23	74.60	−12.37
typst/typst	65.68	85.12	−19.44
Median	**66.96**	**73.39**	**−1.27**

Table 4 Line coverage (%) for generated vs. native behavioral suites across 12 repositories that maintain an identifiable integration or end-to-end test suite, sorted by Δ.

5 Analysis

We study test generation artifacts and evaluation outcomes to better understand the utility of our generated tests and gauge how performance varies across different tasks and models.

5.1 Test Suite Comparisons

We assess how effective our generated test suites are by measuring two complementary properties: how much of each program they exercise (coverage), and whether they actually reject incorrect implementations (assertion strength). Full details on how each analysis was carried out are included in §A.3.2.

Generated test suites achieve comparable line coverage to developer-written test suites. While most ProgramBench repositories lack a dedicated end-to-end test suite, many maintain unit and integration tests, making them a natural baseline. We instrument each task's executable with coverage tracking and measure the fraction of source lines exercised by our generated suite versus the project's native suite across 100 repositories (§A.3.2).

Our generated suites average 79.7% line coverage with a median of 86.2% (Figure 7), compared to native suites that average 56.8% with a median of 64.3%. This places our generated suites comfortably within, and often above, the coverage range of typical developer-written tests.

Coverage remains comparable even against dedicated behavioral test suites. The comparison above includes many unit test suites, which can exercise internal code paths that black-box tests structurally cannot reach. To




Figure 8 Confusion matrix of reference vs. model language. Each cell shows the percentage (and count) of runs per reference language. Models generally prefer, in descending order, Python, Go, Rust, Shell, C/C++. Model-specific breakdowns are visualized in Figure 28.




Figure 9 Reference vs. model code lines on a log–log scale. The $y{=}x$ diagonal indicates parity. Only solutions passing $\geq$75% of tests are shown.

	Opus 4.7		Sonnet 4.6		Gemini 3.1 Pro		GPT 5.4	
	Ref	Model	Ref	Model	Ref	Model	Ref	Model
Function count	133	39 (0.29×)	182	44 (0.24×)	63	10 (0.16×)	88	9 (0.10×)
Avg. length (lines)	25	29 (1.16×)	24	35 (1.46×)	26	42 (1.62×)	24	26 (1.08×)

Table 5 Median function count and average function length of solutions for four models. Ratios compared to original source code in gray. Only solutions passing $\geq$75% of tests are included.

provide a stricter baseline, we identify twelve repositories that maintain a dedicated behavioral or integration test suite (e.g., FFmpeg's FATE suite, PHP's regression harness, jq's regression tests) and compare against those suites directly (Table 4).

Generated suites average 62.16% line coverage versus 66.11% for native behavioral suites, meeting or exceeding native coverage on 6 of 12 projects and falling within 10 percentage points on all but two.

Assertion quality enforcement eliminates trivially passable tests. High coverage alone does not guarantee a useful test suite: a test that only asserts the process exited cleanly provides negligible signal, since any implementation that runs without crashing will pass it. We quantify assertion strength using *dummy pass rate*, the fraction of a task's tests that pass a trivially incorrect implementation. During test generation, our assertion quality linter flags structurally weak patterns such as exit-code-only checks and overly short substring matches (Appendix A.3.5), and the agent is prompted to revise them.

Tests generated with our linter exhibit a mean dummy pass rate of 3.7%, compared to 18.5% without quality enforcement, a 5× reduction. After generation, we eliminate all tests that trivially pass when run with a dummy program, affecting 24 tasks in total.

5.2 Model-Generated Codebases

We highlight differences between model-generated solutions and the original human-written implementations.

Models match the reference language half the time. As mentioned in §2.1, models are free to implement their solutions in any language. Figure 8 reveals that models match the reference language in exactly 50% of runs. Python is the most common choice overall at 36% of all 1,800 model runs, followed by Rust (25%), Go (20%), C/C++ (13%), and Shell (6%). Go projects are reimplemented in the same language most often (70%), while Rust (44%) and C/C++ (46%) projects are frequently rewritten in a different language. Model-specific




Figure 10 Distribution of action types across agent turns for four representative models. Each bar shows the total number of actions of each type at a given turn index, aggregated across all task instances. The natural decay in bar height reflects trajectories of varying length ending at different points.

breakdowns are visualized in Figure 28.

We next draw insights from comparing models' codebases against the reference solutions. To ensure comparisons are between codebases that produce functionally similar executables, we only compare against model solutions that pass 75+% of tests. This yields 207 runs across 88 tasks and 9 models.

Model solutions are significantly shorter. Even among high-scoring solutions, models produce substantially less code than the references: a median of 1,173 lines compared to 3,068 in the originals (Figure 9). Most runs (85%) fall below parity. Just 15% of codebases are larger than the reference, typically for smaller tasks. Models also create far fewer files (median 3 versus 15), with 60% of solutions consisting of 1–3 code files.

Models prefer monolithic files over modular directory structures. We measure the directory structure of model-generated codebases using maximum directory depth, defined as the deepest nesting level of any file (e.g., `src/utils/parser.go` has depth 3). The majority of runs (67%) produce a strictly shallower maximum depth than the reference (median depth 1 vs. 2), while only 2% are deeper. Rather than mirroring the modular decomposition of the original project, models strongly prefer placing most or all code in a single file or a handful of files at the root level.

Models write fewer, longer functions. Table 5 compares function count and average function length between model and reference codebases for four representative models. All models write far fewer functions than the reference (10–29% as many), but compensate with longer functions: Claude Sonnet 4.6 writes functions that are 1.46× longer on average, while Gemini 3.1 Pro reaches 1.62×. GPT 5.4 writes functions that are 1.08× longer while still producing very few of them (10% of the reference count).

5.3 Agent Trajectories

We analyze agent trajectories to understand how models approach the task and where they struggle.

We classify actions into one of six types: `read` (file inspection, searches, directory listing), `write` (file creation, editing), `probe` (any invocation or inspection of the reference executable), `git` (version control), `execute` (compilation, non-probe program execution), and `other`. To classify, we perform keyword matching on the raw command string, checking in priority order to distinguish between different usage techniques of bash commands. For instance, `cat<<'EOF'>main.c` is classified as `write`, distinct from `cat main.c` to `read`. Figure 10 shows the action type distributions per turn across all inference runs for four representative models.

Turn counts vary heavily by model. As reflected by Figure 10, Claude Sonnet 4.6 uses a median of 868 commands per task, with its longest trajectory reaching 1,978 turns. GPT 5.4 sits at the other extreme with a median of just 17 commands, while Gemini 3.1 Pro and Opus 4.7 fall in between at 92 and 157 respectively.




Figure 11 Codebase growth over normalized trajectory progress for four models. Each thin line is an individual trajectory; the bold line shows the median and the shaded region the interquartile range. The y-axis is capped at the 95th percentile of final codebase sizes.




Figure 12 Percentage of the final codebase produced by the single largest edit, per model. For instance, GPT 5.4 writes a median of 96% of its code in one turn.

Model	Create	Modify	Delete
Claude Opus 4.7	7.7	3.3	0.2
Claude Sonnet 4.6	11.3	18.3	1.5
Gemini 3.1 Pro	61.2	10.1	9.4
GPT 5.4	5.0	1.2	0.3

Table 6 Mean file mutations per trajectory. Create, modify, and delete counts reflect how frequently models revisit and restructure their codebases. Counts are averaged across all tasks and models.

Models rarely exceed the turn or time budget. Across all nine models (1,800 runs), the agent voluntarily submits its solution in 98.1% of trajectories. Just 1.9% exhaust the 6 hour wall clock time limit, and just a single run reaches the 1,000 turn cap. Timeouts are concentrated in Opus 4.6 (29/200) and Sonnet 4.6 (5/200). All other models complete all 200 tasks within the time and step budget. This finding suggests that the limits do not artificially constrain model performance.

Writing dominates most models' action budgets. Opus 4.7, Sonnet 4.6, Gemini 3.1 Pro, and GPT 5.4 all devote the largest share of turns to writing code (48.7%, 37.5%, 40.7%, and 40.2% respectively). Probing the reference executable is the second-largest category for all four, ranging from 22.6% (Opus 4.7) to 34.1% (Gemini 3.1 Pro). Read actions account for 13–16% across all representative models.

Probing trends differently across models. GPT 5.4's actions are concentrated almost entirely within the first 30 turns. Claude models maintain a steadier mix of probing and writing throughout their trajectories, interleaving exploration with implementation rather than treating them as distinct phases.

Codebase growth varies between gradual iteration and single-shot generation. To study how a SWE-agent's codebase grows across the course of a trajectory, for each trajectory, we replay the subset of commands that modify files (e.g., `touch`, `sed`, `rm`) and snapshot the file system after each turn. This sequence of snapshots allows us to recover a ground-truth timeline of how files are updated at different points in a trajectory.

Figure 11 shows all trend lines of a codebase's total line count with respect to trajectory progress for each model across all 200 instances. Claude Sonnet 4.6 and Gemini 3.1 Pro tend to ramp up steadily, whereas GPT 5.4 produces nearly all code in a single turn early on in the trajectory. To highlight this distinction further, Figure 12 shows that the median fraction of the final codebase written in a single turn ranges from 44% (Sonnet 4.6) to 100% (GPT 5.4), with Opus 4.7 at 67% and Gemini 3.1 Pro at 53%. As reflected in Table 6,

we also found that GPT 5.4 averages just 1.2 file modifications per trajectory, with 39.5% of trajectories performing zero modifications to any existing files. In contrast, Sonnet 4.6 averages 18.3 modifications and Gemini 3.1 Pro averages 10.1, consistent with the gradual growth visible in their curves. All together, the trends suggest that for some models, development is effectively a single-shot generation step, rather than an iterative write-compile-debug cycle.

6 Related Work

Code from scratch. Several prior works have presented variations of evaluating coding systems on 0 to 1 code generation. Commit0, an early work in this lineage, converts 54 Python libraries into task instances by erasing the existing implementations for all functions and classes (Zhao et al., 2024). The model is then asked to fill in the blanks, and performance is quantified as the percentage of the repository's original test suite that passed. Later works follow this paradigm, with differences primarily around how repository specifications are communicated to the model (Li et al., 2024b; Liu et al., 2025). DevBench uses product requirement documents (PRDs) and UML diagrams (Li et al., 2024a), while NL2Repo-bench conveys expected structure via natural language, shifting the burden of creating folders and files onto the agent (Ding et al., 2026). A key commonality is that LMs are asked to fill in a skeleton of pre-defined method headers and classes. In this way, models are never actually tested on their software design capabilities, such as what abstractions to introduce, how to decompose functionality across modules, or what communication protocols to define. By evaluating against executables rather than source code, ProgramBench eliminates the need to prescribe structure with natural language or make expected behavior explicit as programmatic definitions. As discussed in §2, our formulation also yields simpler collection criteria, broader language coverage, and novel reasoning demands.

A few prior and concurrent works have included small-scale case studies and a handful of task instances that touch on program recreation (Merrill et al., 2026; Chu et al., 2026; Adamczewski et al., 2026). These works validate the direction but rely on hand-crafted instances and do not address systematic benchmark construction or scaling; ProgramBench provides both. A related but distinct line of work trains models to decompile binaries back into source code (Tan et al., 2024). Decompilation aims to recover the original implementation; ProgramBench instead evaluates behavioral equivalence, permitting any implementation that reproduces the same input-output behavior.

Issue resolution. SWE-bench (Jimenez et al., 2024) and its variants (Yang et al., 2024b, 2025; Deng et al., 2025; Rashid et al., 2025; Zan et al., 2025; Zhang et al., 2025; Thai et al., 2026) have become popular coding benchmarks. Extracted from GitHub issue-pull request pairs, SWE-bench tasks evaluate models on their ability to address bug fixes or feature requests within an existing codebase. These evaluations are complementary to ProgramBench, which instead focuses on building a codebase from the ground up.

Automatic environment setup. A few works have examined the task of automatically setting up a development environment for a given GitHub repository (Bogin et al., 2024; Eliseeva et al., 2025; Hu et al., 2025). ProgramBench does not evaluate environment setup in isolation, but it arises as a practical prerequisite: models must develop dependencies and configure build tools to produce a working solution. No specific toolchain is prescribed; models can use an entirely distinct line of languages and libraries.

Performance optimization. Alongside measuring correctness, a relevant line of works examines algorithmic (Du et al., 2024; Liu et al., 2024; Waghjale et al., 2024; Huang et al., 2025; Press et al., 2025) and machine-dependent (He et al., 2025; Ma et al., 2025; Ouyang et al., 2025; Shetty et al., 2025) runtime optimization as a measure of how well AI systems can speed up software systems while maintaining functional correctness. The most salient distinction between those works and ProgramBench is that while optimization benchmarks assume a known specification that a model should preserve (while optimizing speed), ProgramBench requires models to recover the specification itself from observed behavior. In this respect, ProgramBench shares motivation with inductive program synthesis benchmarks that require inferring behavior from input-output examples (Wei et al., 2025), but operates at the scale of full software projects, not individual functions.

7 Discussion

Limitations. ProgramBench relies on a finite set of behavioral tests, which under-approximates each executable's full specification. Evaluation therefore is a "lower bound" on correctness: solutions that fail are definitively incorrect, while those that pass may still diverge from the original on untested inputs. ProgramBench tests also currently focus exclusively on input-output equivalence. Non-functional properties like execution speed, memory usage, or disk footprint are not captured. Therefore, it is possible a model reproduces behavior with an implementation orders of magnitude slower or more resource intensive than the original. Developing richer test generation strategies to improve coverage and incorporate system constraints is a promising direction.

Future work. Several technical reports and blogs have suggested the effectiveness of applying multiple SWE-agents towards long horizon coding tasks (Lin, 2026; Carlini, 2026; Geng and Neubig, 2026; Mishra-Sharma, 2026). ProgramBench can serve as a testbed for such works. Our work uses a single SWE-agent as the baseline; this design reflects prior benchmark evidence, notably SWE-bench, where well-tuned single-agent systems have performed competitively, and multi-agent variants have not consistently shown clear advantages. We are excited to use ProgramBench to delineate the benefits of multi-agent approaches. Similarly, ProgramBench could further exploration into human-centered coding agents, where a developer, given the executable, iteratively guides the agent through design decisions (Liu et al., 2025; Baumann et al., 2026; Wang et al., 2026).

Conclusion. We introduce ProgramBench, a benchmark for measuring the ability of software engineering agents to develop, from scratch, programs that match a given executable's behavior. Existing models struggle substantially, and none fully resolve any task. However, via fine-grained metrics, we find that models achieve meaningful partial progress, with stark differences in how models expend turns and the final form of their codebases. Our analyses reveal meaningful gaps in models' decision making in architecting, developing and testing software. We hope that ProgramBench could serve as a testbed for efforts focused on end-to-end autonomous software development.

Acknowledgments

We would like to thank Jordi Armengol-Estape, Quentin Carbonneaux, Jannik Kossen, Michel Meyer, Shengjia Zhao, Yang Song, Rob Fergus, Jiayi Pan, Ori Yoran, and Shuyan Zhou for their valuable discussions and infrastructure assistance.

References

Tom Adamczewski, David Rein, David Owen, and Florian Brand. Mirrorcode: Evidence AI can already do some weeks-long coding tasks. https://epoch.ai/blog/mirrorcode-preliminary-results, 2026. Epoch AI blog post.

Ibragim Badertdinov, Alexander Golubev, Maksim Nekrashevich, Anton Shevtsov, Simon Karasik, Andrei Andriushchenko, Maria Trofimova, Daria Litvintseva, and Boris Yangel. Swe-rebench: An automated pipeline for task collection and decontaminated evaluation of software engineering agents. *arXiv preprint arXiv:2505.20411*, 2025.

Joachim Baumann, Vishakh Padmakumar, Xiang Li, John Yang, Diyi Yang, and Sanmi Koyejo. Swe-chat: Coding agent interactions from real users in the wild, 2026. https://arxiv.org/abs/2604.20779.

Ben Bogin, Kejuan Yang, Shashank Gupta, Kyle Richardson, Erin Bransom, Peter Clark, Ashish Sabharwal, and Tushar Khot. Super: Evaluating agents on setting up and executing tasks from research repositories. *arXiv preprint arXiv:2409.07440*, 2024.

Nicholas Carlini. Building a c compiler with a team of parallel claudes, February 2026. https://www.anthropic.com/engineering/building-c-compiler. Accessed: 2026-02-27.

Neil Chowdhury, James Aung, Chan Jun Shern, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, et al. Introducing swe-bench verified. *arXiv preprint arXiv:2407.01489*, 2024.

Evan Chu, Rajan Agarwal, Abishek Thangamuthu, Brendan Graham, Justus Mattern, Freeman Jiang, Paul Cento, Swarnim Jain, Mersad Abbasi, Mohammad Hossein Rezaei, George Wang, Alex Zhang, Simon Guo, Karina Nguyen, Arash Bidgoli, Aditya Dalmia, Apoorv Dankar, Ashrut Vaddela, Calvin Chen, Keshav Kumar, Kushagra Vaish, Navid Pour, Rishyanth Kondra, Sagar Badiyani, Sidharth Giri, Snagnik Das, Soham Gaikwad, Syed Shah, Vagish Dilawari, and Vishal Agarwal. Frontierswe. *Proximal Blog*, 2026. https://frontierswe.com/blog.

Xiang Deng, Jeff Da, Edwin Pan, Yannis Yiming He, Charles Ide, Kanak Garg, Niklas Lauffer, Andrew Park, Nitin Pasari, Chetan Rane, Karmini Sampath, Maya Krishnan, Srivatsa Kundurthy, Sean Hendryx, Zifan Wang, Vijay Bharadwaj, Jeff Holm, Raja Aluri, Chen Bo Calvin Zhang, Noah Jacobson, Bing Liu, and Brad Kenstler. Swe-bench pro: Can ai agents solve long-horizon software engineering tasks?, 2025. https://arxiv.org/abs/2509.16941.

Jingzhe Ding, Shengda Long, Changxin Pu, Huan Zhou, Hongwan Gao, Xiang Gao, Chao He, Yue Hou, Fei Hu, Zhaojian Li, Weiran Shi, Zaiyuan Wang, Daoguang Zan, Chenchen Zhang, Xiaoxu Zhang, Qizhi Chen, Xianfu Cheng, Bo Deng, Qingshui Gu, Kai Hua, Juntao Lin, Pai Liu, Mingchen Li, Xuanguang Pan, Zifan Peng, Yujia Qin, Yong Shan, Zhewen Tan, Weihao Xie, Zihan Wang, Yishuo Yuan, Jiayu Zhang, Enduo Zhao, Yunfei Zhao, He Zhu, Liya Zhu, Chenyang Zou, Ming Ding, Jianpeng Jiao, Jiaheng Liu, Minghao Liu, Qian Liu, Chongyang Tao, Jian Yang, Tong Yang, Zhaoxiang Zhang, Xinjie Chen, Wenhao Huang, and Ge Zhang. Nl2repo-bench: Towards long-horizon repository generation evaluation of coding agents, 2026. https://arxiv.org/abs/2512.12730.

Mingzhe Du, Anh Tuan Luu, Bin Ji, Qian Liu, and See-Kiong Ng. Mercury: A code efficiency benchmark for code large language models, 2024. https://arxiv.org/abs/2402.07844.

Aleksandra Eliseeva, Alexander Kovrigin, Ilia Kholkin, Egor Bogomolov, and Yaroslav Zharov. Envbench: A benchmark for automated environment setup. *arXiv preprint arXiv:2503.14443*, 2025.

Jiayi Geng and Graham Neubig. Effective strategies for asynchronous software engineering agents, 2026. https://arxiv.org/abs/2603.21489.

Xinyi He, Qian Liu, Mingzhe Du, Lin Yan, Zhijie Fan, Yiming Huang, Zejian Yuan, and Zejun Ma. Swe-perf: Can language models optimize code performance on real-world repositories?, 2025. https://arxiv.org/abs/2507.12415.

Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and Jacob Steinhardt. Measuring coding challenge competence with apps, 2021. https://arxiv.org/abs/2105.09938.

Ruida Hu, Chao Peng, Xinchen Wang, Junjielong Xu, and Cuiyun Gao. Repo2run: Automated building executable environment for code repository at scale. *arXiv preprint arXiv:2502.13681*, 2025.

Dong Huang, Yuhao Qing, Weiyi Shang, Heming Cui, and Jie M. Zhang. Effibench: Benchmarking the efficiency of automatically generated code, 2025. https://arxiv.org/abs/2402.02037.

Anton Jansen and Jan Bosch. Software architecture as a set of architectural design decisions. In *5th Working IEEE/IFIP Conference on Software Architecture (WICSA'05)*, pages 109–120. IEEE, 2005.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. Swe-bench: Can language models resolve real-world github issues?, 2024. https://arxiv.org/abs/2310.06770.

Claire Le Goues, Neal Holtschulte, Edward K. Smith, Yuriy Brun, Premkumar Devanbu, Stephanie Forrest, and Westley Weimer. The manybugs and introclass benchmarks for automated repair of c programs. *IEEE Trans. Softw. Eng.*, 41(12):1236–1256, December 2015. ISSN 0098-5589. doi: 10.1109/TSE.2015.2454513. https://doi.org/10.1109/TSE.2015.2454513.

Bowen Li, Wenhan Wu, Ziwei Tang, Lin Shi, John Yang, Jinyang Li, Shunyu Yao, Chen Qian, Binyuan Hui, Qicheng Zhang, et al. Devbench: A comprehensive benchmark for software development. *CoRR*, 2024a.

Jia Li, Ge Li, Yunfei Zhao, Yongmin Li, Huanyu Liu, Hao Zhu, Lecheng Wang, Kaibo Liu, Zheng Fang, Lanshen Wang, Jiazheng Ding, Xuanming Zhang, Yuqi Zhu, Yihong Dong, Zhi Jin, Binhua Li, Fei Huang, and Yongbin Li. Deveval: A manually-annotated code generation benchmark aligned with real-world code repositories, 2024b. https://arxiv.org/abs/2405.19856.

Wilson Lin. Scaling long-running autonomous coding. https://cursor.com/blog/scaling-agents, Jan 2026. Blog post on scaling multiple autonomous coding agents for extended projects.

Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation, 2023. https://arxiv.org/abs/2305.01210.

Jiawei Liu, Songrun Xie, Junhao Wang, Yuxiang Wei, Yifeng Ding, and Lingming Zhang. Evaluating language models for efficient code generation, 2024. https://arxiv.org/abs/2408.06450.

Kaiyuan Liu, Youcheng Pan, Yang Xiang, Daojing He, Jing Li, Yexing Du, and Tianrun Gao. Projecteval: A benchmark for programming agents automated evaluation on project-level code generation, 2025. https://arxiv.org/abs/2503.07010.

Jeffrey Jian Ma, Milad Hashemi, Amir Yazdanbakhsh, Kevin Swersky, Ofir Press, Enhui Li, Vijay Janapa Reddi, and Parthasarathy Ranganathan. Swe-fficiency: Can language models optimize real-world repositories on real workloads?, 2025. https://arxiv.org/abs/2511.06090.

Mike A Merrill, Alexander G Shaw, Nicholas Carlini, Boxuan Li, Harsh Raj, Ivan Bercovich, Lin Shi, Jeong Yeon Shin, Thomas Walshe, E Kelly Buchanan, et al. Terminal-bench: Benchmarking agents on hard, realistic tasks in command line interfaces. *arXiv preprint arXiv:2601.11868*, 2026.

Siddharth Mishra-Sharma. Long-running Claude for scientific computing. https://www.anthropic.com/research/long-running-Claude, March 2026. Accessed: 2026-03-24.

Anne Ouyang, Simon Guo, Simran Arora, Alex L. Zhang, William Hu, Christopher Ré, and Azalia Mirhoseini. Kernelbench: Can llms write efficient gpu kernels?, 2025. https://arxiv.org/abs/2502.10517.

Minh VT Pham, Huy N Phan, Hoang N Phan, Cuong Le Chi, Tien N Nguyen, and Nghi DQ Bui. Swe-synth: Synthesizing verifiable bug-fix data to enable large language models in resolving real-world bugs. *arXiv preprint arXiv:2504.14757*, 2025.

Ori Press, Brandon Amos, Haoyu Zhao, Yikai Wu, Samuel K. Ainsworth, Dominik Krupke, Patrick Kidger, Touqir Sajed, Bartolomeo Stellato, Jisun Park, Nathanael Bosch, Eli Meril, Albert Steppi, Arman Zharmagambetov, Fangzhao Zhang, David Perez-Pineiro, Alberto Mercurio, Ni Zhan, Talor Abramovich, Kilian Lieret, Hanlin Zhang, Shirley Huang, Matthias Bethge, and Ofir Press. Algotune: Can language models speed up general-purpose numerical programs?, 2025. https://arxiv.org/abs/2507.15887.

Muhammad Shihab Rashid, Christian Bock, Yuan Zhuang, Alexander Buchholz, Tim Esler, Simon Valentin, Luca Franceschi, Martin Wistuba, Prabhu Teja Sivaprasad, Woo Jung Kim, et al. Swe-polybench: A multi-language benchmark for repository level evaluation of coding agents. *arXiv preprint arXiv:2504.08703*, 2025.

Replit. Replit. https://replit.com/, 2026. Cloud-based development environment and AI-assisted coding platform.

Manish Shetty, Naman Jain, Jinjian Liu, Vijay Kethanaboyina, Koushik Sen, and Ion Stoica. Gso: Challenging software optimization tasks for evaluating swe-agents, 2025. https://arxiv.org/abs/2505.23671.

Hanzhuo Tan, Qi Luo, Jing Li, and Yuqun Zhang. Llm4decompile: Decompiling binary code with large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 3473–3487, 2024.

Minh V. T. Thai, Tue Le, Dung Nguyen Manh, Huy Phan Nhat, and Nghi D. Q. Bui. Swe-evo: Benchmarking coding agents in long-horizon software evolution scenarios, 2026. https://arxiv.org/abs/2512.18470.

Alan Mathison Turing et al. On computable numbers, with an application to the entscheidungsproblem. *J. of Math*, 58(345-363):5, 1936.

Siddhant Waghjale, Vishruth Veerendranath, Zora Zhiruo Wang, and Daniel Fried. Ecco: Can we improve model-generated code efficiency without sacrificing functional correctness?, 2024. https://arxiv.org/abs/2407.14044.

Zora Zhiruo Wang, John Yang, Kilian Lieret, Alexa Tartaglini, Valerie Chen, Yuxiang Wei, Zijian Wang Lingming Zhang, Karthik Narasimhan, Ludwig Schmidt, Graham Neubig, et al. Position: Humans are missing from ai coding agent research, 2026.

Anjiang Wei, Tarun Suresh, Jiannan Cao, Naveen Kannan, Yuheng Wu, Kai Yan, Thiago SFX Teixeira, Ke Wang, and Alex Aiken. Codearc: Benchmarking reasoning capabilities of llm agents for inductive program synthesis. *arXiv preprint arXiv:2503.23145*, 2025.

John Yang, Carlos E. Jimenez, Alexander Wettig, Kilian Lieret, Shunyu Yao, Karthik Narasimhan, and Ofir Press. Swe-agent: Agent-computer interfaces enable automated software engineering, 2024a. https://arxiv.org/abs/2405.15793.

John Yang, Carlos E. Jimenez, Alex L. Zhang, Kilian Lieret, Joyce Yang, Xindi Wu, Ori Press, Niklas Muennighoff, Gabriel Synnaeve, Karthik R. Narasimhan, Diyi Yang, Sida I. Wang, and Ofir Press. Swe-bench multimodal: Do ai systems generalize to visual software domains?, 2024b. https://arxiv.org/abs/2410.03859.

John Yang, Kilian Lieret, Carlos E. Jimenez, Alexander Wettig, Kabir Khandpur, Yanzhe Zhang, Binyuan Hui, Ofir Press, Ludwig Schmidt, and Diyi Yang. Swe-smith: Scaling data for software engineering agents, 2025. https://arxiv.org/abs/2504.21798.

Daoguang Zan, Zhirong Huang, Wei Liu, Hanwu Chen, Linhao Zhang, Shulin Xin, Lu Chen, Qi Liu, Xiaojian Zhong, Aoyan Li, Siyao Liu, Yongsheng Xiao, Liangqiang Chen, Yuyu Zhang, Jing Su, Tianyu Liu, Rui Long, Kai Shen, and Liang Xiang. Multi-swe-bench: A multilingual benchmark for issue resolving, 2025. https://arxiv.org/abs/2504.02605.

Linghao Zhang, Shilin He, Chaoyun Zhang, Yu Kang, Bowen Li, Chengxing Xie, Junhao Wang, Maoquan Wang, Yufan Huang, Shengyu Fu, Elsie Nallipogu, Qingwei Lin, Yingnong Dang, Saravan Rajmohan, and Dongmei Zhang. Swe-bench goes live!, 2025. https://arxiv.org/abs/2505.23419.

Wenting Zhao, Nan Jiang, Celine Lee, Justin T Chiu, Claire Cardie, Matthias Gallé, and Alexander M Rush. Commit0: Library generation from scratch, 2024. https://arxiv.org/abs/2412.01769.

Appendix

A Benchmark

In this section, we provide additional details around the collection and evaluation procedures for ProgramBench.

A.1 Task Collection Procedure

The description provided in §2.2 captures the lion's share of details regarding how to construct ProgramBench style task instances. Beyond this, we provide the following miscellaneous details:

- For the `mini-SWE-agent` we deploy to perform executable construction, tests generation, and implementation detail removal, we allow the agent to run as many steps as needed, with a maximum of $3 total cost incurred per run (so $9 total across all three steps).
- The most costly step is typically building the executable. The SWE-agent will typically read existing files that may offer hints at how to compile the binary (e.g., `README.md`, `CONTRIBUTING.md`, `.github/workflows`). In some cases, models also expend turns to identify and correctly install dependencies that are missing from the given environment.
- The base image used for all task instances is built from a custom Dockerfile based on `ubuntu`:22.04 with Rust 1.92.0, Python 3.12, and Golang 1.21.0 installed. The `build-essential` and `cmake` packages provide C/C++ toolchain support. Version control with `git` is configured such that task workers can make commits and track changes if they choose to do so. The `tmux` library is provided to enable manipulation of TUI applications. We note that *no task-specific installations or setups are performed.*

A.2 Inference Setting

In this section, we provide additional details about the setting and conditions that models are asked to solve ProgramBench task instances under. We first motivate the role of constraitns in reducing spurious or undesirable problem solving techniques §A.2.1, then review the inference guidelines in §A.2.3. Finally, we anticipate and address questions about ProgramBench's feasibility under these constraints in §A.2.4.

A.2.1 Motivation

In several early trial runs of the benchmark, we found that without certain guardrails in place, models will "cheat". A recent report on SWE-bench Verified revealed that instead of navigating the repository, localizing buggy modules, and writing a fix, certain models instead fast-forwarded to a future version of the repository


```
"message": {
  "content": "Version 0.16.1 is available. Let me clone this repository and build it:",
  "role": "assistant",
  "tool_calls": [
    {
      "function": {
        "arguments": "{\"command\":\"cd /tmp && git clone --depth 1 --branch v0.16.1
https://github.com/AmmarAbouZor/tui-journal.git\"}",
        "name": "bash"
      },
    }
  ]
```


Figure 13 An example of an undesirable solution pattern that emerges if a SWE-agent is asked to solve a ProgramBench task with internet access. Instead of developing a codebase that mirrors the behavior of the `AmmarAbouZor/tui-journal` repository, Claude Opus 4.5 identified and cloned the source code from GitHub.

> ...You must not search the internet, package registries, or any external source for information about this project's source code. Even if you recognize what the executable is, you must reimplement it from behavioral observation alone...

Figure 14 Excerpt from system prompt that tells model to not cheat. Internet access is also blocked. Full prompt in §A.2.

(by `git checkout`'ing to a commit) where the bug was already fixed, then submitted the `git diff` between the task's "base" commit and future commit as the fix[4].

Similarly, we found that by simply asking the SWE-agent to perform a ProgramBench task with no explicit constraints (e.g., full internet access, read/write permissions for the executable), interesting but undesirable solution patterns occasionally emerge. As shown in Figure 13, we noticed that if Claude Opus 4.5 was able to figure out what GitHub repository the executable originates from, typically by inferring from `./executable -h` standard output, it then performed a shallow clone of the remote repository to obtain the source code.

Although the task worker still must generate a `compile.sh` script that builds the executable, the implementation effort, which is typically where the majority of a task worker's efforts are required, becomes trivially simple and yields no insight into the research questions posed by our work. Another infrequent but still observed failure mode is that a task worker will simply submit a wrapper around the reference executable and call it a day (this is fully mitigated as explained below).

A.2.2 Early Mitigation Attempts

Before blocking internet access entirely, we tried allowing it while detecting and penalizing cheating after the fact. This section describes our LM-as-a-judge cheat detection pipeline, its results, and the limitations that led us to disable internet access.

Detection pipeline. We built a rubric-based annotation system that classifies agent trajectories into two violation types: *source code lookup* (cloning the repository, downloading via package managers, reading cached dependency source) and *binary wrapping* (submitting a thin wrapper around the reference executable instead of a real reimplementation). For each task, 9 LM judges independently review the full command history and classify the trajectory. To reduce single-model bias, the judges are drawn from three model families: 3 instances of GPT 5.2, 3 of Claude Sonnet 4.5, and 3 of Gemini 3.1 Pro. A task is flagged if a strict majority (5 or more of 9) judges identify at least one violation.

Cheating rates. We ran this pipeline on internet-access runs for four models: Claude Opus 4.6, Claude Sonnet 4.6, Gemini 3 Flash, and GPT 5 mini. As reported in Table 3, cheating rates range from 1% (GPT 5 mini) to 36% (Claude Sonnet 4.6). Source code lookup is the main violation type, accounting for 79–95% of flagged tags across the three models with meaningful cheating rates. Models use a range of strategies: directly cloning the GitHub repository, installing the project via a package manager (`cargo install`, `go get`, `apt-get source`), or reading cached dependency source from local package caches such as `~/.cargo/registry/src/` and Go's module cache. This last strategy is especially hard to judge, as it blurs the line between reading dependency code and looking up the project's own source (see below).

Inter-judge agreement. Despite using 9 judges from three model families, agreement is moderate at best. Fleiss' κ ranges from 0.16 (GPT 5 mini) to 0.60 (Claude Sonnet 4.6), with a pooled κ of 0.57 across all 786 annotated tasks, which falls in the "moderate agreement" range. Judges disagree on 16–57% of tasks depending on the model, with the highest disagreement rate for Claude Opus 4.6 (57%), whose cheating strategies tend to be more subtle.

The main source of disagreement is whether reading dependency source code from local package caches counts as a violation. For example, on the `handlr` task (a Rust project), Claude Sonnet 4.6 navigated into `~/.cargo/registry/src/` and read the source of dependencies like `xdg-mime` and `clap`. Five of nine judges flagged this as source code lookup; the other four called it legitimate, reasoning that these are third-party libraries (not the project itself) that happened to be locally available.

Another gray area is consulting API documentation. On the `codesnap` task, Claude Sonnet 4.6 used `curl` to fetch pages from `docs.rs` (the Rust documentation hosting service) for the project's published crate. Four judges flagged this as source lookup; five called it clean, arguing that reading public API docs is closer to consulting a reference manual than obtaining source code. The task was not flagged (4 of 9 is below the majority threshold), but the split shows how reasonable judges can disagree on where to draw the line.

[4] https://github.com/SWE-bench/SWE-bench/issues/465. The loophole was patched in October 2025. Among the 20 most recent submissions, fewer than 1% of the 500 solutions per submission exhibited such violations.

These disagreements reflect real ambiguity in what counts as "cheating" when models have access to package ecosystems and documentation. Stricter rubrics risk penalizing legitimate reverse engineering strategies; looser ones risk missing real violations.

```
Agent action (handlr task, Claude
      Sonnet 4.6):

cat ~/.cargo/registry/src/.../xdg-
      mime-0.3.3/src/lib.rs
cat ~/.cargo/registry/src/.../confy
      -0.4.0/src/lib.rs
cat ~/.cargo/registry/src/.../
      ascii_table-3.0.2/src/lib.rs
```

```
Judge verdict: CHEATING (
      source_lookup)

The agent accessed cached cargo
      registry source
files in ~/.cargo/registry/src/ to
      examine the
APIs and implementations of
      dependencies like
clap, ascii_table, xdg-mime, and
freedesktop_entry_parser.
```

```
Judge verdict: CLEAN

The agent reimplemented the
      software in Rust by
reading the source code of its
      dependencies
(standard crates like clap, xdg-mime
      , ascii_table)
found in the local cargo registry
      cache. The agent
did not access the source code of
      handlr itself.
```

Figure 15 Example of a 5–4 judge disagreement. Claude Sonnet 4.6 read dependency source code from the local Cargo registry cache while working on the `handlr` task. Five judges flagged this as source code lookup (red); four called it legitimate, noting the files are third-party libraries, not the project itself (green).




Figure 16 Distribution of judge votes per task for each model evaluated with internet access. Each bar shows how many tasks received exactly k cheating flags from the 9-judge panel. Tasks at $k \geq 5$ are flagged by majority vote. Claude Sonnet 4.6 shows a bimodal pattern (many tasks at 0 and 9), while Claude Opus 4.6 has more mass in the ambiguous middle range, explaining its higher disagreement rate.

A.2.3 Guidelines

To address these concerns, we attempt to mitigate potential loopholes by imposing several measures and restrictions on the image construction, inference, and evaluation pipelines.

For the Docker image construction pipeline, based on what we discussed in §2.2, we highlight several key steps aimed at making illegitimate solution patterns such as decompilation and re discovering local copies of source code impossible or more difficult to achieve:

- **Execute-only permissions**: To prevent task workers from using a tool like `ghidra` to reverse engineer an executable into code, we set the permissions of the executable to `111` (execute-only).
- **Removal of original executables during evaluation**: The model might attempt to submit the original executable together with a thin wrapper around it as its solution. This is mitigated by removing all files that match the hash of the original executable prior to evaluation.
- **Inject the executable instead of building from source**: Early on, we used a simpler workflow to construct the Docker image for the starting state of a task. Starting with the repository, we would first build the executable by running the model generated `build.sh` script, then invoke a model generated `clean.sh` script that would wipe the source code and any artifacts that give away implementation details. We found that although models' `clean.sh` scripts were quite capable of wiping out source code, they would

often miss build artifacts and hidden files. For instance, at one point we added explicit reminders to remove caches (e.g., ∼/.cargo/, ∼/.cache/**) and build folders (e.g., target/, build/), which contain direct or suggestive information about the implementation. Furthermore, a handful of repositories, typically implemented in C/C++ where build systems are much more heterogenous unlike the Rust or Golang developer ecosystems, would produce artifacts in a much less predictable, uniform manner. Consequently, the model would frequently fail to explore and remove such artifacts when generating clean.sh. The artifact would then be discovered at inference time. Therefore, to eliminate any possibility of such leakage, we opted for the final approach of separating execution compilation and model inference into two separate containers.

- git **history removal**: The original repository's version control history can reveal the remote URL, branch names, and commit messages that identify the project. During image construction, we wipe the existing .git/ directory and reinitialize a fresh repository with a single anonymous commit containing only the documentation and the executable.

Collectively, these steps ensure that decompilation is impossible, submissions that wrap the gold executable are illegitimate, and local build artifacts that partially or fully give away implementation details do not exist. We review the restrictions and checks we impose on the inference and evaluation procedures.

- **No Internet Access**: Early in the project, we experimented with several iterations where we allowed internet access at inference time, but then prohibited specific behaviors that we deemed cheating by describing them specifically in the task instructions. We also ran an LM-as-a-judge pipeline that would flag cheating by checking the agent trajectory corresponding to a solution. Such measures quickly devolved into a cat-and-mouse game, with more capable models coming up with measures to circumvent instructions, such as downloading source code by importing via a dependency manager like cargo rather than directly from Github. Furthermore, verbalizing the fine line of what is (not) permitted also quickly became tricky. On occasion, models' thought traces exhibit uncertainty over whether certain actions were permissible. When working on FFmpeg/FFmpeg, Claude Sonnet 4.6 expressed hesitation over whether it was allowed to download a dependency that happened to be co-located (implemented in the same GitHub repository) with the FFmpeg source code. We considered running the LM-as-a-judge cheat detection with multiple models as a way to address "gray areas", but found that there were high rates of disagreements and volatility in the judgments themselves. Therefore, in favor of simplicity and rigor, we block internet access during ProgramBench inference.
- **System prompt instructions**: As shown below, the task instructions inform what behaviors are disallowed. Even though the aforementioned guardrails ensure that disallowed actions are futile, we still include this text because without it, task workers may waste turns generating unpermitted actions. The full system prompt is shown below.

```
You are a helpful assistant that can interact with a computer.

This is a reverse-engineering benchmark. You are given a compiled binary and its documentation.
Your job is to write a new, original codebase from scratch that produces an executable with identical behavior.
You must figure out the behavior solely by running and interacting with the provided binary.
Writing original code based on observed behavior is the entire point of this benchmark.

Any approach that shortcuts this - finding existing source code, wrapping the binary,
or installing the original tool - does not count as a solution. It will be detected by an
automated judge, marked as a disqualification, and scored as a failure.
The trace will be posted to an online wall of shame.

<RULES>
## What is not allowed

### 1. Obtaining source code

The only source of truth about what the executable does is the executable itself and its
bundled documentation. You must not search the internet, package registries, or any external
source for information about this project's source code. Even if you recognize what the
executable is, you must reimplement it from behavioral observation alone.
```

This includes but is not limited to:
- Cloning or browsing the original GitHub repository, its forks, or mirrors
- Downloading the project from package registries: ‘cargo install <project>‘, ‘go get github.com/<org>/<project>‘, ‘pip install <project>‘, ‘apt-get source <project>‘, ‘npm install <project>‘, etc.
- Fetching source tarballs from project websites (e.g., ‘curl https://lua.org/ftp/lua-5.5.0.tar.gz‘)
- Using a package manager to download the project as a dependency and then reading its cached source (e.g., navigating into ‘~/.cargo/registry/src/‘ or ‘$(go env GOPATH)/pkg/mod/‘)
- Searching the web for the project’s source code or implementation details

2. Wrapping or reusing the original binary

Your submission must be a genuine reimplementation. The provided ‘./executable‘ is for observation only - your final solution must not depend on it or any other pre-built version of the same tool at runtime.

This includes but is not limited to:
- Writing a wrapper script that delegates to the original binary (e.g., ‘exec zstd "$@"‘)
- Installing the tool from a package manager and shimming to it (e.g., ‘apt-get install nnn && cp $(which nnn) ./executable‘)
- Writing a ‘compile.sh‘ that simply makes the provided binary executable (‘chmod +x ./executable‘) or copies it (‘cp ./executable ./executable‘)
- Building a binary whose main function shells out to an external tool (e.g., ‘Command::new("miniserve").args(args).exec()‘)
- Re-linking prebuilt ‘.o‘ object files found in the workspace without writing new source code

3. Binary analysis of the provided executable

All information about the provided ‘./executable‘ must be obtained by interacting with it through its normal user interface (CLI flags, stdin/stdout, etc.).
- You MUST NOT decompile ‘./executable‘ or use disassemblers (objdump, Ghidra, etc.) on it
- You MUST NOT use strace, ltrace, or similar tracing/instrumentation tools on ‘./executable‘

Note: this restriction applies ONLY to the provided ‘./executable‘. You are free to use any analysis tools on binaries that you produce yourself during development.

What IS allowed

- Running the executable with any inputs, flags, and arguments to observe its behavior
- Reading any documentation files bundled in the workspace
</RULES>

A.2.4 On the Feasability of ProgramBench

The difficulty of the ProgramBench task paired with the constraints we impose at inference time may leave some readers wondering whether some, or for that matter, any ProgramBench task instances are even possible to resolve. ProgramBench is a very challenging benchmark by today’s standards. While we do not carry out any formal human studies, based on the development history, codebase size, and range of functionality, we venture that an average ProgramBench task instance could take an individual or team days, if not weeks’ or months’ worth of time to complete.

That said, we argue that while formidable, ProgramBench task instances are certainly solvable by construction. The key reason ProgramBench is not truly impossible: every test asserts executable behavior that is observable and deterministic. The same executable is fully accessible to the model, with the necessary permissions to run with any inputs and see exact outputs. Across the next several paragraphs, we pose and address potential concerns about ProgramBench’s resolvability.

Can functionality written in one language be reproduced with another? It is possible that models chooses to implement their solution in different language than one the original source code is written in, which raises the question: does a solution in an alternative programming language even exist? Computer science theory says yes. By the Church-Turing thesis (Turing et al., 1936), any deterministic input-output behavior that can be realized by a program implemented in one Turing-complete language can be realized by a program written in another Turing-complete language. Simply put, all general-purpose programming languages are equivalent in computational power. All languages represented across ProgramBench task instances are Turing-complete. Models are also provided multiple Turing-complete languages in the task environment.

Could obscure program behaviors be impossible or arbitrarily hard to discover? A subtler concern is discoverability of tested behaviors. To elaborate, given that the test generator runs with full access to the source code, it is possible that some generated tests target hard-to-detect, edge-case behavior. However, this concern is a reflection of ProgramBench's difficulty, not feasibility. Models could very well not think of running the executable with certain permutations of flags and inputs. This does not mean the task is impossible. Rather, it demonstrates how exploration of program behavior is a key challenge posed by ProgramBench, and that beyond writing code, models are tested on their thoroughness when it comes to uncovering behaviors and considering boundary conditions that human developers accounted for.

Conceptually, one scenario where behavior is borderline impossible to discover is if an executable supports functionality that is not communicated or documented via any observable channel. In other words, there is functionality that is not revealed by the `README.md`, `--help` flag standard output, or any artifacts that could be unveiled by typical exploratory actions. A corresponding test would then effectively be penalizing models for failing to discover behavior that was never observable in the first place. Such tests may also incentivize models to exhaustively and unintelligibly probe an executable with random inputs, rather than engage in systematic, hypothesis-driven exploration.

In practice, we find that well-maintained programs document their interfaces thoroughly. Flags, subcommands, supported inputs, and example invocations are frequently surfaced as help output, man pages, or usage documentation. The above scenario, an executable with important but entirely undiscoverable functionality, would be considered not only bad practice, but even defective by conventional software engineering practices. Out of caution, we reviewed all 200 repositories for such discrepancies and did not find any instances where an executable's supported behavior was entirely absent from the task instance's start state.

What if tasks require internet to solve? While creating task instances, we came across several repositories that require internet access for a variety of reasons. The following are a handful of GitHub repositories that successfully construct an executable, but were not usable as ProgramBench task instances because the executable inherently requires communication with one or more endpoints on the web.

- `thomas-mauran/chess-tui`: A terminal chess client. Its core gameplay requires connecting to lichess.org to match with remote opponents.
- `aquaproj/aqua`: A CLI tool manager. It downloads tool binaries from GitHub releases, making the entire tool lifecycle network-dependent.
- `builditluc/wiki-tui`: A terminal Wikipedia reader. Every user interaction fetches and renders articles from the Wikipedia API.

We take care to only admit task instances to the test set that do not have this need. That said, ProgramBench nonetheless contains networking tools; 18 task instances are utilities such as HTTP clients, DNS resolvers, and port scanners. While internet access is cut off, ProgramBench task environments still retain loopback networking (`127.0.0.1`). The reverse engineering challenge in these tools lies in their protocol handling, output formatting, and CLI logic, not in reaching a remote host. Therefore, task workers can still develop faithful implementations by spinning up local servers and exercising program behavior against localhost. We mark the 18 task instances that involve networking functionality in Table 12.

Do task workers have access to evaluation assets? Some behavioral tests exercise the executable with input files such as images, audio files, videos, spreadsheets, or domain specific configurations. Coupled with the lack of internet access, this highlights an unfair asymmetry where evaluation uses assets that either models are unable to generate on their own or are relatively obscure, executable-specific file formats.

To address this, for each task instance, after generating tests, we run a script to extract such assets. The script abides by a simple heuristic: keep any files with extensions that aren't on a "blocklist" of popular, standardized, text-based file formats. The rationale is that we are not interested in the failure mode where models fail to develop a solution because it could not come up with characteristic test data. This means that binaries (e.g., `png`, `mp3`, `wav`, `xlsx`) are always provided, as today's models may not be capable of synthesizing such files directly. A handful of repositories propose and use their own file formats (e.g., `.hcl` for HashiCorp configurations); our script also keeps these as well. On the other hand, files represented in popular formats are not provided; for example, we do not give `.php` or `.c` files used by evaluation suites for

the `php/php-src` and `tinycc/tinycc` task instances respectively. Just as a human developer could come up with sample files, we impose the same expectations on the task worker. Coming up with a diverse range of inputs that accounts for edge cases is part of tackling a ProgramBench task instance.

As a final note, we have observed evidence of models being able to programmatically generate binary assets. During test generation for `FFmpeg/FFmpeg`, models used ffmpeg's built-in `lavfi` virtual input device to synthesize audio and video on the fly (e.g., `sine` for waveforms, `testsrc` for video patterns), avoiding the need for pre-existing media files entirely. Similarly, during inference across several image-processing tasks (e.g., `cslarsen/jp2a`, `hpjansson/chafa`), models wrote inline Python scripts using Pillow to programmatically create test images. This suggests that going forwards, the need to provide binary assets may diminish as models become more adept at generating their own.

A.3 Test Generation

We briefly extend upon our motivation for designing novel test generation pipelines, then explore several strategies for automated test generation via `mini-SWE-agent`.

Limitations of skeleton-based evaluations. As alluded to in the related works (§6), the preceding common approach to evaluating language models on their ability to build projects to scratch has typically abided by a fill-in-the-blank structure. This is a direct consequence of the collection and evaluation methodology. To create a task instance, typically from an open source GitHub repository, class and method implementations are first deleted procedurally using Python-specific libraries like `ast`. The repository's original unit test suite is then used for evaluation. Consequently, if a model deviates from the expected signatures, even if the deviation is reasonable, the test harness won't locate or execute that code.

It is effectively impossible to evaluate truly free-form solutions if tests assert against implementation. From manual inspection of repositories during early stages of the project, we also found that behavioral checks, such as end-to-end, integration testing, do not exist in the wild anywhere near as frequently as unit testing. The yield rate of filtering for repositories that not only satisfy ProgramBench's collection constraints, but also have high coverage, end-to-end testing suites is extremely low based on our initial attempts.

Frequency of existing testing. To motivate the need to generate behavioral tests, we first check to what extent repositories already have such testing. As mentioned in §2.2, ProgramBench does *not* require repositories have pre-existing tests, nor does the test generation strictly depend on such information. That said, we perform this investigation to gauge the necessity of our test generation strategies.

Out of all 200 task instances, 141 (70.5%) have tests, while 59 (29.5%) do not have an existing test suite. We detect tests via filename conventions (e.g., `test_*.py`, `*_test.go`) and directory names (e.g., `tests/`, `__tests__/`); a repository is marked as having tests if at least one such file exists. We find that either the large majority or entirety of existing test suites consist of implementation focused unit tests targeting code-level correctness. Behavioral test suites that invoke an executable in multiple ways occasionally appear in the codebase, but not nearly consistently enough to obviate the need for generating additional tests.

A.3.1 Strategies

To generate tests, we generally first give one or more prompts to a SWE-agent. The agent is then asked to write the behavioral tests. We summarize the approaches we investigate:

- *Monolithic*: We give the SWE-agent a single prompt, asking it to generate a comprehensive behavioral test suite in one pass.
- *Decomposed*: We give the SWE-agent six specialized prompts, each targeting a narrow category: argument parsing, configuration, help output, I/O behavior, subcommand dispatch, and TUI interaction. The hypothesis is that more variegated prompting leads to more diverse testing.
- *Coverage-Guided Iterative*: We use the SWE-agent to explore the program, its source code, existing tests, and documentation, and then generate behavioral tests. We also prompt the agent to identify and include in its test suite any existing behavioral tests defined in the repository (*harvesting*). The

agent continuously measures the line coverage of the current test suite and iteratively writes new tests to invoke missing code paths, attempting to achieve full coverage.

Naturally, some generated tests may have missing or trivially true assertions. Therefore, to ensure assertion quality, tests are flagged if they fail the gold binary or trigger our assertion quality linter, which detects structurally weak assertion patterns such as exit-code-only checks, short substring matches, and disjunctive assertions (see A.3.5 for full list of rules). The agent is prompted to revise all flagged tests. The loop continues until the suite satisfies a target coverage threshold.

At the end of every strategy, we discard any tests that do not pass with the gold binary deterministically or pass a dummy binary.

A.3.2 Analyses

We provide several statistical and qualitative breakdowns of the proposed test generation strategies.

The coverage-guided iterative strategy does the best. The monolithic strategy averages 27.8 tests per task. The decomposed strategy does better, averaging 51.7 tests per task. However, the coverage-guided iterative strategy results in a significantly larger number of tests with a median of 750 tests per task and with most tasks having between 200 to 2000 tests. It also results in a very high mean line coverage of 79.7%, with a median of 86.2% (Figure 7). Furthermore, when possible, the agent effectively makes use of existing tests, e.g., SQLite, PHP, Bedtools2, Proj and Ctags (Figure 17).

The majority of tests are generated, not harvested. Our test generation pipeline combines two sources: tests generated from scratch via the strategies described above, and tests harvested from existing repository test suites that exercise executable behavior, as done in the 'coverage-guided iterative' strategy. Figure 17 shows the distribution of total tests per task, and breaks down the proportion from each source. The majority of tests are self-generated (79.5%), while the remaining 20.5% are harvested from existing suites.

Incorporating assertion-quality signals generates stronger tests. A static linter plus gold/dummy execution feedback in the test generation loop reduces the mean dummy pass rate from 18.5% to 3.7% (a 5× reduction) and eliminates the worst-case failure mode where a large fraction of a task's tests are trivially passable. On the same set of tasks evaluated across four frontier models (Opus 4.6, Sonnet 4.6, Gemini 3.1 Pro and GPT-5.4), the resulting tests are 20–30 percentage points harder to pass than tests generated without these signals, with no change in model rank ordering, confirming the gain comes from stricter assertions rather than from incidentally harder tests.

Coverage measurement methodology. For each task, we merge all active generated test branches and execute them against a coverage-instrumented build of the original binary. We measure first-party line coverage only, excluding system headers, vendored dependencies, and auto-generated code. The coverage scatter plot (Figure 7) shows a representative subsample of 100 tasks drawn from the 154 tasks where we independently performed coverage measurement, disregarding the coverage recorded by the test generating agent.

Behavioral suite baseline selection. From our benchmark's hard tasks (difficulty score ≥ 4; see §A.4 for the scoring formula), we selected twelve repositories that maintain an identifiable application-level behavioral or integration test suite, as opposed to only internal unit tests. The selected suites are: PHP's `.phpt` regression harness, FFmpeg's FATE suite, Typst's CLI and rendering tests, Miller's regression cases, StGit's shell

Table 7 The six specialized configs used in the *decomposed* test generation strategy. Each config prompts a SWE-agent to write tests targeting a narrow behavioral category of the executable.

Type	Description
Args	Flag formats, required/optional arguments, positional args, type validation
Config	Environment variables, config file loading, precedence rules
Help	`–help`/`-h` output, usage synopsis, subcommand help text
I/O	Stdin/file input, stdout/stderr separation, exit codes, output formatting
Subcommand	Subcommand dispatch, routing, global vs. local flags, aliases
TUI	Interactive navigation, key bindings, screen state, mode switching




Figure 17 Distribution of test volume and source across all ProgramBench task instances. Left: each dot is one task; the x-axis shows the total number of tests (log scale) and the y-axis shows the percentage of tests harvested from existing repository test suites versus self-generated tests. Bin counts are annotated above the plot. Right: global split of harvested vs. self-generated tests across all tasks.

workflow tests, Doxygen's documentation fixtures, Lazygit's integration tests, Atlas's CLI/e2e plus SQLite integration tests, Rumdl's integration tree, JSON Schema's CLI plus conformance tests, Zstd's CLI and fuzzer suite, and jq's regression harness. We audited each baseline against upstream CI configurations to ensure the comparison is integration-test only, excluding `src/` unit tests in projects (Rumdl, Atlas) where the default test runner would otherwise inflate native coverage with code paths our black-box generated tests structurally cannot reach.

A.3.3 Test Examples

We present examples of tests generated by our pipeline for a select set of task instances. Generally, all tests are represented in Python using the `pytest` library, a design that is explicitly requested by our instructions.

```
1  def test_test_mode_detects_corruption(exe,
       workdir):
2      src = write_file(workdir / "f.bin", os.urandom
         (4096))
3      run([exe, str(src)], cwd=workdir)
4      zst = workdir / "f.bin.zst"
5
6      cp_ok = run([exe, "--test", str(zst)], cwd=
         workdir)
7      assert cp_ok.returncode == 0
8
9      data = bytearray(zst.read_bytes())
10     data[len(data) // 2] ^= 0xFF
11     zst.write_bytes(bytes(data))
12
13     cp_bad = run([exe, "--test", str(zst)], cwd=
         workdir)
14     assert cp_bad.returncode != 0
```

zstd (corruption detection): `zstd` is a compression tool. The test compresses random bytes (L2), then runs `--test`, which verifies archive integrity without decompressing (L5). It then flips a single byte in the compressed file (L8–9) and re-runs `--test`, asserting that the corruption is now detected (L12).

```
1  def test_import_csv_and_query(self, tmpdir):
2      csv_file = tmpdir / "data.csv"
3      csv_file.write_text(
4          "id,name,value\n1,Alice,100\n2,Bob,200\n"
5      )
6      result = run_batch(stdin=(
7          f".import {csv_file} my_data\n"
8          "SELECT name FROM my_data "
9          "WHERE value > 150;\n"
10     ))
11     assert result.returncode == 0
12     assert b"Bob" in result.stdout
13     assert b"Alice" not in result.stdout
```

DuckDB (CSV import and query): `duckdb` is an analytical database with a CLI shell. The test writes a CSV file to disk (L2–4), then uses the `.import` dot-command to load it into a table (L6). It immediately queries the table with a `WHERE` filter (L7–8) and asserts that only the matching row appears in the output (L11–12).

```
1  def test_script_file_execution_and_argv(
       tmp_path):
2      script = tmp_path / "script.php"
3      script.write_text(
4          "<?php\n"
5          "echo $argc, '\n';\n"
6          "echo implode(',', $argv);\n"
7          "?>\n",
8      )
9      cp = run_php(
10         ["-n", "-f", str(script), "--", "a", "b c"]
11     )
12     assert cp.returncode == 0
13     lines = cp.stdout.splitlines()
14     assert lines[0] == "3"
15     assert lines[1].endswith("a,b c")
```

PHP (script execution): `php` is the PHP language interpreter. The test writes a small PHP script to disk (L2–7) that prints the argument count (`$argc`) and a comma-joined argument list (`$argv`). It invokes the interpreter with `-n` (no config file), `-f` (execute script from path), and `--` (separates interpreter flags from script arguments) on L9. The assertions verify the argument count and that a space-containing argument (`"b c"`) is passed through correctly (L12–13).

```
1  def test_stdin_pipe_produces_identical_bytes(
       tmp_path):
2      gen = run_ffmpeg(
3          "-v", "error", "-f", "lavfi", "-i",
4          "anullsrc=r=8000:cl=mono", "-t", "0.05",
5          "-c:a", "pcm_s16le", "-f", "wav", "-",
6      )
7      assert gen.returncode == 0
8      wav = gen.stdout
9      assert wav[:4] == b"RIFF"
10
11     r = run_ffmpeg(
12         "-v", "error", "-i", "-",
13         "-c", "copy", "-f", "wav", "-",
14         stdin=wav,
15     )
16     assert r.returncode == 0
17     assert r.stderr == b""
18     assert sha256(r.stdout) == sha256(wav)
```

FFmpeg (stdin piping): `ffmpeg` is a multimedia processing tool. The test first generates a WAV audio file from a silent source (`-f lavfi` on L3 selects a virtual input device; L4 synthesizes silence at 8 kHz). It confirms the output has a valid WAV header (L7). A second invocation on L9 pipes the WAV back through `ffmpeg` via stdin (`-i -`) with `-c copy` (stream-copy, no re-encoding), then asserts SHA-256 equality (L14).

A.3.4 On Test Overspecification

As referenced in §2.2, here we provide an extended discussion about test over-specification and its impact on the feasibility of accomplishing a ProgramBench task instance.

Overspecified tests are undesirable because they make a ProgramBench task instance infeasible to successfully complete. Generally, an "overspecified" test checks a solution for details that are not stated explicitly in the task instructions *and* impossible to discover during the task solving process. In other words, an overspecified test asserts a condition that is completely inaccessible to a task worker.

ProgramBench addresses this issue by virtue of how tests are constructed. In lieu of unit tests, which we define as tests that check against source code, ProgramBench tests assert only on observable behavior of an executable, such as standard output/error, exit codes, and file system modifications. Therefore, because tests always involve invocations of an executable, they inherently are incapable of targeting details such as variable names or method definitions.

A subtler concern is whether tests might demand exact reproduction of implementation-dependent outputs, such as floating point precision or hash iteration order. A concurrent case study highlights this tension: MirrorCode (Adamczewski et al., 2026) addresses this explicitly by manually vetting 4 repositories "that seemed feasible for a human software engineer to reimplement under similar constraints", where feasibility is defined as programs where the behavior and documentation are closer to a specification rather than a reverse engineering challenge.

We take a different approach. Rather than deciding manually which behaviors are reasonable, we treat the gold executable as the complete specification, which means any deterministic, observable behavior is fair game. This is a deliberate design choice. First, the model has full access to the executable at inference time, so any behavior a test checks can be discovered by running the same command. The suite contains no hidden information that the model cannot obtain itself. Second, after several rounds of annotations, we came to the conclusion that distinguishing "meaningful behavior" from "implementation artifact" can be very subjective and does not scale. Whether the 8th decimal digit of a computation matters depends entirely on the application; for a library used to calculate the trajectory of a satellite in space, precision is of utmost importance. Third, our gold evaluation procedure filters nondeterministic tests by running each test against the reference executable multiple times and throwing out any that do not pass consistently. The tests that remain reliably characterize an executable's behavior, which is precisely what we ask the model to reproduce.

We audited ProgramBench task instances to investigate whether any task instances are "at risk" of overspecification. We find that in our setting, there are very limited manners in which overspecification can occur; namely, floating point precision, hash/map iteration order, and rendering discretization. Other potential forms of non-determinism such as timestamp formatting or locale-dependent sorting are really an attribute of *environment* differences, not implementation differences, which our Docker based set up standardizes. Out of 200 instances, we found only 5 instances where such behavior could plausibly appear in test output:

- `oppiliappan/eva`: a terminal calculator REPL, where arithmetic results could differ in precision depending on the floating point library or operation ordering used by a reimplementation.
- `gromacs/gromacs`: a molecular dynamics simulation toolkit, where simulation outputs involve extensive floating point computation sensitive to operation ordering.
- `rs/jplot`: a terminal plotting tool, where mapping continuous values to discrete character-grid positions involves rounding decisions (e.g., floor vs. round) that affect visual output.
- `OSGeo/PROJ`: a cartographic projection library, where coordinate transformations involve chained floating point operations and intermediate rounding.
- `OSGeo/gdal`: a geospatial data translator, where raster/vector transformations and coordinate reprojections involve floating point arithmetic sensitive to operation ordering.

We manually inspected the test suites for these five instances and did not find evidence of assertions on implementation-dependent numerical output; the tests predominantly check CLI flag behavior, file format handling, and string output.

Rule	Sev.	Description
no_assertions	HIGH	Test contains no assert statements
trivially_true	HIGH	assert True or assert X or True
sole_returncode	HIGH	Only assertion checks returncode == 0
returncode_in_list	HIGH	assert returncode in [...] launders non-zero exits
pass_body	HIGH	Test body is just pass
assertion_disjunction	HIGH	assert A or B: should assert exact outcome
if_no_else	HIGH	if branch asserts with no else: silently passes when condition is false
if_else_both_assert	HIGH	Both if/else branches assert: suggests non-deterministic behavior
try_except_swallow	HIGH	except handler with pass swallows failures
all_assertions_weak	HIGH	All assertions only check returncode, len, or isdigit
short_substring	HIGH	Substring check shorter than 15 characters
golden_written_in_test	HIGH	Test writes to its own golden file (always passes)
golden_no_equality	HIGH	Golden file referenced in docstring but never compared with ==
golden_docstring	HIGH	Golden file mentioned in docstring not found in test body
for_no_guard	MED	Loop-only assertions with no pre-loop length check
weak_sole_assertion	MED	Sole assertion is len(x) > N
relative_length_assertion	MED	assert len(x) >= N: relative bound verifies nothing about content
any_all_no_guard	MED	any()/all() with no non-empty guard
file_exists_no_content	MED	path.exists() with no content assertion
only_negative_assertions	MED	All assertions are negative (not in, !=)
catches	LOW	Missing or too-short CATCHES: docstring

Table 8 Assertion lint rules. HIGH rules indicate tests likely to pass trivially incorrect implementations. MED rules indicate weak but not necessarily vacuous assertions.

A.3.5 Assertion Lint Rules

Table 8 lists all rules checked by the assertion linter.

Examples of Weak Assertions. The following illustrates common failure modes our linter detects, drawn from real generated tests.

```
def test_help_flag(run_binary):
    result = run_binary(["--help"])
    assert result.returncode == 0
```

Exit-code-only assertion: passes any implementation that runs without crashing. Ignores the contents of the help text.

```
def test_list_output(run_binary):
    result = run_binary(["list"])
    assert "*" in result.stdout
    assert result.returncode == 0
```

Short substring check: the 3-character literal `"*"` matches trivially.

```
def test_compile_output(run_binary):
    result = run_binary(["main.c"])
    assert result.stdout.startswith("gcc -c ") or \
           result.stdout.startswith("clang -c ")
```

Disjunctive assertion: accepts either outcome rather than asserting the true expected output.

```
def test_parse_output(run_binary):
    result = run_binary(["input.json"])
    try:
        data = json.loads(result.stdout)
        assert len(data) > 0
    except Exception:
        pass
```

`try/except` swallowing failures: any exception silently passes. Also only asserts on content length, not content itself.

A.4 Dataset Statistics

In the following sections, we provide breakdowns of the ProgramBench dataset by various dimensions, including programming languages, repository size, and file extensions. These statistics characterize the diversity of the ProgramBench dataset and can help inform future analyses and evaluations. In general, our typical approach to these analyses is to perform simple, straightforward aggregations (e.g., line, file counts) or keyword-based searches (e.g., `test_*.go` to identify test files), unless specified otherwise explicitly. GitHub community statistics (stars, contributors, commits) were crawled on April 21, 2026.




Figure 18 Distribution of total/code files per repository.




Figure 19 Distribution of total/code lines per repository.




Figure 20 Distribution of build systems across ProgramBench repositories. The build system distribution closely mirrors the language distribution (Figure 3), as each language ecosystem has a dominant build tool.




Figure 21 Distribution of runtime dependencies across ProgramBench repositories. Counts are extracted by parsing root-level package manifests (`Cargo.toml`, `go.mod`, `CMakeLists.txt`, etc.), excluding development and test dependencies.

Number of files and lines. Figures 18 and 19 show the distribution of repository sizes in ProgramBench by number of files and lines. The median codebase has 93 total files with 50 code files, and 8,635 lines of code spread across all files. The extremes of the ProgramBench dataset feature several prodigious codebases. `FFmpeg/FFmpeg` has the most code files at 4566 total, while `php/php-src` (the official source code for the




Figure 22 Distribution of GitHub community and development history metrics across ProgramBench repositories: stars, contributors, commits, and repository age.

PHP interpreter) is implemented with 1.97 million lines of code. In comparison to existing benchmarks, these statistics confirm how ProgramBench is a step function increase in terms of implementation scale.

Build systems. A repository's primary language is determined by counting lines of code per language (mapped from file extensions) and selecting the one with the most lines (see Figure 3 in the main paper). From Figure 20, the distribution of build systems used correspond with these ratios. Build systems are identified by scanning for sentinel marker files (e.g., `Cargo.toml`, `go.mod`, `CMakeLists.txt`), with the primary build system being the one whose marker appears at the repository root. For Rust and Golang repositories, the `cargo` and native `go build` constitutes the entirety of build systems with which the corresponding executables are compiled respectively. There is relatively slightly more variance with C/C++ repositories due to the differences in libraries that certain projects rely on, but the build procedure generally remains quite uniform.

Directory depth. Repositories in ProgramBench are generally shallow: the median maximum depth is 3, with an average file depth of 2.5 levels from the repository root, and a median of 13 directories per repository. We compute depth by measuring each file's distance from the repository root. While most repositories (73%) have maximum depth ≤ 4, deeper hierarchies exist (up to 13 levels). Rust repositories tend to be the flattest (median 9 directories), while C/C++ projects are structurally more complex (median 32 directories), reflecting the heavier use of nested module hierarchies, platform-specific source trees, and vendored dependencies common in C/C++ ecosystems. At the extremes, 3 repositories consist of a single flat directory with no nesting at all (e.g., `seqtk`, `tty-clock`), while the deepest (`gromacs/gromacs` at depth 13) contains over 850 directories.

Dependency count. Of the 200 repositories, 171 (85.5%) contain a recognized package manifest file; among these, the median repository declares 17 total dependencies (12 runtime). Dependencies are counted by

Category	Subcategory	Count	Representative Examples
CLI Utilities	Text Processing	31	wfxr/csview, sclevine/yj, elkowar/pipr
	File & Disk	26	canop/broot, sitkevij/hex, jarun/nnn
	System & Network	22	rs/curlie, chmln/handlr, htop-dev/htop
Developer Tools	Build & Codegen	24	esubaalew/run, pemistahl/grex, cweill/gotests
	Linters & Formatters	18	paradigmxyz/solar, mgechev/revive, rvben/rumdl
	Documentation	9	crowdagger/crowbook, typst/typst, jgm/pandoc
	VCS/Git	9	jesseduffield/lazygit, foriequal0/git-trim, stacked-git/stgit
Terminal Fun & Demos	—	12	wintermute-cell/ngrrram, jrnxf/thokr, abishekvashok/cmatrix
Media & Graphics	—	12	cslarsen/jp2a, thezoraiz/ascii-image-converter, sharkdp/pastel
Productivity & Notes	—	10	naggie/dstask, lfos/calcurse, cheat/cheat
Security & Forensics	—	7	filosottile/age, rbakbashev/elfcat, sirwart/ripsecrets
Database & Data	—	7	ariga/atlas, multiprocessio/dsq, skeema/skeema
Compression & Encoding	—	7	facebook/zstd, madler/pigz, tukaani-project/xz
Languages & Interpreters	—	6	lua/lua, nuta/nsh, hush-shell/hush

Table 9 Distribution of ProgramBench task instances across functional categories. Each repository is assigned to a category based on its primary utility. Representative examples showcase the diversity within each category.

parsing root-level manifest files (`Cargo.toml`, `go.mod`, `package.json`, etc.) and summing declared packages. This distribution, with 20.0% of repositories in the moderate range (16 to 30 dependencies) and 11.0% heavy (>30), implies that successful reconstruction often requires correctly identifying and integrating third-party libraries rather than implementing all functionality from scratch.

Contribution statistics. To proxy how much human effort a repository corresponds to, we present some observations of contribution-related metrics on GitHub (Figure 22). The statistics generally showcase how the GitHub repositories represented in ProgramBench span a wide range of development lifetimes, with no bias towards any particular statistic, aside from the fact that it produces an executable.

Repositories span a wide range of community adoption, from projects like `HaliteChallenge/Halite` with 202 stars to widely used utilities like `junegunn/fzf` with over 79,000 stars (median of 2,124 stars). The distribution is roughly split in half: 49% of repositories have fewer than 2,000 stars, while 22% exceed 10,000. Many popular tools, such as `ffmpeg`, `jq`, `tinycc`, `php-src`, `ripgrep`, and `zstd` are represented. Similarly, projects have a wide range of development history, from `unhappychoice/gittype` created in late 2025, to `xorg62/tty-clock` which was seeded in 2008. The majority of repositories (56%) were created 4 to 10 years ago, with 30% being older than a decade. Solo projects with just a single contributor like `madler/pigz` account for 5 task instances. Others like `typst/typst` reflect larger collaborations with over 400 contributors (median of 22 contributors). Most repositories are small-team projects: 47% have fewer than 20 contributors, though 21% have over 100. Development effort varies dramatically as well, from `ip7z/7zip` with 13 commits to `php/php-src` with over 145,000 commits. About 44% of repositories have fewer than 500 commits, while 24% exceed 2,000.

Functional categories. Table 9 presents a breakdown of ProgramBench task instances by functional category, illustrating the diverse range of software utilities represented in the dataset. The 200 repositories span 14 distinct categories, with CLI utilities for text processing (31) and file/disk operations (26) being the most prevalent, followed by developer tools for build systems and code generation (24), and system/network utilities (22). The dataset also includes specialized domains such as security and forensics tools (7), programming language interpreters (6), and compression utilities (7). This breadth of functional categories ensures that ProgramBench tests a task worker's ability to reverse engineer software across a wide spectrum of real-world applications, from everyday productivity tools like `dstask` and `calcurse`, to foundational infrastructure like the Lua interpreter and Facebook's `zstd` compression library.

Task difficulty. To enable difficulty-stratified analyses, we assign each task a scalar difficulty score on a 0–10 scale derived from two repo-intrinsic metrics: lines of code and number of runtime dependencies. Concretely, the score is computed as $\text{score} = \text{clamp}\big(\log_{10}(\text{code_lines}) + \log_{10}(1 + \text{runtime_deps}) - 2,\ 0,\ 10\big)$, where the -2 shift accounts for the baseline produced by even trivial projects and the clamp caps the scale. Lines of code are counted across files with recognized code extensions (e.g., `.py`, `.rs`, `.go`, `.c`), while runtime dependencies

Difficulty	Score Range	Count	Examples
Easy	$[0, 2)$	28	`tty-clock`, `entr`, `cmatrix`, `figlet`, `seqtk`
Medium	$[2, 4)$	143	`ripgrep`, `fzf`, `jq`, `fd`, `zstd`, `htop`
Hard	$[4, 10]$	29	`lazygit`, `FFmpeg`, `typst`, `php-src`, `bat`

Table 10 Distribution of ProgramBench tasks across difficulty bins, with representative repositories.

Model	Easy	Medium	Hard	Avg
Claude Opus 4.6	**73.9%**	**53.3%**	24.7%	**52.0%**
Claude Opus 4.7	73.8%	52.1%	25.0%	51.2%
Claude Sonnet 4.6	67.1%	48.8%	**28.6%**	48.5%
GPT 5.4	50.9%	39.9%	18.0%	38.3%
Gemini 3.1 Pro	50.9%	37.7%	17.8%	36.6%
Gemini 3 Flash	49.6%	31.9%	17.9%	32.4%
Claude Haiku 4.5	41.9%	30.6%	15.6%	30.0%
GPT 5.4 mini	24.1%	17.4%	7.8%	16.9%
GPT 5 mini	21.3%	15.9%	11.0%	15.9%

Table 11 Macro-averaged test pass rate by difficulty bin: for each task instance we compute the fraction of tests passed, then average these fractions within each bin. Rates decrease monotonically from Easy to Hard for every model.

are extracted from root-level package manifests (`Cargo.toml`, `go.mod`, `CMakeLists.txt`, etc.), excluding development and test dependencies. We assign fixed, dataset-independent thresholds to bin tasks into three difficulty levels: *Easy* (< 2), *Medium* ($2 \leq$ score < 4), and *Hard* (≥ 4). To build intuition for the scale: a small single-file project like `pingu` (212 lines, 3 dependencies) scores 0.93 and falls squarely in the Easy range. A moderately-sized project with a handful of libraries (for instance, `direnv/direnv` at ∼8k lines and 3 dependencies, for instance) lands around 2.5, typical of the Medium bin. Reaching the Hard threshold generally requires either a very large codebase or a combination of substantial code and many dependencies; `lazygit`, with ∼593k lines and 36 dependencies, scores 5.3, while `FFmpeg` reaches 4.25 on the strength of its 1.8M lines alone.

We note that 22 repositories use custom or non-standard build systems (e.g., hand-written `Makefile`s or bespoke `./configure` scripts) for which no recognized package manifest was detected, resulting in a runtime dependency count of zero for those tasks; their difficulty scores therefore reflect code size alone. Table 10 summarizes the distribution across bins; per-task scores and labels are listed in Table 12.

As a sanity check, we look at whether our difficulty score correlates with observed agent performance. Table 11 reports the average test pass rate within each difficulty bin, broken down by model. Pass rates decrease monotonically from *Easy* to *Hard* across all models, suggesting that the metric captures meaningful variation in task complexity.

B Additional Results

We present additional figures and discussion that complement the experiment setup discussion (§3), main evaluation (§4), and analyses (§5).

B.1 Experimental Setup

Beyond its adoption by widely used leaderboards (§3), `mini-SWE-agent` is built to be neutral in how models interact with a codebase. Each turn, a model simply issues a bash action which is then executed directly; there are no manually crafted tools or prompts that could unfairly advantage or disadvantage particular models. This minimal design ensures that performance differences can be attributed directly to model capabilities rather than idiosyncrasies in agentic harnesses.

All configurations below are specified declaratively in `mini-SWE-agent`'s YAML configuration files, which control the agent loop, container provisioning, and model invocation.

- **Per-action timeout.** Each agent action must complete within 3 minutes; actions exceeding this limit are terminated with a descriptive error message. Models can work around this by launching background processes and polling output files.
- **Cost limit.** No cost limit is imposed. For reported costs, prompt caching is enabled and accounted for across all models.
- **Output truncation.** Command outputs exceeding 10,000 characters are truncated, showing the first and last 5,000 characters with an elision notice.
- **Soft warnings.** When fewer than 20 steps or 10 minutes remain, the agent receives a warning to wrap up and ensure its solution compiles.

B.2 Further Findings




Figure 23 Distribution of test pass rates across all 1,800 leaderboard runs in 5% bins. The median pass rate across all runs is 32%.

Most runs achieve meaningful partial progress rather than all-or-nothing outcomes. We examine how test pass rates are distributed across all leaderboard runs to understand how partial progress varies across models and task instances. Figure 23 shows the distribution across all 1,788 runs. The 0–5% bin is the single largest, containing roughly 18% of runs, indicating that models do frequently fail to make any meaningful progress on a task. Beyond that initial spike, however, scores are spread roughly uniformly across the pass-rate spectrum, with a median of 32%. The distribution tapers gradually at the high end: fewer than 5% of runs exceed 90%, and near-perfect reimplementations are rare. The large low-scoring bin provides a floor of genuinely difficult tasks, the uniform middle range rewards incremental progress, and the sparse right tail leaves room for future models to improve.

Across all models, performance on C/C++ tasks is substantially lower than Go and Rust. We break down pass rates by reference language to understand whether task difficulty varies across language families. Figure 24 shows




Figure 24 Distribution of per-task test pass rates by reference language across all models. Each box spans the interquartile range with the median shown in white; individual task scores are overlaid as jittered points. Two tasks whose reference language is the sole representative of its family (one Haskell, one Java) are omitted.

per-model box plots for each of the three reference languages. Rust and Go tasks yield similar average pass rates (38.5% and 38.4% respectively), while C/C++ tasks lag behind at 27.7%. The model ranking is largely preserved across languages, but C/C++ compresses the distribution downward: even the strongest models see median pass rates drop by 15–20 percentage points relative to Go. The gap likely reflects the greater complexity of the C/C++ codebases in ProgramBench (which include projects such as FFmpeg, GCC, and DuckDB) rather than an inherent language disadvantage.




Figure 25 Per-instance test pass rate vs. API calls (left) and cost (right). Each point is one (task, model) run. The x-axes are clipped at the 95th percentile for readability.

More turns spent does not correlate with improved scores. We plot per-instance test pass rate against API calls and cost to understand whether additional compute translates to better outcomes. Figure 25 shows scatter plots across all 1,788 runs, colored by model. The per-instance Pearson correlations are weak (r=0.27 for API calls, r=0.21 for cost), and the scatter plots show no clear trend: high-scoring runs appear at all turn counts and cost levels, while many expensive runs still score near zero. The modest positive correlations are largely driven by model-level differences, as stronger models tend to both use more turns and score higher, rather than by within-model scaling.




Figure 26 Cumulative distribution of trajectory lengths (API calls) per model. Lines that reach 100% before the 1,000-step limit indicate that all runs for that model submitted voluntarily.




Figure 27 Language confusion matrix under the different-language constraint. Compared to the default setting (Figure 8), the diagonal is nearly empty and Python becomes the dominant choice across all reference languages.

Models vary by over an order of magnitude in how many steps they use, falling into three distinct tiers. We examine the cumulative distribution of trajectory lengths to understand how models differ in compute allocation. Figure 26 shows CDFs of API calls per run for each model. The GPT family is the most concise: GPT 5.4, GPT 5.4 mini, and GPT 5 mini all finish 90% of tasks within 25 steps, with medians of 10, 9, and 14 respectively. Opus 4.7, Gemini 3.1 Pro, Gemini 3 Flash, and Haiku 4.5 form a middle tier with medians between 80 and 119 steps. Opus 4.6 and Sonnet 4.6 are clear outliers: Opus 4.6 has a median of 253 steps and Sonnet 4.6 reaches 443, with its 95th percentile at 840 steps approaching the 1,000-step cap. Combined with the weak score-vs-turns correlation (Figure 25), these differences appear to reflect model-specific interaction styles rather than a strategy that pays off in higher scores.

Models comply with the different-language constraint, defaulting overwhelmingly to Python. We examine the language confusion matrix under the different-language ablation setting to verify that models respect the constraint and to see which alternative languages they prefer. Figure 27 shows the results. The near-empty diagonal confirms that models largely comply, abandoning same-language reimplementations in favor of alternatives. Python dominates as the fallback across all three reference languages, accounting for 48–58% of runs per row and 51% overall, compared to 36% in the default setting (Figure 8). Despite this heavy skew, the different-language runs achieve only modestly lower pass rates overall (§4), providing empirical evidence that cross-language reimplementation is practical and reinforcing the theoretical argument laid out in §A.2.4.




Figure 28 Implementation language chosen by each model, as a percentage of runs. Models are free to choose any language; preferences vary significantly across models.

Models exhibit distinct language preferences, ranging from Python-dominant to broadly distributed. Since models are free to choose any language for their reimplementation, we examine which languages each model gravitates toward. Figure 28 shows the breakdown across all runs. GPT 5.4 is the most skewed, writing 79% of its solutions in Python, while Gemini 3.1 Pro and Gemini 3 Flash also lean heavily toward Python (56% and 43%). Claude Opus 4.7 and Opus 4.6 instead favor Rust and Go, with Python accounting for only 14% and 20% of their runs respectively. Sonnet 4.6 produces the most balanced distribution, with meaningful fractions across Rust, Go, Python, and C/C++. These preferences likely reflect differences in training data composition and instruction tuning rather than task-level signals, as the same tasks elicit different language choices from different models.




Figure 29 LoC ratio (model / reference) per model for solutions passing ≥75% of tests. Dashed line marks parity.




Figure 30 LoC ratio by reference language for solutions passing ≥75% of tests. C/C++ references see the largest gap, while Rust references are closest to parity.

Model solutions are consistently shorter than the reference, but the gap varies across models. We compare the lines of code in model solutions to the reference codebase for runs passing at least 75% of tests, to understand how much code models need to reproduce equivalent functionality. Figure 29 shows the LoC ratio per model. All models fall well below parity (the dashed line at 1.0), with medians ranging from roughly 0.15 for Gemini Flash and GPT 5.4 to 0.35 for Opus 4.7 and Sonnet 4.6. The wide whiskers for Opus 4.7, Opus 4.6, and Sonnet 4.6 indicate that these models occasionally produce solutions approaching or exceeding the reference in length, while Gemini Flash and GPT 5.4 are tightly concentrated at the low end.

The LoC ratio gap is largest for C/C++ references and smallest for Rust. We further break down LoC ratios by reference language to disentangle language-level effects. Figure 30 shows the results. C/C++ references exhibit the lowest ratios, with a median around 0.2, consistent with models frequently rewriting these tasks in higher-level languages like Python. Rust references are closest to parity, with a median near 0.5 and several outliers exceeding 1.0, likely because models that stay in Rust retain similar verbosity to the original. Go falls in between, with a median around 0.4.

Higher-scoring solutions tend to contain more code, but code volume alone does not guarantee high scores. We plot test pass rate against model code lines to examine whether there is a relationship between solution size and performance. Figure 31 shows the result across all 1,788 runs on a log-scaled y-axis. At the low end of the score spectrum, solutions span a wide range of sizes, from under 10 lines to over 10,000. As pass rates increase, the floor rises: solutions scoring above 75% cluster between roughly 200 and 10,000 lines, suggesting that a minimum level of implementation completeness is necessary to pass most tests. However, many large solutions still score poorly, and the overall relationship is noisy.




Figure 31 Test pass rate vs. model code lines across all 1,800 runs. Points are colored by model.

C Miscellaneous

C.1 Repository Index

Table 12 provides a complete listing of all 200 repositories included in ProgramBench, along with a brief description of each project's functionality, its difficulty score, and difficulty label (Easy, Medium, or Hard) as defined in §A.4. As a reminder, the thresholds are: Easy (<2), Medium ($2 \leq$ score < 4), and Hard ($\geq$4). Task difficulty scores fall in the range of 0 to 10.

Repository	Description	Score	Difficulty
abishekvashok/cmatrix	Terminal screensaver that simulates the falling text from The Matrix	1.8	Easy
agourlay/zip-password-finder	Brute-force password recovery tool for protected ZIP archives	2.3	Medium
ajeetdsouza/zoxide	A smarter cd command. Supports all major shells.	2.6	Medium
alecthomas/chroma	A general purpose syntax highlighter in pure Go	2.8	Medium
alexpovel/srgn	Syntax-aware code search and replacement tool supporting multiple languages	3.7	Medium
altdesktop/i3-style[†]	Applies color themes to i3 window manager configuration files	2.1	Medium
ammarabouzor/tui-journal	Terminal-based journaling application with a text user interface	3.4	Medium
anordal/shellharden	Bash syntax analyzer that suggests quoting and safety corrections	1.6	Easy
antonmedv/fx	Terminal-based JSON viewer and interactive processor	3.4	Medium
antonmedv/walk	Terminal file manager with interactive directory navigation	2.3	Medium
ariga/atlas	Declarative database schema migration tool using schema-as-code workflows	4.2	Hard
arq5x/bedtools2	bedtools - the swiss army knife for genome arithmetic	3.0	Medium
arthursonzogni/json-tui	Terminal user interface for browsing and navigating JSON data	1.8	Easy
ast-grep/ast-grep	A CLI tool for code structural search, lint and rewriting. Written in Rust	4.5	Hard

Continued on next page

Repository	Description	Score	Difficulty
astaxie/bat	Go-based HTTP client for the command line, similar to cURL	1.3	Easy
astro/deadnix	Static analyzer that detects unused code in Nix expressions	2.2	Medium
axodotdev/oranda	Static site generator for creating landing pages for developer tools	3.7	Medium
bellard/quickjs	Public repository of the QuickJS Javascript Engine.	3.0	Medium
bensadeh/tailspin	Log file viewer with syntax highlighting for common patterns	3.1	Medium
blacknon/hwatch†	File-watching alternative to the watch command that records and diffs output history	3.4	Medium
blake3-team/blake3	the official Rust and C implementations of the BLAKE3 cryptographic hash function	3.3	Medium
bootandy/dust	Disk usage analyzer that displays directory sizes as a visual tree	2.9	Medium
boyter/scc	Sloc, Cloc and Code: scc is a very fast accurate code counter with complexity calculations and COCOMO estimates written in pure Go	4.6	Hard
brocode/fblog	Command-line viewer for JSON-formatted log files	2.3	Medium
burntsushi/ripgrep	Fast recursive regex search tool that respects gitignore rules	3.7	Medium
burntsushi/xsv	High-performance command-line toolkit for working with CSV files	3.0	Medium
byron/dua-cli	Disk usage analyzer with interactive mode for reviewing and deleting files	3.3	Medium
canop/broot	Terminal-based directory tree navigator and file manager	4.3	Hard
canop/rhit	Nginx log file analyzer and statistics viewer	2.8	Medium
cheat/cheat	cheat allows you to create and view interactive cheatsheets on the command-line. It was designed to help remind *nix system administrators of options for commands that they use frequently, but not frequently enough to remember.	4.5	Hard
chirlu/sox	SoX, Swiss Army knife of sound processing	2.8	Medium
chmln/handlr†	Command-line tool for managing default applications on Linux via MIME types	2.3	Medium
chmln/sd	Command-line find-and-replace tool designed as a simpler alternative to sed	2.1	Medium
clog-tool/clog-cli	Changelog generator that parses conventional Git commit messages	1.5	Easy
cmatsuoka/figlet	Generates large ASCII art text banners from input strings	1.8	Easy
codesnap-rs/codesnap	Generates stylized code snippet images from source files	3.3	Medium
cordx56/rustowl	Visualizes ownership and lifetime annotations in Rust source code	3.3	Medium
crowdagger/crowbook	Converts Markdown books to HTML, LaTeX, PDF, and EPUB formats	3.4	Medium
cslarsen/jp2a	Converts JPEG images to ASCII art for terminal display	1.7	Easy
cweill/gotests	Generates Go test function boilerplate from source code signatures	2.5	Medium
dalance/amber	Command-line code search and replacement tool with regex support	2.9	Medium

Continued on next page

Repository	Description	Score	Difficulty
dandavison/delta	Syntax-highlighting pager for git diff, grep, and blame output	4.0	Hard
danmar/cppcheck	Static analysis tool for detecting bugs in C and C++ code	3.9	Medium
direnv/direnv	Automatically loads and unloads environment variables per directory	2.5	Medium
doxygen/doxygen	Documentation generator for C++, C, Java, and other languages	5.1	Hard
drew-alleman/datasurgeon	Extracts structured data such as IPs, emails, and hashes from text	2.0	Easy
ducaale/xh†	Command-line HTTP client with a user-friendly interface	3.8	Medium
duckdb/duckdb	DuckDB is an analytical in-process SQL database management system	4.7	Hard
dundee/gdu	Fast interactive disk usage analyzer with a terminal interface	3.5	Medium
ecumene/rust-sloth	Software 3D rasterizer that renders graphics in the terminal	2.5	Medium
ekzhang/bore†	CLI tool for creating network tunnels to expose localhost to the internet	2.1	Medium
eliukblau/pixterm	Renders images in the terminal using ANSI true color escape sequences	1.7	Easy
elkowar/pipr	Interactive tool for incrementally building Unix shell pipelines	2.6	Medium
epistates/treemd	Terminal Markdown viewer with tree-based structural navigation	3.9	Medium
eradman/entr	Runs specified commands automatically when watched files change	1.3	Easy
esubaalew/run	Universal multi-language script runner and REPL	3.3	Medium
eudoxia0/hashcards	Plain-text spaced repetition flashcard system for the command line	3.1	Medium
facebook/zstd	Fast lossless compression algorithm and library by Facebook	3.2	Medium
facebookresearch/fasttext	Library for fast text representation and classification.	2.2	Medium
ffmpeg/ffmpeg	Multimedia framework for encoding, decoding, transcoding, and streaming audio and video	4.2	Hard
filosottile/age	A simple, modern and secure encryption tool (and Go library) with small explicit keys, no config options, and UNIX-style composability.	3.0	Medium
foriequal0/git-trim	Automatically deletes local Git branches whose remote refs are merged or deleted	2.9	Medium
gabotechs/dep-tree	Visualizes source code file dependencies as a 3D force-directed graph	3.4	Medium
ggreer/the_silver_-searcher	Fast code search tool similar to ack, optimized for large codebases	2.6	Medium
git-bahn/git-graph	Displays Git commit history as a formatted branching graph	2.9	Medium
go-critic/go-critic	Opinionated Go source code linter for style and correctness auditing	3.6	Medium
google/brotli	Brotli compression format	2.9	Medium
gromacs/gromacs	Public/backup repository of the GROMACS molecular simulation toolkit.	5.6	Hard

Continued on next page

Repository	Description	Score	Difficulty
guumaster/hostctl†	Command-line tool for managing /etc/hosts file entries by profile	2.7	Medium
hairyhenderson/gomplate	Command-line template rendering tool supporting multiple data sources	4.0	Hard
halitechallenge/halite	AI programming competition framework for building game-playing bots	2.9	Medium
hatoo/oha†	HTTP load testing tool with real-time terminal animation	3.6	Medium
hooklift/gowsdl	Generates Go client code from WSDL service definitions	2.0	Medium
hpjansson/chafa	Renders images and animations as character art in the terminal	3.9	Medium
htop-dev/htop†	Interactive terminal-based process viewer and system monitor	4.0	Medium
hush-shell/hush	Unix shell built on the Lua programming language	3.5	Medium
incu6us/goimports-reviser	Go import sorting and code formatting tool	2.5	Medium
ip7z/7zip	7-Zip	3.5	Medium
ismaelgv/rnr	Command-line tool for batch renaming files using regex patterns	2.5	Medium
isona/dirble	Fast web directory and file enumeration scanner	3.0	Medium
ivanceras/svgbob	Convert your ascii diagram scribbles into happy little SVG	3.2	Medium
jarun/nnn	Lightweight and fast terminal file manager	2.2	Medium
jesseduffield/lazygit	Terminal user interface for common Git operations	5.3	Hard
jgm/pandoc	Universal markup converter	3.1	Medium
jhspetersson/fselect	Find files with SQL-like queries	3.9	Medium
johanneskaufmann/html-to-markdown	Converts HTML content to Markdown with configurable rules	3.1	Medium
johnkerl/miller	Command-line tool for processing structured data in CSV, TSV, and JSON formats	5.3	Hard
jonas/tig	Text-mode interface for browsing Git repositories	3.1	Medium
jqlang/jq	Command-line processor for querying and transforming JSON data	3.5	Medium
jrnxf/thokr	Terminal typing speed test with result visualization and history logging	2.1	Medium
junegunn/fzf	General-purpose command-line fuzzy finder for interactive filtering	3.6	Medium
kaushiksrini/parqeye	Terminal tool for inspecting and previewing Parquet file contents	2.7	Medium
kisielk/errcheck	Go linter that detects unchecked error return values	1.8	Easy
konradsz/igrep	Interactive grep tool with a terminal user interface	2.6	Medium
ksxgithub/parallel-disk-usage	Parallelized directory tree size analyzer for fast disk usage reporting	3.4	Medium
kyoh86/richgo	Enriches Go test output with color and formatting decorations	2.3	Medium
kyoheiu/felix	Terminal file manager with Vim-style key bindings	3.2	Medium
lfos/calcurse	Text-based calendar and scheduling application for the terminal	2.5	Medium

Continued on next page

Repository	Description	Score	Difficulty
lh3/seqtk	Toolkit for processing sequences in FASTA/Q formats	1.5	Easy
lua/lua	Reference implementation of the Lua programming language interpreter	2.7	Medium
luajit/luajit	High-performance just-in-time compiler for the Lua programming language	3.0	Medium
lymphatus/caesium-clt	Command-line image compression tool supporting lossy and lossless modes	2.4	Medium
lz4/lz4	Extremely fast lossless compression algorithm and library	2.5	Medium
madler/pigz	Parallel implementation of gzip for multi-core processors	2.0	Medium
mfridman/tparse	Summarizes and formats Go test output for terminals and CI pipelines	2.3	Medium
mgdm/htmlq	Command-line tool for extracting content from HTML using CSS selectors	1.5	Easy
mgechev/revive	Fast and configurable Go linter as a drop-in replacement for golint	3.6	Medium
mibk/dupl	Detects duplicate code fragments in Go source files	1.3	Easy
mikefarah/yq	yq is a portable command-line YAML, JSON, XML, CSV, TOML, HCL and properties processor	4.0	Hard
miserlou/loop†	Command-line utility for repeating commands with intervals and counters	1.6	Easy
mkj/dropbear†	Lightweight SSH server and client implementation	4.0	Medium
mookid/diffr	Side-by-side diff viewer with word-level highlighting	2.0	Medium
multiprocessio/dsq	Runs SQL queries against JSON, CSV, Excel, and Parquet files from the command line	1.9	Easy
nachoparker/dutree	Disk usage analyzer that displays results as a colored directory tree	1.7	Easy
naggie/dstask	Git-backed terminal task and note manager with Markdown support	3.0	Medium
nikoladucak/caps-log	Terminal-based journaling application with a calendar interface	3.0	Medium
nikolassv/bartib	Command-line time tracker that stores activity logs as plain text	2.5	Medium
ninja-build/ninja	Small and fast build system focused on incremental compilation speed	3.0	Medium
noborus/ov	Feature-rich terminal pager for viewing text files and command output	3.9	Medium
noborus/trdsql	Executes SQL queries on CSV, JSON, YAML, and other tabular file formats	3.4	Medium
nukesor/pueue	Manage your shell commands.	4.0	Medium
nuta/nsh	POSIX-compatible command-line shell with fish-like interactive features	3.3	Medium
o2sh/onefetch	Displays Git repository summary and statistics in the terminal	3.2	Medium
ogham/dog†	Command-line DNS lookup client with colorized output	2.9	Medium
oppiliappan/eva	Terminal calculator REPL similar to bc with expression evaluation	2.0	Medium
oppiliappan/statix	Linter and diagnostic tool for the Nix programming language	3.0	Medium

Continued on next page

Repository	Description	Score	Difficulty
orf/gping[†]	Ping utility that displays response times as a live terminal graph	2.4	Medium
osgeo/gdal	GDAL is an open source MIT licensed translator library for raster and vector geospatial data formats.	5.4	Hard
osgeo/proj	PROJ - Cartographic Projections and Coordinate Transformations Library	4.4	Hard
paradigmxyz/solar	Modular Solidity compiler written in Rust for fast compilation	5.2	Hard
parcel-bundler/lightningcss	High-performance CSS parser, transformer, bundler, and minifier	4.5	Hard
peco/peco	Interactive line filtering tool for terminal pipelines	3.2	Medium
pemistahl/grex	Generates regular expressions from user-provided example strings	3.1	Medium
php/php-src	Source code of the PHP programming language interpreter	5.1	Hard
pier-cli/pier	Organizes and runs short reusable shell scripts from a central registry	2.3	Medium
pls-rs/pls	Modern directory listing tool with formatting and metadata display	3.1	Medium
psampaz/go-mod-outdated	Reports outdated dependencies in Go module projects	1.1	Easy
quinn-rs/quinn[†]	Async-compatible QUIC protocol implementation in Rust	4.2	Hard
raviqqe/muffet[†]	Fast recursive website link checker for detecting broken URLs	2.9	Medium
rbakbashev/elfcat	Visualizes ELF binary structure by generating annotated HTML output	1.4	Easy
rcoh/angle-grinder	Slice and dice logs on the command line	3.4	Medium
rhysd/kiro-editor	Small terminal text editor with UTF-8 support written in Rust	2.7	Medium
riquito/tuc	Column-cutting tool with advanced field selection beyond cut	2.9	Medium
robertdavidgraham/masscan[†]	Asynchronous TCP port scanner capable of scanning the entire internet rapidly	2.8	Medium
rochacbruno/marmite	Static site generator that builds blogs from Markdown files	3.7	Medium
rs/curlie[†]	Command-line HTTP client combining curl functionality with a simpler interface	1.5	Easy
rs/jplot	Real-time JSON and expvar data plotting tool for iTerm2	2.0	Easy
rust-embedded/svd2rust	Generates Rust register map structs from SVD hardware description files	3.3	Medium
rust-ethereum/ethabi	Encodes and decodes Ethereum smart contract ABI invocations	3.2	Medium
rust-lang/mdbook	Generates online books from Markdown source files	3.6	Medium
rvben/rumdl	Markdown linter and formatter written in Rust	5.1	Hard
samtools/samtools	Tools (written in C using htslib) for manipulating next-generation sequencing data	3.1	Medium
sayanarijit/xplr	Extensible terminal file explorer with a scriptable plugin system	3.6	Medium
sclevine/yj	Converts between YAML, TOML, JSON, and HCL configuration formats	1.8	Easy

Continued on next page

Repository	Description	Score	Difficulty
segmentio/chamber	CLI tool for managing application secrets via AWS SSM Parameter Store	3.1	Medium
sharkdp/bat	A cat(1) clone with wings.	5.6	Hard
sharkdp/fd	Fast and user-friendly alternative to the find command	3.2	Medium
sharkdp/hexyl	Command-line hex viewer with colored output	2.5	Medium
sharkdp/hyperfine	A command-line benchmarking tool	3.0	Medium
sharkdp/pastel	Command-line tool for generating, converting, and manipulating colors	2.8	Medium
shashwatah/jot	Minimal command-line note-taking tool for quick capture	2.0	Medium
sheepla/pingu	Ping wrapper that displays results with a Pingu-themed animation	0.9	Easy
sibprogrammer/xq	Command-line XML and HTML formatter and content extractor	2.2	Medium
sigoden/argc	A Bash CLI framework, also a Bash command runner.	3.4	Medium
simeg/eureka	CLI tool for quickly capturing and storing ideas from the terminal	2.3	Medium
sirwart/ripsecrets	Pre-commit scanner that prevents secret keys from entering source code	2.0	Easy
sitkevij/hex	Command-line hex dump viewer written in Rust	2.0	Medium
skeema/skeema	Declarative schema management tool for MySQL and MariaDB using pure SQL	4.3	Hard
sqlite/sqlite	Official Git mirror of the SQLite source tree	3.7	Medium
sstadick/hck	Fast column-extraction tool as an alternative to cut	2.8	Medium
stacked-git/stgit	Manages a stack of patches on top of Git branches	4.0	Hard
stathissideris/ditaa	ditaa is a small command-line utility that can convert diagrams drawn using ascii art ('drawings' that contain characters that resemble lines like | / -), into proper bitmap graphics.	2.1	Medium
stranger6667/jsonschema	High-performance JSON Schema validation library for Rust	4.3	Hard
svenstaro/genact	A nonsense activity generator	2.9	Medium
svenstaro/miniserve†	Simple command-line HTTP file server for quick local file sharing	3.5	Medium
tarka/xcp	Extended file copy tool with progress display and parallel operations	2.9	Medium
thezoraiz/ascii-image-converter	Converts images to ASCII and Braille art for terminal display	2.4	Medium
tinycc/tinycc	Unofficial mirror of mob development branch	3.1	Medium
tomarrell/wrapcheck	Go linter that checks whether errors from external packages are wrapped	2.5	Medium
tomnomnom/gron	Make JSON greppable!	2.2	Medium
trasta298/keifu	Terminal interface for navigating and visualizing Git commit graphs	2.9	Medium
tree-sitter/tree-sitter	Incremental parsing library for building syntax-aware programming tools	3.0	Medium

Continued on next page

Repository	Description	Score	Difficulty
tstack/lnav	Log file navigator	4.7	Hard
tukaani-project/xz	XZ Utils data compression tools and liblzma library	3.5	Medium
typst/typst	Markup-based typesetting system for producing documents and publications	5.2	Hard
unhappychoice/gittype	Terminal typing game that uses source code as typing challenges	4.6	Hard
universal-ctags/ctags	A maintained ctags implementation	4.2	Hard
wfxr/code-minimap	Renders a scrollable code minimap in the terminal	1.5	Easy
wfxr/csview	Terminal CSV viewer with column alignment and Unicode support	1.9	Easy
wgunderwood/tex-fmt	Fast LaTeX source code formatter written in Rust	2.7	Medium
wintermute-cell/ngrrram	Terminal typing practice tool for learning keyboard layouts	1.9	Easy
xampprocky/tokei	Counts lines of code, comments, and blanks across programming languages	3.2	Medium
xorg62/tty-clock	Digital clock displayed in the terminal using ncurses	0.9	Easy
y2z/monolith[†]	Saves complete web pages as a single self-contained HTML file	3.3	Medium
yaa110/nomino	Batch file renaming utility with regex and template support	2.3	Medium
yassinebridi/serpl	Terminal interface for interactive search and replace across files	3.2	Medium
yoav-lavi/melody	Language that compiles to regular expressions for improved readability	3.0	Medium
ys-l/flamelens	Terminal-based flamegraph viewer for performance profile analysis	2.6	Medium
zevv/duc	Disk usage analysis tool suite with multiple visualization options	3.3	Medium
zk-org/zk	Command-line tool for managing a plain text Zettelkasten note collection	3.7	Medium

Table 12 Complete list of repositories in ProgramBench with brief descriptions and difficulty scores. [†] Networking tool; tested over localhost (see §A.2.4).