	Page No.: Date: / /
07	What would be output of following code
	# include <stdio.h></stdio.h>
	10/08 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Horney	& blue, sed, yellow 3;
1111	main () she getter and in the called all a contractions
	& enym color c;
	C=yellow;
	print("xd" c); 3 Smaller the life (v
	(2) justing the second
<u>(11)</u>	#include < stdro-h>
	enym hello
, 18	& 9, b, cg; 3;
	main()
	f enum hello mi
	printf ("1.d" m); 13" 1 (h)
	Syntax error (2;)
	Compared to the office of the Same of the
(iii)	Hindude <stdio-n></stdio-n>
	engin hello Kronde shilling H. 161
-	$\{a_1b = 99, c_1d = -13\}$
	main()
	{ enum hello m;
	printf ("rannyd my. dn. rd m", q.b, qid);
	2 danier
	As 5 0 (Impasio ham) Stains
	99
	100

į V) Pick incorrect statement wat enums.	
	Two enums connot have some value	· ; 57 3
	b) Only integer constants are allowed in envi	
	c) It is not possible to change value of enum	Symbols
	d) Enum variables are automotically assigned v	alues
	if no value is specified	
	i wilder -	
V) #include < stolio.n>	
	enum eanfoundry	k -
	اکی	
	a=2, b=3.56	Kir .
	3;	
	enum santoundry s;	
	main()	
	in alle or as &	
	3 printf ("%d%d", a,b);	N
	3	-
0	Ans error sice 3.50 je not an integer	
	Crephtes abusin	
VI	# include 2stdio.n>	
1	enum days	4
	A Common	1
	a, b, c	
	13; 13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
	main()	
	7	•
	printf ("1.d", size of (m);	
	My 4.	

	Date. 1 1
(11)	#include < stdio-h>
V-1/-	enam sanfoundry
	8
	a, b, c = c
	J;
	enum sanfoundry s;
	int main()
	£ .
1	of print to ("Y. d", c) in a show up ab wall (1)
	return 0;
	3
	A 5 Canal took 200
V114	If a function reseives a reference to avariable
-	can it modify the value of the variables?
	a) yes
	D'ue connot pass reference to a variable
	d) reference carnot contain function.
	or gerevene constitutions.
'(x).	Références con be NULL?
	a) References has constant value O
	a) References has constant value o
	c) Yus
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ut) No

	Date: / /
×,	How many objects reference can refer
	during it's lifetime?
	ome and
	(S)
	5) 2
	U3
	D4
(11	How do you create a variable with the floating
	number = 2-8
	Ans float num = 2.8+;
(IIX	using namespace stdj
	True it is orifice the sailed for marity is
	int main()
	7
	int m=11)
	m + = 1 - 1 - 1
	Cout < mi
1940 64 4 ()	return 0;
5	(12) "I sull so not reported in "
	the confidence of the contract
	with transform the same of the

CILIX	# include 2 iostream>
A	using namespace stoj
	int main()
	of the state of th
	int m=(;
	if(m==2);
	Cout << "Mi";
	if (m == 2); (out <2 "Hello";
	veturn 0;
	3
	Hitello
	y
w 4	