

Legacy and current methods differ at six layers

Layer	Legacy prototype	Current completed run	Impact and remaining limit
Data	12 normal sequences 1 source video	Stage 0: 75 sequences / 18 videos Stage 4: 159 sequences / 35 videos	Broader support, but added-normal provenance can still be a shortcut
Targets	10 eligible landmark identities	12 identities from shoulders through feet uniform batch-safe draw; no motion score	Heels restored; rule is explicit realized fraction is not fixed at 0.60
Objective	Centered, sharpened latent cross-entropy	JEPA + 0.05 VICReg + 0.25 group group term starts after Stage 0	Active anti-collapse pressure added later stages are label-informed
Training	Normal-only checkpoint	Normal first, then four condition stages with condition-balanced replay	One continuing 600-epoch model normal anchor still drifted to 0.617
Artifacts	Loose filename-based reuse	Lineage, cohort, configuration, and fingerprint are recorded	Reject incomplete, stale, wrong-mode, or mixed-fingerprint artifacts
Evaluation	Single video-confounded 47/21 comparison	A1, A2, grouped-RF Lane C, plus missingness and exposure audits	Claims are narrower; no lane yet retrains the encoder outside test videos

The rows must be interpreted together. The accuracy change cannot be assigned to any single row without a controlled ablation.