



# Build fast. Build right.

Composable framework for building advanced applications with stability and flexibility.



## Romuald Brillout

- Creator of Vike and Telefunc (tRPC alternative)
- Half German/French, grew up in Paris
- Computer Science at KIT (Karlsruhe, Germany)
- Lives in Munich

Intro  
●○○○

Hooks  
○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○



## Vite

webpack alternative



## Vike

Next.js/Nuxt alternative

Intro  
○●○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○

# Status quo

Frontend frameworks:

- Tightly coupled with UI framework (e.g. Next.js  $\Leftrightarrow$  React, Nuxt  $\Leftrightarrow$  Vue)
- Impose their priorities (e.g. Next.js Server Components)
- 100% "free"  $\Rightarrow$  skewed interests

Unstable  $\Rightarrow$  but stability is crucial for large projects:

- Shouldn't be forced complex refactors
- Should adopt new technology at their own pace
- Should be able to adopt new technology progressively

## Vike

A fundamentally new approach.

Intro  
○○●○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○



# vite-plugin-ssr

Like Next.js/Nuxt but as do-one-thing-do-it-well Vite plugin.

- Started vite-plugin-ssr in 2021
  - Vite's early days (before its meteoric rise)
  - Idea: Powerful low-level hooks ⇒ full control over integration
- Renamed to Vike
  - For "street cred"
  - Extensions: vike-react / vike-vue / vike-solid (and more)

```
// pages/hello/+Page.jsx
// Environment: client and/or server

export function Page(pageContext) {
  return <h1>Hello c't webdev</h1>
}
```

Intro  
○○○○○

Hooks  
●○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○

```
// pages/+onRenderHtml.js
// Environment: server

import ReactDOMServer from 'react-dom/server'

export function onRenderHtml(pageContext) {
  const { Page } = pageContext
  const pageHtml = ReactDOMServer.renderToString(<Page/>)
  return `
    <html>
      <body>
        <div id="root">${pageHtml}</div>
      </body>
    </html>`
}
```

```
// pages/+onRenderClient.js
// Environment: client

import ReactDOMClient from 'react-dom/client'

export function onRenderClient(pageContext) {
  const { Page } = pageContext
  ReactDOMClient.hydrateRoot(
    document.getElementById('root'),
    <Page/>
  )
}
```

```
// Doesn't depend on Node.js (e.g. can be used in Cloudflare Workers)
import { renderPage } from 'vike/server'

// Any server: Express.js, Cloudflare Worker, AWS Lambda Function, Fastify, Hono, Nitro, ...
server.addMiddleware({
  method: 'GET',
  route: '*', // catch-all
  async handler(request) {
    const pageContextInit = { urlOriginal: request.url }
    const pageContext = await renderPage(pageContextInit)
    // `body` is the HTML of the page with a route matching pageContextInit.urlOriginal
    const { body, statusCode, headers } = pageContext.httpResponse
    const response = { body, statusCode, headers }
    return response
  }
})
```



```
// pages/+onCreateGlobalContext.server.js
// Environment: server
export async onCreateGlobalContext() {
  const dataFromAPI = await fetchDataFromAPI()
  const someGlobalData = select(dataFromAPI)
  globalContext.someGlobalData = someGlobalData
}
```

```
// pages/+config.js
export default {
  passToClient: 'someGlobalData'
}
```

```
// Anywhere (client,server)
import { getGlobalContext } from 'vike'
const { someGlobalData } = await getGlobalContext()
```

- `+data.js`
  - Data fetching
- `+onCreateGlobalContext.client.js`
  - Client-side initialization (e.g. authentication)
  - Init store (e.g. Redux or Zustand)
- `+onCreatePageContext.{client,server}.js`
- `+guard.js`
  - Authorization
- `+onPageTransition{Start,End}.js`
  - Full control over page transition animation
- `+onBeforeRoute.js`
  - Full control over i18n integration
- ...

# Extensions

- `vike-react`
- `vike-react-rsc` 🚧 (Server Components)
- `vike-react-redux`
- `vike-react-zustand`
- `vike-react-query`
- `vike-react-apollo`
- ...

More: `vike-vue`, `vike-vue-pinia`, `vike-vue-query`, `vike-solid`, `vike-angular`, ...

# Vike

Stable & flexible core:

- Unopinionated & agnostic  $\Rightarrow$  foundational stability
- Low-level hooks  $\Rightarrow$  powerful flexibility

## Extensions

Powerful extensions:

- Opinionated  $\Rightarrow$  pick extensions  $\Rightarrow$  assemble *your* dream stack
- Minimal yet deep/full-fledged integration

Extensions are "cheap" (to create)  $\Rightarrow$

- Quickly adopts new tech
- Experimental extensions

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○●

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○

## Use case Ecosia

[ecosia.de](https://ecosia.de): Google alternative made in Berlin

- Vue SPA/SSR
- Vue 2 ⇒ Vue 3 progressive migration

## Use case Alignable

[alignable.com](https://alignable.com): business owner networking platform

- Backend: Ruby on Rails
- React + SSR
- Mixed: some pages with Ruby, some with Vike

# Use case Contra

[contra.com](https://contra.com): freelance platform (upwork alternative)

- React + SPA/SSR
- Advanced GraphQL Relay integration

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○●○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
○

# Use case Burda

Burda GmbH owns [focus.de](#), [chip.de](#), [bunte.de](#), ...

- Solid (React alternative) + SSR
- **Before:** fragmented stacks
  - ⇒ cannot improve all websites at once
- **Now:** Internal company framework powering all websites
  - ⇒ Software architects control stack of all websites
  - ⇒ App code: product developers
- Vike without extensions
  - ⇒ full control over architecture + foundational stability
- `vike-react` is ~1k LoC ⇒ easy to build your own framework

# SPA/SSR/SSG

## SSR/SSG:

- HTML streaming
- Progressive rendering (aka partial hydration)

## SPA/SSG:

- `+prerender` (boolean)  $\Rightarrow$  disable/enable (on page-by-page basis)
- `+ssr` (boolean)  $\Rightarrow$  toggle SSR/SPA (on page-by-page basis)
- `+data.client.js`  $\Rightarrow$  100% client-side data fetching
- SSG redirects
-  SSG dynamic routes (aka SPA fallback)

Easily create SPA like the old days.

$\Rightarrow$  surprisingly hard with other frameworks (but shouldn't!)





Remote Functions. Instead of API.

- RPC (Remote Procedure Call)
- Optional: you case use REST/GraphQL instead
- Simple

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○●○○○○○○○

Business model  
○

Future  
○

Conclusion  
○

```
// CreateTodo.telefunc.ts
// Environment: server

// Telefunc makes onNewTodo() remotely callable
// from the browser.
export { onNewTodo }

import { getContext } from 'telefunc'

// Telefunction arguments are automatically validated
// at runtime, so `text` is guaranteed to be a string.
async function onNewTodo(text: string) {
  const { user } = getContext()

  // With an ORM
  await Todo.create({ text, authorId: user.id })

  // With SQL
  await sql(
    'INSERT INTO todo_items VALUES (:text, :authorId)',
    { text, authorId: user.id }
  )
}
```

Server

```
// CreateTodo.tsx
// Environment: client

// CreateTodo.telefunc.ts isn't actually loaded;
// Telefunc transforms it into a thin HTTP client.
import { onNewTodo } from './CreateTodo.telefunc.ts'

async function onClick(form) {
  const text = form.input.value
  // Behind the scenes, Telefunc makes an HTTP request
  // to the server.
  await onNewTodo(text)
}

function CreateTodo() {
  return (
    <form>
      <input input="text"></input>
      <button onClick={onClick}>Add To-Do</button>
    </form>
  )
}
```

Browser

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○●○○○○○

Business model  
○

Future  
○

Conclusion  
○

## React Router

```
// article/delete.js
// Only a single action per file 😞
export async function action({ request }) {
  const { article_id } = await request.json()
  await db.article.delete({ article_id })
  return Response.json({ success: true })
}

// Article.jsx
export default function Article() {
  const onClick = async () => {
    // Lots of boilerplate 😞
    const res = await fetch("/article/delete", {
      method: "POST",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ article_id })
    })
    const { success } = await res.json()
    if (!success) alert("Deletion failed")
  }
  return <button onClick={onClick}>Delete</button>
}
```

## Vike + Telefunc

```
// Article.telefunc.js
export async function onArticleDelete({ article_id }) {
  await db.article.delete({ article_id })
  return { success: true }
}

// Article.jsx
import { onArticleDelete } from './article.telefunc.js'
export default function Article() {
  const onClick = async () => {
    const { success } = await onArticleDelete({ article_id })
    if (!success) alert("Deletion failed")
  }
  return <button onClick={onClick}>Delete</button>
}
```

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○●○○○○

Business model  
○

Future  
○

Conclusion  
○

## Next.js ( app/ )

```
// Article.jsx
// Environment: client

import { revalidatePath } from 'next/cache'

export default function Article({ article_id }) {
  async function onArticleDelete() {
    // Environment: server
    'use server'
    // 🙄 Mixed server and client code inside same file
    // 🙄 Magic passing of props
    await db.article.delete({ article_id })
    // 🙄 Complex caching
    revalidatePath('/articles')
  }
  return <button onClick={onArticleDelete}>Delete</button>
}
```

## Vike + Telefunc

```
// Article.telefunc.js
// Environment: server

export async function onArticleDelete({ article_id }) {
  await db.article.delete({ article_id })
}
```

```
// Article.jsx
// Environment: client

import { onArticleDelete } from './article.telefunc.js'
export default function Article({ article_id }) {
  const onClick = () => onArticleDelete({ article_id })
  return <button onClick={onClick}>Delete</button>
}
```

✓ Cache is opt-in

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○●○○○

Business model  
○

Future  
○

Conclusion  
○

# RPC

- Not built-in by design (unlike Remix and Next.js)
- Any RPC tool: Telefunc, tRPC, ...
- Any non-RPC tool: React Query, GraphQL, ...
- Progressive migration from one paradigm to another
  - E.g. progressively migrate from GraphQL to RPC

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○●○○

Business model  
○

Future  
○

Conclusion  
○

npm pnpm yarn bun

>\_ npm create vite@latest --- --react --tailwindcss --daisyui --authjs --telefunc --hono --drizzle --eslint

 Try me in Stackblitz

## Presets

Frontend

Full-stack

Next.js

Nuxt

CMS

## Frontend

### Frontend Framework (required)



Vike


### UI Framework (required)



React




Vue



SolidJS

### CSS




TailwindCSS




Compiled


### UI Component Libraries



daisyUI




shadcn/ui



Mantine

## Data

### Auth



Auth.js



Auth0


### Data fetching



Telefunc




tRPC



ts-rest

### Server



Hono



h3




Express



Fastify

### Database



Drizzle




SQLite



Prisma

## Deployment


### Hosting



Cloudflare



Vercel



Netlify



AWS

## Utilities

### Linter



ESLint




Prettier



Biome


### Analytics



Plausible.io



Google Analytics



Segment

### Error tracking



Sentry



Logrocket

# Details

- Bugs quickly fixed (usually under 24h)
- Deployment skew protection
- Different Base URL for client/server
- `>=400` helpful warnings & error messages
  - Minimal in client-side production to save KBs
- Infinite loop guards
- CSP support
- ...

# Open Source Pricing

- 100% MIT licensed
- 100% gratis for engineers
  - No license needed — works like a regular open source tool
- Only larger companies pay
  - Pesky toaster in dev: Purchase a license at ...
    - Only shown for larger teams (Vike uses a heuristic)
  - Pay only as much you can/want

**It's a feature** ⇒ Vike's interests are aligned with yours.

Intro  
○○○○

Hooks  
○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○

Business model  
●

Future  
○

Conclusion  
○



# Future

- Powerful extensions
  - Full-stack extensions — like Django, Ruby on Rails
  - Full-stack default path
  - Partial eject ⇒ progressive & cherry-picked control

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
●

Conclusion  
○



# Vike

## Why

- ✓ Architecture (foundational stability & flexibility)
- ✓ Next-generation DX
- ✓ Sustainable business model

## Team

- Rom Germany, Munich
- Joël France, Belfort
- Dani Hungary, Lake Balaton
- Muhammad Indonesia, Aceh

# Questions?

Intro  
○○○○

Hooks  
○○○○○○○

Architecture  
○○

Use cases  
○○○

DX  
○○○○○○○○○

Business model  
○

Future  
○

Conclusion  
●