

# Systems Security

## COMSM1500

# STUDENTS: DON'T MISS OUT

THINK AHEAD AND MAKE SURE YOU CAN VOTE IN THE GENERAL ELECTION, 12 DEC 2019



## GET REGISTERED TO VOTE BEFORE 26 NOVEMBER

You only need to register once, but may need to change your details if you have changed your name or moved house.



## TO REGISTER QUICKLY HAVE YOUR NI NUMBER READY

Don't have your National Insurance number? Call **0800 141 2075** or visit **gov.uk/apply-national-insurance-number** ASAP.



## UNSURE IF YOU'LL BE AT YOUR HOME OR TERM-TIME ADDRESS?

You can register at both, but can only vote once in the general election. Register at **gov.uk/register-to-vote** Remember, it is an offence to vote twice.



## CAN'T GET TO YOUR POLLING STATION ON 12 DECEMBER?

Once registered, apply for a postal vote before:

- 5pm on 26 November if you live in England, Scotland or Wales
- 5pm on 21 November if you live in Northern Ireland

Register today | [gov.uk/register-to-vote](https://gov.uk/register-to-vote)

YOUR VOTE MATTERS

DON'T LOSE IT



# Feedback on the unit

- Blackboard
- Unit evaluation (left menu)
- Mid Unit Evaluation Survey (TB1)
- Read instructions and fill the form!



# Access Control

[bristol.ac.uk](http://bristol.ac.uk)



# Access Control

- Physical access control
  - Physical enforcement to access to areas
- Digital access control
  - Restrict access to resources and interactions



# Subjects and Objects


- Object
  - Passive entity that contains information
  - e.g. file, record, memory location etc.
- Access
  - Ability to perform an action on/interact with an object
  - Flow of information between a subject and an object
- Subject
  - Active entity requesting access to an object or data within an object
  - Different subjects have different access levels
  - e.g. users, processes etc.

# Access Control

- Concerned with **authorisation**: what a subject is allowed to do
- **Mediates** a subject access to object
- **Enforces a security policy**, limiting which actions are allowed

# Complete mediation

- That is our aim
- **Trusted computing base**: all hardware and software that is responsible for enforcing the policy
  - For example, OS kernel, all trusted processes, and the PC hardware. A fault in one can compromise security (we have seen many examples).
- Complete mediation is important (if it can be subverted, then use is limited)
- **Reference monitor** concept (all access through it)





# Protection state

- **Security context:** security identity information used to inform authorisation decision.
  - For example, UID and GID associated with a process
- The **protection state** is made up of the security sensitive actions every entity is able to do
  - For example, when a user change identity the protection state has changed
- **Transition** between protection state need to be tightly controlled (e.g. setgid)



# Access Control Matrix

- Simplest way to represent the protection state of a system
- A table representing every subjects and objects, and the permitted type of actions between them

	File 1	File 2	File 3
User A	Read, Write, Own	Read, Write	Read, Write, Own
User B	Append	Read, Write, Own	Read, Write

# What's the fundamental issue here?



# Access Control Matrix

- Could in theory express any possible access control policy
- Only useful in theory...
- In any practical systems there is too many subjects and objects
- ... but any protection state can be expressed this way

	File 1	File 2	File 3
User A	Read, Write, Own	Read, Write	Read, Write, Own
User B	Append	Read, Write, Own	Read, Write

# Access control policy


- Express formally or informally what is allowed
- Generally express confidentiality/integrity requirements

	File 1	File 2	File 3
User A	Read, Write, Own	Read, Write	Read, Write, Own
User B	Append	Read, Write, Own	Read, Write


# Mechanisms and Models

- A **mechanism** how the policy is enforced (think of software/hardware implementation)
  - e.g. SELinux, AppArmor on Linux distributions
- A **model** how to represent policies
  - e.g. access control matrix (this is not a good idea)

# Access Control List



# Capabilities






# Access Control List/Capabilities

- Access Control List
  - Object centric
- Capabilities
  - Subject centric

# Discretionary / Mandatory

- Discretionary: owner of a resource defines/delegates right
  - Requires the notion of owner
  - Most systems
  - Resource owner define associated policy
- Mandatory: policies centrally set by an administrator
  - Notion of owner optional
  - Well suited when an organization own the data (e.g. military government)

# Access Control List




# Access Control List

- On Windows work more or less like this (virtually unlimited list)
- On UNIX: 3 entries Owner, Group, World
- By default owner=creator
- Inheritance rules (objects inherit rules of containers)
  - e.g. files inherit folders permission
- Owner can **revoke** access
- DAC

# UNIX

```
~/syssec/2017$ ls -l
-rw-r--r-- csxdb cosc ... accesscontrol.pdf
-rw-r--r-- csxdb cosc ... systems.pdf
-rw----- csxdb cosc ... exam.pdf
-rwxr-x--- csxdb cosc ... slides.sh
```



owner	group
-------	-------

owner	group	other
-------	-------	-------


read	write	exec
------	-------	------

# Role-based Access Control

[bristol.ac.uk](http://bristol.ac.uk)




## Groups / Roles



# RBAC (NIST)

- RBAC 0: users have a role, role have permission
- RBAC 1: roles can be inherited



- RBAC 2: allows for separation of duties
- RBAC 4: all of the above



# Information Flow Control

[bristol.ac.uk](http://bristol.ac.uk)



# IFC

- read: receiving information from another entity
- write: sending information from another entity
- Concept emerges from US military

# IFC- Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

# IFC- Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

- read:  $f_s(s) \geq f_o(o)$   
–no read up

# IFC- Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

- read:  $f_s(s) \geq f_o(o)$   
–no read up
- write:  $f_s(s) \leq f_o(o)$   
–no write down

# IFC- Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

- read:  $f_s(s) \geq f_o(o)$   
–no read up
- write:  $f_s(s) \leq f_o(o)$   
–no write down
- read/write:  $f_s(s) == f_o(o)$

# Problem with this naïve approach?



# IFC - Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

- Need to add categories!
- $(c, s)$ 
  - $c$  classification
  - $s$  categories
- $f_s(s)$  dominates  $f_o(o)$ 
  - if  $c_s \geq c_o$  MAC
    - e.g. top-secret  $\geq$  secret
  - if  $s_s \supseteq s_o$  DAC
    - e.g. {Iraq, Syria}  $\supseteq$  {Iraq}




# IFC- Bell Lapadula

Top-secret (2)
Secret (1)
Unclassified (0)

- read:  $f_s(s)$  dominates  $f_o(o)$ 
  - no read up
- write:  $f_o(o)$  dominates  $f_s(s)$ 
  - no write down
- read/write:  $f_s(s) == f_o(o)$
- SELinux variant
  - Level per category

# IFC - Bell Lapadula

- Categories have a partial order.
- Form a lattice



# IFC - Biba Model (similar idea for integrity)

Fact (2)
Belief (1)
Rumor (0)

# IFC - Biba Model (similar idea for integrity)

Fact (2)
Belief (1)
Rumor (0)

- read:  $f_s(s) \leq f_o(o)$   
–no read down

# IFC - Biba Model (similar idea for integrity)

Fact (2)
Belief (1)
Rumor (0)

- read:  $f_s(s) \leq f_o(o)$   
–no read down
- write:  $f_s(s) \geq f_o(o)$   
–no write up

# IFC - Biba Model (similar idea for integrity)

Fact (2)
Belief (1)
Rumor (0)

- read:  $f_s(s) \leq f_o(o)$   
–no read down
- write:  $f_s(s) \geq f_o(o)$   
–no write up
- read/write:  $f_s(s) == f_o(o)$

# IFC - Biba Model (similar idea for integrity)

Fact (2)
Belief (1)
Rumor (0)

- read:  $f_s(s) \leq f_o(o)$   
–no read down
- write:  $f_s(s) \geq f_o(o)$   
–no write up
- read/write:  $f_s(s) == f_o(o)$
- Similarly we can add categories

# Brewer and Nash Model


a.k.a Chinese Wall

[bristol.ac.uk](http://bristol.ac.uk)





# Chinese Wall Model




# Chinese Wall Model

O = objects (clients' files)

C = clients

Col(o) = Conflict of Interest Group

x(o): owner, y(o): conflict class Col(o) – x(o)



# Chinese Wall Model

- Define  $n(s, o)$ : has  $s$  ever read  $o$ ?

# Chinese Wall Model

- Define  $n(s, o)$ : has  $s$  ever read  $o$ ?
- $s$  can read  $o$  if:
  - For all  $o'$  such that  $n(s, o') = \text{true}$ ,  $y(o) = y(o')$  or  $y(o) \not\equiv x(o')$
  - $o$  is from the same company as previously read objects or  $o$  belong to a different conflict of interest class

# Chinese Wall Model

- Define  $n(s, o)$ : has  $s$  ever read  $o$ ?
- $s$  can read  $o$  if:
  - For all  $o'$  such that  $n(s, o') = \text{true}$ ,  $y(o) = y(o')$  or  $y(o) \not\in x(o')$
  - $o$  is from the same company as previously read objects or  $o$  belong to a different conflict of interest class
- $s$  can write  $o$  if:
  - $s$  can read  $o$
  - $\nexists o'$  such that  $n(s, o') = \text{true}$  with  $y(o) \neq y(o')$  unless  $x(o') = \emptyset$
  - You can't write client data if reading anyone else data, unless other data have been sanitized

# Chinese Wall Model

- Define  $n(s, o)$ : has  $s$  ever read  $o$ ?
- $s$  can read  $o$  if:
  - For all  $o'$  such that  $n(s, o') = \text{true}$ ,  $y(o) = y(o')$  or  $y(o) \not\in x(o')$
  - $o$  is from the same company as previously read objects or  $o$  belong to a different conflict of interest class
- $s$  can write  $o$  if:
  - $s$  can read  $o$
  - $\nexists o'$  such that  $n(s, o') = \text{true}$  with  $y(o) \neq y(o')$  unless  $x(o') = \emptyset$
  - You can't write client data if reading anyone else data, unless other data have been sanitized
  - Need sanitization/declassification policy
    - Simple example owner can declassify objects they own
    - Authority may declassify audit report etc.

# Clark-Wilson Model

Integrity

[bristol.ac.uk](http://bristol.ac.uk)



# Clark-Wilson Model

- Bank-like context
- Integrity defined as a set of constraints
  - Data in a valid state when it meet constraints
  - Example
    - YB: Yesterday Balance, TD: today deposit, TW: today withdrawal, TB: today balance
    - $TB = YB + TD - TW$
- Well formed transactions
  - Move system to one consistent state to another
- Require separation of duty
  - Who certify transactions
  - Who verify constraints



# Clark-Wilson Model



constrained  
data item



unconstrained  
data item



transformation  
procedure



integrity verification  
procedure

# Clark-Wilson Model

CDI

constrained  
data item

UDI

unconstrained  
data item

TP


transformation  
procedure

IVP

integrity verification  
procedure

- Permission as a triple
  - (user, TP, {CDIs/UDIs})
- e.g. (bob, transfer, hisaccount)
- transfer(CDI:account, UDI:accountref)

# Clark-Wilson Model



## Certification rules

- C1: CDI state validated by IVP
- C2: TPs preserve valid state
- C3: separation of duty
- C4: TPs write to log
- C5: UDIs are validated by TPs

## Enforcement rules

- E1: Only TPs change CDIs
- E2: TPs require authorisation
- E3: All users are authenticated
- E4: only authorised people can change permissions

# Summary

- Many models for different objectives
- ... and there is many more
  - attribute-based access control
  - provenance-based access control
  - etc..
- Different model for different objectives (in theory you could obtain the same access control matrix from two different models)
- They have led to programming pattern
- In practice hard to implement
  - Real world is full of exception and edge cases
  - May get in the way of business

# Thank you

Office MVB 3.26

[bristol.ac.uk](http://bristol.ac.uk)

