

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**

- **Trade name:** ECOCOOL XEP

- **Article number:** 600517366

- **Application of the substance / the preparation** Metal working

- **Manufacturer/Supplier:**

FUCHS LUBRICANTS (UK) PLC.

New Century Street

Hanley

Stoke-on-Trent, Staffordshire, ST1 5HU

UK

Emergency telephone: (UK) 08701 200400

e-mail: product.safety@fuchs-oil.com

- **Further information obtainable from:** Product safety department.

- **Information in case of emergency:** Emergency telephone: (UK) 08701 200400

2 Hazards identification

- **Hazard description:**



Xi Irritant

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 36/38 Irritating to eyes and skin.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**

- **Description:** A blend of highly refined mineral oils with multifunctional additives.

- **Dangerous components:**

	Fatty acid soaps Xi; R 36/38	10-25%
CAS: 68187-80-4	Vegetable oil dialkalonamide Xi; R 36/38	2.5-10%
CAS: 68855-56-1 EINECS: 272-490-6	Alcohols, C12-16 N; R 50	≤ 2.5%
CAS: 39464-69-2	Polyoxyethylene ether phopshate Xi; R 36/38	≤ 2.5%
CAS: 5395-50-6 EINECS: 226-408-0	Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione Xi; R 43	≤ 2.5%
CAS: 55406-53-6 EINECS: 259-627-5	3-Iodo-2-propynylbutylcarbamate Xn, Xi, N; R 20/22-41-50	≤ 2.5%
CAS: 4299-07-4	n-Butyl-1,2-benzisothiazolin-3-one C, N; R 34-43-50/53	≤ 2.5%

- **Additional information:**

For the wording of the listed risk phrases refer to section 16.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

Trade name: ECOCOOL XEP

Contains >0.1=≤5.4% Boric Acid (SVHC List)

(Contd. of page 1)

4 First aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Check for and remove any contact lenses.
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Wash mouth out with water
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
High pressure injection injuries through the skin require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow to penetrate the ground/soil.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
- **Additional information:** No dangerous substances are released.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Prevent formation of aerosols.
Ensure good ventilation/exhaustion at the workplace.
Avoid splashes or spray in enclosed areas.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

Trade name: ECOCOOL XEP

(Contd. of page 2)

- **Further information about storage conditions:**
Protect from frost.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
Select PPE appropriate for the operations taking place taking into account the product properties.
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not carry product impregnated cleaning cloths in trouser pockets.
Do not eat, drink, smoke or sniff while working.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:** Not required.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Safety glasses
Goggles recommended during refilling
- **Body protection:** Oil resistant protective clothing

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	Brown
Odour:	Mineral-oil-like

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point:	> 100°C
-----------------------	---------

· Ignition temperature:	>250°C
--------------------------------	--------

· Self-igniting:	Product is not selfigniting.
-------------------------	------------------------------

· Danger of explosion:	Product does not present an explosion hazard.
-------------------------------	---

· Density at 20°C:	0.94 g/cm ³
---------------------------	------------------------

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

Trade name: ECOCOOL XEP

(Contd. of page 3)

- | | |
|--|---------------|
| · Solubility in / Miscibility with water: | Emulsifiable. |
| · pH-value (80 g/l) at 20°C: | 9.0 |
| · Viscosity: | |
| Kinematic at 40°C: | 109.7 cSt |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:** Strong oxidising agents.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

4299-07-4 n-Butyl-1,2-benzisothiazolin-3-one

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitizing effect by skin contact is possible by prolonged exposure.
- **Additional toxicological information:**

The Control of Substances Hazardous to Health Regulations (COSHH) requires exposure to metalworking fluids by inhalation, ingestion or skin contact to be prevented where reasonably practicable, or failing that, adequately controlled.

Exposure to metalworking fluids can cause irritation of the skin, dermatitis and breathing problems following repeated exposure. Additionally, if not controlled properly, fluid systems that contain water-mixes can become highly contaminated with microorganisms. These organisms, their metabolites and their remains can affect human health if they should enter the breathing zones of workers and other persons leading to chronic respiratory diseases. Such contamination of fluids and associated machinery and pipework must be appropriately monitored and controlled. Direct means of measuring such contamination must be used in conjunction with other relevant checks on fluid quality. Also, systems containing water-mixes must be appropriately cleaned on a regular basis.

Refer to the FUCHS Lubricants guidance "Effective Fluid Monitoring" and "Coolant Management Guide" for further information.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Information about elimination (persistence and degradability):** Inherently biodegradable
- **Behaviour in environmental systems:**
- **Mobility and bioaccumulation potential:** Product is not expected to bioaccumulate.
- **Ecotoxic effects:**

- **Acquatic toxicity:**

4299-07-4 n-Butyl-1,2-benzisothiazolin-3-one

EC50	0.093 mg/kg (daphnia)
------	-----------------------

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

Trade name: ECOCOOL XEP

(Contd. of page 4)

- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation**
 Contact waste processors for recycling information.
 Delivery of waste oil to officially authorized collectors only.
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.
- **European waste catalogue**
 Waste key numbers in accordance with the European Waste catalogue (EWC) are origin-referred defined.
 Since this product is used in several industries, no waste key can be provided by the supplier. The waste key number should be determined in arrangement with your waste disposal partner or the responsible authority.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -

- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No

- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** -

- **Transport/Additional information:** Not dangerous according to the above specifications.

15 Regulatory information

- **Labelling according to EU guidelines:**
 Observe the general safety regulations when handling chemicals.
 The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
 Xi Irritant
- **Risk phrases:**
 36/38 Irritating to eyes and skin.
- **Safety phrases:**
 24/25 Avoid contact with skin and eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- **Special labelling of certain preparations:**
 Contains Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, n-Butyl-1,2-benzisothiazolin-3-one. May produce an allergic reaction.

(Contd. on page 6)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 05.07.2010

Revision: 05.07.2010

Trade name: ECOCOOL XEP

(Contd. of page 5)

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

· Substances of very high concern (SVHC) according to REACH, Article 57	
10043-35-3	Boric acid

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**

- The risk phrases shown below are for those component substances which are listed in section 3 and not for the actual finished formulation.
 - Hazards are concentration dependent. Therefore for the actual hazard classification and risk/safety phrases appropriate for the actual finished formulated product refer to section 15.
 - Please note that, when diluted to the recommended working concentration with water, the work fluid will not be classified as hazardous to health.
- 20/22 Harmful by inhalation and if swallowed.
- 34 Causes burns.
- 36/38 Irritating to eyes and skin.
- 41 Risk of serious damage to eyes.
- 43 May cause sensitisation by skin contact.
- 50 Very toxic to aquatic organisms.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Department issuing MSDS:** Product safety department.
- **Contact:** GORDON SHARP

— GB —