

Product Name: MOBILCUT 140  
Revision Date: 21 Jun 2018  
Page 1 of 12

## SAFETY DATA SHEET

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT

**Product Name:** MOBILCUT 140  
**Product Description:** Base Oil and Additives  
**Product Code:** 2015703010J0, 662114-00, 97BT27  
**Intended Use:** Water-miscible cutting fluid

#### COMPANY IDENTIFICATION

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>Supplier:</b>                      | <b>EXXON MOBIL CORPORATION</b><br>22777 Springwoods Village Parkway<br>Spring, TX 77389 USA         |
| <b>24 Hour Health Emergency</b>       | 609-737-4411                                                                                        |
| <b>Transportation Emergency Phone</b> | 800-424-9300 or 703-527-3887 CHEMTREC                                                               |
| <b>Product Technical Information</b>  | 800-662-4525                                                                                        |
| <b>MSDS Internet Address</b>          | <a href="http://www.exxon.com">www.exxon.com</a> , <a href="http://www.mobil.com">www.mobil.com</a> |

### SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

#### CLASSIFICATION:

Skin irritation: Category 2. Serious eye damage: Category 1.

#### LABEL:

##### Pictogram:



**Signal Word:** Danger

#### Hazard Statements:

H315: Causes skin irritation. H318: Causes serious eye damage.

#### Precautionary Statements:

P264: Wash skin thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves and eye / face protection. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P362 + P364: Take off contaminated clothing and wash it before reuse. P501: Dispose of contents and container in accordance with local regulations.

Product Name: MOBILCUT 140  
Revision Date: 21 Jun 2018  
Page 2 of 12

**Contains:** 3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE); CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester; FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH ETHANOLAMINE

**Other hazard information:**

**HAZARD NOT OTHERWISE CLASSIFIED (HNOC):** None as defined under 29 CFR 1910.1200.

**PHYSICAL / CHEMICAL HAZARDS**

No significant hazards.

**HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. Mists may be irritating to the eyes, nose, throat, and lungs.

**ENVIRONMENTAL HAZARDS**

Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

|                        |           |                 |               |
|------------------------|-----------|-----------------|---------------|
| <b>NFPA Hazard ID:</b> | Health: 3 | Flammability: 1 | Reactivity: 0 |
| <b>HMIS Hazard ID:</b> | Health: 3 | Flammability: 1 | Reactivity: 0 |

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

|                  |                                                 |
|------------------|-------------------------------------------------|
| <b>SECTION 3</b> | <b>COMPOSITION / INFORMATION ON INGREDIENTS</b> |
|------------------|-------------------------------------------------|

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

| Name                                                          | CAS#       | Concentration* | GHS Hazard Codes                                                  |
|---------------------------------------------------------------|------------|----------------|-------------------------------------------------------------------|
| 2-PROPANOL, 1-(2-BUTOXY-1-METHYLETHOXY)-,                     | 29911-28-2 | 1 - < 5%       | H302                                                              |
| 3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE)                       | 66204-44-2 | 1 - < 5%       | H302, H312, H314(1B), H402                                        |
| ALCOHOLS C11-C14-ISO-, C13-RICH                               | 68526-86-3 | 1 - < 5%       | H305, H315, H400(M factor 1), H411                                |
| BORIC ACID, COMPOUND WITH 2-AMINOETHANOL                      | 26038-87-9 | 1 - < 5%       | H315, H319(2A)                                                    |
| CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester                | 55406-53-6 | 0.1 - < 1%     | H302, H317, H331, H318, H372, H400(M factor 10), H410(M factor 1) |
| ETHANOL, 2,2,2-NITRILOTRIS-                                   | 102-71-6   | 1 - < 5%       | None                                                              |
| ETHANOL, 2-(2-BUTOXYETHOXY)-                                  | 112-34-5   | 1 - < 5%       | H319(2A)                                                          |
| FATTY ACIDS, TALL-OIL COMPOUNDS WITH DIISOPROPANOLAMINE       | 68953-28-6 | 1 - < 5%       | H315, H319(2A)                                                    |
| FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH ETHANOLAMINE    | 68440-25-5 | 1 - < 5%       | H315, H318                                                        |
| FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH TRIETHANOLAMINE | 67784-78-5 | 1 - < 5%       | H315, H319(2A)                                                    |

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 3 of 12

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

## **SECTION 4 FIRST AID MEASURES**

### **INHALATION**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

### **SKIN CONTACT**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

### **EYE CONTACT**

Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

### **INGESTION**

First aid is normally not required. Seek medical attention if discomfort occurs.

### **PRE-EXISTING MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY EXPOSURE**

Pre-existing conditions which may be aggravated by exposure include emphysema and asthma.

## **SECTION 5 FIRE FIGHTING MEASURES**

### **EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water

### **FIRE FIGHTING**

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Unusual Fire Hazards:** Pressurized mists may form a flammable mixture. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 4 of 12

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Nitrogen oxides, Oxides of carbon, Smoke, Fume, Sulfur oxides

## FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >100°C (212°F) [ASTM D-92]

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Autoignition Temperature:** >150°C (302°F)

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

### NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

### PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

### SPILL MANAGEMENT

**Land Spill:** Stop leak if you can do it without risk. Do not touch or walk through spilled material. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Seek advice of a specialist. This product emulsifies, disperses or is miscible in water.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### ENVIRONMENTAL PRECAUTIONS

**Large Spills:** Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7

## HANDLING AND STORAGE

### HANDLING

Avoid breathing mists or vapors. Avoid contact with skin. Avoid contact with eyes. Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation.

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 5 of 12

Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

## STORAGE

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

**Exposure limits/standards (Note: Exposure limits are not additive)**

| Substance Name                  | Form                         | Limit / Standard |                     |  | NOTE | Source     |
|---------------------------------|------------------------------|------------------|---------------------|--|------|------------|
| ALCOHOLS C11-C14-ISO-, C13-RICH |                              | TWA              | 50 ppm              |  | N/A  | ExxonMobil |
| ETHANOL, 2,2,2-NITRILOTRIS-     |                              | TWA              | 5 mg/m <sup>3</sup> |  | N/A  | ACGIH      |
| ETHANOL, 2-(2-BUTOXYETHOXY)-    | Inhalable fraction and vapor | TWA              | 10 ppm              |  | N/A  | ACGIH      |

**Exposure limits/standards for materials that can be formed when handling this product:** When mists/aerosols can occur the following is recommended: 5 mg/m<sup>3</sup> - OSHA PEL.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Eye washes and showers for emergency use.

### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Particulate air-purifying respirator approved for dust / oil mist is recommended.

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 6 of 12

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended.

**Eye Protection:** Chemical goggles and face shield are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

|                  |                                         |
|------------------|-----------------------------------------|
| <b>SECTION 9</b> | <b>PHYSICAL AND CHEMICAL PROPERTIES</b> |
|------------------|-----------------------------------------|

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

## GENERAL INFORMATION

**Physical State:** Liquid  
**Color:** Amber  
**Odor:** Characteristic  
**Odor Threshold:** N/D

## IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

**Relative Density (at 15.6 °C):** 0.95  
**Flammability (Solid, Gas):** N/A  
**Flash Point [Method]:** >100°C (212°F) [ASTM D-92]  
**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D  
**Autoignition Temperature:** >150°C (302°F)  
**Boiling Point / Range:** > 100°C (212°F) [Estimated]  
**Decomposition Temperature:** N/D  
**Vapor Density (Air = 1):** > 1 at 101 kPa [Estimated]  
**Vapor Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated]  
**Evaporation Rate (n-butyl acetate = 1):** < 1  
**pH:** 9  
**Log Pow (n-Octanol/Water Partition Coefficient):** N/D

Product Name: MOBILCUT 140  
Revision Date: 21 Jun 2018  
Page 7 of 12

**Solubility in Water:** Emulsifies  
**Viscosity:** [N/D at 40 °C]  
**Oxidizing Properties:** See Hazards Identification Section.

#### OTHER INFORMATION

**Freezing Point:** N/D  
**Melting Point:** N/A  
**Pour Point:** < 0°C (32°F)

### SECTION 10 STABILITY AND REACTIVITY

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Heat/ Freezing temperatures., High energy sources of ignition.

**MATERIALS TO AVOID:** Strong Acids, Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

### SECTION 11 TOXICOLOGICAL INFORMATION

#### INFORMATION ON TOXICOLOGICAL EFFECTS

| <b>Hazard Class</b>                                            | <b>Conclusion / Remarks</b>                                                                                                             |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>                                              |                                                                                                                                         |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.                                                                                 |
| Irritation: No end point data for material.                    | Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs. |
| <b>Ingestion</b>                                               |                                                                                                                                         |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.                                                                                 |
| <b>Skin</b>                                                    |                                                                                                                                         |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.                                                                                 |
| Skin Corrosion/Irritation: No end point data for material.     | Irritating to the skin. Based on assessment of the components.                                                                          |
| <b>Eye</b>                                                     |                                                                                                                                         |
| Serious Eye Damage/Irritation: No end point data for material. | Severely irritating, and may seriously damage eye tissue. Based on assessment of the components.                                        |
| <b>Sensitization</b>                                           |                                                                                                                                         |
| Respiratory Sensitization: No end point data for material.     | Not expected to be a respiratory sensitizer.                                                                                            |
| Skin Sensitization: No end point data for material.            | Not expected to be a skin sensitizer. Based on assessment of the components.                                                            |
| <b>Aspiration:</b> Data available.                             | Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.                                          |

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 8 of 12

|                                                                |                                                                                                                |
|----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>Germ Cell Mutagenicity:</b> No end point data for material. | Not expected to be a germ cell mutagen. Based on assessment of the components.                                 |
| <b>Carcinogenicity:</b> No end point data for material.        | Not expected to cause cancer. Based on assessment of the components.                                           |
| <b>Reproductive Toxicity:</b> No end point data for material.  | Not expected to be a reproductive toxicant.                                                                    |
| <b>Lactation:</b> No end point data for material.              | Not expected to cause harm to breast-fed children. Based on assessment of the components.                      |
| <b>Specific Target Organ Toxicity (STOT)</b>                   |                                                                                                                |
| Single Exposure: No end point data for material.               | Not expected to cause organ damage from a single exposure.                                                     |
| Repeated Exposure: No end point data for material.             | Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components. |

## TOXICITY FOR SUBSTANCES

| NAME                                           | ACUTE TOXICITY                                                                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester | Inhalation Lethality: 4 hour(s) LC50 0.68 mg/l (Aerosol) (Rat); Oral Lethality: LD50 1056 mg/kg (Rat) |

## OTHER INFORMATION

### For the product itself:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations.

Oil Mist (highly refined oils): Animals exposed to high concentrations of mist developed oil retention, inflammation, and oil granulomas in the respiratory tract. Oils exposed to high temperatures, cracking conditions, or mixing with tramp / used oils may introduce polycyclic aromatic compounds or microbial contaminants that could result in cancer or severe respiratory hazards.

### Contains:

Alkanolamines: Repeated overexposure to alkanolamines caused liver and kidney damage in laboratory animals.

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

GLYCOL ETHERS: Some glycol ethers cause adverse effects in animals that include the reproductive system, offspring, blood, kidney and liver.

The following ingredients are cited on the lists below: None.

### --REGULATORY LISTS SEARCHED--

1 = NTP CARC  
2 = NTP SUS

3 = IARC 1  
4 = IARC 2A

5 = IARC 2B  
6 = OSHA CARC

## SECTION 12

## ECOLOGICAL INFORMATION



Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 9 of 12

The information given is based on data available for the material, the components of the material, and similar materials.

#### **ECOTOXICITY**

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

#### **MOBILITY**

Components -- Expected to remain in water or migrate through soil.

#### **PERSISTENCE AND DEGRADABILITY**

##### **Biodegradation:**

Components -- Expected to be inherently biodegradable

#### **BIOACCUMULATION POTENTIAL**

Components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

#### **OTHER ECOLOGICAL INFORMATION**

**VOC:** 75.5 G/L [ASTM E1868-10]

### **SECTION 13**

### **DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### **DISPOSAL RECOMMENDATIONS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

#### **REGULATORY DISPOSAL INFORMATION**

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

### **SECTION 14**

### **TRANSPORT INFORMATION**

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 10 of 12

**LAND (DOT):** Not Regulated for Land Transport

**LAND (TDG):** Not Regulated for Land Transport

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport

| SECTION 15 | REGULATORY INFORMATION |
|------------|------------------------|
|------------|------------------------|

**OSHA HAZARD COMMUNICATION STANDARD:** This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**Listed or exempt from listing/notification on the following chemical inventories:** IECSC, TCSI, TSCA  
**Special Cases:**

| Inventory | Status             |
|-----------|--------------------|
| NDSL      | Restrictions Apply |

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

**CWA / OPA:** This product is classified as an oil under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center at 800-424-8802.

**SARA (311/312) REPORTABLE GHS HAZARD CLASSES:** Serious eye damage or eye irritation, Skin Corrosion or Irritation

**SARA (313) TOXIC RELEASE INVENTORY:**

| Chemical Name                | CAS Number | Typical Value |
|------------------------------|------------|---------------|
| ETHANOL, 2-(2-BUTOXYETHOXY)- | 112-34-5   | 1 - < 5%      |

The following ingredients are cited on the lists below:

| Chemical Name                           | CAS Number | List Citations |
|-----------------------------------------|------------|----------------|
| 3,3'-METHYLENEBIS (5-METHYLOXAZOLIDINE) | 66204-44-2 | 6              |
| DIETHANOLAMINE                          | 111-42-2   | 10             |

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 11 of 12

|                                           |            |               |
|-------------------------------------------|------------|---------------|
| ETHANOL, 2,2,2-NITRILOTRIS-               | 102-71-6   | 1, 16, 17, 18 |
| ETHANOL, 2-(2-BUTOXYETHOXY)-              | 112-34-5   | 1, 17, 18, 19 |
| HYDRO TREATED HEAVY NAPHTHENIC DISTILLATE | 64742-52-5 | 13, 17, 18    |

## --REGULATORY LISTS SEARCHED--

|               |                  |                   |             |
|---------------|------------------|-------------------|-------------|
| 1 = ACGIH ALL | 6 = TSCA 5a2     | 11 = CA P65 REPRO | 16 = MN RTK |
| 2 = ACGIH A1  | 7 = TSCA 5e      | 12 = CA RTK       | 17 = NJ RTK |
| 3 = ACGIH A2  | 8 = TSCA 6       | 13 = IL RTK       | 18 = PA RTK |
| 4 = OSHA Z    | 9 = TSCA 12b     | 14 = LA RTK       | 19 = RI RTK |
| 5 = TSCA 4    | 10 = CA P65 CARC | 15 = MI 293       |             |

Code key: CARC=Carcinogen; REPRO=Reproductive

## SECTION 16

## OTHER INFORMATION



**WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

This warning is given to comply with California Health and Safety Code 25249.6 and does not constitute an admission or a waiver of rights.

N/D = Not determined, N/A = Not applicable

## KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H302: Harmful if swallowed; Acute Tox Oral, Cat 4  
H305: May be harmful if swallowed and enters airways; Aspiration, Cat 2  
H312: Harmful in contact with skin; Acute Tox Dermal, Cat 4  
H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B  
H315: Causes skin irritation; Skin Corr/Irritation, Cat 2  
H317: May cause allergic skin reaction; Skin Sensitization, Cat 1  
H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1  
H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A  
H331: Toxic if inhaled; Acute Tox Inh, Cat 3  
H372: Causes damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 1  
H400: Very toxic to aquatic life; Acute Env Tox, Cat 1  
H402: Harmful to aquatic life; Acute Env Tox, Cat 3  
H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1  
H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

## THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Composition: Component Table information was modified.  
GHS Health Classification information was modified.  
GHS Health Hazards information was modified.  
GHS Health Symbol information was modified.  
GHS Precautionary Statements - Prevention information was modified.  
GHS Precautionary Statements - Response information was modified.  
Hazard Identification: Physical/Chemical Hazard information was added.  
Hazard Identification: Physical/Chemical Hazard information was deleted.

Product Name: MOBILCUT 140

Revision Date: 21 Jun 2018

Page 12 of 12

---

Section 02: GHS Contains for LABEL\_GHS codes information was modified.

Section 06: Protective Measures information was modified.

Section 08: Exposure Limits Table information was modified.

Section 09: Vapor Pressure information was deleted.

Section 11 Acute Toxicity data - Header information was added.

Section 11 Substance Name - Header information was added.

Section 11 Substance Toxicity table - Header information was added.

Section 11 Substance Toxicology table information was added.

Section 11: Other Health Effects information was modified.

Section 11: Skin Sensitization Conclusion information was modified.

Section 12: Ecological Information - Acute Aquatic Toxicity information was added.

Section 12: Ecological Information - Acute Aquatic Toxicity information was deleted.

Section 15: List Citations Table information was modified.

Section 15: SARA (311/312) REPORTABLE GHS HAZARD CLASSES information was added.

Section 15: SARA (311/312) REPORTABLE HAZARD CATEGORIES information was deleted.

Section 16: HCode Key information was modified.

Section 16: Standard phrases for California Proposition 65 information was added.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

Internal Use Only

MHC: 0, 0, 0, 4, 4, 1

PPEC: D

DGN: 7108461XUS (1010628)

---

Copyright 2002 Exxon Mobil Corporation, All rights reserved