



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Marine Rust Preventative Coating
Product Code	99708
MSDS Number	6652
Version #	4.0
Issue date	12-21-2011
Revision date	06-02-2016
Supersedes date	10-04-2013
Product use	Not available.

Supplier Not available.

2. Hazards Identification

Emergency overview DANGER

FLAMMABLE LIQUID AND VAPOR.

Flammable liquid - may release vapors that form flammable mixtures at or above the flash point.

CONTENTS UNDER PRESSURE.

Aerosol. Pressurized container may explode when exposed to heat or flame. Will be easily ignited by heat, spark or flames. Cancer hazard. Irritating to eyes and skin.

Irritating to respiratory system. Mutagen. This is a consumer care product that is safe for consumers when used according to the label directions. Like many consumer products, a small number of individuals may experience reactions such as redness, rash and / or swelling upon prolonged or repeated skin contact or eye contact.

Potential health effects

Routes of exposure

Inhalation. Ingestion. Skin contact. Eye contact.

Eyes

Contact with eyes may cause irritation. Avoid contact with eyes.

Skin

May be harmful if absorbed through skin. May cause skin irritation. Do not get this material in contact with skin.

Inhalation

May cause cancer by inhalation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion

Exposure by ingestion of an aerosol is unlikely. Irritating. May cause nausea, stomach pain and vomiting. Do not ingest.

Target organs

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects

May be harmful if absorbed through skin. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Pregnant women or women of child-bearing age should not be exposed to this product. May cause birth defects. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Signs and symptoms Behavioral changes. Narcosis. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Decrease in motor functions. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Potential environmental effects May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
HEPTANE (N-HEPTANE)	142-82-5	30 - 40
Propane	74-98-6	10 - 30
Solvent Naphtha, Petroleum, Medium Aliphatic	64742-88-7	10 - 15
BUTANE	106-97-8	5 - 10
Isobutane	75-28-5	<10
Calcium Carbonate	471-34-1	1 - 5
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1 - 5
OIL, MINERAL	64741-88-4	1 - 5
Non-hazardous components	CAS #	Percent
OIL, MINERAL	8009-03-8	1 - 5
Other components below reportable levels		7 - 13

Composition comments Not applicable to consumer products.

4. First Aid Measures

First aid procedures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.
Skin contact	Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Never give liquid to an unconscious person.

Notes to physician In case of shortness of breath, give oxygen. Symptoms may be delayed.

General advice In case of shortness of breath, give oxygen. If you feel unwell, seek medical advice (show the label where possible). Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

5. Fire Fighting Measures

Flammable properties Flammable by OSHA criteria. Flammable by WHMIS criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back.

Extinguishing media

Suitable extinguishing media Powder. Alcohol resistant foam. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Protection of firefighters

Specific hazards arising from the chemical Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Explosion data	
Sensitivity to static discharge	Not available.
Sensitivity to mechanical impact	Not available.
Hazardous combustion products	Carbon monoxide and carbon dioxide.

6. Accidental Release Measures

Personal precautions	Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.
Methods for cleaning up	Should not be released into the environment. This product is miscible in water. Stop the flow of material, if this is without risk. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Clean up in accordance with all applicable regulations. For waste disposal, see section 13 of the MSDS.
Other information	Clean up in accordance with all applicable regulations.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using do not eat or drink. Use only in area provided with appropriate exhaust ventilation. Wash thoroughly after handling. Avoid release to the environment.
Storage	Level 3 Aerosol. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Keep out of the reach of children. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS).

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	STEL	1000 ppm	
ETHYLENE GLYCOL	TWA	20 ppm	
MONOBUTYL ETHER (CAS 111-76-2)			
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	500 ppm	

**US. ACGIH Threshold Limit Values
Components**

Components	Type	Value	Form
	TWA	400 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
OIL, MINERAL (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	TWA	1000 ppm	
Calcium Carbonate (CAS 471-34-1)	TWA	10 mg/m3	
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)	TWA	97 mg/m3	
		20 ppm	
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	2050 mg/m3	
	TWA	500 ppm	
		1640 mg/m3	
		400 ppm	
OIL, MINERAL (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
OIL, MINERAL (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
OIL, MINERAL (CAS 8009-03-8)	TWA	5 mg/m3	Mist.
OIL, MINERAL (CAS 64741-88-4)	TWA	5 mg/m3	Mist.
Propane (CAS 74-98-6)	TWA	1000 ppm	
Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Vapor.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	STEL	750 ppm	
	TWA	600 ppm	
Calcium Carbonate (CAS 471-34-1)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)	TWA	20 ppm	
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
Isobutane (CAS 75-28-5)	TWA	1000 ppm	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.

Canada. Manitoba OELs (Reg. 217 / 2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	STEL	1000 ppm	
ETHYLENE GLYCOL	TWA	20 ppm	
MONOBUTYL ETHER (CAS 111-76-2)			
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
OIL, MINERAL (CAS 64741-88-4)	TWA	5 mg/m3	Inhalable fraction.
OIL, MINERAL (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.
Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	TWA	800 ppm	
ETHYLENE GLYCOL	TWA	20 ppm	
MONOBUTYL ETHER (CAS 111-76-2)			
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
Isobutane (CAS 75-28-5)	TWA	800 ppm	
OIL, MINERAL (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
OIL, MINERAL (CAS 64741-88-4)	TWA	5 mg/m3	Mist.
OIL, MINERAL (CAS 8009-03-8)	TWA	5 mg/m3	Mist.
Propane (CAS 74-98-6)	TWA	1000 ppm	
Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
BUTANE (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Calcium Carbonate (CAS 471-34-1)	TWA	10 mg/m3	Total dust.
ETHYLENE GLYCOL	TWA	97 mg/m3	
MONOBUTYL ETHER (CAS 111-76-2)			
		20 ppm	
HEPTANE (N-HEPTANE) (CAS 142-82-5)	STEL	2050 mg/m3	
	TWA	500 ppm	
		1640 mg/m3	
		400 ppm	
OIL, MINERAL (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
OIL, MINERAL (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
OIL, MINERAL (CAS 8009-03-8)	TWA	5 mg/m3	Mist.
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium Carbonate (CAS 471-34-1)	PEL	5 mg/m3	Respirable fraction.
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)	PEL	15 mg/m3 240 mg/m3	Total dust.
HEPTANE (N-HEPTANE) (CAS 142-82-5)	PEL	50 ppm 2000 mg/m3	
OIL, MINERAL (CAS 64741-88-4)	PEL	500 ppm 5 mg/m3	Mist.
OIL, MINERAL (CAS 8009-03-8)	PEL	5 mg/m3	Mist.
OIL, MINERAL (CAS 64741-88-4)	PEL	2000 mg/m3	
Propane (CAS 74-98-6)	PEL	500 ppm 1800 mg/m3 1000 ppm	

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines
Canada - Alberta OELs: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Solvent Naphtha, Petroleum, Medium Aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment
Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Wear suitable protective clothing. Wear protective gloves.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Hand protection

Wear protective gloves.

9. Physical & Chemical Properties

Appearance	Gaseous. Liquid.
Physical state	Liquid.
Form	Aerosol.
Color	Tan.
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Vapor pressure	52.18 hPa estimated
Density	687.50 kg/m ³
Vapor density	Not available.
Boiling point	Not available.
Melting point/Freezing point	-305.68 °F (-187.6 °C) estimated
Solubility (water)	Negligible
Solubility (other)	Oil
Specific gravity	0.69 estimated
Relative density	Not available.
Flash point	-155.2 °F (-104.0 °C) Pensky-Martens Closed Cup
Flammability limits in air, upper, % by volume	9.5 % estimated
Flammability limits in air, lower, % by volume	0.7 % estimated
Auto-ignition temperature	Not available.
VOC	80 %
Evaporation rate	Not available.
Partition coefficient (n-octanol/water)	Not available.
Other data	
Heat of combustion (NFPA 30B)	36 kJ/g estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of explosion.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	Irritants. At thermal decomposition temperatures, carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data		
Product	Species	Test Results
Marine Rust Preventative Coating		
<u>Acute</u>		
Dermal		
LD50	Rabbit	13892 mg/kg estimated
Inhalation		
LC50	Mouse	23333 ppm, 7 Hours estimated
		10667 mg/l, 2 Hours estimated

Product	Species	Test Results
LD50 Oral LD50	Rat	689 mg/l, 1 Hours estimated
		15000 ppm, 4 Hours estimated
		8973 mg/l, 15 Minutes estimated
		261 mg/l, 4 Hours estimated
	Mouse	195 mg/l, 2 Hours estimated
	Guinea pig	40 g/kg estimated
	Mouse	40 g/kg estimated
	Rabbit	11 g/kg estimated
	Rat	24983 mg/kg estimated
Components	Species	Test Results
BUTANE (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Calcium Carbonate (CAS 471-34-1)		
<u>Acute</u>		
Oral		
LD50	Mouse	6450 mg/kg
	Rat	6450 mg/kg
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	400 mg/kg
Inhalation		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
HEPTANE (N-HEPTANE) (CAS 142-82-5)		
<u>Acute</u>		
Inhalation		
LC50	Rat	103 mg/l, 4 Hours
LD50	Mouse	75 mg/l, 2 Hours
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	52 mg/l, 1 Hours
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes

Acute effects	Respiratory tract irritation.
Sensitization	Not available.
Chronic effects	Hazardous by WHMIS criteria. May be harmful if absorbed through skin. Prolonged inhalation may be harmful.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
	Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
Carcinogenicity	Hazardous by WHMIS criteria. Cancer hazard.
ACGIH Carcinogens	
2-BUTOXYETHANOL (EGBE) (CAS 111-76-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.
KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-88-7)	A3 Confirmed animal carcinogen with unknown relevance to humans.
OIL, MINERAL MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 64741-88-4)	A4 Not classifiable as a human carcinogen.
OIL, MINERAL MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, PURE, HIGHLY AND SEVERELY REFINED, INHALABLE FRACTION (CAS 8009-03-8)	A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-BUTOXYETHANOL (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
Skin corrosion/irritation	Not available.
Serious eye damage/irritation	Not available.
Mutagenicity	Not available.
Reproductive effects	Mutagenic effects. May cause reproductive system disorder and/or damage.
Teratogenicity	Not available.
Synergistic materials	Not available.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Product	Species		Test Results
Marine Rust Preventative Coating			
Aquatic			
Fish	LC50	Fish	6047.8003 mg/l, 96 hours estimated
Components	Species		Test Results
Calcium Carbonate (CAS 471-34-1)			
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affinis)	> 56000 mg/l, 96 hours
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
HEPTANE (N-HEPTANE) (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment.		
Environmental effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.		
Aquatic toxicity	Not available.		

Persistence and degradability Not available.

Partition coefficient

BUTANE	2.89
ETHYLENE GLYCOL MONOBUTYL ETHER	0.83
HEPTANE (N-HEPTANE)	4.66
Isobutane	2.76
Propane	2.36

Mobility in environmental media This product is miscible in water.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

TDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	D
Special precautions for user	Read safety instructions, MSDS and emergency procedures before handling.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, MSDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable, MARINE POLLUTANT
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
Special precautions for user	Read safety instructions, MSDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
IATA; IMDG

Not available.



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory Information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status

Controlled

WHMIS classification

B2 - Flammable Liquids
D2A - Other Toxic Effects-VERY TOXIC
D2B - Other Toxic Effects-TOXIC

WHMIS labeling



International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0
Disclaimer	Bel-Ray Company, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Prepared by	Not available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.