

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

SECTION 1. IDENTIFICATION

Product name : WHITE LITHIUM GREASE, 200 g
Product code : 893.870201
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée
Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1
Telephone : 1-800-263-5002
Telefax : 1-905-564-3671
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin sensitization : Sub-category 1A
Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.
H361f Suspected of damaging fertility.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust, fume, gas, mist, vapors or spray.
P272 Contaminated work clothing should not be allowed out of the workplace.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version
3.0

Revision Date:
11/19/2025

SDS Number:
11370330-00003

Date of last issue: 07/03/2025
Date of first issue: 04/11/2024

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P308 + P313 IF exposed or concerned: Get medical attention.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
12-Hydroxy lithium stearate	Octadecanoic acid, 12-hydroxy-, lithium salt (1:1)	7620-77-1	$\geq 5 - < 10$ *
Distillates (petroleum), hydrotreated heavy naphthenic	No data available	64742-52-5	$\geq 5 - < 10$ *
Antimony, dialkyl dithiocarbamate	Antimony Di-amyldithiocarbamate	15890-25-2	$\geq 1 - < 5$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 1 - < 5$ *
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	4-(2,2,3-Trimethylbut-3-en-1-yl)-N-[4-(2,2,3-trimethylbut-3-en-1-yl)phenyl]aniline	68411-46-1	$\geq 0.1 - < 1$ *
Fatty acids, tall-oil, reaction products with diethylenetriamine	Amidation products of tall-oil fatty acids with diethylenetriamine	61790-69-0	$\geq 0.1 - < 1$ *
2,5-Bis(octyldithio)-1,3,4-thiadiazole	2,5-Dimercaptothi-	13539-13-4	$\geq 0.1 - < 1$ *

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version 3.0 Revision Date: 11/19/2025 SDS Number: 11370330-00003 Date of last issue: 07/03/2025
Date of first issue: 04/11/2024

	adiazole deriva- tive		
Hydrocarbon polymer	No data availa- ble	Not Assigned	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Suspected of damaging fertility.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version 3.0 Revision Date: 11/19/2025 SDS Number: 11370330-00003 Date of last issue: 07/03/2025
Date of first issue: 04/11/2024

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m ³	CA AB OEL
		TWA (Inhalable)	10 mg/m ³	CA BC OEL
		TWA (Respirable)	3 mg/m ³	CA BC OEL
		TWAEV (inhalable dust)	10 mg/m ³	CA QC OEL
		TWAEV (respirable aerosol fraction)	3 mg/m ³	CA QC OEL
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Antimony, dialkyl dithiocarbamate	15890-25-2	TWA	0.5 mg/m ³ (antimony)	CA AB OEL
		TWAEV	0.5 mg/m ³ (antimony)	CA QC OEL
		TWA	0.5 mg/m ³ (antimony)	CA BC OEL
		TWA	0.5 mg/m ³ (antimony)	ACGIH
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust)	3 mg/m ³	CA BC OEL

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version 3.0 Revision Date: 11/19/2025 SDS Number: 11370330-00003 Date of last issue: 07/03/2025
Date of first issue: 04/11/2024

		fraction)		
		TWAEV (total dust)	10 mg/m ³	CA QC OEL

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grease

Color : white

Odor : Petroleum, mild

Odor Threshold : No data available

pH : substance/mixture is non-soluble (in water)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Not applicable
Lower explosion limit / Lower flammability limit	:	Not applicable
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	0.889 g/cm ³
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	Not applicable
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Titanium dioxide:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425 Remarks: The test was conducted according to guideline
Acute inhalation toxicity	: LC50 (Rat): > 5.09 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Acute oral toxicity	: LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
---------------------	---

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): 3.08 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

|| Not classified based on available information.

Components:

12-Hydroxy lithium stearate:

Species	: Rabbit
Result	: No skin irritation
Remarks	: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Distillates (petroleum), hydrotreated heavy naphthenic:

Species	:	Rabbit
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Species	:	Rabbit
Result	:	No skin irritation

Titanium dioxide:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
Remarks	:	The test was conducted equivalent or similar to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Mild skin irritation

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 431

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439

Result	:	No skin irritation
--------	---	--------------------

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Skin irritation

Serious eye damage/eye irritation

|| Not classified based on available information.

Components:

12-Hydroxy lithium stearate:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Antimony, dialkyl dithiocarbamate:

Species	:	Rabbit
Result	:	No eye irritation

Titanium dioxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Species	:	Bovine cornea
Method	:	OECD Test Guideline 437

Species	:	Tissue Culture
Method	:	OECD Test Guideline 492

Result	:	Irritation to eyes, reversing within 21 days
--------	---	--

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

|| May cause an allergic skin reaction.

Respiratory sensitization

|| Not classified based on available information.

Components:

12-Hydroxy lithium stearate:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Result : negative
Remarks : Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Titanium dioxide:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in humans

Hydrocarbon polymer:

Assessment : Probability or evidence of skin sensitization in humans

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Germ cell mutagenicity

|| Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: positive Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: The test was conducted according to guideline Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: The test was conducted according to guideline Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: The test was conducted according to guideline
Genotoxicity in vivo	: Test Type: Transgenic rodent somatic cell gene mutation assay Species: Mouse (male) Application Route: Intravenous injection Method: OECD Test Guideline 488 Result: negative Remarks: The test was conducted equivalent or similar to

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

|| guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 490
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Carcinogenicity

|| Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse
Application Route : Skin contact
Exposure time : 78 weeks
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

|| Suspected of damaging fertility.

Components:

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Titanium dioxide:

Effects on fertility : Test Type: Extended one-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

STOT-single exposure

|| Not classified based on available information.

STOT-repeated exposure

|| Not classified based on available information.

Components:

12-Hydroxy lithium stearate:

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

12-Hydroxy lithium stearate:

Species : Rat
NOAEL : > 88 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rat
NOAEL : > 0.98 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Remarks : Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Species	: Rat
NOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 54 Days
Method	: OECD Test Guideline 422

Titanium dioxide:

Species	: Rat
NOAEL	: $\geq 1,000$ mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species	: Rat
NOAEL	: 25 mg/kg
LOAEL	: 75 mg/kg
Application Route	: Ingestion
Exposure time	: 53 Days
Method	: OECD Test Guideline 422

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species	: Rat
NOAEL	: 330 mg/kg
LOAEL	: 1,000 mg/kg
Application Route	: Ingestion
Exposure time	: 54 Days
Method	: OECD Test Guideline 422

Aspiration toxicity

|| Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

12-Hydroxy lithium stearate:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

EL10 (Pseudokirchneriella subcapitata (green algae)): 34 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 0.02 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Titanium dioxide:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

	Remarks: The test was conducted according to guideline Based on transformation/dissolution testing and data from soluble metal compounds
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: The test was conducted according to guideline
Toxicity to algae/aquatic plants	: EL50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: The test was conducted according to guideline
	NOELR (Raphidocelis subcapitata (freshwater green alga)): >= 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: The test was conducted according to guideline
Toxicity to microorganisms	: NOEC (activated sludge): >= 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: The test was conducted according to guideline

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Toxicity to fish	: LL50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 51 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOELR (Desmodesmus subspicatus (green algae)): > 1 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	: EL10 (Daphnia magna (Water flea)): 1.69 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Fatty acids, tall-oil, reaction products with diethylenetriamine:

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 11 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 10.4 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- EL10 (Desmodesmus subspicatus (green algae)): 9.29 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC10 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Test substance: Neutralized product
Method: OECD Test Guideline 209

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 45 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC (activated sludge): 10 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Persistence and degradability

Components:

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 20 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Antimony, dialkyl dithiocarbamate:

Partition coefficient: n- : log Pow: > 4
octanol/water Method: Regulation (EC) No. 440/2008, Annex, A.8

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Calculation

Fatty acids, tall-oil, reaction products with diethylenetriamine:

Partition coefficient: n-octanol/water : log Pow: 6
Remarks: Calculation

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Partition coefficient: n-octanol/water : log Pow: > 4
Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Antimony, dialkyl dithiocarbamate)

Class : 9

Packing group : III

Labels : 9

Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Antimony, dialkyl dithiocarbamate)

Class : 9

Packing group : III

Labels : Miscellaneous

Packing instruction (cargo aircraft) : 956

Packing instruction (passenger aircraft) : 956

Environmentally hazardous : yes

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

IMDG-Code

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Antimony, dialkyl dithiocarbamate)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Antimony, dialkyl dithiocarbamate)
Class	: 9
Packing group	: III
Labels	: 9
ERG Code	: 171
Marine pollutant	: yes(Antimony, dialkyl dithiocarbamate)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

CA. DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
---------	--

Canadian lists

|| No substances are subject to CEPA Section 84 Ministerial Conditions.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

	borne contaminants
ACGIH / TWA	: 8-hour, time-weighted average
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA QC OEL / TWAEV	: Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MERCOSUR - The Agreement for the Facilitation of the Transport of Dangerous Goods; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/19/2025
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided

SAFETY DATA SHEET

according to the Hazardous Products Regulations



WHITE LITHIUM GREASE, 200 g

Version	Revision Date:	SDS Number:	Date of last issue: 07/03/2025
3.0	11/19/2025	11370330-00003	Date of first issue: 04/11/2024

relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8