

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** ECOCOOL ULTRALIFE A
- **Article number:** 600542122
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Application of the substance / the preparation** Metal working
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
FUCHS LUBRICANTS (UK) PLC.
New Century Street
Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU
UK
e-mail: product.safety@fuchs-oil.com
- **Further information obtainable from:** Product safety department.
- **Emergency telephone number:** Emergency telephone: (UK) 01782 203700

2 Hazards identification

- **Classification of the substance or mixture**
 - **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 Xi; Irritant
R38-41: Irritating to skin. Risk of serious damage to eyes.
 - **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
 - **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
-
- **Label elements**
 - **Labelling according to EU guidelines:**
Observe the general safety regulations when handling chemicals.
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
 - **Code letter and hazard designation of product:**
Xi Irritant
 - **Risk phrases:**
38 Irritating to skin.
41 Risk of serious damage to eyes.
 - **Safety phrases:**
23 Do not breathe vapour.
25 Avoid contact with eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
37/39 Wear suitable gloves and eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
60 This material and its container must be disposed of as hazardous waste.
 - **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

GB

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 1)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** A blend of highly refined mineral oils with multifunctional additives.

- **Dangerous components:**

	Highly refined mineral oil substance with a Community workplace exposure limit	25-50%
CAS: 5625-90-1 EINECS: 227-062-3	N,N'-methylenbismorpholine C R34; Xn R22	2.5-10%
CAS: 102-81-8 EINECS: 203-057-1	2-dibutylaminoethanol C R34; Xn R22 R52/53	2.5-10%
CAS: 26027-37-2	Oleic acid amidoethanol polyethoxylate Xi R36	2.5-10%
	Fatty acid soaps Xi R36/38	2.5-10%
CAS: 75782-86-4 EINECS: 278-306-0	C12-C13 Primary alcohols blend N R50	≤ 2.5%
CAS: 70131-54-3	Fatty acid amide Xi R38-41	≤ 2.5%
CAS: 929-06-6 EINECS: 213-195-4	2-(2-aminoethoxy)ethanol C R34	≤ 2.5%
CAS: 68511-37-5 polymer	Poly(oxy-1,2-ethanediyl),a-hydroxy-0-w-hydroxy-,mono-C12-14-alkyl ethers, phosphates C R34; Xn R22; Xi R41 R52/53	≤ 2.5%
CAS: 55406-53-6 EINECS: 259-627-5	3-Iodo-2-propynylbutylcarbamate Xn R20/22; Xi R41; N R50	≤ 2.5%

- **Additional information:**

Annex I Nota L applies to the base oil(s) in this product. Nota L - The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

For the wording of the listed risk phrases refer to section 16.

Contains >0.1=<5.4% Boric Acid (SVHC List)

4 First aid measures

- **Description of first aid measures**

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Check for and remove any contact lenses.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** Seek medical treatment.

- **Information for doctor:**

Hand this Safety data Sheet to the doctor with the special comment "water miscible cutting oil"

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Particular danger of slipping on leaked/spilled product.
- **Environmental precautions:**
Do not allow to penetrate the ground/soil.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Avoid splashes or spray in enclosed areas.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Protect from frost.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 3)

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

Highly refined mineral oil	
OEL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

Select PPE appropriate for the operations taking place taking into account the product properties.

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Do not carry product impregnated cleaning cloths in trouser pockets.

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Neoprene gloves

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Oil resistant protective clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Yellow

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 4)

· Odour:	Mineral-oil-like
· Odour threshold:	Not determined.
· pH-value (5 g/l) at 20°C:	9.1
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100°C
· Flash point:	> 100°C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	>250°C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure at 20°C:	23 hPa
· Density at 15°C:	0.965 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Emulsifiable.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40°C:	40 cSt
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidising agents.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The Control of Substances Hazardous to Health Regulations (COSHH) requires exposure to metalworking fluids by inhalation, ingestion or skin contact to be prevented where reasonably practicable, or failing that,

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 5)

adequately controlled.

Exposure to metalworking fluids can cause irritation of the skin, dermatitis and breathing problems following repeated exposure. Additionally, if not controlled properly, fluid systems that contain water-mixes can become highly contaminated with microorganisms. These organisms, their metabolites and their remains can affect human health if they should enter the breathing zones of workers and other persons leading to chronic respiratory diseases. Such contamination of fluids and associated machinery and pipework must be appropriately monitored and controlled. Direct means of measuring such contamination must be used in conjunction with other relevant checks on fluid quality. Also, systems containing water-mixes must be appropriately cleaned on a regular basis.

Refer to the FUCHS Lubricants guidance "Effective Fluid Monitoring" and "Coolant Management Guide" for further information.

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** Inherently biodegradable
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** Product is not expected to bioaccumulate.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Contact waste processors for recycling information.
Delivery of waste oil to officially authorized collectors only.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Used, degraded or contaminated product may be classified as hazardous waste. Anyone classifying hazardous waste and determining its fate must be qualified in accordance with state and international legislation.

· European waste catalogue

12 01 07*	mineral-based machining oils free of halogens (except emulsions and solutions)
-----------	--

- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Disposal must be made according to official regulations.
EWC 15 01 02 or 15 01 04
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2012

Revision: 01.11.2011

Trade name: ECOCOOL ULTRALIFE A

(Contd. of page 6)

14 Transport information

· UN-Number	Void
· UN proper shipping name	Void
· Transport hazard class(es)	Void
· Packing group	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable to packaged goods.
· Transport/Additional information:	Not dangerous according to the above specifications.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

10043-35-3	Boric acid
------------	------------

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- The risk phrases shown below are for those component substances which are listed in section 3 and not for the actual finished formulation.
- Hazards are concentration dependent. Therefore for the actual hazard classification and risk/safety phrases appropriate for the finished formulated product refer to section 2.
- Please note that, when diluted to the recommended working concentration with water, the work fluid will not be classified as hazardous to health.

R20/22 Harmful by inhalation and if swallowed.

R22 Harmful if swallowed.

R34 Causes burns.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50 Very toxic to aquatic organisms.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Department issuing MSDS: Product safety department.
- Contact: STEVEN PRITCHARD