



# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 8/7/2023 Revision date: 8/7/2023 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : 22184, 22185, 22145 Top Tec ATF 1800 R  
Product code :

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant  
Restrictions on use : None known

#### 1.3. Supplier

Liqui Moly GmbH  
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany  
T +49 731 1420 0  
[info@liqui-moly.de](mailto:info@liqui-moly.de) - [www.liqui-moly.us](http://www.liqui-moly.us)

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC  
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

|                                                                  |      |                                                   |
|------------------------------------------------------------------|------|---------------------------------------------------|
| Hazardous to the aquatic environment – Acute Hazard Category 2   | H401 | Toxic to aquatic life                             |
| Hazardous to the aquatic environment – Chronic Hazard Category 3 | H412 | Harmful to aquatic life with long lasting effects |

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

|                                   |                                                                                                                                                                                                                    |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statements (GHS US)        | : H401 - Toxic to aquatic life<br>H412 - Harmful to aquatic life with long lasting effects                                                                                                                         |
| Precautionary statements (GHS US) | : P273 - Avoid release to the environment.<br>P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### 3.2. Mixtures

| Name                                                                 | Product identifier   | %       |
|----------------------------------------------------------------------|----------------------|---------|
| Distillates (petroleum), hydrotreated heavy paraffinic               | CAS-No.: 64742-54-7  | 30 – 60 |
| Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based | CAS-No.: 72623-87-1  | 30 – 60 |
| Distillates (petroleum), hydrotreated light paraffinic               | CAS-No.: 64742-55-8  | 3-7     |
| Proprietary Additives                                                | CAS-No.: Proprietary | 1 – 5   |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based | CAS-No.: 72623-86-0  | 1 – 5   |

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

|                                       |                                                                                                     |
|---------------------------------------|-----------------------------------------------------------------------------------------------------|
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing.                                    |
| First-aid measures after skin contact | : Wash skin with mild soap and water.                                                               |
| First-aid measures after eye contact  | : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists. |
| First-aid measures after ingestion    | : Call a poison center or a doctor if you feel unwell.                                              |

### 4.2. Most important symptoms and effects (acute and delayed)

|                  |                                                                                            |
|------------------|--------------------------------------------------------------------------------------------|
| Symptoms/effects | : No adverse effects expected.                                                             |
| Inhalation       | : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation. |
| Skin             | : Repeated or prolonged skin contact may cause dermatitis and defatting.                   |
| Eyes             | : May cause minor eye irritation.                                                          |
| Ingestion        | : Abdominal pain. Diarrhoea.                                                               |
| Chronic symptoms | : None known.                                                                              |

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Use of heavy stream of water may spread fire.  |

### 5.2. Specific hazards arising from the chemical

|                                                  |                                                                                              |
|--------------------------------------------------|----------------------------------------------------------------------------------------------|
| Fire hazard                                      | : This product is not classified as flammable or combustible.                                |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. Carbon oxides (CO, CO2). Fire will produce dense black smoke. |

### 5.3. Special protective equipment and precautions for fire-fighters

|                                |                                                                                                                                          |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Firefighting instructions      | : Cool down the containers exposed to heat with a water spray.                                                                           |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible materials : Strong oxidizers.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 22184, 22185, 22145 Top Tec ATF 1800 R

No additional information available

##### Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

##### USA - ACGIH - Occupational Exposure Limits

|               |                               |
|---------------|-------------------------------|
| ACGIH OEL TWA | 5 mg/m <sup>3</sup> inhalable |
|---------------|-------------------------------|

##### USA - OSHA - Occupational Exposure Limits

|                |                     |
|----------------|---------------------|
| OSHA PEL (TWA) | 5 mg/m <sup>3</sup> |
|----------------|---------------------|

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

|                                                                                          |                                                                               |
|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>               |                                                                               |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                                        |                                                                               |
| Local name                                                                               | Mineral oil, excluding metal working fluids Pure, highly and severely refined |
| ACGIH OEL TWA                                                                            | 5 mg/m <sup>3</sup> (I - Inhalable particulate matter)                        |
| Remark (ACGIH)                                                                           | TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)   |
| Regulatory reference                                                                     | ACGIH 2021                                                                    |
| <b>USA - OSHA - Occupational Exposure Limits</b>                                         |                                                                               |
| Local name                                                                               | Oil mist, mineral                                                             |
| OSHA PEL (TWA)                                                                           | 5 mg/m <sup>3</sup>                                                           |
| Regulatory reference (US-OSHA)                                                           | OSHA Annotated Table Z-1                                                      |
| <b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>               |                                                                               |
| No additional information available                                                      |                                                                               |
| <b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b> |                                                                               |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                                        |                                                                               |
| ACGIH OEL TWA                                                                            | 5 mg/m <sup>3</sup> inhalable                                                 |
| <b>USA - OSHA - Occupational Exposure Limits</b>                                         |                                                                               |
| OSHA PEL (TWA)                                                                           | 5 mg/m <sup>3</sup>                                                           |
| <b>Proprietary Additives (Proprietary)</b>                                               |                                                                               |
| No additional information available                                                      |                                                                               |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

|                                                                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Hand protection:</b>                                                                                                                                                                                                                                                                 |
| In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.                                                                                                                                                                                    |
| <b>Eye protection:</b>                                                                                                                                                                                                                                                                  |
| Not required for normal conditions of use                                                                                                                                                                                                                                               |
| <b>Skin and body protection:</b>                                                                                                                                                                                                                                                        |
| Wear suitable protective clothing                                                                                                                                                                                                                                                       |
| <b>Respiratory protection:</b>                                                                                                                                                                                                                                                          |
| In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice. |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

|                                                 |                                |
|-------------------------------------------------|--------------------------------|
| Color                                           | : Red                          |
| Odor                                            | : Characteristic               |
| Odor threshold                                  | : No data available            |
| pH                                              | : No data available            |
| Melting point                                   | : -45 °C                       |
| Freezing point                                  | : No data available            |
| Boiling point                                   | : No data available            |
| Flash point                                     | : 210 °C 410°F                 |
| Relative evaporation rate (butyl acetate=1)     | : No data available            |
| Flammability (solid, gas)                       | : Not applicable.              |
| Vapor pressure                                  | : No data available            |
| Relative vapor density at 20°C                  | : No data available            |
| Relative density                                | : 0.845                        |
| Solubility                                      | : Insoluble in water.          |
| Partition coefficient n-octanol/water (Log Pow) | : No data available            |
| Auto-ignition temperature                       | : No data available            |
| Decomposition temperature                       | : No data available            |
| Viscosity, kinematic                            | : 27.5 mm <sup>2</sup> /s @40C |
| Viscosity, dynamic                              | : No data available            |
| Explosion limits                                | : No data available            |
| Explosive properties                            | : None.                        |
| Oxidizing properties                            | : None.                        |

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

|                                                                                          |                                                                                                                                                                    |
|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b> |                                                                                                                                                                    |
| LD50 oral rat                                                                            | 5000 mg/kg body weight                                                                                                                                             |
| LD50 dermal rat                                                                          | > 2000 mg/kg body weight                                                                                                                                           |
| LC50 Inhalation - Rat                                                                    | > 5 mg/l/4h                                                                                                                                                        |
| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>               |                                                                                                                                                                    |
| LD50 oral rat                                                                            | > 5000 mg/kg                                                                                                                                                       |
| LD50 dermal rat                                                                          | > 2000 mg/kg body weight                                                                                                                                           |
| LD50 dermal rabbit                                                                       | > 5000 mg/kg Source: IUCLID                                                                                                                                        |
| LC50 Inhalation - Rat                                                                    | > 5000 mg/m <sup>3</sup>                                                                                                                                           |
| <b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>               |                                                                                                                                                                    |
| LD50 oral rat                                                                            | > 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| LD50 dermal rabbit                                                                       | > 2000 mg/kg Source: IUCLID                                                                                                                                        |
| <b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b> |                                                                                                                                                                    |
| LD50 oral rat                                                                            | > 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method) |
| Skin corrosion/irritation                                                                | : Not classified                                                                                                                                                   |
| Serious eye damage/irritation                                                            | : Not classified                                                                                                                                                   |
| Respiratory or skin sensitization                                                        | : Not classified                                                                                                                                                   |
| Germ cell mutagenicity                                                                   | : Not classified                                                                                                                                                   |
| Carcinogenicity                                                                          | : Not classified                                                                                                                                                   |
| Reproductive toxicity                                                                    | : Not classified                                                                                                                                                   |
| STOT-single exposure                                                                     | : Not classified                                                                                                                                                   |
| STOT-repeated exposure                                                                   | : Not classified                                                                                                                                                   |
| <b>Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b> |                                                                                                                                                                    |
| LOAEL (oral,rat,90 days)                                                                 | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)                                 |
| <b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>               |                                                                                                                                                                    |
| LOAEL (oral,rat,90 days)                                                                 | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)                                 |
| <b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>               |                                                                                                                                                                    |
| LOAEL (oral,rat,90 days)                                                                 | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)                                 |
| NOAEC (inhalation,rat,dust/mist/fume,90 days)                                            | > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)                                                            |
| <b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b> |                                                                                                                                                                    |
| LOAEL (oral,rat,90 days)                                                                 | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)                                 |
| Aspiration hazard                                                                        | : Not classified                                                                                                                                                   |
| Viscosity, kinematic                                                                     | : 27.5 mm <sup>2</sup> /s @40C                                                                                                                                     |
| <b>Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)</b> |                                                                                                                                                                    |
| Viscosity, kinematic                                                                     | 1.99 – 847 mm <sup>2</sup> /s Temp.: '40°C' Parameter: 'mm <sup>2</sup> /s'@40C                                                                                    |

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)               |                                                                                            |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Viscosity, kinematic                                                              | 73.9 mm²/s                                                                                 |
| Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)               |                                                                                            |
| Viscosity, kinematic                                                              | 1.99 – 847 mm²/s Temp.: '40°C' Parameter: 'mm²/smm2/s '                                    |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) |                                                                                            |
| Viscosity, kinematic                                                              | 1.99 – 847 mm²/s Temp.: '40°C' Parameter: 'mm²/smm2/s '                                    |
| Symptoms/effects                                                                  | : No adverse effects expected.                                                             |
| Inhalation                                                                        | : Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation. |
| Skin                                                                              | : Repeated or prolonged skin contact may cause dermatitis and defatting.                   |
| Eyes                                                                              | : May cause minor eye irritation.                                                          |
| Ingestion                                                                         | : Abdominal pain. Diarrhoea.                                                               |
| Chronic symptoms                                                                  | : None known.                                                                              |

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Harmful to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) |                            |
|---------------------------------------------------------------------|----------------------------|
| LC50 - Fish [1]                                                     | ≥ 100 mg/l                 |
| EC50 - Crustacea [1]                                                | > 10000 ml/l               |
| EC50 96h - Algae [1]                                                | > 1000 mg/l Source: IUCLID |
| Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) |                            |
| LC50 - Fish [1]                                                     | > 5000 mg/l Source: IUCLID |
| EC50 - Crustacea [1]                                                | > 1000 mg/l Source: IUCLID |

### 12.2. Persistence and degradability

| Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) |  |
|---------------------------------------------------------------------|--|
| Not rapidly degradable                                              |  |

### 12.3. Bioaccumulative potential

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) |                        |
|---------------------------------------------------------------------|------------------------|
| Partition coefficient n-octanol/water (Log Pow)                     | 3.9 – 6 Source: IUCLID |
| Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) |                        |
| Partition coefficient n-octanol/water (Log Pow)                     | 3.9 – 6 Source: IUCLID |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

| DOT                                     | TDG           | IMDG          | IATA          |
|-----------------------------------------|---------------|---------------|---------------|
| <b>14.1. UN number</b>                  |               |               |               |
| Not regulated for transport             |               |               |               |
| <b>14.2. Proper Shipping Name</b>       |               |               |               |
| Not regulated                           | Not regulated | Not regulated | Not regulated |
| <b>14.3. Transport hazard class(es)</b> |               |               |               |
| Not regulated                           | Not regulated | Not regulated | Not regulated |
| <b>14.4. Packing group</b>              |               |               |               |
| Not regulated                           | Not regulated | Not regulated | Not regulated |
| <b>14.5. Environmental hazards</b>      |               |               |               |
| Not regulated                           | Not regulated | Not regulated | Not regulated |
| No supplementary information available  |               |               |               |

#### 14.6. Special precautions for user

##### DOT

Not regulated

##### TDG

Not regulated

##### IMDG

Not regulated

##### IATA

Not regulated

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### 22184, 22185, 22145 Top Tec ATF 1800 R

|                                     |                                                    |
|-------------------------------------|----------------------------------------------------|
| SARA Section 311/312 Hazard Classes | Refer to Section 2 for OSHA Hazard Classification. |
|-------------------------------------|----------------------------------------------------|

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.



# 22184, 22185, 22145 Top Tec ATF 1800 R

## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

##### Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Listed on the Canadian DSL (Domestic Substances List)

##### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

No additional information available

#### National regulations

##### 22184, 22185, 22145 Top Tec ATF 1800 R

Listed on the Canadian DSL (Domestic Substances List)

##### Proprietary Additives (Proprietary)

Listed on the Canadian DSL (Domestic Substances List)

### 15.3. US State regulations



#### WARNING:

This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 8/7/2023

Data sources : This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

#### Full text of H-phrases

|      |                                                   |
|------|---------------------------------------------------|
| H401 | Toxic to aquatic life                             |
| H412 | Harmful to aquatic life with long lasting effects |

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

# 22184, 22185, 22145 Top Tec ATF 1800 R


## Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

---

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.