



Energol OE-HT 30

Crosshead engine system oil

Description

Energol OE-HT 30 is a high performance alkaline oil suitable for use in the crankcase of low speed marine crosshead engines.

Application

Energol OE-HT 30 is recommended as a main system lubricant in all low speed crosshead engines.

Energol OE-HT 30 is suitable for use in the new generation of camless engines such as the Wartsila RT-flex engine and the MAN Diesel & Turbo "ME" and "MB" engines. These engines are designed to use the engine system oil as a servo oil in the Hydraulic Power System and Energol OE-HT 30 has been formulated with the required load-carrying properties for this additional function.

Approval

Energol OE-HT 30 is fully approved by major marine crosshead diesel engine manufacturers worldwide.

Main Performance Features

- Excellent thermal and oxidative stability to minimise oil degradation at high piston undercrown temperatures.
- Detergency to minimise the formation of piston undercrown deposits with oil cooled pistons.
- Centrifugibility to enable removal of water and insoluble particulate contamination.
- Alkalinity to provide protection against the corrosive effects of acidic combustion products.
- High anti-wear properties to FZG FLS (fail load stage) 12 for hydraulic fluid performance.
- Excellent anti-rust performance.

Typical Characteristics

Name	Method	Units	OE-HT 30
SAE Number			30
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	11.5
Total Base Number, TBN	ASTM D2896	mg KOH/g	5
Density @ 15°C, Relative	ASTM D1298	g/ml	0.89
Flash Point, PMC	ASTM D93	°C	>200
Pour Point	ASTM D97	°C	-12

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Packaging and Storage

Supplied in bulk and drums of approximately 210 litres. Ensure drums are tightly re-sealed after use.

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings.

Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Energol OE-HT 30

24 Jan 2012

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.bpmarine.com

