

Alphasyn EP 320

In accordance with Industrial Safety and Health Act

Section 1. Chemical product and company identification

Product name Alphasyn EP 320
Code 454017-BE02
SDS no. 454017
Supplier BP Korea Ltd.
19F., 302, Teheran-ro, Gangnam-gu, Seoul, 06210
Republic of Korea

Tel: +82 -1577-1904

EMERGENCY TELEPHONE NUMBER Carechem: +65 3158 1074 (24/7)

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture Gear lubricant.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Section 2. Hazards identification

GHS Classification LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements, including precautionary statements

Signal word No signal word.

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention P273 - Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture

Synthetic base stock. Proprietary performance additives.

Hazardous ingredients

Section 3. Composition/information on ingredients

Ingredient name	Synonym	CAS number	%
Amines, C12-14-tert-alkyl	(C12-14) tert-Alkyl primary amines; Primene 81-R; t-Alkyl-C12-14-primary amines; C12-14 tert-Alkylamines; Monoalkyl (or alkenyl, C5-28) amine; t-Alkyl (C12-C14) primary amines; tert-Alkyl(C=12-14) amines; (C12-14)tert-alkylamines; Tert-Alkyl (C12-C14), Amines; (C12-14)-tert-Alkyl-amine	68955-53-3	0.132235
(Z)-octadec-9-enylamine	9-Octadecen-1-amine, (9Z)-; Oleylamine; 9-Octadecen-1-amine, (Z)-; 9-Octadecenylamine, (Z)-; (9Z)-9-Octadecen-1-amine; Alamine 11; OLEAMINE; (Z)-9-Octadecen-1-amine; N-Alkyl [or alkenyl(C16-28)]-N, N-dialkyl(C1-5 or H) amine; N,N,N-Trialkyl (or alkenyl, at least one of the alkyl or alkenyl group is C8-24, others are H or C1-5) amine; Monoalkyl (or alkenyl, C5-28) amine	112-90-3	0.026235

Non-hazardous ingredients

Ingredient name	Synonym	CAS number	%
Trade secret.	Trade secret.	Trade secret.	87.32
Trade secret.	Trade secret.	Trade secret.	0.1 - 10
Trade secret.	Trade secret.	Trade secret.	0.9275 - 1.06
Trade secret.	Trade secret.	Trade secret.	0.3975 - 0.52973
Trade secret.	Trade secret.	Trade secret.	0.265 - 0.3975
Trade secret.	Trade secret.	Trade secret.	0.1325 - 0.265
Trade secret.	Trade secret.	Trade secret.	0.1325 - 0.26235

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Section 4. First aid measures

Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.
<u>Indication of immediate medical attention and special treatment needed, if necessary</u>	
Specific treatments	No specific treatment.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media

Suitable	Use foam or all-purpose dry chemical to extinguish.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.
Hazardous thermal decomposition products	None expected.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
<u>Methods and material for containment and cleaning up</u>	
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Ingredient name	Exposure limits
methanol	Ministry of Employment and Labor (Republic of Korea). Absorbed through skin. STEL: 250 ppm 15 minutes. Issued/Revised: 3/1997 TWA: 200 ppm 8 hours. Issued/Revised: 3/1997
Ethylene oxide	Ministry of Employment and Labor (Republic of Korea). TWA: 1 ppm 8 hours. Issued/Revised: 3/2012

Biological exposure indices

No exposure indices known.

Other ingredients including trade secret: not applicable

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant

Section 8. Exposure controls/personal protection

Environmental exposure controls

airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Personal protective equipment

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m³), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m³). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye protection

Safety glasses with side shields.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 10. Stability and reactivity

Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Acute toxicity

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.
Symptoms related to the physical, chemical and toxicological characteristics	
Inhalation	No specific data.
Ingestion	No specific data.
Skin	Adverse symptoms may include the following: irritation dryness cracking
Eyes	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Product/ingredient name	Test	Species	Result	Exposure	Remarks
Amines, C12-14-tert-alkyl	LC50 Inhalation Vapour	Rat	1.19 mg/l	4 hours	-
	LD50 Dermal	Rat	251 mg/kg	-	-
	LD50 Oral	Rat	612 mg/kg	-	-
(Z)-octadec-9-enylamine methyl alcohol	LD50 Oral	Rat	1689 mg/kg	-	-
	LC50 Inhalation Vapour	Rat	128.2 mg/l	4 hours	Based on methanol
	LC50 Inhalation Vapour	Rat	130.7 mg/l	4 hours	Based on methanol
	LC50 Inhalation Vapour	Rat	>115.9 mg/l	4 hours	Based on methanol
	LC50 Inhalation Vapour	Rat	87.5 mg/l	6 hours	Based on methanol
	LC50 Inhalation Vapour	Rat	92.6 mg/l	6 hours	Based on methanol
	LC50 Inhalation Vapour	Rat	82.1 mg/l	6 hours	Based on methanol
	LD50 Oral	Rat	>1187 mg/kg	-	Based on methanol

Section 11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Test authority / Test number		Species	Route / Result	Conc.	Remarks
Amines, C12-14-tert-alkyl	-	-	Rabbit	Eyes - Visible necrosis	-	-
	-	-	Rabbit	Skin - Visible necrosis	-	-
(Z)-octadec-9-enylamine	OECD	405	Rabbit	Eyes - Severe irritant	-	-
	OECD	404	Rabbit	Skin - Visible necrosis	-	-
methanol	not guideline	-	Rabbit	Eyes - Non-irritating to the eyes.	-	Based on methanol
	not guideline	-	Rabbit	Skin - Non-irritant to skin.	-	Based on methanol

Skin corrosion or irritation Not available for product and all ingredients.

Serious eye damage/eye irritation Not available for product and all ingredients.

Respiratory Irritation Not available for product and all ingredients.

Sensitisation

Respiratory Sensitisation Not available for product and all ingredients.

Skin Sensitisation

Product/ingredient name	Route of exposure	Species	Result	Remarks
Amines, C12-14-tert-alkyl methyl alcohol	skin	Guinea pig	Sensitising	- Based on methanol
	skin	Guinea pig	Not sensitising	

CMR - ISHA Article 42 Public Notice No 2016-41 Occupational Exposure Limits

Product/ingredient name	CAS number	Classification
Ethylene oxide	75-21-8	GERM CELL MUTAGENICITY - Category 1B CARCINOGENICITY - Category 1A

Carcinogenicity

methyl alcohol	Inhalation	Mouse	Negative - Inhalation - Unspecified	>1.3 mg/l	24 months	Based on methanol
	Inhalation	Rat	Negative - Inhalation - Unspecified	>1.3 mg/l	24 months	Based on methanol

Germ cell mutagenicity

Product/ingredient name	Test	Experiment	Result	Remarks
-------------------------	------	------------	--------	---------

Section 11. Toxicological information

Amines, C12-14-tert-alkyl	471 Bacterial Reverse Mutation Test	Experiment: In vitro	Negative	-
	476 In vitro Mammalian Cell Gene Mutation Test	Subject: Bacteria Experiment: In vitro	Negative	-
	474 Mammalian Erythrocyte Micronucleus Test	Subject: Mammal - species unspecified Experiment: In vivo	Negative	-
(Z)-octadec-9-enylamine	OECD 471	Subject: Mammal - species unspecified Experiment: In vitro	Negative	-
	OECD 476	Subject: Bacteria Experiment: In vitro	Negative	-
	OECD 473	Subject: Mammal - species unspecified Experiment: In vitro	Negative	-
methanol	OECD 471	Subject: Unspecified Experiment: In vitro	Negative	Based on methanol
	OECD 476	Subject: Mammalian-Animal Experiment: In vitro	Negative	Based on methanol
	-	Subject: Mammalian-Animal Experiment: In vitro	Negative	Based on methanol
	OECD 474	Subject: Cell: Somatic Experiment: In vivo	Negative	Based on methanol
	OECD 473	Subject: Mammalian-Animal Cell: Somatic Experiment: In vivo	Negative	Based on methanol

Reproductive toxicity

Product/ ingredient name	Test detail		Species	Exposure		Developmental toxin	Maternal toxicity	Fertility	Remarks
Amines, C12-14-tert-alkyl (Z)-octadec-9-enylamine	OECD	415	Rat	Oral	-	Negative	Negative	Negative	-
	OECD	421	Rat	Oral	-	Negative	Positive	Negative	Based on studies with similar substances.
methanol	Equivalent to OECD	414	Mouse	Inhalation	2 generation	-	-	Negative	Based on methanol
	Equivalent to OECD	414	Mouse	Inhalation	5 days	Negative	-	Negative	Based on methanol
	Equivalent to OECD	414	Rat	Inhalation	10 days	Negative	-	Negative	Based on methanol
	Equivalent			Inhalation					

Section 11. Toxicological information

to OECD 414 Rat 2 generation - - Negative Based on methanol

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
(Z)-octadec-9-enylamine	Category 3	-	Respiratory tract irritation
methyl alcohol	Category 1	-	-
ethylene oxide	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
(Z)-octadec-9-enylamine	Category 2	-	-
ethylene oxide	Category 1	-	-

Potential chronic health effects

General No known significant effects or critical hazards.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Aspiration hazard

Name	Result
(Z)-octadec-9-enylamine	ASPIRATION HAZARD - Category 1

Other information Not available.

Section 12. Ecological information

Ecotoxicity This material is harmful to aquatic life with long lasting effects.

Persistence/degradability

Not expected to be rapidly degradable.

Mobility in soil Spillages may penetrate the soil causing ground water contamination.

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Other adverse effects No known significant effects or critical hazards.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Section 13. Disposal considerations

Disposal precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
A. UN number	Not regulated.	Not regulated.
B. UN proper shipping name	-	-
C. Transport hazard class(es)	-	-
D. Packing group	-	-
E. Environmental hazards	No.	No.
F. Additional information	-	-

Special precautions for user Not available.

Section 15. Regulatory information

Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture)

None of the components are listed.

ISHA article 118 (Harmful substances requiring permission)

None of the components are listed.

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

methyl alcohol
ethylene oxide

ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors)

The following components are listed: methanol, ethylene oxide

ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement)

None of the components are listed.

ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check-up)

None of the components are listed.

Section 15. Regulatory information

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)

None of the components are listed.

Regulation according to Chemicals Control Act

Article 20 Toxic Chemicals (K-Reach Article 20)

Not applicable

Article 18 Prohibited (K-Reach Article 27)

None of the components are listed.

Article 20 Restricted (K-Reach Article 27)

None of the components are listed.

CCA Article 11 (TRI)

None of the components are listed.

CCA Article 39 (Accident Precaution Chemicals)

None of the components are listed.

Dangerous Materials Safety Management Act

Class: Class 4 - Flammable Liquid
Item: 6. Class 4 petroleums
Threshold: 6000 L
Danger category: III
Signal word: Contact with sources of ignition prohibited

Wastes regulation

Designated Waste

Regulation according to other foreign laws

Australia inventory (AIRC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Japan inventory (CSCL)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan inventory (TCSI)

All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

Section 16. Other information

History

Source of Information

Sources of key data used to compile the Safety Data Sheet: Hazard assessment review data, toxicological reviews, and product physical properties; component supplier hazard communication data; and other publically available resources.

Date first prepared

13/08/2024

Number of revisions and date of last revision

1 13/08/2024.

Prepared by

Product Stewardship

Section 16. Other information

Key to abbreviations

AMP = Acceptable Maximum Peak
ACGIH = American Conference of Governmental Industrial Hygienists, an agency that promulgates exposure standards.
ADG = Australian Code for the Transport of Dangerous Goods by Road and Rail
ADG Code = Australian Code for the Transport of Dangerous Goods by Road and Rail
CAS Number = Chemical Abstracts Service Registry Number
HAZCHEM Code = Emergency action code of numbers and letters which gives information to emergency services. Its use is required by the ADG Code for Dangerous Goods in bulk.
ICAO = International Civil Aviation Organization.
IATA = International Air Transport Association, the organization promulgating rules governing shipment of goods by air.
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.
IP 346 = A chemical screening assay for dermal toxicity. The European Commission has recommended that Method IP 346 be used as the basis for labelling certain lubricant oil base stocks for carcinogenicity. The EU Commission has stipulated that the classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. (See Note L, European Commission Directive 67/548/EEC as amended and adapted.) DMSO is a solvent.
NOHSC = National Occupational Health & Safety Commission, Australia
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
TWA = Time weighted average
STEL = Short term exposure limit
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
TCCA = Toxic Chemical Control Act
GHS = Global Harmonized System
ISHA = Industrial Safety and Health Act
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.