



Product Data

Castrol Brayco[®] Micronic 882

Hydraulic fluid, fire resistant synthetic hydrocarbon base

Description

The Castrol Brayco[®] Micronic 882 is a red colored synthetic hydrocarbon hydraulic fluid ISO viscosity Grade 15 for aircraft, ordnance, and industrial use. It contains no VI improvers and, unlike conventional hydraulic fluids, is not subject to polymer breakdown under high shear conditions. It can be used as a replacement and make-up oil for MIL-PRF-5606, and it is also compatible with MIL-PRF-6083 in all proportions. Castrol Brayco[®] Micronic 882 has a high flash and fire point, exceptionally high auto ignition point, and very low flame propagation. Its properties also include controlled rubber swell for long seal life, low foaming, excellent anti-wear, and good corrosion and oxidation stability.

Temperature Range

-40°C to 205°C

Uses

Brayco Micronic 882 is primarily designed as a fire resistant hydraulic fluid for aircraft and missile use, but also has many industrial applications where fire and fluid toxicity are a hazard. Brayco Micronic 882 is a direct replacement for MIL-PRF-5606.

Packaging

Brayco Micronic 882 is specially filtered to micron specifications. It is available in 55 gallon drums, 6/1 gallon cases and 24/1 quart cases.

Specification

Brayco Micronic 882 meets all requirements and is qualified under military specification MIL-PRF-83282D, Amendment 1.

Brayco Micronic 882
030692_2006_11

Castrol and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product. See www.msds.castrol.com.au

Castrol Australia Pty Limited, Industrial Lubricants and Services, GPO Box 5222, Melbourne VIC 3001
Technical Advice Line 1300 557 998 / Customer Service 1300 722 088
www.castrol.com/industrial

Typical Characteristics

Brayco Micronic 882			
Test Method	Description	MIL-PRF-83282D Requirements	Result
D 1298	API Gravity, degrees	---	36.5
Table 3	Specific Gravity @ 15°C	Report	0.841
Table 8	Pounds per Gallon @ 15°C	---	7.03
D 1298	Specific Gravity Variance	0.008 Maximum	0.001
D 445	Kinematic Viscosity, cSt @ 205°C @ 100°C @ 40°C @ -40°C @ -54°C	1.0 Minimum 3.45 Minimum 14.0 Minimum 2200 Maximum	1.1 3.57 14.60 2100 12,230
D 97	Pour Point, °C	-55 Maximum	-63
D 92	Flash Point, COC, °C	205 Minimum	224
D 92	Fire Point, COC, °C	245 Minimum	250
D 664	Neutralization Number, mgKOH/g	0.10 Maximum	0.014
FTM 350	Evaporation Loss, % wt 6.5 hrs @ 205 °C	20.0 Maximum	11.35
FTM 3458	Low Temperature Stability 72 hrs @ -40°C	No gelling, clouding, crystallization, solidification or separation	Pass
D 892	Foam, Sequence I Tendency, ml Stability, ml	65 ml maximum 0	10 0
D 1744	Water by KFR, ppm	100 Maximum	41
FTM 352	Evaporation Effect on Wick Flammability	10 cycles Minimum	15
D 4172	Lubricity, AWSD, mm @ 1 kg load @ 10 kg load @ 40 kg load	0.21 Maximum 0.30 Maximum 0.65 Maximum	0.15 0.25 0.50
FTM 3009	Solid Particle Contamination per 100 mL Autocount 5 - 15 Microns 15 - 25 Microns 25- 50 Microns 50- 100 Microns 100 + Microns	10,000 Maximum 1,000 Maximum 150 Maximum 20 Maximum 5 Maximum	2500 103 32 5 0
D 4898(spec) FTM 3009 (spec)	Gravimetric Residue, mg per 100 mL Filtering Time, minutes	0.3 Maximum 15 Maximum	0.12 9.0
D2270	Viscosity Index	---	129

Additional Information

Brayco Micronic 882 is classified as non hazardous according to the criteria of NOHSC. However, in line with safe handling practices, it is recommended that the handling instructions outlined in the Castrol Material Safety Data Sheet be followed.

Brayco Micronic 882
030692_2006_11
Castrol and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product. See www.msds.castrol.com.au

Castrol Australia Pty Limited, Industrial Lubricants and Services, GPO Box 5222, Melbourne VIC 3001
Technical Advice Line 1300 557 998 / Customer Service 1300 722 088
www.castrol.com/industrial

Brayco Micronic 882 is classified as a C2 combustible liquid for storage and handling purposes. Store in a cool, dry, well-ventilated area out of direct sunlight. Avoid sparks, flames and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

- Spillage: SMALL - 20 LITRES OR LESS
Soak up on Castrol Diatomaceous Earth or similar inert oil absorbent. Arrange for disposal through an approved facility.
- LARGE - GREATER THAN 20 LITRES
Contain as soon as possible, remove by best means available and arrange recycling (preferred) or disposal through an approved facility.
- Disposal: New or used material must not be allowed to enter the ground, ground water, water courses, sewers or drainage systems. Advice may be sought from the Environmental Protection Authority or from the local waste disposal authority.

Brayco Micronic 882
030692_2006_11
Castrol and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product. See www.msds.castrol.com.au

Castrol Australia Pty Limited, Industrial Lubricants and Services, GPO Box 5222, Melbourne VIC 3001
Technical Advice Line 1300 557 998 / Customer Service 1300 722 088
www.castrol.com/industrial