



Product Data

Castrol GTX Full Synthetic High Mileage 0W-20

Helps Prevent Emission System Failure

Description

Castrol GTX Full Synthetic High Mileage is a full synthetic motor oil specially formulated for vehicles with over 75,000 miles. As vehicles age, they change and some of these changes can result in costly repairs. Among these, Catalytic Converter failure is one of the most common and costliest problems faced by higher mileage vehicles.

All motor oil contains phosphorus to prevent engine wear, but phosphorus is known to be effectively poisonous to catalytic converters. Castrol GTX Full Synthetic High Mileage is engineered with Phosphorous Replacement Technology that replaces some of the phosphorous with an advanced additive that maintains robust wear protection.

Application

Castrol GTX Full Synthetic High Mileage 0W-20 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SQ, ILSAC GF-6 or earlier specification 0W-20 lubricant.

Advantages

- Phosphorous Replacement Technology helps prevent catalytic converter and emission system failure
- Advanced additives minimize engine wear 6X better than the industry standard
- Exceptional oil burn-off protection exceeding industry standards*
- Seal conditioners to help reduce leaks
- Superior dispersancy that fights sludge build-up
- Protects for up to 10,000 miles between oil changes**

* Based on API and ACEA volatility specifications

**Up to 10,000 miles or 1 year, whichever comes first

Typical Characteristics

Name	Method	Units	Castrol GTX Full Synthetic High Mileage 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.846
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.6
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	45
Viscosity Index	ASTM D2270	None	165
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5800
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	205
Ash, Sulphated	ASTM D874	% wt	0.84

Performance

API SQ

ILSAC GF-7

Meets Ford WSS-M2C962-A1

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Full Synthetic High Mileage 0W-20

06 May 2025

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com