



22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Issue date: 11/16/2022 Revision date: 11/16/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : 22260, 22261, 22262 Special Tec B FE 0W-30
Product code :

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Engine oil
Restrictions on use : None known

1.3. Supplier

Liqui Moly GmbH
Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
T +49 731 1420 0
info@liqui-moly.de - www.liqui-moly.us

1.4. Emergency telephone number

Emergency number : INFOTRAC
+1800 535 5053 (USA, Canada); +1352 323 3500 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	30-60

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Name	Product identifier	%
1-Decene tetramer, mixed with 1-decene trimer, hydrogenated	CAS-No.: 68649-12-7	30 – 60
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based	CAS-No.: 72623-87-1	5 – 10

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with mild soap and water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: No adverse effects expected.
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Abdominal pain. Diarrhoea.
Chronic symptoms	: None known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂). Fire will produce dense black smoke.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Absorb and/or contain spill with inert material, then place in suitable container. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|--|
| Storage conditions | : Store in a well-ventilated place. Keep cool. |
| Incompatible materials | : Strong oxidizers. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

22260, 22261, 22262 Special Tec B FE 0W-30

No additional information available

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

USA - ACGIH - Occupational Exposure Limits

Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2021

USA - OSHA - Occupational Exposure Limits

Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

No additional information available

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	5 mg/m ³ inhalable
---------------	-------------------------------

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA)	5 mg/m ³
----------------	---------------------

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves. Consult supplier for specific recommendations.

Eye protection:

Not required for normal conditions of use

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Brown
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: -45 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 220 °C (428F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.845
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 51 mm ² /s @40C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: None.

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Oxidizing properties : None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LC50 Inhalation - Rat	> 5000 mg/m ³
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LD50 oral rat	5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight
LC50 Inhalation - Rat	> 5 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: 51 mm ² /s @40C
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	73.9 mm ² /s
1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
Viscosity, kinematic	18 mm ² /s
Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	
Viscosity, kinematic	1.99 – 847 mm ² /s Temp.: '40°C' Parameter: 'mm ² /s'
Symptoms/effects	: No adverse effects expected.
Inhalation	: Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Abdominal pain. Diarrhoea.
Chronic symptoms	: None known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	≥ 100 mg/l
EC50 - Crustacea [1]	> 10000 ml/l
1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
LC50 - Fish [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS
EC50 96h - Algae [1]	> 1000 mg/l Source: e-ChemPortal;HPVIS

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)	
Partition coefficient n-octanol/water (Log Pow)	7.64 Source: e-ChemPortal;HPVIS

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

12.4. Mobility in soil

1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Mobility in soil	192200000 Source: EPISUITE
------------------	----------------------------

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

SECTION 15: Regulatory information

15.1. US Federal regulations

22260, 22261, 22262 Special Tec B FE 0W-30

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Zinc Compounds	CAS-No.	1 – 5%
----------------	---------	--------

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

1-Decene tetramer, mixed with 1-decene trimer, hydrogenated (68649-12-7)

Listed on the Canadian DSL (Domestic Substances List)

Lubricating Oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

22260, 22261, 22262 Special Tec B FE 0W-30

Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Revision date : 11/16/2022

Data sources : This safety data sheet was compiled with data and information from the following sources :
RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.


22260, 22261, 22262 Special Tec B FE 0W-30

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.