



CARTER SY

Synthetic lubricant (PAG) for enclosed gear drives

Applications

Worm drives, bevel and spur gears

- Lubrication of gear drives operating under severe conditions: high loads, high temperatures peaks and corrosive atmospheres
- Non miscible with mineral oils

Specifications

International specifications

- DIN 51517 Part 3 - CLP
- ISO 12925-1 category CKE

Approvals

- SEW, NORD GETRIEBE, BONFIGLIOLI, BREVINI, CMD GEARS, DB SANTASALO, REGGIANA RIDUTTORI and many others

Advantages

- Superior resistance to oxidation and high thermal stability leading to reduce maintenance downtime
- Very high natural viscosity index and low friction coefficient leading to energy savings
- Superior level corrosion protection (tested with sea and acidic water)
- Excellent extreme-pressure and anti-wear properties
- Very good foaming behavior

TYPICAL CHARACTERISTICS	METHODS	UNITS	Carter SY				
			150	220	320	460	680
Density at 15 °C	ISO 3675	kg/m ³	1004	1004	1003	1003	1002
Viscosity at 40°C	ISO 3104	mm ² /s	150	220	320	460	680
Viscosity at 100°C	ISO 3104	mm ² /s	23	34	50	71	95
Viscosity index	ISO 2909		185	202	220	230	240
Open cup Flash Point	ISO 2592	°C	230	230	230	230	230
Pour point	ISO 3016	°C	-33	-30	-30	-27	-27

Above characteristics are mean values given as an information



TotalEnergies Lubrifiants
INDUSTRY & SPECIALTIES
19/01/2023
Carter SY
1/1

