



CARTER XEP

Mineral oil for enclosed gear drives

Applications

Light to heavy duty gearboxes

- **Carter XEP** has been specially designed for lubricating enclosed gear drives operating under severe conditions

Specifications

International specifications

- DIN 51517 Part 3 - CLP
- ISO 12925-1 category CKD
- AGMA 9005-F16 AS
- SEB 181226
- JIS K 2219:2006 (Class 2)
- Chinese GB 5903 L-CKD
- US STEEL 224

Approvals

- FLENDER, CMD GEARS and many others

Advantages

- High quality extreme-pressure and anti-wear properties ensuring micropitting protection
- Excellent resistance to oil oxidation and degradation
- Excellent seal compatibility
- Outstanding protection to rust and corrosion of copper alloys
- Excellent resistance to foaming and emulsion formation

TYPICAL CHARACTERISTICS	METHODS	UNITS	Carter XEP				
			150	220	320	460	680
Pour point	ISO 3016	°C	-39	-39	-36	-36	-30
Temperature at 25 mm ² /s		°C	84	95	104	114	130
Temperature at 2000 mm ² /s		°C	3	8	13	18	23
Temperature at 5000 mm ² /s		°C	-7	-2	3	7	11
Viscosity index	ISO 2909		115	118	119	122	142
Color index	ISO 2049		L0.5	L0.5	L0.5	L0.5	L0.5
Water solubility			No	No	No	No	No
Density at 15 °C	ISO 3675	kg/m ³	870	871	873	873	881
Kinematic viscosity at 40°C	ISO 3104	mm ² /s	150	220	320	460	680
Kinematic viscosity at 100°C	ISO 3104	mm ² /s	16	22	28	37	55
Open cup Flash Point	ISO 2592	°C	252	230	222	214	216
FZG A/8.3/90 – A/16.9/90	ISO 14635-1	Load stage	>12	>12	>12	>12	>12
FZG Micropitting	FVA 54/7	Damage load stage	>10	>10	>10	>10	>10
FZG- GFT class		Classification	High	High	High	High	High

Above characteristics are mean values given as an information

CAUTION: not compatible with polyglycol (PAG) based gear oils



TotalEnergies Lubrifiants
INDUSTRY & SPECIALTIES
19/01/2023
Carter XEP
1/1

