

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

### SECTION 1. IDENTIFICATION

Product name : PREMIUM WHITE LITHIUM GREASE, 319 g  
Product code : 5986.310411  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited/Limitée  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : 1-800-263-5002  
Telefax : 1-905-564-3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300

Urgences impliquant un déversement, incendie, explosion ou exposition: CHEMTREC (24/7): 1-800-424-9300

E-mail address : prodsafe@wurth.ca

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricant  
Restrictions on use : Not applicable

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aerosols : Category 1  
Skin irritation : Category 2  
Carcinogenicity (Inhalation) : Category 2  
Specific target organ toxicity : Category 3  
- single exposure  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms :   

Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

Version 2.0      Revision Date: 07/03/2025      SDS Number: 11305126-00002      Date of last issue: 11/28/2023  
Date of first issue: 11/28/2023

H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer if inhaled.

Precautionary Statements :

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

| Chemical name                                 | Common Name/Synonym | CAS-No.    | Concentration (% w/w) |
|-----------------------------------------------|---------------------|------------|-----------------------|
| Propane                                       | Dimethylmethane     | 74-98-6    | >= 10 - < 30 *        |
| Distillates (petroleum), light distillate hy- | No data available   | 68410-97-9 | >= 10 - < 30 *        |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

Version 2.0      Revision Date: 07/03/2025      SDS Number: 11305126-00002      Date of last issue: 11/28/2023  
Date of first issue: 11/28/2023

|                                                                                                                         |                                         |            |                   |
|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|------------|-------------------|
| drotreating process, low-boiling                                                                                        |                                         |            |                   |
| Distillates (petroleum), hydrotreated light                                                                             | Isoparaffins petroleum hydrotreated HFP | 64742-47-8 | $\geq 5 - < 10$ * |
| Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] | Titanic anhydride                       | 13463-67-7 | $\geq 1 - < 5$ *  |

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

|                                                             |                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice                                              | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.                                                                                          |
| If inhaled                                                  | : If inhaled, remove to fresh air.<br>Get medical attention.                                                                                                                                                                                      |
| In case of skin contact                                     | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse.        |
| In case of eye contact                                      | : Flush eyes with water as a precaution.<br>Get medical attention if irritation develops and persists.                                                                                                                                            |
| If swallowed                                                | : If swallowed, DO NOT induce vomiting.<br>If vomiting occurs have person lean forward.<br>Call a physician or poison control center immediately.<br>Rinse mouth thoroughly with water.<br>Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : May be fatal if swallowed and enters airways.<br>Causes skin irritation.<br>May cause drowsiness or dizziness.<br>Suspected of causing cancer if inhaled.                                                                                       |
| Protection of first-aiders                                  | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).                                                                     |
| Notes to physician                                          | : Treat symptomatically and supportively.                                                                                                                                                                                                         |

### SECTION 5. FIRE-FIGHTING MEASURES

|                                |                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------|
| Suitable extinguishing media   | : Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical |
| Unsuitable extinguishing media | : High volume water jet                                                                      |
| Specific hazards during fire   | : Flash back possible over considerable distance.                                            |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

|                                                |                                                                                                                                                                                                                                                   |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fighting                                       | Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health.<br>If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.                                    |
| Hazardous combustion products                  | : Carbon oxides                                                                                                                                                                                                                                   |
| Specific extinguishing methods                 | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers.<br>Remove undamaged containers from fire area if it is safe to do so.<br>Evacuate area. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.<br>Use personal protective equipment.                                                                                                                                            |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Remove all sources of ignition.<br>Use personal protective equipment.<br>Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Environmental precautions                                           | : Avoid release to the environment.<br>Prevent further leakage or spillage if safe to do so.<br>Prevent spreading over a wide area (e.g., by containment or oil barriers).<br>Retain and dispose of contaminated wash water.<br>Local authorities should be advised if significant spillages cannot be contained.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Methods and materials for containment and cleaning up               | : Non-sparking tools should be used.<br>Soak up with inert absorbent material.<br>Suppress (knock down) gases/vapors/mists with a water spray jet.<br>For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.<br>Clean up remaining materials from spill with suitable absorbent.<br>Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.<br>Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

### SECTION 7. HANDLING AND STORAGE

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

Version 2.0      Revision Date: 07/03/2025      SDS Number: 11305126-00002      Date of last issue: 11/28/2023  
Date of first issue: 11/28/2023

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Do not spray on an open flame or other ignition source.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases

Recommended storage temperature : < 40 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                                  | CAS-No.    | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------------------------------|------------|----------------------------------|------------------------------------------------|-----------|
| Propane                                     | 74-98-6    | TWA                              | 1,000 ppm                                      | CA AB OEL |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA                              | 200 mg/m <sup>3</sup><br>(total hydrocarbon)   | CA BC OEL |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

Version 2.0      Revision Date: 07/03/2025      SDS Number: 11305126-00002      Date of last issue: 11/28/2023  
Date of first issue: 11/28/2023

|                                                                                                                   |            |                                              |                                                       |           |
|-------------------------------------------------------------------------------------------------------------------|------------|----------------------------------------------|-------------------------------------------------------|-----------|
|                                                                                                                   |            |                                              | vapor)                                                |           |
|                                                                                                                   |            | TWA                                          | 200 mg/m <sup>3</sup><br>(total hydrocarbon<br>vapor) | CA AB OEL |
|                                                                                                                   |            | TWAEV                                        | 200 mg/m <sup>3</sup>                                 | CA QC OEL |
|                                                                                                                   |            | TWA                                          | 525 mg/m <sup>3</sup>                                 | CA ON OEL |
| Titanium dioxide; [in powder<br>form containing 1 % or more of<br>particles with aerodynamic<br>diameter ≤ 10 µm] | 13463-67-7 | TWA                                          | 10 mg/m <sup>3</sup>                                  | CA AB OEL |
|                                                                                                                   |            | TWA (Total<br>dust)                          | 10 mg/m <sup>3</sup>                                  | CA BC OEL |
|                                                                                                                   |            | TWA (respir-<br>able dust<br>fraction)       | 3 mg/m <sup>3</sup>                                   | CA BC OEL |
|                                                                                                                   |            | TWAEV (to-<br>tal dust)                      | 10 mg/m <sup>3</sup>                                  | CA QC OEL |
|                                                                                                                   |            | TWA<br>(Respirable<br>particulate<br>matter) | 2.5 mg/m <sup>3</sup><br>(Titanium dioxide)           | ACGIH     |

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Protective gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Hygiene measures : protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).  
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                  |                                                                             |
|--------------------------------------------------|-----------------------------------------------------------------------------|
| Appearance                                       | : Aerosol containing a liquefied gas                                        |
| Propellant                                       | : Propane                                                                   |
| Color                                            | : white                                                                     |
| Odor                                             | : odorless                                                                  |
| Odor Threshold                                   | : No data available                                                         |
| pH                                               | : Solvent mixture; pH value determination not possible, no aqueous solution |
| Melting point/freezing point                     | : No data available                                                         |
| Initial boiling point and boiling range          | : 28 °C<br>Solvent                                                          |
| Flash point                                      | : Not applicable                                                            |
| Evaporation rate                                 | : Not applicable                                                            |
| Flammability (solid, gas)                        | : Extremely flammable aerosol.                                              |
| Upper explosion limit / Upper flammability limit | : 25.0 %(V)                                                                 |
| Lower explosion limit / Lower flammability limit | : 0.6 %(V)                                                                  |
| Vapor pressure                                   | : 4,826.32 - 5,515.80 hPa (20 °C)                                           |
| Relative vapor density                           | : Not applicable                                                            |
| Relative density                                 | : 0.802                                                                     |
| Solubility(ies)<br>Water solubility              | : No data available                                                         |
| Partition coefficient: n-octanol/water           | : Not applicable                                                            |
| Autoignition temperature                         | : No data available                                                         |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

##### Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.61 mg/l



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.0 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

### Skin corrosion/irritation

Causes skin irritation.

### Components:

#### Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

### Distillates (petroleum), hydrotreated light:

Assessment : Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

---

**Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]:**

|         |   |                    |
|---------|---|--------------------|
| Species | : | Rabbit             |
| Result  | : | No skin irritation |

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

|         |   |                                      |
|---------|---|--------------------------------------|
| Species | : | Rabbit                               |
| Result  | : | No eye irritation                    |
| Remarks | : | Based on data from similar materials |

#### **Distillates (petroleum), hydrotreated light:**

|         |   |                                      |
|---------|---|--------------------------------------|
| Species | : | Rabbit                               |
| Result  | : | No eye irritation                    |
| Remarks | : | Based on data from similar materials |

**Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]:**

|         |   |                   |
|---------|---|-------------------|
| Species | : | Rabbit            |
| Result  | : | No eye irritation |

### Respiratory or skin sensitization

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

### Components:

#### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

|                    |   |                                      |
|--------------------|---|--------------------------------------|
| Test Type          | : | Buehler Test                         |
| Routes of exposure | : | Skin contact                         |
| Species            | : | Guinea pig                           |
| Result             | : | negative                             |
| Remarks            | : | Based on data from similar materials |

#### **Distillates (petroleum), hydrotreated light:**

|                    |   |                                      |
|--------------------|---|--------------------------------------|
| Test Type          | : | Maximization Test                    |
| Routes of exposure | : | Skin contact                         |
| Species            | : | Guinea pig                           |
| Result             | : | negative                             |
| Remarks            | : | Based on data from similar materials |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

|                    |                                 |
|--------------------|---------------------------------|
| Test Type          | : Local lymph node assay (LLNA) |
| Routes of exposure | : Skin contact                  |
| Species            | : Mouse                         |
| Result             | : negative                      |

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Propane:**

|                       |                                                                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)<br>Result: negative                                                                                                                       |
| Genotoxicity in vivo  | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)<br>Species: Rat<br>Application Route: inhalation (gas)<br>Method: OECD Test Guideline 474<br>Result: negative |

#### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

|                       |                                                                                                                                                                                                                                       |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)<br>Result: negative<br>Remarks: Based on data from similar materials                                                                                                             |
| Genotoxicity in vivo  | : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)<br>Species: Rat<br>Application Route: Intraperitoneal injection<br>Result: negative<br>Remarks: Based on data from similar materials |

#### **Distillates (petroleum), hydrotreated light:**

|                       |                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Genotoxicity in vitro | : Test Type: In vitro mammalian cell gene mutation test<br>Result: negative<br>Remarks: Based on data from similar materials                                            |
| Genotoxicity in vivo  | : Test Type: Chromosome aberration test in vitro<br>Species: Mouse<br>Application Route: Ingestion<br>Result: negative<br>Remarks: Based on data from similar materials |

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)<br>Result: negative |
|-----------------------|--------------------------------------------------------------------------|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Result: negative

### **Carcinogenicity**

Suspected of causing cancer if inhaled.

### **Components:**

#### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative  
Remarks : Based on data from similar materials

#### **Distillates (petroleum), hydrotreated light:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 105 weeks  
Result : negative  
Remarks : Based on data from similar materials

#### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Species : Rat  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : positive  
Remarks : The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### **Distillates (petroleum), hydrotreated light:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: Based on data from similar materials

### **STOT-single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Propane:**

Assessment : May cause drowsiness or dizziness.

### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

---

### Repeated dose toxicity

#### Components:

##### **Propane:**

|                   |   |                         |
|-------------------|---|-------------------------|
| Species           | : | Rat                     |
| NOAEL             | : | 7.214 mg/l              |
| Application Route | : | inhalation (gas)        |
| Exposure time     | : | 6 Weeks                 |
| Method            | : | OECD Test Guideline 422 |

##### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

|                   |   |                                      |
|-------------------|---|--------------------------------------|
| Species           | : | Rat                                  |
| NOAEL             | : | > 20 mg/l                            |
| Application Route | : | inhalation (vapor)                   |
| Exposure time     | : | 13 Weeks                             |
| Method            | : | OPPTS 870.3465                       |
| Remarks           | : | Based on data from similar materials |

##### **Distillates (petroleum), hydrotreated light:**

|                   |   |                                      |
|-------------------|---|--------------------------------------|
| Species           | : | Rat                                  |
| NOAEL             | : | > 10.4 mg/l                          |
| Application Route | : | inhalation (vapor)                   |
| Exposure time     | : | 90 Days                              |
| Remarks           | : | Based on data from similar materials |

##### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

|                   |   |                             |
|-------------------|---|-----------------------------|
| Species           | : | Rat                         |
| NOAEL             | : | 24,000 mg/kg                |
| Application Route | : | Ingestion                   |
| Exposure time     | : | 28 Days                     |
| Species           | : | Rat                         |
| NOAEL             | : | 10 mg/m <sup>3</sup>        |
| Application Route | : | inhalation (dust/mist/fume) |
| Exposure time     | : | 2 y                         |

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Product:

May be fatal if swallowed and enters airways.

#### Components:

##### **Distillates (petroleum), light distillate hydrotreating process, low-boiling:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

### Distillates (petroleum), hydrotreated light:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Distillates (petroleum), light distillate hydrotreating process, low-boiling:

- |                                                                        |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish                                                       | : | LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l<br>Exposure time: 96 h<br>Test substance: Water Accommodated Fraction<br>Remarks: Based on data from similar materials                                                                                                                                                                                                                                                                              |
| Toxicity to daphnia and other aquatic invertebrates                    | : | EL50 (Daphnia magna (Water flea)): 4.5 mg/l<br>Exposure time: 48 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 202<br>Remarks: Based on data from similar materials                                                                                                                                                                                                                                                     |
| Toxicity to algae/aquatic plants                                       | : | EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201<br>Remarks: Based on data from similar materials<br><br>NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l<br>Exposure time: 72 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 201<br>Remarks: Based on data from similar materials |
| Toxicity to fish (Chronic toxicity)                                    | : | NOELR (Pimephales promelas (fathead minnow)): 2.6 mg/l<br>Exposure time: 14 d<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 204                                                                                                                                                                                                                                                                                           |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOELR (Daphnia magna (Water flea)): 2.6 mg/l<br>Exposure time: 21 d<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 211<br>Remarks: Based on data from similar materials                                                                                                                                                                                                                                                    |

#### Distillates (petroleum), hydrotreated light:

- |                  |   |                                                                                                                                                                   |
|------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish | : | LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l<br>Exposure time: 96 h<br>Test substance: Water Accommodated Fraction<br>Method: OECD Test Guideline 203 |
|------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 2 mg/l  
Exposure time: 5 h  
Remarks: Based on data from similar materials

### **Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### **Persistence and degradability**

#### **Components:**

**Propane:**



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

### Distillates (petroleum), light distillate hydrotreating process, low-boiling:

Biodegradability : Result: Inherently biodegradable.  
Biodegradation: 74.3 %  
Exposure time: 28 d

### Distillates (petroleum), hydrotreated light:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.6 %  
Exposure time: 28 d

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty  
(including propellant)  
Empty containers should be taken to an approved waste  
handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or  
expose such containers to heat, flame, sparks, or other  
sources of ignition. They may explode and cause injury and/or  
death.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Environmentally hazardous : no

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

### IATA-DGR

|                                          |                              |
|------------------------------------------|------------------------------|
| UN/ID No.                                | : UN 1950                    |
| Proper shipping name                     | : Aerosols, flammable        |
| Class                                    | : 2.1                        |
| Packing group                            | : Not assigned by regulation |
| Labels                                   | : Flammable Gas              |
| Packing instruction (cargo aircraft)     | : 203                        |
| Packing instruction (passenger aircraft) | : 203                        |

### IMDG-Code

|                      |                              |
|----------------------|------------------------------|
| UN number            | : UN 1950                    |
| Proper shipping name | : AEROSOLS                   |
| Class                | : 2.1                        |
| Packing group        | : Not assigned by regulation |
| Labels               | : 2.1                        |
| EmS Code             | : F-D, S-U                   |
| Marine pollutant     | : no                         |

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

|                      |                              |
|----------------------|------------------------------|
| UN number            | : UN 1950                    |
| Proper shipping name | : AEROSOLS                   |
| Class                | : 2.1                        |
| Packing group        | : Not assigned by regulation |
| Labels               | : 2.1                        |
| ERG Code             | : 126                        |
| Marine pollutant     | : no                         |

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

|                                                 |                                                                                                               |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Volatile organic compounds (VOC) content</b> | Canada - Volatile Organic Compound Concentration Limits for Certain Products Regulations<br>VOC content: 25 % |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------|

### The ingredients of this product are reported in the following inventories:

|     |                                                                                                                                                                |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DSL | : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL). |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

|                 |   |                                                                                                                                          |
|-----------------|---|------------------------------------------------------------------------------------------------------------------------------------------|
| ACGIH           | : | USA. ACGIH Threshold Limit Values (TLV)                                                                                                  |
| CA AB OEL       | : | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)                                                                      |
| CA BC OEL       | : | Canada. British Columbia OEL                                                                                                             |
| CA ON OEL       | : | Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.                                         |
| CA QC OEL       | : | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants |
| ACGIH / TWA     | : | 8-hour, time-weighted average                                                                                                            |
| CA AB OEL / TWA | : | 8-hour Occupational exposure limit                                                                                                       |
| CA BC OEL / TWA | : | 8-hour time weighted average                                                                                                             |
| CA ON OEL / TWA | : | Time-Weighted Average Limit (TWA)                                                                                                        |
| CA QC OEL / TWA | : | Time-weighted average exposure value                                                                                                     |

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

|                                                                    |   |                                                                                                                                                                                   |
|--------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sources of key data used to compile the Material Safety Data Sheet | : | Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a> |
|--------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## PREMIUM WHITE LITHIUM GREASE, 319 g

|         |                |                |                                 |
|---------|----------------|----------------|---------------------------------|
| Version | Revision Date: | SDS Number:    | Date of last issue: 11/28/2023  |
| 2.0     | 07/03/2025     | 11305126-00002 | Date of first issue: 11/28/2023 |

---

Revision Date : 07/03/2025  
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8